# Garbling a Hash-Based STARK Verifier for Bitcoin

Stephen Duan*[1, 2], Vanhger Pham[1], Blake Hou[1], Ethan Zhu[2], and Jingping Yin[1]

[1]ZKM Team
[2]GOAT Network

**Abstract**

BitVM-style protocols verify succinct proofs on Bitcoin by garbling a proof verifier off-chain. What reaches the chain in a dispute is the proof itself: its bits under one-time keys, the scripts that authenticate them and the signatures that bind them to transactions. Existing designs garble elliptic-curve SNARK verifiers, which a quantum adversary breaks and which need a trusted or secret setup; a hash-based STARK removes both but publishes a far larger proof. This paper measures and reduces that on-chain data for a garbled STARK verifier. For a $2^{18}$-row Keccak-$f$ algebraic intermediate representation (AIR) over WHIR in the binary tower field $\mathbb{F}_{2^{128}}$ with Blake3 throughout, the verifier reads 1,041,024 input bits. Bitcoin Core-tested fixtures that reveal and authenticate them for one key set measure 2.22 million virtual bytes (MvB) with Schnorr adaptors and 7.86–17.27 MvB with hash-based one-time keys, against a few kilobytes for Groth16. Tuning WHIR removes a fifth of the input, and recursing the statement through a narrow tape machine brings it to 564,552 bits, with unreviewed proof-system changes that we list and without binding the zkVM program or its outputs. The verifier is made garblable by a fixed-shape circuit with a transcript recovered from the prover and by free-XOR gadgets for tower multiplication and Blake3: 94.1M non-free gates and 1.5 GB at 104 bits of soundness, about 30× fewer non-free gates than the Boolean-garbled Groth16 verifier of a different statement. These are measured components, not a total on-chain cost: the dispute graph and the soldering of one key set to the kept garblings are not constructed. The proof system gives 104 classical and about 52 quantum bits under stated assumptions, while cut-and-choose gives about 40 bits and Bitcoin's signatures are not post-quantum.

## 1 Introduction

Bitcoin cannot verify a succinct proof economically within current Script and policy limits, but a trust-minimized bridge needs such verification. Consider a withdrawal from a rollup: an operator has paid out a user on Bitcoin and must prove, to a Bitcoin script, that the rollup's state authorizes the payment; the proof is a STARK over the rollup's execution. Hashing dominates such statements, and we evaluate on a hash-heavy standard case, proofs of Keccak-$f$ permutations [Nat15].

A SNARK verifier written in Script takes hundreds of megabytes [GKS+26], and our own STARK verifier in Script needs 1.24 GB of script at $2^{20}$ rows [GOA26a]. The BitVM line of work therefore verifies *optimistically*: a prover claims a result, and a challenger disputes it only if it is wrong. BitVM2 [LAA+25] settles a dispute by bisecting the verifier's execution trace on-chain, which is secure but expensive: a mainnet experiment put the unhappy path at over $14,000 [GKS+26]. BitVM3 moves the verifier off-chain into a *garbled circuit* [WAA+26, Che25].

*Corresponding author: stephen.d@zkm.io

At setup the verifier circuit is garbled. At dispute time the proof is published under one-time signatures that give the evaluator the circuit's input labels, and the outcome depends on which output label the evaluation yields. For the Groth16-sized instances reported by BitVM3 and BABE, only the signed proof and a hashlock remain on-chain, for tens of dollars [GKS+26].

What a dispute publishes is therefore the proof: its bits under one-time keys, the scripts that check them and the signatures that bind them to the transaction. This paper is about the size of that data when the proof is a STARK, which is a thousand times larger than a Groth16 proof, and about reducing it: fewer input bits, less script per bit and fewer signature bytes per bit.

The off-chain side is where the existing designs fall short. A garbled circuit has to be generated, stored for the lifetime of the deposit and checked, because the garbler may cheat, typically by cut-and-choose over many instances. The Boolean-garbled Groth16 verifier [Bit25] has about $3 \times 10^9$ non-free gates, some 42 GiB, and hours of cut-and-choose setup [GKS+26]. Garbling Groth16 with native group operations [KFLT26] and witness encryption [GKS+26] shrink the artifact to megabytes. All of these designs, however, verify an elliptic-curve SNARK, pairing-based or its designated-verifier form over BN254 or a binary curve: a quantum adversary breaks them, and they need a trusted or secret setup. A STARK proof must first be wrapped in such a SNARK, which reintroduces both.

**Key idea.** We garble a hash-based STARK verifier directly and make it cheap by choosing its field. Under free-XOR [KS08] a garbled circuit pays only for non-linear gates, and in a field of characteristic two every addition is an XOR. A STARK over the binary tower field $\mathbb{F}_{2^{128}}$ with Blake3 commitments therefore costs, as a garbled circuit, its hashes and field multiplications, with additions free. Its algebraic checks rest on WHIR over $\mathbb{F}_{2^{128}}$, while Blake3 instantiates the commitments, the Fiat–Shamir transcript and the garbling hash, modeled as circular correlation robust (§6).

**Challenges.** Three problems stand between this idea and a dispute that Bitcoin can settle.

C1 *On-chain data.* A STARK proof is about a thousand times a Groth16 proof, and in a dispute every bit of it is published under a one-time key: the selection material that reveals the bit, the script that authenticates it and the signature that binds it to the transaction. At a million bits this is megabytes of virtual bytes, where the Groth16 designs publish a few kilobytes.

C2 *Post-quantum security.* Pairing-based verifiers fall to Shor's algorithm and need a trusted or secret setup. A hash-based verifier removes both only if its commitments, transcript and garbling hash are hash-based too, and the input publication keeps that property only with hash-based keys, which cost more script per bit than adaptor signatures.

C3 *Garbling the verifier.* A garbled circuit has one shape for all inputs, while the verifier redraws challenges and fixes coordinates depending on sampled values. The bytes it absorbs and samples are specified nowhere outside the prover's implementation, and a wrong schedule loses Fiat–Shamir soundness. Merkle paths, leaf rows and the transcript are hash compressions, each costing more than four field multiplications.

**Contributions.** The first two answer C1, the paper's objective; the last two answer C3 and make the verifier garblable; C2 runs through the choice of hash and the input schemes.

- **Bitcoin integration and on-chain cost (C1, C2).** We place the verifier in a BitVM3-style dispute, state the label-selection task that publishing its input must solve, and price four one-time input schemes and two transport baselines as complete signed transactions

replayed through Bitcoin Core, accounting for selection material, authentication script and transaction signature per bit and separating the measured one-key-set component from the unimplemented multi-copy soldering and transaction graph (§4.1, §4.3). The component measures 2.22 MvB with the 8-bit adaptor baseline and 7.86–17.27 MvB per hash-based key set, against a few kilobytes for Groth16, and we serialize the hash-based construction that would match the adaptor cost under a batch opcode.

- **Input reduction (C1).** Sweeping the WHIR parameters removes a fifth of the 1,041,024 input bits, narrow-statement layouts would remove 37–58%, batching amortizes the input per permutation 3.76×, and garbling the verifier of a narrow-recursion proof of Ziren's binary stage brings the input to 564,552 bits, 0.54×, on real proofs, with the effect of each level-4 change listed (§4.4, §5, Appendix C.5).
- **A fixed-shape circuit for the measured verifier path (C3).** We implement the path through Plonky3's STARK verifier [Plo26] exercised by our Keccak-$f$ AIR over the Boolean WHIR trace commitment as a Boolean circuit with one output wire: the transcript, the zerocheck of the AIR, the batching of the opened columns, the bit ring switch and the WHIR opening. Data-dependent branches are fixed and guarded, and the transcript follows a byte schedule recovered from Plonky3's own verifier, so one circuit serves every proof of a configuration and can be garbled before the proof exists (§4.2).
- **Cheaper gadgets (C2, C3).** Tower-field multiplication at $3^k$ AND gates per $2^k$ bits, with squaring and multiplication by the tower generator free, and a Blake3 circuit at 10,281 AND gates per compression instead of 20,657, with tree mode for long inputs, so that one hash serves the commitments, the transcript and the garbling without a number-theoretic assumption (§4.2.2).

For C2, §6.1 analyzes the STARK and garbling components in the quantum random-oracle model, including Grover search on the garbling offset, and separates those bounds from the lower cut-and-choose level and the non-post-quantum transaction layer; §5 measures real Keccak-$f$ proofs from $2^5$ to $2^{20}$ rows, profiles and ablates the circuit, and compares it with pairing-based designs and estimated garbled STARK verifiers. The circuit builder and the measurements are open source; the Blake3 circuit and a label-level evaluator are contributed to GOAT's bitvm-gc [GOA26b].

## 2 Related work

We group prior work by how it verifies a proof on Bitcoin: by garbling a verifier, by witness encryption, or through small pairing-based SNARKs that both approaches rely on. We close with the garbling techniques we use.

**BitVM.** BitVM2 [LAA+25] verified optimistically: the operator commits to every intermediate value of the verifier, and a challenger disproves one wrong step on-chain. BitVMX [LAM+24] located a disputed step of a general CPU's trace (RISC-V or MIPS) by an n-ary search over a hash chain of the trace. ColliderVM [KLN25] left the optimistic model: it placed the computation on-chain in validity form and passed state between transactions through hash-collision puzzles, without fraud proofs, at a script length its authors estimate as nearly practical for STARK verification. Delbrag [Rub25] proposed replacing BitVM's fraud proof by the off-chain evaluation of a garbled circuit whose outcome is revealed as a secret, proving the circuit's correctness in zero knowledge.

BitVM3 took up that idea and garbled the verifier [WAA+26, Che25], defining BitVM3-CORE as a sound and complete on-chain proof system with on-chain costs of about $9.

**Garbled verifiers.** The Boolean-garbled Groth16 verifier [Bit25] has about $3 \times 10^9$ non-free gates, 42 GiB, with cut-and-choose setup of over three hours at $(N, M) = (181, 7)$ [GKS+26]. Garbling Groth16 with native elliptic-curve group operations reduced the garbled program to 2.4 MiB [KFLT26]. Glock [Eag25] formalized garbled locks and garbled a designated-verifier variant of Pari; BABE reported its garbled circuit at about 12 MB on a binary elliptic curve [GKS+26]. GOAT's bitvm-gc [GOA26b] garbles Groth16 and a designated-verifier form of Pari [DMS24] over BN254 and over the binary curve sect233k1.

We garble a measured STARK-verifier path with the same garbling code, and we contribute our Blake3 circuit back to it. BitVM3's comparison of garbling schemes already listed a Yao-style garbled STARK verifier, at about 10 GB of off-chain storage and as an estimate [WAA+26, Table 9]; we build one and measure 1.5 GB per instance. TRAPGC-DV [FBF+26] verified Groth16 by designated evaluation: the prover wraps its proof in an outer Groth16 proof under a per-session trapdoor SRS and garbles a small circuit that checks it in scalar form, with cut-and-choose and a universal-composability analysis. It too rests on pairings.

**Garbling on Bitcoin: security and inputs.** Futoransky, Larotonda and Barbara [FLB25] broke the authenticity of the RSA-based garbling proposed for BitVM3 and of linear adaptors: coprime public exponents let the evaluator forge labels by extended Euclid, and linear adaptors fall to the Franklin–Reiter related-message attack. Our hash-based garbling has no such label algebra. Mosaic [KTA+26] made cut-and-choose maliciously secure with an on-chain footprint independent of the number of garbled copies, and Antichain Winternitz [TF26a] published input labels on-chain at a cost up to 52.9% lower than Lamport signatures. Both are independent of the garbled circuit; §4.3 prices both for our million-bit input. Tiwari and Feickert [TF26b] assessed the post-quantum cost of such bridges, estimated Boolean STARK verifier sizes, and found proof size the main obstacle to on-chain feasibility. QSB [Lev26] constructed a hash-based, non-standard authorization path under existing consensus rules, mined on mainnet in August 2026 [Sta26]; a pre-signed, timelocked dispute graph is not yet within its reach.

**Witness encryption.** BABE [GKS+26] replaced the garbled Groth16 verifier with witness encryption for linear pairing relations [GKPW24], making the one quadratic pairing linear with a small garbled circuit built from decomposable randomized encodings on Argo MAC [EL26]: a 22 MiB artifact per instance, on-chain cost comparable to BitVM3 and a cut-and-choose setup of seconds. Deferred binding [Pha26] extended it to public inputs known only at dispute time with two further garbled circuits, at 0.92 GiB per finalized instance, 768 input labels, an Assert of 2,154 bytes and a 14,312-byte ChallengeAssert witness, which §5 quotes. Bitcoin PIPEs v2 [ACG+26] witness-encrypted a Schnorr signing key under an NP statement to emulate covenants without a soft fork, with arithmetic affine determinant programs [SRG+26, BIJ+20] whose ciphertexts are cubic in the constraint count, about 338 TB for a 14,371-constraint pairing-SNARK verifier, under a heuristic security analysis. All witness-encryption designs are smaller off-chain than a garbled verifier, but all need a pairing SNARK, so a STARK would first be wrapped in one, and none is post-quantum.

**Binary-field proof systems and garbling.** Binius [DP25] built succinct arguments over binary towers, and ring switching [DP26] turned a claim about a polynomial's bits into one about its packed

form; Plonky3's Boolean WHIR commitment, which we garble, uses both with WHIR [ACFY25] as the proximity test, and its cheap additions are what make a garbled verifier small. We use privacy-free garbling [FNO15] with free-XOR [KS08], one ciphertext per AND gate [ZRE15] and the syntax of Bellare, Hoang and Rogaway [BHR12b]; free-XOR rests on circular correlation robustness [CKKZ12]. Witness encryption in general goes back to Garg, Gentry, Sahai and Waters [GGSW13].

# 3 Setting

## 3.1 Garbled verifiers on Bitcoin

We follow the BitVM3 setting [WAA+26]. A *garbler*, the operator who proves, and an *evaluator*, a challenger, agree on a verifier circuit $C$ with one output wire, and $C$ is garbled at setup. At dispute time the operator publishes its proof on-chain under one-time keys, and each published bit gives the evaluator the input label of that bit's value. The proof is public, so we use *privacy-free* garbling: the evaluator may learn every wire's value. What garbling must provide is *authenticity*. Holding the labels of an input $x$, the evaluator obtains the label of the output value $C(x)$, and it cannot obtain the label of the other value. A hashlock on the label of value 0 lets a challenger who evaluates an invalid proof stop the operator's claim.

The garbler may cheat, so the garbling is checked by cut-and-choose, as in BABE [GKS+26], Mosaic [KTA+26] and bitvm-gc [GOA26b]; its cost is linear in the size of the garbled circuit, which our gadgets keep small (§4.2.2). Section 4 gives the integration sketch, the verifier circuit, the accounted input-publication components and the unresolved deployment requirements.

## 3.2 The garbling scheme

We use privacy-free garbling [FNO15] with free-XOR [KS08] and one ciphertext per non-free gate, in the syntax of Bellare, Hoang and Rogaway [BHR12b].

Let $\Delta$ be a random secret 128-bit offset. Every wire $w$ has a false label $w_0$, and its true label is $w_1 = w_0 \oplus \Delta$. Let $H(\ell, g) = \text{Blake3}(\ell \,\|\, g)$ truncated to 128 bits, where $g$ is the gate's index. An XOR gate sets $c_0 = a_0 \oplus b_0$ and has no ciphertext. An AND gate $c = a \wedge b$ sets

$$c_0 = H(a_0, g), \qquad ct = H(a_1, g) \oplus H(a_0, g) \oplus b_0.$$

The evaluator recovers the output label from its two input labels, the ciphertext and one hash [ZRE15]; an OR gate is symmetric. The garbled circuit is one 16-byte ciphertext per non-free gate.

Two details matter in practice. First, $\Delta$ must be secret and fresh for each garbling: with a public $\Delta$ any label yields its complement, and the output's other label is free to compute. Second, a hash modeled as circular correlation robust (§6) gives labels no algebraic structure. RSA-based garbling proposals for BitVM3 were broken exactly through such structure: label forgery by extended Euclid on coprime exponents, and by the Franklin–Reiter related-message attack [FLB25].

## 3.3 The proof system

We target a STARK verification pipeline over a Boolean WHIR trace commitment, as implemented in Plonky3 [Plo26]. The evaluated implementation instantiates one AIR, with no public values, preprocessed columns or lookups, and requires current- and next-row openings for every column.

The pipeline uses fields in the Wiedemann tower [Wie88]

$$\mathsf{T}_0 = \mathbb{F}_2, \qquad \mathsf{T}_{k+1} = \mathsf{T}_k[X_k]/(X_k^2 + X_{k-1}X_k + 1), \qquad X_{-1} = 1,$$

up to $\mathsf{T}_7 = \mathbb{F}_{2^{128}}$. An element of $\mathsf{T}_{k+1}$ is stored as its low half (the coefficient of 1) and its high half (the coefficient of $X_k$), recursively down to bits. The trace is committed as bits: a Boolean column is packed into $\mathbb{F}_{2^{128}}$ elements, and WHIR commits to the packed multilinear polynomial on an additive (Cantor) evaluation domain [Can89, LCH14]. Binary towers and ring switching come from Binius [DP25, DP26]. Appendix A defines the terms used below.

**Verification.** The verifier:

1. runs a *zerocheck* of the AIR: a degree-4 sumcheck over the row variables, then the AIR constraints, evaluated at the bound point from the opened current and next rows and Horner-batched under a challenge $\alpha$, against $\mathrm{eq}(\tau, r)$;
2. batches the opened columns into one bit-level claim, at a column point drawn from the transcript;
3. runs the *bit ring switch*, which turns that claim into an $\mathbb{F}_{2^{128}}$ claim on the packed polynomial. It uses a $128 \times 128$ tensor and, above $2^7$ rows, its carry and last tensors, a batched sumcheck, and a closing weight computed in the tensor algebra;
4. runs the WHIR opening of that claim: sumcheck rounds with proof of work, STIR queries on Merkle-committed folded codewords, and a final polynomial.

All challenges come from a Blake3 [OANWO20] sponge over bytes, and all Merkle trees use Blake3 compressions.

# 4 A garbled STARK dispute and its on-chain data

This section is the paper's construction. It places a garbled STARK verifier in a BitVM3-style dispute [WAA+26, KTA+26], with a bridge as the motivating application, and follows the data of one dispute: the roles and the transaction graph (§4.1), the verifier circuit whose input that graph must publish (§4.2), the publication of that input under one-time keys, which is the on-chain cost (§4.3), and the levers that shrink the input (§4.4). Appendix B holds the per-scheme fixtures and a post-quantum instantiation.

## 4.1 Roles and dispute

The operator garbles and challengers evaluate. The roles follow from the construction: evaluation is one Blake3 call per non-free gate and needs no secret, so any party holding the kept garblings can check a claim and stop a fraud, and the garbler's cost is paid once at setup. The reverse assignment would also make the operator's payment depend on a challenger handing over its input labels. This subsection fixes the setup and the intended dispute; §6 accounts for what they guarantee.

The accounting boundary is as follows. We use *total on-chain footprint* to mean the sum of the serialized virtual sizes, in virtual bytes (vB), of every transaction in the dispute graph, including ordinary transaction signatures, authentication signatures or preimages, witness framing, revealed tapscripts, control blocks, transaction inputs and outputs, anchors, timeouts and fee-management

transactions. We measure the input-publication component of that footprint: bounded funding–reveal publication slices for all four schemes, and a signed join for Lamport. The challenge, timeout, Disprove, anchor and fee-management branches, the hash-based soldering across the kept garblings and the binding of public values are not constructed, so the figures are components of that footprint and conditional projections.

**Setup.** The operator garbles $N$ instances of $C$ from independent seeds and commits, for every instance $j$, the hash of its garbled tables, $h_j = \mathrm{SHA256}(\ell_0^j)$ for the label of output value 0 (reject), and the hashes of its one-time keys and label translations. A challenger chooses $N - M$ instances to open, re-garbles each from its seed and checks every commitment; only then is the transaction graph signed, by a committee as in BitVM2 [LAA+25], whose enforcement needs one honest signer.

Publishing bit $b$ of input $i$ must give a challenger only the label of value $b$ on wire $i$ in every kept instance; Mosaic provides this correlation for its adaptor-signature path [KTA+26], and the hash-based soldering is open here.

Appendix B.1 gives the intended transaction graph and the semantics of its branches; its Assert node is a placeholder for an unconstructed publication subgraph.

**Intended dispute.** The operator's Kickoff claims a reimbursement; a challenger may spend its challenge output within $\Delta_C$, after which the operator must publish every authenticated input bit through Assert or lose its stake on timeout. A challenger then reads the published bits, derives the input labels of every kept instance and evaluates each off-chain, one Blake3 call per non-free gate, 17 s at $2^8$ rows (§5). An invalid proof yields $\ell_0^j$ from a correctly garbled instance, which opens $\mathrm{Disprove}_j$. The circuit size affects off-chain evaluation, while the proof size controls the Assert payload. The evaluated circuit has no public values, so binding the withdrawal and rollup-state commitment into the AIR relation and transcript, which a bridge needs, is unimplemented and outside the reported figures. What Assert publishes is the verifier's input, so the quantities to reduce are its bit count, which the circuit fixes, and the script and signature bytes that each bit costs, which the publication scheme fixes. We take them in that order.

## 4.2 The verifier circuit

The circuit sets the first quantity: it reads the proof's bits, so its input layout is the bit count that Assert publishes. Its size is also what cut-and-choose garbles and challengers store. This subsection turns the verifier of §3 into a Boolean circuit with one output wire. Figure 1 shows its stages in transcript order, with each stage's share of the non-free gates of our running example: a $2^{18}$-row Keccak-$f$ trace with 1,625 columns, 1,650 AIR constraints and 22 packed variables, whose proof is 140 KiB and whose verifier has 94.1M non-free gates. We first state the approach and the two choices that fix its cost, then describe the gadgets, the transcript, the zerocheck, batching and ring switch, and WHIR.

### 4.2.1 Approach

The construction has two parts. First, a deterministic circuit builder emits the STARK verifier of one configuration, an AIR, a trace height and a set of WHIR parameters, as a Boolean circuit over the proof's bits with one output wire. Every data-dependent branch of the verifier is fixed and guarded by a check, and the transcript follows the byte schedule recovered from the prover's own challenger, so the same circuit serves every proof of the configuration and is built before any proof exists. Second, gadgets for the two operations on which the verifier spends its gates, tower-field





Figure 1: The ring switch dominates the verifier circuit, followed by WHIR. The stages appear in transcript order, and each segment's width is its share of the 94.1M non-free gates of the $2^{18}$-row verifier: transcript is the STARK and WHIR sponges, zerocheck is its sumcheck, AIR constraints and closing, and WHIR is everything after the ring switch except its transcript.

multiplication and Blake3 compression, under the free-XOR garbling of §3.2. Garbling needs only each gate's input labels, so the builder is garbled as it emits gates and the circuit itself is never stored. At setup the operator garbles with every input at 0 and publishes the ciphertexts; at dispute the challenger obtains the input labels of the published proof and evaluates the same builder on them. Two choices fix the cost of the second part.

**Why a binary field.** The Keccak-$f$ AIR is Boolean and its trace is committed as bits, so a prime-field pipeline would spend its arithmetic emulating bits, whereas in $\mathbb{F}_{2^{128}}$ addition is XOR, free under free-XOR, and the only AND gates are base-field products: 2,187 per multiplication by Karatsuba down the tower, with squaring and multiplication by the tower generator free. The bit ring switch of Binius [DP26], which turns the bit-level claims into claims on the packed $\mathbb{F}_{2^{128}}$ polynomial, is the price of the choice: a third of the circuit (Figure 1).

To price the prime-field alternative we also built KoalaBear ($p = 2^{31} - 2^{24} + 1$) and Poseidon2 on wires. A KoalaBear multiplication is 3,451 AND gates, and a degree-4 extension multiplication 60,615, against 2,187 for all of $\mathbb{F}_{2^{128}}$. One Poseidon2 permutation of width 16 is 1,240,747 AND gates: 120 Blake3 compressions. The WHIR opening of a $2^{20}$ KoalaBear configuration (2,157 permutations, about 7,500 extension multiplications) would be about $3.1 \times 10^9$ gates with Poseidon2, more than the whole Boolean-garbled Groth16 verifier, and still $0.3$–$0.5 \times 10^9$ with Blake3, against our 21M for a $2^{18}$-variable opening. The four-fold difference in size does not account for a gap of 15 to 150×: a garbled STARK verifier should use a binary field.

**Why Blake3.** One hash serves three roles: the Merkle commitments and the Fiat–Shamir sponge of the proof system, and the garbling hash $H$ of §3.2. Blake3 is an add-rotate-XOR design, so in Boolean gates its only non-free operations are the 32-bit additions, one AND per bit with the carry gadget of §4.2.2, which is the 120-fold gap to Poseidon2 above. A prover that already commits and samples with Blake3 needs no change, and the circuit's transcript can be checked byte for byte against it. A single hash also keeps the verifier's assumptions to those of §6, Blake3 as a random oracle with circular correlation robustness, with no elliptic-curve or lattice assumption, which is what makes the verifier's own security claim post-quantum (§6.1).

### 4.2.2 Gadgets

**Tower arithmetic.** A wire vector for an element of $\mathsf{T}_k$ is its bit pattern, so gadget outputs can be read back directly as field elements. Multiplication follows the tower recursively, Karatsuba at

| gadget | AND gates |
|---|---|
| $\mathbb{F}_{2^{128}}$ multiplication | 2,187 |
| $\mathbb{F}_{2^{128}}$ squaring, multiplication by $X_{k-1}$, addition | 0 |
| Blake3 of 64 bytes (a Merkle compression) | 10,281 |
| Blake3 of 256 bytes (a leaf row of 16 elements) | 41,511 |
| Blake3 of 1,072 bytes (two chunks: a transcript flush) | 186,125 |

Table 1: Gadget costs, checked against reference implementations of the field and the hash.

each level:

$$z_0 = a_0 b_0, \quad z_2 = a_1 b_1, \quad z_1 = (a_0 + a_1)(b_0 + b_1) + z_0 + z_2, \qquad ab = (z_0 + z_2) + (z_1 + X_{k-1} z_2)\, X_k.$$

Additions are free. Multiplication by the generator $X_{k-1}$ is a rewiring plus XORs, and squaring is linear over $\mathbb{F}_2$. The only AND gates are the base-field products, three per level, so a $2^k$-bit multiplication costs $3^k$ AND gates: 2,187 in $\mathbb{F}_{2^{128}}$. A multiplication by a constant folds to XORs entirely.

**Blake3.** We start from bitvm-gc's Blake3 circuit and change two things. A 32-bit addition's carry is the majority

$$\mathrm{maj}(a, b, c) = c \oplus \big((a \oplus c) \wedge (b \oplus c)\big),$$

one AND per bit, and the carry out of the top bit is discarded, so it is not computed. This halves a compression from 20,657 to 10,281 AND gates. We also add Blake3's tree mode (chunk chaining values on a stack, parent nodes, the root last). The verifier's transcript absorbs more than one 1,024-byte chunk between samples: the final polynomial is 64 coefficients, 1,024 bytes on its own. Table 1 gives the costs. Every gadget is checked against reference implementations of the field and the hash on random inputs.

### 4.2.3 Transcript

The transcript is a Blake3 byte sponge that mirrors the prover's challenger. Observing appends to an input buffer; sampling, when the output buffer is empty, hashes the input buffer, replaces it with the digest, and pops bytes from the digest's end. A field element is 16 little-endian bytes. A query index is 8 bytes read as a little-endian integer and masked. A proof-of-work check absorbs the witness and requires a fixed number of sampled bits to be zero. We implement the same challenger on wires. Its schedule has no data-dependent branch: queries are a fixed number of masked draws, and a proof-of-work check a fixed number of bits. So the circuit's shape is a function of the configuration alone. The sub-transcripts' domain separators are constants, baked in as constant wires, and everything the prover sends is an input.

The byte schedule, that is, the order in which roots, out-of-domain answers, sumcheck messages, proof-of-work witnesses, stratified query draws and the final polynomial are absorbed and sampled, is implicit in the prover's implementation and specified nowhere else. We recover it by running that implementation's own verifier through a challenger that logs every byte, and we test the circuit against the log op for op.

### 4.2.4 Zerocheck, batching and ring switch

The zerocheck, the column batching and the ring switch are implemented gate for gate from a reference implementation that is checked op for op against the prover's verifier. The AIR arrives

as symbolic constraints and is evaluated on wires.

Two data-dependent branches of the reference verifier cannot appear in a fixed circuit. We fix them and guard them with checks.

- The verifier redraws a zerocheck challenge coordinate that happens to be zero. The circuit takes a fixed number of draws and requires each to be nonzero.
- The ring switch would fix a column-point coordinate that is exactly 0 or 1. The circuit assumes there is no such coordinate and checks it.

Each event has probability about $2^{-127}$ per coordinate. When it occurs the circuit rejects where the reference verifier would continue, never the reverse.

#### 4.2.5 WHIR

The WHIR layer checks every proof-of-work witness. It hashes every opened row and walks it up its Merkle path to the root absorbed in the transcript. It then folds each queried row with the round's folding randomness, and checks the final queries against the final polynomial and the closing sumcheck identity. The prover's pruned Merkle openings are expanded into one full path per query outside the circuit, and a Merkle cap of $2^h$ roots trades $h$ compressions per query for a multiplexer (Appendix C.2).

### 4.3 Publishing the input

**Label selection.** Every input mechanism we price is an instance of one two-party task. The *garbler* $\mathsf{G}$ (the operator, who also proves) holds the two labels $\ell_w^0, \ell_w^1$ of every input wire $w$ of the kept garblings; the *evaluator* $\mathsf{E}$ (a challenger) will run the garbled verifier on the proof $\pi$. Publishing $\pi$ on-chain must (i) *deliver* $\ell_w^{\pi_w}$ to $\mathsf{E}$ for every $w$, (ii) be *exclusive*: no party learns any $\ell_w^{1-\pi_w}$, since one complementary label breaks authenticity (§6), (iii) be *binding*: $\mathsf{G}$ publishes at most one value per wire, and the publication is also the authorization of the spending transaction, and (iv) be *public*: any observer can recover $\pi$ and check the published object.

A malformed publication cannot be spent, a missing one forfeits the stake through AssertTimeout, and Disprove is reserved for the reject label. Lamport achieves (i)–(iv) with one preimage per bit, at the cost of a per-bit script. Figure 2, the adaptor construction of BitVM3 and Mosaic [WAA+26, KTA+26], achieves them with one signature per $k$-bit digit and no per-bit script. The hash-based alternative (Figure 4, Appendix B.2) replaces the signature by a pair of hash-chain openings and underlies the Antichain row and the hash-based projections of §6.1.

Both protocols publish the same selection material per digit: the 130,128 adaptor completions at $k = 8$ and the 16,266 hash records at $k = 4$, $n = 16$ of our fixtures are both exactly 8,458,320 bytes. They differ in the rest. The adaptor's selection is verified by one `CHECKSIG` per digit, 3 bytes of script that is also the transaction binding, on a discrete-logarithm assumption that Shor's algorithm removes (§6.1); the hash-based selection pays 2 bytes of script per hash step and a separate transaction signature, which makes the Antichain row 5.3 times the adaptor row in Table 4. Table 2 sets the four schemes side by side. With a native batch opcode, a hash-based transaction signature and full-width nodes, the hash-based selection would cost about 2.13 MvB, just below the adaptor's 2.23 MvB on the same accounting (Table 9), at about 117 quantum bits; we serialized that construction, but none of its three ingredients exists on Bitcoin today (Table 9, Appendix B.3).





Figure 2: Schnorr adaptor label selection for one $k$-bit digit position $i$, as in BitVM3 and Mosaic [WAA+26, KTA+26]. $m_i$ is the BIP341 message seen by the $i$-th CHECKSIG; wire $(i, j)$ is bit $j$ of the digit. Everything above the dispute line is off-chain and repeated for every digit and every candidate value.

**Four one-time schemes.** We price four one-time schemes for carrying the input bits; Appendix B.4 gives their scripts and fixtures and Table 4 their sizes. *Lamport* reveals one of two hashed 16-byte preimages per bit against a 49-byte leaf script, 998 bits per input, with a 32-byte authorization key and OP_CHECKSIGVERIFY prefixed to each leaf. *Antichain Winternitz* [TF26a] closes the forward-hashing gap of plain Winternitz chains at a cited marginal 11.31 vB per bit at parameters $(2, 16)$; our fixture pins the upstream implementation and adds a 64-byte Schnorr authorization. *Winternitz with a translation table* [SST+26] closes the same gap by making each label a Shamir secret whose threshold a signed chunk's checksum sets; our fixture uses 3-bit digits, eight per chunk, at the price of a 1.905 GB off-chain table per instance.

*Schnorr adaptor signatures* over 8-bit digits, as in BitVM3 and Mosaic, reproduce BitVM3's

| scheme | selection material | script | transaction binding | vB/bit | assumption |
|---|---|---|---|---|---|
| Schnorr adaptor, $k = 8$ | one 64-byte completion per 8-bit digit | one `CHECKSIG` per digit, 3 bytes | the same signature | 2.13 | discrete logarithm |
| WOTS translation, $k = 3$ | one 20-byte chain node per 3-bit digit, plus two checksum chains per chunk | hash ladder in Script, 2 bytes per step | separate 64-byte Schnorr signature per input | 7.55 | hash; 128-bit translation chain |
| Antichain $(2, 16)$, $k = 4$ | two 16-byte chain nodes per 4-bit digit | hash ladder in Script, 2 bytes per step | separate 64-byte Schnorr signature per input | 11.38 | hash |
| Lamport | one 16-byte preimage per bit | 49 bytes per bit | separate 64-byte Schnorr signature per input | 16.59 | hash |

Table 2: Where the four input schemes spend their bytes. Selection material and script are per digit or per bit as stated; vB/bit is the measured one-key-set component of Table 4, including transaction shells. The adaptor's selection and binding are one object, which is why its script is three bytes per digit; the hash-based schemes pay for the ladder in Script and for a separate signature, and only their selection is hash-based.

9,323 weight units per 1,024-bit Assert shell and validate every completed signature under Core 31.1; the signatures rest on discrete logarithms, and this repository does not implement Mosaic's polynomial soldering. Packing more bits into each adaptor completion shrinks the serialized transactions to 1.11 MvB at 16 bits, but the off-chain choice table grows to 277 GB per key set and the exclusive delivery of binary labels for such digits is unimplemented, so the 8-bit construction remains the authenticated baseline.

Our labels are free-XOR correlated, so a hash-based preimage $s$ cannot itself be a label: a key-derivation function (KDF) maps it to one by a translation ciphertext $\mathrm{KDF}(s) \oplus w_b$, two per input bit and instance, 33 MB per instance at $2^{18}$ rows. Using one on-chain key set for all $M$ kept instances requires a proof that the translations of opened and kept instances encode the same bit choices. BABE's zero-knowledge soldering [GKS+26] and Glock's verifiable secret sharing [Eag25] give related mechanisms at smaller input sizes; we have neither constructed nor costed one for a million bits, so the one-key-set hash rows of Table 4 are conditional on it and $\varepsilon_{\mathrm{sol}}$ is unbounded. Authenticating each input independently for every kept instance instead multiplies the component by $M$: at $M = 7$, 120.86 MvB for Lamport, 82.94 MvB for Antichain and 55.03 MvB for WOTS translation, before graph overhead and still without enforcing the same bit choice across the sets.

### 4.4 Reducing the input

The input is the proof, so it shrinks only where the proof does. We use three levers, and §5 measures what each removes.

**WHIR parameters.** The input bit count is a function of the WHIR schedule alone: the rate, the folding factor and the grinding budget fix the number of rounds, queries and opened rows. We compute the count exactly from a configuration and check it against the measured input, then sweep the schedule at a fixed soundness target; a lower rate and more grinding trade queries for proof size. The opened trace values, two rows of the AIR's columns at 128 bits each, do not depend on WHIR and bound what this lever can reach.

**Statement width.** Those opened values scale with the number of columns, so a narrower AIR at a greater height reads fewer bits for the same committed cells; the same schedule model counts the input of hypothetical layouts. Batching more permutations into one trace does not shrink the input of one proof, but it amortizes that input over the work proved.

**Recursion into a narrow machine.** The floor of the first two levers belongs to the statement, so the third changes the statement: the verifier of a proof built to be verified cheaply. Ziren's binary stage records a verifier as a straight-line tape over $\mathbb{F}_{2^{128}}$, a five-table tape machine proves a run of the tape, and its own verifier is recorded and proved again, each round narrowing the statement. We translate the final tape gate by gate into the circuit of §4.2 and garble it.

# 5 Evaluation

The experiments answer five questions: how the garbled verifier scales with the trace (Table 3), where its gates go and what the adder saves, how the circuit-input authentication component projects (Table 4), how far the input shrinks, and how the result compares with estimated STARK verifiers and pairing-based designs (Table 6). Appendix C holds the gate profile, the ablation, the Core replay, the input sweep and the recursion details.

**Setup.** We instantiate the construction of §4.2 on Plonky3 [Plo26], whose Blake3 challenger, symbolic AIR constraints and Boolean WHIR commitment are the ones described in §3; the gadgets are checked against its binary-field crate and the `blake3` crate. We proved Keccak-$f$ permutations with Plonky3's 1,625-column characteristic-2 Keccak AIR, at rate 1/32, folding factor 4 and 110 bits per WHIR term; booleanity is not constrained, since the commitment is to bits. A byte-logging challenger recorded each run, our reference replayed Plonky3's verifier byte for byte, the circuit was tested against the log, and the verifier circuit was then garbled on one core.

Runs up to $2^{18}$ rows had 32 GB of RAM and eight cores of an Intel Xeon Platinum 8375C at 2.9 GHz; the $2^{20}$ run used an AMD EPYC 9355 limited to 128 GB and 32 cores. Appendix C.1 lists the pinned revisions and commands. Gate, wire and input counts are deterministic; wall-clock times are single-run measurements unless a range is stated. The circuit's size depends on the AIR, since the transcript, column combination and constraint evaluation grow with the columns and constraints; all sizes are for this 1,625-column AIR, a demanding case, whereas a Groth16 verifier's circuit is fixed for a given verifying key and public-input arity.

**Scaling.** Table 3 gives the measured verifier configuration from $2^5$ to $2^{20}$ rows. Every circuit accepted its proof, and at $2^5$ and $2^8$ we also checked that it rejected the proof with one opened value changed. Growing the trace 32,768-fold grew the circuit 2.2-fold, because the verifier depends on the trace length only through the logarithmic number of variables.

**Where the gates go.** Table 10 in Appendix C.2 breaks the $2^{18}$ circuit down by the verifier phase that emits each gate. The largest single item is the ring switch closing, 33.6%: 256 multiplications per packed variable, plus a fixed $11 \times 512$ for the column selector. The STARK transcript, the column combination and the AIR constraints, 34.9% together, grow with the number of columns, so a narrower AIR shrinks them directly.

| trace | vars | non-free gates | garbled | garbling | input bits |
|---|---|---|---|---|---|
| $2^5$ rows (1 Keccak-$f$) | 9 | 44,573,121 | 713 MB | 35 s | 586,240 |
| $2^8$ rows (10) | 12 | 66,459,859 | 1,063 MB | 53 s | 743,808 |
| $2^{12}$ rows (163) | 16 | 77,736,394 | 1,243 MB | 53 s | 874,240 |
| $2^{16}$ rows (2,621) | 20 | 88,680,747 | 1,418 MB | 66 s | 997,760 |
| $2^{18}$ rows (10,485) | 22 | **94,069,548** | **1,505 MB** | 57 s | 1,041,024 |
| $2^{20}$ rows (41,943) | 24 | 99,613,898 | 1,593 MB | 42 s† | 1,108,992 |

Table 3: The measured verifier configuration stays below 100M non-free gates and 1.6 GB garbled up to $2^{20}$ rows. Measured on real Keccak-$f$ proofs; "vars" is the number of packed variables WHIR opens, garbled size is 16 bytes per non-free gate. Garbling is single-threaded, and its time varied by up to 50% with load on the shared machine (23–35 s at $2^5$ across runs). †The $2^{20}$ proof was generated on a second, larger machine, where the circuit was also garbled, again on one core.

**Ablation.** Replacing our Blake3 adder with the original two-AND adder, with everything else unchanged, grew the circuit by 32% at $2^5$ rows and 29% at $2^8$: the adder saves a quarter of the whole verifier, because Blake3 is in the transcript, the leaf hashes and every Merkle path (Table 11, Appendix C.2).

**Accounted input-publication components.** A Taproot output commits to its tree through a 32-byte output key at funding time; the large cost occurs if the dispute branch is spent and the witness reveals the authentication signature or preimage, leaf script and control block. Table 4 accounts for that dispute-time component for the $2^{18}$-row circuit, which reads 1,041,024 logical bits (127.1 KiB) from a 140 KiB proof. Every authenticated row includes its signature or opening witness, transaction-binding authorization, authentication script and complete reveal-transaction shell, with two P2TR outputs per transaction for the adaptor, WOTS-translation and Antichain fixtures and one for Lamport; the table compares concrete components, not complete or identical dispute graphs. Two transport rows are reference points, not lower bounds: a raw-data fixture of 1,627 80-byte witness items over two one-leaf P2TR inputs, 33,299 vB with no signature or label authentication, and a Core-accepted signed envelope in the style of ESSPI, BitVMX's signed program-input transport [LJF25], 33,004 vB, which authenticates the bytes but delivers no selected labels.

For one key set, the executable fixtures measure 2.22 MvB with the 8-bit Schnorr-adaptor baseline, 7.86 MvB with translated Winternitz, 11.85 MvB with safe Antichain Winternitz and 17.27 MvB with Lamport; the two hash-based figures are all-nonzero worst cases, and the adaptor's largest transaction is 64 WU below the 400,000-WU standard limit. All selected leaves execute with real BIP341 contexts under Bitcoin Core 31.1 strict policy. On isolated regtest nodes with non-standard transactions disabled, Core rejected each reveal as `too-large-cluster` while its funding parent was unconfirmed, accepted every reveal after confirmation, mining the four fixtures in 3, 9, 12 and 18 blocks, and accepted Lamport's 13,060-vB signed join only after its 174 reveals confirmed (Appendix C.3). This establishes staged standard-policy feasibility for bounded signed publication slices, not propagation, fee management, timeout trees or the missing challenge, Disprove, anchor and soldering graph.

At BABE's historical 2.2 sat/vB and $95,500 per bitcoin [GKS+26], the four components correspond to 0.049, 0.173, 0.261 and 0.380 BTC, neither current quotes nor fees for a complete dispute. The one-set hash rows require the unimplemented soldering of §4, and the seven-key-set rows are its arithmetic projection, which proves no consistency of bits across the sets.

| input mechanism | key sets | vB/bit | accounted component | evidence and accounting boundary |
|---|---|---|---|---|
| raw transport baseline | 0 | 0.032 | 33.30 kvB | serialized two-input fixture: data, drop scripts, control blocks and tx shell; no signature or label authentication |
| signed envelope transport [LJF25] | 0 | 0.032 | 33.00 kvB | Core-tested commit and signed reveal; authenticates bytes but supplies no selected GC labels and excludes the data-availability and fraud graph |
| Schnorr adaptor, 8-bit baseline [WAA+26, KTA+26] | 1 | 2.13 | 2.22 MvB | Core-tested 133-input, 23-transaction fixture; completed signatures, code separators, scripts, depth-zero controls and two P2TR outputs |
| WOTS translation [SST+26] | 1 | 7.55 | 7.86 MvB | Core-tested all-nonzero worst case: 886 signed inputs in 81 two-output transactions; off-chain table 1.9 GB per instance |
| Antichain $(2, 16)$ [TF26a] | 1 | 11.38 | 11.85 MvB | Core-tested all-nonzero worst case: 784 signed inputs in 131 two-output transactions using pinned upstream openings and scripts |
| Lamport | 1 | 16.59 | 17.27 MvB | fully serialized 174-reveal fixture: transaction-binding signatures, preimages, scripts, depth-zero controls, input/output shells; Core 31.1 accepted after funding confirmation |
| WOTS translation, independent keys | 7 | 52.86 | 55.03 MvB | arithmetic 7× worst-case projection; consistency and graph unimplemented |
| Antichain, independent keys | 7 | 79.67 | 82.94 MvB | arithmetic 7× worst-case projection; consistency and graph unimplemented |
| Lamport, independent keys | 7 | 116.10 | 120.86 MvB | arithmetic 7× projection; consistency and graph unimplemented |

Table 4: Source-specific accounting of the dispute-time circuit-input publication component for 1,041,024 logical bits. The adaptor row includes completed transaction-binding Schnorr signatures. Each hash-based row includes its one-time opening witness plus an ordinary transaction-binding Schnorr signature. Every label-authentication row also includes the authentication scripts, control blocks, input/output shells and reveal-transaction framing. Adaptor, WOTS translation and Antichain use two outputs per transaction, whereas Lamport uses one. Funding for all four and Lamport completion are reported separately in the text. The complete challenge/timeout/Disprove graph, anchors, robust fee management and multi-copy soldering are not included. The table therefore does not report total on-chain cost.

**How far the input shrinks.** We counted the verifier's input bits by proof component from the WHIR schedule alone; the count equals the measured input at the five tested configurations through $2^{18}$ rows. Sweeping rates 1/8 to 1/256, folding factors 2 to 6 and grinding budgets up to 48 bits at $2^{18}$ rows, keeping 110 bits per WHIR term in the Johnson regime, the smallest input, at rate 1/256, folding 4 and 48 bits of grinding, is 845,952 bits, 19% below the measured configuration, at 103.9 bits of composed soundness (Table 5, Appendix C.4). Its WHIR part shrinks by 35%, but 480,256 bits do not depend on WHIR at all: the opened values are 416,000 bits, two rows of 1,625 columns at 128 bits each. The tuning also moves soundness from queries to grinding, which halves under quantum search (§6.1).

Below this the input shrinks only with a narrower AIR or by recursion. Narrowing the AIR while keeping at least the measured $1{,}625 \times 2^{18}$ committed cells, hypothetical widths 128 and 32 at heights $2^{22}$ and $2^{24}$ need 659,840 and 636,288 input bits under the current WHIR profile, and 464,768 and 441,216 bits with the best swept configuration, reductions of 37–58%; these are exact schedule counts for layout models, not generated proofs, since no such narrow Keccak AIR exists. Batching has real artifacts at both ends: the $2^{18}$ and $2^{20}$ traces hold 10,485 and 41,943 permutations for 1,041,024 and 1,108,992 input bits, so four times the work adds 6.53% to the input and amortizes it from 99.29 to 26.44 bits per permutation, 3.76×, without reducing the absolute unhappy-path payload of one proof.

| component | measured | tuned |
|---|---|---|
| opened values (current and next row) | 416,000 | 416,000 |
| zerocheck and ring switch | 64,256 | 64,256 |
| WHIR Merkle paths | 346,624 | 239,616 |
| WHIR leaf rows | 163,840 | 92,160 |
| WHIR caps, OOD answers, sumchecks, final polynomial | 50,304 | 33,920 |
| total input bits | 1,041,024 | 845,952 |
| STIR queries per round | $33 + 20 + 15 + 12$ | $16 + 12 + 9 + 8$ |
| rate, folding, grinding budget | 1/32, 4, 32 | 1/256, 4, 48 |
| composed soundness (bits) | 104.3 | 103.9 |

Table 5: Tuning WHIR removes a fifth of the input, and the AIR's opened values set the floor. Input bits at $2^{18}$ rows by proof component, for the measured configuration and the smallest configuration found in the sweep; 128 bits per field element and 256 per digest, with full Merkle paths below each cap.

**Recursion into a narrow machine.** The floor above belongs to the statement, so we also garbled the verifier of a statement built to be verified cheaply. The binary stage of the MIPS32 zkVM Ziren [DYH+26, ZKM26] proves, over $\mathbb{F}_{2^{128}}$ with Boolean WHIR and Blake3, the program that verifies a shrunk zkVM proof, and records Plonky3's verifier of a binary-stage proof as a straight-line tape over $\mathbb{F}_{2^{128}}$; a five-table tape machine proves a run of the tape, and its own verifier is recorded and proved again. We translate a tape gate by gate, trusting Ziren's recorder. For a Fibonacci program the binary stage's verifier has 3.37G non-free gates and 18,050,304 input bits; after three rounds of narrow recursion, with the recording choices and five unreviewed proof-system changes of Appendix C.5, the verifier of the last proof has 564,552 input bits, made of 9,513 bytes and 3,816 field elements, 0.54× the Keccak verifier's, in 218.0M non-free gates and 3.49 GB (Table 7). Every row of that table is the garbled verifier of a real proof; each accepts its proof and rejects three single-input changes.

The runs bind no public values, so the circuit attests that some zkVM proof verifies, not which program ran; binding the public-value digest would add at most 1,024 input bits. Each proof meets 100 bits of composed soundness by Plonky3's assessment, with up to 46 bits of grinding per term, which halves under quantum search. At 564,552 bits, the fixtures of Table 4 serialize to 1.21 MvB for the adaptor baseline, 4.26 MvB for WOTS translation, 6.43 MvB for Antichain and 9.36 MvB for Lamport, not replayed in Core. Tiwari and Feickert [TF26b] estimated the Boolean verifiers of three zkVMs' recursion proofs from their operation counts (Table 12); the smallest, RISC Zero's with Blake3 in place of its internal hash, has 1.56G non-free gates, 7.2× our measured recursion verifier, whose input is 3.2× smaller than that proof.

**Comparison.** Table 6 places the result among approaches to verifying proofs on Bitcoin (§2). For the designated-verifier pairing SNARK we garbled bitvm-gc's circuit: 481.6M non-free gates; it accepted the valid proof and rejected it with one witness bit flipped. The Keccak verifier has 5.1× fewer non-free gates, and 30× fewer than the Boolean-garbled Groth16 verifier; the recursion verifier has 2.2× and about 13× fewer. Native-group garbling of Groth16 [KFLT26] and witness encryption [GKS+26] produce artifacts of megabytes and need far fewer input bits, on pairings and a trusted setup. For setup, at $(N, M) = (181, 7)$ and $2^{18}$ rows the operator garbles 181 instances at about 57 s each, 2.9 core-hours or about 11 minutes on 16 cores, and a challenger stores the 7 kept instances, 1.5 GB each or 10.5 GB; BitVM3 reports 3 hours 24 minutes on 16 cores and 288.4 GB

| approach | statement | off-chain size | input bits | on-chain dispute path, as reported | assumptions |
|---|---|---|---|---|---|
| Boolean garbled verifier [Bit25] | Groth16 | 42 GiB | 1,019 | Assert 2.4 kvB and Disprove 93 vB, about $5 at 2 sat/vB [WAA+26]; the published experiment normalized to $37.65 [GKS+26] | pairings, trusted setup |
| native-group garbling [KFLT26] | Groth16 | 2.4 MiB | n/r | n/r | pairings, trusted setup |
| garbled DV-Pari (bitvm-gc, our measurement) | DV-SNARK | 7.7 GB | n/r | n/r | elliptic curves, secret trapdoor |
| BABE [GKS+26] | Groth16 | 22.2 MiB | 508 | Assert 9,240 vB, ChallengeAssert 17,400 vB, WronglyChallenged 149 vB: 26.8 kvB, $56.90 at 2.2 sat/vB | pairings (generic group and random-oracle models), trusted setup |
| deferred-binding WE [Pha26] | Groth16, late inputs | 0.92 GiB† | 768 | Assert 2,154 B, ChallengeAssert 14,312 B witness and 109,393 B script, WronglyChallenged 64 B; about 32 kvB | BABE + DLog |
| PIPE with AADP WE [ACG+26, SRG+26] | pairing SNARK | ≈ 338 TB (estimate) | one hash | one hash in Assert, one signature in Disprove; no size reported | heuristic |
| **this work** | **Keccak-$f$ STARK over $\mathbb{F}_{2^{128}}$, $2^{18}$ rows** | **1.5 GB** | **1,041,024** | **input publication 2.22 MvB (adaptor, DLog) or 7.86 MvB (hash-based), about $4,700 or $16,500 at 2.2 sat/vB, Core-replayed; Disprove 97 vB; graph incomplete§** | **Blake3 as a random oracle; assumed circular correlation robustness and adaptive authenticity‡** |
| this work, narrow recursion | STARK recursion proof over $\mathbb{F}_{2^{128}}$ | 3.49 GB | 564,552 | input publication 1.21 MvB (adaptor, DLog) or 4.26 MvB (hash-based), about $2,500 or $9,000 at 2.2 sat/vB; Disprove 97 vB; graph incomplete§ | as above, plus unreviewed proof-system changes‡ |

Table 6: This work is the only entry that verifies a STARK directly, and it publishes a thousand times more input bits and a far larger dispute path than the pairing-based designs. Columns: off-chain artifact per instance (garbled circuits at 16 bytes per non-free gate), input bits published at dispute time, and on-chain dispute path, each as its source reports it; n/r: not reported. †One instance: 59.3M non-free gates in three garbled circuits plus adaptor tables, sharing a 3.83 GiB circuit artifact; the kvB total is our arithmetic. §One key set; the hash-based figure is WOTS translation, whose table adds 1.9 GB (Keccak) or 1.0 GB (recursion) per instance. Both rows serialize the reveal fixtures of Table 4 and add the reject-label Disprove; the rest of the graph is not constructed (§4), so each is a lower bound. ‡Verifier assumptions only; the protocol adds discrete-logarithm signatures, or the unimplemented hash-based soldering and post-quantum authorization. Neither measured run binds public values (§5). The recursion row, the last proof of Table 7, uses the unreviewed changes of Appendix C.5, and its statement, a Ziren proof, rests on an elliptic-curve digest [DYH+26].

for the Boolean-garbled Groth16 verifier at the same parameters [WAA+26]. These setup figures are derived from the measured garbling time, not measured end to end.

On-chain, the comparison inverts: the Groth16 designs publish 508 to 1,019 input bits and report dispute paths of a few to a few tens of kilobytes, under $60, whereas our Keccak dispute publishes 1,041,024 bits at a Core-tested input component of 2.22 MvB with adaptors or 7.86 MvB hash-based, and the recursion verifier's 564,552 bits serialize to 1.21 and 4.26 MvB. That is one to

| verifier | input bits | non-free gates | garbled |
|---|---|---|---|
| binary stage (level 1) | 18,050,304 | 3,371.4M | 53.94 GB |
| narrow recursion, level 2 | 2,356,864 | 473.9M | 7.58 GB |
| level 4, rate 1/1024 | 1,248,384 | 231.2M | 3.70 GB |
| + known opened values as constants | 1,137,536 | 226.8M | 3.63 GB |
| + one tensor for claims sharing a point | 1,006,464 | 221.7M | 3.55 GB |
| + 200-bit Merkle digests | 895,504 | 220.2M | 3.52 GB |
| + packed operand columns | 834,832 | 219.2M | 3.51 GB |
| + linear forms, per-round folds, deep preprocessed cap | 643,688 | 215.8M | 3.45 GB |
| + one ring switch per pair, eq-factored bus rounds | 603,112 | 216.5M | 3.46 GB |
| + affine preprocessed forms, one shared forms sumcheck | 574,952 | 217.8M | 3.48 GB |
| + preprocessed cap 18 layers deep | **564,552** | 218.0M | 3.49 GB |

Table 7: Narrow recursion removes the statement's width from the garbled verifier's input. Exact counts for Ziren's binary stage and for the verifier of its narrow-recursion proofs (level 2 with 26-bit addresses, the smallest that fit the real tape); the rows from the third on use the experimental changes listed in Appendix C.5, measured on an earlier, unpublished Ziren commit (Appendix C.1).

three orders of magnitude more, about 38× deferred binding's 32 kvB even for the recursion verifier with adaptors, before the unconstructed remainder of the graph: the price of verifying the STARK directly rather than wrapping it, which §4.4 and §7 are about reducing.

# 6 Security

This section states what the garbled verifier guarantees and on which assumptions. It combines the soundness of the proof system, the effect of the two guarded branches, and the authenticity of the garbling, and then accounts for the dispute of §4.1.

**The circuit and the verifier.** When neither guarded event of §4.2 occurs, the circuit computes exactly the reference verifier; we test this op for op against its logged transcript and on real proofs. When a guarded event occurs, the circuit outputs 0. Hence an output of 1 implies that the reference verifier accepts, and an honest proof is rejected only if a guarded event occurs, with probability at most $\varepsilon_{\text{guard}} \approx n \cdot 2^{-127}$ for $n$ guarded coordinates.

**Soundness of the proof system.** We take the reference implementation's own security assessment of each configuration as the classical bound, with every proximity term in the Johnson list-decoding regime. At $2^{18}$ rows the binding term is the WHIR opening at 104.3 bits, and the composed soundness stays at about 104 bits at every measured size (Appendix D). We write $\varepsilon_{\text{STARK}}(t)$ for the composed error against an adversary making $t$ hash queries, $\varepsilon_{\text{STARK}}(t) \le t \cdot 2^{-104.3}$ classically at $2^{18}$ rows; §6.1 gives the quantum bound.

**Authenticity of the garbling.** Our scheme is privacy-free garbling [FNO15] with free-XOR [KS08] and one ciphertext per non-free gate [ZRE15], with $H$ = Blake3 and a fresh secret $\Delta$ per garbling. Free-XOR is secure when $H$ is circular correlation robust [CKKZ12]; we assume this of Blake3, as is standard for hash-based garbling. In the BitVM setting the garbled circuit is published at setup and the proof is chosen afterwards, so authenticity must hold for inputs chosen adaptively, after the garbled circuit is seen [BHR12a]. Let $\varepsilon_{\text{GC}}$ be the advantage of an evaluator

that sees the garbled circuit, then chooses an input $x$, receives its labels, and outputs the label of the value $\neg C(x)$ on the output wire. We assume that our Blake3-based free-XOR garbling has adaptive authenticity in this sense, with Blake3 modeled as a random oracle; Bellare, Hoang and Rogaway give constructions proven adaptively secure [BHR12a].
The following circuit-level statement is conditional on the Blake3 circular-correlation-robustness and adaptive-authenticity assumptions stated above. It does not cover cut-and-choose, input soldering or Bitcoin transaction enforcement.

**Theorem 1.** *Let $C$ be a correctly garbled verifier of a fixed configuration, and $x$ the encoding of a proof $\pi$ for a statement.*

*(i)* Soundness. *If the statement is false, an evaluator holding the labels of $x$ obtains the output label of value 0, except with probability at most $\varepsilon_{\mathrm{STARK}}(t)$, where $t$ bounds the hash queries of the party that chose $\pi$.*

*(ii)* Authenticity. *If $\pi$ is honestly generated, an evaluator holding the labels of $x$ obtains the output label of value 0 with probability at most $\varepsilon_{\mathrm{guard}} + \varepsilon_{\mathrm{GC}}$.*

*Proof sketch.* (i) If $C(x) = 1$, the reference verifier accepts $\pi$ by the previous paragraphs, which for a false statement happens with probability at most $\varepsilon_{\mathrm{STARK}}(t)$. Otherwise $C(x) = 0$, and correctness of the garbling yields the label of value 0. (ii) For an honest proof $C(x) = 1$ unless a guarded event occurs, and the label of value 0 is then the label of $\neg C(x)$, which the evaluator obtains with probability at most $\varepsilon_{\mathrm{GC}}$. □
The theorem applies only to the relation represented by $C$. In our experiments that relation is Keccak-$f$ trace validity without external public values; it does not prove authorization of a bridge withdrawal.

**The dispute.** Let $\varepsilon_{\mathrm{cc}}$ bound the probability that every kept instance is malformed while every opened one is correct; for choosing $N - M$ of $N$ uniformly this is $1/\binom{N}{M}$, which is $2^{-40}$ at $(N, M) = (181, 7)$ [GKS+26]. Let $\varepsilon_{\mathrm{sol}}$ bound a failure of the soldering, and let $\varepsilon_{\mathrm{sig}}$ bound the aggregate probability of forging any one-time or transaction-authorization signature across the entire dispute, so a reduction from a per-target bound must include the number of targets. At these parameters, cut-and-choose alone limits the intended malicious-garbler security to about 40 bits, irrespective of the STARK verifier's 104-bit classical soundness.

Subject to an enforced transaction graph, timely confirmation and an instantiated soldering bound, Theorem 1 supports two intended properties of the dispute of §4.1. *A false claim is disproved:* if the operator's statement is false, an honest challenger obtains some $\ell_0^j$ except with probability $\varepsilon_{\mathrm{STARK}}(t) + \varepsilon_{\mathrm{cc}} + \varepsilon_{\mathrm{sol}}$, since a correctly garbled kept instance exists, its labels are those of the published proof, and Theorem 1(i) applies; an operator that publishes no proof loses its stake to AssertTimeout. *An honest operator keeps its stake:* if the proof is honest, no challenger obtains any $\ell_0^j$ except with probability $M(\varepsilon_{\mathrm{guard}} + \varepsilon_{\mathrm{GC}}) + \varepsilon_{\mathrm{sol}} + \varepsilon_{\mathrm{sig}}$, by Theorem 1(ii) and a union bound over the kept instances. This is conditional accounting, not a protocol theorem in a ledger model: $\varepsilon_{\mathrm{sol}}$ has no instantiated bound, and the transaction graph and ledger-timing assumptions have not been implemented or proved. BitVM3 [WAA+26] and BABE [GKS+26] analyze their own instantiations.

### 6.1 Post-quantum analysis

The verifier construction avoids number-theoretic assumptions: the proof system, commitments, transcript and garbling use Blake3. This statement does not cover Bitcoin transaction autho-

rization or every proposed input-publication mechanism. The estimates below are conditional on the stated random-oracle, round-by-round-soundness and adaptive-authenticity assumptions; they are not an end-to-end post-quantum security proof. Pairing-based verifiers (Groth16, Pari and their designated-verifier variants), the witness-encryption schemes built on them (§2) and Bitcoin's own Schnorr signatures fall to Shor's algorithm [Sho94]. Our verifier does not. Avoiding discrete-logarithm and pairing assumptions is necessary for quantum resistance here, but a hash-based verifier is not sufficient by itself: a quantum adversary still speeds up generic preimage and collision search [Gro96, BHT98]. Table 8 gives component-level estimates; Appendix D derives them.

**The proof system and the garbling.** In the quantum random-oracle model, Fiat–Shamir applied to a round-by-round-sound protocol gives a quantum adversary with $t$ hash queries advantage $O(t^2\varepsilon_{\mathrm{rbr}} + t^3/2^\lambda)$ [CMS19], so a round with error $2^{-a}$ offers about $a/2$ quantum bits, and $b$ bits of grinding cost about $2^{b/2}$ quantum hashes. At $2^{18}$ rows each WHIR term targets 110 bits, of which grinding supplies 26 to 32, so the composed 104.3 bits become about 52; the algebraic terms, Schwartz–Zippel errors over the $2^{128}$-element field, offer 54 to 58 bits and no number of queries raises them. Raising the per-term target does not help either: the proven profile raises grinding, not queries, and no configuration of the current proof system exceeds about 54 quantum bits, so a quantum target is a change to the proof system, not to its parameters. The garbling offset $\Delta$ can be tested against a single gate, so Grover search recovers it in about $2^{64}$ Blake3 evaluations; with 128-bit labels the garbling, and a hashlock on a 128-bit output label, offer about 64 quantum bits.

**The surrounding protocol.** The protocol is not post-quantum as instantiated. Schnorr adaptor signatures, the committee's pre-signed transactions and Taproot key-path spends fall to Shor's algorithm. Hash-based input keys avoid the adaptor-signature dependency, but their one-key-set cost assumes the unimplemented soldering in §4; the seven-key-set projection is 25–54 times the adaptor payload. Bitcoin has no opcode that natively verifies a post-quantum signature. QSB gives a non-standard hash-based authorization path under existing consensus rules [Lev26, Sta26], but whether it can replace the authorization of a pre-signed, timelocked dispute graph is outside our scope. We therefore treat graph authorization as an explicit open assumption rather than a solved component. The hash-based input keys themselves are bounded by multi-target preimage search over the $T \approx 2^{20}$ published preimages, about 54 quantum bits for one key set and 52.6 for seven (Table 8, Appendix D).

**Parameters for a quantum target.** No single rule doubles every classical parameter. Appendix E lists the seven changes a 100-quantum-bit target requires, about 2.1× the WHIR queries, one more tower level, 256-bit labels, a hash with a wider digest and state, longer input preimages, stronger cut-and-choose and post-quantum transaction authorization, and estimates the first three at about 280M non-free gates and 9 GB garbled, 3× today's, without the replacement hash or the protocol layers.

| component | attack | classical | quantum estimate | to reach $\lambda_Q$ quantum bits |
|---|---|---|---|---|
| WHIR opening | Fiat–Shamir (FS) search, grinding | 104.3 (max. 111.3) | $\approx 52$ | $\approx 2\lambda_Q$ per term: $\approx 2.1\times$ queries at $\lambda_Q = 100$ |
| zerocheck, sumchecks, ring switch | FS search | 109–115 | $\approx 54$–$58$ | a field of $\gtrsim 2^{2\lambda_Q+14}$ elements: $\mathbb{F}_{2^{256}}$ |
| Merkle and transcript hash | collision, preimage | 128 | $\approx 85$ | $\gtrsim 3\lambda_Q$-bit digest and wider internal state; unmeasured |
| garbling ($\Delta$, output hashlock) | Grover on 128-bit labels | 128 | $\approx 64$ | $2\lambda_Q$-bit labels: 256 bits |
| hash-based input keys | multi-target preimage, $T \approx 2^{20}$ ($7T$ for seven sets) | $\approx 108$ (105.2) | $\approx 54$ (52.6) | at least 220 (223) bits of preimage entropy under a 256-bit hash |
| cut-and-choose $(181, 7)$ | bad kept set | 40 | 40 | increase $(N, M)$ for the target error |
| adaptor keys, pre-signed graph | Shor | – | broken | post-quantum transaction authorization |

Table 8: The measured proof system has a bottleneck near 52 quantum bits under the stated assumptions; this is not the composed protocol level. The reported cut-and-choose parameters provide about 40 statistical bits, and the transaction authorization is broken by Shor. Reaching 100 quantum bits also requires more queries, a 256-bit field, 256-bit labels, a hash with at least a 300-bit digest and sufficiently wide internal state, a 256-bit input hash with 28-byte preimages, stronger cut-and-choose and post-quantum transaction authorization.

# 7 Discussion and conclusion

We have measured what a garbled STARK dispute would publish on Bitcoin and reduced it. The $2^{18}$-row Keccak-$f$ verifier reads 1,041,024 input bits, whose Core-tested publication costs 2.22 MvB with adaptor signatures and 7.86–17.27 MvB with hash-based keys for one key set; WHIR tuning removes a fifth of the input, and the verifier of the last of three narrow-recursion proofs of Ziren's binary stage reads 564,552 bits in 218.0M non-free gates, measured on real proofs but resting on unreviewed changes to Plonky3 and Ziren and binding neither the zkVM program nor its outputs. The verifier that makes this possible has 94.1M non-free gates and a 1.5 GB garbled artifact, about $30\times$ fewer non-free gates than the reported Boolean-garbled Groth16 verifier. The rest of this section says what stands between these components and an end-to-end Bitcoin protocol.

**Input authentication dominates the measured components.** The largest measured on-chain component is revealing and authenticating the 1,041,024 circuit-input bits in a dispute, not committing or transporting them. The raw bits fit a 33-kvB transport fixture, whereas authenticating them for one key set costs 2.22–17.27 MvB (Table 4); strict Core 31.1 accepted the four signed funding–reveal slices, but only in confirmed stages, none is an atomic unconfirmed graph, and only the Lamport fixture also tests a join. The hash-based rows assume the unimplemented soldering or multiply by $M$, and the independent seven-set projection is 55–121 MvB before the transaction graph.

WHIR tuning removes only a fifth of the input (Table 5); equal-area narrow-statement models remove 37–58% but need a new AIR; batching amortizes the input per permutation by $3.76\times$ without reducing the absolute input; and narrow recursion reaches $0.54\times$ (Table 7) at the price of

a recursion prover and of proof-system changes still to be reviewed.

The approximately 52-bit quantum figure applies to the measured proof-system parameters under the stated assumptions, cut-and-choose is configured at 40 statistical bits, and the current transaction authorization is not post-quantum. Before deployment, the construction needs public-input support, an implemented and measured multi-copy input layer, a serialized and policy-tested Assert graph, post-quantum graph authorization, and a measured parameter set with an enlarged field and labels, a wider-state hash and stronger cut-and-choose.

**Open directions.** Two input-layer ideas could cut the published data below the proof's size, and neither is implemented. TinyLabels [DLL24] delivers selected labels in $|x| + \mathrm{poly}(\lambda)$ online bits under Ring-LWE, about 0.24 MB for our input, but its selector key is not publicly verifiable and a malformed delivery aborts instead of yielding the reject label that opens Disprove. Segmented verification would commit once to the proof, locate a faulty verifier segment by bisection and authenticate only the challenged chunk, but only the WHIR Merkle paths and leaf rows split by query; the rest, more than half the input (Table 5), is global to the verifier, so every layer would need segmenting with bound boundary states, and the worst case remains the full input.

## References


[ACFY24] Gal Arnon, Alessandro Chiesa, Giacomo Fenzi, and Eylon Yogev. STIR: Reed–solomon proximity testing with fewer queries. In *Advances in Cryptology – CRYPTO 2024, Part X*, volume 14929 of *LNCS*, pages 380–413. Springer, 2024. Full version: Cryptology ePrint Archive, Paper 2024/390.

[ACFY25] Gal Arnon, Alessandro Chiesa, Giacomo Fenzi, and Eylon Yogev. WHIR: Reed–Solomon proximity testing with super-fast verification. In *Advances in Cryptology – EUROCRYPT 2025, Part IV*, volume 15604 of *LNCS*, pages 214–243. Springer, 2025. Cryptology ePrint Archive, Paper 2024/1586.

[ACG+26] Michel Abdalla, Brent Carmer, Muhammed El Gebali, Handan Kilinc-Alper, Mikhail Komarov, Yaroslav Rebenko, Lev Soukhanov, Erkan Tairi, Elena Tatuzova, and Patrick Towa. Bitcoin PIPEs v2: Covenants and ZKPs on Bitcoin via witness encryption. Cryptology ePrint Archive, Paper 2026/186, 2026.

[BHR12a] Mihir Bellare, Viet Tung Hoang, and Phillip Rogaway. Adaptively secure garbling with applications to one-time programs and secure outsourcing. In *Advances in Cryptology – ASIACRYPT 2012*, volume 7658 of *LNCS*, pages 134–153. Springer, 2012.

[BHR12b] Mihir Bellare, Viet Tung Hoang, and Phillip Rogaway. Foundations of garbled circuits. In *Proceedings of the 2012 ACM Conference on Computer and Communications Security*, pages 784–796. ACM, 2012.

[BHT98] Gilles Brassard, Peter Høyer, and Alain Tapp. Quantum cryptanalysis of hash and claw-free functions. In *LATIN 1998: Theoretical Informatics*, volume 1380 of *LNCS*, pages 163–169. Springer, 1998.

[BIJ+20] James Bartusek, Yuval Ishai, Aayush Jain, Fermi Ma, Amit Sahai, and Mark Zhandry. Affine determinant programs: A framework for obfuscation and witness

encryption. In *11th Innovations in Theoretical Computer Science Conference (ITCS 2020)*, volume 151 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 82:1–82:39. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, 2020.

[Bit25] BitVM. Garbled SNARK verifier. Source code, commit `5a2cd4dc6cb19e37adb1b3ab94414e01d1e8b338`, 2025.

[Bit26] Bitcoin Core developers. Bitcoin Core 31.1 transaction relay policy constants. Source code, release tag `v31.1`, 2026. Defines `MAX_STANDARD_TX_WEIGHT` and `DEFAULT_CLUSTER_SIZE_LIMIT_KVB`.

[Can89] David G. Cantor. On arithmetical algorithms over finite fields. *Journal of Combinatorial Theory, Series A*, 50(2):285–300, 1989.

[CBBZ23] Binyi Chen, Benedikt Bünz, Dan Boneh, and Zhenfei Zhang. HyperPlonk: Plonk with linear-time prover and high-degree custom gates. In *Advances in Cryptology – EUROCRYPT 2023, Part II*, volume 14005 of *LNCS*, pages 499–530. Springer, 2023. Full version: Cryptology ePrint Archive, Paper 2022/1355.

[Che25] Weikeng Chen. SoK: BitVM with succinct on-chain cost. Cryptology ePrint Archive, Paper 2025/1253, 2025.

[CKKZ12] Seung Geol Choi, Jonathan Katz, Ranjit Kumaresan, and Hong-Sheng Zhou. On the security of the "free-XOR" technique. In *Theory of Cryptography Conference (TCC 2012)*, volume 7194 of *LNCS*, pages 39–53. Springer, 2012.

[CMS19] Alessandro Chiesa, Peter Manohar, and Nicholas Spooner. Succinct arguments in the quantum random oracle model. In *Theory of Cryptography Conference (TCC 2019), Part II*, volume 11892 of *LNCS*, pages 1–29. Springer, 2019. Cryptology ePrint Archive, Paper 2019/834.

[DLL24] Marian Dietz, Hanjun Li, and Huijia Lin. TinyLabels: How to compress garbled circuit input labels, efficiently. Cryptology ePrint Archive, Paper 2024/2048, 2024.

[DMS24] Michel Dellepere, Pratyush Mishra, and Alireza Shirzad. Garuda and pari: Faster and smaller SNARKs via equifficient polynomial commitments. Cryptology ePrint Archive, Paper 2024/1245, 2024.

[DP25] Benjamin E. Diamond and Jim Posen. Succinct arguments over towers of binary fields. In *Advances in Cryptology – EUROCRYPT 2025, Part IV*, volume 15604 of *LNCS*, pages 93–122. Springer, 2025. Full version: Cryptology ePrint Archive, Paper 2023/1784.

[DP26] Benjamin E. Diamond and Jim Posen. Polylogarithmic proofs for multilinears over binary towers. In *Advances in Cryptology – EUROCRYPT 2026, Part VII*, volume 16547 of *LNCS*, pages 3–32. Springer, 2026. Full version: Cryptology ePrint Archive, Paper 2024/504.

[DYH+26] Stephen Duan, Jingping Yin, Blake Hou, Vanhger Pham, Ethan Zhu, and Ming Guo. Ziren: Succinct arguments for MIPS32 execution. Cryptology ePrint Archive, Paper 2026/2330, 2026.

[Eag25] Liam Eagen. Glock: Garbled locks for Bitcoin. Cryptology ePrint Archive, Paper 2025/1485, 2025.

[EL26] Liam Eagen and Ying Tong Lai. Argo MAC: Garbling with elliptic curve MACs. Cryptology ePrint Archive, Paper 2026/049, 2026.

[FBF+26] Ariel Futoransky, Fadi Barbàra, Ramses Fernandez, Gabriel Larotonda, and Sergio Demian Lerner. TRAPGC-DV: Trapdoor garbled circuit designated verification of Groth16 on Bitcoin. Cryptology ePrint Archive, Paper 2026/1430, 2026.

[FLB25] Ariel Futoransky, Gabriel Larotonda, and Fadi Barbara. A note on the security of the BitVM3 garbling scheme. Cryptology ePrint Archive, Paper 2025/1291, 2025.

[FNO15] Tore Kasper Frederiksen, Jesper Buus Nielsen, and Claudio Orlandi. Privacy-free garbled circuits with applications to efficient zero-knowledge. In *Advances in Cryptology – EUROCRYPT 2015, Part II*, volume 9057 of *LNCS*, pages 191–219. Springer, 2015.

[GGSW13] Sanjam Garg, Craig Gentry, Amit Sahai, and Brent Waters. Witness encryption and its applications. In *45th ACM STOC*, pages 467–476. ACM, 2013.

[GKPW24] Sanjam Garg, Dimitris Kolonelos, Guru-Vamsi Policharla, and Mingyuan Wang. Threshold encryption with silent setup. In *Advances in Cryptology – CRYPTO 2024, Part VII*, volume 14926 of *LNCS*, pages 352–386. Springer, 2024.

[GKS+26] Sanjam Garg, Dimitris Kolonelos, Mikhail Sergeevitch, Srivatsan Sridhar, and David Tse. BABE: Verifying proofs on Bitcoin made 1000x cheaper. Cryptology ePrint Archive, Paper 2026/065, 2026.

[GOA26a] GOAT Network. bitcoin-stark-verifier: a STARK verifier in Bitcoin Script without OP_CAT. GOATNetwork/bitcoin-stark-verifier, crates `poseidon2` and `whir`, commit `d45e453`, 2026.

[GOA26b] GOAT Network. bitvm-gc: garbled SNARK verifier and BABE for BitVM. Source code, commit `10083d4a63eb08a344dc40ee84bc11394b218a89`, 2026.

[Gro96] Lov K. Grover. A fast quantum mechanical algorithm for database search. In *Proceedings of the 28th Annual ACM Symposium on Theory of Computing*, pages 212–219. ACM, 1996.

[KFLT26] Nakul Khambhati, Aaron Feickert, Christian Lewe, and Mukesh Tiwari. Garbling Groth16 with native group operations. Cryptology ePrint Archive, Paper 2026/2100, 2026.

[KLN25] Victor I. Kolobov, Avihu M. Levy, and Moni Naor. ColliderVM: Stateful computation on Bitcoin without fraud proofs. Cryptology ePrint Archive, Paper 2025/591, 2025.

[KS08] Vladimir Kolesnikov and Thomas Schneider. Improved garbled circuit: Free XOR gates and applications. In *Automata, Languages and Programming (ICALP 2008), Part II*, volume 5126 of *LNCS*, pages 486–498. Springer, 2008.

[KTA+26] Nakul Khambhati, Mukesh Tiwari, Azz, Sapin Bajracharya, Manish Bista, Liam Eagen, Christian Lewe, and Aaron Feickert. Mosaic: Practical malicious security for garbled circuits on Bitcoin. Cryptology ePrint Archive, Paper 2026/812, 2026.

[LAA+25] Robin Linus, Lukas Aumayr, Zeta Avarikioti, Matteo Maffei, Andrea Pelosi, Orfeas Stefanos Thyfronitis Litos, Christos Stefo, David Tse, and Alexei Zamyatin. Bridging Bitcoin to second layers via BitVM2. Cryptology ePrint Archive, Paper 2025/1158, 2025.

[LAM+24] Sergio Demian Lerner, Ramon Amela, Shreemoy Mishra, Martin Jonas, and Javier Álvarez Cid-Fuentes. BitVMX: A CPU for universal computation on Bitcoin. arXiv preprint arXiv:2405.06842, 2024.

[LCH14] Sian-Jheng Lin, Wei-Ho Chung, and Yunghsiang S. Han. Novel polynomial basis and its application to Reed–Solomon erasure codes. In *IEEE 55th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 316–325. IEEE, 2014.

[Lev26] Avihu Mordechai Levy. Quantum-safe Bitcoin transactions without softforks. Technical report, `https://github.com/avihu28/Quantum-Safe-Bitcoin-Transactions/blob/main/paper/QSB.pdf`, 2026. Source code: `https://github.com/avihu28/Quantum-Safe-Bitcoin-Transactions`.

[LFKN92] Carsten Lund, Lance Fortnow, Howard Karloff, and Noam Nisan. Algebraic methods for interactive proof systems. *Journal of the ACM*, 39(4):859–868, 1992.

[LJF25] Sergio Demian Lerner, Martin Jonas, and Ariel Futoransky. ESSPI: ECDSA/Schnorr signed program input for BitVMX. arXiv preprint arXiv:2503.02772, 2025.

[Nat15] National Institute of Standards and Technology. SHA-3 standard: Permutation-based hash and extendable-output functions. FIPS PUB 202, NIST, 2015.

[OANWO20] Jack O'Connor, Jean-Philippe Aumasson, Samuel Neves, and Zooko Wilcox-O'Hearn. BLAKE3: One function, fast everywhere. `https://github.com/BLAKE3-team/BLAKE3-specs`, 2020.

[Pha26] Vanhger Pham. Deferred binding: Extending BABE for dynamic public inputs in GOAT BitVM3. GOAT Research, HackMD, 2026. Accessed 5 November 2026. Implementation: GOATNetwork/bitvm2-gc, branch `feat/goat-bitvm3`, commit `c23130a`.

[Plo26] Plonky3 contributors. Plonky3: binary tower fields, WHIR and multi-STARK. Source code, commit `ca4da2daa2e0dfdd31419af5c870813083398955`, 2026.

[Rub25] Jeremy Rubin. Delbrag. Draft, April 2025.

[Sho94] Peter W. Shor. Algorithms for quantum computation: Discrete logarithms and factoring. In *35th Annual Symposium on Foundations of Computer Science*, pages 124–134. IEEE, 1994.

[SRG+26] Lev Soukhanov, Yaroslav Rebenko, Muhammad El Gebali, Mikhail Komarov, Handan Kilinc-Alper, Michel Abdalla, and Patrick Towa. Implementable witness encryption from arithmetic affine determinant programs. Cryptology ePrint Archive, Paper 2026/175, 2026.

[SST+26] Mikhail Sergeevitch, Konrad Staniec, David Tse, Nikhil Vanjani, and Robin Linus Woll. Non-interactive translation of Winternitz signatures to Lamport signatures via secret sharing. Cryptology ePrint Archive, Paper 2026/1684, 2026.

[Sta26] StarkWare. The first quantum-safe Bitcoin transaction has been mined. `https://starkware.co/blog/the-first-quantum-safe-bitcoin-transaction-has-been-mined/`, August 2026. Mainnet transaction: `https://mempool.space/tx/305a24ffea912b9cf428f29ebf952321c96dab5bab284fc0d0801562f5abab07`.

[TF26a] Mukesh Tiwari and Aaron Feickert. Antichain Winternitz: Guaranteed garbled-circuit label revelation on Bitcoin with permissionless recovery. Cryptology ePrint Archive, Paper 2026/1568, 2026.

[TF26b] Mukesh Tiwari and Aaron Feickert. The post-quantum cost of garbled-circuit Bitcoin bridges. Cryptology ePrint Archive, Paper 2026/2383, 2026.

[WAA+26] Robin Linus Woll, Ioannis Alexopoulos, Lukas Aumayr, Zeta Avarikioti, Matteo Maffei, and David Tse. BitVM3: Efficient Bitcoin bridges via garbled circuits. Cryptology ePrint Archive, Paper 2026/933, 2026.

[Wie88] Doug Wiedemann. An iterated quadratic extension of GF(2). *The Fibonacci Quarterly*, 26(4):290–295, 1988.

[WNT20] Pieter Wuille, Jonas Nick, and Anthony Towns. BIP 342: Validation of Taproot scripts. Bitcoin Improvement Proposal, 2020. Defines Tapscript signature semantics and resource limits.

[ZKM26] ZKM. Ziren: a MIPS zero-knowledge virtual machine, branch `feat/binary-whir-blake3`. Source code, commit `80af2779c17d4aa40ba2cafdea21734812892b4e`, 2026.

[ZRE15] Samee Zahur, Mike Rosulek, and David Evans. Two halves make a whole: Reducing data transfer in garbled circuits using half gates. In *Advances in Cryptology – EUROCRYPT 2015, Part II*, volume 9057 of *LNCS*, pages 220–250. Springer, 2015.

# A Terms

An *AIR* (algebraic intermediate representation) is a set of polynomial constraints over a trace's current and next rows. A *zerocheck* [CBBZ23] proves that the constraints vanish on every row by a sumcheck [LFKN92] against the equality polynomial $\mathrm{eq}(\tau, \cdot)$ at a random point $\tau$. *WHIR* [ACFY25] is a Reed–Solomon proximity test used as a multilinear polynomial commitment. Its *STIR queries* [ACFY24] open the committed, folded codeword at random positions, and its *out-of-domain* (OOD) samples bind the committed polynomial at points outside the evaluation domain. The *Cantor basis* is the $\mathbb{F}_2$-basis $v_0 = 1$, $v_i^2 + v_i = v_{i-1}$, which gives binary fields an additive FFT domain. The *bit ring switch* turns a claim about a polynomial's bits into a claim about its packed $\mathbb{F}_{2^{128}}$ representation. *Johnson list-decoding regime* refers to the proximity parameters for which the soundness bounds are proven via the Johnson bound, without conjectures.





Figure 3: Logical outcomes of the proposed dispute. The dashed Assert$_1$, . . . ,Assert$_k$ node denotes an unspecified publication subgraph. The figure does not define its UTXO dependencies, completion anchor, timeout enforcement or fee management, all of which remain to be constructed and policy-tested.

# B Bitcoin integration details

This appendix holds the material that §4 summarizes: the intended transaction graph, the hash-based label selection, its post-quantum instantiation and the four input-publication schemes as fixtures.

## B.1 The dispute graph

Figure 3 summarizes the intended logical outcomes for one claim. The Assert node is a placeholder for an unconstructed transaction subgraph.

**Required transaction semantics.** The intended branches are:

- *Kickoff*: the operator claims reimbursement for a withdrawal it has paid. If no challenge follows within $\Delta_C$, *Take1* pays it. This is the happy path.
- *Challenge*: any challenger may spend Kickoff's challenge output, paying the operator a bond that covers the cost of Assert, as BitVM2's crowdfunded challenge does [LAA+25].
- *Assert*$_1$, . . . ,*Assert*$_k$: the operator must publish every authenticated circuit-input bit. Because the payload exceeds one standard transaction, a concrete construction needs a subgraph whose terminal output is spendable only after every chunk has been published. We do not specify that fanout, chaining or completion mechanism here.
- *AssertTimeout*: if the operator fails to create the completion output before $\Delta_A$, a timeout branch should transfer its stake. The enforceable condition for "all chunks published" depends on the missing subgraph and is not specified by Figure 3.
- *Disprove*$_j$: after such a completion output exists, a challenger holding $\ell_0^j$ would open the corresponding hashlock before $\Delta_D$; otherwise Take2 would pay the operator. The required transaction dependencies and relative timelocks remain unimplemented.

The complete graph must be tested against the release policy targeted for deployment; current policy limits a standard transaction to 400,000 weight units and an unconfirmed cluster to 101 virtual kilobytes [Bit26].

## B.2 Hash-based label selection

Figure 4 is the hash-based counterpart of Figure 2: the signature completion is replaced by a pair of hash-chain openings, the evaluator contributes nothing at setup, and the transaction binding must be added as a separate signature.

## B.3 A post-quantum instantiation

**A post-quantum instantiation.** Figure 4 becomes a post-quantum replacement for the adaptor under three changes, none of which is available on Bitcoin today. First, the forward hashing moves out of Script into a native batch verifier: one leaf per transaction carries the batch root $\rho$, the first digit index and the count, and an opcode re-derives every endpoint from the records on the stack. Second, the transaction-binding signature becomes hash-based; the draft P2MR output type and its 0xC2 leaf version[1] would provide a 548-byte stateful hash-based signature per transaction and 6,000-byte stack items. Third, the node width $n$ must match the quantum target: forging a different digit from a published opening is a second-preimage search over the roughly $2^{22}$ chain nodes that the whole input makes public, so $n = 16$ gives about 53 quantum bits, $n = 24$ about 85 and $n = 32$ about 117.

We serialized this construction exactly with rust-bitcoin for $n = 16$ and $n = 24$ at $k = 4$, including the P2MR outputs, 0xC2 leaves, placeholder signatures, depth-one control blocks and canonical multi-record stack items, and tested the pair code and the batch parser against tampering, reordering, cross-batch splicing and padding; nothing in it is executable by Bitcoin Core. Table 9 gives the results together with a projection whose model reproduces both serialized fixtures within 0.03%. The operative row is $n = 32$, $k = 8$: full-width nodes, about 117 quantum bits for the selection, and about 2.13 MvB against the Schnorr adaptor's 2.23 MvB, at the price of 255 hash steps per byte inside the opcode, about $3.3 \times 10^7$ compressions for the input. Its setup is two seeds per digit rather than the adaptor's $2^k$ secrets, so widening $k$ does not grow the choice table; only the translation table grows, to $2^k \cdot k \cdot 16$ bytes per digit, 4.3 GB per instance at $k = 8$. The delivery and soldering of that table across the $M$ kept garblings is the same open item as for every other row.

## B.4 The four input schemes

The four one-time schemes of Table 4 trade on-chain size against assumptions.

- *Lamport.* Each bit has two hashed 16-byte preimages, and the revealed preimage is the one-time-signature witness. The leaf script per bit,

  `OP_HASH160 OP_DUP` $h_0$ `OP_EQUAL OP_SWAP` $h_1$ `OP_EQUAL OP_BOOLOR OP_VERIFY`

  is 49 bytes, and the witness 17 bytes. We executed it with 998 bits per input, and it rejected wrong preimages. The transaction-bound fixture prefixes each leaf with a 32-byte authorization key and `OP_CHECKSIGVERIFY`, and supplies a 64-byte `SIGHASH_DEFAULT` signature. Its initial stack has 999 items and the measured transient peak is exactly the 1,000-item Tapscript limit [WNT20]. Its serialized size is the Lamport row of Table 4. The fixture uses a one-leaf tree with a 33-byte control block; timeout siblings and their longer control paths belong to the missing complete graph.

[1] BIP360, `https://github.com/bitcoin/bips/blob/master/bip-0360.mediawiki`, and the SHRINCS proposal for a stateful hash-based signature in that leaf; both are drafts and may change.





Figure 4: Hash-based label selection for one $k$-bit digit position $i$ with $n$-byte chain nodes. The selection material is two nodes instead of one signature, the evaluator contributes nothing at setup, and the transaction binding that the adaptor gets from the same signature must be added separately. Verification is a hash ladder, in Script today or in a batch opcode under the soft fork of Table 9.

| selection | consensus | $n$ | $k$ | vB/bit | component | selection security, quantum |
|---|---|---|---|---|---|---|
| Schnorr adaptor (Fig. 2) | current | – | 8 | 2.14 | 2.23 MvB | broken (Shor) |
| WOTS translation [SST$^+$26] in Script | current | 20 | 3 | 7.59 | 7.90 MvB | $\approx 64$ bits ($\kappa$ chain; nodes $\approx 70$) |
| Antichain $(2, 16)$ in Script (Fig. 4) | current | 16 | 4 | 11.41 | 11.88 MvB | $\approx 53$ bits |
| batched selector, one record per item | P2MR, 0xC2, batch opcode | 16 | 4 | 2.05 | 2.13 MvB | $\approx 53$ bits |
| batched selector, 11-record items | same | 16 | 4 | 2.04 | 2.12 MvB | $\approx 53$ bits |
| batched selector, 5-record items | same | 24 | 4 | 3.05 | 3.17 MvB | $\approx 85$ bits |
| batched selector, projected | same | 32 | 8 | $\approx 2.05$ | $\approx 2.13$ MvB | $\approx 117$ bits |

Table 9: Hash-based label selection against the adaptor baseline for the 1,041,024-bit input, funding plus reveals. The first three rows are the Core-tested fixtures of Table 4. The batched-selector rows are exact rust-bitcoin serializations of a construction that requires the draft P2MR output, a hash-based transaction signature and a hypothetical batch verification opcode; the last row is a model projection. The security column is the multi-target second-preimage cost of the chain nodes alone, except for WOTS translation, whose 128-bit key chain gives the lower bound; the composed protocol remains bound by the proof system (§6.1).

- *Antichain Winternitz.* Plain Winternitz chains are unsafe here: from a published chain value the evaluator hashes forward to the labels of other digit values [TF26a]. Antichain Winternitz closes this and costs a cited marginal 11.31 vB per bit at parameters $(2, 16)$, counting the hash-chain opening witness and authentication script but cancelling fixed transaction overhead. Our transaction-bound fixture pins the upstream implementation, prepends a 64-byte Schnorr authorization, and includes two pay-to-Taproot (P2TR) outputs, input shells, leaf scripts and depth-zero controls. With at most 332 four-bit digits per input, its size is the Antichain row of Table 4, an all-nonzero worst case that zero-valued ScriptNum coordinates only reduce. The source reports 0.256 kB of off-chain table per bit. Its larger parameters save more on-chain but need up to 43.8 kB per bit off-chain [TF26a], 46 GB for our input.
- *Winternitz with a translation table.* The translation gadget of [SST$^+$26] also closes the gap of plain Winternitz: each label is a Shamir secret whose threshold is set by the chunk's checksum and the bit value, so a signed chunk opens exactly the labels of its bits. In the source, one such Winternitz signature over 508 bits, its Assert, is 3,748 vB, or 7.38 vB per bit. Our transaction-bound fixture uses 3-bit digits, eight per chunk, with the checksum split over two chains, and the authorization, outputs and controls of the Antichain fixture. With at most 49 chunks per input, its size is the WOTS row of Table 4, again an all-nonzero worst case. The price is the off-chain table, 1,830 bytes per bit or 1.905 GB per instance. The challenger must decode digits as consensus does and, at setup, reject keys in which one chain end lies within seven hashes of another; neither check costs on-chain space.
- *Schnorr adaptor signatures* over 8-bit digits, as in BitVM3 and Mosaic. BitVM3 reports 9,707 weight units (WU) for a 1,024-bit Assert transaction with one input and two P2TR outputs [WAA$^+$26], or 2.37 vB per bit at that size. Its printed witness formula instead sums to 9,451 WU once the SegWit marker and flag are included, while the merged 64-

byte-`SIGHASH_DEFAULT` implementation implies 9,323 WU for that shell. Our executable fixture reproduces 9,323 WU, uses the BIP342 opcode index rather than a byte offset for every code separator, and reaches the exact 998-signature stack capacity. Core 31.1 validates all completed signatures. Its size for the 130,128 eight-bit digits is the adaptor row of Table 4. Mosaic's source construction solders all kept instances to one set of signatures by polynomial label correlation, with an on-chain footprint independent of the number of instances [KTA+26]. This repository tests only the one-key-set transaction fixture; it does not implement or test Mosaic's polynomial correlation or setup verification. The signatures rest on discrete logarithms, and an evaluator that holds the signing key can spend without completing the adaptor [TF26a].

Packing more bits into each adaptor completion reduces the serialized transaction shape. Our Core-tested 16-bit fixture uses 2,960 vB of funding and 1,111,128 vB across 12 reveals, or 1,114,088 vB in 13 transactions. Exact serializations of 10-, 11- and 12-bit digits, still with placeholder signatures and not replayed in Core, give 1,782,498, 1,620,499 and 1,485,410 vB including funding. The price is off-chain: a table of every digit's $2^b$ choices at 65 bytes each is 2.165 GB per key set at 8 bits, 6.929, 12.598 and 23.097 GB at 10, 11 and 12 bits, and 277.162 GB at 16. This is an encoding sensitivity result, not yet a binary-label authentication mechanism: the complete $2^{16}$ choice table and exclusive digit-to-binary-label delivery remain unimplemented. We therefore retain the 8-bit construction as the authenticated baseline in Table 4.

# C Additional measurements

## C.1 Artifact availability

**Artifact availability.** The source repository includes the locked dependencies and benchmark commands; the commands and memory caps are listed in `whir-gc/README.md`. The raw measurement logs, with a SHA-256 manifest and a map from tables and figures to logs, are archived separately and available on request. The experimental Plonky3 and Ziren changes behind Table 7 are public in Ziren commit `80af2779` on `feat/binary-whir-blake3` and Plonky3 commit `be1c6f92` on ProjectZKM's `zkm/binary-whir`. The figures were measured on an earlier, unpublished Ziren commit. `Cargo.lock` pins Plonky3 at revision `ca4da2daa2e0dfdd31419af5c870813083398955` and bitvm-gc at revision `10083d4a63eb08a344dc40ee84bc11394b218a89`. Gate, wire and input counts are deterministic; wall-clock times are single-run engineering measurements on the machines above unless a range is stated.

## C.2 Gate profile, garbling efficiency, WHIR parameters and ablation

**Merkle openings and caps.** The prover sends Merkle openings pruned: siblings that another query can recompute are left out. Our implementation expands the proof outside the circuit into one full path per query. This is an engineering choice rather than an inherent limitation of a fixed circuit: a fixed upper-bound circuit could verify a padded frontier with data-dependent routing. A million-trial simulation of the actual stratified queries and cap forest, however, reduces the expected path from 1,354 to 1,335.71 digests, only 4,683 input bits or 0.45% of the total, before the routing and padding overhead. When the commitment uses a Merkle cap of $2^h$ roots, the transcript absorbs all of them, and each query selects its root with a multiplexer on the top $h$ index bits: $256(2^h - 1)$ AND gates, against $h$ compressions saved.

| phase | non-free gates | share |
|---|---|---|
| ring switch closing | 31,633,960 | 33.6% |
| WHIR Merkle paths | 14,613,722 | 15.5% |
| column combination | 11,582,352 | 12.3% |
| AIR constraints (1,650, Horner under $\alpha$) | 10,736,110 | 11.4% |
| STARK transcript | 10,531,194 | 11.2% |
| WHIR leaf hashes | 3,320,880 | 3.5% |
| WHIR closing query weights | 3,069,960 | 3.3% |
| WHIR query folds | 2,624,400 | 2.8% |
| WHIR transcript | 1,603,940 | 1.7% |
| zerocheck sumcheck | 1,227,336 | 1.3% |
| ring switch statement | 835,688 | 0.9% |
| other (9 phases) | 2,290,006 | 2.4% |
| total | 94,069,548 | 100% |

Table 10: A third of the $2^{18}$-row verifier is the ring switch closing, and the five largest phases make up 84%. Non-free gates by the verifier phase that emits them.

**Garbling efficiency.** To compare garbled verifiers across trace sizes and AIRs, we define the *garbling efficiency* of a configuration as

$$\eta = \frac{|\mathsf{GC}|}{R \cdot W} \quad \text{bytes per committed cell,}$$

where $|\mathsf{GC}|$ is the garbled circuit's size in bytes, 16 per non-free gate, $R$ the number of trace rows and $W$ the number of committed columns. It is a cost per unit of verified computation, so smaller is better. For our Keccak-$f$ AIR, $W = 1{,}625$ and each cell is one bit. Because $|\mathsf{GC}|$ grows with $\log R$ while $R \cdot W$ grows with $R$, $\eta$ falls almost in inverse proportion to the trace: from 13,715 bytes per cell at $2^5$ rows through 2,556, 186.9 and 13.32 at $2^8$, $2^{12}$ and $2^{16}$ to 3.53 at $2^{18}$ and 0.94 at $2^{20}$ (Table 3). At $2^{20}$ rows this is less than one garbled byte per committed bit: 7.5 garbled bits per bit, or 38 kB per Keccak-$f$ permutation. Comparing $\eta$ across proof systems needs the same computation and cells of the same kind.

Table 10 breaks the $2^{18}$-row verifier down by the phase that emits each gate, and Table 11 isolates the adder on the measured verifier.

**WHIR alone, and its parameters.** On a standalone instance, garbling only the WHIR opening of an 18-variable polynomial (rate 1/32, folding 4, $35 + 22 + 16$ queries) cost 24.3M non-free gates with single-root commitments, and 21.2M with a Merkle cap of 32 roots. That cap is Plonky3's recommended height and was the optimum in our sweep of 1 to 256 roots. Three quarters of the WHIR circuit was hashing. Across rates 1/16–1/64 and folding factors 2–5, rate 1/32 with folding 4 gave the smallest circuit among the configurations we kept; rate 1/64 saved a further 10% of gates at the price of a prover domain twice as large.

### C.3 Core replay and fee equivalents

The raw transport fixture of Table 4 serializes to 132,788 bytes, 133,193 WU and 33,299 vB, below the 400,000-WU standard-transaction limit [Bit26]; it uses synthetic outpoints and was not submitted to `testmempoolaccept`. The signed-envelope fixture commits the 130,128-byte payload in a 154-vB wallet-signed transaction and reveals it in a 32,850-vB script-path spend whose 130,917-byte tapscript, control block and transaction shells are included; strict Core 31.1 policy accepts the

| configuration | non-free gates |
|---|---|
| $2^5$ rows, this work | 44,573,121 |
| $2^5$ rows, original Blake3 adder | 58,997,590 (+32%) |
| $2^8$ rows, this work | 66,459,859 |
| $2^8$ rows, original Blake3 adder | 85,768,603 (+29%) |

Table 11: The one-AND adder removes about a quarter of the verifier's gates.

unconfirmed parent–child pair. The adaptor fixture serializes 133 P2TR inputs in 23 two-output transactions, the largest 399,936 WU, so its packing is specific to the measured two-output shell.

We exported all four transaction-bound fixtures to isolated Bitcoin Core 31.1 regtest nodes with non-standard transactions disabled. Core rejected each representative reveal while its funding parent was unconfirmed as `too-large-cluster`. After funding confirmation, it accepted every reveal. The adaptor fixture used a 5,841-vB funding transaction and 23 reveals totaling 2,222,213 vB, or 2,228,054 vB together, and mined in 3 blocks. WOTS translation used 38,211 vB of funding and 81 reveals totaling 7,861,144 vB, or 7,899,355 vB together, and mined in 9 blocks; a reveal with one revealed chain node altered failed its script.

Antichain used 33,836 vB of funding and 131 reveals totaling 11,848,875 vB, or 11,882,711 vB together, and mined in 12 blocks. Lamport used 45,016 vB of funding and 174 reveals totaling 17,265,635 vB, or 17,310,651 vB together, and mined in 18 blocks; 173 reveals are 99,312 vB (397,246 WU) and the tail is 84,659 vB. Core also rejected Lamport's signed 174-parent join while its reveal parents were unconfirmed. After they confirmed, it accepted and mined the 13,060-vB join, bringing that tested slice to 17,323,711 vB. This establishes staged standard-policy feasibility for these bounded signed publication slices, not peer-to-peer propagation, robust fee management, multi-leaf timeout trees or the missing challenge, Disprove, anchor and soldering graph. Adaptor, WOTS-translation and Antichain join/completion transactions remain unconstructed.

At BABE's historical scenario of 2.2 sat/vB and \$95,500 per bitcoin [GKS+26], the one-set measurements have component fee equivalents of 0.049, 0.173, 0.261 and 0.380 BTC for the adaptor, WOTS translation, Antichain and Lamport, respectively; these are neither current quotes nor fees for a complete dispute. Their serialized packings use 23, 81, 131 and 174 transactions; dividing by 100 kvB instead gives 23, 79, 119 and 173 capacity equivalents, which are not transaction counts. For the adaptor fixture, the two extra inputs of the 133-input packing remove three transaction shells and lower the reveal total by 184 vB, while creating the two extra P2TR prevouts costs about 86 vB, so that packing remains smaller before counting its three fewer completion parents. For example, 1,041,024 Lamport bits require 1,044 inputs at 998 bits per input, and the simplest one-output 400-kWU packing fits at most six full inputs, so the minimal-input, maximal-chunk layout uses 174 transactions. This is not a transaction-count lower bound: repartitioning into more, smaller inputs can fit 173 transactions, but increases the total serialized footprint. The strict Core fixture also shows that mempool policy cannot admit the 174 reveals as a single zero-confirmation graph: funding must confirm first, the independent reveals then require at least 18 blocks, and only then can the join be admitted. The tuned proof of Table 5 reduces input-proportional terms by 18.74%. A deployment must serialize and policy-test the tuned transactions and size its challenge bond to the resulting complete graph.

## C.4 Input sweep

Table 5 in §5 gives the input bits of the $2^{18}$-row verifier by proof component for the measured configuration and for the smallest configuration in the sweep. The equal-area narrow-statement models of §5, widths 128 and 32 at heights $2^{22}$ and $2^{24}$, reduce the input by 36.6% and 38.9% under the current WHIR profile and by 55.4% and 57.6% with the best swept configuration; the power-of-two rounding represents 126.03% of the original cell count, and the aggressive result inherits the quantum-search and prover-cost caveats of grinding. Recursion into a proof whose own WHIR opening is still some 0.37M bits at these parameters is the other route below the floor.

## C.5 Narrow recursion

Table 7 in §5 lists every verifier of the narrow-recursion experiment; from the third row on, each is a level-4 proof re-proved from the same level-3 tape at the Johnson rate 1/1024 and re-recorded. The tape machine can bind up to eight of a tape's first inputs as public values, enough for the binary stage's public-value digest, which commits to the zkVM program's verifying key and outputs; our runs bind none. We translate a tape gate by gate in the `binary_tape` module of `whir-gc`, and Ziren's `binary-recursion` crate records the tapes.

The steps combine recording choices with changes to the proof system. The recorder reads opened values the verifier already knows (padding and constant preprocessed columns) as constants, and reads the fixed preprocessed Merkle tree, down to 18 layers below its root, as circuit constants selected by a one-hot of the query's top index bits. The schedule folds 4, 5, 4 and 4 variables per WHIR round at 46 bits of grinding. The five protocol changes are: (i) ring-switch claims at points sharing the coordinates that one packed element absorbs send a single tensor, weighted by powers of a challenge drawn after the points, and a pair's main and preprocessed switches run as one over both packings behind a selector variable; (ii) Merkle digests are Blake3 truncated to 200 bits, which keeps collisions at $2^{100}$ work classically and $2^{66.7}$ under Brassard–Høyer–Tapp quantum collision search [BHT98]; (iii) each table sends one value per linear form of its columns that its constraints and buses read, derived from the symbolic AIR, and a sumcheck over the column index reduces them to the table's ring-switch claim, the verifier rebuilding the columns with a constant right inverse that costs only XORs; (iv) preprocessed forms are cut to those independent over the fixed trace's GF(2) column basis and the all-ones column, the rest are rebuilt by an affine inverse, and one sumcheck over the widest table's column index serves every table; and (v) bus product-GKR rounds send the round polynomial without its linear eq factor. Each change passes Plonky3's and Ziren's tests and its own tamper tests, but none has been reviewed; they are the Ziren and Plonky3 commits cited above.

Each proof meets 100 bits of composed soundness by Plonky3's assessment in the Johnson regime, with up to 46 bits of grinding per term at level 4, which halves under quantum search. Because the circuit checks only the last proof, the statement's soundness also composes over the earlier levels and over the zkVM proof itself. For the zkVM proof, Ziren reports more than 100 bits of interactive soundness per proof stage and 93.5 bits for an illustrative tree of 150 proofs in its measured Poseidon2 configuration; it gives no numerical bound for the non-interactive proof and claims no post-quantum security, because its cross-shard digest is an elliptic-curve multiset hash [DYH+26]. Proving level 4 alone took 1.8 hours on 64 cores with four GPUs grinding, and about 470 GB of memory.

At 564,552 bits, the input-publication fixtures of Table 4, with every transaction signed and every leaf executed under the stack limit, serialize to 1,205,217 vB for the 8-bit adaptor baseline (73 inputs in 13 reveal transactions), 4,263,180 vB for WOTS translation (481 inputs in 44),

| verifier (hash) | non-free gates | garbled | input bits |
|---|---|---|---|
| RISC Zero 3.0.5 (Poseidon2) | 15,640M | 233.0 GiB | 1.78M |
| RISC Zero 3.0.5 (Blake3) | 1,560M | 23.3 GiB | 1.78M |
| SP1 6.3.1 shrink (Poseidon2) | 28,200M | 420.2 GiB | 7.13M |
| SP1 6.3.1 shrink (Blake3) | 2,810M | 41.8 GiB | 7.13M |
| Stwo `49f8e037` (Blake2s) | 7,130M | 106.2 GiB | 4.37M |
| Stwo `49f8e037` (Blake3) | 7,060M | 105.2 GiB | 4.37M |
| this work, narrow recursion (Blake3) | 218.0M | 3.25 GiB | 0.56M |

Table 12: Garbled verifiers of zkVM recursion proofs, at 16 bytes per non-free gate. The first six rows are the estimates of [TF26b], counted from the verifiers' operations, at the 96–100 classical bits their configurations report; their Blake3 rows assume the internal hash replaced with field arithmetic and proof size unchanged, and their input is the proof size. The last row is measured: the verifier of the last narrow-recursion proof (Table 7, 3.49 GB), whose run binds no public values and whose proof system carries the unreviewed changes of Appendix C.5.

6,425,757 vB for Antichain $(2, 16)$ (426 inputs in 71) and 9,363,254 vB for Lamport (566 inputs in 95, plus a 7,155 vB join); Disprove is one 97 vB transaction. Plain 4-bit Winternitz, modeled from one executed input at 23.06 weight units per bit, would be about 3.26 MvB, but it cannot deliver garbled labels without a translation table, which for WOTS translation costs 1.03 GB per instance at this input. The accounting boundary is that of Table 4.

Table 12 places the measured recursion verifier beside the estimates of [TF26b] for three zkVMs' recursion proofs.

# D Security details

This appendix holds the proof-system soundness figures behind §6 and the derivation of the quantum estimates of Table 8.

**Hash-based input keys under multi-target search.** The protocol of §4 publishes input bits under one-time keys. Lamport, Antichain Winternitz and translated Winternitz keys rest on `HASH160` preimages. The familiar $2^{64}$ quantum cost for our 16-byte preimages is a single-target estimate. One Lamport key set exposes $T = 1{,}041{,}024 \approx 2^{20}$ alternative preimages, so generic multi-target search costs about $2^{128}/T \approx 2^{108}$ classically and $\sqrt{2^{128}/T} \approx 2^{54}$ quantumly. Seven independent sets lower these figures to about $2^{105.2}$ and $2^{52.6}$. Hash-chain alternatives have the same multi-target issue; Table 9 gives the widths that lift the selection itself above this bound. Even 20-byte preimages under `HASH160` are capped near 70 quantum bits for one set, rather than 80, once the target count is included. Translated Winternitz keys are further bounded by the 128-bit key chain of the translation table. Because each step of that chain is salted with the instance, the chunk and the step index, an inversion targets a single step, and its cost is $2^{128}$ classically and $2^{64}$ quantumly.

**Soundness of the proof system.** We use Plonky3's own security assessment of each configuration as the input to the classical accounting of §6. The proximity terms are in the Johnson list-decoding regime (Table 13). The quantum conversion in §6.1 additionally assumes round-by-round soundness for the sumcheck-based layers. At $2^{18}$ rows the binding term is the WHIR opening at 104.3 bits (110 bits per term, rate 1/32, folding factor 4, proof of work up to 32 bits). The other

| trace rows | $2^5$ | $2^8$ | $2^{12}$ | $2^{16}$ | $2^{18}$ | $2^{20}$ |
|---|---|---|---|---|---|---|
| composed soundness (bits) | 106.1 | 105.2 | 104.7 | 104.3 | 104.3 | 104.0 |

Table 13: Soundness stays at about 104 bits at every measured size, 103.95 at $2^{20}$ rows. The values are Plonky3's composed soundness for each configuration.

terms are constraint batching 109.0, zerocheck 114.5 and its sumcheck 113.5, bit ring switch 114.0, column batching 115.2, and commitment and transcript collisions 128 (Blake3). We write $\varepsilon_{\mathrm{STARK}}(t)$ for the composed error against an adversary making $t$ hash queries; Plonky3's report states it as bits of security, 104.3 at $2^{18}$ rows, meaning that $\varepsilon_{\mathrm{STARK}}(t) \le t \cdot 2^{-104.3}$ for a classical adversary; §6.1 gives the quantum bound.

**Fiat–Shamir against quantum adversaries.** In the quantum random-oracle model, Chiesa, Manohar and Spooner [CMS19] show that applying Fiat–Shamir with a hash to a public-coin interactive oracle proof with round-by-round soundness error $\varepsilon_{\mathrm{rbr}}$ bounds the success of a quantum adversary that makes $t$ hash queries by $O(t^2\varepsilon_{\mathrm{rbr}} + t^3/2^{\lambda})$, where $\lambda = 256$ is the digest length. A classical adversary is bounded by $O(t\,\varepsilon_{\mathrm{rbr}})$.

WHIR has round-by-round soundness [ACFY25, §5]. For the sumcheck-based layers (zerocheck, column batching, ring switch) we assume it, as is standard for sumcheck, with each of Plonky3's terms as the round error. A round with error $2^{-a}$ therefore offers about $a/2$ bits against a quantum adversary, and Grover search [Gro96] attains this generically when the bad challenges form an unstructured set. Proof-of-work grinding is generic search too: $b$ bits of grinding cost $2^b$ hashes classically and about $2^{b/2}$ quantumly.

**The proof system at our parameters.** At $2^{18}$ rows each WHIR term targets 110 bits, of which grinding supplies 26 to 32 bits (per round: 33 queries with 30 and 28 bits of grinding, 20 with 32 and 30, 15 with 29 and 32, and 12 terminal queries with 27). Both parts halve under quantum search, so each WHIR term offers about 55 bits, and the composed 104.3 bits become about 52. The algebraic terms (zerocheck 114.5, its sumcheck 113.5, ring switch 114.0, column batching 115.2, constraint batching 109.0) are Schwartz–Zippel errors over the $2^{128}$-element field and offer 54 to 58 bits. They are capped by the field: no number of queries raises them. Collisions in the 256-bit Blake3 digests cost about $2^{85}$ quantum queries [BHT98], and preimages $2^{128}$.

**The ceiling of the current configuration space.** Raising Plonky3's per-term target does not raise the quantum level. We searched the target that the proven-list-decoding profile accepts at $2^{18}$ rows. Up to 134 bits per term it keeps the queries at $33 + 20 + 15 + 12$ and raises the grinding to 51–56 bits, its ceiling; at 200 bits it refuses, needing 103 bits of grinding. Plonky3's security report fully assesses targets up to 117 bits per term, where the composed soundness is 108.6 bits, bound by constraint batching at 109.0, a field-size term no WHIR parameter moves. Grinding and the field-bound terms both halve under quantum search, so no configuration of the current proof system exceeds about 54 quantum bits. Reaching a quantum target is a change to the proof system, not to its parameters.

**The garbling.** Authenticity rests on the secrecy of $\Delta$, and $\Delta$ can be tested against a single gate. An evaluator holding the labels $a, b$ of an $\mathsf{AND}$ gate with known values $x, y$ and its ciphertext $ct$ checks a candidate $\Delta'$ by recomputing $ct$ from $a, a \oplus \Delta', b$ and $\Delta'$. A wrong candidate passes

with probability $2^{-128}$. Grover search therefore recovers $\Delta$ with about $2^{64}$ quantum evaluations of Blake3, after which every label's complement is known and the output label of the other value is free. With 128-bit labels the garbling offers about 64 bits against a quantum adversary. The same holds for a hashlock on a 128-bit output label: a preimage search over $2^{128}$ labels costs about $2^{64}$. Grover search is highly sequential, and the adversary has only the time between setup and the end of the dispute window, but we do not rely on this.

# E Parameters for a quantum target

There is no single rule that doubles every classical parameter. Fiat–Shamir and preimage-search terms need about $2\lambda_Q$ classical bits, generic collision search on an $n$-bit digest costs about $2^{n/3}$ quantum queries, and an information-theoretic cut-and-choose error must itself be at most $2^{-\lambda_Q}$. Seven changes follow.

- The WHIR terms need about $2\lambda_Q$ bits each. Since grinding also halves, the query count must carry most of it: from about 80 information-theoretic bits per term today to about 168 at $\lambda_Q = 100$, about 2.1× the queries. Plonky3's profile raises grinding instead, so this needs a query-heavy profile.

- The algebraic terms need challenges from a field of about $2^{2\lambda_Q+14}$ elements, which means one more tower level, $\mathbb{F}_{2^{256}}$, at $3^8 = 6{,}561$ AND gates per multiplication, three times today's. Repeating each algebraic check with independent challenges is an alternative at a similar cost.

- Labels of $2\lambda_Q$ bits: 256-bit labels double the ciphertext size to 32 bytes per non-free gate. The gate count is unchanged, because labels feed the garbling hash, not the circuit.

- Merkle commitments and the transcript need a hash that withstands $2^{\lambda_Q}$ quantum collision search. Generic collision search therefore calls for at least a $3\lambda_Q$-bit digest and a sufficiently wide internal state. Blake3-256 caps this component near 85 quantum bits; requesting a longer XOF output does not widen its 256-bit chaining value. A replacement hash circuit and its cost remain to be designed and measured.

- For $T$ possible input-authentication targets, 100 quantum bits require at least $200 + \lceil \log_2 T \rceil$ bits of preimage entropy under a hash wider than 160 bits: about 220 bits for one key set and 223 for seven. Byte-aligned 28-byte preimages under `SHA256` meet this generic target, but that construction and its larger witness cost remain to be designed and measured.

- Cut-and-choose needs parameters satisfying $1/\binom{N}{M} \leq 2^{-\lambda_Q}$, together with an ungrindable uniform selection of the opened instances. The setup time and kept-instance storage must be recomputed for those parameters.

- The pre-signed graph needs post-quantum transaction authorization. Bitcoin currently has no general post-quantum signature opcode. QSB gives a non-standard hash-based spend under existing consensus rules, but adapting it to the committee-authorized, timelocked graph is unstudied here.

Applying only the first three factors to the measured $2^{18}$ verifier profile gives a partial lower-bound estimate, not a 100-bit configuration measurement. Merkle paths and leaf hashes scale with the query count (2.1×), and leaves also with the element size (2×), to about 45M gates. The transcripts absorb twice the bytes, about 24M. Multiplications triple, and those that depend on the queries also

scale with them, to about 213M. The result is about 280M non-free gates, 3× today's, and about 9 GB garbled at 32 bytes per gate. It leaves Blake3-256 and its 85-bit quantum collision ceiling unchanged and excludes the replacement hash circuit, stronger cut-and-choose, input authentication and graph authorization. It is therefore not an estimate of a 100-bit end-to-end protocol.