Toward Efficient Post-Quantum Bitcoin Bridges

Stephen Duan*[1, 2], Vanhger Pham[1], Blake Hou[1], Ethan Zhu[2], and Jingping Yin[1]

[1]ZKM Team
[2]GOAT Network

Abstract

BitVM-style protocols verify succinct proofs on Bitcoin by garbling a proof verifier off-chain. What reaches the chain in a dispute is the proof itself: its bits under one-time keys, the scripts that authenticate them and the signatures that bind them to transactions. Existing designs garble elliptic-curve SNARK verifiers, which a quantum adversary breaks. Our goal is a post-quantum alternative: a hash-based STARK verifier, garbled and fed with hash-based one-time keys, with no number-theoretic assumption anywhere in the verifier; its price is a far larger proof, and this paper measures and reduces that on-chain data. We compile the complete verifier for WHIR-based STARK proofs from Ziren into a Boolean circuit using free-XOR gadgets for binary-tower arithmetic and Blake3. Our implementation uses Ziren's binary-field proof stage and narrow recursion. For the final recursive WHIR-proof verifier, our circuit-cost analysis gives 218.0M non-free gates and 564,552 input bits, corresponding to 3.49 GB of garbled tables. The transactions publishing that input with translated Winternitz keys have a total virtual size of 4.26 million virtual bytes (MvB) for one key set.

1 Introduction

Bitcoin cannot verify a succinct proof economically within current Script and policy limits, but a trust-minimized bridge needs such verification. Consider a withdrawal from a rollup: an operator has paid out a user on Bitcoin and must prove, to a Bitcoin script, that the rollup's state authorizes the payment; the proof is a STARK over the rollup's execution. Our target computation is the complete verifier for WHIR-based [ACFY25] STARK proofs from Ziren [DYH+26], which we call *WHIR proofs*. These binary-field proofs are generated by Ziren's binary stage and narrow recursion. We estimate the cost of garbling this verifier and publishing its inputs from the compiled circuit and serialized transactions.

A SNARK verifier written in Script takes hundreds of megabytes [GKS+26]. The BitVM line of work therefore verifies *optimistically*: a prover claims a result, and a challenger disputes it only if it is wrong. BitVM2 [WAA+26b] settles a dispute by checking a challenged verifier chunk on-chain, which can be expensive: a mainnet experiment put the unhappy path at over $14,000 [GKS+26]. BitVM3 moves the verifier off-chain into a *garbled circuit* [WAA+26a, Che25]. At setup the verifier circuit is garbled. At dispute time the proof is published under one-time signatures that give the evaluator the circuit's input labels, and the outcome depends on which output label the evaluation yields. For the Groth16 [Gro16] instances reported by BitVM3 and BABE, only the signed proof and a hashlock remain on-chain, for tens of dollars [GKS+26].

*Corresponding author: stephen.d@zkm.io




Figure 1: WHIR proofs of successive verification programs, followed by compilation and garbling of the final verifier. In the Ziren implementation, the initial zkVM proof is a shrink proof. Arrows in the top row denote proof generation; those in the lower row denote program transformations. Binding a program and its outputs requires carrying their public-value digest through the proof chain and binding it in the final statement; the measured runs bind no public values.

What a dispute publishes is therefore the proof: its bits under one-time keys, the scripts that check them and the signatures that bind them to the transaction. This paper is about the size of that data when the proof is a STARK, which is a thousand times larger than a Groth16 proof, and about reducing it: fewer input bits, less script per bit and fewer signature bytes per bit.

Key idea. We garble the complete verifier of the final WHIR proof in a binary-field recursion pipeline. Ziren's binary stage proves the execution of the shrink-proof verification program; narrow recursion then proves executions of the successive verification programs. We compile the final verifier into a Boolean circuit and garble it, using Plonky3's existing Wiedemann tower representation [Plo26, Wie88]. Under free-XOR [KS08] a garbled circuit pays only for non-linear gates, and in a field of characteristic two every addition is an XOR. A STARK over the binary tower field $\mathbb{F}_{2^{128}}$ with Blake3 commitments therefore costs, as a garbled circuit, its hashes and field multiplications, with additions free. Its algebraic checks rest on WHIR over $\mathbb{F}_{2^{128}}$, while Blake3 instantiates the commitments, the Fiat–Shamir transcript and the garbling hash, modeled as circular correlation robust (§6). This gives a hash-based outer verifier without an additional pairing-SNARK wrapper. We price input publication with hash-based one-time keys, and treat the adaptor-signature path as a baseline. Figure 1 distinguishes the proof stages from the verifier circuit that is garbled.

Challenges. Two problems stand between this idea and a dispute that Bitcoin can settle.

C1 *Garbling the verifier.* Compiling the complete verification program must preserve its transcript, multi-table constraints and commitment checks in a circuit of fixed shape. The recorded verifier's assertions and operand types must remain enforced on circuit inputs, and the Fiat–Shamir schedule must match the reference implementation. Merkle authentication and transcript hashing also account for substantial circuit cost.

C2 *On-chain data.* A STARK proof is about a thousand times a Groth16 proof, and in a dispute every bit of it is published under a one-time key: the selection material that reveals the bit, the script that authenticates it and the signature that binds it to the transaction. At a million

input bits, publication requires millions of virtual bytes, compared with thousands of virtual bytes for Groth16-based designs.

Contributions. We address both on-chain input cost (C2) and off-chain garbling and verification cost (C1). The binary-field verifier and garbling use hash-based assumptions; the underlying Ziren proof and the transaction layer have the separate assumptions stated above.

- **Bitcoin integration and on-chain cost (C2).** We place the verifier in a BitVM3-style dispute, state the label-selection task that publishing its input must solve, and price four one-time input schemes using signed transaction serializations for the final verifier input. We account for selection material, authentication script and transaction signature per bit and separate the measured one-key-set component from the unimplemented multi-copy soldering and transaction graph (§2.1.2, §4.2). The component measures 1.21 MvB with the 8-bit adaptor baseline and 4.26–9.36 MvB per hash-based key set for the final Ziren verifier's 564,552-bit input, against a few thousand virtual bytes for Groth16. We also serialize a hash-based construction that would match the adaptor cost under a batch opcode.

- **Circuit Input reduction (C2).** Narrow recursion over Ziren's binary stage reduces the final verifier's input to 564,552 bits on real proofs, with cumulative configurations measured. The construction combines aligned narrow layouts, fixed-data specialization, compressed linear-form openings, shared reductions and commitment-parameter tuning (§4.3, §5, Appendix B.2).

- **Circuit compilation of the recursive verifier (C1).** We translate the verifier produced by Ziren's binary stage and narrow recursion from a recorded program over $\mathbb{F}_{2^{128}}$ into a Boolean circuit with one acceptance output. The translation implements its arithmetic and hashing operations, preserves its equality and nonzero assertions, and constrains byte and selector operands. The recorded program includes the transcript, multi-table constraint verification and Boolean WHIR openings; correctness relies on Ziren's recorder (§4.1.1, §5).

- **Boolean arithmetic gadgets and Blake3 optimization (C1).** We implement Plonky3's existing Wiedemann tower arithmetic as Boolean circuits for free-XOR garbling, using recursive Karatsuba multiplication: 3^k AND gates per 2^k-bit product, with squaring and multiplication by the tower generator implemented using only XORs. We also optimize bitvm-gc's Blake3 circuit [GOA26] from 20,657 to 10,281 AND gates per compression and add tree mode for long inputs (§4.1.2).

For the post-quantum goal, §6.1 analyzes the STARK and garbling components in the quantum random-oracle model, including Grover search on the garbling offset, and distinguishes those bounds from the lower cut-and-choose level, the underlying Ziren assumptions and the non-post-quantum transaction layer. Section 5 estimates the complete WHIR-proof verifier's garbling and input-publication costs across cumulative optimizations, and compares the results with BitVM3's Groth16-based verification and the post-quantum Bitcoin-bridge cost analysis of Tiwari and Feickert [TF26b]. The circuit translator and benchmark commands are open source; Appendix B.1 documents the availability limits of the historical recursion implementation. The Blake3 circuit and a label-level evaluator are contributed to GOAT's bitvm-gc [GOA26].

2 Related work

We group prior work by how it verifies a proof on Bitcoin: by garbling a verifier, by witness encryption, or through small pairing-based SNARKs that both approaches rely on. We also discuss locally refutable verification and the garbling techniques we use.

BitVM. BitVMX [LAM+24] located a disputed step of a general CPU's trace (RISC-V or MIPS) by an n-ary search over a hash chain of the trace. ColliderVM [KLN25] left the optimistic model: it placed the computation on-chain in validity form and passed state between transactions through hash-collision puzzles, without fraud proofs, at a script length its authors estimate as nearly practical for STARK verification. Delbrag [Rub25] proposed replacing BitVM's fraud proof by the off-chain evaluation of a garbled circuit whose outcome is revealed as a secret, proving the circuit's correctness in zero knowledge. BitVM3 took up that idea and garbled the verifier [WAA+26a, Che25], defining BitVM3-CORE as a sound and complete on-chain proof system with on-chain costs of about $9.

Garbled verifiers. The Boolean-garbled Groth16 verifier [Bit25] has about 3×10^9 non-free gates and a 42 GiB garbled artifact [GKS+26]. Garbling Groth16 with native elliptic-curve group operations reduced the garbled program to 2.4 MiB [KFLT26]. Glock [Eag25] formalized garbled locks and garbled a designated-verifier variant of Pari; BABE reported its garbled circuit at about 12 MB on a binary elliptic curve [GKS+26]. GOAT's bitvm-gc [GOA26] garbles Groth16 and a designated-verifier form of Pari [DMS24] over BN254 and over the binary curve sect233k1.

We garble Ziren's final recursive verifier with bitvm-gc, and we contribute our Blake3 circuit back to it. BitVM3's comparison of garbling schemes already listed a Yao-style garbled STARK verifier, at about 10 GB of off-chain storage and as an estimate [WAA+26a, Table 9]; our compiled gate count gives 3.49 GB per instance for the final WHIR-proof verifier from Ziren. TRAPGC-DV [FBF+26] verified Groth16 by designated evaluation: the prover wraps its proof in an outer Groth16 proof under a per-session trapdoor SRS and garbles a small circuit that checks it in scalar form, with cut-and-choose and a universal-composability analysis. It too rests on pairings.

Garbling on Bitcoin Futoransky, Larotonda and Barbara [FLB25] broke the authenticity of the RSA-based garbling proposed for BitVM3 and of linear adaptors: coprime public exponents let the evaluator forge labels by extended Euclid, and linear adaptors fall to the Franklin–Reiter related-message attack. Our hash-based garbling has no such label algebra. Mosaic [KTA+26] made cut-and-choose maliciously secure with an on-chain footprint independent of the number of garbled copies, and Antichain Winternitz [TF26a] published input labels on-chain at a cost up to 52.9% lower than Lamport signatures. Both are independent of the garbled circuit; §4.2 prices both for our final verifier input.

Post-quantum Bitcoin bridges. Tiwari and Feickert [TF26b] analyze the post-quantum cost of garbled-circuit Bitcoin bridges, including the proof verifier and the on-chain encoding of its input labels. Their estimates identify a tradeoff: hash-based STARK verification can reduce the garbled artifact relative to a pairing-based verifier, while the larger proof increases on-chain publication costs. We compare against a representative STARK configuration from their analysis in Table 6. Our implementation addresses both costs by compiling the complete WHIR-proof verifier from Ziren and reducing the proof input consumed by that circuit. QSB [Lev26] constructed a hash-based, non-standard authorization path under existing consensus rules, mined on mainnet in August

2026 [Sta26]; a pre-signed, timelocked dispute graph is not yet within its reach.

Direct hash-based verification. Bitcoin Wildlife Sanctuary's Circle-STARK verifier [Bit24] implements field arithmetic, FRI, Merkle paths and the Fiat–Shamir transcript in Bitcoin Script, using `OP_CAT` with `OP_SHA256` for hashing. StarkWare reports a Fibonacci-related proof verified on an `OP_CAT`-enabled Signet [Sta24]. This provides an implemented alternative for hash-based proof verification. Its on-chain Script execution and opcode requirement differ from our off-chain garbling and input-publication approach. The reported demonstration does not provide costs for the same final Ziren verifier, so we compare the architectures without assigning it a numerical cost advantage. The STARK verification uses hash-based assumptions; the covenant and transaction-authorization mechanisms must be assessed separately for post-quantum security.

Locally refutable verification. FlatChecks [Ler26] publishes a proof first and supplies the verifier's intermediate trace on challenge; the dispute checks a named local condition. This offers a different way to distribute verification across Bitcoin transactions. Our measured publication mechanism authenticates every input label needed to evaluate a complete garbled verifier. Comparing costs requires the same proof statement, challenge path and publication boundary; we do not infer a numerical advantage from the different applications reported in the two works.

Witness encryption. BABE [GKS+26] replaced the garbled Groth16 verifier with witness encryption for linear pairing relations [GKPW24], making the one quadratic pairing linear with a small garbled circuit built from decomposable randomized encodings on Argo MAC [EL26]: a 22 MiB artifact per instance, on-chain cost comparable to BitVM3 [GKS+26]. Deferred binding [Pha26] extended it to public inputs known only at dispute time with two further garbled circuits, at 0.92 GiB per finalized instance, 768 input labels, an Assert of 2,154 bytes and a 14,312-byte ChallengeAssert witness. Bitcoin PIPEs v2 [ACG+26] witness-encrypted a Schnorr signing key under an NP statement to emulate covenants without a soft fork, with arithmetic affine determinant programs [SRG+26, BIJ+20] whose ciphertexts are cubic in the constraint count, about 338 TB for a 14,371-constraint pairing-SNARK verifier, under a heuristic security analysis. All witness-encryption designs are smaller off-chain than a garbled verifier, but all need a pairing SNARK, so a STARK would first be wrapped in one, and none is post-quantum.

Binary-field proof systems and garbling. Binius [DP25] built succinct arguments over binary towers, and ring switching [DP26] turned a claim about a polynomial's bits into one about its packed form; Plonky3's Boolean WHIR commitment [Plo26], which we garble, uses both with WHIR [ACFY25] as the proximity test, and its cheap additions are what make a garbled verifier small. We use privacy-free garbling [FNO15] with free-XOR [KS08], one ciphertext per AND gate [ZRE15, §6] and the syntax of Bellare, Hoang and Rogaway [BHR12b]; free-XOR rests on circular correlation robustness [CKKZ12]. Witness encryption in general goes back to Garg, Gentry, Sahai and Waters [GGSW13].

2.1 BitVM3-style verification

In BitVM3 [WAA+26a], the operator acts as the garbler and a challenger as the evaluator. At setup, the operator garbles a proof-verification circuit. At dispute time, the operator publishes the proof under one-time keys that reveal the selected input labels. Any party holding the garbled circuit and these labels can evaluate the verifier off-chain. An invalid proof yields a reject-output

label that unlocks an on-chain hashlock and prevents reimbursement. The proof is public, so the garbling needs authenticity rather than privacy: the evaluator may know the wire values but must not derive the label for an incorrect output. Cut-and-choose checks the garbler's construction; BABE [GKS+26], Mosaic [KTA+26] and bitvm-gc [GOA26] use this approach. Our construction follows this division between off-chain verification and on-chain input publication and refutation.

2.1.1 Dispute graphs

We describe transaction dependencies and execution conditions using the UTXO transaction model [WAA+26b, §2.2 and Appendix B.2].

Definition 1 (Dispute graph)**.** *A dispute graph is $\mathcal{G} = (V, E, \perp)$, where V is a finite set of transaction skeletons. A skeleton $T = (I_T, O_T)$ specifies the set I_T of input outpoints and the indexed collection O_T of outputs, each with a value and locking predicate. An edge $(T, i, T') \in E$ means that T' consumes output i of T; these dependencies are acyclic. For distinct transactions, $T \perp T'$ means $I_T \cap I_{T'} \neq \varnothing$. Let U_0 be the initial set of unspent outpoints. An execution of n transactions is a sequence $(T_k, \omega_k, h_k)_{k=0}^{n-1}$, where $T_k \in V$, ω_k is its witness and h_k its confirmation height. Let U_k denote the set of unspent outpoints after the first k transactions. The execution is valid if, for every $0 \leq k < n$,*

$$U_k \xrightarrow{T_k, \omega_k, h_k} U_{k+1} = (U_k \setminus I_{T_k}) \cup \mathrm{Out}(T_k),$$
$$I_{T_k} \subseteq U_k, \qquad \mathsf{Valid}(T_k, \omega_k, h_k; H_k) = 1.$$

Here H_k is the confirmed history before step k, $\mathrm{Out}(T)$ is the set of newly created outpoints, and Valid *includes value conservation with fees, witness checks, authorization and absolute or relative timelocks. Initial funding outputs may be created by transactions outside V.*

This definition distinguishes a dependency graph from an execution: a transaction with several parents requires all its inputs, and independent publication branches may execute in either order. Conflicting transactions cannot both occur in one valid history. A timeout is a lower bound on the height at which a competing spend becomes valid; it does not itself cancel another branch. Cancellation requires consuming an input needed by that branch. Covenant emulation must additionally prevent unauthorized spends of the protected outputs; graph notation alone does not enforce that property.

Refutation predicate. The refutation witness is a reject-output label from a kept garbled verifier. Let ℓ_0^j denote the reject-output label of kept instance j, and let $h_j = \mathrm{SHA256}(\ell_0^j)$ be its committed hash. For a candidate label ℓ, the refutation condition is

$$\mathsf{Reject}_j(\ell) := \mathbf{1}\{\mathrm{SHA256}(\ell) = h_j\}.$$

Here $\mathbf{1}\{\cdot\}$ is 1 when its condition holds and 0 otherwise. Circuit authenticity and cut-and-choose relate this hashlock witness to an invalid verifier input (§6); the transaction graph controls how its disclosure prevents reimbursement.

Dispute transitions. Figure 2 shows the dispute graph. Let h_K, h_C and h_A denote the confirmation heights of Kickoff, Challenge and completed input publication. Let Δ_C, Δ_A and Δ_D be the challenge, input-publication and refutation delays, respectively, measured in blocks from these

transition	required guard and effect
Kickoff → Take1	$h \geq h_K + \Delta_C$ and the challenge connector remains unspent; reimburse the operator.
Kickoff → Challenge	Spend the challenge connector and supply the challenge bond; disable Take1.
Challenge → completed Assert	Publish all authenticated chunks so that $\mathsf{Complete}(x) = 1$, and create the completion output while its required inputs remain unspent.
Challenge → AssertTimeout	$h \geq h_C + \Delta_A$ and a connector needed for completion remains unspent; penalize the operator and disable completion.
completed Assert → Disprove$_j$	Supply ℓ with $\mathsf{Reject}_j(\ell) = 1$ and consume a connector required by Take2; prevent reimbursement.
completed Assert → Take2	$h \geq h_A + \Delta_D$ and every required refutation connector remains unspent; reimburse the operator.

Table 1: Transition guards and effects for the garbled-verifier dispute. The publication subgraph must enforce completion before either terminal branch.




Figure 2: Dispute graph. The dashed Assert$_1$, . . . ,Assert$_k$ node groups the input-publication transactions.

three heights. For an encoded verifier input x partitioned into k chunks $x^{(1)}, \ldots, x^{(k)}$ of fixed layout, define

$$\mathsf{Complete}(x) := \bigwedge_{i=1}^{k} \mathsf{Auth}_i(x^{(i)}),$$

where Auth_i requires publication and authentication of the prescribed chunk and its binding to the same dispute instance. The chunks must cover every input wire. Table 1 specifies the required transition guards. The conditions on unspent connectors encode conflicts, rather than asking Script to prove the absence of a transaction.

The challenge and refutation windows provide time for a competing spend to confirm; after a timelock matures, unresolved branches may race for the same input. Safety and progress therefore also require ledger-confirmation and honest-monitoring assumptions. The publication fanout or chain, its completion and timeout connectors, and fee-management transactions remain to be instantiated. Our fixtures in §5 measure publication components; they do not establish that the complete graph realizes these transition guards.

2.1.2 Setup and dispute

Measurement scope. We use *total on-chain footprint* to mean the sum of the virtual transaction sizes, in virtual bytes (vB), of every transaction in the dispute graph, including ordinary transaction signatures, authentication signatures or preimages, witness framing, revealed tapscripts, control

blocks, transaction inputs and outputs, anchors, timeouts and fee-management transactions. A transaction's virtual size is its weight divided by four, rounded up to an integer [LLW15]; it differs from the transaction's serialized size in bytes. We measure the input-publication component of that footprint: bounded funding–reveal publication slices for all four schemes, and a signed join for Lamport. The challenge, timeout, Disprove, anchor and fee-management branches, the hash-based soldering across the kept garblings and the binding of public values are not constructed, so the figures are components of that footprint and conditional projections.

Setup. Let C be the proof-verification circuit with one acceptance output, N the total number of garbled instances and M the number retained for evaluation, with $1 \leq M < N$. The operator garbles N instances of C from independent seeds and commits, for every instance j, the hash of its garbled tables, $h_j = \mathrm{SHA256}(\ell_0^j)$ for the label of output value 0 (reject), and the hashes of its one-time keys and label translations. A challenger chooses $N - M$ instances to open, re-garbles each from its seed and checks every commitment; only then is the transaction graph signed, by a committee as in BitVM2 [WAA$^+$26b], whose enforcement requires at least one honest signer to delete its signing key after setup.

Publishing bit b of input i must give a challenger only the label of value b on wire i in every kept instance; Mosaic provides this correlation for its adaptor-signature path [KTA$^+$26], and the hash-based soldering is open here.

Section 2.1.1 formalizes the dispute graph and its transition guards. Its Assert node represents the input-publication subgraph.

Intended dispute. The operator's Kickoff claims a reimbursement; a challenger may spend its challenge output within Δ_C, after which the operator must publish every authenticated input bit through Assert or lose its stake on timeout. A challenger then reads the published bits, derives the input labels of every kept instance and evaluates each off-chain, one Blake3 call per non-free gate. An invalid proof yields ℓ_0^j from a correctly garbled instance, which opens $\mathrm{Disprove}_j$. The circuit size affects off-chain evaluation, while the proof size controls the Assert payload. The historical Ziren recursion measurements bind no external public values, so binding the withdrawal and rollup-state commitment into the AIR relation and transcript, which a bridge needs, is unimplemented and outside the reported figures. What Assert publishes is the verifier's input, so the quantities to reduce are its bit count, which the circuit fixes, and the script and signature bytes that each bit costs, which the publication scheme fixes. Section 4 develops these cost reductions.

3 Setting

3.1 Garbled verifiers on Bitcoin

Let C be the agreed proof-verification circuit with one output wire. The operator garbles C, and a challenger evaluates it on the labels of the published input x. We use *privacy-free* garbling: the evaluator may learn every wire's value. The required property is *authenticity*: given the labels of x, the evaluator obtains the label for $C(x)$ but cannot derive the label for $1 - C(x)$. The reject-output label is the witness for the hashlock defined in §2.1.1.

3.2 The garbling scheme

We use privacy-free garbling [FNO15] with free-XOR [KS08] and one ciphertext per non-free gate, in the syntax of Bellare, Hoang and Rogaway [BHR12b].

Let Δ be a random secret 128-bit offset. Every wire w has a false label w_0, and its true label is $w_1 = w_0 \oplus \Delta$. Let $H(\ell, g) = \text{Blake3}(\ell \,\|\, g)$ truncated to 128 bits, where g is the gate's index. An XOR gate sets $c_0 = a_0 \oplus b_0$ and has no ciphertext. An AND gate $c = a \wedge b$ sets

$$c_0 = H(a_0, g), \qquad ct = H(a_1, g) \oplus H(a_0, g) \oplus b_0.$$

The evaluator recovers the output label from its two input labels, the ciphertext and one hash [ZRE15, §6]; an OR gate is symmetric. The garbled circuit is one 16-byte ciphertext per non-free gate.

Two details matter in practice. First, Δ must be secret and fresh for each garbling: with a public Δ any label yields its complement, and the output's other label is free to compute. Second, a hash modeled as circular correlation robust (§6) gives labels no algebraic structure. RSA-based garbling proposals for BitVM3 were broken exactly through such structure: label forgery by extended Euclid on coprime exponents, and by the Franklin–Reiter related-message attack [FLB25].

3.3 The target verification program

Our target computation is the complete verifier of a WHIR-based STARK proof from Ziren, abbreviated as a *WHIR proof*. This includes the AIR and cross-table checks as well as the WHIR opening proof that authenticates polynomial evaluations. In our Ziren implementation [DYH+26], the binary stage proves execution of the shrink-proof verifier over $\mathbb{F}_{2^{128}}$ using Boolean WHIR and Blake3. Subsequent narrow recursion reduces the cost of the final WHIR-proof verifier that we compile into a Boolean circuit and garble (§5). This binary-field verification backend is implemented in Plonky3 [Plo26] and uses fields in the Wiedemann tower [Wie88]

$$\mathsf{T}_0 = \mathbb{F}_2, \qquad \mathsf{T}_{k+1} = \mathsf{T}_k[X_k]/(X_k^2 + X_{k-1}X_k + 1), \qquad X_{-1} = 1,$$

up to $\mathsf{T}_7 = \mathbb{F}_{2^{128}}$. An element of T_{k+1} is stored as its low half (the coefficient of 1) and its high half (the coefficient of X_k), recursively down to bits. The trace is committed as bits: a Boolean column is packed into $\mathbb{F}_{2^{128}}$ elements, and WHIR uses Reed–Solomon proximity testing to authenticate the packed multilinear polynomial on an additive (Cantor) evaluation domain [ACFY25, Can89, LCH14]. Binary towers and ring switching come from Binius [DP25, DP26].

Verification predicate. The Boolean circuit C implements the acceptance predicate of the final WHIR proof, including its transcript and all verification constraints, and produces a single acceptance bit. We garble C for evaluation in the dispute protocol (§3.2).

The verification program for this WHIR proof comprises the following stages:

1. *Transcript reconstruction.* Absorb the preprocessed and main trace commitments and the declared public values, and derive Fiat–Shamir challenges in the prescribed order throughout verification. The algebraic intermediate representations (AIRs) specify polynomial constraints on current and next trace rows; these constraints, the table dimensions and the verifying key determine the expected proof structure.

2. *Cross-table consistency.* Verify the binary-bus product argument linking the recursion machine's tables, together with any lookup reductions required by the configured AIRs. The resulting evaluation claims must subsequently be bound to committed trace values.

3. *Constraint reduction.* Verify the shared *zerocheck* sumcheck [CBBZ23, LFKN92], which reduces the claim that AIR and bus constraints vanish on every row to a check at a common random evaluation point. Each table uses the coordinates corresponding to its trace height; any indexed lookup reduction is verified at its prescribed points.

4. *Opening reduction.* Reduce the required evaluations of main and preprocessed columns, or their linear forms, to claims on the packed trace polynomials. This includes the column-batching sumchecks and the bit ring-switch arguments over $\mathbb{F}_{2^{128}}$.

5. *Commitment verification.* Verify the Boolean WHIR openings for those claims, including the sumcheck rounds, grinding checks, STIR queries [ACFY24] that open folded codewords at random positions, Merkle authentication paths and final-polynomial checks. Main values are bound to the proof's trace commitment, and preprocessed values to the commitment fixed by the verifying key.

6. *Constraint closure.* Evaluate the AIR and bus constraints using the authenticated openings, discharge the remaining lookup claims, and check consistency with the sumcheck's terminal claim. The circuit returns acceptance only if these checks and all assertions introduced by the Boolean translation hold.

All challenges come from a Blake3 [OANWO20] sponge over bytes, and all Merkle trees use Blake3 compressions.

4 Construction and optimizations

Two quantities determine the principal costs of our garbled WHIR-proof verifier: the number of published input bits and the number of non-free gates. The former controls input authentication on Bitcoin; the latter controls garbling, evaluation and garbled-table storage. Within the BitVM3 framework of §2.1, we develop Boolean compilation and gate reductions (§4.1), input publication (§4.2), and recursion and proof reductions (§4.3). These optimizations trade prover work, circuit size and input length; we state those tradeoffs explicitly. Appendix A details the input-authentication schemes, and Appendix B.2 gives the algebraic arguments.

4.1 Boolean compilation and off-chain verification cost

The circuit sets the first quantity: it reads the proof's bits, so its input layout is the bit count that Assert publishes. Its size is also what cut-and-choose garbles and challengers store. This subsection turns the verifier of §3 into a Boolean circuit with one output wire. We first describe how the recursive verifier is recorded and compiled, then the arithmetic and hash gadgets that reduce its non-free gate count.

4.1.1 Verifier recording and circuit compilation

Ziren's binary stage proves the execution of the program that verifies a Blake3-committed shrink proof. Its verifier is recorded as a straight-line tape of operations over $\mathbb{F}_{2^{128}}$. A five-table machine, comprising ledger, arithmetic, rewiring, hash and Blake3-round tables, proves an execution of that tape. Recording and proving the resulting verifier repeats this narrow recursion; the circuit we garble is compiled from the final verifier tape. The recorder captures the multi-STARK verification program, including its transcript, AIR and bus constraints, preprocessed data and commitment openings. Recording and proof-system optimizations are developed in §4.3.

Our `binary_tape` translator implements each tape instruction with Boolean gates. Field addition and squaring use XORs; multiplication uses the tower gadget, and inversion uses an addition chain with a nonzero check. Equality and nonzero assertions become check bits. Byte conversions and selectors enforce their operand ranges, while hash instructions use the Blake3 circuit and

Merkle instructions select the order of the two child digests before hashing. Inputs are encoded according to their use as bits, bytes or 128-bit field elements. All assertion and range-check bits are conjoined into one acceptance output. The circuit shape is fixed by the recorded tape and its input types; the translation relies on the recorder to capture the reference verifier faithfully.

Streaming execution. We use bitvm-gc's streaming backend [GOA26] for the compiled verifier. A planning pass determines wire lifetimes; the streaming pass reuses storage after a wire's final use, retaining the acceptance output. This reduces the live-label memory required to execute the circuit without changing its gates or input. Planning metadata and the stored garbled tables remain separate costs. In particular, streaming does not remove the challenger's obligation to retain the kept garblings.

Why a binary field. The binary stage and narrow recursion use Boolean WHIR commitments over $\mathbb{F}_{2^{128}}$, whose addition is XOR and hence free under free-XOR. A field multiplication costs 2,187 AND gates by Karatsuba down the tower, while squaring and multiplication by the tower generator are free. The bit ring switch of Binius [DP26] reduces bit-level claims to claims on the packed $\mathbb{F}_{2^{128}}$ polynomial. The resulting opening reductions are further combined in §4.3.

Why Blake3. One hash serves three roles: the Merkle commitments and the Fiat–Shamir sponge of the proof system, and the garbling hash H of §3.2. Blake3 is an add-rotate-XOR design, so in Boolean gates its only non-free operations are the 32-bit additions, one AND per bit with the carry gadget of §4.1.2. For comparison, our Boolean implementation of a width-16 Poseidon2 permutation over KoalaBear [GKS23] uses 1,240,747 AND gates, about 120 Blake3 compressions. A prover that already commits and samples with Blake3 needs no change, and the circuit's transcript can be checked byte for byte against it. A single hash also keeps the verifier's assumptions to those of §6, Blake3 as a random oracle with circular correlation robustness, with no elliptic-curve or lattice assumption, which is what makes the verifier's own security claim post-quantum (§6.1).

4.1.2 Gadgets

Tower arithmetic. We retain Plonky3's Wiedemann tower representation [Plo26, Wie88] and translate its reference arithmetic into Boolean gates. A wire vector for an element of T_k is its bit pattern, so gadget outputs can be read back directly as field elements. Multiplication follows the existing tower algorithm recursively, using Karatsuba at each level. For $a = a_0 + a_1 X_k$ and $b = b_0 + b_1 X_k$ in T_{k+1}, with $a_0, a_1, b_0, b_1 \in \mathsf{T}_k$, define the intermediate products

$$z_0 = a_0 b_0, \quad z_2 = a_1 b_1, \quad z_1 = (a_0 + a_1)(b_0 + b_1) + z_0 + z_2, \qquad ab = (z_0 + z_2) + (z_1 + X_{k-1} z_2)\, X_k.$$

Additions are free. Multiplication by the generator X_{k-1} is a rewiring plus XORs, and squaring is linear over $\mathbb{F}_2$. The only AND gates are the base-field products, three per level, so a 2^k-bit multiplication costs 3^k AND gates: 2,187 in $\mathbb{F}_{2^{128}}$. A multiplication by a constant folds to XORs entirely.

Blake3. We start from bitvm-gc's Blake3 circuit [GOA26] and change two things. A 32-bit addition's carry is the majority

$$\mathrm{maj}(a, b, c) = c \oplus \big((a \oplus c) \wedge (b \oplus c)\big),$$

gadget	AND gates
$\mathbb{F}_{2^{128}}$ multiplication	2,187
$\mathbb{F}_{2^{128}}$ squaring, tower-generator multiplication, addition	0
Blake3 of 64 bytes (a Merkle compression)	10,281
Blake3 of 256 bytes (a leaf row of 16 elements)	41,511
Blake3 of 1,072 bytes (two chunks: a transcript flush)	186,125

Table 2: Gadget costs, checked against reference implementations of the field and the hash.

where a, b are the operand bits and c is the incoming carry. This uses one AND per bit, and the carry out of the top bit is discarded, so it is not computed. This halves a compression from 20,657 to 10,281 AND gates. We also add Blake3's tree mode (chunk chaining values on a stack, parent nodes, the root last). Tree mode supports transcript messages that exceed one 1,024-byte chunk between samples. Table 2 gives the costs. Every gadget is checked against reference implementations of the field and the hash on random inputs.

4.2 Publishing the input

Label selection. Every input mechanism we price is an instance of one two-party task. The *garbler* G (the operator, who also proves) holds the two labels ℓ_w^0, ℓ_w^1 of every input wire w of the kept garblings; the *evaluator* E (a challenger) will run the garbled verifier on the proof π. Write π_w for bit w of its fixed circuit-input encoding; instance indices are suppressed in ℓ_w^b. Publishing π on-chain must (i) *deliver* $\ell_w^{\pi_w}$ to E for every w, (ii) be *exclusive*: an evaluator given the published input labels cannot compute any $\ell_w^{1-\pi_w}$ without the garbler's secrets, since one complementary label breaks authenticity (§6), (iii) be *binding*: G publishes at most one value per wire, and the publication is also the authorization of the spending transaction, and (iv) be *public*: any observer can recover π and check the published object.

A malformed publication cannot be spent, a missing one forfeits the stake through AssertTimeout, and Disprove is reserved for the reject label. Lamport signatures [Lam79] achieve (i)–(iv) with one preimage per bit, at the cost of a per-bit script. The Schnorr adaptor baseline of BitVM3 and Mosaic [WAA+26a, KTA+26] achieves them with one signature per k-bit digit and no per-bit script; Appendix A.1 gives its protocol diagram (Figure 3). The hash-based alternative (Figure 4, Appendix A.2) replaces the signature by a pair of hash-chain openings and underlies the Antichain row and the hash-based projections of §6.1.

The adaptor uses one `CHECKSIG` per digit for both selection and transaction binding. Hash-based schemes additionally authenticate their openings with hash ladders and require a separate transaction signature. For the final verifier's 564,552-bit input, these differences give 1.21 MvB for the adaptor baseline and 4.26–9.36 MvB for the hash-based schemes (Table 5). Table 3 breaks down their costs per digit or bit. Appendix A.3 separately considers a hash-based batch-verification opcode.

One-time signature schemes. We price four one-time schemes for carrying the input bits; Appendix A.4 gives their scripts and fixtures and Table 5 their sizes. *Lamport* reveals one of two hashed 16-byte preimages per bit against a 49-byte leaf script, 998 bits per input, with a 32-byte authorization key and `OP_CHECKSIGVERIFY` prefixed to each leaf. *Antichain Winternitz* [TF26a] closes the forward-hashing gap of plain Winternitz chains at a cited marginal 11.31 vB per bit at parameters $(2, 16)$; our fixture pins the upstream implementation and adds a 64-byte Schnorr authorization. *Winternitz with a translation table* [SST+26] closes the same gap by making each

scheme	selection material	script	transaction binding	vB/bit	assumption
Schnorr adaptor, $k = 8$	one 64-byte completion per 8-bit digit	one `CHECKSIG` per digit, 3 bytes	the same signature	2.13	discrete logarithm
WOTS translation, $k = 3$	one 20-byte chain node per 3-bit digit, plus two checksum chains per chunk	hash ladder in Script, 2 bytes per step	separate 64-byte Schnorr signature per input	7.55	hash; 128-bit translation chain
Antichain $(2, 16)$, $k = 4$	two 20-byte chain nodes per 4-bit digit	hash ladder in Script, 2 bytes per step	separate 64-byte Schnorr signature per input	11.38	hash
Lamport	one 16-byte preimage per bit	49 bytes per bit	separate 64-byte Schnorr signature per input	16.59	hash

Table 3: Where the four input schemes spend their bytes. Selection material and script are per digit or per bit as stated; vB/bit is the measured one-key-set component of Table 5, including transaction shells. The adaptor's selection and binding are one object, which is why its script is three bytes per digit; the hash-based schemes pay for the ladder in Script and for a separate signature, and only their selection is hash-based.

label a Shamir secret whose threshold a signed chunk's checksum sets; our fixture uses 3-bit digits, eight per chunk. For the final Ziren input, the off-chain translation table occupies 1.03 GB per instance (Table 6).

Schnorr adaptor signatures over 8-bit digits, as in BitVM3 and Mosaic [WAA+26a, KTA+26], yield 9,323 weight units per 1,024-bit Assert shell in our fixture, which validates every completed signature under Core 31.1; the signatures rest on discrete logarithms, and this repository does not implement Mosaic's polynomial soldering. Increasing the digit width reduces the number of on-chain signatures but expands the off-chain choice table exponentially; we retain the 8-bit construction as the authenticated baseline.

Our labels are free-XOR correlated, so a hash-based preimage s cannot itself be a label: a key-derivation function (KDF) maps it to one by a translation ciphertext $\mathrm{KDF}(s) \oplus w_b$, two per input bit and instance, 18.07 MB for the final verifier's 564,552-bit input. Using one on-chain key set for all M kept instances requires a proof that the translations of opened and kept instances encode the same bit choices. BABE's zero-knowledge soldering [GKS+26] and Glock's verifiable secret sharing [Eag25] give related mechanisms at smaller input sizes; we have neither constructed nor costed one for our input, so the one-key-set hash rows of Table 5 are conditional on it. The soldering-failure probability $\varepsilon_{\mathrm{sol}}$ has no instantiated bound. Authenticating each input independently for every kept instance instead multiplies the component by M: for the final Ziren input at $M = 7$, 65.54 MvB for Lamport, 44.98 MvB for Antichain and 29.84 MvB for WOTS translation, before graph overhead and still without enforcing the same bit choice across the sets.

4.3 Reducing recursive-proof inputs and verification work

The circuit consumes only the proof values read by the final verifier tape. We reduce that input at three levels: the recursion machine's layout, the representation of its opening claims, and commitment authentication. Some changes also eliminate non-free gates; others add verification work to save published bits. Table 4 reports the cumulative measured configurations, including changes evaluated together rather than in isolated ablations. The following mechanisms apply to the Ziren recursion path.

The opening reductions connect the values used by AIR and bus checks to the committed trace. A column sumcheck [LFKN92] reduces claims about linear combinations of columns to column evaluations at random points. The bit ring switch [DP26] translates those claims into the packed-field representation authenticated by WHIR [ACFY25]. The optimizations below reduce the values and round messages carried between these steps. Each transmitted field element adds 128 circuit-input bits; processing it also incurs transcript and verification work. The final commitment openings remain necessary to authenticate the reduced claims.

4.3.1 Narrow recursion and aligned trace layouts

Recursing over the verification program. The binary stage proves execution of the complete shrink-proof verifier. Each subsequent level proves execution of the preceding verifier in the five-table machine of §4.1.1. The final garbled circuit therefore verifies a proof of a narrow machine rather than exposing the original verification program's trace width at its input. This reduces final-verifier input and gate counts by moving work into recursive proof generation. Our cost evaluation focuses on garbling and evaluating the final verifier and publishing its inputs.

Aligned table packing. A power-of-two table block placed at an offset aligned to its own size needs one ring-switch claim. An unaligned block can split into several claims, each carrying a tensor and its verification work. We align the narrow machine's power-of-two blocks and pad its preprocessed round-table width accordingly. This removes split claims before the later claim-merging step. An aligned block has a fixed address prefix and free trailing coordinates, so one restriction of the packed polynomial describes the entire block. A block crossing such an address boundary needs several restrictions, which explains the additional claims. The layout change applies to the narrow machine; it does not impose this alignment on the binary stage's arbitrary table layouts.

Narrow rewiring rows. We reduce the rewiring table's row width from 128 bytes to 64 bytes. A transpose gathers halves separately and uses arithmetic additions to join disjoint halves; the bus authenticates those halves. Fewer columns require fewer opened field values, but the extra arithmetic rows increase prover work. Thus narrowing the machine is a tradeoff between final verification cost and the size of the execution trace that recursion must prove.

4.3.2 Specializing fixed data and input encodings

Typed inputs and known values. The translator allocates one bit, eight bits or 128 bits according to a consumed input's type, while enforcing its byte and selector ranges. Unread proof values receive no input wires. The recorder also replaces known padding values and preprocessed columns constant over every row with circuit constants, after checking their values in the recording proof. Their transcript absorption and commitment-opening relations remain checked; the substitution removes input wires rather than omitting the corresponding verification constraints. Constant field multiplications then reduce to XORs.

A deep cap for fixed preprocessing. The preprocessed Merkle tree is fixed by the verifying key. We embed its nodes at a chosen depth as constants, checked against the key's cap, and select the appropriate node using a one-hot decoding of the query index. A query authenticates only the path below that node, so upper siblings are no longer circuit inputs and their hashes are no longer computed. The verifier still hashes the query-dependent leaf and lower path to a selected constant

node. Each omitted upper sibling saves one digest from the input and one path hash; the one-hot selector enforces which embedded node the query reaches. Greater depth adds selection gates: the historical final configuration uses depth 18, whose input saving comes with a small increase in total gates (Table 4). This specialization depends on the fixed preprocessing tree; proof-dependent main commitments cannot be treated as constants.

4.3.3 Opening only the linear forms used by verification

Packed operands and general linear forms. The ledger's values and arithmetic operands are read by their constraints and buses as packed field elements. We first replace each such group of column openings by its packed value. We then generalize this compression: symbolic AIR and bus expressions determine a fixed matrix L of required linear forms. Instead of transmitting the full column-evaluation vector x, the prover sends the vector $y = Lx$ of linear-form evaluations. For example, if the affected checks use two columns only through $x_0 + \gamma x_1$, for a fixed coefficient $\gamma \in \mathbb{F}_{2^{128}}$, one transmitted field element can replace the two column evaluations. The extractor must retain every additional combination read elsewhere by a constraint or bus. The verifier reconstructs a representative Ry using a fixed right inverse R on the image of L, so $LRy = y$ for $y \in \operatorname{im} L$. This preserves an affected expression precisely when it factors through L, as formalized in Lemma 1. The reconstruction uses constant field coefficients and therefore only XORs. A column sumcheck binds the transmitted forms to the committed trace; fewer transmitted values do not dispense with that authentication.

Affine relations in fixed preprocessing. For preprocessed columns, we additionally derive relations over every row of the fixed trace, including the all-ones column in the basis. Dependent forms are reconstructed from an independent subset and constants. Linearity of multilinear extension preserves these affine identities at every opening point. This removes further input values without guessing relations from a particular proof's evaluations.

One shared forms sumcheck. The forms must be checked against the committed columns. Running a separate column sumcheck for each table repeats the round messages and transcript updates. We instead batch the form claims before running one sumcheck over the widest column domain. Here a group t contains the forms of one table block at a fixed row point. Let k_t be its column-variable count, C_t the multilinear column polynomial at that row point, and $L_{t,j}$ the multilinear extension of the coefficient vector of form j. Its claimed value $y_{t,j}$ must satisfy

$$y_{t,j} = \sum_{u \in \{0,1\}^{k_t}} L_{t,j}(u) C_t(u).$$

The commitments, row points and claimed forms are absorbed before sampling $\rho \in \mathbb{F}_{2^{128}}$. Enumerate all forms with distinct consecutive exponents $e_{t,j}$ starting at zero, and define

$$Y = \sum_{t,j} \rho^{e_{t,j}} y_{t,j}, \qquad W_t(u) = \sum_j \rho^{e_{t,j}} L_{t,j}(u).$$

The combined claim is $Y = \sum_t \sum_u W_t(u) C_t(u)$. These random weights prevent a fixed collection of false form claims from cancelling except with the batching error accounted for in Lemma 2.

To share rounds across different widths, let $d_{\mathrm{col}} = \max_t k_t$ and zero-extend both W_t and C_t to $\{0,1\}^{d_{\mathrm{col}}}$. For $z \in \mathbb{F}_{2^{128}}^{d_{\mathrm{col}}}$, write z_t for its trailing k_t coordinates and define $b_t(z) = \prod_{i=1}^{d_{\mathrm{col}}-k_t}(1 - z_i)$.

The shared integrand is

$$S(z) = \sum_t b_t(z)^2 W_t(z_t) C_t(z_t), \qquad Y = \sum_{u \in \{0,1\}^{d_{\mathrm{col}}}} S(u).$$

The prefix is squared because both factors are zero-extended. On Boolean points $b_t^2 = b_t$, but the terminal point is a random field point, where the square cannot be dropped. The integrand has degree at most two in each variable, so every sumcheck round uses a quadratic polynomial.

Starting from running claim $s_0 = Y$, round i supplies a polynomial $g_i(X) = A_i + B_i X + D_i X^2$ whose Boolean sum must equal s_i. The prover sends only A_i, D_i; the verifier reconstructs $B_i = s_i - 2A_i - D_i$ to enforce $g_i(0) + g_i(1) = s_i$. After absorbing the message, it samples α_i and sets $s_{i+1} = g_i(\alpha_i)$. After d_{col} rounds, the challenges form z and the verifier checks $s_{d_{\mathrm{col}}} = S(z)$. It computes each $W_t(z_t)$ from the known coefficients and batching weights, while the prover supplies the column fold $C_t(z_t)$. Each fold becomes a ring-switch claim and is subsequently authenticated against the commitment.

For n_{grp} groups, the reduction sends $2d_{\mathrm{col}} + n_{\mathrm{grp}}$ field elements, excluding the forms themselves, instead of $2\sum_t k_t + n_{\mathrm{grp}}$ for separate sumchecks with the same round encoding. For example, 16-column and 8-column groups share four rounds instead of running four and three rounds separately. The terminal fold for each group is retained. The saving is in repeated messages and transcript work; the verifier still computes the batched terminal relation. Lemma 2 gives the conditional algebraic bound, with commitment-authentication errors accounted for separately.

4.3.4 Combining ring-switch claims and shortening bus rounds

Merged ring-switch tensors. A ring-switch tensor connects a claim on unpacked bits to their packed field representation. Several claims can repeat this tensor message even when the coordinates absorbed into each packed element are identical. In that case their tensors share one linear reading map ℓ. For tensors $T_0, \ldots, T_{m-1}$ with claimed readings $y_i = \ell(T_i)$, bind the points and readings before sampling $\mu \in \mathbb{F}_{2^{128}}$, and transmit

$$T = \sum_{i=0}^{m-1} \mu^i T_i, \qquad \ell(T) = \sum_{i=0}^{m-1} \mu^i y_i.$$

Linearity makes the second equality the randomly weighted combination of the original claims. The remaining tensor checks and sumcheck bind the merged tensor to the packing. The implementation checks the shared-coordinate condition and excludes successor views from this case, since a different reading map would invalidate this combination. Sending one tensor saves repeated tensor inputs and their verification work. The batching error and the subsequent authentication are treated in Appendix B.2.

A joint main/preprocessed ring switch. A trace has proof-dependent main columns and fixed preprocessed columns. Opening them through separate ring switches repeats the reduction transcript. We combine equal-size main and preprocessed packings, whose multilinear extensions are P_0 and P_1, respectively. For their common coordinate vector z and a new selector variable s, define

$$P(s, z) = (1 - s)P_0(z) + sP_1(z).$$

The selector s identifies which half of the combined packing is read: the original main and preprocessed claims enter at $s = 0$ and $s = 1$. One ring switch over this enlarged domain reduces

the combined claims to a terminal point, where the paired WHIR opening authenticates both P_0 and P_1 and the verifier checks their selector-weighted sum. This removes a second ring-switch transcript while adding one selector coordinate. Both commitments and both terminal openings are retained; the saving comes from sharing their algebraic reduction. This operation complements tensor merging: tensor merging combines compatible readings, while the joint switch combines the main and preprocessed packing domains.

Eq-factored bus rounds. The bus product argument reduces a claim about products to claims about their children. In a radix-four layer, the product of four multilinear child values has degree at most four in the current sumcheck variable. Multiplication by the known equality weight raises the round degree to five. We avoid transmitting the extra polynomial data contributed by that known factor. The round polynomial has the form $g(X) = e_r(X)h(X)$, with known linear factor $e_r(X) = (1-r)(1-X) + rX$ and $\deg h \leq 4$, where r is the current coordinate of the equality-polynomial challenge point. A degree-five round normally needs five transmitted field elements after using the Boolean-sum constraint. Factoring out e_r leaves a degree-four polynomial, which needs four transmitted elements once the same constraint is used. From the running claim $s = g(0)+g(1)$, the verifier reconstructs the omitted value as

$$h(1) = \frac{s - (1-r)h(0)}{r}.$$

Since $e_r(0) = 1 - r$ and $e_r(1) = r$, this reconstruction enforces the original Boolean-sum relation. The circuit requires $r \neq 0$. After absorbing the round message, it samples the next sumcheck challenge $\alpha \in \mathbb{F}_{2^{128}}$ and advances the claim to $e_r(\alpha)h(\alpha)$. Each round sends one fewer field element, at the cost of reconstruction arithmetic, including the inverse of r. This saves 128 circuit-input bits per affected round, but need not reduce the non-free gate count. The verified polynomial still has degree five; the shorter message does not lower its soundness error. Appendix B.2 gives the algebraic checks for these reductions.

4.3.5 Commitment parameters and accelerated grinding

Per-round WHIR scheduling. WHIR [ACFY25] repeatedly folds the committed polynomial, authenticates queried codeword values and reduces verification to a smaller polynomial. Its proof input includes opened leaf rows, Merkle siblings, out-of-domain (OOD) answers, sumcheck messages and the final polynomial. OOD answers bind evaluations at points outside the code's evaluation domain. Reducing one component can enlarge another, so we select folding factors, code rates and grinding budgets jointly for the recursive proof's shape.

A larger fold eliminates more variables in one stage and can remove later stages, but can also widen the row opened by each query. A lower code rate adds redundancy, which can reduce the query count required by the security assessment, while enlarging the evaluation domain and its Merkle tree. More grinding requires the prover to search for a transcript nonce, trading hash trials for fewer queries under the chosen assessment. Every removed query saves its leaf payload and authentication path; the garbled verifier also avoids the corresponding path hashes. We score the complete opening schedule, including round messages and terminal data, rather than minimizing the number of queries alone. Since polynomial arity decreases through the protocol, different folding factors can be preferable in different rounds.

The historical final configuration folds 4, 5, 4 and 4 variables with up to 46 bits of grinding. A schedule must fit the actual polynomial arity; these historical parameters are not a universal setting for other recursion traces.

Shorter Merkle digests. We reduce each Blake3 Merkle digest from 32 bytes to 25 bytes (256 bits to 200 bits). This directly reduces proof input; it does not imply a proportional reduction in hash gates. It also caps generic collision resistance at 100 classical bits and about 66.7 quantum bits [BHT98]. The historical calculator used incorrect 128-bit collision metadata. Our correction and the remaining composition obligations are stated in Appendix B.2; the historical parameter estimates are not certified security bounds.

GPU grinding. To reduce the wall-clock cost of the increased grinding budget, the prover prepares the candidate-independent Blake3 transcript state on the host and tests nonce candidates in a CUDA kernel. Every returned witness is rechecked by the CPU verifier. This accelerates the search without changing the acceptance predicate or removing its logical work. It does not address the memory cost of the enlarged proving domains.

5 Evaluation

We estimate the cost of the complete WHIR-proof verifier from Ziren's binary stage and narrow recursion using compiled circuit counts (Table 4), then account for publishing the final verifier input (Table 5). We compare its on-chain data and off-chain storage with BitVM3 and the post-quantum Bitcoin-bridge estimates of Tiwari and Feickert [TF26b] (Table 6). Appendix B gives the artifact provenance and recursion details.

We report circuit-input lengths in bits and serialized data sizes in bytes. The prefixes kB, MB and GB denote powers of 10^3; KiB, MiB and GiB denote powers of 2^{10}. Transaction costs use virtual bytes, with $1\,\mathrm{kvB} = 10^3\,\mathrm{vB}$ and $1\,\mathrm{MvB} = 10^6\,\mathrm{vB}$.

5.1 WHIR-proof verification in Ziren

Verifier cost model. We estimate garbling storage from the compiled verifier's non-free gate count at 16 bytes per gate, and derive input-publication costs from its input encoding. The target is the complete WHIR-proof verification program, including its transcript, algebraic checks and commitment openings. Following the recording and compilation procedure of §4.1.1, the binary stage's verifier has 3.37G non-free gates and 18,050,304 input bits; after three rounds of narrow recursion, with the recording and proof-system optimizations of §4.3, the verifier of the last proof has 564,552 input bits, comprising 76,104 bits from byte-valued inputs and 488,448 bits from field-valued inputs, in 218.0M non-free gates and an estimated 3.49 GB of garbled tables (Table 4). Every row of that table is the verifier compiled from a recorded execution on a real proof; the archived runs accept that proof and reject three single-input changes. For the final row, the log records agreement on all 9,831,799 intermediate values and a full streaming garbling with acceptance output 1. These checks exercise the recorded execution and selected mutations. They do not establish that the same fixed circuit accepts independently generated valid proofs, or that recording is independent of witness values. Such differential tests, including transcript, bus, opening and operand-range failures, and a public-digest-binding test are still required for the complete Ziren path. Small synthetic-tape regressions separately check zero inversion, selector and byte ranges, and Blake3 slot padding; they do not exercise Ziren's recorder or proof chain.

Independent-proof recorder regression. On the public reconstruction, with the collision metadata corrected, we generated two proofs of one small binary-machine program using different execution witnesses. Both recordings contain exactly the same 769,910 operations, including

verifier	input bits	non-free gates	garbled
binary stage (level 1)	18,050,304	3,371.4M	53.94 GB
narrow recursion, level 2	2,356,864	473.9M	7.58 GB
level 4, rate 1/1024	1,248,384	231.2M	3.70 GB
+ known opened values as constants	1,137,536	226.8M	3.63 GB
+ one tensor for claims sharing a point	1,006,464	221.7M	3.55 GB
+ 200-bit digests, first-round fold of 3	895,504	220.2M	3.52 GB
+ packed operand columns	834,832	219.2M	3.51 GB
+ linear forms, per-round folds, deep preprocessed cap	643,688	215.8M	3.45 GB
+ one ring switch per pair, eq-factored bus rounds	603,112	216.5M	3.46 GB
+ affine preprocessed forms, one shared forms sumcheck	574,952	217.8M	3.48 GB
+ preprocessed cap 18 layers deep	**564,552**	218.0M	3.49 GB

Table 4: Narrow recursion and cumulative optimizations reduce the measured verifier input. Exact counts for Ziren's binary stage and for the verifier of its narrow-recursion proofs (level 2 with 26-bit addresses, the smallest that fit the real tape); the rows from the third on use the experimental changes described in §4.3. Rows combining several changes are cumulative configurations, not isolated ablations. Input lengths and gate counts are historical measurements supported by archived logs; garbled-table sizes are derived at 16 bytes per non-free gate. The exact level-4 proof and tape are not included in the available artifact (Appendix B.1).

operands and constants, with 87,426 input field values. Each tape accepts the other proof's input vector and reproduces all 1,075,048 native intermediate values. Mutating each of the eight public-digest elements separately causes rejection. Boolean evaluation also accepts both input vectors using the first tape's operations, constants and input encoding, matching all native intermediate values for each proof. This tests the recorded program and its Boolean translation; it does not reuse a stored garbled artifact. The exporter and test commands are provided in `patches/README.md`. This checks a small binary-machine instance; it does not reproduce the final level-4 verifier configuration or establish a bound on proof-dependent recording failures.

Effect of the cumulative optimizations. Relative to the first level-4 configuration, the final configuration reduces input from 1,248,384 to 564,552 bits (54.8%), while non-free gates fall from 231.2M to 218.0M (5.7%). The smallest circuit in this sequence is the 215.8M-gate configuration with linear forms, per-round folds and a deep preprocessed cap. The subsequent configurations reduce input by another 12.3% while increasing gates by 1.0%. They therefore favor lower input-publication cost over the minimum garbled-artifact size. The grouped rows do not isolate the individual contributions of shared forms sumcheck, affine preprocessing relations, joint ring switching or eq-factored bus rounds.

The historical recursion measurements bind no public values, so the circuit attests that some zkVM proof verifies, not which program ran; binding the public-value digest would add at most 1,024 public-input bits; the associated circuit and publication overhead has not been measured. The historical parameter assessment reports at least 100 classical bits per proof, with up to 46 bits of grinding per term. Its collision metadata still charges 128 bits despite the 200-bit Merkle digests, so the estimate requires correction as well as a soundness argument for the modified protocol and the complete recursive statement (Appendix B.2). Generic quantum search halves the exponent of the grinding work. At 564,552 bits, the serializations in Table 5 have total virtual sizes of 1.21 MvB for the adaptor baseline, 4.26 MvB for WOTS translation, 6.43 MvB for Antichain and 9.36 MvB for Lamport, not replayed in Core.

input mechanism	inputs	reveal transactions	component (kvB)
Schnorr adaptor, 8-bit baseline	73	13	1,205.217
WOTS translation	481	44	4,263.180
Antichain $(2, 16)$	426	71	6,425.757
Lamport	566	95	9,363.254

Table 5: Input-publication costs for the complete Ziren narrow-recursion verifier, with 564,552 input bits and one input-key set. WOTS translation and Antichain use all-nonzero worst-case encodings. Adaptor, WOTS translation and Antichain have two outputs per reveal transaction; Lamport has one. Funding, completion, Disprove and the remaining dispute graph are excluded. Lamport's separately serialized join adds 7.155 kvB.

5.2 Publishing the final verifier input

We serialize the four input-authentication schemes for the final Ziren verifier's 564,552 input bits. Table 5 includes selection witnesses, transaction-binding signatures, authentication scripts, control blocks and reveal-transaction shells. Every selected leaf is executed under the stack limit. These serializations have not been replayed in Bitcoin Core.

WOTS translation requires a 1,033,130,160-byte off-chain table per instance. A single on-chain key set across all kept instances requires the soldering discussed in §4.2. Independent publication for seven sets multiplies the WOTS, Antichain and Lamport components to 29.84, 44.98 and 65.54 MvB, respectively; these arithmetic projections exclude the transaction graph and do not enforce cross-instance input consistency.

5.3 On-chain and off-chain cost comparison

Table 6 compares our approach with Boolean-garbled Groth16 verification in BitVM3 and the post-quantum Bitcoin-bridge analysis of Tiwari and Feickert [TF26b]. We separate transaction data and stored artifacts. Our circuit-cost estimates use the complete verifier for Ziren's final narrow-recursion proof, with the archived configuration of Table 4. The Tiwari–Feickert column uses their estimated RISC Zero configuration with Blake3 substituted for the internal hash; it is the combined-cost example in their Section 3.5, using Antichain Winternitz (ACW) for input-label revelation.

Off-chain storage. The Ziren circuit's 3.25 GiB (3.49 GB) garbled artifact is about 12.5× smaller than the 40.5 GiB Boolean Groth16 baseline. With WOTS label translation included, its stored data is 4.21 GiB per instance. The representative STARK configuration in the Tiwari–Feickert bridge analysis estimates a 23.3 GiB core artifact plus 72.7 GiB of ACW translation tables, approximately 96.0 GiB in total. Their ACW integration also requires a post-quantum proof binding the translation table to the intended labels. Its cost is outside these table sizes. The proof systems and input-label mechanisms differ, so this comparison does not isolate the effect of any individual optimization.

On-chain data. The accounted transaction subtotals in Table 6 are approximately 2.5 kvB for BitVM3 and 4,263.277 kvB for our verifier with WOTS translation, each using one input-key set. Even the 1,205.217 kvB adaptor input-publication baseline for the Ziren input remains substantially larger. Tiwari and Feickert estimate 14.9 MvB for ACW input revelation or 31.7 MvB for Lamport, excluding fixed transaction overheads. Our corresponding serialized input-publication components

Cost component	Boolean Groth16 (BitVM3) [WAA+26a, GKS+26]	PQ bridge analysis [TF26b][d]	**This work**
PQ-safe verifier assumptions[c]	No (pairings)	Yes (hash-based)	Yes (hash-based)
Verifier input bits	1,019	$\approx 1.78 \times 10^6$	564,552
On-chain data: one input-key set			
Input publication (kvB)	≈ 2.4 (Assert; adaptor)	$\approx 14{,}900$ (ACW)[d]	4,263.18 (WOTS translation)
Additional verification transactions (kvB)	0.093 (Disprove)	—	0.097 (Disprove)
Accounted transaction subtotal (kvB)[a]	≈ 2.5	—	4,263.277
Off-chain storage			
Core artifact per instance (GiB)[b]	40.5	23.3 (estimate)	3.25
Input-label translation tables (GiB)	—	72.7 (ACW)	0.96 (WOTS)
Total tables per instance (GiB)	—	≈ 96.0	4.21
Seven core artifacts (GiB; derived)	283.5	163.1 (derived)	22.74

Table 6: On-chain data and off-chain storage for Bitcoin bridge verification. Units are fixed per row; kvB is decimal and GiB is binary. A dash denotes an unreported or inapplicable component. [a]These are the named verification transactions, not complete bridge lifecycles. BitVM3 pads the proof input to 1,024 bits for its reported Assert size. Our subtotal is the virtual size of the worst-case input-publication transactions (4,263,180 vB) plus Disprove; the remaining dispute graph and cross-instance input consistency are excluded, and this Ziren-size fixture has not been replayed in Core. The adaptor alternative is 1.21 MvB for input publication (Appendix A.1). [b]Our core artifact is $218{,}022{,}788 \times 16$ bytes; adding the 1,033,130,160-byte WOTS translation table [SST+26] gives 4.21 GiB per instance, or 29.48 GiB for seven instances. The BitVM3 column uses the artifact definition reported by its sources; the compared designs use different input-key mechanisms. Storage excludes proving memory. [c]PQ-safe refers to the assumptions used by the compared proof verifier and its garbling. It excludes Bitcoin transaction authorization and is not a claim of a certified end-to-end quantum security level or a common quantum security level; concrete parameters and recursive composition are discussed in §6.1. [d]Tiwari–Feickert's Table 2 and Sections 3.3–3.5 give the modeled RISC Zero/Blake3 circuit and ACW publication costs. The latter include revelation scripts and witnesses but exclude fixed transaction overheads; no complete transaction subtotal is reported. Their input is the proof length; ours counts consumed input bits. Seven copies are an arithmetic projection for all columns.

are 4.26 MvB with WOTS translation, 6.43 MvB with Antichain and 9.36 MvB with Lamport (Table 5). Their 0.043 kvB witness contribution for a hashlock fault signal is not a complete Disprove transaction, so it is not entered in that row of Table 6. The comparison therefore identifies two distinct costs: Boolean compilation reduces the off-chain verifier artifact, while the authenticated proof input remains the dominant measured on-chain component. Section 4.3 reduces both through narrower recursion, proof-layout changes and WHIR parameter selection.

6 Security

This section states what the garbled verifier guarantees and on which assumptions. It distinguishes the recording and translation assumptions of the Ziren path, combines proof-system soundness with garbling authenticity, and then accounts for the dispute of §2.1.2.

The circuit and the verifier. For the Ziren path, the argument assumes that the recorder captures every check of the reference verifier and that the Boolean translation preserves the tape's semantics. The translator enforces the tape's equality and nonzero assertions and the ranges of byte and selector operands. The measured circuits agree with the recorded execution on valid proofs and reject the tested input mutations. These tests support implementation correctness; they do not prove the recorder's correctness for all proofs.

In the theorem below, $\varepsilon_{\text{guard}}$ denotes the completeness loss introduced by the circuit translation and additional protocol guards. The eq-factored bus guard is analyzed in Appendix B.2; a bound for the complete recorded verifier requires accounting for all guards.

Soundness of the proof system. We use $\varepsilon_{\text{STARK}}(t)$ for the composed soundness error against an adversary making t hash queries. A parameter calculator alone does not establish this bound: the reduction must include composition losses and hash-related errors. Section 6.1 gives the QROM accounting. For the Ziren path, the historical assessment reports at least 100 classical bits per binary or narrow-recursion proof, using collision metadata that requires correction for the truncated Merkle digests. The modifications in Appendix B.2 require additional soundness arguments, and the full computation also depends on every preceding proof layer and the zkVM proof. The theorem below is conditional on their composed soundness.

Authenticity of the garbling. Our scheme is privacy-free garbling [FNO15] with free-XOR [KS08] and one ciphertext per non-free gate [ZRE15, §6], with H = Blake3 and a fresh secret Δ per garbling. Free-XOR is secure when H is circular correlation robust [CKKZ12]; we assume this of Blake3, as is standard for hash-based garbling. In the BitVM setting the garbled circuit is published at setup and the proof is chosen afterwards, so authenticity must hold for inputs chosen adaptively, after the garbled circuit is seen [BHR12a]. Let ε_{GC} be the advantage of an evaluator that sees the garbled circuit, then chooses an input x, receives its labels, and outputs the label of the value $\neg C(x)$ on the output wire. We assume that our Blake3-based free-XOR garbling has adaptive authenticity in this sense, with Blake3 modeled as a random oracle; Bellare, Hoang and Rogaway give constructions proven adaptively secure [BHR12a].
The following circuit-level statement is conditional on the Blake3 circular-correlation-robustness and adaptive-authenticity assumptions stated above, and assumes that the circuit translation is faithful to its reference verifier with completeness loss at most $\varepsilon_{\text{guard}}$. It does not cover cut-and-choose, input soldering or Bitcoin transaction enforcement.

Theorem 1. *Let C be a correctly garbled verifier of a fixed configuration, and x the encoding of a proof π for a statement.*

(i) Soundness. *If the statement is false, an evaluator holding the labels of x obtains the output label of value 0, except with probability at most $\varepsilon_{\text{STARK}}(t)$, where t bounds the hash queries of the party that chose π.*

(ii) Authenticity. *If π is honestly generated, an evaluator holding the labels of x obtains the output label of value 0 with probability at most $\varepsilon_{\text{guard}} + \varepsilon_{\text{GC}}$.*

Proof sketch. (i) If $C(x) = 1$, the reference verifier accepts π by the previous paragraphs, which for a false statement happens with probability at most $\varepsilon_{\mathrm{STARK}}(t)$. Otherwise $C(x) = 0$, and correctness of the garbling yields the label of value 0. (ii) For an honest proof, the assumed completeness loss bounds $\Pr[C(x) = 0]$ by $\varepsilon_{\mathrm{guard}}$. When $C(x) = 1$, the label of value 0 is the label of $\neg C(x)$, which the evaluator obtains with probability at most $\varepsilon_{\mathrm{GC}}$. □

The theorem applies only to the relation represented by C: validity of the final recursive proof, with the preceding verification computations represented through recursion. The historical measurements bind no external public values, so they do not establish authorization of a particular bridge withdrawal. Applying the theorem to an underlying zkVM statement requires the composed soundness error of the entire proof chain.

The dispute. Let $\varepsilon_{\mathrm{cc}}$ bound the probability that every kept instance is malformed while every opened one is correct; for choosing $N - M$ of N uniformly this is $1/\binom{N}{M}$, which is 2^{-40} at $(N, M) = (181, 7)$ [GKS+26]. Let $\varepsilon_{\mathrm{sol}}$ bound a failure of the soldering, and let $\varepsilon_{\mathrm{sig}}$ bound the aggregate probability of forging any one-time or transaction-authorization signature across the entire dispute, so a reduction from a per-target bound must include the number of targets. At these parameters, cut-and-choose alone limits the intended malicious-garbler security to about 40 bits, irrespective of the higher per-proof classical soundness estimates.

Subject to an enforced transaction graph, timely confirmation and an instantiated soldering bound, Theorem 1 supports two intended properties of the dispute of §2.1.2. *A false claim is disproved:* if the operator's statement is false, an honest challenger obtains some ℓ_0^j except with probability $\varepsilon_{\mathrm{STARK}}(t) + \varepsilon_{\mathrm{cc}} + \varepsilon_{\mathrm{sol}}$, since a correctly garbled kept instance exists, its labels are those of the published proof, and Theorem 1(i) applies; an operator that publishes no proof loses its stake to AssertTimeout. *An honest operator keeps its stake:* if the proof is honest, no challenger obtains any ℓ_0^j except with probability $M(\varepsilon_{\mathrm{guard}} + \varepsilon_{\mathrm{GC}}) + \varepsilon_{\mathrm{sol}} + \varepsilon_{\mathrm{sig}}$, by Theorem 1(ii) and a union bound over the kept instances. This is conditional accounting, not a protocol theorem in a ledger model: $\varepsilon_{\mathrm{sol}}$ has no instantiated bound, and the transaction graph and ledger-timing assumptions have not been implemented or proved. BitVM3 [WAA+26a] and BABE [GKS+26] analyze their own instantiations.

6.1 Post-quantum analysis

The binary-field verifier uses hash-based commitments, a hash-based transcript and hash-based garbling. We analyze these components first, then address input publication and Bitcoin transaction authorization separately. The Ziren recursion path uses 200-bit Merkle digests; its soundness must also account for the earlier proof layers. The estimates are conditional on the stated random-oracle, round-by-round-soundness and adaptive-authenticity assumptions; they are not an end-to-end post-quantum security proof. Pairing-based verifiers (Groth16, Pari and their designated-verifier variants), the witness-encryption schemes built on them (§2) and Bitcoin's own Schnorr signatures fall to Shor's algorithm [Sho94]. Avoiding discrete-logarithm and pairing assumptions is necessary for quantum resistance here, but a hash-based verifier is not sufficient by itself: a quantum adversary still speeds up generic preimage and collision search [Gro96, BHT98]. Table 7 gives component-level estimates; Appendix C derives them. We write λ_Q for the desired quantum security level in bits.

The proof system and the garbling. For a suitable round-by-round-sound protocol, a Fiat–Shamir reduction in the quantum random-oracle model bounds success after t queries by $O(t^2\varepsilon_{\mathrm{rbr}} + t^3/2^{\lambda})$ [CMS19], where $\varepsilon_{\mathrm{rbr}}$ is the interactive protocol's round-by-round soundness error and λ is

component	basis	classical estimate	quantum scale	candidate changes for λ_Q bits
WHIR and algebraic reductions	composed soundness	–	–	instantiate the full recursive reduction
Merkle hash (200-bit digest)	generic collision search	100	≈ 66.7	$\gtrsim 3\lambda_Q$-bit digest and sufficiently wide internal state
Blake3 transcript (256-bit digest)	generic collision search	128	≈ 85.3	wider digest and internal state for higher targets
garbling (Δ, output hashlock)	Grover on 128-bit labels	128	≈ 64	$2\lambda_Q$-bit labels: 256 bits
Lamport input keys	multi-target preimage, $T = 564{,}552$ ($7T$ for seven sets)	≈ 108.9 (106.1)	≈ 54.4 (53.0)	at least 220 (222) bits of preimage entropy for 100 quantum bits under a 256-bit hash
cut-and-choose $(181, 7)$	bad kept set	40	40	increase (N, M) for the target error
adaptor keys, pre-signed graph	Shor	–	broken	post-quantum transaction authorization

Table 7: Component-level estimates for the final Ziren configuration, in bits. Dashes denote an uninstantiated composed soundness bound. Hash and garbling rows describe generic search scales; they do not certify the complete protocol. Cut-and-choose has about 40 statistical bits. Candidate parameter changes are design targets.

the hash-output length in bits for the hash modeled in the reduction. If $\varepsilon_{\mathrm{rbr}} = 2^{-a}$, the first term becomes order one near $t = 2^{a/2}$, suppressing constants. This is the scale at which that bound ceases to certify small error, not evidence of an attack at that cost. Instantiating this bound for the complete recursive verifier requires the composition analysis in Appendix B.2. Grinding is a separate generic search problem: a b-bit predicate can be satisfied in about $2^{b/2}$ quantum queries. For the garbling, an evaluator can test candidates for the 128-bit offset Δ against gate data; generic search has an approximately 2^{64} query scale. A hashlock on a 128-bit output label has the same single-target search scale.

The surrounding protocol. The protocol is not post-quantum as instantiated. Schnorr adaptor signatures, the committee's pre-signed transactions and Taproot key-path spends fall to Shor's algorithm. Hash-based input keys avoid the adaptor-signature dependency, but their one-key-set cost assumes the unimplemented soldering in §4; the seven-key-set projection is 25–54 times the adaptor payload. Bitcoin has no opcode that natively verifies a post-quantum signature. QSB gives a non-standard hash-based authorization path under existing consensus rules [Lev26, Sta26], but whether it can replace the authorization of a pre-signed, timelocked dispute graph is outside our scope. We therefore treat graph authorization as an explicit open assumption rather than a solved component. The hash-based input keys themselves are bounded by multi-target preimage search over the $T = 564{,}552$ alternative Lamport preimages, about 54.4 quantum bits for one key set and 53.0 for seven (Table 7, Appendix C).

7 Future Work

Our circuit compilation and proof-input reductions lower the estimated cost of garbling the complete WHIR-proof verifier from Ziren. Input authentication remains the dominant accounted on-chain

component. Extending these results to a post-quantum Bitcoin bridge requires completing the protocol integration and reducing both authenticated data and retained off-chain artifacts.

Complete bridge integration. The recursion machine already supports public-value binding. The next step is to instantiate and evaluate this binding throughout the proof chain for the program, rollup state and withdrawal claim, and connect the final statement to the bridge's transaction graph. The input layer must ensure that one published input selects consistent labels across all kept garblings. This requires implementing and checking the hash-based soldering mechanism, together with the publication, challenge, timeout and Disprove paths, and testing the complete graph under Bitcoin Core policy. Post-quantum transaction authorization must also support the graph's pre-signing and timelock requirements. As discussed in §6, the current security argument is conditional on recording correctness and the component assumptions. Completing the composed soundness analysis for the modified recursive proof configuration and selecting consistent security parameters across the proof system, garbling, input authentication and cut-and-choose are necessary to assess the resulting bridge. The circuit and publication costs should then be recomputed for that configuration.

Reducing authenticated input. Segmented verification could commit once to the proof, locate a faulty verifier segment through a dispute and authenticate only the inputs needed for that segment. For the recursive verifier, this requires specifying shared inputs, authenticating segment boundaries and preserving the transcript dependencies across segments. The resulting cost must include the commitments and transactions needed to identify and refute a faulty segment. FlatChecks [Ler26] provides a related approach to locally refutable verification; adapting it requires defining local checks and their authenticated dependencies for this verifier. A separate direction is compact label delivery. TinyLabels [DLL24] offers online communication of $|x| + \mathrm{poly}(\lambda_{\mathrm{sec}})$ bits under Ring-LWE, where x is the input and λ_{sec} is its security parameter. This introduces a lattice assumption alongside the hash-based verification path. Its use in a bridge would require publicly checkable selection material and an on-chain refutation mechanism for malformed delivery.

Reducing off-chain setup and storage. The garbled verifier and its label-translation tables must be generated, checked against a malicious garbler and retained across the dispute window. Streaming reduces live-label memory, while retained garblings and translation tables remain substantial costs. Further work should reduce these artifacts and the replication required by cut-and-choose without weakening input consistency or authenticity. Native-group garbling [KFLT26] and witness encryption [GKS+26] achieve compact artifacts for elliptic-curve-based verification. They provide comparison points for storage, but wrapping a STARK in their SNARKs would introduce elliptic-curve assumptions into the verification path. The open question is how to approach those storage costs while preserving hash-based verification. Comparisons should account for setup work, all retained garblings and translation tables, and verification work at matched security targets.

References

[ACFY24] Gal Arnon, Alessandro Chiesa, Giacomo Fenzi, and Eylon Yogev. STIR: Reed–Solomon proximity testing with fewer queries. In *Advances in Cryptology – CRYPTO 2024, Part X*, volume 14929 of *LNCS*, pages 380–413. Springer, 2024. Full version: Cryptology ePrint Archive, Paper 2024/390. https://doi.org/10.1007/978-3-031-68403-6_12.

[ACFY25] Gal Arnon, Alessandro Chiesa, Giacomo Fenzi, and Eylon Yogev. WHIR: Reed–Solomon proximity testing with super-fast verification. In *Advances in Cryptology – EUROCRYPT 2025, Part IV*, volume 15604 of *LNCS*, pages 214–243. Springer, 2025. Cryptology ePrint Archive, Paper 2024/1586. https://doi.org/10.1007/978-3-031-91134-7_8.

[ACG+26] Michel Abdalla, Brent Carmer, Muhammed El Gebali, Handan Kilinc-Alper, Mikhail Komarov, Yaroslav Rebenko, Lev Soukhanov, Erkan Tairi, Elena Tatuzova, and Patrick Towa. Bitcoin PIPEs v2. Cryptology ePrint Archive, Paper 2026/186, 2026. https://eprint.iacr.org/2026/186.

[BHD24] Hunter Beast, Ethan Heilman, and Isabel Foxen Duke. BIP 360: Pay-to-Merkle-Root (P2MR). Bitcoin Improvement Proposal, 2024. Draft, accessed 12 November 2026. https://github.com/bitcoin/bips/blob/master/bip-0360.mediawiki.

[BHR12a] Mihir Bellare, Viet Tung Hoang, and Phillip Rogaway. Adaptively secure garbling with applications to one-time programs and secure outsourcing. In *Advances in Cryptology – ASIACRYPT 2012*, volume 7658 of *LNCS*, pages 134–153. Springer, 2012. https://doi.org/10.1007/978-3-642-34961-4_10.

[BHR12b] Mihir Bellare, Viet Tung Hoang, and Phillip Rogaway. Foundations of garbled circuits. In *Proceedings of the 2012 ACM Conference on Computer and Communications Security*, pages 784–796. ACM, 2012. https://doi.org/10.1145/2382196.2382279.

[BHT98] Gilles Brassard, Peter Høyer, and Alain Tapp. Quantum cryptanalysis of hash and claw-free functions. In *LATIN 1998: Theoretical Informatics*, volume 1380 of *LNCS*, pages 163–169. Springer, 1998. https://doi.org/10.1007/BFb0054319.

[BIJ+20] James Bartusek, Yuval Ishai, Aayush Jain, Fermi Ma, Amit Sahai, and Mark Zhandry. Affine determinant programs: A framework for obfuscation and witness encryption. In *11th Innovations in Theoretical Computer Science Conference (ITCS 2020)*, volume 151 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 82:1–82:39. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, 2020. https://doi.org/10.4230/LIPIcs.ITCS.2020.82.

[Bit24] Bitcoin Wildlife Sanctuary contributors. Circle STARK Verifier in Bitcoin Script. GitHub repository, 2024. https://github.com/Bitcoin-Wildlife-Sanctuary/bitcoin-circle-stark.

[Bit25] BitVM. Garbled SNARK verifier. Source code, commit 5a2cd4dc6cb19e37adb1b3ab94414e01d1e8b338, 2025. https://github.com/BitVM/garbled-snark-verifier/tree/5a2cd4dc6cb19e37adb1b3ab94414e01d1e8b338.

[Can89] David G. Cantor. On arithmetical algorithms over finite fields. *Journal of Combinatorial Theory, Series A*, 50(2):285–300, 1989. https://doi.org/10.1016/0097-3165(89)90020-4.

[CBBZ23] Binyi Chen, Benedikt Bünz, Dan Boneh, and Zhenfei Zhang. HyperPlonk: Plonk with linear-time prover and high-degree custom gates. In *Advances in Cryptology – EUROCRYPT 2023, Part II*, volume 14005 of *LNCS*, pages 499–530. Springer, 2023. Full version: Cryptology ePrint Archive, Paper 2022/1355. https://doi.org/10.1007/978-3-031-30617-4_17.

[Che25] Weikeng Chen. SoK: BitVM with succinct on-chain cost. Cryptology ePrint Archive, Paper 2025/1253, 2025. https://eprint.iacr.org/2025/1253.

[cHK+26] conduition, Ethan Heilman, Mikhail Kudinov, Oleksandr Kurbatov, Jonas Nick, and remix7531. SHRINCS: A compact hash-based signature scheme. Draft specification, 2026. Accessed 12 November 2026. https://github.com/SHRINCS/shrincs-bip/blob/main/SHRINCS.md.

[CKKZ12] Seung Geol Choi, Jonathan Katz, Ranjit Kumaresan, and Hong-Sheng Zhou. On the security of the "free-XOR" technique. In *Theory of Cryptography Conference (TCC 2012)*, volume 7194 of *LNCS*, pages 39–53. Springer, 2012. https://doi.org/10.1007/978-3-642-28914-9_3.

[CMS19] Alessandro Chiesa, Peter Manohar, and Nicholas Spooner. Succinct arguments in the quantum random oracle model. In *Theory of Cryptography Conference (TCC 2019), Part II*, volume 11892 of *LNCS*, pages 1–29. Springer, 2019. Cryptology ePrint Archive, Paper 2019/834. https://doi.org/10.1007/978-3-030-36033-7_1.

[DLL24] Marian Dietz, Hanjun Li, and Huijia Lin. TinyLabels: How to compress garbled circuit input labels, efficiently. Cryptology ePrint Archive, Paper 2024/2048, 2024. https://eprint.iacr.org/2024/2048.

[DMS24] Michel Dellepere, Pratyush Mishra, and Alireza Shirzad. Garuda and Pari: Faster and smaller SNARKs via equifficient polynomial commitments. Cryptology ePrint Archive, Paper 2024/1245, 2024. https://eprint.iacr.org/2024/1245.

[DP25] Benjamin E. Diamond and Jim Posen. Succinct arguments over towers of binary fields. In *Advances in Cryptology – EUROCRYPT 2025, Part IV*, volume 15604 of *LNCS*, pages 93–122. Springer, 2025. Full version: Cryptology ePrint Archive, Paper 2023/1784. https://doi.org/10.1007/978-3-031-91134-7_4.

[DP26] Benjamin E. Diamond and Jim Posen. Polylogarithmic proofs for multilinears over binary towers. In *Advances in Cryptology – EUROCRYPT 2026, Part VII*, volume 16547 of *LNCS*, pages 3–32. Springer, 2026. Full version: Cryptology ePrint Archive, Paper 2024/504. https://doi.org/10.1007/978-3-032-25336-1_1.

[DYH+26] Stephen Duan, Jingping Yin, Blake Hou, Vanhger Pham, Ethan Zhu, and Ming Guo. Ziren: Succinct arguments for MIPS32 execution. Cryptology ePrint Archive, Paper 2026/2330, 2026. https://eprint.iacr.org/2026/2330.

[Eag25] Liam Eagen. Glock: Garbled locks for Bitcoin. Cryptology ePrint Archive, Paper 2025/1485, 2025. https://eprint.iacr.org/2025/1485.

[EL26] Liam Eagen and Ying Tong Lai. Argo MAC: Garbling with elliptic curve MACs. Cryptology ePrint Archive, Paper 2026/049, 2026. https://eprint.iacr.org/2026/049.

[FBF+26] Ariel Futoransky, Fadi Barbàra, Ramses Fernandez, Gabriel Larotonda, and Sergio Demian Lerner. TRAPGC-DV: Trapdoor garbled circuit designated verification of Groth16 on Bitcoin. Cryptology ePrint Archive, Paper 2026/1430, 2026. https://eprint.iacr.org/2026/1430.

[FLB25] Ariel Futoransky, Gabriel Larotonda, and Fadi Barbara. A note on the security of the BitVM3 garbling scheme. Cryptology ePrint Archive, Paper 2025/1291, 2025. https://eprint.iacr.org/2025/1291.

[FNO15] Tore Kasper Frederiksen, Jesper Buus Nielsen, and Claudio Orlandi. Privacy-free garbled circuits with applications to efficient zero-knowledge. In *Advances in Cryptology – EUROCRYPT 2015, Part II*, volume 9057 of *LNCS*, pages 191–219. Springer, 2015. https://doi.org/10.1007/978-3-662-46803-6_7.

[GGSW13] Sanjam Garg, Craig Gentry, Amit Sahai, and Brent Waters. Witness encryption and its applications. In *45th ACM STOC*, pages 467–476. ACM, 2013. https://doi.org/10.1145/2488608.2488667.

[GKPW24] Sanjam Garg, Dimitris Kolonelos, Guru-Vamsi Policharla, and Mingyuan Wang. Threshold encryption with silent setup. In *Advances in Cryptology – CRYPTO 2024, Part VII*, volume 14926 of *LNCS*, pages 352–386. Springer, 2024. https://doi.org/10.1007/978-3-031-68394-7_12.

[GKS23] Lorenzo Grassi, Dmitry Khovratovich, and Markus Schofnegger. Poseidon2: A faster version of the Poseidon hash function. Cryptology ePrint Archive, Paper 2023/323, 2023. https://eprint.iacr.org/2023/323.

[GKS+26] Sanjam Garg, Dimitris Kolonelos, Mikhail Sergeevitch, Srivatsan Sridhar, and David Tse. BABE: Verifying proofs on Bitcoin made 1000x cheaper. Cryptology ePrint Archive, Paper 2026/065, 2026. https://eprint.iacr.org/2026/065.

[GOA26] GOAT Network. bitvm-gc. GitHub repository, 2026. https://github.com/GOATNetwork/bitvm-gc.

[Gro96] Lov K. Grover. A fast quantum mechanical algorithm for database search. In *Proceedings of the 28th Annual ACM Symposium on Theory of Computing*, pages 212–219. ACM, 1996. https://doi.org/10.1145/237814.237866.

[Gro16] Jens Groth. On the size of pairing-based non-interactive arguments. In *Advances in Cryptology – EUROCRYPT 2016, Part II*, volume 9666 of *LNCS*, pages 305–326. Springer, 2016. https://doi.org/10.1007/978-3-662-49896-5_11.

[KFLT26] Nakul Khambhati, Aaron Feickert, Christian Lewe, and Mukesh Tiwari. Garbling Groth16 with native group operations. Cryptology ePrint Archive, Paper 2026/2100, 2026. https://eprint.iacr.org/2026/2100.

[KLN25] Victor I. Kolobov, Avihu M. Levy, and Moni Naor. ColliderVM: Stateful computation on Bitcoin without fraud proofs. Cryptology ePrint Archive, Paper 2025/591, 2025. https://eprint.iacr.org/2025/591.

[KS08] Vladimir Kolesnikov and Thomas Schneider. Improved garbled circuit: Free XOR gates and applications. In *Automata, Languages and Programming (ICALP 2008),*

Part II, volume 5126 of *LNCS*, pages 486–498. Springer, 2008. https://doi.org/10.1007/978-3-540-70583-3_40.

[KTA+26] Nakul Khambhati, Mukesh Tiwari, Azz, Sapin Bajracharya, Manish Bista, Liam Eagen, Christian Lewe, and Aaron Feickert. Mosaic: Practical malicious security for garbled circuits on Bitcoin. Cryptology ePrint Archive, Paper 2026/812, 2026. https://eprint.iacr.org/2026/812.

[Lam79] Leslie Lamport. Constructing digital signatures from a one way function. Technical Report CSL-98, SRI International, 1979. https://lamport.azurewebsites.net/pubs/dig-sig.pdf.

[LAM+24] Sergio Demian Lerner, Ramon Amela, Shreemoy Mishra, Martin Jonas, and Javier Álvarez Cid-Fuentes. BitVMX: A CPU for universal computation on Bitcoin. arXiv preprint arXiv:2405.06842, 2024. https://arxiv.org/abs/2405.06842.

[LCH14] Sian-Jheng Lin, Wei-Ho Chung, and Yunghsiang S. Han. Novel polynomial basis and its application to Reed–Solomon erasure codes. In *IEEE 55th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 316–325. IEEE, 2014. https://doi.org/10.1109/FOCS.2014.41.

[Ler26] Sergio Demian Lerner. Verifiable data on Bitcoin: FlatMerkle commitments, refutable proofs, and FlatChecks. Cryptology ePrint Archive, Paper 2026/2717, 2026. https://eprint.iacr.org/2026/2717.

[Lev26] Avihu Mordechai Levy. Quantum-safe Bitcoin transactions without softforks. Technical report, https://github.com/avihu28/Quantum-Safe-Bitcoin-Transactions/blob/main/paper/QSB.pdf, 2026. Source code: https://github.com/avihu28/Quantum-Safe-Bitcoin-Transactions.

[LFKN92] Carsten Lund, Lance Fortnow, Howard Karloff, and Noam Nisan. Algebraic methods for interactive proof systems. *Journal of the ACM*, 39(4):859–868, 1992. https://doi.org/10.1145/146585.146605.

[LLW15] Eric Lombrozo, Johnson Lau, and Pieter Wuille. BIP 141: Segregated witness (consensus layer). Bitcoin Improvement Proposal, 2015. https://github.com/bitcoin/bips/blob/master/bip-0141.mediawiki.

[OANWO20] Jack O'Connor, Jean-Philippe Aumasson, Samuel Neves, and Zooko Wilcox-O'Hearn. BLAKE3: One function, fast everywhere. https://github.com/BLAKE3-team/BLAKE3-specs, 2020.

[Pha26] Vanhger Pham. Deferred binding: Extending BABE for dynamic public inputs in GOAT BitVM3. GOAT Research, HackMD, 2026. Accessed 5 November 2026. Implementation: GOATNetwork/bitvm2-gc, branch `feat/goat-bitvm3`, commit `c23130a`. https://hackmd.io/@goatresearch/HkKp2g1Zfl.

[Plo26] Plonky3 contributors. Plonky3. GitHub repository, 2026. https://github.com/Plonky3/Plonky3.

[Rub25] Jeremy Rubin. Delbrag. Draft, April 2025. https://rubin.io/public/pdfs/delbrag.pdf.

[Sho94] Peter W. Shor. Algorithms for quantum computation: Discrete logarithms and factoring. In *35th Annual Symposium on Foundations of Computer Science*, pages 124–134. IEEE, 1994. https://doi.org/10.1109/SFCS.1994.365700.

[SRG+26] Lev Soukhanov, Yaroslav Rebenko, Muhammad El Gebali, Mikhail Komarov, Handan Kilinc-Alper, Michel Abdalla, and Patrick Towa. Implementable witness encryption from arithmetic affine determinant programs. Cryptology ePrint Archive, Paper 2026/175, 2026. https://eprint.iacr.org/2026/175.

[SST+26] Mikhail Sergeevitch, Konrad Staniec, David Tse, Nikhil Vanjani, and Robin Linus Woll. Non-interactive translation of Winternitz signatures to Lamport signatures via secret sharing. Cryptology ePrint Archive, Paper 2026/1684, 2026. https://eprint.iacr.org/2026/1684.

[Sta24] StarkWare. The path to general computation on bitcoin. StarkWare Research, July 2024. https://starkware.co/blog/general-computation-on-bitcoin/.

[Sta26] StarkWare. The first quantum-safe Bitcoin transaction has been mined. https://starkware.co/blog/the-first-quantum-safe-bitcoin-transaction-has-been-mined/, August 2026. Mainnet transaction: https://mempool.space/tx/305a24ffea912b9cf428f29ebf952321c96dab5bab284fc0d0801562f5abab07.

[TF26a] Mukesh Tiwari and Aaron Feickert. Antichain Winternitz: Guaranteed garbled-circuit label revelation on Bitcoin with permissionless recovery. Cryptology ePrint Archive, Paper 2026/1568, 2026. https://eprint.iacr.org/2026/1568.

[TF26b] Mukesh Tiwari and Aaron Feickert. The post-quantum cost of garbled-circuit Bitcoin bridges. Cryptology ePrint Archive, Paper 2026/2383, 2026. https://eprint.iacr.org/2026/2383.

[WAA+26a] Robin Linus Woll, Ioannis Alexopoulos, Lukas Aumayr, Zeta Avarikioti, Matteo Maffei, and David Tse. BitVM3: Efficient Bitcoin bridges via garbled circuits. Cryptology ePrint Archive, Paper 2026/933, 2026. https://eprint.iacr.org/2026/933.

[WAA+26b] Robin Linus Woll, Lukas Aumayr, Zeta Avarikioti, Matteo Maffei, Andrea Pelosi, Orfeas Stefanos Thyfronitis Litos, Christos Stefo, David Tse, and Alexei Zamyatin. Bridging Bitcoin to second layers via BitVM2. In *35th USENIX Security Symposium (USENIX Security 26)*, pages 969–988. USENIX Association, 2026. Full version: Cryptology ePrint Archive, Paper 2025/1158. https://www.usenix.org/conference/usenixsecurity26/presentation/woll.

[Wie88] Doug Wiedemann. An iterated quadratic extension of GF(2). *The Fibonacci Quarterly*, 26(4):290–295, 1988. https://www.fq.math.ca/Scanned/26-4/wiedemann.pdf.

[WNR20] Pieter Wuille, Jonas Nick, and Tim Ruffing. BIP 340: Schnorr signatures for secp256k1. Bitcoin Improvement Proposal, 2020. https://github.com/bitcoin/bips/blob/master/bip-0340.mediawiki.

[WNT20a] Pieter Wuille, Jonas Nick, and Anthony Towns. BIP 341: Taproot: SegWit version 1 spending rules. Bitcoin Improvement Proposal, 2020. https://github.com/bitcoin/bips/blob/master/bip-0341.mediawiki.

[WNT20b] Pieter Wuille, Jonas Nick, and Anthony Towns. BIP 342: Validation of Taproot scripts. Bitcoin Improvement Proposal, 2020. Defines Tapscript signature semantics and resource limits. https://github.com/bitcoin/bips/blob/master/bip-0342.mediawiki.

[ZRE15] Samee Zahur, Mike Rosulek, and David Evans. Two halves make a whole: Reducing data transfer in garbled circuits using half gates. In *Advances in Cryptology – EUROCRYPT 2015, Part II*, volume 9057 of *LNCS*, pages 220–250. Springer, 2015. https://doi.org/10.1007/978-3-662-46803-6_8.

A Bitcoin integration details

This appendix details the label-selection mechanisms summarized in §4: the Schnorr adaptor baseline, hash-based label selection, its post-quantum instantiation and the four input-publication schemes as fixtures. Section 2.1.1 gives the dispute-graph model and its transition guards.

A.1 Schnorr adaptor baseline

Figure 3 details the Schnorr adaptor label-selection baseline of BitVM3 and Mosaic [WAA+26a, KTA+26]. The same signature both authorizes the transaction and releases the secret that selects the input labels. This baseline relies on discrete logarithms and is not post-quantum.

A.2 Hash-based label selection

Figure 4 is the hash-based counterpart of Figure 3: the signature completion is replaced by a pair of hash-chain openings, the evaluator contributes nothing at setup, and the transaction binding must be added as a separate signature.

A.3 A post-quantum instantiation

A post-quantum instantiation. Figure 4 becomes a post-quantum replacement for the adaptor under three changes, none of which is available on Bitcoin today. First, the forward hashing moves out of Script into a native batch verifier: one leaf per transaction carries the batch root ρ, the first digit index and the count, and an opcode re-derives every endpoint from the records on the stack. Second, the transaction-binding signature becomes hash-based. We model the draft P2MR output type [BHD24] with a new 0xC2 leaf, 6,000-byte stack items and a 548-byte stateful SHRINCS signature [cHK+26] per transaction. The leaf version and stack limit are assumptions of our serialization model; 548 bytes is the minimum stateful signature size in the SHRINCS draft. Third, the node width n must match the quantum target: forging a different digit from a published opening is a second-preimage search over the roughly 2^{22} chain nodes that the whole input makes public, so $n = 16$ gives about 53 quantum bits, $n = 24$ about 85 and $n = 32$ about 117.

We serialized this construction exactly with rust-bitcoin for $n = 16$ and $n = 24$ at $k = 4$, including the P2MR outputs, 0xC2 leaves, placeholder signatures, depth-one control blocks and canonical multi-record stack items, and tested the pair code and the batch parser against tampering, reordering, cross-batch splicing and padding; nothing in it is executable by Bitcoin Core. Table 8 gives the results together with a projection whose model reproduces both serialized fixtures within 0.03%. The operative row is $n = 32$, $k = 8$: full-width nodes, about 117 quantum bits for the selection, and about 2.13 MvB against the Schnorr adaptor's 2.23 MvB, at the price of 255 hash steps per byte inside the opcode, about 3.3×10^7 compressions for the input. Its setup is two seeds




Figure 3: Schnorr adaptor label selection for one k-bit digit position i, as in BitVM3 and Mosaic [WAA+26a, KTA+26]. m_i is the BIP341 [WNT20a] message seen by the i-th CHECKSIG; wire (i, j) is bit j of the digit. Here G is the group generator, q its order, $t_{i,v}$ is the secret adaptor scalar for candidate v, and v_j is bit j of v. The notation $\mathrm{x}(P)$ denotes a point's x-coordinate. X has even y as in BIP340 [WNR20], $\sigma_v \in \{-1, 1\}$ makes R'_v have even y, and $e_v = H_{\mathrm{BIP340}}(\mathrm{x}(R'_v) \,\|\, \mathrm{x}(X) \,\|\, m_i)$. For each fixed i we suppress i on $R'_v, s'_v, \sigma_v, e_v$. Every pre-signature uses a fresh independent nonce, including across candidate values, digit positions and sessions; a zero nonce sum or duplicate candidate $\mathrm{x}(R'_v)$ is resampled. The candidate nonce list is made public at setup. Everything above the dispute line is off-chain and repeated for every digit and every candidate value. In the final step, u indexes the kept garbled instance that rejects.

per digit rather than the adaptor's 2^k secrets, so widening k does not grow the choice table; only the translation table grows, to $2^k \cdot k \cdot 16$ bytes per digit, 4.3 GB per instance at $k = 8$. The delivery and soldering of that table across the M kept garblings is the same open item as for every other row.




Figure 4: Hash-based label selection for one k-bit digit position i with n-byte chain nodes. The selection material is two nodes instead of one signature, the evaluator contributes nothing at setup, and the transaction binding that the adaptor gets from the same signature must be added separately. Verification is a hash ladder, in Script today or in a batch opcode under the soft fork of Table 8. In this figure, H denotes the domain-separated chain hash, with A and B distinguishing the two chains; the digit index i is suppressed on A_j, B_j. The value v_j is bit j of candidate digit v, while u indexes the kept garbled instance that rejects.

selection	consensus	n	k	vB/bit	component	selection security, quantum
Schnorr adaptor (Fig. 3)	current	–	8	2.14	2.23 MvB	broken (Shor)
WOTS translation [SST+26] in Script	current	20	3	7.59	7.90 MvB	≈ 64 bits (translation-key chain; nodes ≈ 70)
Antichain $(2, 16)$ in Script	current	20	4	11.41	11.88 MvB	≈ 69 bits
batched selector, one record per item	P2MR, 0xC2, batch opcode	16	4	2.05	2.13 MvB	≈ 53 bits
batched selector, 11-record items	same	16	4	2.04	2.12 MvB	≈ 53 bits
batched selector, 5-record items	same	24	4	3.05	3.17 MvB	≈ 85 bits
batched selector, projected	same	32	8	≈ 2.05	≈ 2.13 MvB	≈ 117 bits

Table 8: Hash-based label selection against the adaptor baseline for the 1,041,024-bit input, funding plus reveals. The first three rows are the independent Core-tested publication fixtures at this payload size. The batched-selector rows are exact rust-bitcoin serializations of a construction that requires the draft P2MR output, a hash-based transaction signature and a hypothetical batch verification opcode; the last row is a model projection. The security column is the multi-target second-preimage cost of the chain nodes alone (the 20-byte Antichain nodes expose roughly 2^{23} chain targets at this payload size), except for WOTS translation, whose 128-bit key chain gives the lower bound; the composed protocol remains bound by the proof system (§6.1).

A.4 The four input schemes

The four one-time schemes of Table 5 trade on-chain size against assumptions. The totals in this subsection use the final WHIR verifier's 564,552-bit input.

- *Lamport.* Each bit has two hashed 16-byte preimages, and the revealed preimage is the one-time-signature witness. The leaf script per bit,

  `OP_HASH160 OP_DUP` h_0 `OP_EQUAL OP_SWAP` h_1 `OP_EQUAL OP_BOOLOR OP_VERIFY`

  uses h_0, h_1 for the hashes of the two preimages. It is 49 bytes, and the witness 17 bytes. We executed it with 998 bits per input, and it rejected wrong preimages. The transaction-bound fixture prefixes each leaf with a 32-byte authorization key and `OP_CHECKSIGVERIFY`, and supplies a 64-byte `SIGHASH_DEFAULT` signature. Its initial stack has 999 items and the measured transient peak is exactly the 1,000-item Tapscript limit [WNT20b]. Its serialized size is the Lamport row of Table 5. The fixture uses a one-leaf tree with a 33-byte control block; timeout siblings and their longer control paths belong to the missing complete graph.

- *Antichain Winternitz.* Plain Winternitz chains are unsafe here: from a published chain value the evaluator hashes forward to the labels of other digit values [TF26a]. Antichain Winternitz closes this and costs a cited marginal 11.31 vB per bit at parameters $(2, 16)$, counting the hash-chain opening witness and authentication script but cancelling fixed transaction overhead. Our transaction-bound fixture pins the upstream implementation, prepends a 64-byte Schnorr authorization, and includes two pay-to-Taproot (P2TR) outputs, input shells, leaf scripts and depth-zero controls. With at most 332 four-bit digits per input, its size is the Antichain row of

Table 5, an all-nonzero worst case that zero-valued ScriptNum coordinates only reduce. The source reports 0.256 kB of off-chain table per bit. Its larger parameters save more on-chain but need up to 43.8 kB per bit off-chain [TF26a].

- *Winternitz with a translation table.* The translation gadget of [SST+26] also closes the gap of plain Winternitz: each label is a Shamir secret whose threshold is set by the chunk's checksum and the bit value, so a signed chunk opens exactly the labels of its bits. In the source, one such Winternitz signature over 508 bits, its Assert, is 3,748 vB, or 7.38 vB per bit. Our transaction-bound fixture uses 3-bit digits, eight per chunk, with the checksum split over two chains, and the authorization, outputs and controls of the Antichain fixture. With at most 49 chunks per input, its size is the WOTS row of Table 5, again an all-nonzero worst case. The price is the off-chain table, 1,033,130,160 bytes per instance at this input size. The challenger must decode digits as consensus does and, at setup, reject keys in which one chain end lies within seven hashes of another; neither check costs on-chain space.

- *Schnorr adaptor signatures* over 8-bit digits, as in BitVM3 and Mosaic. BitVM3 reports 9,707 weight units (WU) for a 1,024-bit Assert transaction with one input and two P2TR outputs [WAA+26a], or 2.37 vB per bit at that size. Its printed witness formula instead sums to 9,451 WU once the SegWit marker and flag are included, while the merged 64-byte-`SIGHASH_DEFAULT` implementation implies 9,323 WU for that shell. Our executable fixture reproduces 9,323 WU, uses the BIP342 opcode index rather than a byte offset for every code separator, and reaches the exact 998-signature stack capacity. Core 31.1 validates all completed signatures. The final-input serialization uses 70,569 eight-bit digits; its size is the adaptor row of Table 5. Mosaic's source construction solders all kept instances to one set of signatures by polynomial label correlation, with an on-chain footprint independent of the number of instances [KTA+26]. This repository tests only the one-key-set transaction fixture; it does not implement or test Mosaic's polynomial correlation or setup verification. The signatures rest on discrete logarithms, and an evaluator that holds the signing key can spend without completing the adaptor [TF26a].

B Additional measurements

B.1 Artifact availability

Artifact availability. The source repository includes the locked dependencies and benchmark commands; the commands and memory caps are listed in `whir-gc/README.md`. The measurement logs and helper sources are included in `paper/data/`, together with a SHA-256 manifest and a README mapping tables and figures to logs. The level-2 row of Table 4 was measured at Ziren `f6137ecc` with 26-bit address and permutation identifiers. The later optimized measurements are associated with Ziren `9398469a` on the unpublished `whir-gc/narrow-verifier-input` branch, with subsequent experimental patches. Although the branch reference is no longer available, its base commit survives in the local Git object database, including the dumper test and 64-byte rewiring rows. Cumulative patches preserved at this repository's revision `8359bb0` apply cleanly to that base and to Plonky3 `fb5d0d89`. The script `patches/reconstruct_historical.py` reconstructs those trees and emits a file-checksum manifest. The archival notes associate these patches with the measurements; no original final-tree hash is available to confirm that association independently. The public reconstruction uses Ziren `80af2779` on `feat/binary-whir-blake3` and Plonky3 `be1c6f92` on ProjectZKM's `zkm/binary-whir`. It has a rewritten dumper and lacks the original rewiring-row

implementation, so rebuilding from these public commits does not reproduce the reported level-4 counts exactly. The available archive contains the final gate-count, value-check, mutation and streaming-garbling log, but no checksummed level-4 proof/tape pair from that run. Consequently, these logs support auditing the reported observations, not independently replaying the exact circuit. Reproduction requires either recovery of that pair and its recorder/configuration manifest, or a new measurement on the public reconstruction with separately reported counts. `patches/README.md` documents the reconstruction and commands. Gate, wire and input counts are deterministic.

B.2 Narrow recursion

Table 4 in §5 lists every verifier of the narrow-recursion cost analysis; from the third row on, each is a level-4 proof re-proved from the same level-3 tape at the Johnson rate 1/1024 and re-recorded. The tape machine can bind up to eight of a tape's first inputs as public values, enough for the binary stage's public-value digest, which commits to the zkVM program's verifying key and outputs; our runs bind none. We translate a tape gate by gate in the `binary_tape` module of `whir-gc`, and Ziren's `binary-recursion` crate records the tapes.

Section 4.3 describes the layout, recording, opening and commitment optimizations used in these configurations. Here we give their algebraic conditions and the remaining security obligations. The archived tests exercise honest and tampered inputs; they do not prove soundness. Appendix B.1 documents the public reconstruction and its differences from the measurement version.

Algebraic reductions and their scope. Write $q = |\mathbb{F}_{2^{128}}|$. The following arguments concern the interactive algebraic reductions, conditional on fixed statement shapes, correctly derived linear forms and fresh uniform challenges after the preceding messages are fixed. They do not establish round-by-round soundness of the complete composition or its Fiat–Shamir transform. When a commitment admits several candidate traces, the error must also account for that candidate set.

Merged tensors and the joint switch. When the absorbed coordinates agree, all claims use the same linear map ℓ from a ring-switch tensor to its claimed value. For m tensors T_i and claimed readings y_i, with $0 \le i < m$, sample μ uniformly from $\mathbb{F}_{2^{128}}$ after fixing the readings. The merged tensor is $T = \sum_{i=0}^{m-1} \mu^i T_i$, and the verifier checks $\ell(T) = \sum_i \mu^i y_i$. For any fixed nonzero discrepancy vector, $\sum_i \mu^i(\ell(T_i) - y_i)$ has degree at most $m-1$, giving error at most $(m-1)/q$. The subsequent tensor checks and sumcheck must still bind T to the packing; their errors are additional. The implementation checks equality of the absorbed coordinates and disallows successor views in the merged case. Its outer opening transcript binds the claimed forms and column folds before the ring switch draws μ; the ring-switch transcript then binds T before drawing its tensor-batching point. The standalone ring-switch routine relies on that prior binding of readings.

The joint switch concatenates two equal-size packed tables. If their multilinear extensions are P_0 and P_1, its polynomial is $P(s, z) = (1 - s)P_0(z) + sP_1(z)$. Original claims are embedded at $s = 0$ or $s = 1$. At the terminal point (s^*, z^*), the verifier authenticates both $P_0(z^*)$ and $P_1(z^*)$ through the paired WHIR opening and checks their selector-weighted sum against the ring-switch value. This is an exact identity; security still includes the ring-switch error at the enlarged arity and the paired opening's error.

Lemma 1 (Linear-form reconstruction)**.** *Let L be a fixed matrix and R a right inverse on its image. Suppose each constraint and bus expression affected by the substitution factors as $P(x, u) = \widehat{P}(Lx, u)$, with u denoting the unchanged operands. Then replacing x by $R(Lx)$ preserves all those*

expressions. Affine identities among forms of a fixed preprocessed trace also hold at every multilinear evaluation point if they hold at every row of that trace.

Proof. The first claim follows from $LR(Lx) = Lx$. For the second, multilinear extension is linear, and the extension of the all-ones column is the constant polynomial 1. Thus, for vectors f, g of preprocessed forms, a fixed coefficient matrix A and a constant vector c, an identity $f = Ag + c$ on the Boolean row domain extends to $f(r) = Ag(r) + c$ at every row evaluation point r. □

The implementation derives the forms from symbolic constraints and bus expressions, and checks the right-inverse identities. For preprocessed forms, the affine relations are derived from the fixed trace. This lemma explains the substitution; validating the symbolic extractor and binding the transmitted forms to committed columns remain implementation obligations.

Lemma 2 (Shared forms sumcheck)**.** *Suppose m_{form} claimed forms, their row points and the relevant commitments are fixed before a uniform challenge $\rho \in \mathbb{F}_{2^{128}}$. Let d_{col} be the largest column-variable count, and assume the commitments admit at most K candidate collections of column evaluations before ρ. A degree-two sumcheck over the zero-extended column tables reduces these claims to authenticated column folds with algebraic error at most $K(m_{\mathrm{form}} - 1 + 2d_{\mathrm{col}})/q$, in addition to the error of authenticating those folds.*

Proof. For a fixed candidate collection, let δ_j be claimed form j minus its candidate evaluation. A false vector of forms gives a nonzero polynomial $\sum_{j=0}^{m_{\mathrm{form}}-1} \rho^j \delta_j$, which vanishes with probability at most $(m_{\mathrm{form}} - 1)/q$. Otherwise the initial weighted claim is false. Each round checks a polynomial of degree at most two, so the usual sumcheck induction adds at most $2d_{\mathrm{col}}/q$ before a false terminal claim remains. Union-bounding over the K candidate collections gives the stated term. □

For a table t with k_t column variables and a terminal point $z \in \mathbb{F}_{2^{128}}^{d_{\mathrm{col}}}$, let $b_t(z) = \prod_{i=1}^{d_{\mathrm{col}}-k_t}(1 - z_i)$ and let z_t be the trailing k_t coordinates of z. Zero extension multiplies both its column polynomial C_t at the fixed row point and its batched form-weight polynomial W_t by b_t. Writing S for the combined sumcheck integrand, the terminal check must be

$$S(z) = \sum_t b_t(z)^2 W_t(z_t) C_t(z_t).$$

The implementation uses this squared prefix factor, binds every table's forms before drawing ρ, and absorbs each round's two coefficients before sampling its coordinate. Each $C_t(z_t)$ then becomes a ring-switch claim. A concrete assessment must charge the total number m_{form} of forms and the applicable candidate multiplicity; the previous column-batching term cannot be reused solely because the transcript is shorter.

Eq-factored bus rounds. A radix-four product layer still uses one-variable Boolean sumcheck rounds. Its degree-five round polynomial is $g(X) = e_r(X)h(X)$, where $e_r(X) = (1-r)(1-X)+rX$ and $\deg h \le 4$; r is the current coordinate of the equality-polynomial challenge point. Given running claim $s = g(0) + g(1)$ and next sumcheck challenge $\alpha \in \mathbb{F}_{2^{128}}$, the verifier reconstructs the omitted value as

$$h(1) = \frac{s - (1 - r)h(0)}{r}, \qquad s' = e_r(\alpha)h(\alpha).$$

Here s' is the updated claim. For $r \neq 0$, this enforces $g(0) + g(1) = s$ exactly. The round message is absorbed before α is sampled, so the degree-five sumcheck argument still applies; omitting a transmitted value does not itself reduce that error bound. The implementation rejects $r = 0$, introducing a completeness loss of at most n_{guard}/q for n_{guard} such coordinates under uniform challenges. This guard contributes to the recursion path's completeness loss.

Collision accounting and composition. Both the reconstructed historical source and the public reconstruction use 25-byte Merkle digests but return 128 from `collision_resistance_bits`. That metadata is inconsistent with the digest width: generic collision work is about 2^{100} classically and $2^{200/3}$ quantumly. The accompanying correction derives the metadata from the digest width in both native and traced configurations. This affects the security report, not the historical gate counts. Accordingly, the previously reported 100-bit per-proof calculator estimates must be recomputed with the corrected cap and the new reduction terms; they are not certified bounds for the modified protocol. The full analysis must also instantiate the candidate-set charges, tensor and paired-opening reductions, round-by-round soundness, hash errors and the recursive composition. Because the circuit checks only the last proof, the statement's soundness also composes over the earlier levels and over the zkVM proof itself. For the zkVM proof, Ziren reports more than 100 bits of interactive soundness per proof stage and 93.5 bits for an illustrative tree of 150 proofs in the Poseidon2 configuration evaluated in that paper [DYH+26]. These figures concern that configuration's interactive soundness.

At 564,552 bits, the input-publication fixtures of Table 5, with every transaction signed and every leaf executed under the stack limit, have total virtual sizes of 1,205,217 vB for the 8-bit adaptor baseline (73 inputs in 13 reveal transactions), 4,263,180 vB for WOTS translation (481 inputs in 44), 6,425,757 vB for Antichain $(2, 16)$ (426 inputs in 71) and 9,363,254 vB for Lamport (566 inputs in 95, plus a 7,155 vB join); Disprove is one 97 vB transaction. Plain 4-bit Winternitz, modeled from one executed input at 23.06 weight units per bit, would be about 3.26 MvB, but it cannot deliver garbled labels without a translation table, which for WOTS translation costs 1.03 GB per instance at this input. The accounting boundary is that of Table 5.

C Security details

This appendix derives the component-level estimates in Table 7 and explains the QROM accounting used in §6. The recursive proof's algebraic and composition obligations appear in Appendix B.2.

Hash-based input keys under multi-target search. The protocol of §2.1.2 publishes input bits under one-time keys. Lamport, Antichain Winternitz and translated Winternitz keys rest on `HASH160` preimages. The familiar 2^{64} quantum cost for our 16-byte preimages is a single-target estimate. One Lamport key set exposes $T = 564{,}552$ alternative preimages for the final verifier input, so generic multi-target search costs about $2^{128}/T \approx 2^{108.9}$ classically and $\sqrt{2^{128}/T} \approx 2^{54.4}$ quantumly. Seven independent sets lower these figures to about $2^{106.1}$ and $2^{53.0}$. Hash-chain alternatives have the same multi-target issue; Table 8 gives the widths that lift the selection itself above this bound. Even 20-byte preimages under `HASH160` are capped near 70 quantum bits for one set, rather than 80, once the target count is included. Translated Winternitz keys are further bounded by the 128-bit key chain of the translation table. Because each step of that chain is salted with the instance, the chunk and the step index, an inversion targets a single step, and its cost is 2^{128} classically and 2^{64} quantumly.

Fiat–Shamir against quantum adversaries. Chiesa, Manohar and Spooner [CMS19] give a QROM Fiat–Shamir reduction for suitable public-coin interactive oracle proofs with round-by-round soundness. In the form used here its error is $O(t^2\varepsilon_{\mathrm{rbr}} + t^3/2^{\lambda})$, where λ is the hash-output length for the random oracle modeled in the reduction. The corresponding classical accounting includes both a term linear in $t\varepsilon_{\mathrm{rbr}}$ and hash-related errors; constants and protocol-dependent factors must be retained for a concrete bound. WHIR proves round-by-round soundness [ACFY25,

§5]. Extending this accounting to the implemented composition requires checking every algebraic layer and the transcript, not just invoking WHIR's theorem.

If a valid round-by-round bound is 2^{-a}, the expression above remains small for t sufficiently below both $2^{a/2}$ and $2^{\lambda/3}$, up to its constants. It supplies no converse: once the bound becomes uninformative, the existence of a successful attack does not follow. In particular, a Schwartz–Zippel bound is an upper bound on bad-challenge density. Grover search gives a matching attack only when a searchable set of successful challenges of the asserted density is actually available to the adversary.

The garbling. Authenticity rests on the secrecy of Δ, and Δ can be tested against a single gate. An evaluator holding the labels a, b of an AND gate with known values x, y and its ciphertext ct checks a candidate Δ' by recomputing ct from $a, a \oplus \Delta', b$ and Δ'. A wrong candidate passes with probability 2^{-128}. Grover search therefore recovers Δ with about 2^{64} quantum evaluations of Blake3, after which every label's complement is known and the output label of the other value is free. With 128-bit labels the garbling offers about 64 bits against a quantum adversary. The same holds for a hashlock on a 128-bit output label: a preimage search over 2^{128} labels costs about 2^{64}. Grover search is highly sequential, and the adversary has only the time between setup and the end of the dispute window, but we do not rely on this.