

Package ‘dst’

September 24, 2021

Type Package

Title Using the Theory of Belief Functions

Encoding UTF-8

Version 1.5.0

Date 2021-09-20

Author Claude Boivin, Stat.ASSQ <webapp.cb@gmail.com>

Maintainer Claude Boivin <webapp.cb@gmail.com>

Description Using the Theory of Belief Functions for evidence calculus. Basic probability assignments, or mass functions, can be defined on the subsets of a set of possible values and combined. A mass function can be extended to a larger frame. Marginalization, i.e. reduction to a smaller frame can also be done. These features can be combined to analyze small belief networks and take into account situations where information cannot be satisfactorily described by probability distributions.

License GPL (>= 2)

LazyData true

BugReports <https://github.com/RAPLER/dst-1/issues>

RoxygenNote 7.1.1

Depends R (>= 2.10)

Suggests testthat,
knitr,
rmarkdown,
igraph

VignetteBuilder knitr

R topics documented:

addTobca	2
ads	3
bca	4
bcaPrint	6
bcaRel	6
belplau	8
decode	9
dlfm	10
dotprod	11

doubles	12
dsrwon	13
dst	14
elim	15
encode	16
extmin	17
fw	18
inters	19
marrayToMatrix	20
matrixToMarray	20
mrf	21
mrt	22
nameCols	23
nameCols_prod	23
nameRows	24
nzdsr	25
peeling	26
plautrans	28
productSpace	29
reduction	30
shape	31
swr	31
tabresul	32

Index 34

addTobca	<i>Add some elements of 0 mass to an existing basic chance assignment.</i>
----------	--

Description

Given a previously defined basic chance assignment (bca), the user may want to add some elements of the set of possible values or some subsets, even if they have zero mass value. This feature is useful, for example, to examine the measure of plausibility of these elements or subsets of zero mass value.

Usage

```
addTobca(x, tt, f)
```

Arguments

x	A basic chance assignment (see bca).
tt	A matrix constructed in a boolean style (0,1) or a boolean matrix. The number of columns of the matrix tt must match the number of columns of the tt matrix of x (see bca). Each row of the matrix identify a subset of the set of possible values.
f	Deprecated. Old name for tt matrix.

Value

x The original basic chance assignment x augmented with the added subsets defined by f.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
y <- bca(f = matrix(c(1,0,0,1,1,1),nrow=2, byrow = TRUE),
m=c(0.6, 0.4), cnames = c("a", "b", "c"), varnb=1)
addTobca(y, matrix(c(0,1,0,0,0,1, 0,1,1), nrow=3, byrow = TRUE))
x <- bca(f = matrix(c(0,1,1,1,1,0,1,1,1),nrow=3,
byrow = TRUE), m=c(0.2,0.5, 0.3),
cnames =c("a", "b", "c"), varnb=1)
xy <- dsrwon(x,y)
xy1 <- addTobca(nzdsr(xy), matrix(c(0,1,0,0,0,1), nrow=2, byrow = TRUE))
xy1
addTobca(x, f = diag(1, ncol(x$tt) ) ) # add all singletons
```

ads

*The Captain's Problem. ads: Relation between variables Arrival (A),
Departure delay (D) and Sailing delay (S)*

Description

This dataset is the tt matrix establishing the relation $A = D + S$, where $A = 0:6$, $D = 0:3$ and $S = 0:3$. All the elements (a,d,s) of $(A \times D \times S)$ where $a = d + s$ is true form a subset with a mass value of 1. To construct the tt matrix, we put the variables A, D, S side by side, as in a truth table representation.

Usage

ads

Format

An integer matrix with 18 rows and 17 columns.

[1,c(1,2)] value = 0, not used

[1,3:17] Identification numbers of the three variables. Column 3 to 9: variable 1; column 10 to 13: variable 2; column 14 to 17: variable 3.

nospec identification number of the specification

m the value of the specification, a number between 0 and 1

6 1 if 6 is part of the specification, 0 otherwise

5 1 if 5 is part of the specification, 0 otherwise

4 1 if 4 is part of the specification, 0 otherwise

3 1 if 3 is part of the specification, 0 otherwise

2 1 if 2 is part of the specification, 0 otherwise

1 1 if 1 is part of the specification, 0 otherwise

0 1 if 0 is part of the specification, 0 otherwise

Author(s)

Claude Boivin, Stat.ASSQ

Source

https://www.researchgate.net/publication/265993533_Fusion_and_Propagation_in_Graphical_Belief_Models

bca	<i>Basic chance assignment mass function</i>
-----	--

Description

Function bca is used to define subsets of a finite set Θ of possible values and to assign their corresponding mass value.

The set Θ is called the frame of discernment. Each subset A of Θ with a positive mass value is called a focal element or a proposition. The associated mass value is a number of the $(0, 1]$ interval, called "basic chance assignment" (the basic probability assignment of Shafer's book). All other subsets that have not received a positive mass value are assumed to have a mass value of zero.

Usage

```
bca(
  tt,
  m,
  cnames = NULL,
  con = NULL,
  idvar = NULL,
  infovar = NULL,
  varnames = NULL,
  valuenames = NULL,
  infofel = NULL,
  f,
  varnb,
  infovarnames
)
```

Arguments

tt	(formerly f) A (0,1)-matrix or a boolean matrix. The number of columns must match the number of elements (values) of the frame of discernment Θ . Each row is a subset of Θ . The last row is the frame Θ , represented by a vector of 1's.
m	A numeric vector of length equal to the number of rows of the matrix tt. Values of m must lie in the interval $(0, 1]$ and must add to one. The mass $m(k)$ represents the chance value allotted to the proposition represented by the row k of the matrix tt.
cnames	A character vector containing the names of the elements of the frame of discernment Θ . The length must be equal to the number of elements of Θ . The names are first searched in the valuenames parameter. If NULL, column names of the matrix tt are taken if present. Otherwise, names are generated.

con	The measure of conflict can be provided. 0 by default.
idvar	The number given to the variable. A number is necessary to correctly manage relations between variables and make computations on a graph. 0 if omitted.
infovar	A two-column matrix containing variable identification numbers and the number of elements of the variable. Generated if omitted.
varnames	The name of the variable. Generated if omitted.
valuenames	A list of the names of the variables with the name of the elements of their frame of discernment.
inforel	Not used here. Defined within function bcaRel .
f	Deprecated. Old name for tt matrix.
varnb	Deprecated. Old name for idvar.
infovarnames	Deprecated. Old name for varnames.

Value

y An object of class `bcaspec` called a `bca` for "basic chance assignment":

- `tt` The table of focal elements `tt`. Rownames of the matrix of focal elements are generated from the column names of the elements of the frame. See [nameRows](#) for details.
- `spec` A two column matrix. First column: numbers given to the subsets, 1 to `nrow(tt)`. Second column: the mass values of the subsets.
- `con` The measure of conflict.
- `infovar` The number of the variable and the size of the frame of discernment.
- `varnames` The name of the variable.
- `valuenames` A list of length 1 consisting of the name of the variable with the names of the elements of the frame of discernment (the column names of the `tt` matrix).
- `inforel` Set at 0. used in function [bcaRel](#).

Author(s)

Claude Boivin, Stat.ASSQ

References

- Shafer, G., (1976). A Mathematical Theory of Evidence. Princeton University Press, Princeton, New Jersey, p. 38: Basic probability assignment.
- Guan, J. W. and Bell, D. A., (1991). Evidence Theory and its Applications. Elsevier Science Publishing company inc., New York, N.Y., p. 29: Mass functions and belief functions

Examples

```
tt<- t(matrix(c(1,0,1,1),ncol=2))
m<- c(.9,.1)
cnames <- c("yes","no")
bca(tt, m)
bca(tt, m, cnames)
bca(tt, m, cnames, idvar = 1)
tt1<- t(matrix(c(1,0,1,1),ncol=2))
colnames(tt1)<- c("yes", "no")
m<- c(.9,.1)
```

```

bca(tt=tt1, m, idvar = 1)
x <- bca(tt=matrix(c(0,1,1,1,1,0,1,1,1),nrow=3,
byrow = TRUE), m=c(0.2,0.5, 0.3),
cnames =c("a", "b", "c"), idvar = 1)
y <- bca(tt=matrix(c(1,0,0,1,1,1),nrow=2,
byrow = TRUE), m=c(0.6,0.4),
cnames =c("a", "b", "c"),varnames = "y", idvar = 1)
vacuous <- bca(matrix(c(1,1,1), nrow=1), m=1, cnames = c("a","b","c"))

```

bcaPrint	<i>Simple printing of the tt matrix and mass values of a basic chance assignment (bca)</i>
----------	--

Description

This utility function does a simple printing of a bca

Usage

```
bcaPrint(x)
```

Arguments

x A list of class bcaspec.

Value

A table of subsets with their associated mass. Subsets are identified by row names.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```

z <- bca(tt = matrix(c(0,1,1,1,1,0,1,1,1),nrow=3,
byrow = TRUE), m=c(0.2,0.5, 0.3),
cnames =c("a", "b", "c"), varnb = 1)
bcaPrint(z)

```

bcaRel	<i>Representation of a mass function in a product space</i>
--------	---

Description

This function is used to represent a mass function which establish a relation between two or more variables in their product space.

Usage

```
bcaRel(
  tt,
  spec,
  infovar,
  varnames,
  valuenames,
  relnb = NULL,
  infovarnames,
  infovaluenames
)
```

Arguments

<code>tt</code>	A (0,1)-matrix or a boolean matrix establishing the relation between two or more variables. The matrix is constructed by placing the variables side by side, as in a truth table representation.
<code>spec</code>	A two-column matrix. First column: numbers given to the subsets. Second column: the mass values of the subsets. A subset number and its associated mass value are repeated to match the number of elements of the subset.
<code>infovar</code>	A two column matrix containing variable identification numbers and the number of elements of each variable. The identification numbers must be ordered in increasing number.
<code>varnames</code>	The names of the variables.
<code>valuenames</code>	A list of the names of the variables with the name of the elements of their frame of discernment.
<code>relnb</code>	A number given to the relation. Set at 0 if omitted.
<code>infovarnames</code>	Deprecated. Old name for <code>varnames</code> .
<code>infovaluenames</code>	Deprecated. Old name for <code>valuenames</code> .

Value

`zr` An object of class `bcaspec` called a `bca` for "basic chance assignment". This is a list containing the following components:

- `con` The measure of conflict.
- `tt` The resulting table of subsets. Rownames of the matrix of subsets are generated from the column names of the elements of the product frame. See [nameRows](#) for details.
- `spec` The resulting two-column matrix of specification numbers with associated mass values.
- `infovar` The two-column matrix of variables number and size given in the input data.
- `valuenames` A list of the names of the variables with the name of the elements of their frame of discernment.
- `inforel` A two-column matrix containing the relation number and the depth (number of variables) of the relation.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
# A logical implication rule
# A typical relation between two variables is the
# logical implication a -> b. Let us suppose
# that a stands for Rain: {yes, no} and b stands for
# Roadworks: {yes, no}. From experience,
# I am 75 % sure that there will be RoadWorks if there is no rain.

# 1. The tt table of the logical implication
ttrwf <- matrix(c(0,1,1,0,1,0,1,0,1,0,0,1,1,1,1),
  nrow=4, byrow = TRUE,
  dimnames = list(NULL, c("rWdy", "rWdn", "Ry", "Rn")))

# 2. The mass distribution
specrw <- matrix(c(1,1,1,2,0.75,0.75,0.75,0.25), ncol = 2,
  dimnames = list(NULL, c("specnb", "mass")))

# 3. Variables numbers and sizes
inforw <- matrix(c(4,5,2,2), ncol = 2,
  dimnames = list(NULL, c("varnb", "size")))
bcaRel(tt = ttrwf, spec = specrw, infovar = inforw,
  varnames = c("RdWorks", "Rain"), relnb = 6)
```

belplau

Calculation of the degrees of Belief and Plausibility of a basic chance assignment (bca).

Description

Degrees of Belief Bel and Plausibility Pl of the focal elements of a bca are computed. The ratio of the plausibility of a focal element against the plausibility of its contrary is also computed. Subsets with zero mass can be excluded from the calculations.

Usage

```
belplau(x, remove = FALSE)
```

Arguments

x	A basic chance assignment mass function (see bca).
remove	= TRUE: Exclude subsets with zero mass.

Details

The degree of belief Bel is defined by:

$$bel(A) = Sum((m(B); B \subseteq A))$$

for every subset B of A.

The degree of plausibility pl is defined by:

$$pl(A) = Sum[(m(B); B \cap A \neq \emptyset)]$$

for every subset B of the frame of discernment.

The plausibility ratio of a focal element A versus its contrary not A is defined by: $Pl(A)/(1 - Bel(A))$.

Value

A matrix of M rows by 3 columns is returned, where M is the number of focal elements:

- Column 1: the degree of belief Bel;
- Column 2: the degree of Plausibility Pl;
- Column 3: the Plausibility ratio

Author(s)

Claude Boivin, Stat.ASSQ

References

- Shafer, G., (1976). A Mathematical Theory of Evidence. Princeton University Press, Princeton, New Jersey, p. 39-43.
- Williams, P., (1990). An interpretation of Shenoy and Shafer's axioms for local computation. International Journal of Approximate Reasoning 4, pp. 225-232.

Examples

```
x <- bca(tt = matrix(c(0,1,1,1,1,0,1,1,1),nrow=3,
byrow = TRUE), m=c(0.2,0.5, 0.3),
cnames =c("a", "b", "c"), varnames = "x", varnb = 1)
belplau(x)
y <- bca(tt = matrix(c(1,0,0,1,1,1),nrow=2,
byrow = TRUE), m=c(0.6, 0.4),
cnames = c("a", "b", "c"), varnames = "y", varnb = 1)
xy <- nzdsr(dsrwon(x,y))
belplau(xy)
print("compare all elementary events")
xy1 <- addTobca(x = xy, tt = matrix(c(0,1,0,0,0,1), nrow=2, byrow = TRUE))
belplau(xy1)
```

decode

Find the value in base 10 of a number coded in another base

Description

The `aplDecode` function of the project APL in R (<https://rpubs.com/deleeuw/158476>) has been adapted to follow the standard implementation of the APL decode function.

Usage

```
decode(base, ind)
```

Arguments

base	A scalar or a numeric vector which describes the number system in which the data is coded.
ind	The value to decode represented by a numeric vector in the base system.

Details

If the base value is a number system, namely base 2, we need only to enter a scalar, which is treated to match the length of the expression to decode. If the base value is a number system, e.g. base 2, we need only to enter it as a scalar, which is then processed to match the length of the expression to decode. If `length(ind)` is less than `length(base)`, zeroes are added to the left of the vector `ind` to match the length of the two vectors. And vice-versa.

Value

A scalar representing the conversion of the coded number `ind` to its decimal representation.

Author(s)

Claude Boivin, Stat.ASSQ.

References

- Jan de Leeuw and Masanao Yajima (March 07, 2016) *APL in R (Version 009)*, Source code. <https://rpubs.com/deleeuw/158476>
- L. Gilman and A. J. Rose.(1974): *APL an Interactive Approach*, Second Edition, John Wiley, New York.
- APL 68000 Level II language manual. MicroAPL Ltd. 1990.

Examples

```
decode(c(2,2,2,2), c(1,0,1,1)) # Find the base 10 value of the base 2 number 1011.
decode(2, c(1,0,1,1)) # left argument is extended to vector c(2,2,2,2)
decode(c(365,24,60), c(2,1,57)) # transform 2 days 1 h 57 min in minutes
decode(c(365,24,60), c(1,57)) # right vector extended
decode(c(24,60), c(2,1,57)) # left vector extended
decode(1.5, c(1,2,3)) # polynomial 1*x^2 +2*x +3 evaluated at x=1.5
```

dlfm

The Captain's Problem. dlfm: Relation between variables Departure delay (D), Loading delay (L), Forecast of the weather (F), Maintenance delay (M)

Description

This dataset is the tt matrix establishing the relation between the four variables. Each event (loading = true, forecast = foul, Maintenance = true) adds one day of Departure Delay. The elements (d,l, f, m) of (D x L x F x M) satisfying the relation form a subset with a mass value of 1. To construct the tt matrix, we put the variables D,L,F,M side by side, as in a truth table representation.

Usage

dlfm

Format

An integer matrix with 10 rows and 12 columns.

[1,c(1,2)] value = 0, not used

[1,3:12] Identification numbers of the four variables. Column 3 to 6: variable 2; columns 7,8: variable 4; columns 9, 10: variable 5; columns 11,12: variable 6.

nospec identification number of the specification

m the value of the specification, a number between 0 and 1

d3 1 if d3 is part of the specification, 0 otherwise

d2 1 if d2 is part of the specification, 0 otherwise

d1 1 if d1 is part of the specification, 0 otherwise

d0 1 if d0 is part of the specification, 0 otherwise

true 1 if true is part of the specification, 0 otherwise

false 1 if false is part of the specification, 0 otherwise

foul 1 if foul is part of the specification, 0 otherwise

fair 1 if fair is part of the specification, 0 otherwise

Author(s)

Claude Boivin, Stat.ASSQ

Source

https://www.researchgate.net/publication/265993533_Fusion_and_Propagation_in_Graphical_Belief_Models

dotprod	<i>Generalized inner product of two matrices</i>
---------	--

Description

The generalized inner product of two matrices combines two operators in the same manner as the classical inner product defined for the multiplication of two matrices. The number of rows of the second matrix must be equal the number of columns of the first matrix.

Usage

dotprod(x, y, g, f)

Arguments

x	A matrix of M rows by K columns.
y	A matrix of K rows by N columns.
g	Any operator: +, -, *, /, &, , ==, <=, paste etc.
f	Any operator: +, -, *, /, &, , ==, <=, paste etc.

Value

The result of the generalized inner product is returned.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
print("Standard matrix product")
x <- y <- matrix(c(1:6), nrow = 2, byrow = TRUE)
dotprod(x, t(y), g = "+", f = "*") ## same as x %*% t(y)
print("Find some data x2 in the rows of a larger matrix y2")
x2 <- matrix(c(1,0,0,1,1,1), nrow = 2, byrow = TRUE)
y2 <- matrix(c(1,0,0,0,1,0,1,1,0,0,1,1,1,1,1),
nrow = 5, byrow = TRUE)
(1:nrow(y2)) * dotprod(x2, t(y2), g = "&", f = "==")

print("Find some names in a long list")
team_names <- matrix(c("Patrick", "Dole", "Amanda",
"Dole", "Robert", "Calvin", "Alvina", "Klein",
"Robert", "Garipey", "Nellie", "Arcand"),
ncol = 2, byrow = TRUE)
colnames(team_names) <- c("First_name", "Last_name")
print("Where in the list are the person with first name Robert and where are the Doles?")
BobandDoles <- matrix(c("Robert", "", "", "Dole"),
ncol = 2, byrow = TRUE)
dotprod(team_names, t(BobandDoles), g="|", f=="") * (1:nrow(team_names))
```

doubles

Remove duplicate rows in a two-dimensional table

Description

Remove duplicate rows in a two-dimensional table

Usage

```
doubles(x)
```

Arguments

x A matrix of numeric, character or logical type.

Value

The submitted matrix with duplicated rows removed from.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
td0<-matrix(c(rep(c(1,0,1),times=3),0,0,1,1,1,1, 1,1,1),ncol=3,byrow=TRUE)
(doubles(td0))
td1<-matrix(c(rep(c(1,0,1),times=3),0,0,1,1,1,1),ncol=3,byrow=TRUE)
(doubles(td1))
td2<-matrix(c(1:3, 1:3,4:6,1:3),nrow=4,byrow=TRUE)
(doubles(td2))
td3<-matrix(c("d","e","f", rep(c("a","b","cc"),times=3),"g","h","i"),nrow=5,byrow=TRUE)
(doubles(td3))
td4<-matrix(as.logical(td1),nrow=5,byrow=TRUE)
(doubles(td4))
```

dsrwon

Combination of two mass functions

Description

The unnormalized Dempster's rule is used to combine two mass functions m_x and m_y defined on the same frame of discernment and described by their respective basic chance assignments x and y . Dempster's rule of combination is applied. The normalization is not done, leaving the choice to the user to normalize the results or not (for the normalization operation, see [nzdsr](#)).

Usage

```
dsrwon(x, y, varnames = NULL, relnb = NULL, infovarnames)
```

Arguments

<code>x</code>	A basic chance assignment (see bca).
<code>y</code>	A A basic chance assignment (see bca).
<code>varnames</code>	A character string to name the resulting variable. named "z" if omitted.
<code>relnb</code>	Identification number of the relation. Can be omitted.
<code>infovarnames</code>	Deprecated. Old name for <code>varnames</code> .

Details

The two `bca`'s x and y must be defined on the same frame of discernment for the combination to take place. The relation number of the x input is given to the output result.

Value

A basic chance assignment with these two components added:

- `I12` Intersection table of subsets.
- `Sort_order` Sort order of subsets.

Author(s)

Claude Boivin, Stat.ASSQ

References

Shafer, G., (1976). A Mathematical Theory of Evidence. Princeton University Press, Princeton, New Jersey, pp. 57-61: Dempster's rule of combination.

Examples

```
x1 <- bca(tt = matrix(c(0,1,1,1,1,0,1,1,1),nrow=3,
byrow = TRUE), m=c(0.2,0.5, 0.3),
cnames =c("a", "b", "c"),
varnames = "x", varnb=1)
x2 <- bca(tt = matrix(c(1,0,0,1,1,1),nrow=2,
byrow = TRUE), m=c(0.6, 0.4),
cnames = c("a", "b", "c"),
varnames = "x", varnb = 1)
dsrwon(x1,x2)
frame <- bca(matrix(c(1,1,1), nrow=1), m=1, cnames = c("a","b","c"))
dsrwon(frame, frame)
```

dst

Manipulation and combination of belief functions

Description

dst allows you to make basic probability assignments on subsets of a set of possibilities (events) and combine these events with Dempster's rule of combination.

Details

The main operations that can be done are:

- definition of a basic chance assignment (bca) distribution on a variable
- combination of two bca's defined on the same variable
- definition of a bca which establish a relation between two or more variables
- extension of a bca
- marginalization of a bca

Author(s)

Claude Boivin, Stat.ASSQ <webapp.cb@gmail.com>

elim	<i>Reduction of a relation</i>
------	--------------------------------

Description

This function works on a relation defined on a product of two variables or more. Having fixed a variable to eliminate from the relation, the reduced product space is determined and the corresponding reduced bca is computed. This operation is also called "marginalization".

Usage

```
elim(rel, xnb)
```

Arguments

rel	The relation to reduce, an object of class bcaspec.
xnb	Identification number of the variable to eliminate.

Value

r The reduced relation

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
# We construct a relation between two variables to show marginalization.
wr_tt <- matrix(c(1,rep(0,3),rep(c(1,0),3),0,1,1,1,0,0,
1,0,rep(1,5),0,1,1,0,rep(1,5))), ncol=4, byrow = TRUE)
colnames(wr_tt) <- c("Wy Ry", "Wy Rn", "Wn Ry", "Wn Rn")
rownames(wr_tt) <- nameRows(wr_tt)
wr_spec = matrix(c(1:8, 0.017344, 0.046656,
0.004336, 0.199456,0.011664,0.536544,0.049864, 0.134136),
ncol = 2, dimnames = list(NULL, c("specnb", "mass")))
wr_infovar = matrix(c(4,5,2,2), ncol = 2,
dimnames = list(NULL, c("varnb", "size"))) )
wr_rel <- list(tt=wr_tt, con=0.16, spec=wr_spec,
infovar=wr_infovar, varnames = c("Roadworks", "Rain"),
valuenames= list( RdWorks=c("Wy", "Wn"), Rain=c("Ry", "Rn") ))
class(wr_rel)="bcaspec"
bcaPrint(elim(wr_rel, xnb = 5))
bcaPrint(elim(wr_rel, xnb = 4))
```

encode	<i>Convert a value to its representation in another chosen base</i>
--------	---

Description

The `aplEncode` function of the project APL in R (<https://rpubs.com/deleeuw/158476>) has been adapted to follow the standard implementation of the APL encode function.

Usage

```
encode(base, ind)
```

Arguments

base	A numeric vector which describes the number system in which we want to re-code the data.
ind	The value to convert represented by a number or a numeric vector.

Value

A vector or a matrix of the data converted.

Author(s)

Claude Boivin, Stat.ASSQ.

References

- Jan de Leeuw and Masanao Yajima (March 07, 2016) *APL in R (Version 009)*, Source code. <https://rpubs.com/deleeuw/158476>
- L. Gilman and A. J. Rose.(1974): *APL an Interactive Approach*, Second Edition, John Wiley, New York.
- APL 68000 Level II language manual. MicroAPL Ltd. 1990.

Examples

```
encode(c(2,2,2,2), 11) # find the base 2 representation of number 11  
encode(c(365,24,60), 2997) # convert 2997 minutes to days-hrs-min.
```

extmin	<i>Extension of a relation</i>
--------	--------------------------------

Description

This function works on a basic chance assignment (bca) x defined on a single variable or more. A relation of reference is given, and an extension of the space of codex is made to the larger product space of the relation of reference. The basic chance assignment to extend and the relation of reference must have at least one common variable for the extension to be made possible.

Usage

```
extmin(rel1, relRef)
```

Arguments

rel1	An object of class <code>bcaspec</code> , i.e. a basic chance assignment of one variable or a relation.
relRef	The relation of reference. It can be an existing relation, or it can be constructed as a vacuous function.

Details

The `relRef` parameter is used to extract all the information on the variables, namely their identification numbers and the number of elements of each variable, variables names and columns names of the `tt` matrix. The relation of reference `relRef` may simply be an empty relation defined on the set of variables of interest or a relation already defined.

Value

R the resulting extended bca.

Author(s)

Claude Boivin, Stat.ASSQ

References

G. Shafer and P. P. Shenoy. Local Computations in Hypertrees. School of Business, University of Kansas, Lawrence, KS, 1991. See p. 78, vacuous extension of a belief function.

Examples

```
# Making an empty reference relation with mass(frame) = 1 and extending a bca to its space.
init_tt= matrix(rep(1,10),nrow=1,
dimnames =list(NULL, c("3", "2", "1", "0",
"true", "false", "foul", "fair", "true", "false"))) )
init_spec <- matrix(c(1,1), ncol = 2,
dimnames = list(NULL, c("specnb", "mass")))
init_info <- matrix(c(3,4,7,8,4,2,2,2), ncol = 2,
dimnames = list(NULL, c("varnb", "size"))) )
relRef <- bcaRel(tt = init_tt, spec = init_spec,
```

```

infovar = init_info,
varnames = c("Sail", "Loading", "Weather", "Repairs"),
relnb = 0)
# a bcaspec defined on one variable
l_rel <- bca(tt = matrix(c(1,0,1,0,1,1), ncol=2),
m=c(0.3,0.5,0.2), cnames=c("true", "false"),
infovar=matrix(c(4,2), ncol = 2,
dimnames = list(NULL, c("varnb", "size"))),
varnames= c("Loading"),
infovar= matrix(c(7,1), ncol = 2,
dimnames = list(NULL, c("relnb", "depth"))))
z <- extmin(l_rel, relRef)
prmatrix(t(z$tt), collab = rep("", nrow(z$tt)))

```

fw	<i>The Captain's Problem. fw: Relation between variables Forecast of the weather (F) and Weather at sea (W)</i>
----	---

Description

This dataset is the tt matrix establishing the relation between the two variables. An accurate forecast is described by this subset of two events: (Forecast = foul, Weather = foul) and (Forecast = fair, Weather = fair). We assign a mass value of 0.8 to this subset. The remaining mass of 0.2 is allotted to the frame. To construct the tt matrix, we put the variables F and W side by side, as in a truth table representation.

Usage

fw

Format

An integer matrix with 4 rows and 6 columns.

[1,c(1,2)] value = 0, not used

[1,3:6] Identification numbers of the two variables. Column 3,6: variable 5; columns 5,6: variable 7.

nospec identification number of the specification

m the value of the specification, a number between 0 and 1

foul 1 if foul is part of the specification, 0 otherwise

fair 1 if fair is part of the specification, 0 otherwise

Author(s)

Claude Boivin, Stat.ASSQ

Source

https://www.researchgate.net/publication/265993533_Fusion_and_Propagation_in_Graphical_Belief_Models

inters

*Intersection of two tables of propositions***Description**

Function `inters` returns a table of the intersection between two (0,1) or boolean matrices or two vectors. The two matrices must have the same number of columns. The two vectors must be of the same length. This function generalizes the intersection of two subsets represented by boolean vectors to the intersection of two matrices of subsets.

Usage

```
inters(x, y)
```

Arguments

<code>x</code>	A (0,1)-matrix or a boolean matrix of M rows by K columns, or a vector of length K.
<code>y</code>	A (0,1)-matrix or a boolean matrix of N rows by K columns or a vector of length K.

Value

The result is a (0,1)-table of dimensions (M x K) x N). In the case of vectors, the result is a (0,1)-table of dimensions (1 x K) x 1)

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
mx<-matrix(c(0,1,0,0,1,1,1,1,1),nrow=3, byrow = TRUE, dimnames = list(NULL, c("a", "b", "c")))
rownames(mx) <- nameRows(mx)
my<-matrix(c(0,0,1,1,1,1),nrow=2, byrow = TRUE, dimnames = list(NULL, c("a", "b", "c")))
rownames(my) <- nameRows(my)
inters(mx,my)
b1 <- c(FALSE, TRUE, TRUE)
b2 <- c(TRUE, TRUE, FALSE)
names(b1) <- names(b2) <- c("c1","c2","c3")
inters(b1,b2)
x3<-matrix(c(1,1,0,1), ncol=2, dimnames=list(NULL, c("a","b")))
y3<-matrix(c(0,1,1,1), ncol=2, dimnames=list(NULL, c("a","b")))
inters(x3,y3)
x4 <-matrix(c(1,0,1,1,1,1,1,1),nrow=2, byrow = TRUE, dimnames = list(NULL, c("a", "b", "c","d")))
y4 <-matrix(c(1,0,0,1,1,1,1,1),nrow=2, byrow = TRUE, dimnames = list(NULL, c("a", "b", "c","d")))
inters(x4,y4)
```

marrayToMatrix

Transformation of an array data to its matrix representation

Description

The array representation or product space representation is converted to the matrix representation of the corresponding relation.

Usage

```
marrayToMatrix(mtt)
```

Arguments

mtt The matrix tt of the relation in multiarray format

Value

tt The matrix representation of the data.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
mtt <- array(c(1,0,0,0,1,1,0,0,1,0,0,1,1,0,1,0,1,1,0,1,1,1,0,1,0,1,1,1,1,1), c(2,2,8),
dimnames = list( RdWorks=c("Wy", "Wn") , Rain=c("Ry", "Rn"), ev=1:8) )
print(z <- marrayToMatrix(mtt))
```

matrixToMarray

Transformation of the tt matrix of a relation

Description

The matrix representation of a relation is converted to the array representation or product space representation.

Usage

```
matrixToMarray(tt, valuenames)
```

Arguments

tt A (0,1)-matrix or a boolean matrix establishing the relation between two or more variables. The matrix is constructed by placing the variables side by side, as in a truth table representation.

valuenames A list of the names of the variables with the name of each value of their frame of discernment.

Value

mtt The array (product space) representation of the tt matrix.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
# Define wr_tt, a matrix describing the relation between two variables
wr_tt <- matrix(c(1,rep(0,3),rep(c(1,0),3),0,1,1,1,0,0,
1,0,rep(1,5),0,1,1,0,rep(1,5))), ncol=4, byrow = TRUE)
colnames(wr_tt) <- c("Wy Ry", "Wy Rn", "Wn Ry", "Wn Rn")
rownames(wr_tt) <- nameRows(wr_tt)
vars= list( RdWorks = c("Wy", "Wn") , Rain = c("Ry", "Rn"))
print(zmToa <- matrixToMarray(tt = wr_tt, valuenames = vars ) )
```

mrf

The Captain's Problem. mrf: Relation between variables No Maintenance ($M = \text{false}$) and Repairs at sea (R)

Description

This dataset is the tt matrix establishing a set of two relations between the two variables. First, Repairs = true if Maintenance = false in ($M \times R$). We are 20% sure that there will be Repairs if no maintenance. Second, Repairs = false if Maintenance = false in ($M \times R$). We are 20% sure that there will be no repairs if no maintenance.

Usage

mrf

Format

An integer matrix with 4 rows and 6 columns.

[1,c(1,2)] value = 0, not used

[1,3:6] Identification numbers of the two variables. Column 3,4: variable 6; columns 5,6: variable 8

nospec identification number of the specification

m the value of the specification, a number between 0 and 1

true 1 if true is part of the specification, 0 otherwise

false 1 if false is part of the specification, 0 otherwise

Details

These two relations are implication rules. The remaining mass of 0.6 is allotted to the frame. To construct the tt matrix, we put the variables M and R side by side, as in a truth table representation.

Author(s)

Claude Boivin, Stat.ASSQ

Source

https://www.researchgate.net/publication/265993533_Fusion_and_Propagation_in_Graphical_Belief_Models

mrt	<i>The Captain's Problem. mrt: Relation between variables Maintenance done ($M = \text{true}$) and Repairs at sea (R)</i>
-----	---

Description

This dataset is the tt matrix establishing a set of two relations between the two variables. First, Repairs = true if Maintenance = true in ($M \times R$). We are 10% sure that there will be Repairs if maintenance is done. Second, Repairs = false if Maintenance = true in ($M \times R$). We are 70% sure that there will be no repairs if maintenance is done.

Usage

mrt

Format

An integer matrix with 4 rows and 6 columns.

[1,c(1,2)] value = 0, not used

[1,3:6] Identification numbers of the two variables. Column 3,4: variable 6; columns 5,6: variable 8

nospec identification number of the specification

m the value of the specification, a number between 0 and 1

true 1 if true is part of the specification, 0 otherwise

false 1 if false is part of the specification, 0 otherwise

Details

These two relations are implication rules. The remaining mass of 0.2 is allotted to the frame. To construct the tt matrix, we put the variables M and R side by side, as in a truth table representation.

Author(s)

Claude Boivin, Stat.ASSQ

Source

https://www.researchgate.net/publication/265993533_Fusion_and_Propagation_in_Graphical_Belief_Models

nameCols	<i>Naming the columns of the tt matrix</i>
----------	--

Description

This utility function makes use of the valuenames and size parameters of a set of variables to assign values names to the columns of a tt matrix.

Usage

```
nameCols(valuenames, size)
```

Arguments

valuenames	A list of the names of the variables with the name of the elements of their frame of discernment.
size	A vector of the size of the variables.

Value

A character vector of length equal to the sum of the sizes of the variables

Author(s)

Claude Boivin, Stat.ASSQ infoval <- list(A = c("a1", "a2"), B = c("b1", "b2", "b3")) sizes <- c(2,3)
print(nameCols(valuenames = infoval, size = sizes))

nameCols_prod	<i>Naming the columns of the tt matrix of a product space</i>
---------------	---

Description

This utility function makes use of the valuenames and size parameters of a set of variables to assign values names to the columns of the tt matrix of their product space.

Usage

```
nameCols_prod(valuenames, size)
```

Arguments

valuenames	A list of the names of the variables with the name of the elements of their frame of discernment.
size	A vector of the size of the variables.

Value

A character vector of length equal to the product of the sizes of the variables

Author(s)

Claude Boivin, Stat.ASSQ infoval <- list(A = c("a1", "a2"), B = c("b1", "b2", "b3")) sizes <- c(2,3)
 print(nameCols_prod(valuenames = infoval, size = sizes))

nameRows	<i>Combining the column names of a matrix to construct names for the rows</i>
----------	---

Description

This function determines the name of a row from all the columns that have a 1 for that row.

Usage

```
nameRows(tt, f)
```

Arguments

`tt` A (0,1)-matrix or a boolean matrix.
`f` Deprecated. Old name for `tt` matrix.

Details

The row consisting all 1's is called "frame", to avoid too long a character string. The empty set is identified by its code "u00f8". The "+" sign is used to represent the logical "or" operator. The space " " is used to represent the logical "and" operator. Note that in the case of a product space defined on many variables, row labels can become very long.

Value

A character vector of labels obtained for the rows of the matrix `tt`. The length of the result is `nrow(tt)`.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
tt <- matrix(c(0,0,0,1,0,0,0,0,1,1,0,1,1,1,1),ncol=3, byrow = TRUE)
colnames(tt) <- c("A","B","C")
rownames(tt) <- nameRows(tt)
tt
```


nzdsr

*Normalization of a basic chance assignment***Description**

It may occur that the result of the combination of two basic chance assignments with Dempster's Rule of combination contains a non-zero mass allocated to the empty set. The function `nzdsr` normalizes the result of function `dsrwon` by dividing the mass value of the non-empty subsets by 1 minus the mass of the empty set.

Usage

```
nzdsr(x)
```

Arguments

`x` A basic chance assignment, i.e. a object of class `bcaspec`.

Value

`z` The normalized basic chance assignment.

Author(s)

Claude Boivin, Stat.ASSQ

References

Shafer, G., (1976). A Mathematical Theory of Evidence. Princeton University Press, Princeton, New Jersey, pp. 57-61: Dempster's rule of combination.

Examples

```
x1 <- bca(f=matrix(c(1,0,1,1),nrow=2, byrow = TRUE),
m=c(0.9,0.1), cnames =c("yes", "no"),
varnames = "x", varnb = 1)
x2 <- bca(f=matrix(c(0,1,1,1),nrow=2, byrow = TRUE),
m=c(0.5,0.5), cnames =c("yes", "no"),
varnames = "x", varnb = 1)
print("combination of x1 and x2")
x1x2 <- dsrwon(x1,x2, varname = "x")
nzdsr(x1x2)

print("normalization of a bca definition.")
y2 <- bca(f=matrix(c(0,0,0,1,0,0,1,1,1),nrow=3,
byrow = TRUE), m=c(0.2,0.5,0.3),
cnames =c("a", "b", "c"), varnb = 1)
nzdsr(y2)
```

 peeling

The peeling algorithm

Description

An implementation of the peeling algorithm based on the description of the algorithm in terms of hypergraphs by R. Almond [1989].

Usage

```
peeling(vars_def, hgm, hg_rel_names, elim_order, verbose = FALSE)
```

Arguments

vars_def	A list of the variables and their possible values. Simply concatenate the value-names parameter of all the variables of the hypergraph to obtain this list.
hgm	The incidence matrix of the hypergraph (bipartite graph), which is the description of the relations between the variables. The variables are the nodes of the hypergraph, and the relations are the edges. Each column describes a relation between the variables by a (0,1) vector. A "1" indicates that a variable belongs to the relation and a "0" not. This matrix must have row and column names. These names are used to show the graph. They need not be the same as variables and relations names of the set of bca's to be analyzed. Use shorter names to obtain a clearer graph.
hg_rel_names	The names of the relations, which are objects of class "bcaspec".
elim_order	The order of elimination of the variables. A vector of length nrow(hgm). variables are identified by numbers. The first number gives the first variable to eliminate. The variable of interest comes last.
verbose	= TRUE: print steps on the console. Default = FALSE.

Details

The peeling algorithm works on an undirected graph. Nodes (variables) of the graph are eliminated (removed of the graph) one by one until only the variable of interest remains. An order of elimination (peeling) of the variables must be chosen, since no algorithm has yet been provided for that. At each step, a procedure of extension is applied to the bca's to merge, and marginalization is applied. The marginalization has the effect to integrate in the remaining nodes the information of the eliminated variable.

Value

A bca class object.

Author(s)

Claude Boivin, Stat.ASSQ

References

- Almond, R. G. (1989) Fusion and Propagation of Graphical Belief Models: An Implementation and an Example. Ph. D. Thesis, the Department of Statistics, Harvard University. 288 pages (for the description of the algorithm, see pages 52-53).

Examples

```
# Zadeh's Example

# 1. Defining variables and relations
# (for details, see vignette: Zadeh_Example)
e1 <- bca(f= matrix(c(1,0,0,1,1,1), ncol=2, byrow=TRUE),
  m= c(0.99, 0.01, 0), cnames =c("M", "T"),
  varnames = "D1", varnb = 1)
e2 <- bca(f= matrix(c(1,0,0,1,1,1), ncol=2, byrow=TRUE),
  m= c(0.99, 0.01, 0), cnames =c("C", "T"),
  varnames = "D2", varnb = 2)
p_diag <- bca(f= matrix(c(1,1,1), ncol=3, byrow=TRUE),
  m= c(1), cnames =c("M", "T", "C"),
  varnames = "D", varnb = 3)
# Defining the relation between the variables
# tt matrix
tt_r1 <- matrix(c(1,0,1,0,1,0,0,1,0,1,0,0,0,1,
  1,0,0,1,1,0,0,1,0,0,1,0,1,0,0,1,1,0,0,1,0,
  0,1,1,0,0,0,1,0,1,0,1,0,1,0,1,1,1,1,1,1,1),
  ncol = 7,byrow = TRUE)
colnames(tt_r1) = c("M", "T", "C", "T", "M", "T", "C")
# The mass function
spec_r1 = matrix(c(rep(1,7),2, rep(1,7), 0), ncol = 2, dimnames = list(NULL, c("specnb", "mass")))
# Variables numbers and dimension of their Fod
info_r1 =matrix(c(1:3, 2,2,3), ncol = 2, dimnames = list(NULL, c("varnb", "size")) )
# The relation between e1, e2 and a patient p
r1 <-bcaRel(tt = tt_r1, spec = spec_r1, infovar = info_r1, varnames = c("D1", "D2", "D"), relnb = 1)

# 2. Setting the incidence matrix of the graph
rel1 <- 1*1:3 %in% r1$infovar[,1]
ev1 <- 1*1:3 %in% e1$infovar[,1]
ev2 <- 1*1:3 %in% e2$infovar[,1]
meddiag_hgm <- matrix(c(ev1,ev2, rel1), ncol=3,
  dimnames = list(c("D1", "D2", "D"), c("e1","e2", "r1")))

# 3. Setting the names of the variables and their frame of discernment
meddiag_vars1 <- c(e1$valuenames, e2$valuenames, p_diag$valuenames)

# 4. Names of bca specifications (evidence and relations)
meddiag_rel_names <- c("e1", "e2", "r1")

# 5. Order of elimination of variables
elim_order <- c(1,2,3)

tabresul(peeling(vars_def = meddiag_vars1, hgm = meddiag_hgm,
  hg_rel_names = meddiag_rel_names, elim_order = c(1, 2, 3)) )
```

plautrans

Plausibility transformation of the singletons of a frame

Description

Given a mass function defined on some subsets of a frame Θ , the application of the plausibility transformation to the singletons of Θ yields the probability distribution associated with the this mass function.

Usage

```
plautrans(x)
```

Arguments

x A bca mass function.

Details

We compute the plausibility measure of all the singletons of the frame of discernment. The probability distribution of the singletons is obtained from their plausibility measures.

Value

The matrix of singletons with their plausibility transformation added in the last column.

Author(s)

Claude Boivin, Stat.ASSQ

References

Cobb, B. R. and Shenoy, P.P. (2006). On the plausibility transformation method for translating belief function models to probability models. *Journal of Approximate Reasoning*, 41(3), April 2006, 314–330.

Examples

```
x <- bca(tt = matrix(c(0,1,1,1,1,0,1,1,1),nrow=3,
byrow = TRUE), m=c(0.2,0.5, 0.3),
cnames =c("a", "b", "c"),
infovarnames = "x", varnb = 1)
plautrans(x)
```

productSpace	<i>Product space representation of a relation</i>
--------------	---

Description

This utility function takes the input matrix of a relation between two or more variables and yields its product space representation.

Usage

```
productSpace(tt, specnb, infovar)
```

Arguments

<code>tt</code>	A (0,1) or boolean matrix, where the values of the variables put in relation are set side by side, as in a truth table.
<code>specnb</code>	A vector of integers ranging from 1 to k, where k is the number of subsets of the <code>tt</code> matrix. Values must start at one and can be increased only by 0 or 1. They determine the partitioning of the rows of the <code>tt</code> matrix between the k subsets.
<code>infovar</code>	A two-column matrix containing identification numbers of the variables and the number of elements of each variable (size of the frame).

Value

The matrix of the product space representation of the relation.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
ttfw= matrix(c(1,0,1,0,0,1,0,1,1,1,1,1),nrow=3,
  byrow = TRUE,
  dimnames =list(NULL, c("foul", "fair", "foul", "fair")) )
specfw = c(1,1,2)
infovarfw =matrix(c(5,7,2,2), ncol = 2,
  dimnames = list(NULL, c("varnb", "size"))) )
rownames(ttfw) <- nameRows(ttfw)
ttfw
productSpace(tt=ttfw, specnb=specfw, infovar=infovarfw)
```

reduction	<i>Summary of a vector for any operator.</i>
-----------	--

Description

This utility function is used to obtain a summary of a vector of data for many operators. The function is taken from the project APL in R (<https://rpubs.com/deleeuw/158476>).

Usage

```
reduction(x, f = "+")
```

Arguments

x	A vector of numbers or character strings.
f	The operator. Must be compatible with the type of input vector (numeric or character)

Value

The result of applying the chosen operator to all the elements of the vector is an object of length 1.

Author(s)

Claude Boivin, Stat.ASSQ.

References

- Jan de Leeuw and Masanao Yajima (March 07, 2016) *APL in R (Version 009)*, Source code. <https://rpubs.com/deleeuw/158476>
- G. Helzer. (1989): *An Encyclopedia of APL*, second edition, I-APL LTD, St. Albans, G.B.
- L. Gilman and A. J. Rose.(1974): *APL an Interactive Approach*, Second Edition, John Wiley, New-York.

Examples

```
reduction(c(1,2,3,4), f="-")
reduction(c(1,0,1,1,0), f="|")
reduction(c("a", "b", "c"), f="paste")
```

shape	<i>Obtain dimensions of an array or length of a vector with a single command</i>
-------	--

Description

shape returns sizes of each dimension of given array or the length of a given vector. The function is taken from the project APL in R (<https://rpubs.com/deleeuw/158476>).

Usage

```
shape(a)
```

Arguments

a An array or a vector.

Value

The dimensions of the array a or the length of the vector a.

Author(s)

Claude Boivin, Stat.ASSQ.

References

- Jan de Leeuw and Masanao Yajima (March 07, 2016) *APL in R (Version 009)*, Source code. <https://rpubs.com/deleeuw/158476>
- G. Helzer. (1989): *An Encyclopedia of APL*, second edition, I-APL LTD, St. Albans, G.B.
- L. Gilman and A. J. Rose.(1974): *APL an Interactive Approach*, Second Edition, John Wiley, New-York.

Examples

```
shape(array(c(1:6), c(2,3)))
shape(c("a", "b"))
```

swr	<i>The Captain's Problem. swr: Relation between variables Sailing delay (S), Weather at sea (W), and Repairs at sea (R)</i>
-----	---

Description

This dataset is the tt matrix establishing a relation between S, W and R, where S = 0:3, W = foul, fair and R = true, false. The goal of this relation is to account for other causes of sailing delay. All the elements (s,w,r) of (S x W x R) where W or R is true add one day of sailing delay. We put a mass value of 0.9 to this subset. The remaining mass of 0.1 is allotted to the frame.

Usage

```
SWR
```

Format

An integer matrix with 6 rows and 10 columns.

[1,c(1,2)] value = 0, not used

[1,3:10] Identification numbers of the three variables. Column 3 to 6: variable 3; columns 7,8: variable 7, columns 9,10: variable 8

nospec identification number of the specification

m the value of the specification, a number between 0 and 1 #'

3 1 if 3 is part of the specification, 0 otherwise

2 1 if 2 is part of the specification, 0 otherwise

1 1 if 1 is part of the specification, 0 otherwise

0 1 if 0 is part of the specification, 0 otherwise #'

foul 1 if foul is part of the specification, 0 otherwise

fair 1 if fair is part of the specification, 0 otherwise

true 1 if true is part of the specification, 0 otherwise

false 1 if false is part of the specification, 0 otherwise

Details

To construct the tt matrix, we put the variables S, W, R side by side, as in a truth table representation.

Author(s)

Claude Boivin, Stat.ASSQ

Source

https://www.researchgate.net/publication/265993533_Fusion_and_Propagation_in_Graphical_Belief_Models

tabresul

Prepare a table of results

Description

This utility function is a more detailed version of the belplau function. Different tables of measures of belief, plausibility and of the plausibility ratio can be obtained, namely by removing subsets with zero mass if present, or by asking for singletons only.

Usage

```
tabresul(x, singletonsOnly = FALSE, removeZeroes = FALSE)
```


Arguments

`x` A basic chance assignment (bca)
`singletonsOnly` = TRUE reduces the table of results to elementary events (singletons).
`removeZeroes` = TRUE removes subsets with 0 mass.

Value

A list of two elements:

- `mbp`: The table of focal elements with the addition of their associated mass, degree of belief, plausibility and the plausibility ratio.
- `con` The measure of conflict between subsets.

Author(s)

Claude Boivin, Stat.ASSQ

Examples

```
x <- bca(tt = matrix(c(0,1,1,1,1,0,1,1,1),nrow=3,
byrow = TRUE), m=c(0.2,0.5, 0.3),
cnames =c("a", "b", "c"),
varnames = "x", varnb = 1)
y <- bca(tt = matrix(c(1,0,0,1,1,1),nrow=2,
byrow = TRUE), m=c(0.6, 0.4),
cnames = c("a", "b", "c"), varnames = "y", varnb = 1)
xy <- dsrwon(x,y)
xyNorm <- nzdsr(xy)
tabresul(xyNorm)
## print("Show all elementary events")
xy1 <- addTobca(nzdsr(dsrwon(x,y)),
matrix(c(0,1,0,0,0,1),
nrow=2, byrow = TRUE))
tabresul(xy1)
## print("Remove focal elements with 0 mass")
tabresul(xy1, removeZeroes = TRUE)
print("Retain singletons only")
tabresul(xy1, singletonsOnly = TRUE)
```

Index

* datasets

- ads, [3](#)
- dlfm, [10](#)
- fw, [18](#)
- mrf, [21](#)
- mrt, [22](#)
- swr, [31](#)

addTobca, [2](#)

ads, [3](#)

aplDecode (decode), [9](#)

aplEncode (encode), [16](#)

aplRDV (reduction), [30](#)

aplShape (shape), [31](#)

bca, [2](#), [4](#), [8](#), [13](#)

bcaPrint, [6](#)

bcaRel, [5](#), [6](#)

belplau, [8](#)

bpa (bca), [4](#)

decode, [9](#)

dlfm, [10](#)

dotprod, [11](#)

doubles, [12](#)

dsrwon, [13](#)

dst, [14](#)

elim, [15](#)

encode, [16](#)

extmin, [17](#)

fw, [18](#)

inters, [19](#)

marrayToMatrix, [20](#)

matrixToMarray, [20](#)

mrf, [21](#)

mrt, [22](#)

nameCols, [23](#)

nameCols_prod, [23](#)

nameRows, [5](#), [7](#), [24](#)

nzdsr, [13](#), [25](#)

peeling, [26](#)

plautrans, [28](#)

productSpace, [29](#)

reduction, [30](#)

shape, [31](#)

swr, [31](#)

tabresul, [32](#)