

NAME:GOKULRAJ NATARAJAN

REGNO 192512002

COURSE CODE/NAME:ECA5608-5G/6G COMMUNICATION SYSTEM

SLOT:D

TITLE: IoT Network for Smart Environment Monitoring Using ESP32 (5G mMTC Concept)

Question:

How can low-cost ESP32 sensor nodes emulate 5G mMTC architecture using lightweight mesh protocols and NB-IoT to overcome spatial blind spots in urban environmental monitoring?

Abstract

Urban environmental monitoring systems often rely on sparse Continuous Ambient Air Quality Monitoring Stations (CAAQMS), which provide high-quality regulatory measurements but fail to capture localized pollution variations across streets, intersections, industrial boundaries, and urban canyons. This technical report proposes an economical, high-density IoT network using ESP32 sensor nodes to emulate key principles of 5G Massive Machine-Type Communications (mMTC). The proposed model combines low-cost distributed sensing, edge-based Exponential Moving Average filtering, ESP-NOW burst transmission, and NB-IoT gateway backhaul for cloud analytics and real-time environmental heatmapping. The architecture targets spatial blind spots by increasing measurement density while maintaining low device cost, low communication overhead, and scalable cloud integration.

1.Executive Summary & Problem Context

1.1 Executive Summary

Modern cities require high-resolution environmental intelligence to detect localized pollution, protect public health, improve traffic management, and support climate-resilient planning. Conventional air-quality monitoring systems are accurate but sparse. A small number of expensive stations cannot represent pollutant concentration at every street, junction, school zone, bus stop, construction site, underpass, industrial fence, or residential corridor.

The proposed solution uses ESP32-based low-cost sensing nodes distributed at high spatial density. Each node collects measurements from air-quality, carbon monoxide, particulate matter, and climate sensors. Data is filtered at the edge using an Exponential Moving Average algorithm, classified through threshold logic, and transmitted through ESP-NOW to an NB-IoT gateway. The gateway forwards compact payloads to cloud analytics platforms for visualization, alerting, and heatmap generation.

The architecture is inspired by 5G mMTC principles:

- 1 Massive deployment density
- 2 Small periodic payloads
- 3 Low per-device cost

- 4 Battery-efficient operation
- 5 Gateway-based cellular IoT connectivity
- 6 Cloud-scale telemetry processing

This approach does not replace CAAQMS. Instead, it acts as a dense augmentation layer that fills spatial blind spots between reference-grade stations.

1.2 Urban Spatial Blind Spots

Urban spatial blind spots are locations where pollutant concentration differs significantly from values reported by nearby official monitoring stations. These blind spots occur due to localized emission sources and airflow patterns.

Common spatial blind spot locations include:

- 1 Traffic intersections with long vehicle queues
- 2 Narrow commercial streets surrounded by tall buildings
- 3 Bus terminals, parking zones, and underpasses
- 4 Construction corridors and demolition zones
- 5 School gates and hospital entrances near roads
- 6 Industrial fencelines and generator yards
- 7 Low-ventilation residential streets
- 8 Markets and roadside vending areas
- 9 Tunnel portals and flyover approaches

Sparse monitoring causes data interpolation errors. A station several kilometers away may show moderate pollution while a street canyon experiences hazardous short-duration pollutant accumulation.

1.3 Street Canyon Effects

A street canyon forms when tall buildings flank a road corridor. Vehicle emissions accumulate because vertical air mixing is reduced and wind-driven recirculation traps pollutants near ground level.

Street canyon pollution is influenced by:

- 1 Building height-to-road width ratio
- 2 Wind speed and wind direction
- 3 Traffic density and vehicle idling time
- 4 Roadside vegetation and barriers
- 5 Thermal gradients and urban heat island effects
- 6 Heavy-duty vehicle movement
- 7 Construction dust resuspension

High-density sensing is essential because pollutant concentration can vary sharply across sidewalks, lanes, and building edges.

1.4 Limitations of CAAQMS

Continuous Ambient Air Quality Monitoring Stations are critical for regulatory compliance and scientific-grade monitoring. However, their deployment at dense spatial resolution is difficult due to cost and

infrastructure constraints.

Limitation	Technical Impact	Monitoring Consequence
High capital cost	Reference analyzers, shelters, calibration systems, and civil infrastructure are expensive	Limited station density
Fixed installation	Stations require secure sites, stable power, and suitable environmental conditions	Poor coverage of complex streets
Maintenance overhead	Calibration gas, instrument servicing, and technician visits are required	Scaling becomes costly
Low spatial granularity	Stations represent broad areas rather than micro-environments	Localized peaks remain hidden
Limited mobility	Stations are not easily relocated to temporary hotspots	Construction and event pollution may be missed
Infrastructure dependency	Power, network, and protected housing are required	Deployment in remote or dense urban pockets is constrained

1.5 Proposed Engineering Direction

The proposed direction is a hybrid sensing and communication network:

- 1 Dense ESP32 sensing nodes for localized monitoring
- 2 ESP-NOW for lightweight local wireless bursts
- 3 NB-IoT gateway for wide-area 5G-aligned cellular backhaul
- 4 Cloud dashboard for heatmaps, alerts, and historical analysis
- 5 Reference-station calibration for improved reliability

2.Theoretical Framework

2.1 Overview of 5G mMTC

Massive Machine-Type Communications is one of the major 5G service categories. It is designed for very large numbers of low-power devices that transmit small amounts of data periodically or during events.

mMTC differs from high-bandwidth communication systems because it prioritizes:

- Connection scalability
- Energy efficiency
- Low-cost endpoint hardware
- Small data packet transmission
- Wide-area coverage
- Long operational lifetime
- Low complexity device behavior

Environmental sensing is a strong candidate for mMTC-style operation because most sensors transmit small telemetry values rather than continuous high-bandwidth streams.

2.2 5G mMTC Pillars

mMTC Pillar	Target Characteristic	Environmental Monitoring Interpretation
Massive density	Up to 1,000,000 devices/km²	Dense deployment across streets, buildings, farms, forests, and industrial boundaries
Small payload size	Approx. 50-byte telemetry packets	Environmental readings can be encoded as compact payloads
Battery life	5–10 years for optimized low-power endpoints	Supported through duty cycling, deep sleep, and short burst transmission
Low unit cost	Low per-device silicon and communication cost	Enables dense spatial coverage without reference-station-level expense
Uplink-dominant traffic	Devices mostly transmit sensor data to network	Air-quality networks mainly send readings from node to cloud
Event-driven support	Priority transmission during abnormal conditions	Hazard thresholds can trigger immediate alert packets
Wide-area access	Cellular IoT coverage for large deployments	NB-IoT gateway provides scalable backhaul

2.3 ESP32-Based Edge Emulation of mMTC

An ESP32 node is not a native 5G modem. However, a distributed ESP32 sensor network can emulate mMTC behavior through system-level design.

5G mMTC Requirement	ESP32 Edge Emulation Strategy
Massive device density	Use low-cost ESP32 nodes installed at dense spatial intervals
Small payloads	Encode sensor data into compact telemetry frames
Long battery life	Use deep sleep, RTC wakeup, sensor duty cycling, and burst radio transmission
Low device cost	Use ESP32 SoC and shared NB-IoT gateways rather than cellular modem per node
Low overhead communication	Use ESP-NOW for connectionless local packet delivery
Wide-area cloud access	Use NB-IoT gateway for cellular backhaul
Scalable analytics	Use cloud IoT broker, database, and heatmap dashboard

2.4 Compact Payload Model

A typical environmental payload can be compressed into approximately 50 bytes.

Payload Field	Size	Description
Node ID	4 bytes	Unique sensor node identifier
Timestamp index	4 bytes	RTC or gateway-aligned sampling time
PM2.5	2 bytes	Fine particulate concentration
PM10	2 bytes	Coarse particulate concentration
CO index	2 bytes	MQ-7-based carbon monoxide indicator
Air-quality index	2 bytes	MQ-135-based gas index
Temperature	2 bytes	Scaled temperature value
Humidity	2 bytes	Scaled relative humidity
Pressure	2 bytes	Scaled barometric pressure
Battery voltage	2 bytes	Power health indicator
Hazard flag	1 byte	Normal, warning, or critical state
Sequence number	2 bytes	Packet ordering and loss detection
Checksum/CRC	2 bytes	Integrity validation
Reserved metadata	23 bytes	Calibration version, routing level, retry counter, location group, or future extension

2.5 Edge Filtering Model

Low-cost sensors can produce noisy readings. Edge filtering improves stability before transmission.

Exponential Moving Average:

$$y_t = \alpha x_t + (1 - \alpha)y_{t-1}$$

Where:

x_t =current raw sensor reading

y_t =filtered output

y_{t-1} =previous filtered output

α =smoothing factor, commonly 0.1 to 0.4

A smaller smoothing factor produces stable readings but slower response. A larger smoothing factor detects abrupt changes faster but passes more noise.

3.Hardware Specifications Matrix

3.1 Hardware Overview

The proposed node integrates a low-cost microcontroller, gas sensors, particulate sensor, climate sensor, power subsystem, and enclosure. The ESP32 coordinates sampling, filtering, threshold evaluation, wireless

burst transmission, and deep sleep scheduling.

3.2 Hardware Specifications Table

Component	Category	Key Specifications	Interface	Engineering Function
ESP32 SoC	Microcontroller and wireless SoC	Dual-core 32-bit processor, up to 240 MHz, integrated Wi-Fi, BLE, ESP-NOW support, ADC, UART, I ² C, SPI, deep sleep around 10 μA under optimized board conditions	ADC, UART, I ² C, SPI, GPIO	Main controller, edge filtering, packet encoding, local wireless communication, low-power scheduling
MQ-135	Air-quality gas sensor	Sensitive to smoke, ammonia, benzene-like gases, CO ₂ proxy behavior, and VOC-related air-quality trends	Analog ADC	General air-quality trend sensing and localized pollution anomaly detection
MQ-7	Carbon monoxide sensor	Metal-oxide CO sensor with heater cycle requirements for improved CO response	Analog ADC	Carbon monoxide monitoring near roads, tunnels, generators, parking zones, and industrial areas
Nova SDS011	Particulate matter sensor	Laser scattering PM2.5 and PM10 sensor with fan-assisted airflow and digital output	UART	Fine and coarse particulate monitoring from dust, smoke, combustion, and traffic emissions
Bosch BME280	Climate sensor	Temperature, humidity, and barometric pressure sensor with low-power operation	I ² C/SPI	Microclimate sensing, environmental compensation, and weather context
Battery pack	Energy storage	Li-ion or LiFePO ₄ rechargeable battery configuration	Power rail	Off-grid node operation
Solar charger	Energy harvesting	Solar panel with charging controller or MPPT-based module	Power rail	Outdoor lifetime extension
NB-IoT gateway module	Cellular IoT backhaul	Low-bandwidth cellular telemetry support for wide-area IoT deployment	UART/USB/SPI depending on module	Aggregated cloud uplink from ESP-NOW cluster
Weatherproof enclosure	Mechanical protection	Ventilated, UV-resistant, water-resistant housing with airflow path and insect protection	Physical integration	Outdoor durability and sensor exposure control

3.3 Sensor Suitability Analysis

Sensor	Strength	Design Consideration	Best Deployment Use
MQ-135	Very low cost and useful for air-quality trend detection	Requires calibration and environmental compensation	Street-level pollution trend mapping
MQ-7	Detects CO-related hazards economically	Heater cycling affects power budget	Tunnels, parking areas, generators, traffic junctions
SDS011	Direct PM2.5 and PM10 indication	Fan and laser increase energy consumption	Construction zones, dust corridors, wildfire smoke monitoring
BME280	Low power and stable climate data	Requires proper airflow placement	All nodes for environmental context and compensation
ESP32	Low-cost compute and wireless integration	Board-level power design affects actual sleep current	Dense distributed IoT sensing

4.3-Tier System Architecture

4.1 Architecture Overview

The proposed system uses a three-tier architecture:

Tier 1:Sensing Layer:Distributed ESP32 sensor nodes acquire local environmental data.

Tier 2:Aggregation and Transport Layer:ESP-NOW handles local burst forwarding, while NB-IoT provides cellular backhaul from gateway to cloud.

Tier 3:Cloud and Analytics Layer:IoT broker, storage, dashboard, heatmap, and alert systems transform telemetry into decision-support intelligence.

4.2 Tier 1:Sensing Layer

Tier 1 includes dense ESP32 nodes deployed at environmental monitoring points. These nodes are responsible for direct interaction with the physical environment.

Tier 1 functions:

Read MQ-135 air-quality values

Read MQ-7 carbon monoxide values

Read SDS011 PM2.5 and PM10 values

Read BME280 temperature, humidity, and pressure values

Apply local filtering

Classify normal, warning, and critical states

Encode compact telemetry

Transmit through ESP-NOW

Enter deep sleep after transmission

4.3 Tier 2:Aggregation and Transport Layer

Tier 2 connects local ESP32 clusters to wide-area cellular IoT infrastructure. ESP-NOW is used for short-range local burst communication. NB-IoT is used at the gateway for cloud transport.

- Tier 2 functions:
- Receive ESP-NOW packets from multiple nodes
 - Validate node identity and payload integrity
 - Remove duplicate packets
 - Add gateway timestamp and location metadata
 - Buffer data during cellular outages
 - Forward telemetry using MQTT or HTTPS over NB-IoT

4.4 Tier 3:Cloud and Analytics Layer

Tier 3 ingests and analyzes the sensor data. It supports real-time monitoring and long-term environmental intelligence.

- Tier 3 functions:
- IoT message ingestion
 - Time-series storage
 - Node registry and health monitoring
 - Heatmap generation
 - Hazard alerting
 - Spatial interpolation
 - Historical trend analysis
 - Data export for urban planning and research

4.5 Layer-to-Function Mapping

Layer	Primary Hardware/Software	Main Function	Output
Tier 1:Sensing	ESP32, MQ-135, MQ-7, SDS011, BME280	Environmental measurement and edge preprocessing	Filtered sensor payload
Tier 2:Aggregation/Transport	ESP-NOW, ESP32 gateway, NB-IoT module	Local collection and cellular forwarding	Validated cloud telemetry
Tier 3:Cloud/Analytics	IoT broker, database, dashboard, heatmap engine	Storage, visualization, alerting, trend analysis	Actionable environmental intelligence

5.Operational Logic

5.1 Operational Sequence

The node operates in low-duty-cycle mode. It remains in deep sleep for most of the monitoring interval and wakes only to measure, process, transmit, and return to sleep.

- Operational steps:
- RTC timer wakes ESP32 from deep sleep

ESP32 initializes ADC, UART, I²C, GPIO, and wireless subsystem
Sensors are powered or enabled according to duty-cycle schedule
MQ-135, MQ-7, SDS011, and BME280 values are acquired
Raw data is filtered using EMA
Filtered data is checked against thresholds
Normal data is transmitted as routine telemetry
Hazard data is transmitted as priority telemetry with retry burst
Gateway forwards received packets through NB-IoT
Cloud platform updates dashboard, database, and alert engine
ESP32 returns to deep sleep

5.2 Normal vs. Hazard Communication Behavior

Condition	Sensor State	Communication Behavior	Cloud Action
Normal	Values below threshold	Single compact ESP-NOW burst at scheduled interval	Store telemetry and update heatmap
Warning	Moderate threshold exceedance	Priority flag and increased transmission frequency	Dashboard warning and trend tracking
Critical	High threshold exceedance	Immediate burst transmission with retry logic	Alert trigger and incident marking
Sensor fault	Invalid or missing sensor response	Diagnostic packet	Maintenance notification
Low battery	Battery below configured voltage	Reduced sampling or power-save flag	Node health warning

5.3 Power Optimization Logic

Power Strategy	Technical Implementation	Benefit
Deep sleep	ESP32 enters sleep between sampling cycles	Reduces idle current
RTC wakeup	Timer-based scheduled activation	Supports periodic monitoring
Sensor duty cycling	Power high-current sensors only when required	Reduces MQ and SDS011 energy load
ESP-NOW burst	Short transmission without full Wi-Fi association	Reduces communication energy
Gateway aggregation	NB-IoT modem placed at gateway instead of every node	Reduces per-node cost and energy demand
Adaptive sampling	Increase sampling only during hazard events	Balances detection and battery life

5.4 Energy Budget Model

For one sensing cycle:

$$Q_cycle = I_boot + I_sense + I_proc + I_tx + I_sleep$$

Average current:

$$I_avg = Q_cycle / T_cycle$$

Estimated battery life:

$$Life_hours = C_battery / I_avg$$

Where:

Q_cycle=charge consumed per cycle in mA·s

I_boot=boot current

I_sense=sensor acquisition current

I_proc=processing current

I_tx=transmit current

I_sleep=deep sleep current

T_cycle=sampling period in seconds

C_battery=battery capacity in mAh

6. Protocol Comparison Table

6.1 Communication Protocol Evaluation

The communication strategy must support low payload size, high device density, reduced power consumption, and scalable cloud backhaul. Standard Wi-Fi, LoRaWAN, and the proposed ESP-NOW plus NB-IoT hybrid approach are compared below.

Metric	Standard Wi-Fi	LoRaWAN	ESP-NOW + 5G NB-IoT Hybrid
Typical range	30–100 m in dense urban conditions	2–15 km depending on terrain and gateway placement	ESP-NOW:50–250 m local cluster; NB-IoT:wide-area cellular backhaul
Connection time	Higher due to scanning, authentication, association, DHCP, and reconnection	Low-power scheduled access; constrained by duty-cycle and airtime rules	Very short ESP-NOW local burst; NB-IoT handled by gateway
Payload overhead	High overhead for small telemetry packets	Low payload size but airtime-constrained	Low local overhead with compact frames and gateway aggregation
Device density	Limited by access point capacity, congestion, and contention	High, but constrained by gateway capacity and airtime	High local density with ESP-NOW clusters and shared NB-IoT gateways
Power profile	Higher during frequent reconnection and transmission	Low power for sparse transmissions	Low local node power; cellular energy concentrated at gateway
Infrastructure requirement	Wi-Fi access points and network configuration	LoRa gateways and network server	ESP32 cluster gateway with NB-IoT module
Urban street-canyon reliability	Affected by multipath, interference, and AP availability	Long range but obstruction and urban attenuation may affect reliability	Dense local relays reduce blind spots; gateway placed at optimized location
Data rate	High but unnecessary for small environmental payloads	Low	Appropriate for low-rate telemetry
Cloud integration	Direct IP possible but power-heavy for frequent wakeups	Requires LoRaWAN network integration	Gateway forwards MQTT/HTTPS over NB-IoT
5G mMTC alignment	Moderate	Conceptually similar LPWAN behavior but not 5G-native	Strong alignment through small payloads, dense endpoints, gateway aggregation, and NB-IoT backhaul

6.2 Protocol Selection Rationale

The ESP-NOW and NB-IoT hybrid model is selected because:

- ESP-NOW minimizes local communication overhead.

- ESP32 nodes avoid full Wi-Fi connection setup for every sample.

- NB-IoT provides wide-area cellular IoT connectivity.

- Gateway aggregation reduces per-node cellular cost.

- Compact telemetry aligns with mMTC small-payload behavior.

- Dense deployments improve urban spatial visibility.

7.Real-World Applications

7.1 Smart City Street Canyons

Dense ESP32 nodes can monitor micro-scale pollutant variation in urban street canyons.

Use cases:

- CO monitoring near congested traffic signals
- PM2.5 and PM10 mapping in narrow roads
- Air-quality comparison between main roads and side streets
- Pedestrian exposure monitoring near schools and hospitals
- Construction dust detection
- Traffic management based on environmental conditions
- Urban heat island and pollution correlation

Expected impact:

- Improved street-level air-quality visibility
- Faster detection of localized pollution events
- Data support for low-emission zones and traffic policy
- Enhanced public health exposure mapping

7.2 Industrial Fenceline Safety

Industrial zones require perimeter monitoring to detect dust, smoke, gas, or combustion-related hazards before they spread to nearby communities.

Use cases:

- Cement plant dust monitoring
- Generator yard CO monitoring
- Chemical plant boundary observation
- Warehouse smoke detection
- Waste-processing facility air-quality surveillance
- Industrial compliance support through continuous logs

Expected impact:

- Earlier detection of boundary-level hazards
- Lower-cost distributed monitoring around large sites
- Improved incident response and compliance documentation

7.3 Precision Agriculture

Agricultural fields and greenhouses require distributed climate and air-quality sensing to optimize crop health and detect abnormal environmental conditions.

Use cases:

- Temperature and humidity mapping across fields
- Greenhouse microclimate control
- Smoke intrusion detection
- Dust monitoring during dry seasons
- Storage facility air-quality monitoring
- Pressure-based weather trend observation

Expected impact:

Improved microclimate visibility

Targeted irrigation and ventilation decisions

Early detection of crop-stress conditions

Scalable sensing across large agricultural areas

7.4 Wildfire Early Warning

Wildfire risk regions require distributed sensing for early detection of smoke, heat, humidity drop, and carbon monoxide increase.

Use cases:

Smoke and particulate detection in forest regions

Sudden temperature-rise monitoring

Humidity-drop alerts

CO detection from early combustion

Solar-powered remote monitoring

Gateway-based alert transmission from watchtowers or high points

Expected impact:

Faster early warning

Improved monitoring in remote areas

Reduced dependence on visual detection alone

Support for emergency response prioritization

8. Conclusion & Strategic Roadmap

8.1 Conclusion

The proposed ESP32-based IoT network provides an economical engineering approach to resolving urban environmental monitoring spatial blind spots. Sparse CAAQMS stations remain essential for regulatory-grade measurement, but they cannot alone provide fine-grained environmental visibility at every street, intersection, industrial boundary, and urban canyon. A dense network of low-cost ESP32 sensor nodes can fill this gap by collecting localized measurements and transmitting compact telemetry through a lightweight communication stack.

The core question is addressed through a hybrid 5G mMTC-inspired architecture:

ESP32 nodes emulate mMTC endpoints through small payloads, duty cycling, low unit cost, and high deployment density.

ESP-NOW provides low-overhead local communication suitable for compact environmental telemetry.

NB-IoT gateways provide cellular IoT backhaul aligned with 5G massive machine-type communication principles.

Cloud analytics convert raw telemetry into heatmaps, alerts, trends, and decision-support outputs.

This model improves spatial resolution without requiring expensive monitoring stations at every hotspot. It is technically suitable for smart cities, industrial sites, agricultural regions, and wildfire-prone areas.

8.2 Strategic Roadmap

Roadmap Area	Strategic Action	Expected Outcome
Scalability	Deploy clustered ESP32 nodes with shared NB-IoT gateways	Lower communication cost and improved area coverage
Calibration	Co-locate selected nodes with reference-grade CAAQMS stations	Improved sensor correction and data confidence
Cloud analytics	Implement time-series storage, heatmaps, and threshold alerts	Real-time environmental intelligence
Deployment planning	Prioritize street canyons, traffic hotspots, schools, hospitals, and industrial fencelines	Maximum benefit from dense sensing
Power optimization	Use deep sleep, adaptive sampling, solar support, and sensor duty cycling	Extended node lifetime
Reliability	Add packet sequence numbers, CRC checks, buffering, and watchdog timers	Improved data continuity
Security	Use authenticated gateways, encrypted cloud communication, and controlled dashboard access	Reduced risk of data tampering
Future intelligence	Integrate machine learning for drift correction and anomaly detection	Improved long-term accuracy and automated event detection

8.3 Future Scope

Future development can include:

Machine-learning-based calibration and drift compensation

Adaptive sampling based on weather, traffic, and prior hazard probability

Integration with GIS-based urban digital twins

Mobile sensor nodes mounted on buses and municipal vehicles

Advanced NB-IoT power-saving modes such as PSM and eDRX

Gateway-level edge AI anomaly detection

Reference-station hybrid calibration frameworks

Expanded sensor support for NO₂, SO₂, O₃, and VOC modules

Integration with traffic control, public health dashboards, and emergency response systems

The proposed architecture demonstrates a practical pathway toward dense, scalable, and economically viable smart environmental monitoring inspired by 5G mMTC design principles.