R0 PROTOTYPE — NOT HARDWARE VERIFIED

Waveshare Core2350B2 carrier; initial scope: 32 KiB / no MBC

U1
SN74LVC245APWR

U2
SN74LVC245APWR

U3
SN74LVC245APWR

M1
Core2350B2 (31692)

U4
SN74LVC8T245PWR

U5
SN74LVC1G10DBVR

U6
SN74LVC1G332DBVR

Read enable: /OE = /RD OR A15 OR NOT(VALID AND /WR AND /RESET)

VALID is cleared for every read, then asserted only after correct data is loaded.

PWR_FLAG MOD_VBUS

Q1
2N7002

D1
SS14

R1
4.7k

R2
10k

R3
10k

J1
GAME BOY 32 CONTACTS

C1
100nF

C2
100nF

C3
100nF

C4
100nF

C5
100nF

C6
100nF

C7
100nF

C8
10uF

R4
33

R5
33

R6
33

R7
33

R8
33

R9
33

R10
33

R11
33

Module: hand-assembly. J1: PCB fingers. All other parts: PCBA.

Electrical / mechanical validation required

Sheet: /
File: romcart.kicad_sch

Title: RP2350B ROM cartridge — Core2350B2 carrier

Size: A2	Date: 2026-10-12	**Rev: R0 prototype**
KiCad E.D.A. 10.0.6		Id: 1/1