Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th
D6R XL DS (US)	5LN	95-02	175/—	19 200 (42,300)	1.88 (6'2")	4.08 (13'4")	PS						
					2.64 (8'8")	3.20 (10'6")		3.9 (2.4)	6.8 (4.2)	11.9 (7.6)			
D6R XL DS (BRAZIL)	7GR	96-02	175/—	19 200 (42,300)	1.88 (6'2")	4.08 (13'4")	PS						
					2.64 (8'8")	3.20 (10'6")		3.9 (2.4)	6.8 (4.2)	11.9 (7.6)			
D6R XL DS (FRANCE)	9BM	96-01	175/—	19 200 (42,300)	1.88 (6'2")	4.08 (13'4")	PS						
					2.64 (8'8")	3.20 (10'6")		3.9 (2.4)	6.8 (4.2)	11.9 (7.6)			
D6R XL DS (JAPAN)	5RR	97-02	175/—	19 200 (42,300)	1.88 (6'2")	4.08 (13'4")	PS						
					2.64 (8'8")	3.20 (10'6")		3.9 (2.4)	6.8 (4.2)	11.9 (7.6)			
D6R XR CB (US)	6JN	95-02	175/—	18 780 (41,400)	1.88 (6'2")	4.22 (13'10")	PS						
					2.64 (8'8")	3.19 (10'5")		4.0 (2.5)	7.1 (4.4)	12.4 (7.7)			
D6R XR CB (FRANCE)	8XN	97-01	175/—	18 780 (41,400)	1.88 (6'2")	4.22 (13'10")	PS						
					2.64 (8'8")	3.19 (10'5")		4.0 (2.5)	7.1 (4.4)	12.4 (7.7)			
D6R XR CB (JAPAN)	6HR	97-02	175/—	18 780 (41,400)	1.88 (6'2")	4.22 (13'10")	PS						
					2.64 (8'8")	3.19 (10'5")		4.0 (2.5)	7.1 (4.4)	12.4 (7.7)			
D6R XR DS (US)	7KN	95-02	175/—	18 910 (41,700)	1.88 (6'2")	4.22 (13'10")	PS						
					2.64 (8'8")	3.19 (10'5")		3.9 (2.4)	6.8 (4.2)	11.9 (7.6)			
D6R XR DS (FRANCE)	9MN	97-01	175/—	18 910 (41,700)	1.88 (6'2")	4.22 (13'10")	PS						
					2.64 (8'8")	3.19 (10'5")		3.9 (2.4)	6.8 (4.2)	11.9 (7.6)			
D6R XR DS (JAPAN)	7DR	97-02	175/—	18 910 (41,700)	1.88 (6'2")	4.22 (13'10")	PS						
					2.64 (8'8")	3.19 (10'5")		3.9 (2.4)	6.8 (4.2)	11.9 (7.6)			
D6R LGP CB (US)	8LN	95-02	185/—	20 500 (45,200)	2.23 (7'3")	4.24 (13'11")	PS						
					3.43 (11'3")	3.19 (10'5")		4.0 (2.5)	7.1 (4.4)	12.4 (7.7)			
D6R LGP CB (FRANCE)	4HN	97-01	185/—	20 500 (45,200)	2.23 (7'3")	4.24 (13'11")	PS						
					3.43 (11'3")	3.19 (10'5")		4.0 (2.5)	7.1 (4.4)	12.4 (7.7)			

NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th
D6R LGP CB (JAPAN)	7AR	97-01	185/—	20 500 **(45,200)**	2.23 **(7'3")**	4.24 **(13'11")**	PS						
					3.43 **(11'3")**	3.19 **(10'5")**		4.0 **(2.5)**	7.1 **(4.4)**	12.4 **(7.7)**			
D6R LGP DS (US)	9PN	95-02	185/—	20 680 **(45,600)**	2.23 **(7'3")**	4.24 **(13'11")**	PS						
					3.43 **(11'3")**	3.19 **(10'5")**		3.9 **(2.4)**	6.8 **(4.2)**	11.9 **(7.6)**			
D6R LGP DS (FRANCE)	8TM	96-01	185/—	20 680 **(45,600)**	2.23 **(7'3")**	4.24 **(13'11")**	PS						
					3.43 **(11'3")**	3.19 **(10'5")**		3.9 **(2.4)**	6.8 **(4.2)**	11.9 **(7.6)**			
D6R LGP DS (JAPAN)	4TR	96-02	185/—	20 680 **(45,600)**	2.23 **(7'3")**	4.24 **(13'11")**	PS						
					3.43 **(11'3")**	3.19 **(10'5")**		3.9 **(2.4)**	6.8 **(4.2)**	11.9 **(7.6)**			
D6R LGP DD (JAPAN)	6GR	95-02	185/—	20 680 **(45,600)**	2.23 **(7'3")**	4.24 **(13'11")**	PS						
					3.43 **(11'3")**	3.19 **(10'5")**		3.4 **(2.1)**	5.9 **(3.7)**	10.4 **(6.5)**			
D6M XL (FR)	9ZM	96-02	104/140	15 530 **(34,240)**	1.89 **(6'2")**	3.74 **(12'3")**	PS	30 493 **(67,222)**	16 643 **(36,689)**	9211 **(20,306)**			
					2.49* **(8'2")***	3.08** **(10'1")****		3.4 **(2.1)**	6.0 **(3.7)**	10.3 **(6.4)**			
D6M XL (FR)	3WN	96-02	104/140	15 530 **(34,240)**	1.89 **(6'2")**	3.74 **(12'3")**	PS	30 493 **(67,222)**	16 643 **(36,689)**	9211 **(20,306)**			
					2.49* **(8'2")***	3.08** **(10'1")****		3.4 **(2.1)**	6.0 **(3.7)**	10.3 **(6.4)**			
D6M LGP (FR)	2RN	96-02	104/140	16 930 **(37,320)**	2.16 **(7'1")**	4.146 **(13'7")**	PS	30 493 **(67,222)**	16 643 **(36,689)**	9211 **(20,306)**			
					3.02* **(9'11")***	3.194** **(10'6")****		3.4 **(2.1)**	6.0 **(3.7)**	10.3 **(6.4)**			
D6M LGP (FR)	4JN	96-02	104/140	16 930 **(37,320)**	2.16 **(7'1")**	4.146 **(13'7")**	PS	30 493 **(67,222)**	16 643 **(36,689)**	9211 **(20,306)**			
					3.02* **(9'11")***	3.194** **(10'6")****		3.4 **(2.1)**	6.0 **(3.7)**	10.3 **(6.4)**			
D6R SII STD CB (FTC) (US)	AEM	02-05	123/165	17 826 **(39,300)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.4)**	6.6 **(4.1)**	11.5 **(7.2)**			
D6R SII STD CB (FTC) (BRAZIL)	BRJ	02-06	123/165	17 826 **(39,300)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.4)**	6.6 **(4.1)**	11.5 **(7.2)**			
D6R SII STD CB (FTC) (FRANCE)	BLE	01-05	123/165	17 826 **(39,300)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.4)**	6.6 **(4.1)**	11.5 **(7.2)**			

*Width without blade and with standard shoes.
**Height with ROPS cab.
NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th
D6R SII STD CB (FTC) (JAPAN)	BMK	01-06	123/165	17 826 **(39,300)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.4)**	6.6 **(4.1)**	11.5 **(7.2)**			
D6R SII STD DS (US)	AFM	01-05	123/165	18 099 **(39,900)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.3)**	6.6 **(4.1)**	11.4 **(7.1)**			
D6R SII STD DS (BRAZIL)	BPM	03-06	123/165	18 099 **(39,900)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.3)**	6.6 **(4.1)**	11.4 **(7.1)**			
D6R SII STD DS (FRANCE)	BLT	02-05	123/165	18 099 **(39,900)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.3)**	6.6 **(4.1)**	11.4 **(7.1)**			
D6R SII STD DS (JAPAN)	BNL	01-06	123/165	18 099 **(39,900)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.3)**	6.6 **(4.1)**	11.4 **(7.1)**			
D6R SII XL CB (FTC) (US)	AGM	00-05	138/185	18 711 **(41,250)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.4)**	6.6 **(4.1)**	11.5 **(7.2)**			
D6R SII XL CB (FTC) (BRAZIL)	CAD	02-06	138/185	18 711 **(41,250)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.4)**	6.6 **(4.1)**	11.5 **(7.2)**			
D6R SII XL CB (FTC) (FRANCE)	BMJ	02-05	138/185	18 711 **(41,250)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.4)**	6.6 **(4.1)**	11.5 **(7.2)**			
D6R SII XL CB (FTC) (JAPAN)	BPS	01-06	138/185	18 711 **(41,250)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.4)**	6.6 **(4.1)**	11.5 **(7.2)**			
D6R SII XL DS (US)	AAX	00-05	138/185	18 847 **(41,550)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.3)**	6.6 **(4.1)**	11.4 **(7.1)**			
D6R SII XL DS (BRAZIL)	FDT	02-06	138/185	18 847 **(41,550)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.3)**	6.6 **(4.1)**	11.4 **(7.1)**			
D6R SII XL DS (FRANCE)	BMY	01-05	138/185	18 847 **(41,550)**	1.88 **(6'2")**	3.86 **(12'8")**	PS						
					2.64 **(8'8")**	3.2 **(10'6")**		3.8 **(2.3)**	6.6 **(4.1)**	11.4 **(7.1)**			

NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th
D6R SII XL	BRZ	01-06	138/185	18 847	1.88	3.86	PS						
DS				**(41,550)**	**(6'2")**	**(12'8")**							
(JAPAN)					2.64	3.2		3.8	6.6	11.4			
					(8'8")	**(10'6")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SII XW	AEP	2001	138/185	19 550	2.03	3.86	PS						
DS				**(43,100)**	**(6'8")**	**(12'8")**							
(US)					2.95	3.2		3.8	6.6	11.4			
					(9'8")	**(10'6")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SII XW	DAE	02-05	138/185	19 550	2.03	3.86	PS						
DS				**(43,100)**	**(6'8")**	**(12'8")**							
(FRANCE)					2.95	3.2		3.8	6.6	11.4			
					(9'8")	**(10'6")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SII XW	BRE	01-06	138/185	19 550	2.03	3.86	PS						
DS				**(43,100)**	**(6'8")**	**(12'8")**							
(JAPAN)					2.95	3.2		3.8	6.6	11.4			
					(9'8")	**(10'6")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SII LGP	ACJ	01-05	138/185	20 865	2.23	4.24	PS						
CB (FTC)				**(46,000)**	**(7'3")**	**(13'11")**							
(US)					3.43	3.25		3.8	6.6	11.5			
					(11'3")	**(10'8")**		**(2.4)**	**(4.1)**	**(7.2)**			
D6R SII LGP	BPP	01-06	138/185	20 865	2.23	4.24	PS						
CB (FTC)				**(46,000)**	**(7'3")**	**(13'11")**							
(JAPAN)					3.43	3.25		3.8	6.6	11.5			
					(11'3")	**(10'8")**		**(2.4)**	**(4.1)**	**(7.2)**			
D6R SII LGP	ADE	00-05	138/185	21 047	2.23	4.24	PS						
DS				**(46,400)**	**(7'3")**	**(13'11")**							
(US)					3.43	3.25		3.8	6.6	11.4			
					(11'3")	**(10'8")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SII LGP	BNC	01-05	138/185	21 047	2.23	4.24	PS						
DS				**(46,400)**	**(7'3")**	**(13'11")**							
(FRANCE)					3.43	3.25		3.8	6.6	11.4			
					(11'3")	**(10'8")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SII LGP	BPZ	01-06	138/185	21 047	2.23	4.24	PS						
DS				**(46,400)**	**(7'3")**	**(13'11")**							
(JAPAN)					3.43	3.25		3.8	6.6	11.4			
					(11'3")	**(10'8")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII			138/185	18 326	1.88	3.86	PS						
(US)	HCD	05-07		**(40,400)**	**(6'2")**	**(12'8")**							
(BRAZIL)	GMT	06-07				3.20		3.8	6.6	11.4			
(FRANCE)	TBC	06-07				**(10'6")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII	JEK	06-10	138/185	18 326	1.88	2.67	PS	3.8	6.6	11.4			
(JAPAN)				**(40,400)**	**(6'2")**	**(8'9")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII XL			149/200	20 081	1.88	3.86	PS						
(US)	GJB	05-07		**(44,270)**	**(6'2")**	**(12'8")**							
(BRAZIL)	JDL	05-07			2.13	3.20		3.8	6.6	11.4			
(FRANCE)	LFM	06-07			**(7'0")**	**(10'6")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII XL	EXL	06-12	149/200	20 081	1.88	2.87	PS	3.8	6.6	11.4			
(JAPAN)				**(44,270)**	**(6'2")**	**(9'5")**		**(2.3)**	**(4.1)**	**(7.1)**			

NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th
D6R SIII XL			149/200	20 081	1.88	3.86	PS						
PAT (US)	HKE	05-07		**(44,270)**	**(6'2")**	**(12'8")**							
(FRANCE)	RFC	06-07			2.13	3.20		3.8	6.6	11.4			
					(7'0")	**(10'6")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII XW			149/200	20 672	2.03	3.86	PS						
(US)	MRT	05-07		**(45,573)**	**(6'8")**	**(12'8")**							
(BRAZIL)	DPS	06-07			2.29	3.20		3.8	6.6	11.4			
					(7'6")	**(10'6")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII XW			149/200	20 672	2.03	3.86	PS						
PAT (US)	HDC	05-07		**(45,573)**	**(6'8")**	**(12'8")**							
(FRANCE)	MTJ	05-07			2.29	3.20		3.8	6.6	11.4			
					(7'6")	**(10'6")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII XW	EXW	07-09	149/200	20 672	2.03	2.87	PS	3.8	6.6	11.4			
(JAPAN)				**(45,573)**	**(6'8")**	**(9'5")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII LGP			149/200	21 716	2.29	4.25	PS						
(US)	WRG	05-07		**(47,874)**	**(7'6")**	**(13'11")**							
(FRANCE)	DMK	06-07			2.29	3.25		3.8	6.6	11.4			
					(7'6")	**(10'8")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII LGP	LGP	06-12	149/200	21 716	2.29	3.28	PS	3.8	6.6	11.4			
(JAPAN)				**(47,874)**	**(7'6")**	**(10'9")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6R SIII LGP			149/200	21 716	2.29	4.25	PS						
PAT (US)	WCB	05-07		**(47,874)**	**(7'6")**	**(13'11")**							
(FRANCE)	DLM	05-07			2.29	3.25		3.8	6.6	11.4			
					(7'6")	**(10'8")**		**(2.3)**	**(4.1)**	**(7.1)**			
D6T XL*	GMK	11-14	207	21 306	1.88	3.86	PS/DS	36 936	22 343	12 124	12 124		
				(46,791)	**(6'2")**	**(12'8")**		**(81,430)**	**(49,260)**	**(26,730)**	**(26,730)**		
					2.64	3.13		3.8	5.1	8.5	11.4		
					(8'8")	**(10'2")**		**(2.3)**	**(3.2)**	**(5.3)**	**(7.1)**		
D6T XL	DTD	11-14	207	23 663	2.13	3.86	PS/DS	36 936	22 343	12 124	12 124		
VPAT*				**(52,167)**	**(7'0")**	**(12'8")**		**(81,430)**	**(49,260)**	**(26,730)**	**(26,730)**		
						3.13		3.8	5.1	8.5	11.4		
						(10'2")		**(2.3)**	**(3.2)**	**(5.3)**	**(7.1)**		
D6T XW*	SLJ	11-14	207	22 191	2.03	3.86	PS/DS	36 936	22 343	12 124	12 124		
				(48,922)	**(6'8")**	**(12'8")**		**(81,430)**	**(49,260)**	**(26,730)**	**(26,730)**		
					2.95	3.13		3.8	5.1	8.5	11.4		
					(9'8")	**(10'2")**		**(2.3)**	**(3.2)**	**(5.3)**	**(7.1)**		
D6T XW	RCW	11-14	207	24 118	2.29	4.25	PS/DS	36 936	22 343	12 124	12 124		
VPAT*				**(53,170)**	**(7'6")**	**(13'11")**		**(81,430)**	**(49,260)**	**(26,730)**	**(26,730)**		
						3.18		3.8	5.1	8.5	11.4		
						(10'5")		**(2.3)**	**(3.2)**	**(5.3)**	**(7.1)**		
D6T LGP*	ZJB	11-14	207	24 020	2.29	4.25	PS/DS	36 936	22 343	12 124	12 124		
				(52,954)	**(7'6")**	**(13'11")**		**(81,430)**	**(49,260)**	**(26,730)**	**(26,730)**		
					3.48	3.18		3.8	5.1	8.5	11.4		
					(11'5")	**(10'5")**		**(2.3)**	**(3.2)**	**(5.3)**	**(7.1)**		
D6T LGP	KSB	11-14	207	22 009	2.29	4.25	PS/DS	36 936	22 343	12 124	12 124		
VPAT*				**(48,521)**	**(7'6")**	**(13'11")**		**(81,430)**	**(49,260)**	**(26,730)**	**(26,730)**		
						3.18		3.8	5.1	8.5	11.4		
						(10'5")		**(2.3)**	**(3.2)**	**(5.3)**	**(7.1)**		

*Emits equivalent to Tier 4 Interim/Stage IIIB/Japan 2011 (Tier 4 Interim).
NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th
D7	3T	54-55	108/90	11 770	1.88	4.27	DD						
				(25,925)	**(6'2")**	**(14'0")**							
					2.64	2.06							
					(8'1")	**(6'10")**							
D7C	17A	55-59	128/102	11 954	1.88	4.26	DD	11 759	8045	4521	3428	2397	
				(26,355)	**(6'2")**	**(14'0")**		**(25,900)**	**(17,720)**	**(11,960)**	**(7550)**	**(5280)**	
					2.64	2.06		2.4	3.5	5.2	7.4	9.5	
					(8'1")	**(6'10")**		**(1.5)**	**(2.2)**	**(3.2)**	**(4.6)**	**(5.9)**	
D7D	17A	59-61	140/112	12 056	1.88	4.26	DD	12 300	8600	5700	3650	2600	
				(26,555)	**(6'2")**	**(14'0")**		**(27,100)**	**(18,900)**	**(12,550)**	**(8080)**	**(5720)**	
					2.64	2.06		2.4	3.5	5.2	7.4	9.5	
					(8'1")	**(6'10")**		**(1.5)**	**(2.2)**	**(3.2)**	**(4.6)**	**(5.9)**	
D7E	47A	61-68	160/128	14 787	1.98	4.47	DD	14 741	10 296	6803	4259	3070	
				(32,590)	**(6'6")**	**(14'8")**		**(32,500)**	**(22,700)**	**(15,000)**	**(9390)**	**(6770)**	
					2.56	2.30		2.4	3.5	4.9	7.4	9.4	
					(8'5")	**(7'7")**		**(1.5)**	**(2.2)**	**(3.1)**	**(4.6)**	**(5.9)**	
D7E	48A	61-66	160/128	14 787	1.98	4.47	PS						
				(32,590)	**(6'6")**	**(14'8")**							
					2.56	2.30		3.3	5.7	9.3			
					(8'5")	**(7'7")**		**(2.1)**	**(3.6)**	**(5.8)**			
D7E	47A	66-69	180/144	15 200	1.98	4.47	DD	17 140	11 350	7420	4540	3180	
				(33,500)	**(6'6")**	**(14'8")**		**(37,750)**	**(25,000)**	**(16,340)**	**(9990)**	**(7010)**	
					2.56	2.18		2.4	3.5	5.0	7.4	9.5	
					(8'5")	**(7'2")**		**(1.5)**	**(2.2)**	**(3.1)**	**(4.6)**	**(5.9)**	
D7E	48A	66-69	180	15 500	1.98	4.47	PS						
				(34,000)	**(6'6")**	**(14'8")**							
					2.56	2.18		3.7	6.4	10.1			
					(8'5")	**(7'2")**		**(2.3)**	**(4.0)**	**(6.3)**			
D7E*	TAN	10-14	235	26 055	1.98	4.6	E						
				(57,441)	**(6'6")**	**(15'1")**							
					2.88	3.36							
					(9'5")	**(11'0")**							
D7E LGP*	TJA	10-14	235	28 525	2.28	4.6	E						
				(62,886)	**(7'6")**	**(15'1")**							
					3.42	3.36							
					(11'3")	**(11'0")**							
D7F	94N	69-74	180	14 700	1.98	4.15	PS						
				(32,400)	**(6'6")**	**(13'8")**							
					2.56	2.26		3.5	6.3	9.5			
					(8'5")	**(7'5")**		**(2.2)**	**(3.9)**	**(5.9)**			
D7F	93N	69-74	180	14 700	1.98	4.15	DD	17 100	11 350	7450	4580	3240	
				(32,400)	**(6'6")**	**(13'8")**		**(37,600)**	**(25,000)**	**(16,400)**	**(10,000)**	**(7140)**	
					2.56	2.26		2.4	3.5	5.0	7.4	9.5	
					(8'5")	**(7'5")**		**(1.5)**	**(2.2)**	**(3.4)**	**(4.6)**	**(5.9)**	

*Emits equivalent to Tier 4 Interim/Stage IIIB/Japan 2011 (Tier 4 Interim).
NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th
D7G	92V	77-86	200	20 090	1.98	4.19	PS						
				(44,300)	**(6'6")**	**(13'9")**							
					2.62	3.35		3.7	6.4	10.0			
					(8'7")	**(11'0")**		**(2.3)**	**(4.0)**	**(6.2)**			
D7G	91V	77-86	200	20 090	1.98	4.19	DD	17 690	11 730	7680	4700	3320	
				(44,300)	**(6'6")**	**(13'9")**		**(39,010)**	**(25,860)**	**(16,940)**	**(10,370)**	**(7320)**	
					2.62	3.35		2.5	3.7	5.3	7.8	10.1	
					(8'7")	**(11'0")**		**(1.6)**	**(2.3)**	**(3.3)**	**(4.9)**	**(6.3)**	
D7G (JAPAN)	65V	75-07	149/200	20 580	1.98	2.72	PS	3.7	6.4	10.0			
				(45,381)	**(6'6")**	**(8'11")**		**(2.3)**	**(4.0)**	**(6.2)**			
D7G (INDONESIA)	7MB	83-07	149/200	20 580	1.98	2.72	PS	3.7	6.4	10.0			
				(45,381)	**(6'6")**	**(8'11")**		**(2.3)**	**(4.0)**	**(6.2)**			
D7G LGP	72W	77-86	200	22 630	2.18	4.22	PS						
				(52,100)	**(7'2")**	**(13'9")**							
					3.3	3.28		3.7	6.4	10.0			
					(10'11")	**(10'9")**		**(2.3)**	**(4.0)**	**(6.2)**			
D7G SII (INDONESIA)	7MB	08-12	149/200	20 580	1.98	2.72	PS	3.7	6.4	10.0			
				(45,381)	**(6'6")**	**(8'11")**		**(2.3)**	**(4.0)**	**(6.2)**			
D7G SII (CHINA)	C7G	06-11	149/200	20 580	1.98	2.72	PS	3.7	6.4	10.0			
				(45,381)	**(6'6")**	**(8'11")**		**(2.3)**	**(4.0)**	**(6.2)**			
D7H (CB)	79Z	92-96	171/230	24 778	1.98	4.74	PS						
	(E. Peoria)			**(54,635)**	**(6'6")**	**(15'6")**							
	4AB				3.9	3.5		3.5	6.2	10.6			
	(Sagami)				**(12'10")**	**(11'6")**		**(2.2)**	**(3.8)**	**(6.6)**			
D7H (DS)	5BF	92-96	171/230	25 077	1.98	4.74	PS						
	(E. Peoria)			**(55,295)**	**(6'6")**	**(15'6")**							
	2RG				3.9	3.5		3.5	6.2	10.6			
	(Sagami)				**(12'10")**	**(11'6")**		**(2.2)**	**(3.8)**	**(6.6)**			
D7H LGP (CB)	80Z	92-96	171/230	27 065	2.24	4.74	PS						
	(E. Peoria)			**(59,678)**	**(7'4")**	**(15'6")**							
	5WB				4.50	3.58		3.5	6.2	10.6			
	(Sagami)				**(14'9")**	**(11'9")**		**(2.2)**	**(3.8)**	**(6.6)**			
D7H LGP (DS)	4FG	92-96	171/230	27 065	2.24	4.74	PS						
	(E. Peoria)			**(59,678)**	**(7'4")**	**(15'6")**							
	3XG				4.50	3.58		3.5	6.2	10.6			
	(Sagami)				**(14'9")**	**(11'9")**		**(2.2)**	**(3.8)**	**(6.6)**			
D7H XR (CB)	79Z	92-96	171/230	25 193	1.98	4.74	PS						
	(E. Peoria)			**(55,551)**	**(6'6")**	**(15'6")**							
	4AB				3.9	3.5		3.5	6.2	10.6			
	(Sagami)				**(12'10")**	**(11'6")**		**(2.2)**	**(3.8)**	**(6.6)**			
D7H XR (DS)	5BF	92-96	171/230	25 492	1.98	4.74	PS						
	(E. Peoria)			**(56,211)**	**(6'6")**	**(15'6")**							
	2RG				3.9	3.5		3.5	6.2	10.6			
	(Sagami)				**(12'10")**	**(11'6")**		**(2.2)**	**(3.8)**	**(6.6)**			
D7H	77Z	85-86	215	19 680	1.98	4.73	DD	16 834	12 861	9703	7436	5522	3940
				(43,380)	**(6'6")**	**(15'6")**		**(37,113)**	**(28,353)**	**(21,390)**	**(16,394)**	**(12,173)**	**(8686)**
					2.54			2.7	3.5	4.5	5.8	7.6	10.0
					(8'5")			**(1.7)**	**(2.2)**	**(2.8)**	**(3.6)**	**(4.7)**	**(6.2)**
D7H (US)	79Z*	85-90	215/—	23 647	1.981	4.619	PS						
				(52,134)	**(6'6")**	**(15'2")**							
					2.869	3.421		3.9	6.8	11.9			
					(9'5")	**(11'3")**		**(2.4)**	**(4.2)**	**(7.4)**			

*D7H models prior to Series II. Product identification number prefix still in use for current product.
NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th
D7H (US)	77Z	85-90	215/—	23 570	1.981	4.619	DD	16 834	12 861	9703	7436	5522	3940
				(51,960)	**(6'6")**	**(15'2")**		**(37,113)**	**(28,353)**	**(21,390)**	**(16,394)**	**(12,173)**	**(8686)**
					2.869	3.421		2.7	3.5	4.6	5.8	7.6	10.0
					(9'5")	**(11'3")**		**(1.7)**	**(2.2)**	**(2.8)**	**(3.6)**	**(4.7)**	**(6.2)**
D7H (US)	5BF*	88-90	215/—	24 351	1.981	4.624	PS/DS						
				(53,683)	**(6'6")**	**(15'2")**							
					2.871	3.429		3.7	6.4	11.1			
					(9'5")	**(11'3")**		**(2.3)**	**(4.0)**	**(6.9)**			
D7H (JPN)	4AB*	86-90	215/—	23 647	1.981	4.619	PS						
				(52,134)	**(6'6")**	**(15'2")**							
					2.869	3.421		3.9	6.8	11.9			
					(9'5")	**(11'3")**		**(2.4)**	**(4.2)**	**(7.4)**			
D7H (JPN)	2SB*	86-91	215/—	23 570	1.981	4.619	DD	16 834	12 861	9703	7436	5522	3940
				(51,960)	**(6'6")**	**(15'2")**		**(37,113)**	**(28,353)**	**(21,390)**	**(16,394)**	**(12,173)**	**(8686)**
					2.869	3.421		2.7	3.5	4.6	5.8	7.6	10.0
					(9'5")	**(11'3")**		**(1.7)**	**(2.2)**	**(2.8)**	**(3.6)**	**(4.7)**	**(6.2)**
D7H (JPN)	2RG*	88-90	215/—	24 351	1.981	4.624	PS/DS						
				(53,683)	**(6'6")**	**(15'2")**							
					2.871	3.429		3.7	6.4	11.1			
					(9'5")	**(11'3")**		**(2.3)**	**(4.0)**	**(6.9)**			
D7R LGP (JPN)	6ER	96-02	179 **(240)**	30 605 **(67,472)**	2.24 **(7'4")**	5.8 **(19'0")**	PS/DS	3.5 **(2.3)**	6.4 **(4.0)**	10.8 **(6.8)**			
D7H LGP (JPN)	5WB*	86-90	215/—	25 237 **(55,638)**	2.235 **(7'4")**	4.619 **(15'2")**	PS						
					3.371 **(11'1")**	3.503 **(11'6")**		3.9 **(2.4)**	6.8 **(4.2)**	11.9 **(7.4)**			
D7H LGP (JPN)	82Z*	86-91	215/—	25 445 **(56,096)**	2.235 **(7'4")**	4.619 **(15'2")**	DD	16 834 **(37,113)**	12 861 **(28,353)**	9703 **(21,390)**	7436 **(16,394)**	5522 **(12,173)**	3940 **(8686)**
					3.371 **(11'1")**	3.503 **(11'6")**		2.7 **(1.7)**	3.5 **(2.2)**	4.6 **(2.8)**	5.8 **(3.6)**	7.6 **(4.7)**	10.0 **(6.2)**
D7H LGP (JPN)	3XG*	88-90	230/—	25 894 **(57,086)**	2.235 **(7'4")**	4.624 **(15'2")**	PS/DS						
					3.377 **(11'1")**	3.505 **(11'6")**		3.7 **(2.3)**	6.4 **(4.0)**	11.1 **(6.9)**			
D7R STD (US)	2HR	95-01	171 **(230)**	27 413 **(60,436)**	2.0 **(6'6")**	6.04 **(19'9")**	PS/FTC	3.5 **(2.3)**	6.4 **(4.0)**	10.8 **(6.8)**			
D7R STD	3ZR	96-02	171 **(230)**	27 413 **(60,436)**	2.0 **(6'6")**	6.04 **(19'9")**	PS/FTC	3.5 **(2.3)**	6.4 **(4.0)**	10.8 **(6.8)**			
D7R SII STD (JAPAN)	BRM	02-12	179/240	25 455 **(56,129)**	1.98 **(6'6")****	2.87 **(9'5")†**	PS	3.52 **(2.19)**	6.10 **(3.79)**	10.54 **(6.55)**			
D7R SII STD (US)	AEC	00-10	179/240	25 455 **(56,129)**	1.98 **(6'6")****	2.87 **(9'5")†**	PS	3.52 **(2.19)**	6.10 **(3.79)**	10.54 **(6.55)**			
D7R XR (US)	2EN	95-01	171 **(230)**	27 776 **(61,236)**	2.0 **(6'6")**	6.04 **(19'9")**	PS/DS	3.5 **(2.3)**	6.4 **(4.0)**	10.8 **(6.8)**			
D7R XR	5MR	97-02	171 **(230)**	27 776 **(61,236)**	2.0 **(6'6")**	6.04 **(19'9")**	PS/DS	3.5 **(2.3)**	6.4 **(4.0)**	10.8 **(6.8)**			
D7R SII XR (JAPAN)	BPT	03-12	179/240	27 002 **(59,540)**	1.98 **(6'6")****	3.05 **(10'0")†**	PS	3.52 **(2.19)**	6.10 **(3.79)**	10.54 **(6.55)**			
D7R SII XR (US)	AGN	00-10	179/240	27 002 **(59,540)**	1.98 **(6'6")****	3.05 **(10'0")†**	PS	3.52 **(2.19)**	6.10 **(3.79)**	10.54 **(6.55)**			
D7H LGP (US)	80Z*	85-90	215/—	25 237 **(55,638)**	2.235 **(7'4")**	4.619 **(15'2")**	PS						
					3.371 **(11'1")**	3.503 **(11'6")**		3.9 **(2.4)**	6.8 **(4.2)**	11.9 **(7.4)**			

*D7H models prior to Series II. Product identification number prefix still in use for current product.
**D7R SII STD, XR and LGP machine width is for without trunnion.
†D7R SII STD, XR and LGP machine height is over EROPS, length is for basic machine.
NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th	Remarks
D7R LGP	4SR	96-02	179	29 500	2.24	5.8	PS/FTC	3.5	6.4	10.8				
			(240)	**(65,036)**	**(7'4")**	**(19'0")**		**(2.3)**	**(4.0)**	**(6.8)**				
D7H LGP (US)	4FG*	87-90	230/—	25 894	2.235	4.624	PS/DS							
				(57,086)	**(7'4")**	**(15'2")**								
					3.377	3.505		3.7	6.4	11.1				
					(11'1")	**(11'6")**		**(2.3)**	**(4.0)**	**(6.9)**				
D7R LGP (US)	3DN	95-01	179	30 605	2.24	5.8	PS/DS	3.5	6.4	10.8				
			(240)	**(67,472)**	**(7'4")**	**(19'0")**		**(2.3)**	**(4.0)**	**(6.8)**				
D7R LGP (US)	9HM	95-01	179	29 500	2.24	5.8	PS/FTC	3.5	6.4	10.8				
			(240)	**(65,036)**	**(7'4")**	**(19'0")**		**(2.3)**	**(4.0)**	**(6.8)**				
D7E	MDB	10-11	175	25 700	1.98	4.88	ED**							
			(235)	**(56,669)**	**(6'6")**	**(16'0")**								
					2.88	3.32		FORWARD 11.3 **(7.0)**						
					(9'5")	**(10'11")**		REVERSE 11.3 **(7.0)**						
D7R SII LGP	BNX	01-12	179/240	27 626	2.24	3.16	PS	3.52	6.10	10.54				
				(60,916)	**(7'4")†**	**(10'5")††**		**(2.19)**	**(3.79)**	**(6.55)**				
D7R SII LGP	ABJ	00-10	179/240	27 626	2.24	3.16	PS	3.52	6.10	10.54				
				(60,916)	**(7'4")†**	**(10'5")††**		**(2.19)**	**(3.79)**	**(6.55)**				
D7E LGP	SCG	10-11	175	28 170	2.29	4.88	ED**							
			(235)	**(62,115)**	**(7'6")**	**(16'0")**								
					3.42	3.32		FORWARD 11.3 **(7.0)**						
					(11'3")	**(10'11")**		REVERSE 11.3 **(7.0)**						
D8	1H	35-41	110/95	14 790	1.98	4.64	•	9680	6870	5720	4800	3860	2740	
				(32,600)	**(6'6")**	**(15'3")**		**(21,350)**	**(15,150)**	**(12,610)**	**(10,590)**	**(8520)**	**(6050)**	
					2.64	2.28		2.7	3.8	4.5	5.1	6.3	8.5	RD-8 with 192 cm
					(8'8")	**(7'6")**		**(1.7)**	**(2.4)**	**(2.8)**	**(3.2)**	**(3.9)**	**(5.3)**	**(78")** gauge
D8	8R	41-45	131/113	15 490	1.98	4.64	••	13 060	9750	7940	6800	5620	3990	
				(34,160)	**(6'6")**	**(15'3")**		**(28,800)**	**(21,500)**	**(17,500)**	**(15,000)**	**(12,400)**	**(8800)**	
					2.64	1.85		2.5	3.5	4.2	4.8	5.8	7.9	Horsepower
					(8'8")	**(6'1")**		**(1.6)**	**(2.2)**	**(2.6)**	**(3.0)**	**(3.6)**	**(4.9)**	Increase
D8	2U	45-53	148/130	16 470	1.98	4.85	DD	13 560	9840	7120	5400	3900		
				(36,310)	**(6'6")**	**(15'10")**		**(29,900)**	**(21,700)**	**(15,700)**	**(11,900)**	**(8600)**		
					2.64	2.18		2.5	3.7	4.6	5.9	7.7		HP increase,
					(8'8")	**(7'2")**		**(1.6)**	**(2.3)**	**(2.9)**	**(3.7)**	**(4.8)**		DD transmission
D8	13A	53-55	185/150	16 866	1.98	4.88	DD	20 358	12 939	8926	6955	4935		
				(37,150)	**(6'6")**	**(16'1")**		**(44,840)**	**(28,500)**	**(19,660)**	**(15,320)**	**(10,870)**		
					2.64	2.18		3.1	4.3	5.6	7.2	9.3		
					(8'8")	**(7'2")**		**(1.9)**	**(2.7)**	**(3.5)**	**(4.5)**	**(5.8)**		
D8D, G	15A	55-57	191/155	16 310	1.98	5.23	TC							
				(35,925)	**(6'6")**	**(17'2")**								
					2.58	2.23		5.8	8.5	11.9				
					(8'6")	**(7'8")**		**(3.6)**	**(5.3)**	**(7.4)**				
D8E, F	14A	55-57	191/155	17 734	1.98	4.88	DD	20 439	16 135	10 964	7373	4953		
			Belt	**(39,060)**	**(6'6")**	**(16'1")**		**(45,020)**	**(35,540)**	**(24,150)**	**(16,240)**	**(10,910)**		
					2.64	2.26		2.4	3.1	4.5	6.1	8.3		
					(8'8")	**(7'6")**		**(1.5)**	**(1.9)**	**(2.8)**	**(3.8)**	**(5.2)**		
D8H	35A	59-61	235	20 924	2.13	5.20	TC							
				(46,032)	**(7'0")**	**(17'1")**								
					2.87	2.39		5.6	8.2	12.2				
					(9'1")	**(7'10")**		**(3.5)**	**(5.1)**	**(7.6)**				

*D7H models prior to Series II. Product identification number prefix still in use for current product.
**Electric drive machines do not have transmission gears.
†D7R SII STD, XR and LGP machine width is for without trunnion.
††D7R SII STD, XR and LGP machine height is over EROPS, length is for basic machine.
•Power transmitted through dry tape flywheel clutch to selective type hinge speed gear set.
••Power transmitted through flexible and over center engagement, dry flywheel clutch with metallic friction surfaces. Selective type change speed gear set.
NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th	Remarks
D8H	36A	58-66	235/185	21 400	2.13	5.20	DD	19 958	15 648	10 931	8051	5869	3832	
				(47,180)	**(7'0")**	**(17'1")**		**(44,400)**	**(34,500)**	**(24,100)**	**(17,750)**	**(13,000)**	**(8450)**	
					2.87	2.39		2.4	3.0	4.3	5.6	7.4	10.1	
					(9'1")	**(7'10")**		**(1.5)**	**(1.9)**	**(2.7)**	**(3.5)**	**(4.6)**	**(6.3)**	
D8H	46A	58-74	270	21 863	2.13	5.20	PS							
				(48,210)	**(7'0")**	**(17'1")**								
					2.87	2.39		3.8	6.7	10.4				
					(9'1")	**(7'10")**		**(2.4)**	**(4.2)**	**(6.5)**				
D8K	76V	74-82	300	31 980	2.13	5.26	DD	25 400	18 930	12 990	9370	6610	4090	
				(69,300)*	**(7'0")**	**(17'3")**		**(56,000)**	**(41,740)**	**(28,640)**	**(20,650)**	**(14,580)**	**(9010)**	Turbocharged,
					3.05	2.44		2.7	3.5	4.8	6.3	8.2	11.3	Sealed and
					(10'0")	**(8'0")**		**(1.7)**	**(2.2)**	**(3.0)**	**(3.9)**	**(5.1)**	**(7.0)**	Lubricated Track
D8K	77V	74-82	300	31 430	2.13	5.26	PS							
				(70,500)†	**(7'0")**	**(17'3")**								Turbocharged,
					3.05	2.44		4.0	7.1	10.9				Sealed and
					(10'0")	**(8'0")**		**(2.5)**	**(4.4)**	**(6.8)**				Lubricated Track
D8L	53Y	82-86	335	37 305	2.2	4.95	PS							
	7JC	84-90		**(82,243)**	**(7'3")**	**(16'2")**								
	7YB	85-92			2.84	3.79		3.9	6.8	11.9				
					(9'4")	**(12'5")**		**(2.4)**	**(4.2)**	**(7.4)**				
D8L SA	4FB	84-87	400/325	36 650	2.54		DD	31 679	23 115	17 196	12 388	9154	6428	
				(80,820)	**(8'4")**			**(69,840)**	**(50,960)**	**(37,910)**	**(27,310)**	**(20,180)**	**(14,170)**	
					3.11			2.9	3.9	5.0	6.8	8.9	11.9	
					(10'3")			**(1.8)**	**(2.4)**	**(3.1)**	**(4.2)**	**(5.5)**	**(7.4)**	
D8N	9TC	87-92	285	37 462	2.08	4.95	PS							
	5TJ	92-95	285	**(82,590)**	**(6'10")**	**(16'3")**								
					3.05	3.43		3.5	6.2	10.8				
					(10'0")	**(11'3")**		**(2.2)**	**(3.9)**	**(6.7)**				
D8R Series II (US)	6YZ	00-04	310	37 830	2.08	6.91	PS							
				(83,400)	**(6'10")**	**(22'8")**								
					3.05	3.51		3.4	6.0	10.6				
					(10'0")	**(11'6")**		**(2.1)**	**(3.7)**	**(6.6)**				
D8R Series II (BRAZIL)	AKA	2000	231/310	37 830	2.08	6.91	PS							
				(83,400)	**(6'10")**	**(22'8")**								
					3.05	3.51		3.4	6.0	10.6				
					(10'0")	**(11'6")**		**(2.1)**	**(3.7)**	**(6.6)**				
D8T**	MLN-FTC	11-14	271	39 420	2.08	4.55	PS/DS	67 414	37 025	20 139				
				(86,900)	**(6'10")**	**(14'7")**		**(148,621)**	**(81,628)**	**(44,399)**				
					3.06	3.5		3.4	6.1	10.6				
					(10'1")	**(11'6")**		**2.1**	**3.8**	**6.6**				
D8T LGP**	MLN-FTC	11-14	271	37 420	2.33	4.55	PS/DS	67 414	37 025	20 139				
				(82,496)	**(7'8")**	**(14'7")**		**(148,621)**	**(81,628)**	**(44,399)**				
					3.37	3.5		3.4	6.1	10.6				
					(11'1")	**(11'6")**		**2.1**	**3.8**	**6.6**				

*Approximate operating weight. Includes lubricants, coolant, full fuel tank, hydraulic control, 8S Bulldozer, ROPS canopy and operator. All other weights listed in this column are shipping weights.

**Emits equivalent to Tier 4 Interim/Stage IIIB/Japan 2011 (Tier 4 Interim).

†Power transmitted through dry tape flywheel clutch to selective type hinge speed gear set.

NOTE: Power Shift models show speeds only, not drawbar pull.

NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th
D9D	18A	55-56	286/230	25 772	2.29	5.46	DD	27 631	21 207	15 423	10 706	7658	4958
				(56,765)	**(7'6")**	**(17'11")**		**(60,860)**	**(46,710)**	**(33,970)**	**(23,580)**	**(16,670)**	**(10,920)**
					3.03	2.67		2.6	3.4	4.7	6.3	8.1	10.9
					(10'0")	**(8'9")**		**(1.6)**	**(2.1)**	**(2.9)**	**(3.9)**	**(5.0)**	**(6.8)**
D9D	18A	56-59	320/260	26 125	2.29	5.46	DD	28 603	23 835	16 617	12 167	9171	6106
				(57,543)	**(7'6")**	**(17'11")**		**(63,000)**	**(52,500)**	**(36,600)**	**(26,800)**	**(20,200)**	**(13,450)**
					3.03	2.67							
					(10'0")	**(8'9")**							
D9D	19A	55-56	286/230	25 729	2.29	5.46	TC						
				(56,670)	**(7'6")**	**(17'11")**							
					3.03	2.67		6.6	9.0	12.6			
					(10'0")	**(8'9")**		**(4.1)**	**(5.6)**	**(7.8)**			
D9D	19A	56-59	320/260	26 238	2.29	5.46	TC						
				(57,990)	**(7'6")**	**(17'11")**							
					3.03	2.68		6.6	9.5	13.0			
					(10'0")	**(8'9")**		**(4.1)**	**(5.9)**	**(8.1)**			
D9E	50A	59-60	335	27 016	2.29	5.50	TC						
				(59,506)	**(7'6")**	**(18'1")**							
					3.03	2.70		6.8	9.7	13.2			
					(10'0")	**(8'11")**		**(4.2)**	**(6.0)**	**(8.2)**			
D9D	34A	59-61	335	27 167	2.29	5.50	PS						
				(59,837)	**(7'6")**	**(18'1")**							
					3.03	2.70		4.2	7.2	11.2			
					(10'0")	**(8'11")**		**(2.6)**	**(4.5)**	**(7.0)**			
D9E	49A	59-60	335/268	26 957	2.29	5.50	DD						
				(59,375)	**(7'6")**	**(18'1")**							
					3.03	2.70		2.7	3.5	4.8	6.4	8.2	11.4
					(10'0")	**(8'11")**		**(1.7)**	**(2.2)**	**(3.0)**	**(4.0)**	**(5.1)**	**(7.1)**
D9G	66A	61-74	385	31 072	2.29	5.50	PS						
				(68,500)	**(7'6")**	**(18'1")**							
					3.10	2.10		3.9	6.8	10.5			
					(10'0")	**(8'7")**		**(2.4)**	**(4.2)**	**(6.5)**			

NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th	Remarks
S × S D9G	29N	69-74	770	86 200• (190,000)	5.8* (19'0")	8.0◀ (25'0")	PS							L.H. of S × S D9G
	30N				7.3** (24'0")	2.8◀◀ (9'2")		3.9 (2.4)	6.8 (4.2)	10.0 (6.2)				R.H. of S × S D9G
Dual D9G	90J	69-74	770	79 470• (175,200)	2.3* (7'6")	12.9◀ (42'6")	PS							Front of Dual D9G
	91J				3.3** (10'9")	3.1◀◀ (9'11")		3.9 (2.4)	6.8 (4.2)	10.5 (6.5)				Rear of Dual D9G
S × S D9H	99V	74-77	820	83 400• (183,900)	5.8* (19'0")	9.0◀ (26'1")	PS							L.H. of S × S D9H
	12U				7.3** (24'0")	2.9◀◀ (9'6")		4.0 (2.5)	6.9 (4.3)	10.8 (6.7)				R.H. of S × S D9H
Dual D9H	97V	74-80	820	81 100• (178,800)	2.3* (7'6")	12.9◀ (42'6")	PS							Front of Dual D9H
	98V				3.3** (10'9")	3.1◀◀ (9'11")		4.0 (2.5)	6.9 (4.3)	10.8 (6.7)				Rear of Dual D9H
D9H	90V	74-81	410	32 840 (72,400)	2.3* (7'6")	5.6 (18'5")	PS							Standard Model
					3.0 (9'11")	2.7◀◀ (8'10")		4.0 (2.5)	6.9 (4.3)	10.8 (6.7)				
D9L	14Y	80-87	460	52 055 (114,656)	2.5 (8'2")	5.32 (17'5")								
					3.11 (10'2")	4.41 (14'6")		3.9 (2.4)	7.2 (4.5)	12.4 (7.7)				
D9N	1JD	86-94	370	42 816 (96,196)	2.55 (7'5")	5.17 (16'11.5")	PS							
	6XJ	93-95			2.43 (9'7")	3.91 (12'10")		3.9 (2.4)	6.9 (4.3)	12.1 (7.5)				
D9R (CB) (US)	ACL	00-04	410	49 147 (108,350)	2.25 (7'5")	6.84 (22'5")	PS							
					3.30 (10'10")	3.99 (13'1")		3.8 (2.4)	6.8 (4.2)	11.9 (7.4)				
D9R (DS) (US)	ABK	00-04	410	49 510 (109,150)	2.25 (7'5")	6.84 (22'5")	PS							
					3.30 (10'10")	3.99 (13'1")		3.8 (2.4)	6.8 (4.2)	11.9 (7.4)				
D9T	RJS	04-11	410	47 900 (105,600)	2.25 (7'5")	6.85 (22'6")	PS							
					3.31 (10'11")	3.99 (13'1")		3.9 (2.4)	6.8 (4.2)	11.7 (7.3)				

*Gauge of both tractors combined.
**Width to outside of dozer blade.
◀Length including dozer blade.
◀◀Overall height excluding stack and canopy.
•Approximate weight of both machines plus Bulldozer, hydraulic controls, coolant and 5% fuel. (D10, D11N, D11R includes SS ripper)

NOTE: Power Shift models show speeds only, not drawbar pull.

NOTE: Track-Type Tractor weights do not include blades until 1967.

Track-Type Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Gauge m (ft) and Width m (ft)	Length m (ft) and Height m (ft)	Trans-mission	Rated Drawbar Pull — kg (lb) and Forward Speed — km/h (mph) 1st	2nd	3rd	4th	5th	6th	Remarks
D10	84W	78-86	700	88 245 (194,140)	2.9 (9'6")	5.92 (19'8")	PS							Width 2.2 m (7'0") 2.9 m (9'6") gauge
	76X				3.65 (12'0")	4.63◀ (15'2")		3.9 (2.4)	6.8 (4.2)	11.6 (7.2)				1.9 × 2.7 m (6'4" × 8'10") gauge
D10N	2YD	87-93	520	66 400 (147,405)	2.55 (8'4")	5.89 (18'4")	PS							Width 3.45 m (11'4")
	3SK	93-96			3.30 (10'10")	4.45 (14'7")		4.0 (2.5)	7.1 (4.4)	12.5 (7.7)				
D10R	3KR	95-02	570	65 764 (144,986)	2.55 (8'4")	7.50 (24'7")	TD 3-Spd PS							3412 DITA HEUI™
					3.72 (12'2")	3.27 (10'9")		4.0 (2.5)	7.1 (4.4)	12.5 (7.7)				
D10R	AKT	01-04	580	65 400 (144,200)	2.55 (8'4")	9.16 (30'0")	PS							
					3.74 (12'3")	4.27 (14'0")		4.0 (2.5)	7.1 (4.4)	12.5 (7.7)				
D10T	RJG	05-14	580	70 171 (154,700)	2.55 (8'4")	7.42 (24'4")	TD 3-Spd PS							C27 ACERT™ DITA MEUI™
					3.74 (12'3")	3.22 (10'7")		4.0 (2.5)	7.2 (4.5)	12.7 (7.9)				
D11N	74Z	86-93	770	95 900 (211,000)	2.90 (9'6")	6.16 (20'3")	PS							
	4HK	93-96		97 450 (214,850)	3.65 (12'0")	4.65 (15'3")		3.9 (2.4)	6.8 (4.4)	11.6 (7.2)				
D11R	8ZR	96-97	770	98 413 (216,963)	2.89 (9'6")	6.16 (20'3")	PS							
					3.60 (11'10")	4.65 (15'3")		3.9 (2.4)	6.8 (4.4)	11.6 (7.2)				
D11R	9TR	97-99	850	104 590 (230,100)	2.89 (9'6")	6.16 (20'3")	PS							
					3.60 (11'10")	4.65 (15'3")		3.9 (2.4)	6.8 (4.2)	11.8 (7.3)				
D11R	7PZ	00-07	850	104 600 (230,100)	2.89 (9'6")	5.21 (17'1")	PS							
					3.60 (11'10")	4.57 (15'0")		3.9 (2.4)	6.8 (4.2)	11.8 (7.3)				
D11R CD	9XR	96-99	850	111 590 (246,000)	2.89 (9'6")	6.16 (20'3")	PS							
					3.60 (11'10")	4.65 (15'3")		3.9 (2.4)	6.8 (4.2)	11.8 (7.3)				
D11R CD	AAF	96-07	850	113 000 (248,600)	2.89 (9'6")	5.21 (17'1")	PS							
					3.81 (12'6")	4.57 (15'0")		3.9 (2.4)	6.8 (4.2)	11.8 (7.3)				
D11T	GEB	07-11	850	104 590 (230,581)	2.89 (9'6")	8.64 (28'4")	TD 3-Spd PS							C32 ACERT DITA MEUI
					4.38 (14'4")	3.64 (11'11")		3.9 (2.4)	6.8 (4.2)	11.8 (7.3)				
D11T CD	TPB	07-11	850	113 000 (249,122)	2.89 (9'6")	8.77 (28'9")	TD 3-Spd PS							C32 ACERT DITA MEUI
					4.38 (14'4")	3.64 (11'11")		3.9 (2.4)	6.8 (4.2)	11.8 (7.3)				

◀Overall height excluding stack and canopy.
NOTE: Power Shift models show speeds only, not drawbar pull.
NOTE: Track-Type Tractor weights do not include blades until 1967.

TRACK-TYPE TRACTORS MANUFACTURED OUTSIDE U.S.A.

Source	Model	Product Ident. No. Prefix	Years Built	Horsepower Flywheel/ Drawbar	Transmission	Gauge m (ft)
U.K.	D4C	24A	60-64	63/50	DD	1.52 **(5'0")**
	D4D	88A	64-67	65/52	DD	1.52 **(5'0")**
	D6C	82A	64-68	120/93	DD	1.88 **(6'2")**
	D6C	83A	64-68	120/—	PS	1.88 **(6'2")**
	D6C	46J	71-77	140/—	DD	1.88 **(6'2")**
	D6C	47J	71-77	140/—	PS	1.88 **(6'2")**
	D8H	52A	59-61	235/—	PS	2.13 **(7'0")**
	D8H	22A	59-66	235/185	DD	2.13 **(7'0")**
	D8H	68A	60-66	235/—	PS	2.13 **(7'0")**
	D8K	66V	74-82	300/—	PS	2.13 **(7'0")**
Brazil	D4D	97F	69-78	75/—	DD	1.52 **(5'0")**
	D4D	74U	71-78	75/—	PS	1.52 **(5'0")**
	D6C	24U	71-77	120/93	PS	1.88 **(6'2")**
	D6C	23U	73-77	120/93	DD	1.88 **(6'2")**
	D6D	74W	77-92	140/—	DD	1.88 **(6'2")**
	D6D	75W	77-92	140/—	PS	1.88 **(6'2")**
	D6D	9FK	92-96	140/—	PS	1.88 **(6'2")**
	D6E	2MJ	92-96	155/—	PS	1.88 **(6'2")**
	D6D	19B	85-91	140/—	PS	1.88 **(6'2")**
	D6G	2MJ	89-03	160/—	PS	1.88 **(6'2")**
	D6G SR	3SR	97-01	160/—	PS	
	D6M XL	5WR	96-02	104/140	PS	1.89 **(6'2")**
	D6M XL	6LR	96-02	104/140	PS	1.89 **(6'2")**
	D8L	7JC	84-90	335/—	PS	2.2 **(7'3")**
	D8L	7YB	85-92	335/—	PS	2.2 **(7'3")**
	D8N	7TK	93-95	285/—	PS	2.08 **(6'10")**
	D8R	9EM	95-	305/—		
	D8R Series II	AKA	00-04	310	PS	2.08 **(6'10")**
	D8R Series II	AKA	00-04	310	PS	3.05 **(10'0")**
Australia	D4	29A	59-61	63/50	DD	1.12 **(3'8")**
	D4	30A	59-60	63/50	DD	1.52 **(5'0")**
	D4C	54A	60-62	63/52	DD	1.12 **(3'8")**
	D4C	55A	60-62	65/52	DD	1.52 **(5'0")**
	D4D	85A	63-68	65/52	DD	1.52 **(5'0")**
	D5	51H	68-68	93/75	DD	1.88 **(6'2")**
	D5	52H	68-69	93/—	PS	1.88 **(6'2")**
	D6	31A	58-60	93/75	DD	1.52 **(5'0")**
	D6	32A	58-60	93/75	DD	1.18 **(6'2")**
	D6B	56A	60-66	90/73	DD	1.52 **(5'0")**
	D6B	57A	60-68	90/73	DD	1.88 **(6'2")**
	D6C	71A	63-68	120/93	DD	1.88 **(6'2")**
	D6C	73A	63-68	120/—	PS	1.88 **(6'2")**
	D6C	55J	69-72	125/—	DD	1.88 **(6'2")**
	D6C	56J	69-72	125/—	PS	1.88 **(6'2")**
China	D6G Series 2	C6G	06-11	160	PS	1.88 **(6'2")**
	D6G Series 2 LGP	C6X	08-11	160/—	PS	2.11 **(6'11")**
	D7G Series 2	C7G	06-11	200	PS	1.98 **(6'6")**
	D7G Series 2	C7G	04-11	149/200	PS	1.98 **(6'6")**
Indonesia	D6G Series 2	P6G	06-11	160/—	PS	1.88 **(6'2")**
	D7G	7MB	83-11	202/—	PS	1.98 **(6'6")**
	D7G Series 2	7MB	83-12	149/200	PS	1.98 **(6'6")**
France	D4C	69A	61-63	63/50	DD	1.52 **(5'0")**
	D4D	86A	63-68	65/52	DD	1.52 **(5'0")**
	D4D LGP	18J	66-68	65/52	DD	1.79 **(5'10")**
	D4D	58J	67-68	65/—	PS	1.52 **(5'0")**

Track-Type Tractors Manufactured Outside U.S.A. (cont'd)

Source	Model	Product Ident. No. Prefix	Years Built	Horsepower Flywheel/ Drawbar	Transmission	Gauge m (ft)
France	D4E	68X	78-86	80/—	DD	1.52 **(5'0")**
(cont'd)	D4E	69X	78-85	80/—	PS	1.52 **(5'0")**
	D4E LGP	71X	78-85	80/—	DD	1.77 **(5'10")**
	D4E LGP	72X	78-86	80/—	PS	1.77 **(5'10")**
	D5	62J	69-77	105/—	DD	1.88 **(6'2")**
	D5	63J	69-77	105/—	PS	1.88 **(6'2")**
	D5 LGP	6R	70-77	105/—	PS	2.06 **(6'9")**
	D5 LGP	12R	70-77	105/—	DD	2.06 **(6'9")**
	D5B	43X	77-85	105/—	DD	1.88 **(6'2")**
	D5B	44X	77-86	105/—	PS	1.88 **(6'2")**
	D5B LGP	45X	77-86	105/—	DD	2.06 **(6'9")**
	D5B LGP	46X	77-86	105/—	PS	2.06 **(6'9")**
	D5B	8MB	84-86	105/—	PS	1.52 **(5'0")**
	D5H	8RC	85-96	120/—	PS	1.80 **(5'11")**
	D5H LGP	1DD	86-96	130/—	PS	2.16 **(7'1")**
	D5H XL	8RJ	86-96	130/—	PS	1.89 **(6'2")**
	D5H	7NC	85-96	120/—	DD	1.80 **(5'11")**
	D5H LGP	9HC	85-96	130/—	DD	2.16 **(7'1")**
	D5M XL	4BR	96-02	82/110	PS	1.77 **(5'10")**
	D5M XL	6GN	96-02	82/110	PS	1.77 **(5'10")**
	D5M LGP	3DR	96-02	82/110	PS	2.00 **(6'7")**
	D5M LGP	3CR	96-02	82/110	PS	2.00 **(6'7")**
	D6M XL	9ZM	96-02	104/140	PS	1.89 **(6'2")**
	D6M XL	3WN	96-02	104/140	PS	1.89 **(6'2")**
	D6M LGP	2RN	96-02	104/140	PS	2.16 **(7'1")**
	D6M LGP	4JN	96-02	104/140	PS	2.16 **(7'1")**
Scotland	D6D	19X	78-86	140/—	DD	1.88 **(6'2")**
	D6D	20X	78-86	140/—	PS	1.88 **(6'2")**
	D6D	0IY	79-87	125/—	PS	1.88 **(6'2")**
Glasgow	D6H	7PC	86-87	165/—	PS	1.88 **(6'2")**
	D6H LGP	8YC	86-87	165/—	PS	2.23 **(7'4")**
Japan	D3	79U	73-79	62/—	PS	1.42 **(4'8")**
	D3	82U	73-78	62/—	PS	1.42 **(4'8")**
	D3 LGP	6N	73-79	62/—	PS	1.65 **(5'5")**
	D3 LGP	83U	73-79	62/—	PS	1.65 **(5'5")**
	D3B	23Y	79-87	65/—	PS	1.42 **(4'8")**
	D3B LGP	24Y	79-87	65/—	PS	1.65 **(5'5")**
	D3B	27Y	79-87	65/—	PS	1.42 **(4'8")**
	D3B LGP	28Y	79-87	65/—	PS	1.65 **(5'5")**
	D3B	3YC	85-87	65/—	DD	1.42 **(4'8")**
	D3B LGP	5MC	85-87	65/—	DD	1.65 **(5'5")**
	D3C	5KG	87-90	67/—	PS	1.42 **(4'7")**
	D3C Series II	7JG/4HJ	90-93	70/—	PS	1.42 **(4'7")**
	D3C LGP	1PJ	87-90	67/—	PS	1.65 **(5'4")**
	D3C LGP Series II	8GD/5CJ	90-93	70/—	PS	1.65 **(5'4")**
	D3G XL	CFC	01-03	70	HYS	1.45 **(4'9")**
	D3G XL*	JMH	03-07	70	HYS	1.45 **(4'9")**
	D3G LGP	CFF	01-03	70	HYS	1.68 **(5'6")**
	D3G LGP*	BYR	03-07	70	HYS	1.68 **(5'6")**
	D4D LGP	67A	65-68	65/52	DD	1.79 **(5'10")**
	D4D	91A	65-68	65/52	DD	1.52 **(5'0")**
	D4E	50X	77-86	80/—	DD	1.52 **(5'0")**
	D4E	51X	77-86	80/—	PS	1.52 **(5'0")**
	D4E LGP	52X	77-86	80/—	DD	1.77 **(5'10")**
	D4C	1RJ	87-90	78/—	PS	1.42 **(4'7")**
	D4C Series II	7KG	90-93	80/—	PS	1.42 **(4'7")**

*Emits equivalent to Tier 2/Stage II/Japan 2001 (Tier 2).

Track-Type Tractors Manufactured Outside U.S.A. (cont'd)

Source	Model	Product Ident. No. Prefix	Years Built	Horsepower Flywheel/ Drawbar	Transmission	Gauge m (ft)
Japan (cont'd)	D4C LGP	2CJ	87-90	78/—	PS	1.65 **(5'4")**
	D4C LGP Series II	98G	90-93	80/—	PS	1.65 **(5'4")**
	D4G XL	CFN	01-03	80	HYS	1.50 **(4'11")**
	D4GXL*	HYD	03-07	80	HYS	1.50 **(4'11")**
	D4G LGP	FDC	01-03	80	HYS	1.68 **(5'6")**
	D4G LGP*	TLX	03-07	80	HYS	1.68 **(5'6")**
	D4H	8PB	85-96	90/95	PS	1.67 **(5'5")**
	D4H LGP	9DB	85-96	105/—	PS	2.0 **(6'7")**
	D4H	2AC	85-92	90/95	DD	1.67 **(5'5")**
	D4H LGP	3AC	85-90	90/95	DD	2.0 **(6'7")**
	D4H XL	8PJ	92-96	105/—	PS	1.77 **(5'10")**
	D4H LGP	9GJ	92-96	105/—	PS	2.0 **(6'7")**
	D4H LGP	4NK	92-93	105/—	DD	2.0 **(6'7")**
	D5	37J	67-68	93/75	DD	1.88 **(6'2")**
	D5 LGP	98A	67-68	93/75	DD	2.06 **(6'9")**
	D5	67J	68-77	105/—	DD	1.88 **(6'2")**
	D5	97J	71-76	105/—	PS	1.88 **(6'2")**
	D5 LGP	68J	68-77	105/—	DD	2.06 **(6'9")**
	D5B	47X	77-86	105/—	DD	1.88 **(6'2")**
	D5B	48X	77-86	105/—	PS	1.88 **(6'2")**
	D5B LGP	49X	77-86	105/—	DD	2.06 **(6'9")**
	D5C	6PJ	91-93	90/—	PS	1.54 **(5'1")**
	D5C LGP	3MK	91-93	90/—	PS	1.72 **(5'8")**
	D5G XL	FDH	01-03	90	HYS	1.55 **(5'1")**
	D5GXL*	WGB	03-07	90	HYS	1.55 **(5'1")**
	D5G LGP	FDW	01-03	90	HYS	1.73 **(5'8")**
	D5G LGP*	RKG	03-07	90	HYS	1.73 **(5'8")**
	D5H	3MD	86-96	120/—	PS	1.80 **(5'11")**
	D5H LGP	4KD	86-96	130/—	PS	2.16 **(7'1")**
	D5H	1YD	86-96	120/—	DD	1.80 **(5'11")**
	D5H LGP	2SD	86-96	130/—	DD	2.16 **(7'1")**
	D5M XL	4JS	96-	82/110	PS	1.77 **(5'10")**
	D5M XL	5ES	96-02	82/110	PS	1.77 **(5'10")**
	D5M LGP	5FS	96-	82/110	PS	2.00 **(6'7")**
	D5M LGP	6AS	96-02	82/110	PS	2.00 **(6'7")**
	D5M LGP	7LR	97-02	78/105	DDPS	2.00 **(6'7")**
	D6B	37H	66-67	93/75	DD	1.88 **(6'2")**
	D6B LGP	38H	66-67	93/75	DD	2.06 **(6'9")**
	D6C	41A	66-68	120/93	DD	1.88 **(6'2")**
	D6C	96A	66-68	120/93	PS	1.88 **(6'2")**
	D6C	26K	68-77	125/—	DD	1.88 **(6'2")**
	D6C	69C	68-77	125/—	PS	1.88 **(6'2")**
	D6C LGP	90B	71-77	140/—	DD	2.11 **(6'11")**
	D6D LGP LS	6HC	86-96	160/—	DD	1.88 **(6'2")**
	D6D	31X	86-98	140/—	PS	1.88 **(6'2")**
	D6D	30X	85-96	140/—	DD	1.88 **(6'2")**
	D6D PTNR	5YB	88-96	160/—	PS	1.88 **(6'2")**
	D6G	BWJ	02-07	160/—	PS	1.88 **(6'2")**
	D6M XL	2YS	96-	104/140	PS	1.89 **(6'2")**
	D6M XL	4HS	96-02	104/140	PS	1.89 **(6'2")**
	D6M LGP	4GS	96-	104/140	PS	2.16 **(7'1")**
	D6M LGP	5NR	96-02	104/140	PS	2.16 **(7'1")**

*Emits equivalent to Tier 2/Stage II/Japan 2001 (Tier 2).

Track-Type Tractors Manufactured Outside U.S.A. (cont'd)

Source	Model	Product Ident. No. Prefix	Years Built	Horsepower Flywheel/ Drawbar	Transmission	Gauge m (ft)
Japan (cont'd)	D6R	S6X	10-	175	PS	1.88 **(74")**
	D6R XL	S6T	10-	195	PS	1.88 **(74")**
	D6R LGP	S6Y	10-	195	PS	2.286 **(90")**
	D6R SIII	JEK	06-10	138/185	PS	1.88 **(6'2")**
	D6R SIII XL	EXL	06-12	149/200	PS	1.88 **(6'2")**
	D6R SIII XW	EXW	07-09	149/200	PS	2.03 **(6'8")**
	D6R SIII LGP	LGP	06-12	149/200	PS	2.29 **(7'6")**
	D7G	35N	80-91	202/—	PS	1.98 **(6'6")**
	D7G LGP	44W	76-87	202/—	PS	1.98 **(6'6")**
	D7G LGP	45W	75-86	202/—	DD	1.98 **(6'6")**
	D7G	64V	75-88	202/—	DD	1.98 **(6'6")**
	D7G	65V	75-07	202/—	PS	1.98 **(6'6")**
	D7G	65V	75-07	149/200	PS	1.98 **(6'6")**
	D7H	25B	85-92	215/—	DD	1.98 **(6'6")**
						2.54 **(8'5")**
	D7H LGP	82Z	85-92	215/—	DD	2.23 **(7'4")**
						3.15 **(10'4")**
	D7R	DSH	12-	240	PS	1.98 **(78")**
	D7R XR	DJR	12-	240	PS	1.98 **(78")**
	D7R LGP	DLN	12-	240	PS	2.235 **(88")**
	D7R SII	BRM	02-12	179/240	PS	1.98 **(6'6")**
	D7R SII XR	BPT	03-12	179/240	PS	1.98 **(6'6")**
	D7R SII LGP	BNX	01-12	179/240	PS	2.24 **(7'4")**



AGRICULTURAL TRACTORS

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Height m (ft) Gauge m (ft)	Drawbar Pull kg (lb)* and Forward Speed km/h (mph) 1st	2nd	3rd	4th	5th	6th	7th	8th
Challenger 35	8DN	94-98	175/150	9838 - 12 133 (21,690 - 26,750)	3.05 (10'0") 1.47* (60")*	8604 (18,968) 2.62 (1.6)	8499 (18,737) 3.11 (1.9)	8314 (18,329) 3.64 (2.3)	7851 (17,307) 4.17 (2.6)	7161 (15,787) 4.93 (3.1)	6694 (14,757) 5.76 (3.6)	5949 (13,116) 6.79 (4.2)	5147 (11,348) 8.02 (5.0)
Challenger 35	8RD	99-01	175/150	9838 - 12 133 (21,690 - 26,750)	3.05 (10'0") 1.47 (60")	8604 (18,968) 2.62 (1.6)	8499 (18,737) 3.11 (1.9)	8314 (18,329) 3.64 (2.3)	7851 (17,307) 4.17 (2.6)	7161 (15,787) 4.93 (3.1)	6694 (14,757) 5.76 (3.6)	5949 (13,116) 6.79 (4.2)	5147 (11,348) 8.02 (5.0)
Challenger 35	ADK	99-01	175/150	9838 - 12 133 (21,690 - 26,750)	3.05 (10'0") 2.03 (80")	8604 (18,968) 2.62 (1.6)	8499 (18,737) 3.11 (1.9)	8314 (18,329) 3.64 (2.3)	7851 (17,307) 4.17 (2.6)	7161 (15,787) 4.93 (3.1)	6694 (14,757) 5.76 (3.6)	5949 (13,116) 6.79 (4.2)	5147 (11,348) 8.02 (5.0)
Challenger MT735		01-02	235/185	10 977 - 20 400 (24,200 - 45,000)	3.37 (11'1")	12 680 (27,900) 2.7 (1.7)	12 680 (27,900) 3.4 (2.1)	12 680 (27,900) 4.3 (2.7)	10 890 (23,950) 5.4 (3.4)	9130 (20,090) 6.5 (4.0)	8105 (17,830) 7.3 (4.5)	7187 (15,810) 8.2 (5.1)	6388 (14,050) 9.3 (5.8)
Challenger 45	1DR	94-98	200/170	9838 - 12 133 (21,690 - 26,750)	3.05 (10'0") 1.47* (60")*	8675 (19,125) 2.62 (1.6)	8675 (19,125) 3.11 (1.9)	8675 (19,125) 3.64 (2.3)	8255 (18,199) 4.17 (2.6)	7710 (16,997) 4.93 (3.1)	7318 (16,134) 5.76 (3.6)	6757 (14,897) 6.79 (4.2)	5891 (12,987) 8.02 (5.0)
Challenger 45	ABF	99-01	200/170	9838 - 12 133 (21,690 - 26,750)	3.05 (10'0") 1.47 (60")	8675 (19,125) 2.62 (1.6)	8675 (19,125) 3.11 (1.9)	8675 (19,125) 3.64 (2.3)	8255 (18,199) 4.17 (2.6)	7710 (16,997) 4.93 (3.1)	7318 (16,134) 5.76 (3.6)	6757 (14,897) 6.79 (4.2)	5891 (12,987) 8.02 (5.0)
Challenger 45	3BK	99-01	200/170	9838 - 12 133 (21,690 - 26,750)	3.05 (10'0") 2.03 (80")	8675 (19,125) 2.62 (1.6)	8675 (19,125) 3.11 (1.9)	8675 (19,125) 3.64 (2.3)	8255 (18,199) 4.17 (2.6)	7710 (16,997) 4.93 (3.1)	7318 (16,134) 5.76 (3.6)	6757 (14,897) 6.79 (4.2)	5891 (12,987) 8.02 (5.0)
Challenger MT745		01-02	255/205	10 977 - 20 400 (24,200 - 45,000)	3.37 (11'1")	12 680 (27,900) 2.7 (1.7)	12 680 (27,900) 3.4 (2.1)	12 680 (27,900) 4.3 (2.7)	11 828 (26,020) 5.4 (3.4)	9920 (21,820) 6.5 (4.0)	8806 (19,370) 7.3 (4.5)	7808 (17,180) 8.2 (5.1)	6941 (15,270) 9.3 (5.8)
Challenger 55	7DM	96-98	225/191	9838 - 12 133 (21,690 - 26,750)	3.05 (10'0") 1.47* (60")*	8675 (19,125) 2.62 (1.6)	8675 (19,125) 3.11 (1.9)	8675 (19,125) 3.64 (2.3)	8675 (19,125) 4.17 (2.6)	8255 (18,200) 4.93 (3.1)	7802 (17,200) 5.76 (3.6)	7188 (15,848) 6.79 (4.2)	6593 (14,535) 8.02 (5.0)
Challenger 55	AEN	99-01	225/191	9838 - 12 133 (21,690 - 26,750)	3.05 (10'0") 2.03 (80")	8675 (19,125) 2.62 (1.6)	8675 (19,125) 3.11 (1.9)	8675 (19,125) 3.64 (2.3)	8675 (19,125) 4.17 (2.6)	8255 (18,200) 4.93 (3.1)	7802 (17,200) 5.76 (3.6)	7188 (15,848) 6.79 (4.2)	6593 (14,535) 8.02 (5.0)
Challenger 55	6NN	99-01	225/191	9838 - 12 133 (21,690 - 26,750)	3.05 (10'0") 1.47 (60")	8675 (19,125) 2.62 (1.6)	8675 (19,125) 3.11 (1.9)	8675 (19,125) 3.64 (2.3)	8675 (19,125) 4.17 (2.6)	8255 (18,200) 4.93 (3.1)	7802 (17,200) 5.76 (3.6)	7188 (15,848) 6.79 (4.2)	6593 (14,535) 8.02 (5.0)
Challenger MT755		01-02	290/235	10 097 - 20 400 (24,200 - 45,000)	3.37 (11'1")	12 682 (27,900) 2.7 (1.7)	12 682 (27,900) 3.4 (2.1)	12 682 (27,900) 4.3 (2.7)	12 682 (27,900) 5.4 (3.4)	11 302 (24,865) 6.5 (4.0)	10 032 (22,070) 7.3 (4.5)	8896 (19,570) 8.2 (5.1)	7908 (17,397) 9.3 (5.8)
Challenger MT765		01-02	306/255	10 977 - 20 411 (24,200 - 45,000)	3.37 (11'1")	12 682 (27,900) 2.7 (1.7)	12 682 (27,900) 3.4 (2.1)	12 682 (27,900) 4.3 (2.7)	12 682 (27,900) 5.4 (3.4)	11 894 (26,168) 6.5 (4.0)	10 558 (23,228) 7.3 (4.5)	9362 (20,597) 8.2 (5.1)	8322 (18,308) 9.3 (5.8)

*Base gauge (no spacers) of 1.47 m **(60")** available on 8DN1-849, 1DR1-1699, 7DM1-849. Base gauges (no spacers) of 1.47 m **(60")** and 2.03 m **(80")** available on 8DN850-Up, 1DR1700-Up, and 7DM850-Up.

Agricultural Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Height m (ft) Gauge m (ft)	Drawbar Pull kg (lb)* and Forward Speed km/h (mph) 9th	10th	11th	12th	13th	14th	15th	16th
Challenger 35	8DN	94-98	175/150	9838 - 12 133 **(21,690 - 26,750)**	3.05 **(10'0")** 1.47* **(60")***	4436 **(9779)** 9.39 **(5.8)**	3740 **(8244)** 11.11 **(6.9)**	3171 **(6991)** 12.70 **(7.9)**	2601 **(5735)** 15.04 **(9.3)**	2154 **(4749)** 17.60 **(10.9)**	1771 **(3904)** 20.70 **(12.9)**	1449 **(3194)** 24.49 **(15.2)**	1196 **(2637)** 28.64 **(17.8)**
Challenger 35	8RD	99-01	175/150	9838 - 12 133 **(21,690 - 26,750)**	3.05 **(10'0")** 1.47 **(60")**	4436 **(9779)** 9.39 **(5.8)**	3740 **(8244)** 11.11 **(6.9)**	3171 **(6991)** 12.70 **(7.9)**	2601 **(5735)** 15.04 **(9.3)**	2154 **(4749)** 17.60 **(10.9)**	1771 **(3904)** 20.70 **(12.9)**	1449 **(3194)** 24.49 **(15.2)**	1196 **(2637)** 28.64 **(17.8)**
Challenger 35	ADK	99-01	175/150	9838 - 12 133 **(21,690 - 26,750)**	3.05 **(10'0")** 2.03 **(80")**	4436 **(9779)** 9.39 **(5.8)**	3740 **(8244)** 11.11 **(6.9)**	3171 **(6991)** 12.70 **(7.9)**	2601 **(5735)** 15.04 **(9.3)**	2154 **(4749)** 17.60 **(10.9)**	1771 **(3904)** 20.70 **(12.9)**	1449 **(3194)** 24.49 **(15.2)**	1196 **(2637)** 28.64 **(17.8)**
Challenger MT735		01-02	235/185	10 977 - 20 400 **(24,200 - 45,000)**	3.37 **(11'1")**	5678 **(12,490)** 10.4 **(6.5)**	5047 **(11,100)** 11.7 **(7.3)**	4476 **(9850)** 13.2 **(8.2)**	3974 **(8742)** 14.9 **(9.3)**	3339 **(7346)** 17.7 **(11.0)**	2628 **(5782)** 22.5 **(14.0)**	2077 **(4568)** 28.5 **(17.7)**	1635 **(3598)** 39.7 **(24.6)**
Challenger 45	1DR	94-98	200/170	9838 - 12 133 **(21,690 - 26,750)**	3.05 **(10'0")** 1.47* **(60")***	5063 **(11,162)** 9.39 **(5.8)**	4170 **(9193)** 11.11 **(6.9)**	3547 **(7821)** 12.70 **(7.9)**	2920 **(6438)** 15.04 **(9.3)**	2427 **(5351)** 17.60 **(10.9)**	2003 **(4416)** 20.70 **(12.9)**	1646 **(3629)** 24.49 **(15.2)**	1365 **(3010)** 28.64 **(17.8)**
Challenger 45	ABF	99-01	200/170	9838 - 12 133 **(21,690 - 26,750)**	3.05 **(10'0")** 1.47 **(60")**	5063 **(11,162)** 9.39 **(5.8)**	4170 **(9193)** 11.11 **(6.9)**	3547 **(7821)** 12.70 **(7.9)**	2920 **(6438)** 15.04 **(9.3)**	2427 **(5351)** 17.60 **(10.9)**	2003 **(4416)** 20.70 **(12.9)**	1646 **(3629)** 24.49 **(15.2)**	1365 **(3010)** 28.64 **(17.8)**
Challenger 45	3BK	99-01	200/170	9838 - 12 133 **(21,690 - 26,750)**	3.05 **(10'0")** 2.03 **(80")**	5063 **(11,162)** 9.39 **(5.8)**	4170 **(9193)** 11.11 **(6.9)**	3547 **(7821)** 12.70 **(7.9)**	2920 **(6438)** 15.04 **(9.3)**	2427 **(5351)** 17.60 **(10.9)**	2003 **(4416)** 20.70 **(12.9)**	1646 **(3629)** 24.49 **(15.2)**	1365 **(3010)** 28.64 **(17.8)**
Challenger MT745		01-02	255/205	10 977 - 20 400 **(24,200 - 45,000)**	3.37 **(11'1")**	6169 **(13,573)** 10.4 **(6.5)**	5484 **(12,065)** 11.7 **(7.3)**	4864 **(10,700)** 13.2 **(8.2)**	4317 **(9498)** 14.9 **(9.3)**	3628 **(7981)** 17.7 **(11.0)**	2856 **(6282)** 22.5 **(14.0)**	2256 **(4963)** 28.5 **(17.7)**	1777 **(3909)** 39.7 **(24.6)**
Challenger 55	7DM	96-98	225/191	9838 - 12 133 **(21,690 - 26,750)**	3.05 **(10'0")** 1.47* **(60")***	5663 **(12,484)** 9.39 **(5.8)**	4676 **(10,310)** 11.11 **(6.9)**	3990 **(8796)** 12.70 **(7.9)**	3295 **(7264)** 15.04 **(9.3)**	2747 **(6056)** 17.60 **(10.9)**	2275 **(5015)** 20.70 **(12.9)**	1876 **(4135)** 24.49 **(15.2)**	1562 **(3443)** 28.64 **(17.8)**
Challenger 55	AEN	99-01	225/191	9838 - 12 133 **(21,690 - 26,750)**	3.05 **(10'0")** 2.03 **(80")**	5663 **(12,484)** 9.39 **(5.8)**	4676 **(10,310)** 11.11 **(6.9)**	3990 **(8796)** 12.70 **(7.9)**	3295 **(7264)** 15.04 **(9.3)**	2747 **(6056)** 17.60 **(10.9)**	2275 **(5015)** 20.70 **(12.9)**	1876 **(4135)** 24.49 **(15.2)**	1562 **(3443)** 28.64 **(17.8)**
Challenger 55	6NN	99-01	225/191	9838 - 12 133 **(21,690 - 26,750)**	3.05 **(10'0")** 1.47 **(60")**	5663 **(12,484)** 9.39 **(5.8)**	4676 **(10,310)** 11.11 **(6.9)**	3990 **(8796)** 12.70 **(7.9)**	3295 **(7264)** 15.04 **(9.3)**	2747 **(6056)** 17.60 **(10.9)**	2275 **(5015)** 20.70 **(12.9)**	1876 **(4135)** 24.49 **(15.2)**	1562 **(3443)** 28.64 **(17.8)**
Challenger MT755		01-02	290/235	10 097 - 20 400 **(24,200 - 45,000)**	3.37 **(11'1")**	7029 **(15,464)** 10.4 **(6.5)**	6248 **(13,745)** 11.7 **(7.3)**	5541 **(12,190)** 13.2 **(8.2)**	4919 **(10,821)** 14.9 **(9.3)**	4133 **(9093)** 17.7 **(11.0)**	3253 **(7157)** 22.5 **(14.0)**	2570 **(5655)** 28.5 **(17.7)**	2024 **(4454)** 39.7 **(24.6)**
Challenger MT765		01-02	306/255	10 977 - 20 411 **(24,200 - 45,000)**	3.37 **(11'1")**	7397 **(16,274)** 10.4 **(6.5)**	6575 **(14,466)** 11.7 **(7.3)**	5831 **(12,829)** 13.2 **(8.2)**	5176 **(11,388)** 14.9 **(9.3)**	4350 **(9569)** 17.7 **(11.0)**	3424 **(7533)** 22.5 **(14.0)**	2705 **(5951)** 28.5 **(17.7)**	2130 **(4687)** 39.7 **(24.6)**

*Base gauge (no spacers) of 1.47 m **(60")** available on 8DN1-849, 1DR1-1699, 7DM1-849. Base gauges (no spacers) of 1.47 m **(60")** and 2.03 m **(80")** available on 8DN850-Up, 1DR1700-Up, and 7DM850-Up.

Agricultural Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Height m (ft) Gauge m (ft)	Drawbar Pull kg (lb)* and Forward Speed km/h (mph) 1st	2nd	3rd	4th	5th	6th	7th	8th	9th	10th
Challenger 65	7YC	86-90	270/200	14 061	3.24	14 825	10 393	8880	7701	6656	5708	4950	4245	2858	1725
				(31,000)	**(10'8")**	**(32,684)**	**(22,912)**	**(19,577)**	**(16,978)**	**(14,674)**	**(12,583)**	**(10,912)**	**(9358)**	**(6300)**	**(3803)**
					2.15	4.2	6.4	7.5	8.6	9.9	11.3	13.0	14.9	19.3	29.3
					(7'1")	**(2.6)**	**(4.0)**	**(4.7)**	**(5.3)**	**(6.1)**	**(7.0)**	**(8.1)**	**(9.3)**	**(12.0)**	**(18.1)**
Challenger 65B	7YC	91-92	285/225	14 060	3.24	14 893	11 074	9492	8252	7138	6109	5294	4545	3057	1851
				(31,000)	**(10'8")**	**(32,914)**	**(24,413)**	**(20,926)**	**(18,193)**	**(15,737)**	**(13,467)**	**(11,672)**	**(10,019)**	**(6740)**	**(4080)**
					2.15	4.2	6.4	7.5	8.6	9.9	11.3	13.0	14.9	19.3	29.3
					(7'1")	**(2.6)**	**(4.0)**	**(4.7)**	**(5.3)**	**(6.1)**	**(7.0)**	**(8.1)**	**(9.3)**	**(12.0)**	**(18.1)**
Challenger 65C	2ZJ	93-95	285/225	14 330	3.24	12 587	9574	8186	7156	6147	5230	4497	3855	2701	1637
				(31,530)	**(10'8")**	**(27,750)**	**(21,106)**	**(18,046)**	**(15,775)**	**(13,551)**	**(11,530)**	**(9914)**	**(8498)**	**(5955)**	**(3610)**
					2.29	4.2	6.4	7.5	8.6	9.9	11.3	13.0	14.9	19.3	29.1
					(7'5")	**(2.6)**	**(4.0)**	**(4.7)**	**(5.3)**	**(6.1)**	**(7.0)**	**(8.1)**	**(9.3)**	**(12.0)**	**(18.1)**
Challenger 65D	2ZJ	95-97	300	14 909	3.24	12 689	10 706	9161	7934	6837	5843	5005	4256	3119	2030
				(32,875)	**(10'8")**	**(27,975)**	**(23,603)**	**(20,197)**	**(17,492)**	**(15,072)**	**(12,881)**	**(11,034)**	**(9382)**	**(6875)**	**(4475)**
					2.29	4.2	6.4	7.5	8.6	9.9	11.3	13.0	14.9	19.3	29.1
					(7'5")	**(2.6)**	**(4.0)**	**(4.7)**	**(5.3)**	**(6.1)**	**(7.0)**	**(8.1)**	**(9.3)**	**(12.0)**	**(18.1)**
Challenger 65E		97-02	310/277	15 186	3.4	15 098	10 808	9265	8096	6964	6017	5247	4469	3396	2279
				(33,480)	**(11'2")**	**(33,284)**	**(23,827)**	**(20,425)**	**(17,849)**	**(15,352)**	**(13,265)**	**(11,567)**	**(9853)**	**(7488)**	**(5025)**
						4.3	6.4	7.6	8.7	10.0	11.3	12.9	14.8	19.3	29.0
						(2.7)	**(4.0)**	**(4.7)**	**(5.4)**	**(6.2)**	**(7.0)**	**(8.0)**	**(9.2)**	**(12.0)**	**(18.0)**
Challenger 70C	2YL	93-95	1st Gear	16 201	3.24	12 621	9574	8186	7156	6147	5230	4497	3855	2701	1637
			215/154	**(35,685)**	**(10'8")**	**(27,825)**	**(21,106)**	**(18,046)**	**(15,775)**	**(13,551)**	**(11,530)**	**(9914)**	**(8498)**	**(5955)**	**(3610)**
			2nd & up		2.29	4.2	6.4	7.5	8.6	9.9	11.3	13.0	14.9	19.3	21.1
			285/225		**(7'5")**	**(2.6)**	**(4.0)**	**(4.7)**	**(5.3)**	**(6.1)**	**(7.0)**	**(8.1)**	**(9.3)**	**(12.0)**	**(18.1)**
Challenger 75	4CJ	91-92	325/256	14 060	3.24	15 391	12 371	10 753	9382	8073	6923	6017	5162	3588	2181
				(31,000)	**(10'8")**	**(33,931)**	**(27,273)**	**(23,706)**	**(20,684)**	**(17,797)**	**(15,263)**	**(13,264)**	**(11,379)**	**(7910)**	**(4830)**
					2.15	4.2	6.4	7.5	8.6	9.9	11.3	13.0	14.9	19.3	29.3
					(7'1")	**(2.6)**	**(4.0)**	**(4.7)**	**(5.3)**	**(6.1)**	**(7.0)**	**(8.1)**	**(9.3)**	**(12.0)**	**(18.1)**
Challenger 75C	4KK	92-97	325/268	15 158	3.24	12 689	10 761	9329	8106	6932	5944	5095	4380	3075	1878
				(33,419)	**(10'8")**	**(27,975)**	**(23,724)**	**(20,567)**	**(17,871)**	**(15,282)**	**(13,105)**	**(11,232)**	**(9657)**	**(6780)**	**(4140)**
					2.29	4.2	6.4	7.5	8.6	9.9	11.3	13.0	14.9	19.3	29.1
					(7'5")	**(2.6)**	**(4.0)**	**(4.7)**	**(5.3)**	**(6.1)**	**(7.0)**	**(8.1)**	**(9.3)**	**(12.0)**	**(18.1)**
Challenger 75D	5AR	96-97	330	14 878	3.24	12 884	12 562	10 919	9526	8197	7030	6109	5241	3643	2225
				(32,800)	**(10'8")**	**(28,406)**	**(27,693)**	**(24,071)**	**(21,003)**	**(18,071)**	**(15,498)**	**(13,468)**	**(11,554)**	**(8031)**	**(4904)**
					2.29	4.2	6.4	7.5	8.6	9.9	11.3	13.0	14.9	19.3	29.1
					(7'5")	**(2.6)**	**(4.0)**	**(4.7)**	**(5.3)**	**(6.1)**	**(7.0)**	**(8.1)**	**(9.3)**	**(12.0)**	**(18.1)**
Challenger 75E		97-02	340/301	15 186	3.4	15 174	11 696	9402	8155	7015	6412	5543	4798	3502	2447
				(33,480)	**(11'2")**	**(33,452)**	**(25,785)**	**(20,728)**	**(17,979)**	**(15,466)**	**(14,135)**	**(12,221)**	**(10,578)**	**(7722)**	**(5395)**
					2.29	4.5	6.4	7.9	9.0	10.3	11.3	12.9	14.8	20.1	29.0
					(7'6")	**(2.8)**	**(4.0)**	**(4.9)**	**(5.6)**	**(6.4)**	**(7.0)**	**(8.0)**	**(9.2)**	**(12.5)**	**(18.0)**
Challenger 85C	9TK	92-97	1-2 Gears		3.24	12 689	11 596	9544	8302	7089	6406	5490	4720	3146	2024
			325/216		**(10'8")**	**(27,975)**	**(25,565)**	**(21,042)**	**(18,304)**	**(15,629)**	**(14,122)**	**(12,104)**	**(10,406)**	**(6935)**	**(4461)**
			3-10												
			Gears		2.29	4.5	6.4	7.9	9.0	10.5	11.3	13.0	14.9	20.3	29.1
			355/272		**(7'5")**	**(2.8)**	**(4.0)**	**(4.9)**	**(5.6)**	**(6.5)**	**(7.0)**	**(8.1)**	**(9.3)**	**(12.6)**	**(18.1)**
Challenger 85D	4GR	96-97	Gears	15 286	3.24	15 529	10 684	9599	8247	7175	6590	5705	4887	3825	2461
			1-2 330	**(33,700)**	**(10'8")**	**(34,234)**	**(23,553)**	**(21,162)**	**(18,181)**	**(15,819)**	**(14,528)**	**(12,578)**	**(10,774)**	**(8432)**	**(5425)**
			3-5 360		2.29	4.0	6.25	7.75	8.9	10.2	11.2	12.8	14.7	20.3	29.1
			6-10 370		**(7'5")**	**(2.5)**	**(3.9)**	**(4.8)**	**(5.5)**	**(6.4)**	**(7.0)**	**(8.0)**	**(9.2)**	**(12.6)**	**(18.1)**
Challenger 85E		97-02	375/339	15 413	3.4	15 454	11 576	10 566	9177	7997	7268	6323	5417	3954	2763
				(33,980)	**(11'2")**	**(34,070)**	**(25,520)**	**(23,294)**	**(20,232)**	**(17,629)**	**(16,022)**	**(13,940)**	**(11,942)**	**(8718)**	**(6090)**
					2.29	4.5	6.4	7.9	9.0	10.3	11.3	12.9	14.8	20.1	29.0
					(7'6")	**(2.8)**	**(4.0)**	**(4.9)**	**(5.6)**	**(6.4)**	**(7.0)**	**(8.0)**	**(9.2)**	**(12.5)**	**(18.0)**

*Drawbar pull figures for SA and SR models are max. at lug.

NOTE: Drawbar pull figures for the Challenger 65 is at max. power as found in University of Nebraska Tractor Test no. 1268. This test was performed on concrete. Therefore, usable drawbar pull may be less depending upon soil conditions.

Agricultural Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Height m (ft) Gauge m (ft)	Drawbar Pull kg (lb)* and Forward Speed km/h (mph) 1st	2nd	3rd	4th	5th	6th	7th	8th	9th	10th
Challenger 95E		97-02	410/375	15 413 (33,980)	3.4 (11'2")	15 968 (35,202)	11 506 (25,366)	10 505 (23,159)	10 085 (22,234)	8729 (19,244)	7903 (17,423)	6865 (15,134)	5901 (13,009)	4308 (9497)	3010 (6635)
					2.29 (7'6")	4.5 (2.8)	6.4 (4.0)	7.9 (4.9)	9.0 (5.6)	10.3 (6.4)	11.3 (7.0)	12.9 (8.0)	14.8 (9.2)	20.1 (12.5)	29.0 (18.0)
D3B SA	2PC	85-87	101	6650 (14,670)	2.71 (8'11")	7634 (16,830)	6226 (13,725)	5306 (11,700)	4531 (9990)	3888 (8573)					
						4.1 (2.5)	5.0 (3.1)	5.7 (3.6)	6.5 (4.0)	7.6 (4.7)					
D3C SA	7JF	87-92	101	7202 (15,846)	2.71 (8'11")	5552 (12,250)	4521 (9960)	3827 (8450)	3235 (7130)	2755 (6070)					
					1.52 (5'0")	4.1 (2.5)	5.0 (3.1)	5.7 (3.6)	6.5 (4.0)	7.6 (4.7)					
D4D SA	20J	66-68	—/68	6750 (14,900)	2.44 (8'0")	4590 (10,120)	3928 (8660)	3098 (6830)	2631 (5800)	2232 (4920)					
					1.52 (5'0")	4.0 (2.5)	4.7 (2.9)	5.6 (3.5)	6.4 (4.0)	7.4 (4.6)					
D4D SA	84J	66	—/68	6470 (14,270)	2.67 (8'9")	4880 (10,750)	4170 (9200)	3310 (7300)	2840 (6260)	2420 (5330)					
					1.52 (5'0")	4.0 (2.5)	4.7 (2.9)	5.6 (3.5)	6.4 (4.0)	7.4 (4.6)					
D4E SA	7PB	84-89	97	7600 (16,760)	2.71 (8'11")	5901 (13,102)	5148 (11,349)	5831 (12,859)	5002 (11,027)	4433 (9773)					
	2CB	84-91				3.4 (2.1)	4.6 (2.8)	5.5 (3.5)	6.4 (4.0)	8.3 (5.1)					
D4E SA	29X	77-84	—/74	7585 (16,722)	2.72 (8'11")	5802 (12,791)	4986 (10,993)	4007 (8835)	3814 (8408)	2896 (6384)					
					1.52 (5'0")	4.1 (2.5)	4.7 (2.9)	5.8 (3.6)	6.6 (4.1)	7.5 (4.7)					
D4E SR		84-99	125/—	9400 (20,730)	1.93 (6'4")	5450 (12,010)	3744 (8250)	5068 (11,170)	4408 (9715)	3832 (8450)					
					1.52 (5'0")										
D5 SA	21J	67-67	—/90	9300 (20,400)	2.64 (8'8")	6620 (14,580)	5160 (11,360)	3990 (8740)	3080 (6790)	2290 (5030)					
					1.88 (6'2")										
D5 SA	98J	67-77	—/90	9660 (21,300)	2.95 (9'8")	6120 (13,500)	5180 (11,410)	4110 (9950)	3640 (7620)	2950 (6500)	2250 (4970)				
					1.88 (6'2")	3.7 (2.3)	4.6 (2.9)	5.8 (3.6)	7.1 (4.4)	8.8 (5.5)					
D5B SA	26X	77-84	—/90		2.77 (9'1")	6409 (14,130)	5384 (11,870)	4323 (9530)	3688 (8130)	3180 (7010)	2486 (5480)				
					1.88 (6'2")	4.0 (2.5)	4.7 (2.9)	5.6 (3.5)	6.6 (4.1)	7.4 (4.6)	9.0 (5.6)				
D5B SA	22X	77-82	105/—	11 283 (24,875)	2.77 (9'1")	8060 (17,770)	5030 (11,100)	3410 (7520)	2290 (5060)	1480 (3260)					
					1.52 (5'0")	2.7 (1.7)	4.2 (2.6)	5.8 (3.6)	8.0 (5.0)	11.1 (6.9)					
D5B SA	24X	77-84	105/—	11 619 (25,615)	2.77 (9'1")										
					1.52 (5'0")	3.5 (2.2)	6.1 (3.8)	10.1 (6.3)							

*Drawbar pull figures for SA and SR models are max. at lug.

NOTE: Drawbar pull figures for the Challenger 65 is at max. power as found in University of Nebraska Tractor Test no. 1268. This test was performed on concrete. Therefore, usable drawbar pull may be less depending upon soil conditions.

Agricultural Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power FW/ Drawbar	Approx. Machine Weight kg (lb)	Height m (ft) Gauge m (ft)	Drawbar Pull kg (lb)* and Forward Speed km/h (mph) 1st	2nd	3rd	4th	5th	6th	7th	8th	9th	10th
D6C SA	17R	70-76	140	13 064	2.67	850	6970	5880	4810	4080	3190				
				(28,800)	**(8'9")**	**(18,750)**	**(15,370)**	**(12,780)**	**(10,610)**	**(9000)**	**(7030)**				
						4.0	4.8	5.6	6.4	7.4	8.8				
						(2.5)	**(3.0)**	**(3.5)**	**(4.0)**	**(4.6)**	**(5.5)**				
D6D SR	7XF	89-91	140	15 200	2.87	14 358	12 429	11 721	7067	6096	4931				
				(33,500)	**(9'5")**	**(31,645)**	**(27,394)**	**(25,833)**	**(15,576)**	**(13,436)**	**(10,868)**				
						2.0	2.9	4.1	6.5	7.4	8.9				
						(1.2)	**(1.8)**	**(2.5)**	**(4.0)**	**(4.6)**	**(5.5)**				
D6D SA 123-161 kW (165-215 HP)	38C	83-91	165	14 500	2.87	10 098	8510	9210	7789	6732	5456				
				(32,000)	**(9'5")**	**(22,243)**	**(18,744)**	**(20,287)**	**(17,156)**	**(14,828)**	**(12,017)**				
						4.5	5.3	6.1	7.1	8.2	9.8				
						(2.8)	**(3.3)**	**(3.8)**	**(4.4)**	**(5.1)**	**(6.1)**				
D6D SA 123-179 kW (165-240 HP)	19B	83-91	165	14 500	2.87	10 098	8510	7181	8732	7560	6144				
				(32,000)	**(9'5")**	**(22,243)**	**(18,744)**	**(15,817)**	**(19,234)**	**(16,651)**	**(13,532)**				
						4.5	5.3	6.1	7.1	8.2	9.8				
						(2.8)	**(3.3)**	**(3.8)**	**(4.4)**	**(5.1)**	**(6.1)**				
D6E SR	8FJ	91-96	155/216	14 960	2.03	11 308	7771	8130	6866	5926	3135				
			121/170	**(32,987)**	**(6'8")**	**(24,878)**	**(17,097)**	**(17,887)**	**(15,105)**	**(13,037)**	**(6987)**				
					1.88	3.0	4.3	5.8	6.8	7.7	9.3				
					(6'2")	**(1.9)**	**(2.7)**	**(2.6)**	**(4.3)**	**(4.8)**	**(5.8)**				
Ag 6 Generation One	05X	77-86	165/240	14 787	3.43	10 034	8455	7134	9041	7830					
				(32,600)	**(11'3")**	**(22,120)**	**(18,639)**	**(15,727)**	**(19,931)**	**(17,268)**					
						4.5	5.3	6.1	7.1	8.2					
						(2.8)	**(3.3)**	**(3.8)**	**(4.4)**	**(5.1)**					
Ag 6 Generation Two	05X	77-86	200/240	14 787	3.48	12 407	10 482	10 667	9091	7830					
				(32,600)	**(11'5")**	**(27,353)**	**(23,110)**	**(23,514)**	**(19,931)**	**(17,263)**					
						4.5	5.3	6.1	7.1	8.2					
						(2.8)	**(3.3)**	**(3.8)**	**(4.4)**	**(5.1)**					
D7G SA std. trans.	35N	80-86	250	18 462	3.2	19 101	13 622	11 358	10 015	8627	7584				
				(40,700)	**(10'6")**	**(42,110)**	**(30,030)**	**(25,040)**	**(22,080)**	**(19,020)**	**(16,720)**				
						3.5	4.8	5.6	6.4	7.2	8.2				
						(2.2)	**(3.0)**	**(3.5)**	**(4.0)**	**(4.5)**	**(5.1)**				
D7G SA std. trans. 168-186 kW (225-250 HP)		77-86	250	18 462	3.2	16 990	12 090	11 358	10 015	8627	7584				
				(40,700)	**(10'6")**	**(37,424)**	**(26,631)**	**(25,040)**	**(22,080)**	**(19,020)**	**(16,720)**				
						3.5	4.8	5.6	6.4	7.2	8.2				
						(2.2)	**(3.0)**	**(3.5)**	**(4.0)**	**(4.5)**	**(5.1)**				
D8L SA		84-87	400	36 650	3.87	40 252	39 466	22 013	15 953	11 880	8446				
				(80,820)	**(12'8")**	**(88,740)**	**(64,960)**	**(48,530)**	**(35,170)**	**(26,190)**	**(18,620)**				
					2.2	2.9	3.9	5.0	6.8	8.9	11.9				
					(7'3")	**(1.8)**	**(2.4)**	**(3.1)**	**(4.2)**	**(5.5)**	**(7.4)**				

*Drawbar pull figures for SA and SR models are max. at lug.

NOTE: Drawbar pull figures for the Challenger 65 is at max. power as found in University of Nebraska Tractor Test no. 1268. This test was performed on concrete. Therefore, usable drawbar pull may be less depending upon soil conditions.



MOTOR GRADERS

Model	Product Ident. No. Prefix	Years Built	Horse-power, Rated	Approx. Ship Wt. kg (lb)	Wheel-base m (ft)	Length m (ft)	Width m (ft)	Mold-board Length m (ft)	Turning Radius m (ft)	Controls	Maximum Speed km/h (mph) Forward	Maximum Speed km/h (mph) Rev.
212TD	79C	54-57	50	6030 **(13,290)**	5.03 **(16'6")**	6.68 **(21'11")**	2.07 **(6'10")**	3.05 **(10'0")**	11.10 **(36'5")**	Mech.	18.1 **(11.2)**	4.2 **(2.6)**
112	3U	47-59	70	8770 **(19,330)**	5.72 **(18'9")**	7.59 **(24'11")**	2.39 **(7'10")**	3.66 **(12'0")**	10.87 **(35'8")**	Mech.	25.7 **(16.0)**	6.4 **(4.0)**
112	81C	55-59	75	9435 **(20,805)**	5.72 **(18'9")**	7.59 **(24'11")**	2.39 **(7'10")**	3.66 **(12'0")**	10.74 **(35'3")**	Mech.	25.7 **(16.0)**	6.4 **(4.0)**
112E	68E(U.S.)	59-64	85	9500 **(20,900)**	5.72 **(18'9")**	7.62 **(25'0")**	2.36 **(7'9")**	3.66 **(12'0")**	10.74 **(35'3")**	Mech.	29.3 **(18.2)**	9.3 **(5.8)**
	91G(U.S.)	64-68										
112F	82F(U.S.)	60-64	100	9800 **(21,600)**	5.72 **(18'9")**	7.82 **(25'8")**	2.36 **(7'9")**	3.66 **(12'0")**	10.70 **(35'3")**	Mech.	29.9 **(18.6)**	9.7 **(6.0)**
	46D(U.S.)	64-68										
	74H(U.S.)	67-68										
	89J(U.S.)	68-74										
	80J(AUSTL)	69-84										
120	89G(U.S.)	64-67	115	10 480 **(23,100)**	5.71 **(18'9")**	7.62 **(25'0")**	2.36 **(7'9")**	3.66 **(12'0")**	10.74 **(35'3")**	Mech.	32.2 **(20.0)**	10.3 **(6.4)**
120	14K(U.S.)	67-69	125	10 600 **(23,500)**	5.71 **(18'9")**	7.80 **(25'8")**	2.36 **(7'9")**	3.66 **(12'0")**	10.74 **(35'3")**	Mech.	32.2 **(20.0)**	41.5 **(25.8)**
120	10R(U.S.)	69-74	125	10 700 **(23,700)**	5.85 **(19'2")**	7.95 **(26'1")**	2.36 **(7'9")**	3.66 **(12'0")**	10.90 **(35'9")**	Mech.	32.2 **(20.0)**	6.6 **(4.1)**
120	13U(U.S.)	71-74	125	11 000 **(24,300)**	5.85 **(19'2")**	7.95 **(26'1")**	2.36 **(7'9")**	3.66 **(12'0")**	10.90 **(35'9")**	Mech.	32.2 **(20.0)**	6.6 **(4.1)**
120B	64U(BRAZ)	72-89	125	12 000 **(26,460)**	5.85 **(19'2")**	7.92 **(26'0")**	2.36 **(7'9")**	3.66 **(12'0")**	10.90 **(35'9")**	Mech.	35.4 **(22.0)**	23.8 **(14.8)**
120G	87V(U.S.)	73-95	125	12 859 **(28,350)**	5.69 **(18'8")**	7.92 **(26'0")**	2.45 **(8'0")**	3.66 **(12'0")**	6.7 **(22'0")**	Hyd.	40.9 **(25.4)**	40.9 **(25.4)**
	4HD(BRAZ)	86-95										
	11W(AUSTL)	75-95										
	82V(CAN)	74-80										
120H	4MK(U.S.)	95-02	125/140	12 520 **(27,600)**	5.86 **(19'3")**	8.26 **(27'1")**	2.44 **(7'11")**	3.66 **(12'0")**	7.2 **(23'8")**	Hyd.	42.6 **(26.5)**	33.7 **(20.9)**
	6NM(U.S.)											
	9YR(BRAZ)											
	2AN(AUSTL)											
	3GR(S. AFRICA)											
	124 (AUSTL)	03-05										
	ALZ(U.S.)	02-04										
	CAF(BRAZ)	03-07										
120H	ALZ(U.S.)	02-03	125/140	12 650 **(27,880)**	5.92 **(19'5")**	8.31 **(27'3")**	2.44 **(8'0")**	3.66 **(12'0")**	7.3 **(23'7")**	Hyd.	42.6 **(26.5)**	33.7 **(20.9)**
	CAF(BRAZ)	02-07										
	124(AUSTL)	03-05										
120H STD	6TM(U.S.)	96-99	125/140	12 466 **(27,483)**	5.87 **(19'3")**	8.15 **(26'9")**	2.44 **(8'0")**	3.66 **(12'0")**	7.2 **(23'8")**	Hyd.	42.6 **(26.5)**	33.7 **(20.9)**
	5FM(BRAZ)	96-09										
	9FN(INDO)	96-04										

Motor Graders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power, Rated	Approx. Ship Wt. kg (lb)	Wheel-base m (ft)	Length m (ft)	Width m (ft)	Mold-board Length m (ft)	Turning Radius m (ft)	Controls	Maximum Speed km/h (mph) Forward	Maximum Speed km/h (mph) Rev.
130G	74V(U.S.)	73-95	135	13 050	5.92	8.30	2.45	3.66	7.3	Hyd.	39.4	39.4
	12W(AUSTL)	75-89		**(28,770)**	**(19'5")**	**(27'3")**	**(8'0")**	**(12'0")**	**(24'0")**		**(24.5)**	**(24.5)**
135H	3YK(U.S.)	95-02	135/155	12 950	5.86	8.26	2.44	3.66	7.2	Hyd.	41.9	33.1
	AMX(U.S.)	02-04		**(28,550)**	**(19'3")**	**(27'1")**	**(7'11")**	**(12'0")**	**(23'8")**		**(26.0)**	**(20.6)**
	CBC(BRAZ)	03-07										
135H	AMX(U.S.)	02-04	135/155	13 080	5.92	8.31	2.44	3.66	7.3	Hyd.	41.9	33.1
	CBC(BRAZ)	02-07		**(28,840)**	**(19'5")**	**(27'3")**	**(8'0")**	**(12'0")**	**(23'7")**		**(26.1)**	**(20.6)**
12	6M(U.S.)	39-42	66	9440	5.72	7.62	2.39	3.66	10.87	Mech.	24.5	6.1
				(20,820)	**(18'9")**	**(25'0")**	**(7'10")**	**(12'0")**	**(35'8")**		**(15.2)**	**(3.8)**
12	9K(U.S.)	38-45	70	9590	5.72	7.62	2.39	3.66	10.87	Mech.	24.5	6.1
				(21,140)	**(18'9")**	**(25'0")**	**(7'10")**	**(12'0")**	**(35'8")**		**(15.2)**	**(3.8)**
12	7T(U.S.)	45-47	75	9750	5.72	7.62	2.39	3.66	10.87	Mech.	24.5	6.1
				(21,500)	**(18'9")**	**(25'0")**	**(7'10")**	**(12'0")**	**(35'8")**		**(15.2)**	**(3.8)**
12	8T(U.S.)	47-55	100	10 100	5.72	7.62	2.39	3.66	10.87	Mech.	31.1	6.6
	94C(AUSTL)	55-58		**(22,375)**	**(18'9")**	**(25'0")**	**(7'10")**	**(12'0")**	**(35'8")**		**(19.3)**	**(4.1)**
12	70D-71D(U.S.)	57-59	115	10 200	5.72	7.62	2.37	3.66	10.87	Mech.	31.1	10.1
	80C(U.S.)	55-67		**(22,410)**	**(18'9")**	**(25'0")**	**(7'10")**	**(12'0")**	**(35'8")**		**(19.3)**	**(6.3)**
	38E(AUSTL)	58-60										
12E	99E(U.S.)	59-65	115	11 100	5.72	8.03	2.36	3.66	10.90	Mech.	32.0	22.2
	21F(AUSTL)	60-68		**(24,400)**	**(18'9")**	**(26'4")**	**(7'9")**	**(12'0")**	**(35'9")**		**(19.9)**	**(13.8)**
	17K(AUSTL)	68-75										
12F	73G(U.S.)	65-67	115	12 973	6.0	8.20	2.36	3.66	11.40	Hyd.	32.0	22.2
				(28,600)	**(19'8")**	**(26'10")**	**(7'9")**	**(12'0")**	**(37'5")**	Mech.	**(19.9)**	**(13.8)**
12F	89H(U.S.)	69-73	125	12 973	6.00	8.20	2.36	3.65	11.40	Hyd.	34.3	41.5
	13K(U.S.)	67-73		**(28,600)**	**(19'8")**	**(26'10")**	**(7'9")**	**(12'0")**	**(37'5")**	Mech.	**(21.3)**	**(25.8)**
12G	61M(U.S.)	73-95	135	13 554	5.92	8.30	2.45	3.66	7.30	Hyd.	39.4	39.4
	3PL(BRAZ)	93-95		**(29,860)**	**(19'5")**	**(27'3")**	**(8'0")**	**(12'0")**	**(24'0")**		**(24.5)**	**(24.5)**
	3WC(AUSTL)	85-95										
12H	4XM(U.S.)	95-02	140	14 247	6.10	8.57	2.44	3.66	7.40	Hyd.	39.7	31.3
	2LR(U.S.)			**(31,410)**	**(20'0")**	**(28'1")**	**(7'11")**	**(12'0")**	**(24'3")**		**(24.7)**	**(19.5)**
	8MN(BRAZ)											
	2GS(BRAZ)											
	2WR(AUSTL)											
	AMZ(U.S.)	02-07										
	CBK(BRAZ)	02-07										
	125(AUSTL)	03-05										
12H	AMZ(U.S.)	02-07	145/185	14 200	6.09	8.57	2.44	3.66	7.40	Hyd.	44.0	34.7
	CBK(BRAZ)	02-07		**(31,320)**	**(20'0")**	**(28'1")**	**(8'0")**	**(12'0")**	**(24'3")**		**(27.4)**	**(21.6)**
	125(AUSTL)	03-05										
12H	5ZM(U.S.)	97-98	140	14 185	6.09	8.45	2.44	3.66	7.4	Hyd.	41.7	32.9
STD	4ER(BRAZ)	96-09		**(31,273)**	**(20'0")**	**(27'9")**	**(8'0")**	**(12'0")**	**(24'3")**		**(25.9)**	**(20.5)**
	XZJ(CHINA)	06-10										

Motor Graders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power, Rated	Approx. Ship Wt. kg (lb)	Wheel-base m (ft)	Length m (ft)	Width m (ft)	Mold-board Length m (ft)	Turning Radius m (ft)	Controls	Maximum Speed km/h (mph) Forward	Maximum Speed km/h (mph) Rev.
140	14U(U.S.)	71-74	150	13 109	5.84	7.95	2.44	3.66	10.97	Mech.	38.8	47.0
	11R(U.S.)	70-74		**(28,900)**	**(19'2")**	**(26'1")**	**(8'0")**	**(12'0")**	**(36'0")**		**(24.1)**	**(29.2)**
	55F(AUSTL)	71-75										
	24R(CAN)	71-74										
140B	61S(BRAZ)	81-87	150	13 620	6.14	8.07	2.39	3.96	11.60	Mech.	37.6	25.6
				(30,003)	**(20'2")**	**(26'6")**	**(7'10")**	**(13'0")**	**(38'0")**		**(23.4)**	**(15.9)**
140G	72V(U.S.)	73-95	150	14 102	5.92	8.33	2.45	3.66	7.30	Hyd.	41.0	41.0
	5MD(BRAZ)	87-95		**(31,090)**	**(19'5")**	**(27'4")**	**(8'0")**	**(12'0")**	**(24'0")**		**(25.5)**	**(25.5)**
	13W(AUSTL)	75-95										
	81V(CAN)	74-80										
140G	72V(U.S.)	73-95	150	14 914	5.92	8.33	2.45	3.66	7.30	Hyd.	41.0	41.0
AWD				**(32,880)**	**(19'5")**	**(27'4")**	**(8'0")**	**(12'0")**	**(24'0")**		**(25.5)**	**(25.5)**
140H	2ZK(U.S.)	95-02	165/185	14 724	6.10	8.60	2.46	3.66	7.40	Hyd.	41.1	32.4
	8KM(U.S.)			**(32,460)**	**(20'0")**	**(28'3")**	**(8'1")**	**(12'0")**	**(24'3")**		**(25.5)**	**(20.2)**
	9TN(BRAZ)											
	3AS(BRAZ)											
	9ZN(AUSTL)											
	APM(U.S.)	02-07										
	CCA(BRAZ)	02-07										
	126(AUSTL)	03-05										
140H	APM(U.S.)	02-07	165/205	14 677	6.17	8.71	2.46	3.66	7.5	Hyd.	44.0	34.7
	CCA(BRAZ)	02-07		**(32,357)**	**(20'3")**	**(28'7")**	**(8'1")**	**(12'0")**	**(24'7")**		**(27.4)**	**(21.6)**
	126(AUSTL)	03-05										
140H	8JM(U.S.)	96-99	165/185	14 661	6.09	8.60	2.46	3.66	7.4	Hyd.	41.1	32.4
STD	5HM(BRAZ)	96-09		**(32,321)**	**(20'0")**	**(28'3")**	**(8'1")**	**(12'0")**	**(24'3")**		**(25.5)**	**(20.2)**
	XZH(CHINA)	05-10										
143H	1AL(U.S.)	95-02	165/185	15 023	6.10	8.60	2.46	3.66	7.40	Hyd.	41.1	32.4
	APN(U.S.)	02-07		**(33,120)**	**(20'0")**	**(28'3")**	**(8'1")**	**(12'0")**	**(24'3")**		**(25.5)**	**(20.2)**
143H	APN(U.S.)	02-07	165/205	15 270	6.17	8.71	2.55	3.66	7.5	Hyd.	44.0	34.7
				(33,670)	**(20'3")**	**(28'7")**	**(8'5")**	**(12'0")**	**(24'7")**		**(27.4)**	**(21.6)**
14B	78E(U.S.)	59-59	150	13 300	5.84	8.03	2.44	3.66	10.97	Mech.	34.8	11.3
	64C(U.S.)	59-69		**(29,280)**	**(19'2")**	**(26'4")**	**(8'0")**	**(12'0")**	**(36'0")**		**(21.6)**	**(7.0)**
14C	35F(U.S.)	59-61	150	12 973	5.84	8.03	2.44	3.66	10.97	Mech.	34.8	11.3
				(28,600)	**(19'2")**	**(26'4")**	**(8'0")**	**(12'0")**	**(36'0")**		**(21.6)**	**(7.0)**
14D	96F(U.S.)	61-65	150	13 700	6.15	8.33	2.44	3.96	11.58	Mech.	34.1	23.5
				(30,300)	**(20'2")**	**(27'4")**	**(8'0")**	**(13'0")**	**(38'0")**		**(21.2)**	**(14.6)**
14E	99G(U.S.)	65-68	150	13 699	6.15	8.33	2.44	3.96	11.58	Hyd.	36.4	24.9
				(30,200)	**(20'2")**	**(27'4")**	**(8'0")**	**(13'0")**	**(38'0")**	Mech.	**(22.6)**	**(15.5)**
14E	12K(U.S.)	67-73	150	14 300	6.10	8.30	2.44	3.96	11.60	Hyd.	39.1	47.3
	72G(U.S.)	69-73		**(31,600)**	**(20'2")**	**(27'4")**	**(8'0")**	**(13'0")**	**(38'0")**	Mech.	**(24.3)**	**(29.4)**
14G	96U(U.S.)	73-95	200	20 688	6.45	9.21	2.83	4.27	7.90	Hyd.	43.0	50.1
				(45,610)	**(21'2")**	**(30'3")**	**(9'3")**	**(14'0")**	**(25'11")**		**(26.8)**	**(31.1)**
14H	7WJ(U.S.)	95-02	215	18 784	6.45	9.21	2.70	4.27	7.90	Hyd.	42.7	47.3
	ASE(U.S.)	02-07		**(41,410)**	**(21'2")**	**(30'2")**	**(8'10")**	**(14'0")**	**(25'11")**		**(26.5)**	**(29.4)**
14H	ASE(U.S.)	02-07	220/240	18 809	6.56	9.34	2.82	4.27	8.0	Hyd.	46.1	51.1
				(41,465)	**(21'6")**	**(30'8")**	**(9'3")**	**(14'0")**	**(26'4")**		**(28.7)**	**(31.8)**
14M	B9J	07-10	259/275	21,676	6.56	9.35	2.8	4.27	7.9	Electro-	50.4	39.8
	R9J	10-15		**(47,787)**	**(21'6")**	**(30'8")**	**(9'2")**	**(14'0")**	**(25'11")**	Hyd	**(31.3)**	**(24.7)**