Motor Graders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power, Rated	Approx. Ship Wt. kg (lb)	Wheel-base m (ft)	Length m (ft)	Width m (ft)	Mold-board Length m (ft)	Turning Radius m (ft)	Controls	Maximum Speed km/h (mph) Forward	Maximum Speed km/h (mph) Rev.
160H	9EJ(U.S.)	95-02	180/200	15 586	6.10	8.60	2.46	4.27	7.40	Hyd.	40.7	32.1
	6WM(U.S.)			**(34,360)**	**(20'0")**	**(28'3")**	**(8'1")**	**(14'0")**	**(24'3")**		**(25.3)**	**(20.0)**
	3GM(BRAZ)											
	2HS(BRAZ)											
	ASD(U.S.)	02-07										
	CCP(BRAZ)	02-07										
160H	ASD(U.S.)	02-07	180/220	15 676	6.17	8.71	2.48	4.27	7.5	Hyd.	43.6	34.4
	CCP(BRAZ)	03-07		**(34,560)**	**(20'3")**	**(28'7")**	**(8'2")**	**(14'0")**	**(24'7")**		**(27.1)**	**(21.4)**
160H	9JM(U.S.)	96-99	180/200	15 524	6.09	8.49	2.46	4.27	7.4	Hyd.	40.7	32.1
STD	2FM(BRAZ)	96-98		**(34,225)**	**(20'0")**	**(27'10")**	**(8'1")**	**(14'0")**	**(24'3")**		**(25.3)**	**(20.0)**
	XZK(CHINA)	06-10										
163H	5AK(U.S.)	95-02	180/200	16 538	6.10	8.60	2.46	4.27	7.40	Hyd.	40.7	32.1
	ARL(U.S.)	02-07		**(36,460)**	**(20'0")**	**(28'3")**	**(8'1")**	**(14'0")**	**(24'3")**		**(25.3)**	**(20.0)**
163H	ARL(U.S.)	02-07	180/220	16 280	6.17	8.71	2.55	4.27	7.5	Hyd.	43.6	34.4
				(35,890)	**(20'3")**	**(28'7")**	**(8'5")**	**(14'0")**	**(24'7")**		**(27.1)**	**(21.4)**
16	49G(U.S.)	63-73	225	22 499	6.86	9.50	3.00	4.27	13.56	Hyd.	49.7	49.7
				(49,600)	**(22'6")**	**(31'2")**	**(9'10")**	**(14'0")**	**(44'6")**	Mech.	**(30.9)**	**(30.9)**
16G	93U(U.S.)	73-95	275	27 284	6.96	9.99	3.08	4.88	8.20	Hyd.	43.6	43.6
				(60,150)	**(22'10")**	**(32'8")**	**(10'1")**	**(16'0")**	**(27'0")**		**(27.1)**	**(27.1)**
16H	6ZJ(U.S.)	95-02	275	24 748	6.96	9.99	2.99	4.88	8.20	Hyd.	44.5	42.3
	ATS(U.S.)	02-07		**(54,560)**	**(22'10")**	**(32'9")**	**(9'10")**	**(16'0)"**	**(27'0")**		**(27.7)**	**(26.3)**
16H	ATS(U.S.)	02-07	265/285	24 740	6.96	9.99	3.08	4.88	8.2	Hyd.	48.1	45.7
				(54,550)	**(22'10")**	**(32'9")**	**(10'1")**	**(16'0")**	**(26'11")**		**(29.9)**	**(28.4)**
16M	B9H	07-10	291/326	27 531	6.99	9.96	3.10	4.88	8.9	Electro-	51.7	40.8
	R9H	10-15		**(60,695)**	**(22'11")**	**(32'8")**	**(10'2")**	**(16'0")**	**(29'3")**	Hyd	**(32.1)**	**(25.3)**
24H	7KK(U.S.)	96-07	500	61 955	10.23	14.16	4.23	7.3	12.0	Hyd.	37.7	36.1
				(136,611)	**(33'7")**	**(46'6")**	**(13'10")**	**(24'0")**	**(39'11")**		**(23.4)**	**(22.4)**



SKID STEER LOADERS

Model	Product Ident. No. Prefix	Years Built	Approx. Machine Weight kg (lb)	Net Power kW (hp)	Length to Coupler mm (in)	Width over Tires mm (in)**	Height to Top of Cab mm (in)	Engine Model	Top Travel Speed km/h (mph)	Rated Operating Capacity at 50% kg (lb)	Rated Operating Capacity at 50% with counter-weight kg (lb)
216	4NZ	99-03	2490	36	2519	1525	1950	3024C	11.5	635	680
			(5490)	**(48)**	**(99)**	**(60)**	**(77)**		**(7.0)**	**(1400)**	**(1500)**
216B	RLL	04-07	2589	37	2519	1525	1950	3024C	12.7	635	680
			(5709)	**(49)**	**(99)**	**(60)**	**(77)**		**(7.9)**	**(1400)**	**(1500)**
216B2	RLL	07-10	3212	35	2519	1525	1950	C2.2	12.7	635	680
			(7082)	**(47)**	**(99)**	**(60)**	**(77)**		**(7.9)**	**(1400)**	**(1500)**
226	5FZ	99-03	2560	41	2519	1525	1950	3034	11.5	680	726
			(5645)	**(54)**	**(99)**	**(60)**	**(77)**		**(7.0)**	**(1500)**	**(1600)**
226B	MJH	04-07	2646	42	2519	1525	1950	3024CT	12.7	680	726
			(5834)	**(57)**	**(99)**	**(60)**	**(77)**		**(7.9)**	**(1500)**	**(1600)**
226B2	MJH	07-10	3283	42	2519	1525	1950	C2.2T	12.7	680	726
			(7238)	**(56)**	**(99)**	**(60)**	**(77)**		**(7.9)**	**(1500)**	**(1600)**
228	6BZ	99-03	2650	41	2519	1525	1950	3034	11.5	680	726
			(5843)	**(54)**	**(99)**	**(60)**	**(77)**		**(7.0)**	**(1500)**	**(1600)**
232	CAB	02-04	3005	36	2776	1525	1953	3024C	11.1	793	815
			(6627)	**(48)**	**(110)**	**(60)**	**(77)**		**(7.0)**	**(1750)**	**(1795)**
232B	SCH	04-07	3021	37	2760	1525	1953	3024C	11.1	793	815
			(6661)	**(49)**	**(109)**	**(60)**	**(77)**		**(6.9)**	**(1750)**	**(1795)**
232B2	SCH	07-10	3588	42	2760	1525	1950	C2.2T	11.1	862	883
			(7910)	**(56)**	**(109)**	**(60)**	**(77)**		**(6.9)**	**(1900)**	**(1947)**
236	4YZ	99-03	3134	44	2800	1676	2092	3034	12.1	793	839
			(6810)	**(59)**	**(110)**	**(66)**	**(82)**		**(7.5)**	**(1750)**	**(1850)**
236B	HEN	04-07	3178	52	2800	1676	2092	3044C	12.2/18.6*	793	815
			(7007)	**(70)**	**(110)**	**(66)**	**(82)**	DIT	**(7.6/11.6*)**	**(1750)**	**(1850)**
236B2	HEN	07-10	3878	53	2800	1676	2092	C3.4 DIT	12.1	884	929
			(8550)	**(71)**	**(110)**	**(66)**	**(82)**		**(7.5)**	**(1950)**	**(2050)**
236B3	A9H	10-13	3178	53	2800	1676	2092	Cat® C3.4	18.1	884	929
			(7007)	**(71)**	**(110)**	**(66)**	**(82)**	DIT	**(11.2)**	**(1950)**	**(2050)**
242	CMB	02-04	3060	41	2776	1676	1986	3034	11.3	907	930
			(6748)	**(54)**	**(110)**	**(66)**	**(78)**		**(7.0)**	**(2000)**	**(2045)**
242B	BXM	04-07	3085	42	2760	1676	1986	3024CT	12.0	907	930
			(6805)	**(57)**	**(109)**	**(66)**	**(78)**		**(7.4)**	**(2000)**	**(2045)**
242B2	BXM	07-10	3629	42	2760	1676	1986	C2.2T	12.1	952	Standard
			(8000)	**(56)**	**(109)**	**(66)**	**(78)**		**(7.5)**	**(2100)**	on 242B2
242B3	SRS	10-13	3179	53	2760	1676	2019	Cat C3.4	18.4	975	1000
			(7008)	**(71)**	**(108.7)**	**(66)**	**(79)**	DIT	**(11.4)**	**(2150)**	**(2200)**

*With two-speed option.
Models 216-236B with 254 mm **(10") wide tires, 242-268B with 305 mm **(12")** wide tires.

Skid Steer Loaders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Approx. Machine Weight kg (lb)	Net Power kW (hp)	Length to Coupler mm (in)	Width over Tires mm (in)**	Height to Top of Cab mm (in)	Engine Model	Top Travel Speed km/h (mph)	Rated Operating Capacity at 50% kg (lb)	Rated Operating Capacity at 50% with counter-weight kg (lb)
246	5SZ	99-03	3214	55	2800	1676	2092	3034T	12.1	907	952
			(7087)	**(74)**	**(110)**	**(66)**	**(82)**		**(7.5)**	**(2000)**	**(2100)**
246B	PAT	04-07	3239	58	2800	1676	2092	3044CT	12.5/19.1*	907	952
			(7142)	**(78)**	**(110)**	**(66)**	**(82)**		**(7.7/11.8*)**	**(2000)**	**(2100)**
246C	JAY	08-13	3393	54	3692	1676	2104	Cat C3.4	19.3	975	1066
			(7480)	**(73)**	**(145.3)**	**(66)**	**(82.8)**	DIT	**(12.0)**	**(2150)**	**(2350)**
248	6LZ	99-03	3328	55	2800	1676	2092	3034T	12.1	907	952
			(7338)	**(74)**	**(110)**	**(66)**	**(82)**		**(7.5)**	**(2000)**	**(2100)**
248B	SCL	04-07	3320	57	2800	1676	2092	3044C	12.5/19.1*	907	952
			(7321)	**(76)**	**(110)**	**(66)**	**(82)**	DIT	**(7.7/11.8*)**	**(2000)**	**(2100)**
252	FDG	01-03	3454	44	2776	1829	1968	3034	12.1	1020	1043
			(7615)	**(59)**	**(110)**	**(72)**	**(78)**		**(7.5)**	**(2250)**	**(2300)**
252B	SCP	04-07	3552	52	2902	1829	2063	3044C	11.2/17.8*	1134	1134
			(7832)	**(70)**	**(114)**	**(72)**	**(81)**	DIT	**(6.9/11.0*)**	**(2500)**	**(2500)**
252B2	SCP	07-10	4172	53	2901	1829	2063	C3.4 DIT	12.1	1134	1157
			(9198)	**(71)**	**(114)**	**(72)**	**(83)**		**(7.5)**	**(2500)**	**(2551)**
252B3	TNK	10-13	3565	53	2901	1829	2063	Cat C3.4	17.8	1202	1225
			(7861)	**(71)**	**(114.2)**	**(72)**	**(82.6)**	DIT	**(11.1)**	**(2650)**	**(2700)**
262	CED	01-03	3472	55	2902	1829	2098	3034T	12.1	1134	1156
			(7655)	**(74)**	**(114)**	**(72)**	**(83)**		**(7.5)**	**(2500)**	**(2550)**
262B	PDT	04-07	3565	58	2902	1829	2063	3044C	11.6/17.8*	1225	1247
			(7861)	**(78)**	**(114)**	**(72)**	**(81)**	DIT	**(7.2/11.0*)**	**(2700)**	**(2750)**
262C	MST	08-13	3614	61	2979	1676	2104	Cat C3.4	19.3	1225	1336
			(7968)	**(82)**	**(117.3)**	**(66)**	**(82.8)**	DIT	**(12.0)**	**(2700)**	**(2945)**
262C2	TMW	12-13	3614	54	2979	1676	2104	Cat C3.4	19.3	1225	1336
			(7968)	**(73)**	**(117.3)**	**(66)**	**(82.8)**	DIT	**(12.0)**	**(2700)**	**(2945)**
268B	LBA	04-07	3626	57	2902	1829	2063	3044C	11.6/17.8*	1225	1247
			(7995)	**(76)**	**(114)**	**(72)**	**(81)**	DIT	**(7.2/11.0*)**	**(2700)**	**(2750)**
272C	RED	08-13	3793	67	3120	1676	2104	Cat C3.4	16.1	1474	1579
			(8362)	**(90)**	**(122.8)**	**(66)**	**(82.8)**	DIT	**(10.0)**	**(3250)**	**(3480)**
272D	GSL	12-13	3812	71	3139	1930	2104	Cat C3.8	15.1	1451	1565
			(8404)	**(95)**	**(123.6)**	**(76)**	**(82.8)**	DIT	**(9.4)**	**(3200)**	**(3450)**
272D XHP	SHY	12-13	4220	79	3119	1930	2104	Cat C3.8	15.1	1633	—
			(9403)	**(106)**	**(122.8)**	**(76)**	**(84.3)**	DIT	**(9.4)**	**(3600)**	**—**
272D	B5W	13-15	3743	71	3156	1829	2111	Cat C3.8	15.1	1451	1565
			(8252)	**(95)**	**(124.3)**	**(72)**	**(83.1)**	DIT	**(9.4)**	**(3200)**	**(3450)**
272D XHP	ETL	13-15	4220	79	3136	1930	2147	Cat C3.8	16.6	1678	—
			(9403)	**(106)**	**(123.5)**	**(76)**	**(84.5)**	DIT	**(10.3)**	**(3700)**	**—**

*With two-speed option.
Models 216-236B with 254 mm **(10") wide tires, 242-268B with 305 mm **(12")** wide tires.



MULTI TERRAIN LOADERS

Model	Product Ident. No. Prefix	Years Built	Approx. Machine Weight kg (lb)	Net Power kW (hp)	Length to Coupler mm (in)	Width over Tracks mm (in)*	Height to Top of Cab mm (in)	Engine Model	Top Travel Speed km/h (mph)	Rated Operating Capacity at 50% kg (lb)
247	CML	02-04	3023 **(6665)**	41 **(54)**	2518 **(99)**	1676 **(66)**	1990 **(78)**	3034	12.1 **(7.5)**	877 **(1933)**
247B	MTL	04-07	3024 **(6668)**	42 **(57)**	2518 **(99)**	1676 **(66)**	1990 **(78)**	3024CT	12.2 **(7.6)**	885 **(1950)**
247B2	MTL	07-10	3497 **(7710)**	42 **(56)**	2518 **(8'3")**	1676 **(5'6")**	1990 **6'6"**	C2.2T	0-11.3 **(0-7.0)**	929 **(2050)**
247B3	MTL	10-15	3174 **(6997)**	42 **(56)**	2518 **(99.0)**	1676 **(66.0)**	1990 **(78.0)**	Cat C2.2T	11.3 **(7.0)**	975 **(2150)**
257	CMM	02-04	3460 **(7628)**	44 **(59)**	2701 **(106)**	1676 **(66)**	2022 **(80)**	3034T	12.1 **(7.5)**	1046 **(2306)**
257B	SLK	04-07	3428 **(7559)**	42 **(57)**	2701 **(106)**	1676 **(66)**	2022 **(80)**	3024CT	11.4 **(7.1)**	1047 **(2310)**
257B2	SLK	7-10	3906 **(8611)**	42 **(56)**	2701 **(8'10")**	1676 **(5'6")**	2022 **6'7"**	C2.2T	0-11.3 **(0-7.0)**	1134 **(2500)**
257B3	B7H	10-13	3656 **(8060)**	53 **(71)**	2718 **(107)**	1676 **(66)**	2035 **(80)**	Cat C3.4 DIT	16.1 **(10.0)**	1213 **(2675)**
267	CMP	01-04	4134 **(9088)**	44 **(59)**	2923 **(115)**	1898 **(75)**	2074 **(82)**	3034	9.7 **(6.0)**	1315 **(2900)**
267B	CYC	04-07	4250 **(9371)**	52 **(70)**	2923 **(115)**	1898 **(75)**	2074 **(82)**	3044C DIT	11.2 **(7.0)**	1315 **(2900)**
277	CNC	01-04	4148 **(9126)**	55 **(74)**	2923 **(115)**	1898 **(75)**	2074 **(82)**	3034T	9.7 **(6.0)**	1338 **(2950)**
277B	MDH	04-07	4269 **(9411)**	58 **(78)**	2923 **(115)**	1898 **(75)**	2074 **(82)**	3044C DIT	11.2 **(7.0)**	1338 **(2950)**
277C	JWF	08-13	4307 **(9495)**	61 **(82)**	2974 **(117.2)**	1981 **(78)**	2115 **(83.2)**	Cat C3.4 DIT	14.9 **(9.3)**	1451 **(3200)**
277C2	MET	12-13	4307 **(9495)**	54 **(73)**	2974 **(117.2)**	1981 **(78)**	2115 **(83.2)**	Cat C3.4 DIT	14.9 **(9.3)**	1451 **(3200)**
287	CNY	03-04	4471 **(9870)**	55 **(74)**	2900 **(114)**	1962 **(77)**	2122 **(84)**	3034T	11.0 **(7.0)**	1587 **(3500)**
287B	ZSA	04-07	4660 **(10,275)**	58 **(78)**	2900 **(114)**	1962 **(77)**	2122 **(84)**	3044C DIT	11.2 **(7.0)**	1632 **(3600)**
287C	MAS	08-13	4517 **(9958)**	61 **(82)**	2974 **(117.2)**	1981 **(78)**	2115 **(83.2)**	Cat C3.4 DIT	14.9 **(9.3)**	1724 **(3800)**
287C2	SSB	12-13	4517 **(9958)**	54 **(73)**	2974 **(117.2)**	1981 **(78)**	2115 **(83.2)**	Cat C3.4 DIT	14.9 **(9.3)**	1724 **(3800)**
297C	GCP	07-12	4870 **(10,736)**	67 **(90)**	2974 **(108)**	1981 **(78)**	2115 **(83)**	C3.4 DIT	9.0 **(5.6)** 14.9 **(9.2)**	1060 **(2337)**
297D	BE7	14-15	4590 **(10,120)**	71 **(95)**	3155 **(124.2)**	1935 **(76.2)**	2125 **(83.6)**	Cat C3.8 DIT	15.1 **(9.4)**	2063 **(4550)**
297D XHP	HP7	14-15	4905 **(10,815)**	79 **(106)**	3155 **(124.2)**	1935 **(76.2)**	2125 **(83.6)**	Cat C3.8 DIT	15.1 **(9.4)**	2268 **(5000)**

*With 457 mm **(18")** wide track.



COMPACT TRACK LOADERS

Model	Product Ident. No. Prefix	Years Built	Approx. Machine Weight kg (lb)	Net Power kW (hp)	Length to Coupler mm (in)	Width over Tracks mm (in)	Height to Top of Cab mm (in)	Engine Model	Top Travel Speed km/h (mph)	Rated Operating Capacity at 50% kg (lb)
259B3*	YYZ	10-13	4052	53	2722	1676	1986	Cat C3.4	13.6	1338
			(8934)	**(71)**	**(107)**	**(66)**	**(78)**	DIT	**(8.5)**	**(2950)**
279C	MBT	10-13	4487	61	2960	1981	2117	Cat C3.4	13.6	1451
			(9892)	**(82)**	**(116.5)**	**(78)**	**(83.3)**	DIT	**(8.5)**	**(3200)**
279C2	KWB	12-13	4475	54	2960	1981	2117	Cat C3.4	13.6	1383
			(9865)	**(73)**	**(116.5)**	**(78)**	**(83.3)**	DIT	**(8.5)**	**(3050)**
289C	JMP	10-13	4702	61	2960	1981	2117	Cat C3.4	13.6	1746
			(10,365)	**(82)**	**(116.5)**	**(78)**	**(83.3)**	DIT	**(8.5)**	**(3850)**
289C2	RTD	12-13	4687	54	2960	1981	2117	Cat C3.4	13.6	1656
			(10,332)	**(73)**	**(116.5)**	**(78)**	**(83.3)**	DIT	**(8.5)**	**(3650)**
299C	JSP	10-13	4867	67	3101.0	1981	2117	Cat C3.4	13.6	1882
			(10,730)	**(90)**	**(122.1)**	**(78)**	**(83.3)**	DIT	**(8.5)**	**(4150)**
299D	HCL	12-13	4943	71	3138	1931	2104	Cat C3.8	13.6	1928
			(10,898)	**(95)**	**(123.5)**	**(76)**	**(82.8)**	DIT	**(8.5)**	**(4250)**
299D XHP	NLC	12-13	5283	79	3138	1931	2104	Cat C3.8	13.6	1882
			(11,647)	**(106)**	**(123.5)**	**(76)**	**(82.8)**	DIT	**(8.5)**	**(4150)**
299D	GTC	13-15	4862	71	3136	1931	2127	Cat C3.8	13.5	1928
			(10,718)	**(95)**	**(123.5)**	**(76)**	**(83.7)**	DIT	**(8.4)**	**(4250)**
299D XHP	JST	13-15	5267	79	3136	1931	2127	Cat C3.8	13.5	2109
			(11,612)	**(106)**	**(123.5)**	**(76)**	**(83.7)**	DIT	**(8.4)**	**(4650)**

*Configured with 320 mm **(12.6")** tracks.



HYDRAULIC EXCAVATORS (Track)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
205 LC	(3HC)	84-89	Deutz-67	13 135	1.895	3.00	7.30	2.40	8.17	3290
	(4DC)		Perkins®-71	**(28,957)**	**(6'2.5")**	**(9'10")**	**(23'11")**	**(7'10")**	**(26'10")**	**(7300)**
205B	5ZF	90-92	80	12 900	1.895	2.976	7.67	2.495	8.9	3740
				(28,443)	**(6'2.5")**	**(9'9")**	**(25'2")**	**(8'2")**	**(29'2")**	**(8250)**
211 LC	(4EC)	84-89	Deutz-84	15 540	2.08	3.02	8.01	2.49	9.88	4240
	(5CC)		Perkins-94	**(34,260)**	**(6'9.9")**	**(9'11")**	**(26'3")**	**(8'2")**	**(32'5")**	**(9340)**
213 LC	3ZC	83-87	102	17 300	2.08	3.08	8.34	2.49	10.30	5127
				(38,140)	**(6'10")**	**(10'1")**	**(27'4")**	**(8'2")**	**(33'9.5")**	**(11,305)**
215	(96L)	76-80	85	17 450	1.92	3.10	8.94	2.47	9.25	5090
	(57Z) (14Z)	79-84	90	**(38,480)**	**(6'4")**	**(10'1")**	**(29'4")**	**(8'0")**	**(30'4")**	**(11,200)**
215 SA	(57Y) (14Z)	82-84	90	19 440	2.18	3.22	8.94	2.73	9.23	5130
				(42,860)	**(7'2")**	**(10'6")**	**(29'4")**	**(8'11")**	**(30'3")**	**(11,300)**
215B LC	(9YB)	84-87	105	18 510	1.92	3.10	8.94	2.44	9.25	5760
				(40,806)	**(6'4")**	**(10'2")**	**(29'4")**	**(8'0")**	**(30'4")**	**(12,700)**
215C LC	(4HG)	87-89	115	19 570	1.92	3.1	8.94	2.42	9.29	7070
				(43,150)	**(6'4")**	**(10'2")**	**(29'4")**	**(7'11")**	**(30'6")**	**(15,200)**
215D LC	(9TF)	89-92	125	19 900	1.92	3.2	9.0	2.44	9.23	6830
				(43,900)	**(6'4")**	**(10'6")**	**(24'6")**	**(8'0")**	**(30'3")**	**(14,700)**
219	(5CF)	87-89	130	21 120	2.18	3.12	8.94	2.73	10.39	7080
				(46,550)	**(7'2")**	**(10'3")**	**(29'4")**	**(8'11")**	**(34'1")**	**(15,300)**
219D	(5XG)	89-92	140	21 600	2.18	3.12	9.41	2.73	9.75	7670
				(47,500)	**(7'2")**	**(10'3")**	**(30'10")**	**(8'11")**	**(32'0")**	**(16,500)**
219 LC	(5CF)	87-89	130	22 020	2.18	3.12	8.94	2.73	10.39	7080
				(48,550)	**(7'2")**	**(10'3")**	**(29'4")**	**(8'11")**	**(34'1")**	**(15,300)**
219D LC	(5XG)	89-92	140	22 400	2.18	3.12	9.41	2.73	9.75	7670
				(49,300)	**(7'2")**	**(10'3")**	**(30'10")**	**(8'11")**	**(32'0")**	**(16,500)**
225 LC	(51U)	72-86	135	23 900	2.64	3.17	9.83	2.99	9.58	7300
				(52,700)	**(8'8")**	**(10'5")**	**(32'3")**	**(9'10")**	**(31'5")**	**(15,600)**
225 SA	(51U)	77-86	135	27 125	2.64	3.17	9.83	3.35	9.55	7340
				(59,800)	**(8'8")**	**(10'5")**	**(32'3")**	**(11'0")**	**(31'4")**	**(15,700)**
225B	(2ZD)	86-89	145	24 960	2.44	3.17	9.83	2.99	10.16	11 040
	(3YD)	87-89		**(55,030)**	**(8'0")**	**(10'5")**	**(32'3")**	**(9'10")**	**(33'4")**	**(26,100)**
225D	(6RG)	89-91	150	25 400	2.44	3.23	9.94	2.99	10.13	—
				(55,900)	**(8'0")**	**(10'7")**	**(32'7")**	**(9'10")**	**(33'3")**	**—**
225B LC	(2ZD)	86-89	145	26 140	2.44	3.17	9.83	2.99	10.16	11 040
	(3YD)	87-89		**(58,230)**	**(8'0")**	**(10'5")**	**(32'3")**	**(9'10")**	**(33'4")**	**(26,100)**
225D LC	(2SJ)	89-91	165	26 700	2.44	3.23	9.94	2.99	10.13	12 450
				(58,900)	**(8'0")**	**(10'7")**	**(32'7")**	**(9'10")**	**(33'3")**	**(26,900)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
229	(1GF)	86-89	145	29 140	2.64	3.38	9.83	3.45	10.11	—
	(1AF)	86-89		**(64,830)**	**(8'8")**	**(11'1")**	**(32'3")**	**(11'4")**	**(33'2")**	—
229 LC	(1GF)	86-89	180	33 540	2.64	3.38	11.02	3.45	11.35	7940
Custom 180				**(73,940)**	**(8'8")**	**(11'1")**	**(36'2")**	**(11'4")**	**(37'3")**	**(17,100)**
229D	(2LJ)	89-91	157	31 700	2.64	3.52	10.9	3.25	10.76	8300
				(69,900)	**(8'8")**	**(11'7")**	**(35'9")**	**(10'8")**	**(35'4")**	**(18,300)**
231D		90-92	200	34 300	2.64	3.45	10.83	3.45	11.20	15 300
				(75,600)	**(8'8")**	**(11'4")**	**(35'6")**	**(11'4")**	**(36'9")**	**(33,000)**
231D LC		90-92	200	35 500	2.64	3.45	10.83	3.45	11.20	15 300
				(78,100)	**(8'8")**	**(11'4")**	**(35'6")**	**(11'4")**	**(36'9")**	**(33,000)**
235	(32K)	73-86	195	39 320	2.69	3.40	11.27	3.45	11.23	7050
	(64R)			**(86,700)**	**(8'10")**	**(11'2")**	**(37'0")**	**(11'4")**	**(36'10")**	**(17,300)**
235B	(7WC)	86-88	215	40 960	2.69	3.40	11.27	3.45	11.23	9934
	(9PC)			**(89,700)**	**(8'10")**	**(11'2")**	**(37'0")**	**(11'4")**	**(36'10")**	**(21,900)**
235C	(4DG) (5AF)	88-92	250	42 140	2.69	3.50	11.50	3.45	12.00	14 720
	(2PG) (3WG)			**(92,800)**	**(8'10")**	**(11'4")**	**(37'7")**	**(11'4")**	**(39'5")**	**(35,000)**
235D	(8KJ)	92-93	250	46 270	2.69	3.50	11.50	3.45	12.00	14 840
	(8TJ)			**(103,780)**	**(8'10")**	**(11'5")**	**(37'7")**	**(11'4")**	**(39'5")**	**(35,200)**
235D LC	(8KJ)	92-93	250	49 270	3.30	3.60	11.60	3.79	11.97	15 070
	(8TJ)			**(108,620)**	**(10'10")**	**(11'9")**	**(38'1")**	**(12'5")**	**(39'3")**	**(35,700)**
245	(82X)	74-88	325	65 745	3.24	4.62	13.18	3.71	14.02	14 930
	(84X)			**(144,941)**	**(10'7")**	**(15'2")**	**(43'3")**	**(12'2")**	**(46'0")**	**(32,920)**
245B	6MF	88-92	360	65 200	3.24	4.78	13.13	3.61	14.02	—
	1SJ			**(143,500)**	**(10'7")**	**(15'8")**	**(43'1")**	**(11'10")**	**(46'0")**	—
245D	(4LK)	92-93	385	68 420	3.24	5.46	12.82	3.61	13.84	14 640†
	(7ZJ)			**(150,520)**	**(10'7")**	**(17'11")**	**(42'0")**	**(11'10")**	**(45'9")**	**(31,600)**
E70	3BG	87-89	52	6500	1.65	2.59	6.02	2.25	6.67	1300
	3CG	87-89		**(14,300)**	**(5'5")**	**(8'6")**	**(19'9")**	**(7'5")**	**(21'10")**	**(2750)**
E70B	7YF(JPN)	89-94	54	6760	1.75	2.56	6.09	2.32	6.72	1315
	5TG(OSJ)	89-94		**(14,900)**	**(5'9")**	**(8'5")**	**(20'0")**	**(7'7")**	**(22'1")**	**(2900)**
	6AK(OSJ)	92-94								
E110	3FG	87-89	74	10 700	1.9	2.73	7.345	2.5	7.93	2700
	3GG	87-89		**(23,600)**	**(6'3")**	**(8'11")**	**(24'0")**	**(8'2")**	**(26'0")**	**(5750)**
E110B	9HF(OSJ)	90-92	79	11 600	1.99	2.70	7.25	2.495	8.10	3350
	8MF(JPN)	90-92		**(25,600)**	**(6'6")**	**(8'10")**	**(23'9")**	**(8'2")**	**(26'7")**	**(7200)**
	5GK(OSJ)	90-92								

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.
†Lift capacity at 7.5 m **(25'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
E120	1LF(OSJ)	87-89	84	12 200	1.99	2.775	7.66	2.490	8.58	3850
	1MF(JPN)	87-89		**(26,800)**	**(6'6")**	**(9'1")**	**(25'1")**	**(8'2")**	**(28'2")**	**(8300)**
E120B	7NF(OSJ)	90-92	84	12 680	1.99	2.70	7.62	2.495	8.74	4310
	6JF(JPN)	90-92		**(28,200)**	**(6'6")**	**(8'10")**	**(25'10")**	**(8'2")**	**(28'8")**	**(9250)**
	4XK(OSJ)	90-92								
E140	1PF(JPN)	87-94	89	13 970	1.99	2.89	8.29	2.55	5.49	4380
	1NF(OSJ)			**(30,800)**	**(6'6")**	**(9'6")**	**(27'6")**	**(8'4")**	**(18'0")**	**(9650)**
E200B	6KF(OSJ)	87-91	118	18 800	2.20	2.97	9.48	2.83	10.63	8100
	4SG(JPN)	87-91		**(41,400)**	**(7'3")**	**(9'9")**	**(3'11")**	**(9'4")**	**(34'10")**	**(17,350)**
EL200B	7DF(OSJ)	87-91	118	20 100	2.38	2.97	9.48	3.18	10.63	8150
	5EG(JPN)	87-91		**(44,300)**	**(7'10")**	**(9'9")**	**(31'1")**	**(10'5")**	**(34'10")**	**(17,600)**
E240	1FG(OSJ)	87-89	148	23 000	2.39	3.02	9.73	3.19	10.6	9800
	2HF(JPN)	87-89		**(50,700)**	**(7'10")**	**(9'11")**	**(31'11")**	**(10'6")**	**(34'9")**	**(21,600)**
E240B	8SF(OSJ)	89-92	148	23 000	2.39	3.02	9.73	3.19	10.6	9800
	9PF(JPN)			**(50,700)**	**(7'10")**	**(9'11")**	**(31'11")**	**(10'6")**	**(34'9")**	**(21,600)**
E240C	2RL(OSJ)	92-93	148	23 000	2.39	3.02	9.73	3.19	10.6	9800
	8MK(JPN)			**(50,700)**	**(7'10")**	**(9'11")**	**(31'11")**	**(10'6")**	**(34'9")**	**(21,600)**
EL240	4JF(OSJ)	87-89	148	23 600	2.58	3.02	9.73	3.38	10.6	11 300
	4MF(JPN)	87-89		**(52,000)**	**(8'6")**	**(9'11")**	**(31'11")**	**(11'1")**	**(34'9")**	**(24,300)**
EL240B	5WG(OSJ)	89-92	148	23 600	2.58	3.02	9.73	3.38	10.6	10 320
	6MG(JPN)			**(52,000)**	**(8'6")**	**(9'11")**	**(31'11")**	**(11'1")**	**(34'9")**	**(22,750)**
EL240C	9PK(OSJ)	92-93	148	23 600	2.58	3.02	9.73	3.38	10.6	10 320
	9NK(JPN)			**(52,000)**	**(8'6")**	**(9'11")**	**(31'11")**	**(11'1")**	**(34'9")**	**(22,750)**
E300	2CF(OSJ)	87-89	187	30 500	2.6	3.22	10.94	3.4	11.84	12 550
	1KG(JPN)	87-89		**(67,300)**	**(8'6")**	**(10'7")**	**(35'11")**	**(11'2")**	**(38'9")**	**(27,650)**
E300B	1WJ(OSJ)	90-91	206	30 200	2.6	3.22	10.94	3.4	11.84	12 450
	2HJ(JPN)	90-91		**(66,580)**	**(8'6")**	**(10'7")**	**(35'11")**	**(11'2")**	**(38'9")**	**(26,850)**
EL300	4NF(OSJ)	87-89	187	31 600	2.6	3.22	10.94	3.4	11.84	12 550
	4SF(JPN)	87-89		**(69,700)**	**(8'6")**	**(10'7")**	**(35'11")**	**(11'2")**	**(38'9")**	**(27,650)**
EL300B	3FJ(OSJ)	90-91	206	31 200	2.6	3.22	10.94	3.4	11.84	12 450
	1GK(JPN)	90-91		**(68,780)**	**(8'6")**	**(10'7")**	**(35'11")**	**(11'2")**	**(38'9")**	**(26,850)**
E450	3HG(OSJ)	87-93	276	46 000	2.89	3.49	11.96	3.15	13.08	10 900
	3JG(JPN)	87-93		**(101,430)**	**(9'6")**	**(11'5")**	**(39'3")**	**(10'4")**	**(42'11")**	**(23,500)**
E650	3KG(OSJ)	87-92	375	62 600	3.25	4.84	14.0	3.49	13.33	15 850
	3LG(JPN)	87-92		**(138,000)**	**(10'8")**	**(15'11")**	**(45'11")**	**(11'5")**	**(43'9")**	**(34,000)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
301.5	3YW	98-05	17.4	1650 **(3640)**	0.75 **(2'6")**	2.19 **(7'2")**	3.69 **(12'1")**	0.98 **(3'3")**	3.8 **(12'6")**	380† **(830)**
301.6	BDH	00-05	17.4	1690 **(3726)**	0.75 **(2'6")**	2.19 **(7'2")**	3.69 **(12'1")**	0.98 **(3'3")**	3.8 **(12'6")**	370† **(810)**
301.8	BFA	00-05	17.4	1725 **(3803)**	0.75 **(2'6")**	2.19 **(9'8")**	3.69 **(12'1")**	0.98 **(3'3")**	3.8 **(12'6")**	370† **(810)**
302.5	4AZ	99-05	22.9	2730 **(6020)**	1.15 **(3'9")**	2.3 **(7'7")**	4.52 **(14'10")**	1.45 **(4'9")**	4.83 **(15'10")**	870† **(1910)**
303 CR	DMA	01-05	26.1	3210 **(7077)**	1.25 **(4'1")**	2.48 **(8'2")**	4.68 **(15'4")**	1.55 **(5'1")**	5.39 **(17'8")**	1200† **(2646)**
303C CR	BXT	06-10	29.5	7573 **(3435)**	1.25 **(4'1")**	2.5 **(8'2")**	4.73 **(15'6")**	15.5 **(5'1")**	5.1 **(16'9")**	1200 **(2646)**
303.5	AFW	99-02	25	7430	1.25	2.44	5.07	1.55	5.54	1030†
	DCH	01-02		**(7546)**	**(4'1")**	**(8'0")**	**(16'6")**	**(5'1")**	**(18'2")**	**(2270)**
303.5C CR	DMY	06-10	38.9	3790 **(8356)**	1.48 **(4'10")**	2.5 **(8'2")**	4.82 **(15'10")**	17.8 **(5'10")**	5.35 **(17'7")**	1630 **(3594)**
303.5D CR	RHP	10-12	30	3770 **(8300)**	1.48 **(4'10")**	2.5 **(8'2")**	4.73 **(15'6")**	1.78 **(5'10")**	5.32 **(17'5")**	1340† **(2950)**
303.5E CR	RKY	11-	31.6	3800 **(8380)**	1.48 **(4'10")**	2.5 **(8'2")**	4.73 **(15'6")**	1.78 **(5'10")**	5.32 **(17'5")**	1340† **(2950)**
304 CR	NAD	02-05	35.5	4300 **(9480)**	1.58 **(5'2")**	2.6 **(8'6")**	5.18 **(17'0")**	1.98 **(6'6")**	5.95 **(19'6")**	2250† **(5000)**
304C CR	FPK	06-10	41.6	4800 **(10,582)**	1.58 **(5'2")**	2.55 **(8'4")**	5.17 **(17'0")**	19.8 **(6'6")**	5.46 **(17'11")**	2250 **(5000)**
304D CR	TYK	10-12	39	4080 **(8995)**	1.60 **(5'3")**	2.5 **(8'2")**	4.82 **(15'10")**	1.95 **(6'5")**	5.47 **(18'0")**	1570† **(3460)**
304E CR	TTN	11-15	40	4000 **(8820)**	1.6 **(5'3")**	2.5 **(8'2")**	4.82 **(15'10")**	1.95 **(6'5")**	5.47 **(18'0")**	1570† **(3460)**
304.5	ANK	99-02	38	4475	1.5	2.5	5.7	1.9	6.05	1600†
	WAK	01-02		**(9866)**	**(4'11")**	**(8'4")**	**(18'8")**	**(6'6")**	**(19'10")**	**(3630)**
305 CR	DSA	01-03	42	4800 **(10,582)**	1.58 **(5'2")**	2.6 **(8'6")**	5.37 **(17'7")**	1.98 **(6'6")**	6.14 **(20'2")**	2550† **(5622)**
	DGT	03-05	42	4800 **(10,582)**	1.58 **(5'2")**	2.6 **(8'6")**	5.37 **(17'7")**	1.98 **(6'6")**	6.14 **(20'2")**	2550† **(5622)**
305C CR	HWJ	06-10	46.9	5200 **(11,464)**	1.58 **(5'2")**	2.55 **(8'4")**	5.33 **(17'6")**	19.8 **(6'6")**	5.65 **(18'6")**	2550 **(5622)**
305D CR	XER	10-11	42	5260 **(11,600)**	1.58 **(5'2")**	2.55 **(8'4")**	5.18 **(17'0")**	1.98 **(6'6")**	5.81 **(19'1")**	2250† **(4960)**
305E CR	XFA	11-14	40	5210 **(11,490)**	1.58 **(5'2")**	2.55 **(8'4")**	5.18 **(17'0")**	1.98 **(6'6")**	5.81 **(19'1")**	2250† **(4960)**
305.5D CR	FLZ	10-12	47	5560 **(12,260)**	1.58 **(5'2")**	2.55 **(8'4")**	5.33 **(17'6")**	1.98 **(6'6")**	6.02 **(19'9")**	2480† **(5470)**
305.5E CR	FKY	11-14	44.2	5480 **(12,080)**	1.58 **(5'2")**	2.55 **(8'4")**	5.33 **(17'6")**	1.98 **(6'6")**	6.02 **(19'9")**	2490† **(5490)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.
†Lift capacity at 3 m **(10'0")** over front, blade down, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
307	2WM	94-98	54	7600 **(16,760)**	1.75 **(5'9")**	2.61 **(8'7")**	6.3 **(20'8")**	2.4 **(7'11")**	6.38 **(20'11")**	2450 **(5400)**
	2PM(OSJ)	94-98	54	6740 **(14,860)**	1.75 **(5'9")**	2.63 **(8'8")**	6.08 **(19'11")**	2.28 **(7'6")**	6.72 **(22'1")**	1350 **(3000)**
	9ZL(JPN)	94-97	54	6650 **(14,660)**	1.75 **(5'9")**	2.63 **(8'8")**	6.08 **(19'11")**	2.28 **(7'6")**	6.72 **(22'1")**	1350 **(3000)**
307B	5CW(OSJ)	98-00	54	6960 **(15,340)**	1.75 **(5'9")**	2.63 **(8'8")**	6.08 **(19'11")**	2.28 **(7'6")**	6.72 **(22'1")**	1350 **(3000)**
	4RW(JPN)	97-00	54	6500 **(14,330)**	1.75 **(5'9")**	2.64 **(8'8")**	6.08 **(19'11")**	2.28 **(7'6")**	6.72 **(22'1")**	1350 **(3000)**
307B SB	AFB	99-00	40/54	7500 **(16,530)**	1.75 **(5'9")**	2.9 **(9'6")**	6.75 **(22'2")**	2.28 **(7'6")**	7.01 **(23'0")**	1410 **(3100)**
	6KZ(OSJ) 7DZ(JPN)	98-01	40/54	8040 **(17,730)**	1.75 **(5'9")**	2.64 **(8'8")**	6.73 **(22'1")**	2.28 **(7'6")**	7.42 **(24'4")**	1500 **(3300)**
307C	(BCM)	00-09	54	7210 **(15,900)**	1.75 **(5'9")**	2.78 **(9'1")**	6.07 **(19'11")**	2.29 **(7'6")**	6.85 **(22'6")**	947 **(2100)**
	BAJ	00-08	54	6450 **(14,220)**	1.75 **(5'9")**	2.63 **(8'8")**	6.07 **(19'11")**	2.29 **(7'6")**	6.34 **(20'10")**	1052 **(2300)**
307C SB	(BNE)	00-07	54	8390 **(18,500)**	1.75 **(5'9")**	2.63 **(8'8")**	6.79 **(22'3")**	2.29 **(7'6")**	7.55 **(24'9")**	822 **(1800)**
307D	DSG	07-12	55.6	7075 **(15,600)**	1.84 **(6'0")**	2.63 **(8'8")**	6.07 **(19'11")**	2.29 **(7'6")**	6.67 **(21'11")**	3650† **(8050)**
307E	H1Y	12-	55.6	7160 **(15,785)**	1.75 **(5'9")**	2.63 **(8'8")**	6.07 **(19'11")**	2.29 **(7'6")**	6.16 **(20'3")**	4200† **(9260)**
308B CR	3YS(JPN)	99-02	54	7650 **(16,870)**	1.85 **(6'1")**	2.61 **(8'7")**	5.77 **(18'11")**	2.3 **(7'7")**	6.9 **(22'8")**	1600 **(3500)**
308C CR	(KCX)	02-07	54	8040 **(17,730)**	1.87 **(6'2")**	2.61 **(8'7")**	5.83 **(19'2")**	2.47 **(8'1")**	6.9 **(22'8")**	947 **(2100)**
	CPE	01-08	54	7390 **(16,290)**	1.87 **(6'2")**	2.61 **(8'7")**	5.83 **(19'2")**	2.32 **(7'7")**	6.39 **(21'0")**	1135 **(2500)**
308D CR	GBT	07-12	55.6	7850 **(17,310)**	1.87 **(6'2")**	2.63 **(8'7")**	5.81 **(19'1")**	2.32 **(7'7")**	6.71 **(22'0")**	3650† **(8050)**
308D SB	FYC	07-12	55.6	8400 **(18,520)**	1.87 **(6'2")**	2.59 **(8'6")**	6.45 **(21'2")**	2.32 **(7'7")**	7.43 **(24'5")**	3200† **(7055)**
308E SB	GBJ	11-13	65	8330 **(18,365)**	1.87 **(6'2")**	2.55 **(8'4")**	6.38 **(20'11")**	2.32 **(7'7")**	7.35 **(24'1")**	3610† **(7960)**
311	9LJ(OSJ)	93-96	79	11 100 **(24,470)**	1.99 **(6'6")**	2.76 **(9'1")**	7.25 **(23'9")**	2.49 **(8'2")**	8.1 **(26'7")**	3100 **(6800)**
	5PK(JPN)	93-96	79	11 050 **(24,360)**	1.99 **(6'6")**	2.76 **(9'1")**	7.25 **(23'9")**	2.49 **(8'2")**	8.10 **(26'7")**	3100 **(6800)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.
†Lift capacity at 3 m **(10'0")** over front, blade down, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
311B	2LS(blade)	96-01	79	11 890	1.99	2.76	7.25	2.495	8.1	3080
	(OSJ)			**(26,210)**	**(6'6")**	**(9'1")**	**(23'9")**	**(8'2")**	**(26'7")**	**(6800)**
	2MS(blade)	96-01	79	11 900	1.99	2.76	7.25	2.5	8.1	3100
	(JPN)			**(26,230)**	**(6'6")**	**(9'1")**	**(23'9")**	**(8'2")**	**(26'7")**	**(6800)**
	8GR(OSJ)	96-01	79	11 130	1.99	2.76	7.25	2.495	8.1	3120
				(24,540)	**(6'6")**	**(9'1")**	**(23'9")**	**(8'2")**	**(26'7")**	**(6900)**
	8HR(JPN)	96-01	79	11 200	1.99	2.76	7.25	2.49	8.1	3100
				(24,690)	**(6'6")**	**(9'1")**	**(23'9")**	**(8'2")**	**(26'7")**	**(6800)**
311C U	(CKE)	01-07	79	11 980	1.99	2.77	6.92	2.49	8.225	1295
				(26,410)	**(6'6")**	**(9'1")**	**(22'8")**	**(8'2")**	**(27'0")**	**(2900)**
	CLK	01-07	79	11 500	1.99	2.765	6.88	2.49	7.7	1453
				(25,350)	**(6'6")**	**(9'1")**	**(22'7")**	**(8'2")**	**(25'3")**	**(3200)**
311D RR	AKW(JPN)	08-14	80	11 930	1.99	2.86	6.84	2.49	8.1	3350
				(26,310)	**(6'6")**	**(9'5")**	**(22'5")**	**(8'2")**	**(26'7")**	**(7150)**
311D LRR	CLA(OSJ)	08-13	80	12 480	1.99	2.86	6.91	2.49	8.1	3900
	DDW	08-09		**(27,520)**	**(6'6")**	**(9'5")**	**(22'8")**	**(8'2")**	**(26'7")**	**(8350)**
	(PNJ)	10-13								
	LKA	09-12								
	KRM(OSJ)	10-14								
312	6BL	93-97	84	12 600	1.99	2.76	7.6	2.49	8.63	4200
	6GK(OSJ)	93-96		**(27,780)**	**(6'6")**	**(9'1")**	**(24'11")**	**(8'2")**	**(28'4")**	**(9300)**
	7DK(JPN)	93-96	84	12 000	1.99	2.76	7.6	2.49	8.63	4050
				(26,460)	**(6'6")**	**(9'1")**	**(24'11")**	**(8'2")**	**(28'4")**	**(8900)**
312B	6SW	98-01	84	13 000	1.99	2.91	7.59	2.49	8.3	4590
				(28,660)	**(6'6")**	**(9'7")**	**(24'11")**	**(8'2")**	**(27'3")**	**(10,110)**
	9GR(OSJ)	98-01	84	12 440	1.99	2.76	7.595	2.495	8.625	4170
				(27,430)	**(6'6")**	**(9'1")**	**(24'11")**	**(8'2")**	**(28'4")**	**(9200)**
	9HR(JPN)	98-00	84	12 150	1.99	2.76	7.595	2.49	8.625	4050
				(26,790)	**(6'6")**	**(9'1")**	**(24'11")**	**(8'2")**	**(28'4")**	**(8900)**
	9NW(blade)	98-01	66/88	13 785	1.99	2.91	7.59	2.49	8.3	4940
				(30,390)	**(6'6")**	**(9'7")**	**(24'11")**	**(8'2")**	**(27'3")**	**(10,900)**
	2NS(blade)	98-01	66/88	13 200	1.99	2.76	7.595	2.495	8.625	4230
	(OSJ)			**(29,100)**	**(6'6")**	**(9'1")**	**(24'11")**	**(8'2")**	**(28'4")**	**(9300)**
	3ES(blade)	98-00	84	12 900	1.99	2.76	7.595	2.49	8.625	4200
	(JPN)			**(28,440)**	**(6'6")**	**(9'1")**	**(24'11")**	**(8'2")**	**(28'4")**	**(9300)**
312B L	9FS	97-01	84	13 270	1.99	2.91	7.59	2.59	8.3	5000
				(29,260)	**(6'6")**	**(9'7")**	**(24'11")**	**(8'6")**	**(27'3")**	**(11,000)**
	8JR(OSJ)	98-01	66/88	12 940	1.99	2.76	7.595	2.59	8.625	4930
				(28,530)	**(6'6")**	**(9'1")**	**(24'11")**	**(8'6")**	**(28'4")**	**(10,900)**
	2KW(blade)	97-01	84	14 055	1.99	2.91	7.59	2.59	8.3	5050
				(30,990)	**(6'6")**	**(9'7")**	**(24'11")**	**(8'6")**	**(27'3")**	**(11,100)**
	3FS(blade)	98-01	66/88	13 720	1.99	2.76	7.595	2.59	8.625	4920
	(OSJ)			**(30,250)**	**(6'6")**	**(9'1")**	**(24'11")**	**(8'6")**	**(28'4")**	**(10,800)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
312C	BNN(FDS)	01-07	90	12 860	1.99	2.76	7.57	2.59	8.74	1402
				(28,350)	**(6'6")**	**(9'1")**	**(24'10")**	**(8'6")**	**(28'8")**	**(3100)**
	CAE	00-	90	12 200	1.99	2.75	7.57	2.49	8.3	1448
				(26,900)	**(6'6")**	**(9'0")**	**(24'10")**	**(8'2")**	**(27'3")**	**(3200)**
	BNN	01-	71/96	13 000	1.99	2.91	7.59	2.49	8.3	4350
				(28,665)	**(6'6")**	**(9'6")**	**(24'11")**	**(8'2")**	**(27'3")**	**(10,120)**
312C L	CBT(CBA)	01-07	90	13 140	1.99	2.76	7.57	2.59	8.74	1439
				(28,970)	**(6'6")**	**(9'1")**	**(24'10")**	**(8'6")**	**(28'8")**	**(3200)**
	CBT	01-	71/96	13 270	1.99	2.91	7.59	2.59	8.3	5040
				(29,260)	**(6'6")**	**(9'6")**	**(24'11")**	**(8'6")**	**(27'3")**	**(11,025)**
312D	HCW(OSJ)	08-12	90	13 120	1.99	2.83	7.61	2.49	8.62	4300
	HJX	08-11		**(28,930)**	**(6'6")**	**(9'3")**	**(25'0")**	**(8'2")**	**(28'3")**	**(9250)**
	PHH	09-11								
	DLP(CHN)	08-12								
	LRK(CHN)	10-12								
	RHL(OSJ)	10-14								
312D L	JBC(OSJ)	08-12	90	13 650	1.99	2.83	7.61	2.49	8.62	5000
	(XGK)	10-11		**(30,100)**	**(6'6")**	**(9'3")**	**(25'0")**	**(8'2")**	**(28'3")**	**(10,750)**
	KCD	08-11								
	TGY	08-08								
	SKA	11-11								
	RKF	09-11								
	KES(OSJ)	10-14								
313B CR	BAS(OSJ)	00-02	89	13 225	1.99	2.82	7.17	2.49	8.55	3900
				(29,160)	**(6'6")**	**(9'3")**	**(23'6")**	**(8'2")**	**(28'1")**	**(8600)**
	AEX(JPN)	99-02	89	12 750	1.99	2.82	7.17	2.49	8.24	3900
				(28,110)	**(6'6")**	**(9'3")**	**(23'6")**	**(8'2")**	**(27'0")**	**(8600)**
313C CR	HGF(JPN)	01-08		12 600	1.99	2.82	7.28	2.49	8.63	3600
				(27,780)	**(6'6")**	**(9'3")**	**(23'11")**	**(8'2")**	**(28'4")**	**(7700)**
313C SR	WSA(JPN)	02-08		13 900	1.99	2.82	7.48	2.49	7.23	3400
				(30,650)	**(6'6")**	**(9'3")**	**(24'7")**	**(8'2")**	**(23'9")**	**(7250)**
313D	KXD(CHN)	12-12	90	13 430	1.99	2.83	7.61	2.49	8.22	4150
	WPK(CHN)	12-13		**(29,610)**	**(6'6")**	**(9'3")**	**(25'0")**	**(8'2")**	**(27'0")**	**(8900)**
313D SR	LBR(JPN)	08-12	77	14 400	1.99	2.8	7.49	2.49	7.23	3450
				(31,750)	**(6'6")**	**(9'3")**	**(24'7")**	**(8'2")**	**(23'9")**	**(7400)**
314C CR	(KJA)	02-02	90	14 610	1.99	2.81	7.28	2.59	8.765	1351
				(32,210)	**(6'6")**	**(9'3")**	**(23'11")**	**(8'6")**	**(28'9")**	**(3000)**
	KHB	01-	90	13 500	1.99	2.81	7.28	2.49	8.32	1527
				(29,760)	**(6'6")**	**(9'3")**	**(23'11")**	**(8'2")**	**(27'4")**	**(3400)**
314C LCR	(PCA)	02-02	90	14 810	1.99	2.73	7.41	2.59	8.765	1372
				(32,650)	**(6'6")**	**(9'0")**	**(24'4")**	**(8'6")**	**(28'9")**	**(3000)**
314D CR	PDP(OSJ)	08-13	87	14 000	1.99	2.91	7.27	2.49	8.63	4250
	MFK(JPN)	08-12		**(30,870)**	**(6'6")**	**(9'7")**	**(23'10")**	**(8'2")**	**(28'4")**	**(9100)**
	WLN(OSJ)	10-14								
314D LCR	BYJ(OSJ)	08-13	87	14 100	1.99	2.91	7.27	2.49	8.63	4950
	SBP	08-09		**(31,090)**	**(6'6")**	**(9'7")**	**(23'10")**	**(8'2")**	**(28'4")**	**(10,600)**
	(SSZ)	10-12								
	TXN	10-12								
	XHR(OSJ)	10-14								

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
315	3ZM	95-98	99	15 920	1.99	2.88	8.5	2.49	8.21	5300
				(35,100)	**(6'6")**	**(9'5")**	**(27'11")**	**(8'2")**	**(26'11")**	**(11,700)**
	4YM(OSJ)	94-97	99	16 330	1.99	2.88	8.5	2.49	9.14	5290
				(36,000)	**(6'6")**	**(9'5")**	**(27'11")**	**(8'2")**	**(30'0")**	**(11,700)**
	6XM(JPN)	94-97	99	15 330	1.99	2.88	8.5	2.49	9.14	—
				(33,800)	**(6'6")**	**(9'5")**	**(27'11")**	**(8'2")**	**(30'0")**	
315 L	6YM(OSJ)	94-97	99	15 920	1.99	2.88	8.5	2.59	8.74	6320
				(35,100)	**(6'6")**	**(9'5")**	**(27'11")**	**(8'6")**	**(28'8")**	**(13,900)**
315B	1SW(OSJ)	97-01	99	16 300	1.99	2.88	8.5	2.49	9.14	5500
				(35,940)	**(6'6")**	**(9'5")**	**(27'11")**	**(8'2")**	**(30'0")**	**(12,100)**
	2DW(JPN)	97-01	99	15 850	1.99	2.88	8.5	2.49	9.14	—
				(34,940)	**(6'6")**	**(9'5")**	**(27'11")**	**(8'2")**	**(30'0")**	
315B L	5SW	98-	99	16 700	1.995	3.0	8.41	2.49	9.02	6720
				(36,820)	**(6'7")**	**(9'10")**	**(27'7")**	**(8'2")**	**(29'7")**	**(14,800)**
	3AW(OSJ)	97-01	80/107	16 700	1.99	2.88	8.47	2.59	9.14	6600
	7RZ(forest) (OSJ)			**(36,820)**	**(6'6")**	**(9'5")**	**(27'10")**	**(8'6")**	**(30'0")**	**(14,600)**
315C	(CFB)	01-02	110	16 400	1.99	2.99	8.52	2.59	9.29	1675
				(36,160)	**(6'6")**	**(9'10")**	**(27'11")**	**(8'6")**	**(30'6")**	**(3700)**
	CFL	01-	110	16 000	1.99	2.95	8.52	2.49	8.9	1840
				(35,270)	**(6'6")**	**(9'8")**	**(27'11")**	**(8'2")**	**(29'2")**	**(4100)**
	AKE	03-07	110	16 399	1.99	2.88	8.5	2.49	9.14	5650
				(36,160)	**(6'6")**	**(9'5")**	**(27'11")**	**(8'2")**	**(30'0")**	**(12,100)**
315C L	(CFT)	01-02	110	16 750	1.99	2.99	8.52	2.59	9.29	1719
				(36,930)	**(6'6")**	**(9'10")**	**(27'11")**	**(8'6")**	**(30'6")**	**(3800)**
	CJC	03-07	110	16 748	1.99	2.88	8.5	2.59	9.14	6750
				(36,930)	**(6'6")**	**(9'5")**	**(27'11")**	**(8'6")**	**(30'0")**	**(14,450)**
	ANF	03	83/111	16 770	1.99	2.76	8.39	2.49	9.09	7110
				(36,970)	**(6'6")**	**(9'0")**	**(27'6")**	**(8'2")**	**(29'9")**	**(15,675)**
315D L	CJN(OSJ)	07-12	113	17 280	1.99	3.03	8.54	2.59	9.24	7100
	BYK(JPN)	07-11		**(38,100)**	**(6'6")**	**(9'9")**	**(28'0")**	**(8'6")**	**(30'3")**	**(15,100)**
	NCM	07-11								
	KBD	07-09								
	(JGS)	10-11								
	TLE	09-11								
	BZN(OSJ)	09-13								
	JHA(CHN)	10-12								
	YTB	09-12								
317	4MM	95-98	99	17 260	2.15	2.88	8.5	2.75	8.62	4210
				(38,050)	**(7'1")**	**(9'5")**	**(27'11")**	**(9'0")**	**(28'3")**	**(9300)**
317B L	9WW	98-	81/109	17 300	2.2	3.04	8.41	2.8	9.1	7100
				(38,146)	**(7'3")**	**(9'10")**	**(27'6")**	**(9'2")**	**(29'8")**	**(15,655)**
317 N	9SR	96-98	99	17 220	1.99	2.88	8.5	2.75	8.62	6450
				(37,960)	**(6'6")**	**(9'5")**	**(27'11")**	**(9'0")**	**(28'3")**	**(14,200)**
317B LN	6DZ	98-	81/110	17 300	1.995	3.04	8.41	2.49	9.1	7100
				(38,146)	**(6'5")**	**(9'10")**	**(27'6")**	**(8'2")**	**(29'8")**	**(15,655)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
318B L	9WW	98-	86/115	17 700	2.2	3.02	8.67	2.8	8.94	8440
				(39,020)	**(7'3")**	**(9'11")**	**(28'5")**	**(9'2")**	**(29'4")**	**(18,600)**
	3LR(OSJ)	99-02	86/115	18 390	2.2	3.05	8.72	2.8	9.77	7650
				(40,540)	**(7'3")**	**(10'0")**	**(28'7")**	**(9'2")**	**(32'0")**	**(16,900)**
	ADC	99-	86/115	18 500	2.2	3.04	8.69	2.8	9.6	7600
				(40,792)	**(7'3")**	**(9'10")**	**(28'6")**	**(9'2")**	**(31'6")**	**(16,760)**
	(3LR)	01-02	86/115	18 360	2.2	2.83	8.69	2.8	9.78	2200
				(40,480)	**(7'3")**	**(9'3")**	**(28'6")**	**(9'2")**	**(32'1")**	**(4900)**
318B LN	6DZ	98-	86/115	17 160	1.995	3.02	8.67	2.495	8.94	7590
				(37,830)	**(6'7")**	**(9'11")**	**(28'5")**	**(8'2")**	**(29'4")**	**(16,700)**
	7KZ(OSJ)	99-02	86/115	18 260	2.2	3.05	8.72	2.59	9.77	7600
				(40,260)	**(7'3")**	**(10'0")**	**(28'7")**	**(8'6")**	**(32'1")**	**(16,800)**
	AEJ	99-	86/115	18 500	1.995	3.04	8.69	2.49	9.6	7580
				(40,792)	**(6'7")**	**(9'10")**	**(28'6")**	**(8'2")**	**(31'6")**	**(16,710)**
	(7KZ)	01-02	86/115	17 990	1.995	3.05	8.72	2.49	9.78	2200
				(39,660)	**(6'7")**	**(10'0")**	**(28'7")**	**(8'2")**	**(32'1")**	**(4900)**
318C	BTG	03	94/127	19 560	2.2	2.9	8.9	2.8	9.66	7850
				(43,120)	**(7'2")**	**(9'9")**	**(29'2")**	**(9'2")**	**(31'8")**	**(17,305)**
318C L	DAH(MDY)	02-07	94/127	20 160	2.2	2.9	8.9	2.8	9.66	8950
				(44,445)	**(7'2")**	**(9'9")**	**(29'2")**	**(9'2")**	**(31'8")**	**(19,730)**
318C N	FAA(GPA)	02-07	94/127	19 280	1.99	2.9	8.9	2.49	9.66	7730
				(42,505)	**(6'6")**	**(9'9")**	**(29'2")**	**(8'2")**	**(31'8")**	**(17,040)**
318D L	ZKJ(CHN)	12-13	113	17 620	1.99	3.03	8.54	2.59	8.96	6850
				(38,850)	**(6'6")**	**(9'9")**	**(28'0")**	**(8'6")**	**(29'5")**	**(14,700)**
319C LN	KGL	04	94/127	20 080	1.99	2.9	8.9	2.49	9.66	7730
				(44,269)	**(6'6")**	**(9'9")**	**(29'2")**	**(9'2")**	**(31'8")**	**(17,040)**
319D L	EAW(OSJ)	08-13	121	19 460	2.2	3.15	8.82	2.8	9.82	9150
	BZH	07-09		**(42,910)**	**(7'3")**	**(10'4")**	**(28'11")**	**(9'2")**	**(32'3")**	**(19,700)**
	(ZCA)	10-12								
	ZGZ	09-11								
	AYF	11-12								
	KRM(OSJ)	11-13								
319D LN	FMH(OSJ)	08-13	121	19 170	1.99	3.15	8.82	2.49	9.82	9150
	DAY	08-09		**(42,270)**	**(6'6")**	**(10'4")**	**(28'11")**	**(8'2")**	**(32'3")**	**(19,700)**
	(KFM)	10-12								
	WBJ	09-11								
	RJP	11-12								

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
320	7WK(OSJ)	91-96	128	19 120	2.2	2.93	9.37	2.8	10.63	6200
	2DL(OSJ)			**(42,150)**	**(7'3")**	**(9'7")**	**(30'9)**	**(9'2")**	**(34'9")**	**(17,700)**
	8LG(OSJ)									
	7GJ(JPN)									
	3XM(JPN)									
	4ZJ(GOS)									
320 L	1TL(OSJ)	91-96	128	20 370	2.38	2.93	9.37	3.18	10.63	8150
	9KK(OSJ)			**(44,910)**	**(7'10")**	**(9'7")**	**(30'9")**	**(10'5")**	**(34'9")**	**(17,600)**
	8HJ(JPN)									
	4JM(JPN)									
	3XK(GOS)									
320 N	1XM(OSJ)	94-96	128	20 050	1.90	2.93	9.37	2.59	10.63	8150
	9WG(GOS)			**(44,150)**	**(6'6")**	**(9'7")**	**(30'9")**	**(8'6")**	**(34'9")**	**(17,600)**
320 S	6KM									
320B	3MR	96-00	128	19 400	2.2	3.01	9.46	2.8	10.77	8600
	5BR			**(42,770)**	**(7'2.6")**	**(9'10.5")**	**(31'.4")**	**(9'2.2")**	**(35'4")**	**(19,000)**
	1XS									
320B L	4MR	96-00	128	20 720	2.38	3.01	9.46	3.18	10.77	9200
	6CR			**(45,680)**	**(7'9.7")**	**(9'10.5")**	**(31'.4")**	**(10'5.2")**	**(35'4")**	**(20,300)**
	7JR									
320B N	4NR	96-00	128	19 930	2.2	3.01	9.46	2.5	10.77	9100
	2AS			**(43,940)**	**(7'2.6")**	**(9'10.5")**	**(31'.4")**	**(8'2.4")**	**(35'4")**	**(20,100)**
320B LN	3YZ	96-00	128							
320C	MAB	03-06	103	20 870	2.2	3.01	9.39	2.8	9.71	8810
				(46,010)	**(7'3")**	**(9'11")**	**(30'10")**	**(9'2")**	**(31'10")**	**(19,423)**
320C L	ANB	99-07	103	21 415	2.38	3.01	9.39	2.98	9.71	9550
	PAB			**(47,212)**	**(7'10")**	**(9'11")**	**(30'10")**	**(9'9")**	**(31'10")**	**(21,054)**
	TBR									
	SAH									
320C U	MAC	03-05	103	22 300	2.2	3.01	8.73	2.8	9.86	9300
				(49,163)	**(7'3")**	**(9'11")**	**(28'8")**	**(9'2")**	**(32'4")**	**(20,503)**
320C LU	PAC	02-07	103	23 000	2.38	3.01	8.92	2.98	9.86	9600
				(50,706)	**(7'10")**	**(9'11")**	**(29'3")**	**(9'9")**	**(32'4")**	**(21,164)**
320D	AZR	05-15	103	21 000	2.2	3.03	9.46	2.8	10	9000†
	CXY			**(46,300)**	**(7'3")**	**(9'10")**	**(31'0")**	**(9'2")**	**(32'10")**	**(19,800)**
	EBT									
	BWZ									
	FAL									
	A6F									
	BZP									
	JFZ									
	SNS									
	KLM									
	KTF									
	PCM									
	KHN									
	MZD									

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.
†Without bucket.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
320D L	BWP	05-15	103	21 900	2.38	3.03	9.46	2.98	10.0	10 250†
	DHK			**(48,300)**	**(7'10")**	**(9'10")**	**(31'0")**	**(9'9")**	**(32'10")**	**(22,600)**
	MDE									
	FNA									
	DFB									
	KGF									
	A8F									
	MGG									
	PHX									
	A9F									
	WJN									
	TDH									
	SPN									
	GDP									
	KZF									
320D LN	KAF	06-11	103	21 200	2.0	3.03	9.49	2.5	9.78	N/A
	WBN			**(46,700)**	**(6'7")**	**(9'10")**	**(31'2")**	**(8'2")**	**(32'1")**	
	PCX									
320D RR	AMR	05-15	103	22 700	2.2	3.01	8.77	2.8	9.78	9050
	RBL			**(50,045)**	**(7'3")**	**(9'11")**	**(28'9")**	**(9'2")**	**(32'1")**	**(19,952)**
	GKL									
	GMX									
	YDS									
	WFD									
320D LRR	CWN	05-15	103	23 300	2.38	3.01	8.96	2.98	9.78	10 600
	SCW			**(51,368)**	**(7'10")**	**(9'11")**	**(29'5")**	**(9'9")**	**(32'1")**	**(23,369)**
	FXK									
	HJC									
	EBY									
	TAE									
	XCK									
	DHE									
	ZGB									
	EJT									
320E	SHX	13-14	107	20 900	2.2	3.15	9.54	2.8	9.86	9450†
				(46,100)	**(7'3")**	**(10'3")**	**(31'4")**	**(9'9")**	**(32'4")**	**(20,350)**
320E L	WBK	10-16	114	21 700	2.38	3.15	9.54	2.98	9.86	11 650†
	TNJ			**(47,800)**	**(7'10")**	**(10'3")**	**(31'4")**	**(9'9")**	**(32'4")**	**(25,700)**
	NAZ	10-16	107	21 700	2.38	3.15	9.54	2.98	9.86	11 650†
				(47,800)	**(7'10")**	**(10'3")**	**(31'4")**	**(9'9")**	**(32'4")**	**(25,700)**
320E LN	DFG	11-14	107	22 500	2.0	3.15	9.57	2.54	9.85	10 600†
				(49,500)	**(6'7")**	**(10'3")**	**(31'5")**	**(8'4")**	**(32'4")**	**(22,900)**
320E LRR	PNL	11-15	114	23 800	2.38	3.15	8.97	2.98	9.86	11 550†
				(52,470)	**(7'10")**	**(10'3")**	**(29'5")**	**(9'9")**	**(32'4")**	**(24,800)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.
†Without bucket.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
321B CR	AKG(JPN)	98-01	128	19 400	2.2	3.1	8.6	2.98	9.68	8250
				(42,770)	**(7'3")**	**(10'2")**	**(28'3")**	**(9'9")**	**(31'9")**	**(18,200)**
321B LCR	9CZ(JPN)	98-01	128	22 500	2.38	3.1	8.8	2.98	9.68	10 300
				(49,600)	**(7'10")**	**(10'2")**	**(28'11")**	**(9'9")**	**(31'9")**	**(22,700)**
	KGA(OSJ)	02-02	128	23 100	2.38	3.1	8.8	2.98	9.68	10 300
				(50,930)	**(7'10")**	**(10'2")**	**(28'11")**	**(9'9")**	**(31'9")**	**(22,700)**
321C CR	DAX	03-06	103	22 830	2.2	3.17	8.64	2.8	9.69	9050
				(50,332)	**(7'3")**	**(10'5")**	**(28'4")**	**(9'2")**	**(31'9")**	**(19,952)**
321C LCR	KBB	02-07	103	24 000	2.38	3.17	8.83	2.98	9.69	11 000
	MCF			**(52,911)**	**(7'10")**	**(10'5")**	**(29'0")**	**(9'9")**	**(31'9")**	**(24,251)**
	KCR									
321D CR	JCX	07-14	103	23 000	2200	3.03	8.69	2.8	9.71	N/A
				(50,700)	**(7'3")**	**(9'11")**	**(28'6")**	**(9'2")**	**(31'10")**	
321D L CR	KBH	07-15	103	23 780	2.38	3.03	8.83	2.98	9.71	11 150
	KBZ			**(52,400)**	**(7'10")**	**(9'11")**	**(29'0")**	**(9'9")**	**(31'10")**	**(24,000)**
	MDT									
	MPG									
	NAS									
	PBD									
	TXA									
322*	7WL(OSJ)	93-96	153	22 650	2.39	3.12	9.95	2.99	10.47	10 400
	7WL(JPN)			**(50,000)**	**(7'10")**	**(10'3")**	**(32'8")**	**(9'10")**	**(34'4")**	**(22,500)**
322B	8MR	96-01	153	22 760	2.39	3.28	10.0	2.99	10.47	10 650
	3NR	96-00		**(50,180)**	**(7'10")**	**(10'9")**	**(32'10")**	**(9'10")**	**(34'4")**	**(23,500)**
322 L*	8CL(OSJ)	93-96	153	23 950	2.59	3.12	9.95	3.39	10.47	10 400
	8CL(JPN)			**(52,800)**	**(8'6")**	**(10'3")**	**(32'8")**	**(11'1")**	**(34'4")**	**(22,500)**
322B L	8NR	96-01	153	23 990	2.59	3.28	10.0	3.39	10.47	11 600
	5CR	96-00		**(52,890)**	**(8'6")**	**(10'9")**	**(32'10")**	**(11'1")**	**(34'4")**	**(25,600)**
322C	DAA	03-05	121	23 000	2.39	3.12	9.96	2.99	10.01	10 750
				(50,706)	**(7'10")**	**(10'3")**	**(32'8")**	**(9'10")**	**(32'10")**	**(23,700)**
322C L	BGR	01-02	165	24 200	2.59	3.12	9.96	3.39	10.47	11 500
	BFK	02-06		**(53,400)**	**(8'6")**	**(10'3")**	**(32'8")**	**(11'1")**	**(34'4")**	**(24,900)**
	FED	02-05	121	24 200	2.59	3.12	9.96	3.19	10.01	12 000
				(53,352)	**(8'6")**	**(10'3")**	**(32'8")**	**(10'6")**	**(32'10")**	**(26,455)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
323D	WNE	10-11	110	22 200 **(48,900)**	2.2 **(7'3")**	3.12 **(10'3")**	9.46 **(31'0")**	2.8 **(9'2")**	9.83 **(32'3")**	N/A
323D L	PBM	06-11	110	23 200 **(51,100)**	2.38 **(7'10")**	3.12 **(10'3")**	9.46 **(31'0")**	2.98 **(9'9")**	9.83 **(32'3")**	10 330 **(22,800)**
	SDC									
	BYM									
	WGC									
	JLG									
	LFL									
	PBE									
	YSD									
	NDE									
	ZMF									
	GTF									
	NTF									
	NZF									
323D LN	CYD	05-11	110	23 200 **(50,700)**	2.0 **(6'7")**	3.12 **(10'3")**	9.46 **(31'0")**	2.5 **(8'2")**	9.83 **(32'3")**	10 330 **(22,800)**
	RAC									
	CWG									
323D S	DKW	05-07	103	22 500 **(49,600)**	1.9 **(6'3")**	3.1 **(10'2")**	9.46 **(31'0")**	2.5 **(8'2")**	9.44 **(31'0")**	N/A
323D SA	NES	06-11	110	23 500 **(51,800)**	1.9 **(6'3")**	3.12 **(10'3")**	9.5 **(31'2")**	2.5 **(8'2")**	9.98 **(32'9")**	10 360 **(22,800)**
	SED									
323E L	RAP	10-16	114	22 600 **(49,800)**	2.38 **(7'10")**	3.15 **(10'3")**	9.54 **(31'4")**	2.98 **(9'9")**	9.86 **(32'4")**	11 450† **(24,800)**
323E LN	TDW	10-16	114	23 300 **(51,300)**	2.0 **(6'7")**	3.15 **(10'3")**	9.56 **(31'4")**	2.54 **(8'4")**	9.85 **(32'4")**	11 450† **(24,800)**
323E SA	YRP	10-16	114	24 300 **(53,500)**	1.9 **(6'3")**	3.23 **(10'7")**	9.57 **(31'5")**	2.54 **(8'2")**	9.84 **(32'3")**	11 300† **(24,450)**
324D	MND	06-14	140	24 550 **(54,100)**	2.39 **(7'10")**	3.43 **(11'3")**	10.05 **(34'5")**	2.99 **(9'10")**	10.55 **(34'7")**	N/A
	CJX									
	JZR									
	AWN									
	ECH									
324D L	JAT	06-14	140	25 870 **(57,000)**	2.59 **(8'6")**	3.43 **(11'3")**	10.05 **(34'5")**	3.39 **(11'1")**	10.55 **(34'7")**	11 400 **(25,100)**
	SYM									
	PYT									
	GPK									
	DFP									
	TSN									
	T2D									
	LKN									
	BTK									
	JJG									
	LAB									
	BYE									
324D LN	NPC	06-11	140	25 300 **(55,800)**	2.39 **(7'10")**	3.17 **(10'5")**	10.06 **(33'0")**	2.99 **(9'10")**	10.05 **(34'5")**	13 970 **(30,800)**
	TRH									
	EJC									

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.
†Without bucket.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
324E	JCZ	11-16	142	24 750	2.39	3.22	10.06	2.99	10.11	12 350†
				(54,600)	**(7'10")**	**(10'7")**	**(33'0")**	**(9'10")**	**(33'2")**	**(26,450)**
324E L	KTE	10-16	145	26 310	2.59	3.22	10.06	3.38	10.11	15 350†
	PNW			**(58,000)**	**(8'6")**	**(10'7")**	**(33'0")**	**(11'1")**	**(33'2")**	**(32,900)**
	TLF									
324E LN	LDG	10-15	145	25 130	2.39	3.41	10.1	2.99	10.11	15 100†
				(55,400)	**(7'10")**	**(11'2")**	**(33'2")**	**(9'10")**	**(33'2")**	**(32,300)**
325*	5WK(OSJ)	91-95	168	25 520	2.39	3.24	10.27	2.99	11.50	11 100
	8NL(OSJ)			**(56,270)**	**(7'10")**	**(10'8")**	**(33'8")**	**(9'10")**	**(37'7")**	**(24,000)**
	8JG(JPN)	91-95	168	25 520	2.39	3.24	10.27	2.99	11.50	11 000
	5WK(JPN)			**(56,270)**	**(7'10")**	**(10'8")**	**(33'8")**	**(9'10")**	**(37'7")**	**(24,000)**
325 L*	6KK(OSJ)	91-95	168	27 010	2.59	3.24	10.27	3.39	11.50	11 650
	9KL(OSJ)			**(59,560)**	**(8'6")**	**(10'8")**	**(38'8")**	**(11'1")**	**(37'7")**	**(25,150)**
	7CJ(JPN)	91-95	168	27 010	2.59	3.24	10.27	3.39	11.50	11 650
	6KK(JPN)			**(59,560)**	**(8'6")**	**(10'8")**	**(38'8")**	**(11'1")**	**(37'7")**	**(25,150)**
325B L	6DN(GOS)	96-01	168	28 890	2.59	3.21	10.35	3.39	10.57	15 460
				(63,690)	**(8'6")**	**(10'6")**	**(33'11")**	**(11'1")**	**(34'8")**	**(34,080)**
325B LN	8FN(GOS)	96-01	168	27 670	2.39	3.21	10.35	2.99	10.57	15 030
				(61,000)	**(7'10")**	**(10'6")**	**(33'11")**	**(9'10")**	**(34'8")**	**(33,140)**
325C L	CBR	01-06	188	28 600	2.59	3.26	10.34	3.39	10.51	15 600
	CSJ			**(63,100)**	**(8'6")**	**(10'8")**	**(33'11")**	**(11'1")**	**(34'6")**	**(33,750)**
325D L	A3R	06-08	204	29 240	2.59	3.04	10.42	3.39	11.15	15 450
				(64,460)	**(8'6")**	**(10'0")**	**(34'2")**	**(11'1")**	**(36'7")**	**(33,400)**
326D L	PJM	12-14	140	25 560	2.59	3.17	10.06	3.39	10.03	13 900
				(56,400)	**(8'6")**	**(10'5")**	**(33'0")**	**(11'1")**	**(32'11")**	**(30,600)**
328D L CR	RMX	06-15	152	36 200	2.59	3.37	9.82	3.44	10.56	12 300
	JTC			**(79,800)**	**(8'6")**	**(11'1")**	**(32'3")**	**(11'3")**	**(34'8")**	**(28,000)**
	MKR									
	GTN									
	SWF									
	BYH									

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.
†Without bucket.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
329D	BBF	08-14	158	28 010	2.39	3.33	10.36	2.99	10.72	13 750
	WDK			**(61,620)**	**(7'10")**	**(10'11")**	**(34'0")**	**(9'10")**	**(35'2")**	**(29,450)**
	BYS									
	DTZ									
329D L	TAY	08-15	158	29 970	2.59	3.33	10.36	3.39	10.72	16 200
	MNB			**(65,920)**	**(8'6")**	**(10'11")**	**(34'0")**	**(11'1")**	**(35'2")**	**(35,050)**
	DJF									
	JHJ									
	BFC									
	LFW									
	RSK									
	TPM									
	J9D									
	J8D									
	L5G									
	L5H									
	TFW									
	XDB									
	CZF									
	WLT									
	TZL									
329D LN	SCY	08-11	152	28 860	2.39	3.18	10.41	2.99	10.6	13 050
	EBM			**(63,600)**	**(7'10")**	**(10'5")**	**(34'2")**	**(9'10")**	**(34'9")**	**(28,800)**
329E	PTY	10-15	170	27 700	2.39	3.37	10.39	2.99	10.68	14 300†
				(61,100)	**(7'10")**	**(11'1")**	**(34'1")**	**(9'10")**	**(35'0")**	**(30,650)**
329E L	RDX	10-16	170	29 060	2.59	3.37	10.39	3.39	10.68	18 150†
	WJK			**(64,100)**	**(8'6")**	**(11'1")**	**(34'1")**	**(11'1")**	**(35'0")**	**(3,300)**
	ZCD									
	PLW									
	TST									
329E LN	RLD	10-15	170	28 720	2.39	3.37	10.39	2.99	10.68	18 150†
				(63,300)	**(7'10")**	**(11'1")**	**(34'1")**	**(9'10")**	**(35'0")**	**(39,300)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.
†Without bucket.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
330	2ZM	92-95	222	32 100	2.59	3.29	11.01	3.19	12.37	14 600
	6ZK			**(70,600)**	**(8'6")**	**(10'10")**	**(36'1")**	**(10'6")**	**(40'6")**	**(31,500)**
	8RL									
	9NG									
	9PG									
	9WJ									
330 L	2EL	92-95	222	33 500	2.59	3.29	11.01	3.34	12.43	14 600
	5YM			**(73,700)**	**(8'6")**	**(10'10")**	**(36'1")**	**(10'11")**	**(40'9")**	**(31,500)**
	6SK									
	6WJ									
	8FK									
	9ML									
330 LN	8CK	92-95	222	32 740	2.39	3.29	11.01	2.99	12.37	14 600
				(72,030)	**(7'10")**	**(10'10")**	**(36'1")**	**(9'10")**	**(40'6")**	**(31,500)**
330B	2RR	96-01	222	32 500	2.59	3.29	11.06	3.19	11.62	16 450
	4YW			**(71,650)**	**(8'6")**	**(10'10")**	**(36'3")**	**(10'6")**	**(38'1")**	**(35,200)**
	5EZ									
	8SR									
	9HN									
330B L	1JS	96-01	222	33 800	2.59	3.29	11.06	3.34	11.69	17 000
	1KS			**(74,520)**	**(8'6")**	**(10'10")**	**(36'3")**	**(10'11")**	**(38'4")**	**(36,750)**
	3YR									
	3ZZ									
	4RS									
	5LS									
	6DR									
	8TR									
330B LN	5LR	96-01	222	33 200	2.39	3.29	11.06	2.99	11.62	16 950
				(73,190)	**(7'10")**	**(10'10")**	**(36'3")**	**(9'10")**	**(38'1")**	**(36,600)**
330C	BTM	01-06	247	33 300	2.59	3.35	11.14	3.19	11.64	16 900
	GAG			**(73,410)**	**(8'6")**	**(11')**	**(36'7")**	**(10'6")**	**(38'2")**	**(36,550)**
	HAA									
	JCD									
	JNK									
	MCA									
	MKM									
	RBH									
330C L	CAP	01-06	247	34 800	2.59	3.35	11.14	3.34	11.64	16 900
	CYA			**(76,720)**	**(8'6")**	**(11')**	**(36'7")**	**(10'11")**	**(38'2")**	**(36,550)**
	DKY									
	GKX									
	JAB									
	KDD									
330C LN	CGZ	01-06	247	34 400	2.39	3.35	11.14	2.99	11.64	16 900
				(75,840)	**(7'10")**	**(11')**	**(36'7")**	**(9'10")**	**(38'2")**	**(36,550)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
330D	EAH	06-08	270	33 900	2.59	3.34	11.15	3.19	11.64	17 000
	JJM			**(74,740)**	**(8'6")**	**(10'11")**	**(36'7")**	**(10'6")**	**(38'2")**	**(36,550)**
	KAB									
	LCJ									
	MEY									
	PCK									
	PFC									
330D L	B6H	06-08	270	35 100	2.59	3.34	11.15	3.29	11.64	17 000
	EDX			**(77,380)**	**(8'6")**	**(10'11")**	**(36'7")**	**(10'10")**	**(38'2")**	**(36,700)**
	ERN									
	FFK									
	GBC									
	HAS									
	JLP									
	LDR									
	LRM									
	MAG									
	MWP									
	NBD									
	NEF									
	R2D									
	RAS									
	RDA									
	RDK									
	T2Y									
	THJ									
330D LN	GGE	06-08	270	34 900	2.39	3.34	11.15	2.99	11.64	17 000
				(76,940)	**(7'10")**	**(10'11")**	**(36'7")**	**(9'10")**	**(38'2")**	**(36,700)**
336D	EMX	09-13	270	33 900	2.59	3.34	11.15	3.19	11.64	17 000
	JBT			**(74,740)**	**(8'6")**	**(10'11")**	**(36'7")**	**(10'6")**	**(38'2")**	**(36,550)**
	JER									
	KKT									
	PGW									

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
336D L	DTS	09-13	270	35 100	2.59	3.34	11.15	3.29	11.64	17 000
	J2F			**(77,380)**	**(8'6")**	**(10'11")**	**(36'7")**	**(10'10")**	**(38'2")**	**(36,700)**
	JBF									
	JWR									
	KDJ									
	LMG									
	M2P									
	M4T									
	MDS									
	MPL									
	NLS									
	PPN									
	PRF									
	PTB									
	SKE									
	W3K									
	WET									
	WRK									
	ZML									
336D LN	L5K	09-13	270	34 900	2.39	3.34	11.15	2.99	11.64	17 000
	MYG			**(76,940)**	**(7'10")**	**(10'11")**	**(36'7")**	**(9'10")**	**(38'2")**	**(36,700)**
	MYP									
336E	CMR	11-16	306	34 600	2.59	3.51	11.16	3.19	11.72	
	KED			**(76,280)**	**(8'6")**	**(11'6")**	**(36'7")**	**(10'6")**	**(38'5")**	
336E L	BMH	11-16	306	37 300	2.59	3.51	11.16	3.29	11.72	20 100
	BZY			**(82,200)**	**(8'6")**	**(11'6")**	**(36'7")**	**(10'10")**	**(38'5")**	**(43,450)**
	DPX									
	FJH									
	GTJ									
	JRJ									
	TEG									
	YCE									
	YEP									
336E LN	TMZ	11-16	306	35 700	2.39	3.51	11.16	2.99	11.72	20 550
				(78,700)	**(7'10")**	**(11'6")**	**(36'7")**	**(9'10")**	**(38'5")**	**(44,550)**
336E H	HDW	13-16	306	34 800	2.59	3.51	11.19	3.19	11.72	
				(76,720)	**(8'6")**	**(11'6")**	**(36'9")**	**(10'6")**	**(38'5")**	
336E L H	GNY	13-16	306	37 200	2.59	3.51	11.19	3.29	11.72	19 250
	JEA			**(82,000)**	**(8'6")**	**(11'6")**	**(36'9")**	**(10'10")**	**(38'5")**	**(41,650)**
	RZA									
336E LN H	SSL	13-16	306	35 500	2.39	3.51	11.19	2.99	11.72	19 850
				(78,300)	**(7'10")**	**(11'6")**	**(36'9")**	**(9'10")**	**(38'5")**	**(42,950)**
340D L	JTN	11-13	270	38 200	2.92	3.59	11.15	3.52	11.08	18 520
				(84,220)	**(9'7")**	**(11'9")**	**(36'7")**	**(11'7")**	**(36'4")**	**(40,830)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
345B	4SS	97-00	290	44 050 **(97,100)**	2.74 **(9'0")**	3.76 **(12'4")**	11.79 **(33'8")**	3.49 **(11'5")**	13.0 **(42'8")**	20 850 **(45,000)**
345B L	7KS(GOS) 2SW(GOS)	98-00	290	47 665 **(105,080)**	2.39 **(7'10")**	3.68 **(12'1")**	11.74 **(38'6")**	2.99 **(9'10")**	12.97 **(42'6")**	21 000 **(46,300)**
345B L Series II	CCC(VG) FEE(FG) DET(MH)	01-05	321	48 960 **(107,960)**	2.39 **(7'10")**	3.87 **(12'8")**	11.46 **(37'7")**	2.99 **(9'10")**	11.69 **(38'4")**	19 250 **(42,450)**
345C L	ELS(FG) GCL(VG)	05-08	325	50 500 **(111,350)**	2.39 **(7'10")**	3.74 **(12'3")**	11.84 **(38'10")**	2.99 **(9'10")**	11.70 **(38'5")**	20 100 **(44,320)**
345C L	LYS(FG) GPH(VG) FPC(VG)	05-08	325	50 500 **(111,350)**	2.39 **(7'10")**	3.74 **(12'3")**	11.84 **(38'10")**	2.99 **(9'10")**	11.70 **(38'5")**	20 100 **(44,320)**
345D	NEG BYW, FES		380	44 490 **(98,084)**	2.89 **(9'6")**	3.94 **(13'0")**	11.90 **(39'1")**	3.49 **(11'5")**	11.70 **(38'5")**	9050 **(19,500)**
345D L	PBT RAE BYC YEE DPA, HLC EEH, RAJ RGG RDC, MLK RBT, RGD			47 200 **(104,060)**	2.89 **(9'6")**	3.94 **(13'0")**	11.90 **(39'1")**	3.49 **(11'5")**	11.70 **(38'5")**	9050 **(19,500)**
349D	MEN GKF	11-14	380	44 490 **(98,084)**	2.89 **(9'6")**	3.94 **(13'0")**	11.9 **(39'1")**	3.49 **(11'5")**	11.7 **(38'5")**	9050 **(19,500)**
349D L	NNF KLH PZG WTD) JGB KHS RBJ	11-14	380	47 200 **(104,060)**	2.89 **(9'6")**	3.94 **(13'0")**	11.9 **(39'1")**	3.49 **(11'5")**	11.7 **(38'5")**	9050 **(19,500)**
349E L (FG)	TFG MPZ	11-14	317	48 500 **(106,900)**	2.74 **(9'0")**	3.73 **(12'3")**	11.92 **(39'1")**	3.49 **(11'5")**	12.12 **(39'9")**	23 850 **(55,200)**
349E L (VG)	KCN DGE	11-14	317	51 200 **(112,900)**	2.89 **(9'6")**	3.55 **(11'8")**	11.82 **(38'9")**	3.64 **(11'11")**	12.09 **(39'8")**	24 100 **(55,700)**
350	7RK	93-99	286	48 040 **(105,910)**	2.55 **(8'4.4")**	3.75 **(12'3.6")**	12.2 **(40'.3")**	3.2 **(10'6")**	13.45 **(44'1.5")**	17 750 **(39,100)**
	2ZL	93-99	286	50 094 **(110,210)**	2.55 **(8'4.4")**	3.75 **(12'4")**	12.2 **(40'0")**	3.3 **(10'10")**	13.49 **(44'3")**	17 750 **(39,100)**
350 L	9DK	93-99	286	49 010 **(108,050)**	2.55 **(8'4.4")**	3.75 **(12'3.6")**	12.2 **(40'.3")**	3.3 **(10'9.9")**	13.45 **(44'1.5")**	17 750 **(39,100)**
	3ML	93-99	286	51 126 **(112,450)**	2.55 **(8'4.4")**	3.75 **(12'4")**	12.2 **(40'0")**	3.3 **(10'10")**	13.49 **(44'3")**	17 600 **(40,900)**
365B L	9PZ(GOS)	99-02	385	66 245 **(146,050)**	2.75 **(9'0")**	4.57 **(15'0")**	12.17 **(39'11")**	3.50 **(11'6")**	14.04 **(46'1")**	29 200 **(64,370)**
365B L Series II	JMB(EAME) DER(NACD) PEG(FS)	02-04	404	70 250 **(154,900)**	2.75 **(9'0")**	4.7 **(15'5")**	12.54 **(41'2")**	3.42 **(11'3")**	14.09 **(16'3")**	13 040 **(28,750)**

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Track) (cont'd)

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
374D L	PJA PAX PAP PAS PAC	Sep 2010	355 kW **(476 hp)**	71 132 **(156,819)** Reach Boom R3.6 **(11'10")** Stick 3.8 m^3 **(5.0 yd^3)** Bucket 650 mm **(26 in)** Shoe	2.75 **(9'0")** Shipping 3.41 **(11'2")** Working	4.48 **(14'8")** Reach Boom R3.6 **(11'10")** Stick	13.32 **(43'8")** Reach Boom R3.6 **(11'10")** Stick	3.5 **(11'6")** Transpor-tation 750 mm **(30 in)** Shoe	14.23 **(46'8")** Reach Boom R4.67m **(15'4")** Stick 3.8 m^3 **(5.0 yd^3)** Bucket	17 300 **(39,900)** Reach Boom R4.67m **(15'4")** Stick 900 mm **(36 in)** Shoe Ground Level 4.5 m **(15'0")** Over Front
375	8WJ	92-01	428	81 190 **(178,800)**	2.75 **(9'0")**	5.24 **(17'2")**	14.3 **(46'11")**	3.5 **(11'6")**	15.96 **(52'4")**	30 300 **(65,600)**
	6NK(GOS)	92-02	428	79 807 **(175,940)**	2.75 **(9'0")**	5.24 **(17'2")**	13.14 **(43'1")**	3.48 **(11'5")**	15.67 **(51'5")**	23 620 **(52,070)**
375 L	1JM	93-01	428	82 380 **(181,500)**	2.94 **(9'7")**	5.24 **(17'2")**	14.3 **(46'11")**	3.84 **(12'7")**	15.96 **(52'4")**	29 550 **(64,400)**
	9WL(GOS)	92-02	428	80 700 **(177,910)**	2.75 **(9'0")**	5.24 **(17'2")**	14.29 **(46'11")**	3.48 **(11'5")**	15.67 **(51'5")**	23 620 **(52,070)**
385B L	FDL(EAME) RCD(NACD) CLS(EAME) MYA(NACD)	01-04	513	89 130 **(196,530)**	2.75 **(9'0")**	5.16 **(16'11")**	14.6 **(47'11")**	3.73 **(12'3")**	15.61 **(51'2")**	13 810 **(30,450)**
390D L	WAG WBT WAP	Nov 2010	390 kW **(523 hp)**	86 190 **(190,016)** GP Boom **(27'7")** R4.4m **(14'5")** Stick 4.6 m^3 **(6.0 yd^3)** HD Bucket 650 mm **(26 in)** Shoe	2.75 **(9'0")** Shipping 3.51 **(11'6")** Working	5.16 **(16'11")** GP Boom **(27'7")** GP3.4m **(11'2")** Stick	14.72 **(48'4")** GP Boom **(27'7")** GP3.4m **(11'2")** Stick	4.26 **(14'0")** Transpor-tation 750 mm **(30 in)** Shoe	17.25 **(56'7")** Reach Boom R5.5m **(18'1")** Stick 3.9 m^3 **(5.1 yd^3)** Bucket	11 350 **(25,900)** Reach Boom R5.5m **(18'1")** Stick 900 mm **(36 in)** Shoe –1.5 m **(–5.0 ft)** 4.5 m **(15'0")** Over Front
5090B	CLD EAME SJY NACD	01-04	512	87 500 **(192,937)**	3.5 **(11.51)**	4.63 **(15.19)**	14.26 **(46.77)**	3.47 **(11.38)**	10.35 **(33.95)**	— —

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick (6.1 m **(20'0")** over front for 375/375 L).