

HYDRAULIC EXCAVATORS (Wheel)

Model	Product Ident. No. Prefix (USA)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)	Standard Tire Size
206	(2RC)	84-90	Deutz-67	12 185	3.11	7.38	2.40	8.14	3360	Dual 9.00-20 12PR
	(3GC)		Perkins-71	**(26,863)**	**(10'2")**	**(24'2.5")**	**(7'10")**	**(26'9")**	**(7400)**	
212	(3JC)	84-90	Deutz-84	13 700	3.15	8.00	2.49	9.86	3850	Dual 10.00-20 12PR
	(5DC)		Perkins-94	**(30,423)**	**(10'4")**	**(26'3")**	**(8'2")**	**(32'4")**	**(8490)**	
212B	(3PJ)	90-95	110	14 000	3.04	8.28	2.49	9.48	3900	Dual 10.00-20 12PR
				(30,870)	**(10'0")**	**(27'2")**	**(8'2")**	**(31'1")**	**(8600)**	
214	(9MB)	84-88	Deutz-101	15 600	3.06	8.28	2.49			Dual 10.00-20 12PR
	(1KB)		Perkins-102	**(34,175)**	**(10'0")**	**(27'2")**	**(8'2")**			
214B	4CF	88-94	110	18 700	3.06	8.28	2.49	10.41	4200	Dual 10.00-20 12PR
				(41,230)	**(10'0")**	**(27'2")**	**(8'2")**	**(34'2")**	**(9260)**	
214B FT	9NF	88-94	135	18 700	3.06	8.28	2.49	10.41	4200	Dual 10.00-20 12PR
				(41,230)	**(10'0")**	**(27'2")**	**(8'2")**	**(34'2")**	**(9260)**	
224	(2JC)	84-89	Deutz-143	19 000	3.42	8.98	2.49	10.61	4800	Dual 10.00-20 12PR
	(5TC)		Perkins-124	**(41,890)**	**(11'3")**	**(29'6")**	**(8'2")**	**(34'10")**	**(10,600)**	
224B	7WF	89-95	135	21 000	3.95	9.08	2.65	10.75	4800	Dual 11.00-20 14PR
				(46,297)	**(13'0")**	**(29'9")**	**(8'8")**	**(35'3")**	**(10,582)**	

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Hydraulic Excavators (Wheel) (cont'd)

Model	Product Ident. No. Prefix (USA)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)	Standard Tire Size
M312	6TL	96-02	114	13 425 **(29,602)**	3.07 **(10'1")**	8.62 **(28'3")**	2.5 **(8'2")**	8.9 **(29'2")**	4300 **(9482)**	10-20.00 14PR
M313C	H2A	05-06	118	13 100-14 750	3.12	8.08	2.55	8.77	4800	10.00-20 16PR
	BDR	02-05		**(28,886-35,524)**	**(10'2")**	**(26'6")**	**(8'4")**	**(28'9")**	**(10,584)**	
M313D	J3A	12-13	127	14 000-16 200	3.12	8.08	2.55	8.77	4800	10.00-20 16PR
	W3H	07-12		**(30,870-35,721)**	**(10'3")**	**(26'6")**	**(8'4")**	**(28'10")**	**(10,582)**	
M315	7ML	95-02	117	15 570 **(34,332)**	3.08 **(10'1")**	8.84 **(29'0")**	2.5 **(8'2")**	9.26 **(30'5")**	5100 **(11,246)**	10-20.00 14PR
M315C	H2B	05-06	129	15 000-16 650	3.15	8.33	2.55	9.17	5600	10.00-20 16PR
	BDM	02-05		**(33,075-36,713)**	**(10'4")**	**(27'4")**	**(8'4")**	**(30'1")**	**(12,348)**	
M315D	J5B	12-13	136	16 100-18 300	3.15	8.33	2.55	9.17	5700	10.00-20 16PR
	W5M	07-12		**(35,501-40,352)**	**(10'4")**	**(27'4")**	**(8'4")**	**(30'1")**	**(12,566)**	
M316C	H2C	05-06	138	16 300-18 200	3.17	8.40	2.55	9.17	6500	10.00-20 16PR
	BDX	02-05		**(35,942-40,131)**	**(10'5")**	**(27'7")**	**(8'4")**	**(30'1")**	**(14,330)**	
M316D	D6W	11-13	158	17 000-19 200	3.17	8.4	2.55	9.17	6400	10.00-20 16PR
	W6A	07-11		**(37,478-42,329)**	**(10'5")**	**(27'7")**	**(8'4")**	**(30'1")**	**(14,110)**	
M318	8AL	95-02	131	17 870 **(39,403)**	3.1 **(10'2")**	8.97 **(29'5")**	2.6 **(8'6")**	10.55 **(34'7")**	6400 **(14,112)**	10-20.00 14PR
M318C	H2D	05-06	151	17 800-19 700	3.21	8.96	2.55	9.60	6600	10.00-20 16PR
	BCZ	02-05		**(39,249-43,439)**	**(10'6")**	**(29'5")**	**(8'4")**	**(31'6")**	**(14,550)**	
M318D	D8W	11-13	166	18 200-20 100	3.17	8.96	2.55	9.6	6600	10.00-20 16PR
	W8P	07-11		**(40,124-44,312)**	**(10'5")**	**(29'5")**	**(8'4")**	**(31'6")**	**(14,550)**	
M320	6WL	97-02	131	20 200 **(44,541)**	3.21 **(10'6")**	9.55 **(31'4")**	2.75 **(9'0")**	11.18 **(36'8")**	7500 **(16,538)**	11-20.00 14PR
M322C	H2E	05-06	164	20 500-22 700	3.25	9.64	2.75	10.32	7300	11.00-20 16PR
	BDK	02-05		**(45,203-50,054)**	**(10'8")**	**(31'7")**	**(9'0")**	**(33'10")**	**(16,093)**	
M322D	D2W	11-13	164	20 500-22 500	3.20	9.64	2.75	10.32	7200	11.00-20 16PR
	W2S	07-11		**(45,195-49,604)**	**(10'6")**	**(31'7")**	**(9'0")**	**(33'10")**	**(15,873)**	

*When shipped with medium stick and bucket curled under, one-piece boom.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, rear dozer up, one-piece boom, longest stick.



5000 SERIES EXCAVATORS AND FRONT SHOVELS

Model	Product Ident. No. Prefix COSA (US)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Track Gauge m (ft)	Height* m (ft)	Length* m (ft)	Width m (ft)	Max. Reach** m (ft)	Lift Capacity*** kg (lb)
5080	6XK(GOS)	94-02	428	83 800 **(184,750)**	2.75 **(9'0")**	4.73 **(15'6")**	13.76 **(45'2")**	3.48 **(11'5")**	9.76 **(32'0")**	—
5090B	CLD(EAME) SJY(NACD)	01-04	512	87 500 **(192,940)**	3.51 **(11'6")**	4.63 **(15'2")**	14.26 **(46'9")**	3.47 **(11'5")**	10.35 **(33'11")**	—

*When shipped with medium stick and bucket curled under.
**Maximum reach at ground level, one-piece boom, longest stick.
***Lift capacity at 4.6 m **(15'0")** over front, one-piece boom, longest stick.

Model	Product Ident. No. Prefix (USA)	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Rated* Capacity m^3 (yd^3)	Breakout Force kN (lb)	Crowd Force kN (lb)	Track Gauge m (ft)	Max. Reach* m (ft)	Max. Load Height m (ft)	Max. Digging Depth m (ft)
5110B ME	AAA	00-03	696	127 000 **(280,000)**	7.6 **(9.9)**	501 **(112,600)**	439 **(98,800)**	4.1 **(13.4')**	13.9 **(45.7')**	8.6 **(28.0')**	7.9 **(25.9')**
5110B L	AAK	02-03	696	129 000 **(284,000)**	4.6 **(6.0)**	463 **(104,175)**	377 **(84,825)**	4.1 **(13.4')**	16.39 **(53.8')**	10.06 **(33.0')**	10.51 **(34.5')**
5130 ME	5ZL	92-97	755	180 000 **(397,000)**	10.0 **(13.0)**	615 **(138,400)**	624 **(140,300)**	4.72 **(15'6")**	14.9 **(48'11")**	9.1 **(29'10")**	8.4 **(27'7")**
5130 FS	5ZL	92-97	755	179 000 **(395,000)**	10.5 **(13.7)**	715 **(161,000)**	770 **(173,000)**	4.72 **(15'6")**	12.4 **(40'8")**	9.1 **(29'10")**	—
5130B ME	4CS	97-03	800	182 000 **(401,000)**	10.5 **(13.7)**	672 **(151,100)**	624 **(140,300)**	4.72 **(15.5')**	14.9 **(48.9')**	9.1 **(29.8')**	8.4 **(27.6')**
5130B FS	4CS	97-03	800	181 000 **(399,000)**	11.0 **(14.5)**	715 **(161,000)**	770 **(173,000)**	4.72 **(15.5')**	12.4 **(40.7')**	9.1 **(29.8')**	—
5230 ME	7LL	94-00	1470	316 600 **(698,000)**	16.0 **(21.0)**	873 **(196,260)**	874 **(196,480)**	5.2 **(17'0")**	17.7 **(58'0")**	9.8 **(32'2")**	9.4 **(30'10")**
5230 FS	7LL	94-00	1470	318 422 **(702,000)**	17.0 **(22.2)**	1125 **(253,000)**	1250 **(281,000)**	5.2 **(17'0")**	14.8 **(48'7")**	10.3 **(33'10")**	—
5230B ME	4HZ	01-04	1550	328 100 **(723,400)**	16.0 **(21.0)**	855 **(192,083)**	885 **(198,848)**	5.196 **(17.0')**	17.8 **(58.4')**	9.8 **(32.0')**	9.5 **(31.3')**
5230B FS	4HZ	01-04	1550	327 000 **(721,000)**	17.0 **(22.2)**	1162 **(261,145)**	1145 **(257,324)**	5.196 **(17.0')**	14.9 **(48.8')**	10.4 **(34.1')**	—

*Standard boom and stick.



6000 SERIES HYDRAULIC MINING SHOVELS

Model	Product Ident. No. Prefix	Years Built	Approx. Operating Weight kg (lb)	Flywheel Horsepower kW (hp)	Rated Capacity m^3 (yd^3)	Breakout Force kN (lb)	Tearout/ Crowd Force kN (lb)	Track Gauge m (ft)	Max. Reach m (ft)	Max. Load Height m (ft)	Max. Digging Depth m (ft)
6015	DHB	95-16	106 100 **(233,910)**	496 **(665)**	6.0 **(7.8)**	380 **(85,400)**	375 **(84,270)**	3.8 **(12'6")**	13.5 **(44'3")**	9.0 **(29'6")**	7.3 **(23'11")**
6015 ME*	DHB	96-16	106 000 **(233,690)**	496 **(665)**	7.0 **(9.2)**	410 **(92,140)**	390 **(87,640)**	3.8 **(12'6")**	12.6 **(41'4")**	9.2 **(30'2")**	6.0 **(19'8")**
6015 FS	DHF	95-16	104 900 **(231,260)**	496 **(665)**	7.0 **(9.2)**	480 **(107,870)**	645 **(144,950)**	3.8 **(12'6")**	10.5 **(34'5")**	8.8 **(28'10")**	—
6018	DHT	86-16	186 000 **(410,060)**	824 **(1104)**	10.0 **(13.1)**	510 **(114,610)**	540 **(121,350)**	4.5 **(14'9")**	15.6 **(51'2")**	8.9 **(29'2")**	8.5 **(27'11")**
6018 FS	DHD	86-16	183 400 **(404,320)**	824 **(1104)**	10.0 **(13.1)**	730 **(164,050)**	910 **(204,500)**	4.5 **(14'9")**	12.9 **(42'4")**	10.1 **(33'2")**	—

*Mass Excavation backhoe attachment.



WHEEL MATERIAL HANDLERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower kW (hp)	Approx. Operating Weight kg (lb)	Max. Reach m (ft)	Lift Capacity* kg (lb)
M318 MH	6ES	98-02	104 **(140)**	19 500 **(43,000)**	10.5 **(34'8")**	2100 **(4630)**
	8SS	98-02	104 **(140)**	19 500 **(43,000)**	10.5 **(34'8")**	2100 **(4630)**
M318C MH	BEB	02-05	113 **(151)**	21 460 **(47,311)**	11.0 **(36'1")**	2100 **(4630)**
	H2F	05-06	113 **(151)**	21 460 **(47,311)**	11.0 **(36'1")**	2100 **(4630)**
M318D MH	D9X W8R	11-13 07-11	124 **(166)**	18 200-20 100 **(40,124-44,312)**	11.0 **(36'1")**	2150 **(4740)**
M320 MH	9PS	98-02	104 **(140)**	21 150 **(46,600)**	11.6 **(38'0")**	3200 **(7055)**
M322C MH	BDY	02-05	122 **(164)**	24 690 **(54,432)**	12.5 **(41'0")**	2300 **(5070)**
	H2G	05-06	122 **(164)**	24 690 **(54,432)**	12.5 **(41'0")**	2300 **(5070)**
M322D MH	D3X W2T	11-13 07-11	122 **(164)**	20 500-22 500 **(45,195-49,604)**	12.5 **(41'0")**	2050) **(4519)**
325 WMH	2SL	98	125 **(168)**	35 100 **(77,400)**	13.4 **(43'11")**	4200 **(9400)**
325B WMH	2JR	98	132 **(177)**	34 958 **(77,000)**	13.4 **(43'11")**	4700 **(10,400)**
M325B MH	2JR	99-00	125 **(168)**	37 200 **(82,040)**	15.5 **(50'10")**	3040 **(6700)**
	BGN	01-04	125 **(168)**	37 200 **(82,040)**	15.5 **(50'10")**	3040 **(6700)**
M325C MH	XJA	03-06	128 **(173)**	31 500 **(69,450)**	15.65 **(51'4")**	2960 **(6526)**
M325C LMH	PAN	03-06	140 **(189)**	37 000 **(81,570)**	15.65 **(51'4")**	3510 **(7738)**
W330B MH	AME	00-02	165 **(222)**	52 800 **(116,300)**	14.4 **(47'3")**	4800 **(10,700)**
W345B MH	ANJ	02	216 **(290)**	64 250 **(141,650)**	16.5 **(54'0")**	5300 **(11,800)**
	CDY	02-04	239 **(321)**	66 040 **(145,288)**	16.5 **(54'0")**	5300 **(11,800)**
W345C MH	R5K	05	257 **(345)**	64 745 **(142,740)**	18.0 **(59'1")**	5150 **(11,400)**
350 WMH	9FL	98	213 **(286)**	68 812 **(151,800)**	17.1 **(56'3")**	6300 **(13,889)**
	3ML	99	213 **(286)**	68 812 **(151,800)**	17.1 **(56'3")**	6300 **(13,889)**

*Lift at maximum reach over front at 3 m **(10 ft)** elevation from stick pin, no tool.



TRACK MATERIAL HANDLERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower kW (hp)	Approx. Operating Weight kg (lb)	Max. Reach m (ft)	Lift Capacity* kg (lb)
320 MH	3XK	-99	96 **(128)**	23 030 **(50,670)**	12.4 **(40'8")**	2910 **(6400)**
	9KK	-99	96 **(128)**	23 030 **(50,670)**	12.4 **(40'8")**	2910 **(6400)**
320B MH	6LS	99-01	100 **(134)**	23 030 **(50,670)**	12.4 **(40'8")**	3150 **(6900)**
320C MH	BGB	01-02	103 **(138)**	25 530 **(56,283)**	12.4 **(40'8")**	3150 **(6900)**
	SAH	03-07	103 **(138)**	25 530 **(56,283)**	12.4 **(40'8")**	3150 **(6900)**
325 MH	2SL	-98	125 **(168)**	31 400 **(69,237)**	13.4 **(43'11")**	4130 **(9100)**
325B MH	2JR	98-02	132 **(177)**	33 236 **(73,120)**	13.4 **(43'11")**	4200 **(9200)**
325C MH	S2C	03-05	140 **(188)**	34 630 **(76,350)**	15.5 **(50'10")**	3000 **(6600)**
325D MH	RJK	05-12	152 **(204)**	35 526 **(78,321)**	15.5 **(50'11")**	3010 **(6630)**
	C4H	05-12	152 **(204)**	35 526 **(78,321)**	15.5 **(50'11")**	3010 **(6630)**
330 MH	5YM	-98	166 **(222)**	39 100 **(86,215)**	14.4 **(47'3")**	4080 **(9000)**
330B MH	6DR	98-02	165 **(222)**	41 430 **(91,350)**	14.4 **(47'3")**	4900 **(10,800)**
330C MH	D3C	03-05	184 **(247)**	43 815 **(96,595)**	15.9 **(52'2")**	3900 **(8600)**
330D MH	LEM	05-13	200 **(268)**	44 627 **(98,386)**	16.0 **(52'6")**	3670 **(8090)**
	C5K	05-13	200 **(268)**	44 627 **(98,386)**	16.0 **(52'6")**	3670 **(8090)**
345B MH	2NW	97-00	216 **(290)**	55 705 **(122,550)**	16.5 **(54'0")**	5300 **(11,600)**
345BII MH	APB	00-05	239 **(321)**	56 100 **(123,420)**	16.5 **(54'0")**	5300 **(11,600)**
345C MH	M2R	05-13	257 **(345)**	57 431 **(126,615)**	18.0 **(59'1")**	5000 **(11,000)**
	D3S	05-13	257 **(345)**	57 431 **(126,615)**	18.0 **(59'1")**	5000 **(11,000)**
350 MH	8KZ	-00	213 **(286)**	61 576 **(135,630)**	17.1 **(56'3")**	5350 **(11,800)**
	9FL	-00	213 **(286)**	61 576 **(135,630)**	17.1 **(56'3")**	5350 **(11,800)**
365B MH	CTY	02-03	287 **(385)**	74 470 **(164,177)**	18.9 **(61'11")**	6320 **(13,540)**
365BII MH	SDL	04	302 **(404)**	74 470 **(164,177)**	18.9 **(62'3")**	6320 **(13,540)**
365C MH	GWC	05-06	302 **(404)**	79 263 **(174,744)**	19.8 **(65'1")**	5400 **(11,905)**
375 MH	8SL	00	319 **(428)**	92 081 **(203,000)**	21.1 **(69'3")**	5900 **(13,200)**
	1JM	00-05	319 **(428)**	92 081 **(203,000)**	21.1 **(69'3")**	5900 **(13,200)**

*Lift at maximum reach over front at 3 m **(10 ft)** elevation from stick pin, no tool.



LOGGING AND FOREST PRODUCT MACHINES

Model	Product Ident. No. Prefix	Years Built	Flywheel Power kW (hp)	Overall Track Length m (ft)	Overall Length m (ft)	Overall Width m (ft)	Operating Weight kg (lb)
320B Stroke Delimber	9JS	—	96 **(128)**	—	11.96 **(39'3")**	3.66 **(12'0")**	30 390 **(67,000)**
FB221	8XD	1986	147 **(197)**	4.47 **(14'8")**	9.78 **(32'1")**	3.20 **(10'6")**	28 180 **(62,000)**
FB227	10W	1983-93	100/134 **(135/180)**	4.55 **(14'11")**	11.88 **(39'0")**	3.35 **(11'0")**	31 769 **(69,892)**
DL221	8YD	1987	98 **(132)**	4.47 **(14'8")**	—	—	22 816 **(50,300)**
LL216	8JD	1986	95 **(128)**	—	10.70 to 11.23 **(35'1" to 36'10")**	2.64 **(8'8")**	17 577 **(38,750)**
LL228	8MD	1986	131 **(176)**	—	9.7 to 11.6 **(32'0" to 38'0")**	2.62 **(8'7")**	30 391 **(67,000)**
LL231	8PD	1986	175 **(235)**	5.03 **(16'6")**	10.6 to 11.6 **(35'0" to 38'0")**	3.56 **(11'8")**	39 146 **(86,300)**
320B LL	6LS/9JS	96-01	96 **(128)**	4.48 **(14'8")**	—	3.29 **(10'10")**	28 610 **(63,100)**
320C LL	BGB/BKK	01-03	96 **(128)**	4.5 **(14'8")**	—	3.3 **(10'10")**	25 900 **(57,100)**
320C LL	SAH/TBR	02-07	103 **(138)**	4.6 **(14'9")**	—	3.3 **(10'10")**	27 200 **(59,965)**
320D LL	GKS	07-14	110 **(147)**	4.6 **(14'9")**	—	3.3 **(10'10")**	30 300 **(66,812)**
320D GF	BZF/EAX	06-14	110 **(147)**	4.6 **(14'9")**	—	3.3 **(10'10")**	26 900 **(59,315)**
322B LL	1YS	96-02	114 **(153)**	4.66 **(15'3")**	—	3.72 **(12'3")**	32 970 **(72,686)**
322C FM GF (HD/LC)	BPH	01-06	125 **(168)**	4.66 **(15'4")**	9.96 **(32'8")**	3.29 **(10'10")**	28 229 **(62,245)***
322C FM GF (HW)	CAM	01-06	125 **(168)**	4.69 **(15'5")**	9.91 **(32'6")**	3.62 **(11'11")**	30 710 **(67,716)***
322C FM LL (U/U)	CBY	01-06	125 **(168)**	4.69 **(15'5")**	14.10 **(46'3")**	3.62 **(11'11")**	33 607 **(74,103)***
322C FM LL (O/U)	CBY	01-06	125 **(168)**	4.69 **(15'5")**	15 **(49'3")**	3.62 **(11'11")**	33 896 **(74,741)***

*Operating Weight without bucket or grapple and with the new FM Cab/Riser with integrated guarding (available in July 2004).

Logging and Forest Product Machines (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Power kW (hp)	Overall Track Length m (ft)	Overall Length m (ft)	Overall Width m (ft)	Operating Weight kg (lb)
324D FM LGP	JGK	07-10	140 **(188)**	4.7 **(15.3)**	13 **(42.7)**	3.62 **(11.9)**	32 886 **(72,500)**
325B LL	2JR	96-01	124 **(166)**	4.66 **(15'3")**	—	3.62 **(11'11")**	36 916 **(81,400)**
325C FM GF (HD/LC)	G1L	02-06	140 **(188)**	4.70 **(15'5")**	10.34 **(33'11")**	3.44 **(11'3")**	31 942 **(70,432)***
325C FM GF (HW)	M2K	02-06	140 **(188)**	4.70 **(15'5")**	10.29 **(33'9")**	3.62 **(11'11")**	33 078 **(72,937)***
325C FM LL (U/U)	S3M	02-06	140 **(188)**	4.70 **(15'5")**	14.87 **(48'9")**	3.62 **(11'11")**	37 644 **(83,005)***
325C FM LL (O/U)	S3M	02-06	140 **(188)**	4.70 **(15'5")**	15.75 **(51'8")**	3.62 **(11'11")**	38 219 **(84,273)***
330B LL	6DR	96-02	160 **(214)**	5.02 **(16'6")**	—	3.62 **(11'11")**	44 172 **(97,400)**
330C FM GF (HD/LC)	B3M	02-06	184 **(247)**	5.08 **(16'8")**	11.19 **(36'9")**	3.52 **(11'6")**	39 347 **(86,760)***
330C FM GF (HW)	B4N	02-06	184 **(247)**	5.07 **(16'7")**	11.19 **(36'9")**	3.62 **(11'11")**	40 778 **(89,915)***
330C FM LL (U/U)	B1K	02-06	184 **(247)**	5.07 **(16'7")**	16.67 **(54'8")**	3.62 **(11'11")**	44 430 **(97,968)***
330C FM LL (O/U)	B1K	02-06	184 **(247)**	5.07 **(16'7")**	17.36 **(57'0")**	3.62 **(11'11")**	44 965 **(99,148)***
330D FM GF	L2K	06-10	200 **(268)**	5.06 **(16'7")**	111.15 **(36'7")**	3.65 **(11'11")**	41 426 **(91,344)**
330D FM LL (U/U)	H3K	06-10	200 **(268)**	5.06 **(16'7")**	166.3 **(54'7")**	3.65 **(11'11")**	45 801 **(100,991)**
330D FM LL (O/U)	H3K	06-10	200 **(268)**	5.06 **(16'7")**	173.2 **(56'10")**	3.65 **(11'11")**	46 261 **(102,005)**

*Operating Weight without bucket or grapple and with the new FM Cab/Riser with integrated guarding (available in July 2004).



WHEEL SKIDDERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower kW (hp)	Operating Weight kg (lb)	Ground Clearance mm (in)	Wheel Base m (ft/in)
508 Cable	9NC	87-89	71 **(95)**	7770 **(17,130)**	521 **(20.5)**	2.8 **(9'2")**
508 Grapple	2HD	87-89	71 **(95)**	8766 **(19,308)**	521 **(20.5)**	2.8 **(9'2")**
518 FB	8ZC	86-89	96 **(130)**	11 612 **(25,600)**	587 **(23.1)**	3.25 **(10'8")**
518 PS Cable	50S	71-83	90 **(120)**	7718 **(17,000)**	505.4 **(19.8976)**	2895.6 **(9'6")**
518 PS Grapple	55U	1-80/81-83	90/97 **(120/130)**	9307 **(20,500)**	505.4 **(19.8976)**	2895.6 **(9'6")**
518 Cable	94U	3-84/85-92	90/97 **(120/130)**	9988 **(22,000)**	470 **(18.5039)**	3251 **(10'8.4")**
518 Grapple	95U	81-90	97 **(130)**	11 259 **(24,800)**	470 **(18.5039)**	3251 **(10'8.4")**
518 Series II Cable	94U	91-92	dual 97/108 **dual (130/145)**	10 260 **(22,600)**	470 **(18.5039)**	3251 **(10'8.4")**
518 Series II Grapple	95U	91-92	dual 97/108 **dual (130/145)**	12 031 **(26,500)**	470 **(18.5039)**	3251 **(10'8.4")**
518C Cable	1CL	93-95	115 **(154)**	11 528 **(25,391)**	450.7 **(17.74406)**	3251 **(10'8.4")**
518C Grapple	9HJ	93-95	115 **(154)**	12 587 **(27,725)**	463.4 **(18.24406)**	3251 **(10'8.4")**
525	—	—	119 **(160)**	13 558 **(29,891)**	527 **(20.7)**	3.5 **(11.5)**
525B	—	02-06	119 **(160)**	18 325 **(40,400)**	463 **(18.2)**	3.5 **(11.5)**
525C	—	06-14	146 **(196)**	17 711 **(39,045)**	581 **(22.9)**	3534 **(11'7")**
535B	—	6-Feb	134 **(180)**	19 006 **(41,900)**	463 **(18.2)**	3.5 **(11.5)**
535C	—	06-14	162 **(218)**	18 044 **(39,780)**	581 **(22.9)**	3534 **(11'7")**
545 Grapple	—	6-Feb	149.1 **(225)**	20 230 **(44,600)**	606.4 **(23.9)**	3.8 **(12.5)**
545C	—	06-14	173 **(232)**	19 198 **(42,325)**	581 **(22.9)**	3939 **(12'11")**



TRACK SKIDDERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower kW (hp)	Operating Weight kg (lb)	Gauge m (ft/in)
D4TSK Series II	8ZF	90-92	78 **(105)**	12 909 **(28,400)**	2.00 **(6'6")**
D4TSK Series III	7PK	92-96	78 **(105)**	14 000 **(30,900)**	2.00 **(6'6")**
D5HTSK Series II	7EG	92-96	97 **(130)**	18 800 **(41,360)**	2.16 **(7'11")**



TRACK FELLER BUNCHERS

Model	Product Ident. No. Prefix	Years Built	Gross Power kW (hp)	Overall Track Length m (ft)	Overall Length m (ft)	Overall Width m (ft)	Operating Weight kg (lb)
511	511	06-12	184.2 **(247)**	4.6 **(15.0)**	8.5 **(27.7)**	3.2 **(10.5)**	24 362 **(53,710)**
521	521	06-12	211.8 **(284)**	4.8 **(15.8)**	8.6 **(28.3)**	3.2 **(10.5)**	27 084 **(59,710)**
522	522	06-12	211.8 **(284)**	4.8 **(15.8)**	8.6 **(28.3)**	3.5 **(11.4)**	30 410 **(67,040)**
532	532	06-12	211.8 **(284)**	4.9 **(16.1)**	8.6 **(28.3)**	3.5 **(11.4)**	31 620 **(69,710)**
541	541	06-11	227.4 **(305)**	4.9 **(16.1)**	9.4 **(30.9)**	3.6 **(11.8)**	30 191 **(66,560)**
551	551	06-11	227.4 **(305)**	4.9 **(16.1)**	9.4 **(30.9)**	3.6 **(11.8)**	31 057 **(68,468)**
552	552	06-11	227.4 **(305)**	4.9 **(16.1)**	9.4 **(30.9)**	3.6 **(11.8)**	35 680 **(78,660)**



FORWARDERS

Model	Product Ident. No. Prefix	Years Built	Number of Wheels	Engine	Gross Power kW (hp)	Operating Weight kg (lb)	Load Capacity kg (lb)	Transmission	Std. Wheel Base mm (in)
534	HF	06-11	4	C4.4 ACERT	93 **(125)**	12 247 **(27,000)**	7258 **(16,000)**	Electric Powershift	3835 **(151)**
544	HF	06-11	6	C4.4 ACERT	93 **(125)**	14 062 **(31,000)**	10 866 **(24,000)**	Electric Powershift	5334 **(210)**
584	PAK	09-14	8	C7 ACERT	204 **(274)**	22 498 **(49,600)**	18 000 **(39,683)**	2 Speed Hydrostatic	6096 **(240)**



TRACK HARVESTER

Model	Product Ident. No. Prefix	Years Built	Engine	Gross Power kW (hp)	Track Pitch mm (in)	Overall Height m (ft)	Overall Width m (ft)	Operating Weight kg (lb)
501	PH	06-12	C6.6 ACERT	122 **(163)**	171.4 **(6.7)**	3.33 **(11.9)**	2.59 **(8.5)**	15 900 **(35,000)**



WHEEL HARVESTER

Model	Product Ident. No. Prefix	Years Built	Number of Wheels	Engine	Gross Power kW (hp)	Transmission	Boom Reach m (ft)	Std. Wheel Base mm (in)	Operating Weight kg (lb)
550	PH	06-13	6	C7 ACERT	147 **(197)**	Hydrostatic	8.2 **(27)**	4160 **(164)**	21 319 **(47,040)**



BACKHOE LOADERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower kW (hp)	Operating Weight kg (lb)	Digging Depth mm (ft/in)	GP Bucket Capacity m^3 (yd^3)	MP Bucket Capacity m^3 (yd^3)
416	5PC	85-90	46	6156	4420	0.76	0.76
			(62)	**(13,574)**	**(14'6")**	**(1.0)**	**(1.0)**
416 Series II	5PC	90-92	46	6217	4420	0.76	0.76
			(62)	**(13,708)**	**(14'6")**	**(1.0)**	**(1.0)**
416B	8ZK(8SG)	92-95	59	6227	4420	0.76	0.96
			(79)	**(13,700)**	**(14'6")**	**(1.0)**	**(1.25)**
416C	4ZN(5YN)	96-00	56	6330	4420	0.76	0.96
			(75)	**(13,957)**	**(14'6")**	**(1.0)**	**(1.25)**
416C (IT)	1WR(1XR)	96-00	56	6666	4420	0.96	0.96
			(75)	**(14,698)**	**(14'6")**	**(1.25)**	**(1.25)**
416D	BFP, BKG, BGJ, CXP	00-05	58	6900	4390	0.76	0.96
			(78)	**(15,257)**	**(14'5")**	**(1.0)**	**(1.25)**
420D	FDP, BKC	00-05	69	7150	4390	0.96	0.96
			(93)	**(15,772)**	**(14'5")**	**(1.25)**	**(1.25)**
420D (IT)	BLN, BMC, MBH	00-05	69	7150	4390	0.96	0.96
			(93)	**(15,772)**	**(14'5")**	**(1.25)**	**(1.25)**
424D	RXA, CJZ	01-05	56	7502	4854	1.0	0.96
			(75)	**(16,539)**	**(15'9")**	**(1.31)**	**(1.25)**
426	7BC	86-90	52	6549	4720	0.96	0.76
			(70)	**(14,626)**	**(15'6")**	**(1.25)**	**(1.0)**
426 Series II	7BC	90-92	52	7315	4720	0.96	0.76
			(70)	**(15,126)**	**(15'6")**	**(1.25)**	**(1.0)**
426B	6KL(5YJ)	92-95	59	6790	4720	0.96	0.96
			(79)	**(14,970)**	**(15'6")**	**(1.25)**	**(1.25)**
426C	6XN(7WN)	96-98	60	7051	4721	0.96	0.96
			(80)	**(15,548)**	**(15'6")**	**(1.25)**	**(1.25)**
426C	6XN3616 and up (7WN939 and up)	99-00	63	7051	4721	0.96	0.96
			(85)	**(15,548)**	**(15'6")**	**(1.25)**	**(1.25)**
(AWS) 426C	1CR(1ER)	96-98	60	7051	4721	0.96	0.96
			(80)	**(15,548)**	**(15'6")**	**(1.25)**	**(1.25)**
(AWS) 426C	1CR864 and up (1ER864 and up)	99-00	63	7051	4721	0.96	0.96
			(85)	**(15,548)**	**(15'6")**	**(1.25)**	**(1.25)**
426C (IT)	1YR(1ZR)	96-98	60	7387	4721	0.96	0.96
			(80)	**(16,289)**	**(15'6")**	**(1.25)**	**(1.25)**
426C (IT)	1YR1517 and up (1ZR926 and up)	99-00	63	7387	4721	0.96	0.96
			(85)	**(16,289)**	**(15'6")**	**(1.25)**	**(1.25)**
(AWS) 426C (IT)	1MR(1NR)	96-98	60	7387	4721	0.96	0.96
			(80)	**(16,289)**	**(15'6")**	**(1.25)**	**(1.25)**
(AWS) 426C (IT)	1MR956 and up (1NR954 and up)	99-00	63	7387	4721	0.96	0.96
			(85)	**(16,289)**	**(15'6")**	**(1.25)**	**(1.25)**

Backhoe Loaders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower kW (hp)	Operating Weight kg (lb)	Digging Depth mm (ft/in)	GP Bucket Capacity m^3 (yd^3)	MP Bucket Capacity m^3 (yd^3)
428	6TC	86-90	52 **(70)**	6963 **(15,350)**	4790 **(15'9")**	1.0 **(1.31)**	0.92 **(1.2)**
428 Series II	6TC	90-92	52 **(70)**	7143 **(15,750)**	4750 **(15'7")**	1.0 **(1.31)**	0.92 **(1.2)**
428B	7EJ	92-95	60 **(80)**	7254 **(15,992)**	4810 **(15'9")**	1.0 **(1.31)**	0.92 **(1.2)**
428C	8RN	96-00	56 **(75)**	7279 **(16,047)**	4811 **(15'9")**	1.0 **(1.31)**	1.03 **(1.35)**
428C (IT)	2CR	96-00	56 **(75)**	7615 **(16,788)**	4811 **(15'9")**	1.0 **(1.31)**	1.03 **(1.35)**
428D	DSX, BXC, MBM	01-05	61 **(82)**	7738 **(17,059)**	4854 **(15'9")**	1.0 **(1.31)**	1.03 **(1.35)**
430D	BNK	00-05	75 **(101)**	7355 **(16,217)**	4639 **(15'3")**	1.0 **(1.31)**	0.96 **(1.25)**
430D (IT)	BML	00-05	75 **(101)**	7355 **(16,217)**	4639 **(15'3")**	1.0 **(1.31)**	0.96 **(1.25)**
432D	TDR, WEP	01-05	69 **(93)**	7809 **(17,216)**	4854 **(15'9")**	1.0 **(1.31)**	1.03 **(1.35)**
436	5KF	88-90	57 **(77)**	6831 **(15,062)**	4960 **(16'3")**	0.76 **(1.0)**	0.76 **(1.0)**
436 Series II	5KF	90-92	57 **(77)**	6878 **(15,166)**	4950 **(16'3")**	0.76 **(1.0)**	0.76 **(1.0)**
436B	7FL(6MJ)	92-95	63 **(84)**	6857 **(15,086)**	4950 **(16'3")**	0.96 **(1.25)**	0.96 **(1.25)**
436C	8TN(9JN)	96-98	63 **(85)**	7118 **(15,694)**	4953 **(16'3")**	1.0 **(1.31)**	0.96 **(1.25)**
436C	8TN925 and up (9JN884 and up)	99-00	70 **(93)**	7118 **(15,694)**	4953 **(16'3")**	1.0 **(1.31)**	0.96 **(1.25)**
(AWS) 436C	1FR(1GR)	96-98	63 **(85)**	7118 **(15,694)**	4953 **(16'3")**	1.0 **(1.31)**	0.96 **(1.25)**
(AWS) 436C	1FR1416 and up (1GR916 and up)	99-00	70 **(93)**	7118 **(15,694)**	4953 **(16'3")**	1.0 **(1.31)**	0.96 **(1.25)**
436C (IT)	2AR(2BR)	96-98	63 **(85)**	7454 **(16,435)**	4953 **(16'3")**	1.0 **(1.31)**	0.96 **(1.25)**
436C (IT)	2AR1604 and up (2BR911 and up)	99-00	70 **(93)**	7454 **(16,435)**	4953 **(16'3")**	1.0 **(1.31)**	0.96 **(1.25)**
(AWS) 436C (IT)	1PR(1RR)	96-98	63 **(85)**	7454 **(16,435)**	4953 **(16'3")**	1.0 **(1.31)**	0.96 **(1.25)**
(AWS) 436C (IT)	1PR1599 and up (1RR998 and up)	99-00	70 **(93)**	7454 **(16,435)**	4953 **(16'3")**	1.0 **(1.31)**	0.96 **(1.25)**

Backhoe Loaders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower kW (hp)	Operating Weight kg (lb)	Digging Depth mm (ft/in)	GP Bucket Capacity m^3 (yd^3)	MP Bucket Capacity m^3 (yd^3)
438	3DJ	88-90	63	7900	4810	1.0	0.92
			(84)	**(17,420)**	**(15'9")**	**(1.31)**	**(1.2)**
438 Series II	3DJ	90-92	57	7364	4810	1.0	0.92
			(77)	**(16,237)**	**(15'9")**	**(1.31)**	**(1.2)**
438B	3KK	92-95	62.7	8331	4870	1.0	0.92
			(84)	**(18,367)**	**(16'0")**	**(1.31)**	**(1.2)**
438C	9KN	96-98	63	7384	4873	1.0	1.03
			(85)	**(16,279)**	**(16'0")**	**(1.31)**	**(1.35)**
438C	9KN1061 and up	99-00	70	7384	4873	1.0	1.03
			(93)	**(16,279)**	**(16'0")**	**(1.31)**	**(1.35)**
(AWS) 438C	1JR	96-98	63	7384	4873	1.0	1.03
			(85)	**(16,279)**	**(16'0")**	**(1.31)**	**(1.35)**
(AWS) 438C	1JR1107 and up	99-00	70	7384	4873	1.0	1.03
			(93)	**(16,279)**	**(16'0")**	**(1.31)**	**(1.35)**
438C (IT)	2DR	96-98	63	7720	4873	1.0	1.03
			(85)	**(17,020)**	**(16'0")**	**(1.31)**	**(1.35)**
438C (IT)	2DR2717 and up	99-00	70	7720	4873	1.0	1.03
			(93)	**(17,020)**	**(16'0")**	**(1.31)**	**(1.35)**
(AWS) 438C (IT)	1TR	96-98	63	7720	4873	1.0	1.03
			(85)	**(17,020)**	**(16'0")**	**(1.31)**	**(1.35)**
(AWS) 438C (IT)	1TR1284 and up	99-00	70	7720	4873	1.0	1.03
			(93)	**(17,020)**	**(16'0")**	**(1.31)**	**(1.35)**
442D	SMJ, TBD	01-05	75	7809	4854	1.0	1.03
			(101)	**(17,216)**	**(15'9")**	**(1.31)**	**(1.35)**
446	6XF	89-95	71	8892	5220	1.15	1.10
			(95)	**(19,603)**	**(17'2")**	**(1.5)**	**(1.5)**
446B			76	8890	5220	1.15	1.05
			(102)	**(19,600)**	**(17'2")**	**(1.5)**	**(1.375)**
446D	DBL	04-06	76	8939	5142	1.15	1.25
			(102)	**(19,666)**	**(16'10")**	**(1.5)**	**(1.63)**



PIPELAYERS

Model	Tractor Product Ident. No. Prefix	Years Built	Engine HP	Approx. Weight kg (lb)	Counter-weight kg (lb)	Max. Lift Capacity 1.2 m (4'0") Overhang kg (lb)	Speed Range km/h (mph) Forward	Speed Range km/h (mph) Reverse	Ground Clearance mm (in)	Ground Contact m^2 (in^2)
MD6	9U39C	52-57	93	12 375 **(27,820)**	1590 **(3500)**	12 035 **(26,530)**	2.7—10.6 **(1.7—6.6)**	3.2—10.0 **(2.0—6.2)**	321 **(13)**	1.77 **(2744)**
561B	62A	59-66	90	14 560 **(32,100)**	2270 **(5000)**	17 500 **(38,800)**	2.7—10.6 **(1.7—6.6)**	1.8—9.9 **(2.0—6.2)**	267 **(11)**	2.02 **(3130)**
561B	62A	66-67	93	14 350 **(31,637)**	2270 **(5000)**	17 600 **(38,800)**	2.7—10.9 **(1.7—6.8)**	3.4—10.3 **(2.1—6.4)**	267 **(11)**	2.02 **(3130)**
561C	85H	66-67	93	14 700 **(32,500)**	2450 **(5400)**	18 000 **(40,000)**	2.7—11.1 **(1.7—6.9)**	3.4—10.1 **(2.1—6.3)**	395 **(16)**	2.02 **(3130)**
561C	92J	67-77	105	14 700 **(32,500)**	2450 **(5400)**	18 100 **(40,000)**	2.7—11.1 **(1.7—6.9)**	3.4—10.1 **(2.1—6.3)**	395 **(16)**	2.02 **(3130)**
561D	54X	78-89	105	15 800 **(35,000)**	2990 **(6600)**	18 100 **(40,000)**	3.5—10.1 **(2.2—6.3)**	4.2—12.2 **(2.6—7.6)**	395 **(16)**	2.02 **(3130)**
561H	6NL	93-97	105	15 700 **(34,600)**	2128 **(4690)**	18 100 **(40,000)**	3.4—10.2 **(2.1—6.4)**	4.1—12.4 **(2.6—7.7)**	363 **(14.3)**	2.67 **(4120)**
561M		01	110	16 240 **(35,800)**	3260 **(7200)**	18 100 **(40,000)**	3.3—9.9 **(2.0—6.2)**	4.0—12.1 **(2.5—7.5)**	438 **(17.2)**	2.67 **(4120)**
561M CB* (US)	1KW	97-02	110	16 240 **(35,800)**						
561N	CPH	03-08	123	16 851 **(37,150)**	3270 **(7210)**	18 145 **(40,000)**	3.1—9.1 **(1.9—5.6)**	3.8—11.3 **(2.3—6.9)**	422 **(16.6)**	2.93 **(4542)**
561N	TAD	03-08	123	16 851 **(37,150)**	3270 **(7210)**	18 145 **(40,000)**	3.1—9.1 **(1.9—5.6)**	3.8—11.3 **(2.3—6.9)**	422 **(16.6)**	2.93 **(4542)**
571E PS	64A	61-67	160	22 680 **(50,000)**	2360 **(5200)**	7 490 **(60,600)**	3.7—10.3 **(2.3—6.4)**	4.3—12.1 **(2.7—7.5)**	400 **(16)**	3.04 **(4710)**
571E PS	64A	66-72	180	23 100 **(51,000)**	2360 **(5200)**	27 500 **(60,600)**	3.7—10.1 **(2.3—6.3)**	4.3—11.9 **(2.7—7.4)**	400 **(16)**	3.04 **(4710)**
571F	95N	72-74	180	22 800 **(50,300)**	4350 **(9600)**	27 500 **(60,600)**	3.5—9.7 **(2.2—6.0)**	4.2—11.4 **(2.6—7.1)**	400 **(16)**	3.04 **(4710)**
571G	16W	75-81	200	23 040 **(50,800)**	4350 **(9600)**	27 500 **(60,600)**	3.7—10.0 **(2.3—6.2)**	4.5—11.9 **(2.8—7.9)**	399 **(15.7)**	3.04 **(4710)**
	52D(JPN)	87-96	200							
MD7	17A	51-57	140	16 200 **(35,815)**	3400 **(7500)**	24 585 **(54,200)**	2.4—9.5 **(1.5—5.9)**	2.9—8.7 **(1.8—5.4)**	394 **(16)**	3.12 **(4840)**

*Gauge 2.0 m **(6'7")**, Width 3.19 m **(10'5")**, Length 3.73 m **(12'3")**, Height 3.12 m **(10'3")**, PS Transmission.
Forward Speed: 1st gear 3.27 km/h **(2.03 mph)**
2nd gear 5.81 km/h **(3.61 mph)**
3rd gear 9.93 km/h **(6.17 mph)**

Pipelayers (cont'd)

Model	Tractor Product Ident. No. Prefix	Years Built	Engine HP	Approx. Weight kg (lb)	Counter-weight kg (lb)	Max. Lift Capacity 1.2 m (4'0") Overhang kg (lb)	Speed Range km/h (mph) Forward	Speed Range km/h (mph) Reverse	Ground Clearance mm (in)	Ground Contact m^2 (in^2)
572C	21A	57-61	128	26 200	4720	39 000	3.2—7.7	3.9—6.1	483	3.30
				(57,820)	**(10,405)**	**(86,000)**	**(2.0—4.8)**	**(2.4—3.8)**	**(19)**	**(5109)**
572D	21A	59	140	26 500	4940	39 000	4.2—9.7	4.8—7.7	483	3.30
				(58,520)	**(10,900)**	**(86,000)**	**(2.6—6.0)**	**(3.0—4.8)**	**(19)**	**(5109)**
572E PS	65A	61-69	180	28 000	6000	40 800	3.7—10.1	4.3—11.9	480	3.45
				(62,000)	**(13,000)**	**(90,000)**	**(2.3—6.3)**	**(2.7—7.4)**	**(19)**	**(5345)**
572F PS	96N	70-74	180	27 600	6440	40 800	3.5—9.7	4.2—11.4	480	3.45
				(61,000)	**(14,200)**	**(90,000)**	**(2.2—6.0)**	**(2.6—7.1)**	**(19)**	**(5345)**
572G	40U	75-86	200	27 800	6400	40 800	3.7—10.0	4.5—11.9	480	3.45
				(61,300)	**(14,200)**	**(90,000)**	**(2.3—6.2)**	**(2.8—7.4)**	**(19)**	**(5345)**
572G	8PC	84-89	200	27 800	6400	40 800	3.7—10.0	4.5—11.9	480	3.45
				(61,300)	**(14,200)**	**(90,000)**	**(2.3—6.2)**	**(2.8—7.4)**	**(19)**	**(5345)**
572R	2HZ	98-04	230	30 110	5055	40 825	3.5—11.1	4.8—14.2	414	4.19
				(66,250)	**(11,150)**	**(90,000)**	**(2.3—6.9)**	**(3.0—8.8)**	**(16.3)**	**(6500)**
578	8HB	89-97	300	46 580	11 777	70 307	3.8—10.8	4.7—13.8	452	5.17
				(102,690)	**(25,963)**	**(155,000)**	**(2.35—6.7)**	**(2.9—8.6)**	**(17.8)**	**(8020)**
583C	16A	55-58	190	35 440	8470	58 970	3.9—8.7	3.9—8.7	533	4.24
				(78,132)	**(18,676)**	**(130,000)**	**(2.4—5.4)**	**(2.4—5.4)**	**(21)**	**(6580)**
583H TC	38A	59-60	235	38 000	9030	62 140	4.5—10.3	4.5—10.3	537	4.66
				(83,840)	**(19,900)**	**(137,000)**	**(2.8—6.4)**	**(2.8—6.4)**	**(22)**	**(7220)**
583H PS	61A	60-74	191	35 600	8470	58 970	3.9—8.7	3.9—8.7	533	4.55
				(78,500)	**(18,676)**	**(130,000)**	**(2.4—5.4)**	**(2.4—5.4)**	**(21)**	**(7050)**
583H PS	61A	60-67	225	38 200	9000	62 140	4.1—11.1	4.6—12.8	537	4.66
				(84,270)	**(19,900)**	**(137,000)**	**(2.5—6.9)**	**(8.9—8.0)**	**(22)**	**(7220)**
583H PS	61A	61	235	38 900	10 400	62 140	3.9—10.1	4.8—12.6	537	4.66
				(85,720)	**(22,880)**	**(137,000)**	**(2.4—6.3)**	**(3.0—7.8)**	**(22)**	**(7220)**
583H	61A	74	270	40 600	10 300	63 500	3.9—10.5	4.8—13.0	533	4.65
				(89,500)	**(22,700)**	**(140,000)**	**(2.4—6.5)**	**(3.0—8.1)**	**(21)**	**(7220)**
583K	78V	74-89	300	40 960	7840	63 500	4.0—10.9	5.0—13.5	530	4.65
				(90,300)	**(17,290)**	**(140,000)**	**(2.5—6.8)**	**(3.1—8.4)**	**(21)**	**(7220)**
583R	2XS	98-05	228 kW	44 748	9036	63 504	3.5—10.8	4.7—3.8	537	5.10
			(305)	**(98,650)**	**(19,920)**	**(140,000)**	**(2.3—6.8)**	**(2.9—8.6)**	**(21.1)**	**(7896)**
583T	CMX	06-11	231 kW	45 359	9036	63 504	3.5-10.8	4.7-13.8	470	5.10
			(310)	**(100,000)**	**(19,920)**	**(140,000)**	**(2.3-6.8)**	**(2.9-8.6)**	**(18.5)**	**(7896)**
587R	BXL	06-11	273 kW	53 070	12 900	91 625	3.2-10.0	4.3-12.9	457	6.2
			(366)	**(117,000)**	**(28,440)**	**(202,000)**	**(2.0-6.2)**	**(2.7-8.0)**	**(18)**	**(9613)**
587T	FAT	06-11	262 kW	53 442	12 900	91 625	3.2-9.7	4.3-12.6	457	6.2
			(351)	**(117,820)**	**(28,440)**	**(202,000)**	**(2.0-6.0)**	**(2.7-7.8)**	**(18)**	**(9613)**
589	31Z	82-06	313 kW	65 366	11 854	104 330	3.5—10.9	4.3—13.7	625	6.96
			(420)	**(151,212)**	**(26,134)**	**(230,000)**	**(2.2—6.8)**	**(2.7—8.5)**	**(24.6)**	**(12,148)**
594	62H	74	385	55 400	12 600	90 700	3.9—10.5	4.8—12.7	640	5.72
				(122,000)	**(27,800)**	**(200,000)**	**(2.4—6.5)**	**(3.0—7.9)**	**(25)**	**(8865)**
594H	96V	74-82	410	56 065	12 555	90 700	4.0—10.8	5.0—13.2	630	6.48
				(123,600)	**(27,680)**	**(200,000)**	**(2.5—6.7)**	**(3.1—8.2)**	**(25)**	**(10,050)**



WHEEL TRACTOR-SCRAPERS

Model	Product Ident. No. Prefix	Years Built	Horse-power Max/ Rated	Capacity Struck/ Heaped m^3 (yd^3)	Approx. Shipping Weight kg (lb)	Dimensions m (ft) Length	Width	Height	Width of Tread	Tire Size (Standard) & ply rating Tractor & Scraper	Turning Circle m (ft)
DW10 Tractor	1N	41-46	100/*	—	6550	4.57	2.24	1.93	1.73	10.0 × 20-12	—
					(14,350)	**(15'0")**	**(7'4")**	**(6'4")**	**(5'8")**	18.0 × 24-16	
DW10 Tractor	6V	46-47	100/*	—	6850	4.57	2.24	1.93	1.73	10.0 × 20-12	—
					(15,100)	**(15'0")**	**(7'4")**	**(6'4")**	**(5'8")**	18.0 × 24-16	
DW10 Tractor	1V	47-53	115/*	—	7540	4.70	2.34	1.93	1.79	12.0 × 20-14	—
					(16,610)	**(15'5")**	**(7'8")**	**(6'4")**	**(5'10")**	21.0 × 25-20	
DW10 &	1V	47-51	115/*	6.7/8.4	15 980	11.23	3.02	2.69	1.88	12.0 × 20-14	7.92
No. 10 Scraper	3C			**(8.7/11)**	**(35,240)**	**(37'0")**	**(9'11")**	**(8'10")**	**(6'2")**	21.0 × 25-20	**(26'0")**
DW10 &	1V	52-53	115/*	5.3/6.9	15 130	10.72	2.87	2.36	1.80	12.0 × 20-14	11.23
No. 10 Scraper	19C			**(7/9)**	**(33,365)**	**(35'2")**	**(9'5")**	**(7'9")**	**(5'11")**	21.0 × 25-20	**(37'0")**
									Scraper	16.0 × 21-20	
DW15 &	45C	54-55	/150	5.3/6.9	15 960	11.10	2.87	2.36	1.80	12.0 × 20-14	10.36
No. 10 Scraper	19C			**(7/9)**	**(35,180)**	**(36'5")**	**(9'5")**	**(7'9")**	**(5'11")**	21.0 × 25-20	**(34'0")**
									Scraper	16.0 × 21-20	
DW15 &	45C	54-55	/150	7.7/9.2	9400	11.84	3.18	2.69	1.93	12.0 × 20-14	11.23
No. 15 Scraper	4W			**(10/12)**	**(20,720)**	**(38'10")**	**(10'5")**	**(8'10")**	**(6'4")**	21.0 × 25-20	**(37'0")**
DW15 Tractor	45C	54-55	/150	—	9510	5.08	2.39	2.69	1.98	12.0 × 20-14	—
					(20,960)	**(16'8")**	**(7'10")**	**(8'10")**	**(6'6")**	21.0 × 25-20	
DW15C &	59C or 70C	55-57	186/*	7.7/9.5	19 220	11.84	3.18	2.69	1.98	12.0 × 12-14	10.36
No. 15 Scraper				**(10/12.5)**	**(42,370)**	**(38'10")**	**(10'5")**	**(8'10")**	**(6'6")**	21.0 × 25-20	**(34'0")**
DW15E &	75D or 76D	57-59	200/172	10/14	20 280	12.22	3.30	3.05	1.98	12.0 × 20-14	—
No. 428 Scraper				**(13/18)**	**(44,711)**	**(40'1")**	**(10'10")**	**(10'0")**	**(6'6")**	26.5 × 25-20	
DW15F &	75D or 76D	58-59	200/172	10/14	20 280	12.22	3.30	3.05	1.98	12.0 × 20-14	—
No. 428 Scraper				**(13/18)**	**(44,711)**	**(40'1")**	**(10'10")**	**(10'0")**	**(6'6")**	26.5 × 25-20	
DW20 &	21C	51-55	225/*	14/7.6	12 750	13.23	3.53	3.10	2.29	24.0 × 29-4	11.23
No. 20 Scraper	11C			**(18/23)**	**(28,100)**	**(43'5")**	**(11'7")**	**(10'2")**	**(7'6")**		**(37'0")**
DW20 Tractor	6W	51-55	225/*	—	11 620	5.39	2.79	2.41	2.18	14.0 × 24-16	—
(For W20 Wagon)					**(25,610)**	**(17'8")**	**(9'2")**	**(7'11")**	**(7'2")**	24.0 × 29-24	
DW20E &	57C	55-57	300/*	14/19	26 040	13.36	3.58	3.45	2.24	14.0 × 24-16	11.58
No. 456 Scraper	67C			**(18/25)**	**(57,400)**	**(43'10")**	**(11'9")**	**(11'4")**	**(7'4")**	29.5 × 29-22	**(38'0")**
DW20F &	87E	58-60	320/*	14/19	26 870	13.36	3.58	3.45	2.24	14.0 × 24-16	11.58
No. 456 Scraper	88E			**(18/25)**	**(59,240)**	**(43'10")**	**(11'9")**	**(11'4")**	**(7'4")**	29.5 × 29-22	**(38'0")**
DW20G &	87E	58-60	345/*	15/21	27 200	13.36	3.58	3.45	2.24	14.0 × 24-16	11.58
No. 456 Scraper	88E			**(19.5/27)**	**(59,960)**	**(43'10")**	**(11'9")**	**(11'4")**	**(7'4")**	29.5 × 29-28	**(38'0")**
DW20G &	87E	58-60	345/*	18.5/26	31 070	14.05	3.91	3.81	2.39	14.0 × 24-16	11.58
No. 482 Scraper	88E			**(24/34)**	**(68,500)**	**(46'1")**	**(12'10")**	**(12'6")**	**(7'10")**	29.5 × 29-28	**(38'0")**

*Maximum HP only available.

Wheel Tractor-Scrapers (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power Max/ Rated	Capacity Struck/ Heaped m^3 (yd^3)	Approx. Shipping Weight kg (lb)	Dimensions m (ft) Length	Width	Height	Width of Tread	Tire Size (Standard) & ply rating Tractor & Scraper	Turning Circle m (ft)
DW21 &	8W	51-55	225/*	11.5/15	24 790	12.37	3.53	3.28	2.13	24.0 × 29-24	10.67
No. 21 Scraper	8			(15/20)	(54,650)	(40'7")	(11'7")	(10'9")	(7'0")		(35'0")
DW21C &	58C	55-58	300/*	14/19	26 610	12.67	3.58	3.35	2.24	29.5 × 29-22	11.00
No. 470 Scraper	69C			(18/25)	(58,670)	(41'7")	(11'9")	(11'0")	(7'4")		(36'0")
DW21D &	85E	58-58	320/*	14/19	26 310	12.78	3.58	3.35	2.24	29.5 × 29-22	11.00
No. 470 Scraper	86E			(18/25)	(58,010)	(41'11")	(11'9")	(11'0")	(7'4")		(36'0")
DW21G &	85E	58-60	345/*	14.9/20.6	27 210	12.78	3.58	3.48	2.24	29.5 × 29-28	11.00
No. 470 Scraper	86E			(19.5/27)	(59,980)	(41'11")	(11'9")	(11'5")	(7'4")		(36'0")
611	6SZ	99-03	265	11	23 900	12.02	3.27	3.24	2.06	29.5R25	10.2
				(15)	(52,640)	(39'5")	(10'9")	(10'8")	(6'9")		(33'5")
613A	71M	69-76	/150	8.4	13 334	9.67	2.44	2.85	1.89	18.0 × 25-12	9.04
				(11)	(29,395)	(31'9")	(8'0")	(9'4.5")	(6'2.5")		(29'8")
613B	38W	76-84	/150	8.4	14 155	9.78	2.44	2.85	1.89	18.0 × 25-12	8.94
				(11)	(31,210)	(32'1")	(8'0")	(9'4.5")	(6'2.5")		(29'4")
613C		84-93	175	8.4	14 670	10.0	2.44	3.06	1.89	18.00-25,	8.9
				(11)	(32,340)	(32'9")	(8'0")	(10'0")	(6'2.5")	16 PR (E-2)	(29'4")
613C Series II	8LJ	93-08	175	6.8/8.4	15 264	10.14	2.44	3.01	1.80	23.5R25★	9.0
				(8.9/11)	(33,650)	(33'3")	(8'0")	(9'10")	(5'11")		(29'6")
613G	ESB	08-10	181	6.8/8.4	16 887	10.41	2.43	3.01	1.80	23.5R25★	9.0
				(8.9/11)	(37,229)	(34'2")	(8'0")	(9'11")	(5'11")		(29'6")
615	46Z	81-87	/250	12.23	23 400	11.6	3.048	3.590	2.21	26.5-25,	9.63
				(16)	(51,590)	(38'1")	(10'0")	(11'8")	(7'3")	26 PR (E-2)	(31'7")
615C		87-93	265	12.23	23 860	11.6	3.048	3.59	2.21	26.5-25,	9.63
				(16)	(52,600)	(38'1")	(10'0")	(11'9")	(7'3")	26 PR (E-2)	(31'7")
615C Series II	9XG	93-08	265	11/13	25 605	11.6	3.05	3.5	2.1	29.5R25★	10.8
				(14/17)	(56,450)	(38'1")	(10'0")	(11'0")	(6'9")		(35'6")
619B DD	89E	59-60	/225							Turbocharged, Electric start	
DD	90E									Turbocharged, Gas start	
619C PS	61F	60-66	280/250	10.8/14	21 550	11.05	3.30	3.76	2.00	26.5 × 29-22	9.14
DD	62F			(14/18)	(47,500)	(36'3")	(10'11")	(12'2")	(6'7")		(30'0")
619**	43F	64-65	/250	15.3/12.6	27 400	11.89	3.60	3.45	2.30	26.5 × 29-26	10.20
				(20/16.5)	(60,390)	(40'0")	(11'10")	(11'4")	(7'7")		(33'6")
621	43H	65-72	/300	10.7/15.3	28 400	12.00	3.60	3.45	2.19	29.5 × 29-22	11.50
				(14/20)	(62,600)	(39'5")	(11'10")	(11'4")	(7'3")		(37'8")
621	23H	65-74	/300	10.7/15.3	24 900	11.60	3.50	3.40	2.10	29.5 × 29-22	13.00
				(14/20)	(55,000)	(38'1")	(11'7")	(11'2")	(6'10")		(42'6")
621B	45P	73-86	/330	10.7/15.3	30 205	12.7	3.45	3.63	2.21	29.5-29,	11.10
				(14/20)	(66,590)	(41'7")	(11'4")	(11'11")	(7'3")	28 PR (E-3)	(36'6")
621E	6AB	86-93	/330	10.7/15.3	30 480	12.93	3.47	3.71	2.21	33.25-29,	10.9
	2PD			(14/20)	(67,195)	(42'5")	(11'4")	(12'2")	(7'3")	26 PR (E-3)	(35'8")

*Maximum HP only available.
**Johnson Manufacturing Company built the J619 Elevating Scraper for Caterpillar in 1964.

Wheel Tractor-Scrapers (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power Max/ Rated	Capacity Struck/ Heaped m^3 (yd^3)	Approx. Shipping Weight kg (lb)	Dimensions m (ft)				Tire Size (Standard) & ply rating Tractor & Scraper	Turning Circle m (ft)
						Length	Width	Height	Width of Tread		
621F	4SK	93-00	330	10.7/15.3 **(14/20)**	32 090 **(70,740)**	12.93 **(42'5")**	3.47 **(11'4")**	3.71 **(12'2")**	2.21 **(7'3")**	33.25-29 ★★ (E-2/E-3)	10.2 **(33'5")**
621G	ALP	00-03	330/365	10.7/15.3 **(14/20)**	32 250 **(71,090)**	12.93 **(42'5")**	3.47 **(11'4")**	3.71 **(12'2")**	2.20 **(7'3")**	33.25R29	11.7 **(38'5")**
621G	CEN	03-05	330/365	12/17 **(15.7/22)**	32 563 **(71,790)**	12.93 **(42'5")**	3.47 **(11'4")**	3.71 **(12'2")**	2.20 **(7'3")**	33.25R29	11.7 **(38'5")**
621G	DBB	05-10	330/365	12/17 **(15.7/22)**	33 995 **(74,946)**	12.88 **(42'3")**	3.58 **(11'9")**	3.71 **(12'3")**	2.23 **(7'4")** Tractor 2.20 **(7'3")** Scraper	33.25R29 ★★ (E-3)	11.7 **(38'5")**
621H	DBK EAZ	10-13	407	13/18.4 **(17.1/24)**	36 185 **(79,787)**	14.02 **(45'10")**	3.57 **(11'7")**	4.03 **(13'2")**	2.29 **(7'5")** Tractor 2.28 **(7'4")** Scraper	33.25R29 ★★ (E-3)	11.8 **(38'7")**
623	52U	72-74	/300	16.8 **(22)**	29 900 **(66,000)**	11.90 **(39'0")**	3.50 **(11'7")**	3.70 **(12'1")**	2.20 **(7'3")**	29.5 × 29-28	13.70 **(44'11")**
623B	46P	73-86	/330	16.8 **(22)**	32 546 **(71,750)**	12.5 **(41'1")**	3.55 **(11'8")**	3.81 **(12'6")**	2.18 **(7'2")**	29.5-29, 28 PR (E-2)	8.90 **(29'4")**
623E	6CB	86-89	/330	16.8 **(22)**	33 317 **(73,450)**	12.61 **(41'4")**	3.55 **(11'8")**	3.81 **(12'6")**	2.21 **(7'3")**	29.5-29, 34 PR (E-2)	10.9 **(35'9")**
623E	6YF	89-93	/365	13.8/17.6 **(18/23)**	35 290 **(77,800)**	12.61 **(41'4")**	3.55 **(11'8")**	3.94 **(12'11")**	2.18 **(7'2")**	29.5R25	10.9 **(35'8")**
623F	6BK	93-98	365	13.8/17.6 **(18/23)**	35 305 **(77,830)**	12.61 **(41'4")**	3.55 **(11'8")**	3.94 **(12'11")**	2.18 **(7'2")**	29.5-29, 34 PR (E-2)	10.9 **(35'8")**
623F Series II	5EW	98-00	365	13.8/17.6 **(18/23)**	37 122 **(81,840)**	13.28 **(43'7")**	3.55 **(11'8")**	3.55 **(11'8")**	2.21 **(7'3")**	33.25-R29 ★★ (E-2)	8.6 **(28'5")**
623G	ARW	00-02	330/365	13.8/17.6 **(18/23)**	37 120 **(81,840)**	13.21 **(43'4")**	3.55 **(11'8")**	3.68 **(12'1")**	2.2 **(7'3")**	33.25R29	10.9 **(35'8")**
623G	CES	03-05	330/365	13.8/17.6 **(18/23)**	37 120 **(81,840)**	13.21 **(43'4")**	3.55 **(11'8")**	3.68 **(12'1")**	2.2 **(7'3")**	33.25R29	10.9 **(35'8")**
623G	DBC	05-10	330/365	13.8/17.6 **(18/23)**	37 510 **(82,695)**	13.17 **(43'2")**	3.58 **(11'9")**	3.71 **(12'3")**	2.23 **(7'4")** Tractor 2.20 **(7'3")** Scraper	33.25R29 ★★ (E-3)	12.0 **(39'4")**
623H	DBF EJD	10-13	407	14.4/17.6 **(18.8/23)**	39 937 **(88,061)**	13.77 **(45'2")**	3.57 **(11'7")**	3.77 **(12'3")**	2.29 **(7'5")** Tractor 2.28 **(7'4")** Scraper	33.25R29 ★★ (E-3)	11.8 **(38'7")**

Wheel Tractor-Scrapers (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power Max/ Rated	Capacity Struck/ Heaped m^3 (yd^3)	Approx. Shipping Weight kg (lb)	Dimensions m (ft) Length	Width	Height	Width of Tread	Tire Size (Standard) & ply rating Tractor & Scraper	Turning Circle m (ft)
627	54K	68-74	T/225	10.7/15.3	29 900	12.00	3.50	3.60	2.20	29.5 × 29-28	13.30
			S/225	**(14/20)**	**(66,000)**	**(36'9")**	**(11'7")**	**(11'8")**	**(7'3")**		**(43'9")**
627B	14S	73-86	T/225	10.7/15.3	34 610	13.3	3.45	3.63	2.18	29.5-29,	11.10
			S/225	**(14/20)**	**(76,300)**	**(43'9")**	**(11'4")**	**(11'11")**	**(7'2")**	28 PR (E-3)	**(36'6")**
627E	6EB	86-90	T/225	10.7/15.3	34 670	12.89	3.47	3.71	2.21 **(7'3")**	33.25-29,	10.90
			S/225	**(14/20)**	**(76,435)**	**(42'3")**	**(11'4")**	**(12'2")**	2.18 **(7'2")**	26 PR (E-3)	**(35'9")**
627E	7CG	90-93	T/330	10.7/15.3	35 160	12.93	3.47	3.71	2.21	33.25-29,	10.9
			S/225	**(14/20)**	**(77,500)**	**(42'5")**	**(11'4")**	**(12'2")**	**(7'3")**	26 PR (E-3)	**(35'8")**
627F Series II	1DL	93-00	T/330	10.7/15.3	37 060	12.9	3.47	3.71	2.21	33.25-R29	10.9
			S/225	**(14/20)**	**(81,640)**	**(42'5")**	**(11'4")**	**(12'2")**	**(7'3")**	★★ (E-2/E-3)	**(35'9")**
627B/PP	15S	73-86	T/225	10.7/15.3	35 660	14.91	3.45	3.63	2.18	29.5-29,	11.1
			S/225	**(14/20)**	**(78,620)**	**(48'11")**	**(11'4")**	**(11'11")**	**(7'2")**	28 PR (E-3)	**(36'6")**
627E/PP	6GB	86-89	T/225	10.7/15.3	36 130	12.89	3.47	3.71	2.21 **(7'3")**	33.25-29,	10.90
			S/225	**(14/20)**	**(79,655)**	**(42'3")**	**(11'4")**	**(12'2")**	2.18 **(7'2")**	26 PR (E-3)	**(35'9")**
627E/PP	7CG	90-93	T/330	10.7/15.3	36 620	15.2	3.47	3.71	2.21	33.25-29,	10.9
			S/225	**(14/20)**	**(80,735)**	**(49'7")**	**(11'4")**	**(12'2")**	**(7'3")**	26 PR (E-3)	**(35'8")**
627F/PP Series II	1DL	93-00	T/330	10.7/15.3	38 103	15.2	3.47	3.71	2.21	33.25-R29	10.9
			S/225	**(14/20)**	**(84,000)**	**(49'7")**	**(11'4")**	**(12'2")**	**(7'3")**	★★ (E-2/E-3)	**(35'9")**
627G/PP	AXF	00-02	T/330/365	10.7/15.3	38 140	15.2	3.47	3.71	2.20	33.25R29	11.7
			S/225	**(14/20)**	**(84,075)**	**(49'7")**	**(11'4")**	**(12'2")**	**(7'3")**		**(38'5")**
627G/PP	CEX	02-05	T/330/365	12/17	39 186	15.2	3.47	3.71	2.20	33.25R29	11.7
			S/225/249	**(15.7/22)**	**(86,390)**	**(49'7")**	**(11'4")**	**(12'2")**	**(7'3")**		**(38'5")**
627G P/P	DBD	05-10	T/330/365	12/17	39 443	15.2	3.58	3.81	2.23	33.25R29	11.7
			S/239/266	**(15.7/22)**	**(86,957)**	**(49'7")**	**(11'9")**	**(12'6")**	**(7'4")** Tractor 2.20 **(7'3")** Scraper	★★ (E-3)	**(38'5")**
627H	DBW LCT	10-13	T/407 S/290	13/18.4 **17.1/24**	26 127 **(90,213)**	14.02 **(45'10")**	3.57 **(11'7")**	4.03 **(13'2")**	2.29 **(7'5")** Tractor 2.28 **(7'4")** Scraper	33.25R29 ★★ (E-3)	11.8 **(38'7")**
630A & 482C Scraper	52F	60-62	420/335	21/27 **(27/35)**	35 830 **(79,000)**	14.63 **(48'0")**	3.91 **(12'10")**	4.01 **(13'2")**	2.39 **(7'10")** Scraper	16.0 × 25-16 29.5 × 35-28 33.5 × 33-26	11.89 **(39'0")**
630A	52F	60-62	420/335	16/21.4 **(21/28)**	31 430 **(69,300)**	13.82 **(45'4")**	3.58 **(11'9")**	3.73 **(12'3")**	2.21 **(7'3")**	16.0 × 25-16 29.5 × 35-28	11.89 **(39'0")**
630B	14G	62-63	420/335	16/23 **(21/30)**	33 520 **(73,900)**	14.12 **(46'4")**	3.81 **(12'6")**	3.71 **(12'2")**	2.41 **(7'11")**	16.0-25, 16 29.5-35, 28	13.36 **(43'10")**
630B	14G	63-66	400/360	16/23 **(21/30)**	33 570 **(74,000)**	14.30 **(46'11")**	3.81 **(12'6")**	3.94 **(12'11")**	2.41 **(7'11")**	16.0-25, 16 29.5-35, 34	13.36 **(43'10")**
630B	10G	62-69	/400	16/23 **(21/30)**	35 750 **(78,800)**	14.35 **(47'1")**	3.81 **(12'6")**	3.94 **(12'11")**	2.40 **(7'10")**	16.0-25, 16 29.5-35, 34	13.36 **(43'10")**

T — Tractor Engines
S — Scraper Engines

Wheel Tractor-Scrapers (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power Max/ Rated	Capacity Struck/ Heaped m^3 (yd^3)	Approx. Shipping Weight kg (lb)	Dimensions m (ft)				Tire Size (Standard) & ply rating Tractor & Scraper	Turning Circle m (ft)
						Length	Width	Height	Width of Tread		
631A	51F	60-62	420/335	16/21.4	30 250	12.88	3.58	3.56	2.21	29.5-35, 28	11.00
				(21/28)	**(66,700)**	**(42'3")**	**(11'9")**	**(11'8")**	**(7'3")**		**(36'0")**
631B	13G	62-62	420/335	16/23	31 620	13.05	3.81	3.45	2.39	29.5-35, 28	11.31
				(21/30)	**(69,700)**	**(42'10")**	**(12'6")**	**(11'5")**	**(7'10")**		**(37'5")**
631B	13G	62-66	420/360	16/23	31 840	13.29	3.81	3.63	2.41	29.5-35, 34	11.31
				(21/30)	**(70,200)**	**(43'7")**	**(12'6")**	**(11'11")**	**(7'11")**		**(37'5")**
631C	67M	69-75	/415	16/23	36 350	13.54	3.45	3.91	2.39	29.5-35, 34	11.45
				(21/30)	**(80,150)**	**(44'5")**	**(11'4")**	**(12'10")**	**(7'10")**		**(37'7")**
631D	24W	75-85	473/450	16/23.7	42 370	14.25	3.96	4.17	2.46	33.25-35,	12.2
				(21/31)	**(93,410)**	**(46'9")**	**(13'0")**	**(13'8")**	**(8'1")**	38 PR (E-3)	**(40'1")**
631E	1AB	85-91	473/450	16.1/23.7	43 365	14.28	3.94	4.29	2.46	37.25-35, 30	12.2
				(21/31)	**(95,600)**	**(46'10")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
631E Series II	1AB	91-01	473/450	16.1/23.7	44 210	14.56	3.94	4.29	2.46	37.25R35	12.2
				(21/31)	**(97,460)**	**(47'9")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
631G	AWK	00-02	450/485	16.1/23.7	46 475	14.56	3.94	4.29	2.46	37.25R35	12.2
				(21/31)	**(102,460)**	**(47'9")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
631G	CLR	03-05	450/485	18.3/26	46 475	14.56	3.94	4.29	2.46	37.25R35	12.2
				(24/34)	**(102,460)**	**(47'9")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
631G	DFA	05-16	462/500	18.3/26	47 628	14.71	3.94	4.29	2.46	37.25R35	12.2
				(24/34)	**(105,002)**	**(48'3")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
632	14G	62-63	420/335	21.4/29	37 650	15.21	4.04	4.00	2.44	16.0-25, 16	13.36
				(28/38)	**(83,000)**	**(49'11")**	**(13'3")**	**(13'1")**	**(8'0")**	29.5-35, 34	**(43'10")**
632	14G	63-66	420/360	21.4/29	39 420	15.30	4.04	4.00	2.44	16.0-25, 16	13.36
				(28/38)	**(86,910)**	**(50'2")**	**(13'3")**	**(13'1")**	**(8'0")**	29.5-35, 34	**(43'10")**
633C	66M	69-75	/415	24.5	41 750	13.36	3.45	3.96	2.39	33.2-35, 32	11.78
				(32)	**(92,050)**	**(43'10")**	**(11'4")**	**(13'0")**	**(7'10")**		**(38'8")**
633D	25W	75-85	450	17.7/23	47 570	14.40	3.96	4.24	2.46	33.25-35,	12.4
				(23/34)	**(104,870)**	**(47'3")**	**(13'0")**	**(13'11")**	**(8'1")**	38 PR (E-3)	**(40'7")**
633E	1AB	92-96	475	17.7/23	50 800	14.40	3.96	4.24	2.46		13.15
				(23/34)	**(112,000)**	**(47'3")**	**(13'0")**	**(13'11")**	**(8'1")**	37.25R35	**(43'2")**
633E Series II	2PS	96-00	490	17.7/23	51 100	14.8	3.96	4.24	2.46	37.25R35	13.15
				(23/34)	**(112,670)**	**(48'7")**	**(13'0")**	**(13'11")**	**(8'1")**		**(43'2")**

Wheel Tractor-Scrapers (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power Max/ Rated	Capacity Struck/ Heaped m^3 (yd^3)	Approx. Shipping Weight kg (lb)	Dimensions m (ft)				Tire Size (Standard) & ply rating Tractor & Scraper	Turning Circle m (ft)
						Length	Width	Height	Width of Tread		
637	65M	70-75	T/415	16/23	41 300	13.65	3.45	3.93	2.39	33.25-35, 32	11.68
			S/225	**(21/30)**	**(91,050)**	**(44'9.5")**	**(11'4")**	**(12'11")**	**(7'10")**		**(38'4")**
637/PP	79P	70-75	T/415	16/23	43 700	15.82	3.45	3.93	2.39	33.25-35, 32	11.68
			S/225	**(21/30)**	**(96,350)**	**(51'11")**	**(11'4")**	**(12'11")**	**(7'10")**		**(38'4")**
637D	26W	75-85	T/450	16/23	46 987	14.8	3.96	4.17	2.46	33.25-35,	12.2
			S/250	**(21/31)**	**(103,590)**	**(48'8")**	**(13'0")**	**(13'8")**	**(8'1")**	38 PR (E-3)	**(40'1")**
637D/PP	27W	75-85	T/450	16/23	48 531	14.8	3.96	4.17	2.46	33.25-35,	12.2
			S/250	**(21/31)**	**(106,990)**	**(48'8")**	**(13'0")**	**(13'8")**	**(8'1")**	38 PR (E-3)	**(40'1")**
637E	1FB	85-91	T/450	16/23	49 940	14.28	3.94	4.29	2.46	37.25-35, 30	12.2
			S/250	**(21/31)**	**(110,100)**	**(46'10")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
637E Series II	1FB	91-01	T/450	16/23	50 990	14.56	3.94	4.29	2.46	37.25R35	12.2
			S/250	**(21/31)**	**(112,320)**	**(47'9")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
637E/PP	1FB	85-91	T/450	16/23	51 485	15.88	3.94	4.29	2.46	37.25-35, 30	12.2
			S/250	**(21/31)**	**(113,500)**	**(52'1")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
637E Series II/PP	1FB	91-01	T/450	16/23	52 385	16.49	3.94	4.29	2.46	37.25R35	12.2
			S/250	**(21/31)**	**(115,490)**	**(54'1")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
637G/PP	AXT	00-02	T/450/485	16.1/23.7	53 590	16.49	3.94	4.29	2.46	37.25R35	12.2
			S/249	**(21/31)**	**(118,150)**	**(54'1")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
637G/PP	CEH	02-05	T/450/485	18.3/26	53 562	16.49	3.94	4.29	2.46	37.25R35	12.2
			S/249/274	**(24/34)**	**(118,084)**	**(54'1")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
637G/PP	DFJ	06-16	T/462/500	18.3/26	54 005	16.64	3.94	4.29	2.46	37.25R35	12.2
			S/266/283	**(24/34)**	**(119,060)**	**(54'7")**	**(12'11")**	**(14'1")**	**(8'1")**		**(40'1")**
639D	99X	79-84	T/450	26	55 030	14.53	3.96	4.06	2.46	37.25-35, 42	12.4
			S/250	**(34)**	**(121,318)**	**(47'8")**	**(13'0")**	**(13'4")**	**(8'1")**	37.25-35, 42	**(40'7")**
641	64F	62-65	560/450	21.4/29	43 200	14.73	4.04	4.00	2.44	33.5-39, 38	12.68
				(28/38)	**(95,300)**	**(48'4")**	**(13'3")**	**(13'1")**	**(8'0")**		**(41'7")**
641B	65K	69-81	/550	21.4/29	53 070	14.96	4.04	4.24	2.55	37.5-39, 36	13.00
				(28/38)	**(117,000)**	**(49'1")**	**(13'3")**	**(13'11")**	**(8'4")**		**(42'9")**
650	63F	62-64	560/450	24.5/33.6	45 130	16.31	4.24	4.01	2.54	18.0-25, 20	13.87
				(32/44)	**(99,500)**	**(53'6")**	**(13'11")**	**(13'2")**	**(8'4")S**	33.5-39, 32	**(45'6")**
										37.5-39, 36	
650B	22G	62-72	/550	24.5/33.6	46 100	17.00	3.80	4.30	2.65	18.0-25, 20	14.00
				(32/44)	**(101,700)**	**(55'10")**	**(12'6")**	**(14'1")**	**(8'9")S**	37.5-39, 28	**(46'0")**
										37.5-30, 36	

T — Tractor Engines
S — Scraper Engines

Wheel Tractor-Scrapers (cont'd)

Model	Product Ident. No. Prefix	Years Built	Horse-power Max/ Rated	Capacity Struck/ Heaped m^3 (yd^3)	Approx. Shipping Weight kg (lb)	Dimensions m (ft) Length	Width	Height	Width of Tread	Tire Size (Standard) & ply rating Tractor & Scraper	Turning Circle m (ft)
651	33G	62-68	560/450	24.5/33.6	43 730	14.93	4.24	4.01	2.54	37.5-39, 36	13.29
				(32/44)	**(96,400)**	**(49'0")**	**(13'11")**	**(13'2")**	**(8'4")**		**(43'7")**
651B	67K	69-84	/550	24.5/33.6	56 340	15.34	4.32	4.29	2.72	37.5-39, 36	13.5
				(32/44)	**(124,200)**	**(51'4")**	**(14'2")**	**(14'1")**	**(8'11")S**	37.5-39, 36	**(44'2")**
651E	89Z	82-96	550	24.5/33.6	59 420	16.13	4.37	4.7	2.64	37.5R39	14.5
				(32/44)	**(131,000)**	**(52'11")**	**(14'4")**	**(15'5")**	**(8'8")**		**(47'7")**
651E	4YR	96-06	550/605	24.5/33.6	61 126	16.18	4.37	4.7	2.64	40.5/75R39	15.1
				(32/44)	**(134,760)**	**(53'1")**	**(14'4")**	**(15'5")**	**(8'8")**		**(49'8")**
657	31G	62-68	T/450	24.5/33.6	56 550	15.39	4.24	4.09	2.62	37.5-39, 44	13.29
			S/335	**(32/44)**	**(124,700)**	**(50'6")**	**(13'11")**	**(13'5")**	**(8'7")**		**(43'7")**
657	46M	68-69	T/500	24.5/33.6	56 820	15.39	4.24	4.09	2.67	37.5-39, 44	14.57
			S/400	**(32/44)**	**(125,155)**	**(50'6")**	**(13'11")**	**(13'5")**	**(8'8")**		**(47'10")**
657B	68K	69-84	T/550	24.5/33.6	63 100	15.7	4.32	4.21	2.67	37.5-39, 44	13.7
			S/400	**(32/44)**	**(139,100)**	**(51'8")**	**(14'2")**	**(13'10")**	**(8'9")S**	37.5-39, 44	**(45'1")**
657E	90Z	82-95	T/550	24.5/33.6	68 720	17	4.37	4.7	2.64	37.5R39	14.5
			S/400	**(32/44)**	**(151,500)**	**(55'10")**	**(14'4")**	**(15'5")**	**(8'8")**		**(47'7")**
657E	6TR	96-06	T/550/605	24.5/33.6	69 078	16.2	4.37	4.7	2.64	40.5/75R39	15.1
			S/400/440	**(32/44)**	**(152,290)**	**(53'1")**	**(14'4")**	**(15'5")**	**(8'8")**		**(49'8")**
657E/PP	91Z	82-95	T/550	24.5/33.6	72 120	18.01	4.37	4.7	2.64	37.5R39	14.5
			S/400	**(32/44)**	**(159,000)**	**(59'1")**	**(14'4")**	**(15'5")**	**(8'8")**		**(47'7")**
657E/PP	5YR	96-06	T/550/605	24.5/33.6	72 857	18.01	4.37	4.7	2.64	40.5/75R39	15.1
			S/400/440	**(32/44)**	**(160,623)**	**(59'1")**	**(14'4")**	**(15'5")**	**(8'8")**		**(49'8")**
660	90F	62-64	560/450	30.6/41.3	49 130	17.04	4.24	4.37	2.59	18.0 × 25-20	13.87
				(40/54)	**(108,300)**	**(55'11")**	**(13'11")**	**(14'4")**	**(8'6")**	37.5 × 39-28	**(45'6")**
									Scraper	37.5 × 51-36	
660B	58K	70-78	/550	30.6/41.3	59 875	17.27	3.81	4.37		18.0 × 25-20	14.00
				(40/54)	**(132,000)**	**(56'8")**	**(14'2")**	**(14'4")**		37.5 × 39-28	**(46'0")**
666	77F	63-69	T/450	30.6/41.3	56 700	17.04	4.24	4.37	2.59	18.0 × 25-20	13.87
			S/335	**(40/54)**	**(125,000)**	**(55'11")**	**(13'11")**	**(14'4")**	**(8'6")**	37.5 × 39-28	**(45'6")**
									Scraper	37.5 × 51-36	
666	64H	67-69	T/500	30.6/41.3	58 800	17.27	4.24	4.37	2.59	18.0 × 25-20	13.87
			S/400	**(40/54)**	**(129,645)**	**(56'8")**	**(13'11")**	**(14'4")**	**(8'6")**	37.5 × 39-28	**(45'6")**
									Scraper	37.5 × 51-51	
666B	66K	69-78	T/550	30.6/41.3	67 630	17.27	4.31	4.37	2.59	18.0 × 25-20	14.00
			S/400	**(40/54)**	**(149,500)**	**(56'8")**	**(14'4")**	**(14'4")**	**(8'9")**	37.5 × 39-28	**(46'0")**

T — Tractor Engines
S — Scraper Engines



TRACTOR-TOWED SCRAPERS

Model	Product Ident. No. Prefix	Years Built	Capacity Struck/ Heaped m^3 (yd^3)	Weight kg (lb)	Width m (ft)	Length m (ft)	Height m (ft)	Width of Cut m (ft)
40	1W	49-59	2.8/3.4 **(3.6/4.5)**	3348 **(7380)**	2.27 **(7'6")**	6.40 **(21'0")**	1.68 **(5'6")**	1.82 **(6'0")**
60	1D	47-53	4.6/6.1 **(6.0/8.0)**	5579 **(12,300)**	2.65 **(8'9")**	8.43 **(27'8")**	2.36 **(7'9")**	2.13 **(7'0")**
60	2W	52-72	5.4/7.0 **(7.0/9.0)**	6100 **(13,500)**	2.85 **(9'5")**	8.52 **(28'3")**	2.36 **(7'9")**	2.40 **(7'11")**
70	8C	46-53	6.7/8.4 **(8.7/11.0)**	8527 **(18,800)**	3.02 **(10'0")**	9.50 **(31'2")**	2.56 **(8'5")**	2.43 **(8'0")**
70	3W	51-57	7.8/9.9 **(10.2/13.0)**	9140 **(20,150)**	3.16 **(10'5")**	9.53 **(31'4")**	2.61 **(8'7")**	2.59 **(8'6")**
80	2D	46-52	10.3/13.8 **(13.5/18.0)**	11 793 **(26,000)**	3.38 **(11'2")**	10.82 **(35'6")**	2.92 **(9'7")**	2.74 **(9'0")**
80	5W	50-56	11.5/15.3 **(15.0/20.0)**	13 533 **(29,836)**	3.50 **(11'6")**	10.92 **(35'0")**	3.09 **(10'2")**	2.89 **(9'6")**
90	9V	51-55	16.2/20.6 **(21.2/27.0)**	17 208 **(37,937)**	3.65 **(12'0")**	12.19 **(40'0")**	3.20 **(10'6")**	3.04 **(10'0")**
435C	45D	56-61	9.9/13.8 **(13.0/18.0)**	10 659 **(23,500)**	3.28 **(10'10")**	10.16 **(33'4")**	3.01 **(9'11")**	2.84 **(9'4")**
435D	45D	59-61	11.5/14.5 **(15.0/19.0)**	11 521 **(25,400)**	3.29 **(10'10")**	10.16 **(33'4")**	3.01 **(9'11")**	2.84 **(9'4")**
435E	85F	61-72	9.2/13.0 **(12.0/17.0)**	10 400 **(22,900)**	3.29 **(10'10")**	10.06 **(33'1")**	3.07 **(10'1")**	2.84 **(9'4")**
435F	45D	62-72	10.7/13.8 **(14.0/18.0)**	11 300 **(24,900)**	3.29 **(10'10")**	10.06 **(33'1")**	3.02 **(9'11")**	2.84 **(9'4")**
435G	27G	63-73	9.2/13.0 **(12.0/17.0)**	10 400 **(22,900)**	3.27 **(10'9")**	10.08 **(33'1")**	2.97 **(9'9")**	2.84 **(9'4")**
463	62C	55-60	13.8/29.1 **(18.0/25.0)**	14 061 **(31,000)**	3.58 **(11'9")**	11.58 **(38'0")**	3.39 **(11'2")**	3.15 **(10'4")**
463C	62C	59-60	16.8/21.4 **(22.0/28.0)**	15 785 **(34,800)**	3.58 **(11'9")**	11.58 **(38'0")**	3.39 **(11'2")**	3.15 **(10'4")**
463E	86F	60-71	13.8/20.0 **(18.0/26.0)**	15 600 **(34,400)**	3.58 **(11'9")**	11.65 **(38'3")**	3.28 **(10'10")**	3.15 **(10'4")**
463F	62C	63-71	16.0/21.4 **(21.0/28.0)**	15 700 **(34,600)**	3.58 **(11'9")**	11.65 **(38'3")**	3.28 **(10'10")**	3.15 **(10'4")**
463G	28G	63-71	13.8/20.0 **(18.0/26.0)**	13 200 **(29,200)**	3.58 **(11'9")**	11.52 **(37'10")**	3.14 **(10'4")**	3.15 **(10'4")**
491	98C	56-64	20.6/26.0 **(27.0/34.0)**	16 964 **(37,400)**	3.65 **(12'0")**	12.13 **(39'10")**	3.96 **(13'0")**	3.16 **(10'5")**
491B	9A	61-63	20.6/26.8 **(27.0/35.0)**	20 902 **(46,060)**	3.91 **(12'10")**	12.49 **(41'0")**	3.96 **(13'0")**	3.30 **(10'10")**
491C	47E	63-70	20.6/26.8 **(27.0/35.0)**	21 600 **(47,500)**	3.91 **(12'10")**	12.64 **(41'6")**	3.96 **(13'0")**	3.30 **(10'10")**
TS180 Lead	E1J	09-13	11/14.5 **(14.4/19)**	11 748 **(25,900)**	3.378 **(11.08)**	8.915 **(29.25)**	2.362 **(7.75)**	3.2 **(10.5)**
TS180 Trail	E1K	09-13	11/14.5 **(14.4/19)**	12 748) **(25,900)**	3.378 **(11.08)**	8.915 **(29.25)**	2.362 **(7.75)**	3.2 **(10.5)**
TS185 Lead	E1R	09-13	11/14.5 **(14.4/19)**	11 748 **(25,900)**	3.988 **(13.08)**	9.119 **(29.92)**	2.515 **(8.25)**	3.785 **(12.4)**
TS185 Trail	E1S	09-13	11/14.5 **(14.4/19)**	12 748 **(25,900)**	3.988 **(13.08)**	9.119 **(29.92)**	2.515 **(8.25)**	3.785 **(12.4)**
TS220 Lead	E1L	09-13	13/18 **(17/23.5)**	13 145 **(28,980)**	3.683 **(12.08)**	9.677 **(31.75)**	2.464 **(8.08)**	3.480 **(11.4)**
TS220 Trail	E1N	09-13	13/18 **(17/23.5)**	14 145 **(28,980)**	3.683 **(12.08)**	9.677 **(31.75)**	2.464 **(8.08)**	3.480 **(11.4)**
TS225 Lead	E1T	09-13	13/18 **(17/23.5)**	15 250 **(33,620)**	3.988 **(13.08)**	10.287 **(33.75)**	2.515 **(8.25)**	3.785 **(12.4)**
TS225 Trail	E1W	09-13	13/18 **(17/23.5)**	16 250 **(33,620)**	3.988 **(13.08)**	10.287 **(33.75)**	2.515 **(8.25)**	3.785 **(12.4)**



MINING & OFF-HIGHWAY TRUCKS/TRACTORS

Model	Product Ident. No. Prefix	Years Built	Flywheel Kilowatts (Horse-power)	Capacity Metric Tons (U.S. Tons)	Approx. Weight kg (lb)	Dimensions m (ft)						Tire Size
						Width	Length	Height	Loading Height	Dumping Height (55°)	Turning Circle	
768B	79S	71-78	309	—	22 000	3.61	6.55	3.48	—	—	18.0	18.00 × 33—24 PR
			(415)	**—**	**(48,500)**	**(11'10")**	**(21'6")**	**(11'5")**	**—**	**—**	**(59'1")**	
768C	02X	78-95	336	—	24 624	4.70	8.00	3.56	—	—	18.5	18.00R33 E-4
			(450)	**—**	**(54,285)**	**(15'5")**	**(26'3")**	**(11'8")**	**—**	**—**	**(60'8")**	
769	99F	62-67	298	31.8	25 365	3.63	7.64	4.05	3.07	7.18	16.5	18.00 × 25—32 PR
			(400)	**(35.0)**	**(55,870)**	**(11'11")**	**(25'1")**	**(13'4")**	**(10'1")**	**(26'7")**	**(54'5")**	
769B	99F	67-78	309	32.0	28 000	3.64	7.85	3.89	3.15	7.24	18.0	18.00 × 25—32 PR
			(415)	**(35.0)**	**(61,800)**	**(11'11.5")**	**(25'9")**	**(12'9")**	**(10'4")**	**(23'9")**	**(59'1")**	E-3
769C	01X	78-95	336	36.9	30 675	4.70	8.00	3.85	3.24	7.68	18.5	18.00R33 E-4
			(450)	**(40.6)**	**(67,855)**	**(15'5")**	**(26'3")**	**(12'8")**	**(10'7")**	**(25'2")**	**(60'8")**	
769D	5TR, 5SS, BBB	95-06	363	36.4	33 875	5.07	8.24	4.03	3.14	7.71	17	18.00R33
			(487)	**(40.0)**	**(74,682)**	**(16'8")**	**(27'0")**	**(13'3")**	**(10'4")**	**(25'4")**	**(55'9")**	
770	BZZ	07-14	355	36.5	34 642	4.75	8.74	4.14	3.12	8.28	20.2	18.00R33 (E-4)
			(476)	**(40.3)**	**(76,372)**	**(15'8")**	**(28'9")**	**(13'7")**	**(10'3")**	**(27'2")**	**(66'3")**	
771C	3BJ	92-95	336	40.0	34 170	4.74	8.20	4.00	3.30	7.68	18.5	18.00R33 E-4
			(450)	**(44.0)**	**(75,345)**	**(15'7")**	**(26'11")**	**(13'1")**	**(10'10")**	**(25'2")**	**(60'8")**	
771D	6JR, 6YS, BCA	96-06	363	41	33 784	5.07	8.40	4.02	3.40	7.74	17	18.00R33
			(487)	**(45)**	**(74,482)**	**(16'8")**	**(27'7")**	**(13'2")**	**(11'1")**	**(25'5")**	**(55'9")**	
772	RLB	07-14	399	46.2	35 864	4.75	8.74	4.22	3.50	8.36	21.6	21.00R33 (E-4)
			(535)	**(51.0)**	**(79,066)**	**(15'8")**	**(28'9")**	**(13'10")**	**(11'6")**	**(27'5")**	**(70'10")**	
772	80S	71-78	447	—	32 100	4.06	7.11	3.68	—	—	22.1	24.00 × 35—36 PR
			(600)	**—**	**(70,800)**	**(13'4")**	**(23'4")**	**(12'1")**	**—**	**—**	**(72'6")**	
772B	64W	78-95	485	—	32 909	4.86	9.12	4.52	—	—	23.5	24.00R35 E-4
			(650)	**—**	**(72,550)**	**(15'11")**	**(29'11")**	**(14'10")**	**—**	**—**	**(77'0")**	
773	63G	70-78	447	45.4	37 800	4.06	8.71	4.27	3.61	8.36	22.1	21.00 × 35—32 PR
			(600)	**(50.0)**	**(83,360)**	**(13'4")**	**(28'7")**	**(14'0")**	**(11'10")**	**(27'5")**	**(72'6")**	E-3
773B	63W	78-95	485	54.3	38 321	4.86	9.12	4.31	3.77	8.72	23.5	24.00R35 E-4
			(650)	**(59.8)**	**(84,500)**	**(15'11")**	**(29'11")**	**(14'2")**	**(12'5")**	**(28'7")**	**(77'0")**	
773D	7CS, 7ER	96-01	485	52.9	43 600	5.08	9.21	4.42	3.79	8.82	22.0	24.00R35
			(650)	**(58.4)**	**(96,000)**	**(16'8")**	**(29'11")**	**(14'6")**	**(12'5")**	**(28'11")**	**(72'2")**	
773E	BDA (U.S.)	01-06	501	54.4	45 480	5.08	9.21	4.42	3.79	8.82	22.0	24.00R35
			(671)	**(60.0)**	**(100,180)**	**(16'8")**	**(29'11")**	**(14'6")**	**(12'5")**	**(28'11")**	**(72'2")**	
773E	ASK (India)	09-16	501	54.4	45 480	5.08	9.21	4.42	3.79	8.82	22.0	24.00R35
			(671)	**(60.0)**	**(100,180)**	**(16'8")**	**(29'11")**	**(14'6")**	**(12'5")**	**(28'11")**	**(72'2")**	
773F	EED, EXD	06-11	524	54.4	45 069	5.43	10.33	4.44	3.77	9.26	26.1	24.00R35 (E-4)
			(703)	**(60.0)**	**(99,360)**	**(17'10")**	**(33'11")**	**(14'7")**	**(12'5")**	**(30'5")**	**(85'8")**	
775B	7XJ	92-95	485	59.5	42 324	4.91	9.33	4.31	3.86	8.72	23.5	24.00R35 E-4
			(650)	**(65.5)**	**(93,325)**	**(16'2")**	**(30'7")**	**(14'2")**	**(12'8")**	**(28'8")**	**(77'7")**	
775D	6KR, 8AS	95-01	517	63.4	43 200	5.08	9.30	4.42	3.91	8.82	22.0	24.00R35
			(693)	**(69.9)**	**(95,300)**	**(16'8")**	**(30'6")**	**(14'6")**	**(12'10")**	**(28'11")**	**(72'2")**	
775E	BEC	01-06	544	63.5	43 470	5.08	9.21	4.42	3.91	8.82	22.0	24.00R35
			(730)	**(70.0)**	**(95,810)**	**(16'8")**	**(29'11")**	**(14'6")**	**(12'10")**	**(28'11")**	**(72'2")**	
775F	DLS, EYG	06-11	552	63.5	45 620	5.43	10.33	4.44	3.97	9.26	26.1	24.00R35 (E-4)
			(740)	**(70.0)**	**(100,575)**	**(17'10")**	**(33'11")**	**(14'7")**	**(13'0")**	**(30'5")**	**(85'8")**	

Mining & Off-Highway Trucks/Tractors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Kilowatts (Horse-power)	Capacity Metric Tons (U.S. Tons)	Approx. Weight kg (lb)	Dimensions m (ft)						Tire Size
						Width	Length	Height	Loading Height	Dumping Height (55°)	Turning Circle	
776	14H	75-84	649	—	49 686	3.51	8.06	3.40	—	—	26.8	27.00 × 49—36 PR
			(870)	**—**	**(109,540)**	**(11'6")**	**(26'5.5")**	**(11'2")**	**—**	**—**	**(88'0")**	E-3
776B	6JC	84-92	649	—	49 896	3.51	8.06	3.40	—	—	25.8	27.00 × 49—36 PR
			(870)	**—**	**(110,000)**	**(11'6")**	**(26'6")**	**(11'2")**	**—**	**—**	**(84'6")**	E-3
776C	2TK	92-96	649	—	49 896	3.51	8.06	4.55	—	—	25.8	27.00R49
			(870)	**—**	**(110,000)**	**(11'6")**	**(26'5.5")**	**(14'11")**	**—**	**—**	**(84'6")**	
777	84A	74-84	649	77.1	58 886	5.463	9.78	4.90	4.14	9.29	26.8	24.00 × 49—42 PR
			(870)	**(85.0)**	**(129,820)**	**(17'11")**	**(32'1")**	**(16'1")**	**(13'7")**	**(30'6")**	**(88'0")**	E-3
777B	4YC	84-92	649	86.2	60 055	5.463	9.79	4.97	4.17	9.42	25.8	24.00 × 49—48 PR
			(870)	**(95.0)**	**(132,422)**	**(17'11")**	**(32'1")**	**(16'4")**	**(13'8")**	**(30'11")**	**(84'6")**	E-3
777C	4XJ	92-96	649	86.2	61 790	5.463	9.79	4.97	4.17	9.42	25.8	27.00R49
			(870)	**(95.0)**	**(136,227)**	**(17'11")**	**(32'1")**	**(16'4")**	**(13'8")**	**(30'11")**	**(84'6")**	
777D (Decatur)	3PR, AGC (U.S.)	96-06	699	90.9	72 575	6.11	9.78	5.15	4.38	10.06	25.3	27.00R49
			(938)	**(100.0)**	**(160,000)**	**(20'0")**	**(32'1")**	**(16'10")**	**(14'4")**	**(33'0")**	**(83'0")**	
777D (Decatur)	FKR (India)	06-16	699	90.9	72 575	6.11	9.78	5.15	4.38	10.06	25.3	27.00R49
			(938)	**(100.0)**	**(160,000)**	**(20'0")**	**(32'1")**	**(16'10")**	**(14'4")**	**(33'0")**	**(83'0")**	
777F	JRP, JXP	06-11	700	90.9	72 739	6.49	10.54	5.17	4.38	10.33	28.4	27.00R49 (E4)
			(938)	**(100.0)**	**(160,360)**	**(21'4")**	**(34'7")**	**(17'0")**	**(14'4")**	**(33'11")**	**(93'2")**	
784B	5RK	93-98	962	—	89 280	6.74	9.34	5.47	—	—	33.5	36.00R51 E-3
			(1290)	**—**	**(196,825)**	**(22'2")**	**(30'8")**	**(17'1")**	**—**	**—**	**(109'10")**	
784C	2PZ	98-09	1005	—	88 746	7.00	9.34	5.47	—	—	33.8	36.00R51
			(1348)	**—**	**(195,651)**	**(23'0")**	**(30'8")**	**(17'1")**	**—**	**—**	**(110'11")**	
785	8GB	85-92	962	136.0	96 353	6.64	11.02	5.77	4.98	11.20	30.5	33.00 × 51
			(1290)	**(150.0)**	**(212,458)**	**(21'9")**	**(36'2")**	**(18'11")**	**(16'4")**	**(36'9")**	**(100'4")**	
785B	6HK	92-98	962	136.0	96 353	6.64	11.02	5.77	4.98	11.20	30.2	33.00R51
			(1290)	**(150.0)**	**(212,458)**	**(21'9")**	**(36'2")**	**(18'11")**	**(16'4")**	**(36'9")**	**(99'2")**	
789	9ZC	86-92	1272	177.0	121 922	7.67	12.18	6.15	5.21	11.91	30.2	37.00R57
			(1705)	**(195.0)**	**(268,837)**	**(25'2")**	**(39'11")**	**(20'2")**	**(17'1")**	**(39'1")**	**(99'2")**	
789B	7EK	92-98	1272	177.0	121 922	7.67	12.18	6.15	5.21	11.91	30.2	37.00R57
			(1705)	**(195.0)**	**(268,837)**	**(25'2")**	**(39'11")**	**(20'2")**	**(17'1")**	**(39'1")**	**(99'2")**	
789C	2BW	98-12	1417	180.7	132 845	7.67	12.18	6.15	5.21	11.90	30.2	37.00R57
			(1900)	**(199.2)**	**(292,873)**	**(25'2")**	**(39'11")**	**(20'2")**	**(17'1")**	**(39'1")**	**(99'2")**	
793	3SJ	90-92	1534	218.0	376 482	7.60	12.86	6.43	5.86	13.21	30.2	40.00-57
			(2057)	**(240.0)**	**(830,000)**	**(24'11")**	**(42'3")**	**(21'1")**	**(19'3")**	**(43'4")**	**(99'2")**	
793B	1HL	92-96	1534	218.0	376 482	7.60	12.86	6.43	5.86	13.21	30.2	40.00R57
			(2057)	**(240.0)**	**(830,000)**	**(24'11")**	**(42'3")**	**(21'1")**	**(19'3")**	**(43'4")**	**(99'2")**	
793C	4AR, 4GZ, ATY	96-04	1615	218.0	383 739	7.41	12.87	6.43	5.86	13.21	32.4	40.00R57
			(2166)	**(240.0)**	**(846,000)**	**(24'4")**	**(42'3")**	**(21'1")**	**(19'3")**	**(43'4")**	**(106'4")**	
797	5YW	98-02	2395	326.0	557 820	9.14	14.63	7.24	7.05	14.94	32.86	55/80R63
			(3211)	**(360.0)**	**(1,230,000)**	**(30'0")**	**(48'0")**	**(27'6")**	**(26'10")**	**(49'0")**	**(104'10")**	
797B	JSM	02-09	2513	354.0	623 583	9.66	14.4	7.72	7.15	15.34	40.5	59/80/R63
			(3370)	**(394.0)**	**(1,375,000)**	**(31'9")**	**(47'3")**	**(25'4")**	**(23'6")**	**(50'4")**	**(132'10")**	