ON-HIGHWAY TRUCKS

Engine	Horsepower (BHP @ 1700 RPM)	Torque Peak (lbf-ft @ 1000 RPM)	Gov. Speed (RPM)	Clutch Engagement Torque (lbf-ft at 800 RPM)
CT11	330/1250	1250	2100	686
	365/1250	1250	2100	686
	370/1350	1350	2100	770
	390/1450	1450	2100	811
CT15	450/1550	1550	2100	1150
	450/1750	1750	2100	1150
	475/1850	1850	2100	1150
	500/1650	1650	2100	1150
	500/1850	1850	2100	1150
	550/1850	1850	2100	1150



ARTICULATED TRUCKS

Model	Product Ident. No. Prefix	Years Built	Flywheel Kilowatts (Horse-power)	Capacity Metric Tons (U.S. Tons)	Approx. Weight kg (lb)	Dimensions m (ft)						Tire Size
						Width	Length	Height	Loading Height	Dumping Height (55°)	Turning Circle	
D20D	9MG	92-94	134	18.0	15 000	2.75	8.43	3.30	2.40	5.00	7.25	23.5R25
			(180)	**(20.0)**	**(33,070)**	**(9'0")**	**(27'8")**	**(10'10")**	**(7'11")**	**(16'5")**	**(24'0")**	
D22	*	80-82	175	20.0	17 700	3.00	7.85	3.09	2.44	5.03	7.87	26.5R25
			(235)	**(22.0)**	**(39,000)**	**(9'10")**	**(25'9")**	**(10'2")**	**(8'0")**	**(16'6")**	**(25'10")**	
D25	*	80	175	22.7	17 300	3.00	7.85	3.09	2.44	5.03	7.87	26.5R25
			(235)	**(25.0)**	**(38,000)**	**(9'10")**	**(25'9")**	**(10'2")**	**(8'0")**	**(16'6")**	**(25'10")**	
D25B	*	80-83	190	22.7	17 900	3.00	7.99	3.25	2.44	5.03	7.87	26.5R25
			(255)	**(25.0)**	**(39,400)**	**(9'10")**	**(26'2")**	**(10'8")**	**(8'0")**	**(16'6")**	**(25'10")**	
D25C	9YC	85-89	194	22.7	19 233	3.00	8.73	3.27	2.56	5.28	16.14	26.5R25
			(260)	**(25.0)**	**(42,400)**	**(9'10")**	**(28'8")**	**(10'9")**	**(8'5")**	**(17'4")**	**(52'11")**	
D25D	1HK	89-01	194	22.7	19 450	3.00	8.79	3.34	2.63	5.19	7.95	26.5R25
			(260)	**(25.0)**	**(42,880)**	**(9'10")**	**(28'10")**	**(10'11")**	**(8'8")**	**(17'0")**	**(26'1")**	
D30C	7ZC	85-89	194	27.2	21 320	3.30	8.86	3.33	2.85	5.46	16.33	29.5R25
			(260)	**(30.0)**	**(47,000)**	**(10'10")**	**(29'1")**	**(10'11")**	**(9'4")**	**(17'11")**	**(53'7")**	
D30D	3AJ	89-01	213	27.2	21 690	3.30	8.89	3.40	2.83	5.46	8.20	29.5R25
			(285)	**(30.0)**	**(47,320)**	**(10'10")**	**(29'2")**	**(11'2")**	**(9'3")**	**(17'11")**	**(26'11")**	
D35	*	81-83	190	31.8	20 000	3.27	8.44	3.25	2.91	5.46	7.87	26.5R25
			(255)	**(35.0)**	**(44,000)**	**(10'9")**	**(27'8")**	**(10'8")**	**(9'7")**	**(17'11")**	**(25'10")**	33.25R29
D35C	2GD	85-89	194	31.8	23 860	3.50	9.44	3.34	2.93	5.32	16.00	Front 29.5R25
			(260)	**(35.0)**	**(52,600)**	**(11'6")**	**(31'0")**	**(10'11")**	**(9'7")**	**(17'5")**	**(52'5")**	Rear 33.5R29
D35 HP	3FD	85-89	287	31.8	24 950	3.50	9.80	3.51	2.93	5.32	15.78	Front 29.5R25
			(385)	**(35.0)**	**(55,000)**	**(11'6")**	**(32'2")**	**(11'6")**	**(9'7")**	**(17'5")**	**(51'9")**	Rear 33.5R29
D40D	2JJ	89-94	287	36.3	28 027	3.48	9.76	3.56	3.20	6.00	7.90	Front 29.5R25
			(385)	**(40.0)**	**(61,800)**	**(11'5")**	**(32'0")**	**(11'8")**	**(10'7")**	**(19'8")**	**(25'11")**	Rear 33.25R29
D44	*	81-86	336	40.0	28 000	3.66	10.05	3.86	2.90	6.35	9.96	33.25R29
			(450)	**(44.0)**	**(61,600)**	**(12'0")**	**(33'0")**	**(12'8")**	**(9'6")**	**(20'10")**	**(32'8")**	
D44B	4LD	86-87	343	40.0	32 296	3.73	10.05	3.98	2.98	6.40	9.08	33.25R29
			(460)	**(44.0)**	**(71,200)**	**(12'3")**	**(33'0")**	**(13'1")**	**(9'9")**	**(21'0")**	**(29'9")**	
D250	*	75-78	175	25.0	18 500	2.66	8.82	3.04	2.61	6.22	7.67	23.5R25
			(235)	**(27.5)**	**(40,700)**	**(8'9")**	**(29'0")**	**(10'0")**	**(8'7")**	**(20'5")**	**(25'2")**	
D250B	5WD	85-91	163	22.7	17 963	2.50	9.60	3.18	2.55	6.23	7.65	20.5R25
			(218)	**(25.0)**	**(39,600)**	**(8'2.5")**	**(31'8.5")**	**(10'5")**	**(8'4.5")**	**(20'5")**	**(25'1")**	
D250D	6NG	92-94	160	22.8	17 300	2.50	9.60	3.21	2.59	6.22	7.61	20.5R25
			(214)	**(25.0)**	**(38,150)**	**(8'2")**	**(31'6")**	**(10'7")**	**(8'6")**	**(20'5")**	**(25'0")**	
D250E	5TN	95-98	194	22.7	20 135	2.74	9.94	3.35	2.70	6.20	7.44	23.5R25
			(260)	**(25.0)**	**(44,397)**	**(9'0")**	**(32'7")**	**(11'0")**	**(8'10")**	**(20'4")**	**(24'5")**	
D250E Series II	4PS	98-00	201	22.7	21 600	2.88	10.00	3.35	2.75	6.39	7.44	23.5R25
			(270)	**(25.0)**	**(47,628)**	**(9'5")**	**(32'10")**	**(11'0")**	**(9'0")**	**(20'11")**	**(24'5")**	
725	AFX	00-05	209	23.6	22 730	2.88	9.92	3.44	2.75	6.43	7.26	23.5R25
			(280)	**(26.0)**	**(50,120)**	**(9'5")**	**(32'7")**	**(11'3")**	**(9'0")**	**(21'1")**	**(23'10")**	
725	B1L	05-13	230	23.6	22 260	2.88	9.92	3.44	2.75	6.41	7.25	23.5R25
			(309)	**(26.0)**	**(49,075)**	**(9'5")**	**(32'6")**	**(11'3")**	**(9'0")**	**(21'0")**	**(23'10")**	
725C	TFB	14-16	239	23.6	23 220	3.7	10.45	3.47	2.73	6.31	16.2	23.5R25
			(320)	**(26)**	**(51,191)**	**(12'2")**	**(34'3")**	**(11'4")**	**(8'9")**	**(20'7")**	**(53'0")**	
725C	LFB	14-16	239	23.6	22 950	3.7	10.45	3.47	2.73	6.31	16.2	23.5R25
			(320)	**(26)**	**(50,596)**	**(12'2")**	**(34'3")**	**(11'4")**	**(8'9")**	**(20'7")**	**(53'0")**	

*Information not available — DJB models.

Articulated Trucks (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Kilowatts (Horse-power)	Capacity Metric Tons (U.S. Tons)	Approx. Weight kg (lb)	Dimensions m (ft)						Tire Size
						Width	Length	Height	Loading Height	Dumping Height (55°)	Turning Circle	
D275	*	78-80	175	25.0	18 700	2.66	8.82	3.17	2.61	6.22	7.75	23.5R25
			(235)	**(27.5)**	**(41,000)**	**(8'9")**	**(29'0")**	**(10'7")**	**(8'7")**	**(20'5")**	**(25'3")**	
D275B	*	80-82	190	25.0	19 200	2.66	8.96	3.21	2.61	6.22	7.75	23.5R25
			(255)	**(27.5)**	**(42,400)**	**(8'9")**	**(29'5")**	**(10'7")**	**(8'7")**	**(20'5")**	**(25'5")**	
D300	*	76-78	190	30.0	19 500	2.80	8.82	3.04	2.68	6.22	7.67	23.5R25
			(255)	**(33.0)**	**(42,900)**	**(9'2")**	**(29'0")**	**(10'0")**	**(8'10")**	**(20'5")**	**(25'2")**	
D300B	4SD	85-91	194	27.2	19 800	2.50	9.60	3.18	2.55	6.23	7.76	23.5R25
			(260)	**(30.0)**	**(43,520)**	**(8'2.5")**	**(31'8.5")**	**(10'5")**	**(8'4.5")**	**(20'5")**	**(25'6")**	
D300D	5MG	92-95	213	27.2	20 680	2.88	9.87	3.28	2.66	6.42	7.76	23.5R25
			(285)	**(30.0)**	**(45,600)**	**(9'6")**	**(32'5")**	**(10'9")**	**(8'9")**	**(21'1")**	**(25'5")**	
D300E	7FN	95-98	212	27.2	21 940	2.89	9.94	3.35	2.85	6.26	7.60	23.5R25
			(285)	**(30.0)**	**(48,369)**	**(9'6")**	**(32'7")**	**(11'0")**	**(9'4")**	**(20'6")**	**(24'10")**	
D300E Series II	5KS	98-00	212	27.2	22 793	2.91	10.00	3.35	2.89	6.44	7.60	23.5R25
			(285)	**(30.0)**	**(50,235)**	**(9'7")**	**(32'10")**	**(11'0")**	**(9'6")**	**(21'2")**	**(24'10")**	
730	AGF	00-05	228	28.1	23 230	2.88	9.92	3.44	2.89	6.50	7.26	23.5R25
			(305)	**(31.5)**	**(51,222)**	**(9'5")**	**(32'7")**	**(11'3")**	**(9'6")**	**(21'4")**	**(23'10")**	
730	B1M	05-13	242	28.1	22 850	2.88	9.92	3.44	2.90	6.50	7.25	23.5R25
			(325)	**(31.0)**	**(50,376)**	**(9'5")**	**(32'6")**	**(11'3")**	**(9'5")**	**(21'3")**	**(23'0")**	
730 Ejector	B1W	05-13	242	28.1	25 550	3.24	9.73	3.45	3.05	—	7.25	750/65/R25
			(325)	**(31.0)**	**(56,328)**	**(10'6")**	**(31'9")**	**(11'3")**	**(10'0")**	**—**	**(23'10")**	
730C	TFF	14-16	280	28	24 100	3.7	10.45	3.48	2.91	6.46	16.2	23.5R25
			(375)	**(31)**	**(53,131)**	**(12'2")**	**(34'3")**	**(11'4")**	**(9'6")**	**(21'2")**	**(53'0")**	
730C	LFF	14-16	k280	28	23 700	3.7	10.45	3.48	2.91	6.46	16.2	23.5R25
			(375)	**(31)**	**(52,250)**	**(12'2")**	**(34'3")**	**(11'4")**	**(9'6")**	**(21'2")**	**(53'0")**	
730C EJ	TFH	14-16	280	28	26 800	3.7	10.38	3.45	3.03	—	15.2	750/65
			(375)	**(31)**	**(59,084)**	**(12'2")**	**(34'0")**	**(11'3")**	**(9'9")**	**—**	**(49'9")**	
730C EJ	LFH	14-16	280	28	26 400	3.7	10.38	3.45	3.03	—	15.2	750/65
			(375)	**(31)**	**(58,202)**	**(12'2")**	**(34'0")**	**(11'3")**	**(9'9")**	**—**	**(49'9")**	
D330	*	78-80	190	30.0	20 000	2.80	8.82	3.17	2.68	6.22	7.80	23.5R25
			(255)	**(33.0)**	**(43,000)**	**(9'2")**	**(28'11")**	**(10'5")**	**(8'9")**	**(20'5")**	**(25'7")**	
D330B	*	80-83	190	30.0	20 200	2.76	9.08	3.25	2.68	6.33	7.92	23.5R25
			(255)	**(33.0)**	**(44,400)**	**(9'1")**	**(29'9")**	**(10'8")**	**(8'9")**	**(20'9")**	**(26'0")**	
D350	*	78-80	190	31.8	21 000	3.00	8.95	3.21	2.82	6.35	7.95	26.5R25
			(255)	**(35.0)**	**(46,000)**	**(9'10")**	**(29'4")**	**(10'7")**	**(9'3")**	**(20'10")**	**(26'1")**	
D350B	*	80-83	190	31.8	21 400	3.00	9.09	3.25	2.85	6.40	7.95	26.5R25
			(255)	**(35.0)**	**(47,200)**	**(9'10")**	**(29'10")**	**(10'8")**	**(9'4")**	**(21'0")**	**(26'1")**	
D350C	8XC	85-89	194	31.8	23 315	3.00	9.93	3.27	2.91	6.52	16.16	26.5R25
			(260)	**(35.0)**	**(51,400)**	**(9'10")**	**(32'7")**	**(10'9")**	**(9'6")**	**(21'5")**	**(53'0")**	
D350D	9RF	89-94	213	31.8	24 595	3.00	9.95	3.34	2.93	6.52	16.06	26.5R25
			(285)	**(35.0)**	**(54,221)**	**(9'10")**	**(32'7")**	**(11'0")**	**(9'7")**	**(21'5")**	**(52'8")**	
D350E	9LR	96-99	253	31.7	27 871	3.26	10.38	3.51	2.94	6.60	8.21	26.5R25
			(340)	**(35.0)**	**(61,455)**	**(10'8")**	**(34'1")**	**(11'6")**	**(9'8")**	**(21'8")**	**(26'11")**	
D350E Series II	2XW	99-01	265	31.8	30 190	3.26	10.65	3.51	2.92	6.83	8.45	26.5R25
			(355)	**(35.0)**	**(66,560)**	**(10'8")**	**(35'1")**	**(11'6")**	**(9'7")**	**(20'5")**	**(27'8")**	

*Information not available — DJB models.

Articulated Trucks (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Kilowatts (Horse-power)	Capacity Metric Tons (U.S. Tons)	Approx. Weight kg (lb)	Dimensions m (ft)						Tire Size
						Width	Length	Height	Loading Height	Dumping Height (55°)	Turning Circle	
735	AWR	02-05	272	32.7	29 858	3.31	10.89	3.70	2.97	6.96	8.14	26.5R25
			(365)	**(36)**	**(65,825)**	**(10'10")**	**(35'9")**	**(12'2")**	**(9'10")**	**(22'10")**	**(26'9")**	
735	B1N	05-10	324	32.7	31 391	3.43	10.89	3.70	2.98	6.81	16.27	26.5R25
			(435)	**(36)**	**(69,206)**	**(11'3")**	**(35'7")**	**(12'1")**	**(9'8")**	**(22'3")**	**(53'4")**	
735B	T4P	11-14	326	32.7	32 549	3.43	11.00	3.70	2.98	6.81	16.27	26.5R25
			(437)	**(36)**	**(71,758)**	**(11'3")**	**(36'1")**	**(12'1")**	**(9'8")**	**(22'3")**	**(53'4")**	
735B	L4D	11-14	326	32.7	32 549	3.43	11.00	3.70	2.98	6.81	16.27	26.5R25
			(437)	**(36)**	**(71,758)**	**(11'3")**	**(36'1")**	**(12'1")**	**(9'8")**	**(22'3")**	**(53'4")**	
D400	IMD	85-89	287	36.3	25 765	3.00	10.42	3.45	3.00	6.53	16.07	26.5R25
			(385)	**(40.0)**	**(56,800)**	**(9'10")**	**(34'2")**	**(11'4")**	**(9'10")**	**(21'5")**	**(52'9")**	
D400D	8TF	89-95	287	36.3	28 027	3.30	10.62	3.56	2.98	6.60	8.26	29.5R25
			(385)	**(40.0)**	**(61,800)**	**(10'8")**	**(34'10")**	**(11'8")**	**(9'9")**	**(21'8")**	**(27'2")**	
D400E	2YR	96-99	302	36.3	29 263	3.30	10.52	3.58	3.07	6.58	8.26	29.5R25
			(405)	**(40.0)**	**(64,495)**	**(10'10")**	**(34'6")**	**(11'9")**	**(10'1")**	**(21'7")**	**(27'1")**	
D400E Series II	8PS	99-01	302	36.3	31 650	3.43	10.65	3.58	3.10	6.92	8.45	29.5R25
			(405)	**(40.0)**	**(69,760)**	**(11'2")**	**(35'1")**	**(11'9")**	**(10'2")**	**(23'0")**	**(27'8")**	
D400E II Ejector	APF	99-01	302	36.3	32 840	3.50	11.00	3.58	3.07	N/A	8.45	29.5R25
			(405)	**(40.0)**	**(72,380)**	**(11'6")**	**(36'1")**	**(11'9")**	**(10'1")**		**(27'8")**	
740	AXM	01-05	309	38.1	32 693	3.43	10.89	3.75	3.18	7.07	8.14	29.5R25
			(415)	**(42)**	**(72,075)**	**(11'3")**	**(35'9")**	**(12'4")**	**(10'5")**	**(23'2")**	**(26'9")**	
740	B1P	05-10	350	39.5	33 100	3.52	10.89	3.75	3.24	7.09	16.27	29.5R25
			(469)	**(43.5)**	**(72,973)**	**(11'5")**	**(35'7")**	**(12'3")**	**(10'6")**	**(23'4")**	**(53'4")**	
740 Ejector	AZZ	01-05	309	38.1	35 270	3.50	11.59	3.75	3.07	3.07	8.63	29.5R25
			(415)	**(42)**	**(77,770)**	**(11'6")**	**(38'0")**	**(12'4")**	**(10'0")**	**(10'0")**	**(28'4")**	
740 Ejector	AZZ	01-05	309	38.1	35 270	3.50	11.59	3.75	3.07	3.07	8.63	29.5R25
			(415)	**(42)**	**(77,770)**	**(11'6")**	**(38'0")**	**(12'4")**	**(10'0")**	**(10'0")**	**(28'4")**	
740B	T4R	11-14	354	39.5	34 408	3.52	11.00	3.75	3.24	7.09	16.27	29.5R25
			(474)	**(43.5)**	**(75,857)**	**(11'5")**	**(36'1")**	**(12'3")**	**(10'6")**	**(23'4")**	**(53'4")**	
740B	L4E	11-14	352	39.5	34 408	3.52	11.00	3.75	3.24	7.09	16.27	29.5R25
			(472)	**(43.5)**	**(75,857)**	**(11'5")**	**(36'1")**	**(12'3")**	**(10'6")**	**(23'4")**	**(53'4")**	
740B EJ	T4S	11-14	354	38	36 984	3.53	11.70	3.75	3.07	—	17.28	29.5R25
			(474)	**(42)**	**(81,536)**	**(11'6")**	**(38'4")**	**(12'3")**	**(10'0")**	**—**	**(56'7")**	
740B EJ	L4F	11-14	352	38	36 984	3.53	11.70	3.75	3.07	—	17.28	29.5R25
			(472)	**(42)**	**(81,536)**	**(11'6")**	**(38'4")**	**(12'3")**	**(10'0")**	**—**	**(56'7")**	
D550	*	78-86	336	50.0	37 800	3.66	11.35	3.86	3.30	7.83	9.65	33.25R29
			(450)	**(55.0)**	**(83,400)**	**(12'0")**	**(37'3")**	**(12'8")**	**(10'10")**	**(25'8")**	**(31'8")**	
D550B	8SD	86-87	343	50.0	40 370	3.72	11.74	3.97	3.22	8.28	8.73	33.25R29
			(460)	**(55.0)**	**(89,000)**	**(12'2.5")**	**(38'6")**	**(13'0")**	**(10'6")**	**(27'2")**	**(28'8")**	

*Information not available — DJB models.



WHEEL DOZERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Kilowatts (Horsepower)	Approx. Oper. Wt. kg (lb)	Length (Dozer on ground) m (ft)	Tread m (ft)	Wheelbase m (ft)	Ground Clearance mm (in)	Trans-mission	Maximum Speeds km/h (mph) Fwd.	Rev.	
814B	90P	70-81	127	18 780	6.49	2.16	3.10	356	PS	32.7	39.3	*
			(170)	**(41,400)**	**(21'3")**	**(7'1")**	**(10'2")**	**(14)**	4F-4R	**(20.3)**	**(24.4)**	
814B	16Z	81-95	161	20 927	6.82			459	PS	29.9	34.1	*
			(216)	**(46,137)**	**(22'5")**			**(18)**	4F-4R	**(18.6)**	**(21.2)**	
814F	9DM	96-02	164	22 780		2.20	3.35	448	PS	29.9	34.1	
			(220)	**(50,115)**		**(7'3")**	**(11'0")**	**(18)**	4F-4R	**(18.6)**	**(21.2)**	
814F	BGF	03-06	179	21 713	6.82	2.20	3.35	448	PS	29.9	34.1	
			(240)	**(47,877)**	**(22'5")**	**(7'3")**	**(11'0")**	**(18)**	4F-4R	**(18.6)**	**(21.2)**	
814F II	BXG	06	173	20 755	6.90	2.20	3.60	366	PS	31	34.9	
			(232)	**(45,765)**	**(22'6")**	**(7'3")**	**(11'8")**	**(14)**	4F-4R	**(19.3)**	**21.8**	
824	29G	63-65	224	31 700	7.04	2.37	3.35	470	PS	34.1	34.1	
			(300)	**(70,000)**	**(23'1")**	**(7'10")**	**(11'8")**	**(18.2)**	3F-3R	**(21.2)**	**(21.2)**	
824B	36H	65-78	224	33 330	7.40	2.32	3.55	490	PS	29.8	29.8	
			(300)	**(73,480)**	**(24'3.5")**	**(7'7.5")**	**(11'8")**	**(19.4)**	3F-3R	**(18.5)**	**(18.5)**	
824C	85X	78-95	235	30 380	7.69	2.36	3.53	477	PS	33.2	37.8	
			(315)	**(66,975)**	**(25'2")**	**(7'7.5")**	**(11'7")**	**(18.8)**	4F-4R	**(20.6)**	**(23.5)**	
824G	4SN	96-02	235	26 620	8.02	2.44	3.70	383	PS	33	37.8	
			(315)	**(58,697)**	**(26'4")**	**(8'0")**	**(12'2")**	**(15)**	4F-4R	**(20.4)**	**(23.5)**	
824G II	AXB	03-04	253	28 724	8.02	2.44	3.70	383	PS	32.1	36.6	
			(339)	**(63,325)**	**(26'4")**	**(8'0")**	**(12'2")**	**(15)**	4F-4R	**(20)**	**(22.7)**	
824H	ASX	05-14	264	28 724	8.20	2.44	3.70	358	PS	32.1	36.6	
			(354)	**(63,325)**	**(26'9")**	**(8'0")**	**(12'2")**	**(14)**	4F-4R	**(20)**	**(22.7)**	
834	43E	63-74	298	40 300	7.75	2.54	3.80	510	PS	32.8	35.7	
		96-00	**(400)**	**(88,800)**	**(25'5")**	**(8'4")**	**(12'6")**	**(20.0)**	3F-3R	**(20.4)**	**(22.2)**	
834B	7BR	74-00	336	46 350	8.72		3.81	466	PS	34.1	41.8	
			(450)	**(102,200)**	**(28'7")**		**(12'6")**	**(18)**	4F-4R	**(21.2)**	**(25.9)**	
834G	6GZ	98-01	359	44 680	10.40	2.59	4.55	541	PS	38.5	23.0	**
			(481)	**(98,500)**	**(34'2")**	**(8'6")**	**(14'11")**	**(21)**	4F-3R	**(23.9)**	**(14.3)**	
834G	BPC	02-04	359	47 106	10.40	2.59	4.55	541	PS	38.5	23.0	
			(481)	**(103,849)**	**(34'2")**	**(8'6")**	**(14'11")**	**(21)**	4F-3R	**(23.9)**	**(14.3)**	
834H	BTX	05-13	372	47 106	10.42	2.59	4.55	531	PS	35.4	21.4	
			(489)	**(103,849)**	**(34'2")**	**(8'6")**	**(14'11")**	**(21)**	4F-3R	**(22)**	**(13.3)**	
844	2KZ	98-01	466	69 230	10.90	3.10	4.60	552	PS	22.5	25.0	***
			(625)	**(152,620)**	**(35'9")**	**(10'0")**	**(15'1")**	**(22)**	3F-3R	**(14.0)**	**(15.5)**	
844	BBN	01-05	466	70 815	10.90	3.10	4.60	552	PS	22.5	25.0	
			(625)	**(156,120)**	**(35'9")**	**(10'0")**	**(15'1")**	**(22)**	3F-3R	**(14.0)**	**(15.5)**	
844H	BTW	05-14	468	70 815	10.94	3.10	4.60	475	PS	21	23	
			(627)	**(156,120)**	**(35'9")**	**(10'0")**	**(15'1")**	**(19)**	3F-3R	**(13)**	**(14.3)**	
854G	1JW	97-99	597	99 400	13.40	3.30	5.89	691	PS	20.5	22.7	****
			(800)	**(219,125)**	**(44'0")**	**(10'10")**	**(19'3")**	**(27)**	3F-3R	**(12.7)**	**(14.1)**	
854G	AMP	00-04	597	99 400	13.40	3.30	5.39	691	PS	20.5	22.7	
			(800)	**(219,125)**	**(44'0")**	**(10'10")**	**(19'3")**	**(27)**	3F-3R	**(12.7)**	**(14.1)**	
854G	A4W	04-08	597	99 400	13.40	3.30	5.39	691	PS	20.5	22.7	
			(800)	**(219,125)**	**(44'0")**	**(10'10")**	**(19'3")**	**(27)**	3F-3R	**(12.7)**	**(14.1)**	
854K	221	08-11	597	98 100	13.45	3.30	5.89	691	PS	21.2	23.5	
			(801)	**(216,273)**	**(44'0")**	**(10'10")**	**(19'3")**	**(27)**	3F-3R	**(13.2)**	**(14.6)**	
854K	H9K	11-16	597	98 100	13.45	3.30	5.89	691	PS	21.2	23.5	
	H8M		**(801)**	**(216,273)**	**(44'0")**	**(10'10")**	**(19'3")**	**(27)**	3F-3R	**(13.2)**	**(14.6)**	

*Turbocharged, Articulated Steering.
**Move to "G" Series.
***New model from Tiger (590).
****New model from Tiger (790).



COMPACTORS

Model	Product Ident. No. Prefix	Years Built	Flywheel Kilowatts (Horsepower)	Approx. Oper. Wt. kg (lb)	Drum Width m (ft)	Articulated Steering Angle, Maximum	Transmission	Maximum Speeds km/h (mph) Fwd.	Rev.	
815	91P	70-81	127	17 300	0.97	44°	Power Shift	30.1	35.7	*
			(170)	**(38,200)**	**(3'2")**	Either Side	4F-4R	**(18.7)**	**(22.2)**	
815B	17Z	81-95	161	20 035	0.98	45°	Power Shift	37.5	42.9	*
			(216)	**(44,175)**	**(3'2")**	Either Side	4F-4R	**(23.3)**	**(26.6)**	
815F	1GN	96-02	164	20 952	0.98	36°	Power Shift	37.6	43.0	
			(220)	**(46,096)**	**(3'2")**	Either Side	4F-4R	**(23.3)**	**(26.7)**	
815F	BKL	03-06	179	20 755	0.98	36°	Power Shift	17.9	19.5	
			(240)	**(45,765)**	**(3'2")**	Either Side	3F-3R	**(11.1)**	**(12.1)**	
815F II	BYN	06	173	20 755	0.99	42°	Power Shift	17.6	19.5	
			(232)	**(45,756)**	**(3'3")**	Either side	3F-3R	**(11.0)**	**(12.2)**	
816	57U	72-81	127	18 550	1.02	44°	Power Shift	30.1	35.7	**
			(170)	**(40,900)**	**(3'4")**	Either Side	4F-4R	**(18.6)**	**(22.4)**	
816B	15Z	81-95	161	20 628	1.02		Power Shift	35.3	40.4	**
			(216)	**(45,477)**	**(3'4")**		4F-4R	**(22.0)**	**(25.1)**	
816F	5FN	96-02	164	20 879	1.02	42°	Power Shift	36.3	41.4	
			(220)	**(45,934)**	**(3'4")**	Either Side	4F-4R	**(22.5)**	**(25.7)**	
816F II	BZR	06	173	23 748	1.016	42°	Power Shift	9.5	10.6	
			(232)	**(52,364)**	**(3'4")**	Either side	2F-2R	**(5.9)**	**(6.6)**	
825B	43N	70-78	224	30 075	1.13	44°	Power Shift	29.8	29.8	
			(300)	**(66,300)**	**(3'8")**	Either Side		**(18.5)**	**(18.5)**	
825C	86X	78-96	231	32 400	1.13	42°	Power Shift	29.8	33.9	
			(310)	**(71,432)**	**(3'8")**	Either Side	4F-4R	**(18.5)**	**(21.1)**	
825G	6RN	96-02	235	31 740	1.13	42°	Power Shift	15.6	17.2	
			(315)	**(69,828)**	**(3'8")**	Either Side	3F-3R	**(9.7)**	**(10.7)**	
825G II	AXB	03-04	253	32 734	1.13	42°	Power Shift	15.6	17.2	
			(339)	**(72,164)**	**(3'8")**	Either Side	3F-3R	**(9.7)**	**(10.7)**	
825H	AZW	05-14	264	32 734	1.125	42°	Power Shift	15.6	17.2	
			(354)	**(72,164)**	**(3'7")**	Either side	3F-3R	**(9.7)**	**(10.7)**	
826C	87X	78-95	235	34 920	1.20	42°	Power Shift	32.5	37.2	
			(315)	**(76,990)**	**(3'11")**	Either Side	4F-4R	**(20.2)**	**(23.1)**	
826G	7LN	96-02	235	33 350	1.20	42°	Power Shift	11.2	13.5	
			(315)	**(73,537)**	**(3'11")**	Either Side	2F-2R	**(6.9)**	**(8.4)**	
826H	AWF	05-14	264	36 967	1.20	42°	Power Shift	9.7	10.6	
			(354)	**(81,498)**	**(3'11")**	Either side	2F-2R	**(6.03)**	**(6.59)**	
835	44N	70-74	298	35 900	1.22	44°	Power Shift	32.2	34.8	
			(400)	**(79,100)**	**(4'0")**	Either Side	3F-3R	**(20.0)**	**(21.6)**	
836	3RL	93-95	336	45 450	1.40	35°	Power Shift	11.3	14.0	*
	7FR	95-98	**(450)**	**(100,000)**	**(4'7")**	Either Side	2F-2R	**(7.0)**	**(8.7)**	
836G	7MZ	98-01	351	53 680	1.40	35°	Power Shift	6.0	10.2	
			(471)	**118,348**	**(4'7")**	Either Side	2F-2R	**(3.7)**	**(6.3)**	
836H	BXD	05-13	372	53 682	1.40	35°	Power Shift	10.9	11.4	
			(499)	**(118,348)**	**(4'7")**	Either side	2F-2R	**(6.8)**	**(7.1)**	

*Turbocharged, Articulated Steering.
**Turbocharged, ROPS Cab, Sleeve Metering Fuel System.



WHEEL LOADERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horse-power	Approx. Shipping Wt. kg (lb)	Rated Capacity m^3 (yd^3)	Breakout Force kg (lb)	Width Over Tires m (ft)	Ground Clearance mm (in)	Max. Reach at max. height mm (ft)	Dump Clearance at max. height m (ft)	Maximum Speeds km/h (mph) Fwd.	Rev.	Remarks
903C	MW4	14-16	42	4300	0.6	2345	1.71	395	885	2.43	16.0	16.0	
				(9500)	**(0.8)**	**(5171)**	**(5'7")**	**(16)**	**(2'11")**	**(8'0")**	**(10.0)**	**(10.0)**	
904B	B4L	05-08	52	4368	0.6	3633	1.70	218	664	2.38	20.0	20.0	
				(9630)	**(0.8)**	**(8009)**	**(5'7")**	**(8.6)**	**(2'2")**	**(7'10")**	**(12.4)**	**(12.4)**	
906H		07-12	70	5630	0.9	4283	1.84	300	810	2.40	35.0	35.0	
				(12,412)	**(1.2)**	**(9442)**	**(6'0")**	**(11.8)**	**(2'8")**	**(7'10")**	**(22.0)**	**(22.0)**	
906H2		12-15	71	5630	0.9	4283	1.84	300	810	2.40	35.0	35.0	
				(12,412)	**(1.2)**	**(9442)**	**(6'0")**	**(11.8)**	**(2'8")**	**(7'10")**	**(22.0)**	**(22.0)**	
907H		07-12	70	5810	1.0	4283	1.84	300	810	2.40	35.0	35.0	
				(12,809)	**(1.3)**	**(9442)**	**(6'0")**	**(11.8)**	**(2'8")**	**(7'10")**	**(22.0)**	**(22.0)**	
907H2		12-15	71	5810	1.0	4283	1.84	300	810	2.40	35.0	35.0	
				(12,809)	**(1.3)**	**(9442)**	**(6'0")**	**(11.8)**	**(2'8")**	**(7'10")**	**(22.0)**	**(22.0)**	
908H		07-12	79	6465	1.1	4793	1.99	340	855	2.50	35.0	35.0	
				(14,253)	**(1.4)**	**(10,566)**	**(6'6")**	**(13.0)**	**(2'10")**	**(8'3")**	**(22.0)**	**(22.0)**	
908H2		12-15	71	6465	1.1	4793	1.99	340	855	2.50	35.0	35.0	
				(14,253)	**(1.4)**	**(10,566)**	**(6'5")**	**(13.0)**	**(2'10")**	**(8'3")**	**(22.0)**	**(22.0)**	
910	80V	73-79	65	6100	1.0	4530	2.07	405	860	2.46	24.1	10.6	
				(13,400)	**(1.25)**	**(10,000)**	**(6'10")**	**(16)**	**(2'10")**	**(8'1")**	**(15.0)**	**(6.6)**	
910	40Y	79-89	65	6658	1.0	5838	2.07	405	930	2.40	23.9	10.6	
				(14,679)	**(1.25)**	**(12,870)**	**(6'10")**	**(16)**	**(3'0.6")**	**(7'10")**	**(14.8)**	**(6.6)**	
910	41Y	79-89	65	6658	1.0	5838	2.07	405	930	2.40	23.5	24.9	
				(14,679)	**(1.25)**	**(12,870)**	**(6'10")**	**(16)**	**(3'0.6")**	**(7'10")**	**(14.6)**	**(15.5)**	
910E	1SF	89-92	78	7298	1.3	6503	2.15	343	1000	2.57	34.0	22.4	3114 Engine
				(16,062)	**(1.7)**	**(14,339)**	**(7'0")**	**(13.5)**	**(3'3.4")**	**(8'5")**	**(21.1)**	**(13.9)**	Z Bar Linkage
910F	1SF	92-95	80	7009	1.3	6443	2.15	370	981	2.60	34.0	22.4	3114 Engine
				(15,452)	**(1.7)**	**(14,207)**	**(7'0")**	**(14.6)**	**(3'3")**	**(8'6")**	**(21.1)**	**(13.9)**	Z Bar Linkage
910K	AY4	14-16	74	7470	1.2	6741	2.26	348	820	2.81	40.0	40.0	
				(16,463)	**(1.6)**	**(14,857)**	**(7'5")**	**(13)**	**(2'8")**	**(9'2")**	**(25.0)**	**(25.0)**	
914G	7ZM 9WM PDF	95-14	95	7950	1.2-1.4	6200	2.258	456	973	2.659	35.0	35.0	C4.4 ACERT Engine
				(17,530)	**(1.6-1.8)**	**(14,007)**	**(7'5")**	**(16.3)**	**(3'2")**	**(8'9")**	**(22.0)**	**(22.0)**	Z Bar Linkage Hystat Transmission
914G2	KNP	12-14	95	7950	1.2-1.4	6200	2.258	456	973	2.659	35.0	35.0	C4.4 ACERT Engine
				(17,530)	**(1.6-1.8)**	**(14,007)**	**(7'5")**	**(16.3)**	**(3'2")**	**(8'9")**	**(22.0)**	**(22.0)**	Z Bar Linkage Hystat Transmission
914K	CD2	14-16	74	8467	1.4	7357	2.26	405	847	2.78	40.0	40.0	
				(18,663)	**(1.8)**	**(16,214)**	**(7'5")**	**(15)**	**(2'9")**	**(9'1")**	**(25.0)**	**(25.0)**	
916	2XB	86-92	85	8554	1.4	9124	2.33	322	926	2.65	24.8	25.0	3204 Engine
				(18,857)	**(1.75)**	**(20,115)**	**(7'8")**	**(12.7)**	**(3'0.5")**	**(8'9")**	**(15.4)**	**(15.5)**	Z Bar Linkage
918F	3TJ	92-94	98	8973	1.5	9795	2.33	318	802	2.78	37.0	24.5	3114 Engine
				(19,785)	**(2.0)**	**(21,598)**	**(91.6")**	**(13)**	**(2'8")**	**(9'1")**	**(23.0)**	**(15.2)**	Z Bar Linkage
920	62K	69-84	80	8440	1.2	7901	2.16	335	740	2.77	43.8	23.2	
				(18,600)	**(1.5)**	**(17,419)**	**(7'1")**	**(13)**	**(2'5")**	**(9'1")**	**(27.2)**	**(14.4)**	
922A	59A	60-62	80	7350	0.93	6850	2.12	368	655	2.60	30.4	32.8	
				(16,200)	**(1.25)**	**(15,100)**	**(7'0")**	**(15)**	**(2'2")**	**(8'7")**	**(18.9)**	**(20.4)**	
922B	88J	62-68	80	7670	1.15	9000	2.25	390	680	2.60	33.6	42.9	
				(16,900)	**(1.5)**	**(19,900)**	**(7'5")**	**(16)**	**(2'3")**	**(8'7")**	**(20.9)**	**(26.7)**	

Wheel Loaders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Horse-power	Approx. Shipping Wt. kg (lb)	Rated Capacity m^3 (yd^3)	Breakout Force kg (lb)	Width Over Tires m (ft)	Ground Clearance mm (in)	Max. Reach at max. height mm (ft)	Dump Clearance at max. height m (ft)	Maximum Speeds km/h (mph) Fwd.	Rev.	Remarks
924F	5NN	94-99	105	9025	1.7	9553	2.33	318	855	2.70	38.2	23.6	
				(19,900)	**(2.25)**	**(21,067)**	**(7'6")**	**(12.5)**	**(2'8")**	**(8'10")**	**(23.6)**	**(14.8)**	
924G	9SW	99-02	120	9615	1.8	9876	2.36	370	1318	2.828	38.5	21.8	
				(21,197)	**(2.3)**	**(21,772)**	**(7'9")**	**(15)**	**(4'4")**	**(9'4")**	**(23.9)**	**(13.5)**	
924G	3PZ	99-02	120	9615	1.8	9876	2.36	370	1318	2.828	38.5	21.8	
				(21,197)	**(2.3)**	**(21,772)**	**(7'9")**	**(15)**	**(4'4")**	**(9'4")**	**(23.9)**	**(13.5)**	
924G	AAN	99-02	120	9615	1.8	9876	2.36	370	1318	2.828	38.5	21.8	
				(21,197)	**(2.3)**	**(21,772)**	**(7'9")**	**(15)**	**(4'4")**	**(9'4")**	**(23.9)**	**(13.5)**	
924G	DDA	02-07	129	9977	1.8	11 452	2.36	370	1451	2.918	38.5	21.8	
				(21,996)	**(2.3)**	**(25,247)**	**(7'9")**	**(15)**	**(4'10")**	**(9'7")**	**(23.9)**	**(13.5)**	
924G	RBB	02-07	129	9977	1.8	11 452	2.36	370	1451	2.918	38.5	21.8	
				(21,996)	**(2.3)**	**(25,247)**	**(7'9")**	**(15)**	**(4'10")**	**(9'7")**	**(23.9)**	**(13.5)**	
924G	WMB	02-07	129	9977	1.8	11 452	2.36	370	1451	2.918	38.5	21.8	
				(21,996)	**(2.3)**	**(25,247)**	**(7'9")**	**(15)**	**(4'10")**	**(9'7")**	**(23.9)**	**(13.5)**	
924Gz	6YW	99-02	120	9615	1.8	9876	2.36	370	1318	2.828	38.5	21.8	
				(21,197)	**(2.3)**	**(21,772)**	**(7'9")**	**(15)**	**(4'4")**	**(9'4")**	**(23.9)**	**(13.5)**	
924Gz	3DZ	99-03	120	9615	1.8	9876	2.36	370	1318	2.828	38.5	21.8	
				(21,197)	**(2.3)**	**(21,772)**	**(7'9")**	**(15)**	**(4'4")**	**(9'4")**	**(23.9)**	**(13.5)**	
924Gz	AAB	99-04	120	9615	1.8	9876	2.36	370	1318	2.828	38.5	21.8	
				(21,197)	**(2.3)**	**(21,772)**	**(7'9")**	**(15)**	**(4'4")**	**(9'4")**	**(23.9)**	**(13.5)**	
924Gz	DFZ	02-04	129	9615	1.8	9876	2.36	370	1318	2.828	38.5	21.8	
				(21,197)	**(2.3)**	**(21,772)**	**(7'9")**	**(15)**	**(4'4")**	**(9'4")**	**(23.9)**	**(13.5)**	
924Gz	RTA	02-07	129	9615	1.8	9876	2.36	370	1318	2.828	38.5	21.8	
				(21,197)	**(2.3)**	**(21,772)**	**(7'9")**	**(15)**	**(4'4")**	**(9'4")**	**(23.9)**	**(13.5)**	
924Gz	WGX	02-07	129	9615	1.8	9876	2.36	370	1318	2.828	38.5	21.8	
				(21,197)	**(2.3)**	**(21,772)**	**(7'9")**	**(15)**	**(4'4")**	**(9'4")**	**(23.9)**	**(13.5)**	
924H	HXC	07-13	132	11 635	2.1	9003	2.49	436	1060	2.759	39.7	22.9	
				(25,651)	**(2.7)**	**(19,848)**	**(8'2")**	**(17)**	**(3'6")**	**(9'1")**	**(24.7)**	**(14.2)**	
924Hz	JZZ	10-13	132	11 021	2.1	8975	2.49	436	859	2.757	39.7	22.9	
				(24,297)	**(2.7)**	**(19,787)**	**(8'2")**	**(17)**	**(2'10")**	**(9'1")**	**(24.7)**	**(14.2)**	
924K	PWR	11-15	146	12 868	1.9	10 223	2.54	400	1024	2885	40.0	40.0	
				(28,360)	**(2.5)**	**(22,531)**	**(8'4")**	**(15.7)**	**(3'4")**	**(9'5")**	**(25.0)**	**(25.0)**	
924K	HJF	13-15	141	11 550	1.7	12 273	2.54	397	950	2857	40.0	40.0	
	ENC			**(25,464)**	**(2.2)**	**(27,057)**	**(8'4")**	**(15.7)**	**(3'1")**	**(9'4")**	**(25.0)**	**(25.0)**	
926	94Z	84-87	105	8800	1.21	5070	2.33	341	924	2.67	30.3	32.3	
				(19,400)	**(1.75)**	**(11,179)**	**(7'8")**	**(13.5)**	**(3'0")**	**(8'9")**	**(18.8)**	**(20.0)**	
926E	94Z	87-92	110	9432	1.7	10 044	2.33	341	1003	2.75	34.2	36.8	3204 Engine
				(20,794)	**(2.25)**	**(22,143)**	**(7'8")**	**(13.5)**	**(3'3.5")**	**(9'0")**	**(21.2)**	**(22.9)**	Z Bar Linkage
928F	2XL	93-96	120	10 870	2.1	10 090	2.43	318	956	2.74	36.5	21.1	3116 Engine
				(23,920)	**(2.75)**	**(22,200)**	**(8'0")**	**(13)**	**(3'2")**	**(9'0")**	**(22.6)**	**(13.1)**	Z Bar Linkage
928G	6XR	96-02	125	11 250	2.0	11 723	2.44	408	1455	2.879	37.7	25.8	
				(24,802)	**(2.6)**	**(25,849)**	**(8'0")**	**(16)**	**(4'9")**	**(9'5")**	**(23.4)**	**(16)**	
928G	7SR	96-02	125	11 250	2.0	11 723	2.44	408	1455	2.879	37.7	25.8	
				(24,802)	**(2.6)**	**(25,849)**	**(8'0")**	**(16)**	**(4'9")**	**(9'5")**	**(23.4)**	**(16)**	
928Gz	DJD	02-07	143	11 250	2.0	11 723	2.44	408	1455	2.879	37.7	25.8	
				(24,802)	**(2.6)**	**(25,849)**	**(8'0")**	**(16)**	**(4'9")**	**(9'5")**	**(23.4)**	**(16)**	
928Gz	WLG	02-07	143	11 250	2.0	11 723	2.44	408	1455	2.879	37.7	25.8	
				(24,802)	**(2.6)**	**(25,849)**	**(8'0")**	**(16)**	**(4'9")**	**(9'5")**	**(23.4)**	**(16)**	
928Hz	CXK	07-13	152	12 618	2.3	9002	2.57	408	963	2.842	37.6	26.7	
				(27,818)	**(3.0)**	**(19,846)**	**(8'5")**	**(16)**	**(3'2")**	**(9'4")**	**(23.4)**	**(16.6)**	

Wheel Loaders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Horse-power	Approx. Shipping Wt. kg (lb)	Rated Capacity m^3 (yd^3)	Breakout Force kg (lb)	Width Over Tires m (ft)	Ground Clearance mm (in)	Max. Reach at max. height mm (ft)	Dump Clearance at max. height m (ft)	Maximum Speeds km/h (mph) Fwd.	Rev.	Remarks
930	41K	68-85	100	9660	1.7	7900	2.39	348	1350	2.79	44.2	23.3	Z Bar Linkage
				(21,300)	**(2.25)**	**(17,410)**	**(7'10")**	**(13.7)**	**(3'9")**	**(9'2")**	**(27.5)**	**(14.5)**	
930G	TWR	05-07	149	12 756	2.3	14 567	2.41	421	1542	2.917	38.3	24.1	
				(28,122)	**(3.0)**	**(32,115)**	**(7'11")**	**(16)**	**(5'1")**	**(9'7")**	**(23.8)**	**(15)**	
930G	TFR	05-07	149	12 756	2.3	14 567	2.41	421	1542	2.917	38.3	24.1	
				(28,122)	**(3.0)**	**(32,115)**	**(7'11")**	**(16)**	**(5'1")**	**(9'7")**	**(23.8)**	**(15)**	
930H	DHC	07-13	152	13 174	2.3	12 852	2.57	411	995	2.773	39.7	22.9	
				(29,044)	**(3.0)**	**(28,334)**	**(8'5")**	**(16)**	**(3'3")**	**(9'1")**	**(24.7)**	**(14.2)**	
930K	RHN	11-15	160	13 829	2.1	12 366	2.54	400	1064	2828	40.0	40.0	
				(30,479)	**(2.7)**	**(27,254)**	**(8'4")**	**(15.7)**	**(3'5")**	**(9'3")**	**(25.0)**	**(25.0)**	
930K	EYE	13-15	160	13 135	2.1	12 366	2.54	397	1033	2855	40.0	40.0	
	DYB			**(28,958)**	**(2.7)**	**(27,254)**	**(8'4")**	**(15.7)**	**(3'4")**	**(9'4")**	**(25.0)**	**(25.0)**	
936	33Z	83-87	125	11 884	2.1	12 514	2.56	329	1055	2.80	34.4	38.4	
				(26,200)	**(2.75)**	**(28,708)**	**(8'4.5")**	**(13)**	**(3'0")**	**(9'2")**	**(21.4)**	**(23.9)**	
936E	33Z	87-92	135	12 300	2.3	12 920	2.56	379	1026	2.87	40.6	45.3	
				(27,000)	**(3.0)**	**(28,483)**	**(8'5")**	**(14.9)**	**(2'11")**	**(9'2")**	**(25.2)**	**(28.2)**	
936F	8AJ	92-94	140	12 300	2.3	12 920	2.58	379	997	2.84	42.3	46.7	Box Frame
				(27,060)	**(3.0)**	**(28,483)**	**(8'5")**	**(14.9)**	**(3'3")**	**(9'4")**	**(26.3)**	**(29.6)**	
938F		94-97	140	13 030	2.5	12 330	2.61	400	1004	2.85	37.9	22.0	Wet Disc Brakes
				(28,730)	**(3.25)**	**(27,180)**	**(8'7")**	**(16)**	**(3'4")**	**(9'4")**	**(23.6)**	**(13.7)**	
938G	4YS	97-02	160	12 962	2.8	11 227	2.60	400	1055	2.72	39.4	23.4	
				(28,578)	**(3.65)**	**(24,770)**	**(8'6")**	**(16)**	**(3'6")**	**(8'11")**	**(24.5)**	**(14.5)**	
938G	CRD	02-07	160	13 452	2.8	11 156	2.60	400	1068	2.771	38.8	23.3	
Series II				**(29,656)**	**(3.66)**	**(24,594)**	**(8'6")**	**(16)**	**(3'6")**	**(9'1")**	**(24.1)**	**(14.5)**	
938H	MJC	05-12	197	14 919	2.5	13 751	2.65	397	1019	2.849	41.1	25.0	
				(32,881)	**(3.3)**	**(30,316)**	**(8'8")**	**(16)**	**(3'4")**	**(9'4")**	**(25.5)**	**(15.5)**	
938K	SWL	11-15	173	15 928	2.5	13 170	2.675	390	1146	2834	40.0	40.0	
				(35,104)	**(3.3)**	**(29,027)**	**(8'9")**	**(15.3)**	**(3'9")**	**(9'3")**	**(25.0)**	**(25.0)**	
938K	XXT	13-15	188	15 146	2.5	13 170	2.675	286	1108	2869	40.0	40.0	
	HFW			**(33,301)**	**(3.3)**	**(29,027)**	**(8'9")**	**(11.2)**	**(3'7")**	**(9'4")**	**(25.0)**	**(25.0)**	
944	87J	59-68	100	10 100	1.53	9800	2.40	450	905	2.96	38.5	46.6	
				(22,000)	**(2.0)**	**(21,700)**	**(7'10")**	**(18)**	**(3'0")**	**(9'9")**	**(23.9)**	**(28.9)**	
950	81J	68-81	130	12 930	1.53	10 320	2.41	381	740	2.82	35.9	42.5	Articulated Steering,
				(28,500)	**(2.07)**	**(22,760)**	**(7'11")**	**(15)**	**(2'5")**	**(9'3")**	**(22.3)**	**(26.4)**	4 Wheel Drive
950B	22Z	81-87	155	14 650	2.9	15 680	2.67	427	1125	2.95	36.4	39.4	Z Bar Linkage
				(32,300)	**(3.75)**	**(35,895)**	**(5'9")**	**(16.8)**	**(3'8")**	**(9'8")**	**(22.6)**	**(24.5)**	
950E	22Z	87-91	160	15 856	3.1	13 586	2.76	400	1160	2.85	36.2	39.9	23.5-25 Std. Tires
				(34,883)	**(4.0)**	**(29,925)**	**(9'0")**	**(15.7)**	**(3'10")**	**(9'4")**	**(22.4)**	**(24.7)**	
950F	7ZF	90-92	170	16 086	3.1	14 954	2.76	474	1160	2.85	39.3	43.0	Wet Disc Brakes
				(35,463)	**(4.0)**	**(32,974)**	**(9'0")**	**(18.7)**	**(3'10")**	**(9'4")**	**(24.4)**	**(26.7)**	
950F	5SK	93-98	170	16 880	3.1	14 960	2.76	460	1180	2.83	38.7	42.7	Integral ROPS
Series II				**(37,220)**	**(4.0)**	**(32,980)**	**(9'0")**	**(18.1)**	**(3'10")**	**(9'3")**	**(24.0)**	**(26.5)**	Electronic Shift
950G	3JW	98-02	183	16 904	3.5	14 888	2.89	400	1270	2.89	37.0	40.7	
	4BS			**(37,266)**	**(4.5)**	**(32,810)**	**(9'6")**	**(16)**	**(4'2")**	**(9'6")**	**(23.0)**	**(25.3)**	
950G	AXX	02-05	183	17 780	3.1	15 724	2.89	412	1202	2.92	37.0	40.0	
Series II	AXR			**(39,198)**	**(4.05)**	**(34,666)**	**(9'6")**	**(16.2)**	**(3'11")**	**(9'7")**	**(23.0)**	**(24.9)**	

Wheel Loaders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Horse-power	Approx. Shipping Wt. kg (lb)	Rated Capacity m^3 (yd^3)	Breakout Force kg (lb)	Width Over Tires m (ft)	Ground Clearance mm (in)	Max. Reach at max. height mm (ft)	Dump Clearance at max. height m (ft)	Maximum Speeds km/h (mph) Fwd.	Rev.	Remarks
960F	9ZJ	94-98	200	18 070	3.5	14 500	2.77	454	1030	2.92	39.4	43.2	Material Handler
				(39,840)	**(4.5)**	**(31,970)**	**(9'1")**	**(17.9)**	**(3'5")**	**(9'6")**	**(24.5)**	**(26.8)**	
962G	4PW	98-02	200	17 941	3.8	14 480	2.90	400	1250	2.77	37.0	40.7	
	5AS			**(39,553)**	**(5.0)**	**(31,950)**	**(9'8")**	**(16)**	**(4'2")**	**(9'2")**	**(23.0)**	**(25.3)**	
962G	AXY	02-05	204	18 547	3.5	14 072	2.89	412	1308	2.81	37.0	40.0	
Series II	AXS			**(40,889)**	**(4.58)**	**(31,024)**	**(9'6")**	**(16.2)**	**(4'2")**	**(9'2")**	**(23.0)**	**(24.9)**	
966A	33A	60-63	140	13 060	2.10	13 470	2.70	450	900	2.95	43.0	51.5	
				(28,800)	**(2.75)**	**(29,700)**	**(8'10")**	**(18)**	**(3'0")**	**(9'8")**	**(26.7)**	**(32.3)**	
966B	75A	63-68	150	14 300	2.29	14 000	2.70	400	900	2.95	38.5	46.3	
				(31,500)	**(3.0)**	**(31,000)**	**(8'10")**	**(16)**	**(3'0")**	**(9'8")**	**(23.9)**	**(28.8)**	
966C	76J	68-81	170	16 730	3.1	11 600	2.77	400	1420	2.95	38.0	45.1	
				(36,890)	**(4.0)**	**(25,578)**	**(9'1")**	**(15.7)**	**(4'8")**	**(9'8")**	**(23.6)**	**(28.0)**	
966D	99Y	80-87	200	19 730	3.3	20 972	2.86	451	1230	3.14	34.3	38.1	Z Bar Linkage
				(43,500)	**(4.25)**	**(48,150)**	**(9'4.8")**	**(17.8)**	**(4'0")**	**(10'3.5")**	**(21.3)**	**(23.7)**	
966E	99Y	87-90	216	20 324	3.8	18 939	2.94	476	1290	2.97	38.2	43.6	26.5-25 Std. Tires
				(44,767)	**(5.0)**	**(41,715)**	**(9'8")**	**(18.7)**	**(4'3")**	**(9'9")**	**(23.7)**	**(27.0)**	
966F	4YG	90-93	220	20 466	3.8	20 493	2.94	476	1280	2.98	37.6	42.6	
				(45,119)	**(5.0)**	**(45,187)**	**(9'8")**	**(18.7)**	**(4'2")**	**(9'9")**	**(23.4)**	**(26.4)**	Wet Disc Brakes
966F	1SL	93-98	220	21 290	3.8	20 490	2.94	476	1277	2.98	38.8	43.9	Integral ROPS
Series II				**(46,950)**	**(5.0)**	**(45,180)**	**(9'8")**	**(18.7)**	**(4'2")**	**(9'9")**	**(24.1)**	**(27.3)**	Electronic Shift
966G	3SW	98-02	235	22 068	4.0	19 986	2.97	565	1295	3.10	37.1	42.2	
	3ZS			**(48,651)**	**(5.25)**	**(44,120)**	**(9'9")**	**(22)**	**(4'3")**	**(10'2")**	**(23.1)**	**(26.2)**	
966G	ANZ	01-05	246	22 870	4.25	19 273	3.04	471	1328	3.07	37.2	38.5	
Series II	ANT			**(50,400)**	**(5.5)**	**(42,477)**	**(9'11")**	**(18.5)**	**(4'4")**	**(10'0")**	**(23.1)**	**(23.9)**	
966K XE	NGX	12-14	299	24 189	4.2	17 641	2.99	475	1388	2.99	40.0	28.0	Advanced
				(53,311)	**(5.5)**	**(38,984)**	**(9'9")**	**(18.7)**	**(4'6")**	**(9'9")**	**(24.9)**	**(17.4)**	Power Train
970F	7SK	93-98	250	23 690	4.7	16 510	2.94	482	1357	3.22	37.3	42.7	Material Handler
				(52,240)	**(6.0)**	**(36,400)**	**(9'8")**	**(19)**	**(4'5")**	**(10'6")**	**(23.2)**	**(26.5)**	New Model
972G	4WW	98-02	265	24 468	4.7	21 618	2.97	565	1255	3.15	37.0	41.9	
	7LS			**(53,942)**	**(6.0)**	**(47,580)**	**(9'9")**	**(22)**	**(4'1")**	**(10'4")**	**(22.9)**	**(26.0)**	
972G	AWP	01-05	270	25 490	4.7	22 036	2.95	565	1325	3.23	36.9	38.8	
Series II	ANY			**(56,180)**	**(6.0)**	**(48,554)**	**(9'9")**	**(22.2)**	**(4'4")**	**(10'7")**	**(22.9)**	**(24.0)**	
980	42H	66-70	235	20 000	3.06	18 860	2.87	399	1190	3.07	42.0	26.7	
				(44,000)	**(4.0)**	**(41,570)**	**(9'5")**	**(16)**	**(3'11")**	**(10'1")**	**(26.1)**	**(16.6)**	
980B	89P	70-78	260	23 360	3.44-4.21	15 900	3.11	—	1120	3.20	43.0	27.4	
				(51,500)	**(4.5-5.5)**	**(35,100)**	**(10'2")**	**—**	**(3'8")**	**(10'6")**	**(26.7)**	**(17.0)**	
980C	63X	79-91	270	27 559	5.2	23 188	3.15	417	1480	3.19	34.6	39.6	Dual
				(60,755)	**(6.75)**	**(51,121)**	**(10'4")**	**(16.4)**	**(4'10")**	**(10'6")**	**(21.5)**	**(24.5)**	Z Bar Linkage
980F	8JN	91-92	275	27 580	5.3	23 188	3.15	469	1500	3.16	37.4	42.8	Electronic Shift
				(60,800)	**(7.0)**	**(51,121)**	**(10'4")**	**(18.5)**	**(4'11")**	**(10'5")**	**(23.2)**	**(26.6)**	
980F	4RN	92-95	275	27 580	5.3	23 188	3.15	469	1500	3.16	37.4	42.8	
Series II				**(60,800)**	**(7.0)**	**(51,121)**	**(10'4")**	**(18.5)**	**(4'11")**	**(10'5")**	**(23.2)**	**(26.6)**	
980G	2KR	95-01	300	29 480	5.4	23 760	3.25	467	1540	3.27	37.4	42.8	
				(65,000)	**(7.0)**	**(52,390)**	**(10'8")**	**(18.4)**	**(5'1")**	**(10'8")**	**(23.2)**	**(26.6)**	
980G	AWH	01-05	311	30 207	5.7	21 414	3.25	467	1545	3.27	37.4	42.8	
Series II				**(66,576)**	**(7.5)**	**(47,277)**	**(10'8")**	**(18.4)**	**(5'1")**	**(10'9")**	**(23.2)**	**(26.6)**	

Wheel Loaders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Horse-power	Approx. Shipping Wt. kg (lb)	Rated Capacity m^3 (yd^3)	Breakout Force kg (lb)	Width Over Tires m (ft)	Ground Clearance mm (in)	Max. Reach at max. height mm (ft)	Dump Clearance at max. height m (ft)	Maximum Speeds km/h (mph) Fwd.	Rev.	Remarks
988	87A	63-76	325	35 800	4.6-5.4	21 380	3.20	570	1450	3.33	30.6	30.6	
				(79,000)	**(6.0-7.0)**	**(47,130)**	**(10'7")**	**(22.5)**	**(4'9")**	**(10'11")**	**(19.0)**	**(19.0)**	
988B	50W	76-93	375	43 365	5.4-6.3	36 330	3.52	474	2150	3.19	36.2	41.4	3408 Engine
				(95,600)	**(7.0-8.25)**	**(80,100)**	**(11'7")**	**(18)**	**(7'1")**	**(10'5")**	**(22.5)**	**(25.7)**	Z Bar Linkage
988F	8YG	93-95	400	43 540	5.4-6.1	37 363	3.52	496	1830	3.21	35.1	23.5	Bucket/HP increase
				(95,900)	**(7.0-8.0)**	**(82,371)**	**(11'7")**	**(19)**	**(6'0")**	**(10'6")**	**(21.8)**	**(14.6)**	STIC™ Steer
988F	2ZR	95-00	475	45 678	6.1-6.9	37 400	3.52	496	1611	3.22	35.1	23.5	3408E Engine
Series II				**(100,492)**	**(8.0-9.0)**	**(82,282)**	**(11'7")**	**(19)**	**(5'3")**	**(10'7")**	**(21.8)**	**(14.6)**	Axle Shaft Brakes
988G	2TW	01-05	475	50 040	6.3-7.0	46 950	3.47	549	2113	4.00	38.7	22.3	4.25 m
	BNH			**(110,320)**	**(8.2-9.2)**	**(103,500)**	**(11'5")**	**(21.6)**	**(6'11")**	**(13'1")**	**(24.0)**	**(13.8)**	6 Bar Linkage
988H	BXY	05-15	501	50 144	6.4-7.7	41 531	3.47	549	2153	3.31	38.6	25.1	3.88 m
	A7A			**(110,549)**	**(8.3-10)**	**(91,560)**	**(11'5")**	**(21.6)**	**(7'1")**	**(10'10")**	**(24.0)**	**(15.6)**	6 Bar Linkage
990	7HK	93-95	610	72 910	8.6	59 776	4.13	552	2070	3.99	22.5	25.0	ICTC &
				(160,600)	**(11.2)**	**(131,784)**	**(13'6")**	**(21.7)**	**(6'10")**	**(13'1")**	**(14.0)**	**(15.5)**	New Model
990	4FR	96-05	625	72 200	8.4-9.2	63 100	4.00	490	1990	4.05	22.5	25.0	3412E Engine
Series II				**(159,170)**	**(11-12)**	**(138,800)**	**(13'1")**	**(19.3)**	**(6'6")**	**(13'3")**	**(14.0)**	**(15.5)**	
990H	BWX	05-14	627	77 842	8.6-9.2	602	4.16	478	8.07	4220	22.4	24.8	Standard Lift
				(171,642)	**(11.25-12)**	**(135,429)**	**(13'3")**	**(18.8)**	**(26'6")**	**(13'10")**	**(13.92)**	**(15.41)**	8.6 m^3/**11.2 yd^3** Bucket
992	25K	68-73	550	47 670	7.65	36 900	3.93	530	2820	4.52	35.6	38.5	
				(105,100)	**(10.0)**	**(81,360)**	**(12'11")**	**(21)**	**(8'3")**	**(14'10")**	**(22.1)**	**(23.8)**	
992B	25K	73-77	550	64 320	7.65	29 330	—	—	1930	4.34	40.2	43.6	
				(141,800)	**(10.0)**	**(84,660)**	**—**	**—**	**(6'4")**	**(14'3")**	**(25.0)**	**(27.1)**	
992C	42X	77-81	690	85 640	9.6	66 240	4.55	533	2310	4.17	21.1	23.3	3412 PCT Engine
				(188,800)	**(12.5)**	**(146,030)**	**(14'11")**	**(21)**	**(7'7")**	**(13'8")**	**(13.1)**	**(14.5)**	Z Bar Linkage
992C	49Z	81-92	690	88 430	10.4	66 285	4.50	544	2310	4.17	21.0	22.9	3412 DIT Engine
				(194,950)	**(13.5)**	**(146,132)**	**(14'9")**	**(21)**	**(7'7")**	**(13'8")**	**(13.0)**	**(14.2)**	
992D	7MJ	92-97	710	88 690	10.7	62 670	4.50	544	2300	4.17	21.0	22.9	
				(195,125)	**(14.0)**	**(137,870)**	**(14'9")**	**(21)**	**(7'7")**	**(13'8")**	**(13.0)**	**(14.2)**	
992G	7HR	98-00	800	91 540	11.5-12.3	62 650	4.50	691	2300	4.60	20.2	22.7	6 Bar Linkage
				(201,810)	**(15-16)**	**(137,840)**	**(14'9")**	**(27.2)**	**(7'7")**	**(15'3")**	**(12.5)**	**(14.1)**	"G" Series
992K	H4C	07-11	801	97 294	10.7-12.3	584.66	—	682	9313	4480	20.6	22.4	10.7 m^3/**14 yd^3**
				(214,535)	**(14-16)**	**(128,917)**	**—**	**(26)**	**(30'6")**	**(14'8")**	**(12.8)**	**(13.9)**	Bucket
992K	ZMX	11-16	801	97 294	10.7-12.3	584.66	—	682	9313	4480	20.6	22.4	10.7 m^3/**14 yd^3**
	880			**(214,535)**	**(14-16)**	**(128,917)**	**—**	**(26)**	**(30'6")**	**(14'8")**	**(12.8)**	**(13.9)**	Bucket
993K	Z9K	07-12	945	133 637	12.8-14.5	72 347	4.93	783	9313	4849	20.1	12.5	12.8 m^3/**16.7 yd^3**
				(294,800)	**(16.7-19)**	**(159,500)**	**(16'2")**	**(30.8)**	**(30'7")**	**(15'11")**	**(22.1)**	**(13.7)**	Bucket
994	9YF	90-98	1250	177 000	10.3	103 420	5.20	662	2692	6.20	24.7	26.6	
				(390,300)	**(13.4)**	**(228,000)**	**(17'1")**	**(26)**	**(8'10")**	**(20'4")**	**(15.0)**	**(16.5)**	
994D	3TZ	98-05	1250	191 200	17.0	96 939	5.4	676	2157	5698	24.1	26.6	
				(420,640)	**(22.5)**	**(213,265)**	**(17'8")**	**(26)**	**(7'1")**	**(18'8")**	**(15.0)**	**(16.5)**	
994F	442	05-11	1577	195 434	18.0	104 082	5.4	811	2721	6002	24	25.6	Ext. High Lift
				(429,955)	**(23.5)**	**(229,305)**	**(17'8")**	**(32)**	**(8'11")**	**(19'8")**	**(14.9)**	**(15.9)**	Available
994H	DWC	11-14	1577	195 434	18.0	104 082	5.4	811	2721	6002	24	25.6	Ext. High Lift
				(429,955)	**(23.5)**	**(229,305)**	**(17'8")**	**(32)**	**(8'11")**	**(19'8")**	**(14.9)**	**(15.9)**	Available



TRACK LOADERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Rated Capacity m^3 (yd^3)	Dimensions Length** m (ft)	Dimensions Width m (ft)	Dimensions Height m (ft)	Remarks
931	78U	72-79	62	6940 **(15,300)**	0.77 **(1.0)**	2.74 **(9'0")**	1.78 **(5'10")**	1.96 **(6'5")**	
931 LGP	10N	75-79	62	7498 **(16,530)**	1.15 **(1.5)**	2.74 **(9'0")**	2.29 **(7'6")**	1.98 **(6'6")**	
931B	29Y	79-88	65	7362 **(16,230)**	0.8 **(1.0)**	4.13 **(13'9")**	1.84 **(6'0.5")**	2.68 **(8'10")**	
931B LGP	30Y	79-88	65	8089 **(17,834)**	0.8 **(1.0)**	3.84 **(12'7")**	2.41 **(7'11")**	2.68 **(8'10")**	
931C	2BJ1 7HF		67	7595 **(16,743)**	0.77 **(1.0)**	2.74 **(9'0")**	1.78 **(5'10")**	2.68 **(8'10")**	
931C LGP	6RF1 8AF		67	8170 **(18,012)**	0.77 **(1.0)**	2.74 **(9'0")**	1.78 **(5'10")**	2.68 **(8'10")**	
931C Series II	9AG 6AJ	90-93	70	8047 **(17,742)**	0.83 **(1.08)**	4.14 **(13'1")**	1.97 **(6'5")**	2.68 **(8'10")**	
933C	11A	55-58	50	7030 **(15,500)**	0.77 **(1.0)**	4.22 **(13'10")**	1.77 **(5'10")**	1.91 **(6'4")**	Integral loader
933E	11A	58-65	50	7640 **(16,850)**	0.77 **(1.0)**	4.22 **(13'10")**	1.77 **(5'10")**	1.40 **(6'3")**	Integral loader
933G	42A	65-68	60	7900 **(17,500)**	0.86 **(1.125)**	4.31 **(14'2")**	1.77 **(5'10")**	2.15 **(7'1")**	Sealed Track
935B	30F	87-88	75	7899 **(17,414)**	1.0 **(1.25)**	4.19 **(13'9")**	1.96 **(6'5")**	2.68 **(8'10")**	
935C	8CF		78	8205 **(18,089)**	1.0 **(1.3)**	4.19 **(13'9")**	1.96 **(6'5")**	2.68 **(8'10")**	
935C Series II	SDJ	90-93	80	8759 **(19,311)**	1.0 **(1.3)**	4.37 **(14'4")**	1.97 **(6'5")**	2.68 **(8'10")**	
939C	6DS	96-01	90	9578 **(21,072)**	1.2 **(1.5)**	4.36 **(14'4")**	1.96 **(6'5")**	2.77 **(9'1")**	
941	80H	68-72	70	8900 **(19,700)**	0.96 **(1.25)**	4.50 **(14'10")**	1.86 **(6'1")**	2.75 **(9'0")***	Electric Start
941B	80H	68-81	80	11 294 **(24,900)**	1.15 **(1.5)**	4.50 **(14'10")**	1.98 **(6'6")**	2.75 **(9'0")***	HP Increase, Hydraulic Track Adjusters
943	31Y	80-85	80	11 750 **(25,900)**	1.15 **(1.5)**	5.426 **(17'10")**	2.21 **(8'7")**	3.02 **(9'11")**	Hydrostatic drive
943	19Z	80-92	80	11 750 **(25,900)**	1.15 **(1.5)**	5.426 **(17'10")**	2.21 **(8'7")**	3.02 **(9'11")**	Hydrostatic drive made in France

*Height to top of stack. Others to top of seat back.
**Overall length to tip of smallest General Purpose bucket.

Track Loaders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Rated Capacity m^3 (yd^3)	Dimensions Length** m (ft)	Dimensions Width m (ft)	Dimensions Height m (ft)	Remarks
951B	79H	67-71	85	10 025 **(22,100)**	1.14 **(1.5)**	4.70 **(15'6")**	1.98 **(6'6")**	2.75 **(9'0")***	Pedal Steering
951C	86J	71-81	95	12 338 **(27,200)**	1.34 **(1.75)**	4.77 **(15'8")**	1.98 **(6'6")**	2.75 **(9'0")***	HP Increase, Sealed & Lubricated Track
953	5Z	81-85	110	14 050 **(31,000)**	1.5 **(2.0)**	5.87 **(19'3")**	2.38 **(7'10")**	3.08 **(10'1")**	Hydrostatic drive
953	20Z	81-92	110	14 050 **(31,000)**	1.5 **(2.0)**	5.87 **(19'3")**	2.38 **(7'10")**	3.08 **(10'1")**	Hydrostatic drive
953	76Y	81-85	110	13 800 **(30,500)**	1.5 **(2.0)**	5.87 **(19'3")**	2.38 **(7'10")**	3.08 **(10'1")**	Hydrostatic drive
953	77Y	81-85	110	13 800 **(30,500)**	1.5 **(2.0)**	5.87 **(19'3")**	2.38 **(7'10")**	3.08 **(10'1")**	Hydrostatic drive
953B	5MK	92-96	120	14 400 **(31,800)**	1.75 **(2.25)**	4.23 **(13'4")**	2.38 **(7'10")**	3.08 **(10'1")**	Hydrostatic drive
953C	2ZN	96-03	121	14 680 **(32,360)**	2.3 **(3.0)**	4.35 **(14'3")**	2.30 **(7'7")**	3.08 **(10'1")**	
953C	BBX	03-07	128	15 145 **(33,389)**	1.75 **(2.25)**	4.35 **(14'3")**	2.30 **(7'7")**	3.16 **(10'4")**	SystemOne™ U/C
HT4	7U	50-55	54	2607 **(5748)**	0.96 **(1.25)**	4.32 **(14'2")**	2.03 **(6'8")**	1.83 **(6'0")**	
955C	12A	55-60	70	9590 **(21,145)**	1.15 **(1.5)**	4.60 **(15'2")**	2.03 **(6'8")**	2.08 **(6'11")**	Integral loader
955E	12A	58-60	70	10 160 **(22,400)**	1.15 **(1.5)**	4.60 **(15'2")**	2.03 **(6'8")**	2.09 **(6'11")**	Improved undercarriage
955H	60A	60-66	100	11 320 **(24,950)**	1.34 **(1.75)**	4.79 **(15'9")**	1.90 **(6'3")**	2.65 **(8'8")***	Power shift, Turbo, oil cooled brakes
955K	61H	66-71	115	12 700 **(28,000)**	1.34 **(1.75)**	5.00 **(16'6")**	2.06 **(6'9")**	2.80 **(9'3")***	Horsepower and bucket capacity increase
955L	85J	71-75	130	15 330 **(33,800)**	1.53 **(2.0)**	5.30 **(16'1")**	2.18 **(7'2")**	2.95 **(9'8")***	ROPS Cab, Sealed & Lubricated Track
955L	13X	75-81	130	15 853 **(34,950)**	1.72 **(2.25)**	5.26 **(17'3")**	2.18 **(7'2")**	2.95 **(9'8")**	

*Height to top of stack. Others to top of seat back.
**Overall length to tip of smallest General Purpose bucket.

Track Loaders (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Rated Capacity m^3 (yd^3)	Dimensions Length** m (ft)	Dimensions Width m (ft)	Dimensions Height m (ft)	Remarks
963	6Z	81-85	150	18 250 **(40,250)**	2.0 **(2.6)**	6.35 **(20'10")**	2.50 **(8'2")**	3.30 **(10'10")**	Hydrostatic drive
963	11Z	81-85	150	18 370 **(40,490)**	2.0 **(2.6)**	6.35 **(20'10")**	2.50 **(8'2")**	3.30 **(10'10")**	Hydrostatic drive
963	18Z	82-86	150	18 250 **(40,250)**	2.0 **(2.6)**	6.35 **(20'10")**	2.50 **(8'2")**	3.30 **(10'10")**	Hydrostatic drive made in France
963	21Z	82-95	150	18 370 **(40,490)**	2.0 **(2.6)**	6.35 **(20'10")**	2.50 **(8'2")**	3.30 **(10'10")**	Hydrostatic drive made in France
963B	9BL	95-99	160	19 620 **(43,270)**	2.45 **(3.2)**	6.60 **(21'8")**	2.50 **(8'2")**	3.31 **(10'10")**	3116 engine
963C	2DS	99-03	160	19 020 **(41,940)**	1.75 **(2.25)**	4.61 **(15'2")**	2.40 **(7'11")**	3.32 **(10'11")**	
963C	BBD	03-07	158	19 589 **(43,096)**	2.45 **(3.2)**	4.61 **(15'2")**	2.40 **(7'11")**	3.39 **(11'2")**	SystemOne U/C
973	86G	81-00	210	25 040 **(55,200)**	3.2 **(4.2)**	7.12 **(23'4")**	2.85 **(9'4")**	3.42 **(11'3")**	
973C	3RZ	99-01	210	27 006 **(59,548)**	3.2 **(4.19)**	7.36 **(24'2")**	2.58 **(8'6")**	3.50 **(11'6")**	
973C	BCP	01-05	230	27 006 **(59,548)**	3.2 **(4.19)**	7.36 **(24'2")**	2.58 **(8'6")**	3.50 **(11'6")**	
No. 6	10A	53-55	80	13 229 **(29,165)**	1.5 **(2.0)**	4.90 **(16'1")**	2.44 **(8'1")**	2.11 **(6'11")**	
977D	20A	55-60	100	14 430 **(31,795)**	1.72 **(2.25)**	5.19 **(18'0")**	2.44 **(8'0")**	2.22 **(7'4")**	
977E	20A	58-60	100	15 850 **(34,910)**	1.72 **(2.25)**	5.19 **(18'0")**	2.44 **(8'0")**	2.29 **(7'7")**	Improved undercarriage
977H	53A	60-66	150	17 000 **(37,500)**	1.90 **(2.5)**	5.28 **(17'4")**	2.44 **(8'0")**	2.29 **(7'7")**	Power shift, Turbo, oil cooled brakes
977K	46H	66-78	170	19 100 **(42,000)**	1.90 **(2.5)**	5.50 **(18'0")**	2.38 **(7'10")**	3.05 **(10'0")***	Walk-through compartment, longer roller frame
977L	14X	78-82	190	21 780 **(48,010)**	2.10 **(2.75)**	5.59 **(18'4")**	2.38 **(7'10")**	3.32 **(10'11")***	Horsepower and bucket capacity increase
983	38K	69-78	275	34 460 **(75,980)**	3.82 **(5.0)**	6.78 **(22'3")**	2.90 **(9'6")**	2.79 **(11'10")***	
983B	58X	78-82	275	35 620 **(78,530)**	3.82 **(5.0)**	6.78 **(22'3")**	2.90 **(9'6")**	3.68 **(12'1")***	DI engine

*Height to top of stack. Others to top of seat back.
**Overall length to tip of smallest General Purpose bucket.



INTEGRATED TOOLCARRIERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horse-power	Approx. Operating Weight kg (lb)	Rated Capacity m^3 (yd^3)	Breakout Force kg (lb)	Width Over Tires m (ft)	Ground Clearance mm (in)	Max. Reach at Max. Height mm (in)	Dump Clearance at Max. Height m (ft)	Maximum Speeds km/h (mph) Fwd.	Rev.	Remarks
IT12	2YC	84-89	65	7393	1.0	7193	2.3	405	873	2.84	23.6	24.9	
				(16,299)	**(1.25)**	**(15,858)**	**(7'8")**	**(15.9)**	**(34)**	**(9'4")**	**(14.6)**	**(15.4)**	
IT12B	1KF	89-93	78	7950	1.2	6160	2.15	343	958	2.69	34.0	22.4	
				(17,530)	**(1.6)**	**(13,583)**	**(7'1")**	**(13.5)**	**(37.7)**	**(8'10")**	**(21.1)**	**(13.9)**	
IT12F	1KF	93-95	80	7893	1.3	6479	2.15	365	917	2.74	34.0	22.4	
				(17,401)	**(1.7)**	**(14,247)**	**(7'1")**	**(14)**	**(37)**	**(8'11.8")**	**(21.1)**	**(13.9)**	
IT14B	3NJ	89-93	85	8333	1.2	7525	2.15	344	958	2.70	37.3	24.4	
				(18,374)	**(1.6)**	**(16,593)**	**(7'1")**	**(13.6)**	**(37.7)**	**(8'11")**	**(23.2)**	**(15.2)**	
IT14F	4EL	93-95	85	7999	1.3	7170	2.15	365	918	2.74	37.3	24.4	
				(17,635)	**(1.7)**	**(15,808)**	**(7'1")**	**(14)**	**(37)**	**(9'0")**	**(23.2)**	**(15.2)**	
IT14G	1WN 8ZM FWL KZN	95-14	95	8450	1.2-1.4	7700	2.258	456	787	2.921	32.0	32.0	C4.4 ACERT Engine IT Linkage Hystat Transmission
				(18,632)	**(1.6-1.8)**	**(17,342)**	**(7'5")**	**(16.3)**	**(31)**	**(9'7")**	**(20.0)**	**(20.0)**	
IT14G2	ERP	12-14	95	8450	1.2-1.4	7700	2.258	456	787	2.921	32.0	32.0	C4.4 ACERT Engine IT Linkage Hystat Transmission
				(18,632)	**(1.6-1.8)**	**(17,342)**	**(7'5")**	**(16.3)**	**(31)**	**(9'7")**	**(20.0)**	**(20.0)**	
IT18	9NB	84-86	85	8660	1.2	9105	2.4	285	990	2.84	25.0	25.0	
				(19,092)	**(1.5)**	**(20,108)**	**(7'10")**	**(11.2)**	**(39)**	**(9'4")**	**(15.5)**	**(15.5)**	
IT18B	4ZD	86-92	95	9770	1.3	10 500	2.28	324	993	2.89	26.4	27.7	
				(21,540)	**(1.75)**	**(21,350)**	**(7'6")**	**(12.8)**	**(39)**	**(9'6")**	**(16.4)**	**(17.2)**	
IT18F	6ZF	92-94	105	9959	1.6	8880	2.33	321	1089	2.75	37.0	24.5	
				(21,960)	**(2.0)**	**(19,580)**	**(7'8")**	**(13)**	**(43)**	**(9'0")**	**(23.0)**	**(15.2)**	
IT24F	4NN	94-99	105	9989	1.7	8782	2.33	321	1088	2.75	38.0	23.4	
				(20,022)	**(2.5)**	**(19,361)**	**(7'6")**	**(12.6)**	**(42)**	**(9'0")**	**(23.6)**	**(14.8)**	
IT28	2KC	84-86	105	9560	1.5	9505	2.4	285	1044	2.82	30.8	32.3	
				(21,076)	**(2.0)**	**(20,955)**	**(7'10")**	**(11.2)**	**(41)**	**(9'3")**	**(18.8)**	**(20.0)**	
IT28B	1HF	86-93	110	10 580	1.7	10 456	2.32	324	1091	2.73	34.4	37.2	
				(23,325)	**(2.25)**	**(23,050)**	**(7'7")**	**(12.8)**	**(43)**	**(8'11")**	**(21.4)**	**(23.1)**	
IT28F	3CL	93-96	125	11 430	2.0	9840	2.43	317	1093	2.72	35.4	21.4	
				(25,200)	**(2.6)**	**(21,700)**	**(8'0")**	**(12)**	**(43)**	**(8'11")**	**(21.9)**	**(13.5)**	
IT28G	DBT	02-04	146	12 640	2.0	10 631	2.54	407	958	2.97	37.7	25.8	
				(27,860)	**(2.6)**	**(23,437)**	**(8'4")**	**(16)**	**(38)**	**(9'9")**	**(23.4)**	**(16.0)**	
IT28G	EWF	02-05	131	11 250	2.0	11 723	2.44	408	1455	2.879	37.7	25.8	
				(24,802)	**(2.6)**	**(25,849)**	**(8'0")**	**(16)**	**(57)**	**(9'5")**	**(23.4)**	**(16.0)**	
IT28G	WAC	02-05	131	11 250	2.0	11 723	2.44	408	1455	2.879	37.7	25.8	
				(24,802)	**(2.6)**	**(25,849)**	**(8'0")**	**(16)**	**(57)**	**(9'5")**	**(23.4)**	**(16.0)**	
IT38G Series II	CSX	02-07	160	14 583	2.8	11 216	2.6	400	1224	2.733	38.8	23.3	
				(32,156)	**(3.66)**	**(24,729)**	**(102)**	**(16)**	**(48)**	**(108)**	**(24.1)**	**(14.5)**	
IT38H	JNJ	07-12	200	16 000	3.0	12 797	2.67	400	1152	2.81	43.2	25.5	
				(35,274)	**(3.92)**	**(28,214)**	**(8'9")**	**(16)**	**(45)**	**(9'2")**	**(26.8)**	**(15.8)**	
950F CT	5SK	94-98	170	16 600	3.1	13 590	2.87	460	1714	2.845	38.7	42.7	
				(36,580)	**(4.0)**	**(29,950)**	**(9'5")**	**(18)**	**(68)**	**(9'4")**	**(24.0)**	**(26.5)**	



TELEHANDLERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower kW (hp)	Operating Weight kg (lb)	Engine	Maximum Lift Height m (ft/in)	Maximum Reach m (ft/in)	Maximum Lift Capacity kg (lb)
TH62	4TM	00-02	72 **(105)**	6840 **(15,080)**	Cat 3054T	7.6 **(25'0")**	4.2 **(13'9")**	2725 **(6000)**
TH63	5WM	00-02	72 **(105)**	9260 **(20,420)**	Cat 3054T	12.5 **(41'0")**	8.1 **(26'7")**	3000 **(6615)**
TH82	3JN	00-02	72 **(105)**	7470 **(16,470)**	Cat 3054T	7.6 **(25'0")**	4.2 **(13'9")**	3635 **(8000)**
TH83	3RN	00-02	72 **(105)**	10 000 **(22,050)**	Cat 3054T	12.5 **(41'0")**	8.2 **(27'0")**	3635 **(8000)**
TH103	3PN	00-02	72 **(105)**	12 500 **(27,500)**	Cat 3054T	13.5 **(44'0")**	8.8 **(28'9")**	4536 **(10,000)**
TH210	MHT	03-06	60 **(80)**	5000 **(11,023)**	Cat 3054B DI	5.18 **(17'0")**	2.8 **(9'2")**	2200 **(4840)**
TH215	MHS	03-06	60 **(80)**	5500 **(12,100)**	Cat 3054B DI	5.54 **(18'2")**	3.1 **(10'2")**	2500 **(5500)**
TH220B	SLA/TBF	03-07	74.5 **(100)**	6700 **(14,774)**	Cat 3054E	6.1 **(20'0")**	3.3 **(10'9")**	3500 **(7718)**
TH330B	SLB/TBG	03-07	74.5 **(100)**	7200 **(15,876)**	Cat 3054E	7.2 **(23'7")**	3.8 **(12'6")**	3600 **(7938)**
TH340B	SLC	03-06	74.5 **(99.9)**	7700 **(17,000)**	Cat 3054E	9.0 **(29'6")**	6.5 **(21'4")**	3000 **(6600)**
TH350B	SLD	03-06	74.5 **(99.9)**	8480 **(18,100)**	Cat 3054E	11.0 **(36'0")**	7.4 **(24'0")**	3000 **(6600)**
TH360B	SLE/TBH	03-07	74.5 **(100)**	9970 **(21,984)**	Cat 3054E	13.5 **(44'3")**	9.2 **(30'2")**	3500 **(7718)**
TH460B	SLF	03-06	74.5 **(99.9)**	10 500 **(21,600)**	Cat 3054E	13.5 **(44'4")**	9.2 **(30'0")**	4000 **(8800)**
TH560B	SLG/TBP	03-07	74.5 **(99.9)**	12 000 **(26,500)**	Cat 3054E	13.5 **(44'0")**	9.2 **(30'0")**	5000 **(11,000)**
TH580B	SLH/TBJ	03-07	74.5 **(99.9)**	13 670 **(30,100)**	Cat 3054E	17 **(56'0")**	12.7 **(42'0")**	5000 **(11,000)**



PAVING PRODUCTS — COLD PLANERS

Model	Product Ident. No. Prefix	Years Built	kW Flywheel (Horsepower)	Approximate Operating Weight kg (lb)	General Dimensions (Shipping)		
					Height mm (ft)	Length mm (ft)	Width mm (ft)
PR-75		85-92	52 **(77)**	5900 **(13,000)**	2690 **(8'10")**	3050 **(10'0")**	2130 **(7'0")**
PR-105		85-92	67 **(90)**	7711 **(17,000)**	2921 **(9'7")**	3581 **(11'9")**	2515 **(8'3")**
PR-275	6RC	—	201 **(270)**	17 237 **(38,000)**	2896 **(9'6")**	5740 **(18'10")**	2438 **(8'0")**
PR-450		85-92	336 **(450)**	28 308 **(58,000)**	4270 **(14'0")**	13 280 **(43'8")**	2870 **(9'5")**
PR-450C		92-97	336 **(450)**	28 308 **(58,000)**	3810 **(12'6")**	13 200 **(43'6")**	2490 **(8'2")**
PR-750B		85-92	559 **(750)**	42 638 **(94,000)**	3734 **(12'3")**	16 500 **(54'0")**	3575 **(11'9")**
PR-1000			Cutter 559 **(750)** Track 186 **(250)**	46 780 **(103,130)**	3810 **(12'6")**	16 590 **(54'5")**	4877 **(16'0")**
PM-465	5ZS	97-03	353 **(473)**	14 333 **(31,600)**	2820 **(9'3")**	13 716 **(45'0")**	2489 **(8'2")**
PM-565		xx-05	466 **(625)**	38 595 **(85,100)**	5040 **(16'6")**	15 100 **(49'5")**	2790 **(9'2")**
PM201		05-14	485 **(650)**	39 165 **(86,360)**	5040 **(16'6")**	15 100 **(49'5")**	2810 **(9'2")**



PAVING PRODUCTS — RECLAIMERS & STABILIZERS

Model	Product Ident. No. Prefix	Years Built	kW Flywheel (Horsepower)	Approximate Operating Weight kg (lb)	General Dimensions (Shipping)		
					Height mm (ft)	Length mm (ft)	Width mm (ft)
SS-250	6DD	85-96	250 **(335)**	13 300 **(29,300)**	3220 **(10'7")**	8780 **(28'10")**	2900 **(9'7")**
SS-250B	5GR	96-01	250 **(335)**	14 340 **(31,600)**	2600 **(8'6")**	8560 **(28'1")**	2900 **(9'6")**
RR-250	6ED	85-96	250 **(335)**	17 876 **(39,300)**	3220 **(10'7")**	8780 **(28'10")**	2900 **(9'7")**
RR-250B	3RR	96-01	250 **(335)**	19 260 **(42,470)**	2600 **(8'6")**	8560 **(28'1")**	2900 **(9'6")**
RM-250C			250 **(335)**	16 780 **(37,000)**	3220 **(10'7")**	8780 **(28'10")**	2921 **(9'7")**
RM-350	5FK	92-97	321 **(430)**	21 440 **(47,200)**	3404 **(11'2")**	9577 **(31'5")**	2997 **(9'10")**
SM-350	1RM	92-97	321 **(430)**	18 440 **(40,600)**	3404 **(11'2")**	9577 **(31'5")**	2997 **(9'10")**
RM-350B			373 **(500)**	24 040 **(53,000)**	3404 **(11'2")**	9980 **(32'9")**	2997 **(9'10")**
RM500		06-14	403 **(540)**	28 145 **(62,060)**	3480 **(11'4")**	9680 **(31'8")**	2980 **(9'7")**



PAVING PRODUCTS — UNITIZED VENTURI-MIXERS & UNITIZED DRUM-MIXERS

	Drum Dimensions			Performance	
Model	**Diameter mm (ft)**	**Length m (ft)**	**Gross Volume m^3 (ft^3)**	**Production Range/hr. metric tons (tons)**	**Air Flow m^3/min (ft^3/min)**
UVM-500	1829/1524 **(6'0"/5'0")**	7.9 **(26'0")**	14.17 **(500)**	68-109 **(75-120)**	300-481 **(10,600-17,000)**
UDM-600	1829 **(6'0")**	6.7 **(22'0")**	17.00 **(600)**	82 **(89)**	354.25 **(12,500)**
UDM-900	2134/1829 **(7'0"/6'0")**	9.1 **(30'0")**	25.48 **(900)**	68-227 **(75-250)**	311-793 **(11,000-28,000)**
UVM-1000	2134 **(7'0")**	9.754 **(32'0")**	28.34 **(1000)**	82-272 **(90-300)**	425-1076 **(15,000-38,000)**
UVM-1400	2286 **(7'6")**	10.973 **(36'0")**	39.64 **(1400)**	100-358 **(110-395)**	481-1274 **(17,000-45,000)**
UVM-1700	2591 **(8'6")**	11.582 **(38'0")**	48.14 **(1700)**	122-480 **(135-450)**	651-1614 **(23,000-57,000)**



PAVING PRODUCTS — PORTABLE VENTURI-MIXERS

	Drum Dimensions			Performance	
Model	**Diameter mm (ft)**	**Length m (ft)**	**Gross Volume m^3 (ft^3)**	**Production Range/hr. metric tons (tons)**	**Air Flow m^3/min (ft^3/min)**
PVM-1100	2134 **(7'0")**	10.97 **(36'0")**	31.15 **(1100)**	82-295 **(90-325)**	425-1133 **(15,000-40,000)**
PVM-1500	2286 **(7'6")**	12.19 **(40'0")**	42.48 **(1500)**	100-363 **(110-400)**	510-1274 **(18,000-45,000)**
PVM-2000	2591 **(8'6")**	12.80 **(42'0")**	56.64 **(2000)**	122-454 **(135-500)**	680-1699 **(24,000-60,000)**
PVM-2500	2896 **(9'6")**	12.80 **(42'0")**	70.79 **(2500)**	136-499 **(150-550)**	793-2110 **(28,000-74,500)**
PVM-2900	3048 **(10'0")**	13.41 **(44'0")**	82.12 **(2900)**	168-553 **(185-610)**	906-2265 **(32,000-80,000)**
PVM-3300	3200 **(10'6")**	13.41 **(44'0")**	93.45 **(3300)**	181-612 **(200-675)**	991-2464 **(35,000-87,000)**



PAVING PRODUCTS — STATIONARY VENTURI-MIXERS

	Drum Dimensions			Performance	
Model	Diameter mm (ft)	Length m (ft)	Gross Volume m^3 (ft^3)	Production Range/hr. metric tons (tons)	Air Flow m^3/min (ft^3/min)
SVM-1100	2134 **(7'0")**	10.97 **(36'0")**	31.15 **(1100)**	82-295 **(90-325)**	425-1133 **(15,000-40,000)**
SVM-1500	2286 **(7'6")**	12.19 **(40'0")**	42.48 **(1500)**	100-363 **(110-400)**	510-1274 **(18,000-45,000)**
SVM-2000	2591 **(8'6")**	12.80 **(42'0")**	56.64 **(2000)**	122-454 **(135-500)**	680-1699 **(24,000-60,000)**
SVM-2500	2896 **(9'6")**	12.80 **(42'0")**	70.79 **(2500)**	136-499 **(150-550)**	793-2110 **(28,000-74,500)**
SVM-2900	3048 **(10'0")**	13.41 **(44'0")**	82.12 **(2900)**	168-553 **(185-610)**	906-2265 **(32,000-80,000)**
SVM-3600	3200 **(10'6")**	14.63 **(48'0")**	101.94 **(3600)**	190-623 **(210-685)**	1020-2565 **(36,000-90,000)**



PAVING PRODUCTS — SLIPFORM PAVERS

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower	Approx. Operating Weight kg (lb)	Standard Paving Width m (ft)	Shipping Dimensions (Min.) Length m (ft)	Width m (ft)	Height m (ft)	Remarks
SF-175	5ZC	—	142	9072 **(20,000)**	2.1 **(7'0")**	6.6 **(21'6")**	2.4 **(8'0")**	2.8 **(9'4")**	
SF-250	6XC	—	208	24 494 **(54,000)**	3.6 **(12'0")**	3.0 **(10'0")**	3.7 **(12'0")**		
SF-250B	—	—	250	27 216 **(60,000)**	3.7-7.3 **(12'0"-24'0")**	1.5 **(5'0")**	3.66 **(12'0")**	3.20 **(10'6")**	
SF-350	—	—	290	40 824 **(90,000)**	3.6-7.3 **(12'0"-24'0")**	1.04 **(3'5")**	3.0 **(10'0")**	2.9 **(9'8")**	
SF-450	7GC	73-83	400	43 546* **(96,000)** 53 525** **(118,000)**	3.66-7.62 **(12'0"-25'0")**	9.35 **(30'8")**	3.05 **(10'0")**	2.90 **(9'6")**	
SF-500	8DC	—	400	52 164 **(115,000)**	7.6 **(25'0")**	8.9 **(29'2½")**	3.0 **(10'0")**	3.0*** **(10'2")**	
SF-550	5PD	—	400	52 164 **(115,000)**	5.5-8.5 **(18'0"-28'0")**	7.0 **(23'0")**	3.7 **(12'0")**	2.9 **(9'8")**	

*Weight of 7.62 m **(25'0")** machine.
Weight of 11.58 m **(38'0") machine.
***Machine legs and track shipped separately.



PAVING PRODUCTS — PLACER-SPREADER-TRIMMER, BELT PLACER

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower	Approximate Operating Weight kg (lb)	General Dimensions Height m (ft)	Length m (ft)	Width m (ft)
PST-300	8EC	—	250	38 193 **(84,200)**	2.64 **(8'8")**	10.57 **(34'8")**	9.02 **(29'7")**
BP-100	1EF	—	102	11 340 **(22,000)**	3.27 **(10'9")**	2.49 **(8'2")**	2.49 **(8'2")**



PAVING PRODUCTS — TUBE FINISHER, TEXTURING/CURING

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower	Approximate Operating Weight kg (lb)	General Dimensions (Shipping) Height mm (ft)	Length mm (ft)	Width mm (ft)
TF-250	6YC	—	52	5897 **(13,000)**	2489 **(8'2")**	8484 **(27'10")**	2438 **(8'0")**
TC-250	7HC	—	56	5897 **(13,000)**	2489 **(8'2")**	8484 **(27'10")**	2438 **(8'0")**



PAVING PRODUCTS — TRIMMER-RECLAIMER

Model	Product Ident. No. Prefix	Years Built	Flywheel Horsepower	Approximate Operating Weight kg (lb)	General Dimensions (Shipping) Height mm (ft)	Length m (ft)	Width mm (ft)
TR-225B	6WC	—	250	21 319 **(47,000)**	3200 **(10'6")**	13.9 **(45'9.5")**	2896 **(9'6")**
TR-500	8CC	—	375	46 267 **(102,000)**	3099 **(10'2")**	8.9 **(29'2¾")**	3048 **(10'0")**



PAVING PRODUCTS — ASPHALT PAVERS & WINDROW ELEVATORS

Model	Product Ident. No. Prefix	Years Built	Flywheel kW (hp)	Approx. Op. Weight kg (lb)	Drive	Screed Width mm (ft)	Hopper Capacity m^3 (ft^3)	Maximum Op. Speed m/min (ft/min)
AP-200	2NK	86-01	26 **(35)**	4080 **(9000)**	Track	2743 **(9'0")**	5.4 t **(6 T)**	53.6 **(176)**
AP-200	6AD	85-91	26 **(35)**	4080 **(9000)**	Track	2743 **(9'0")**	5.4 t **(6 T)**	0-54 **(0-177)**
AP-650B		-08	97 **(130)**	13 917 **(30,655)**		2400 **(8'0")**	5 t **(177 T)**	67 **(220)**
AP755	B2T - B3T	06-12	149 **(202)**	21 600 **(47,620)**	Track	9100 **(29'10")**	7.0 **(247)**	26 **(85)**
AP-800	1BF	86-89	76 **(102)**	11 903 **(26,350)**	Wheel	2438 **(8'0")**	5.8 **(206)**	95 **(312)**
AB-800B	1BF	89-93	76 **(102)**	11 903 **(26,350)**	Wheel	2438 **(8'0")**	5.8 **(206)**	95 **(312)**
AP-800C			80 **(107)**	12 115 **(26,700)**	Wheel	2438 **(8'0")**	5.5 **(195)**	76 **(250)**
AP-800D			80 **(107)**	12 115 **(26,700)**	Wheel	2400 **(8'0")**	5.5 **(195)**	76 **(250)**
AP-900		-06	114 **(153)**	14 445 **(31,850)**	Wheel	3000 **(10'0")**	6.1 **(215)**	122 **(400)**
AP-1000B		-05	130 **(174)**	15 490 **(34,150)**	Wheel	3000 **(10'0")**	6.1 **(215)**	114 **(374)**
AP-1000D	N/A	05-11	167 **(224)**	17 851 **(39,320)**	Wheel	7320 **(24'2")**	6.1 **(215)**	91 **(300)**
AP-1050	1JG	89-96	116 **(155)**	14 878 **(32,800)**	Track	3048 **(10'0")**	6.2 **(215)**	57 **(186)**
AP-1050B			130 **(174)**	16 015 **(35,300)**	Track	3048 **(10'0")**	6.1 **(215)**	61 **(200)**
AP-1055B			130 **(174)**	16 556 **(36,500)**	Track	3048 **(10'0")**	6.1 **(215)**	61 **(200)**
AP-1055D	N/A	05-11	167 **(224)**	20 330 **(44,780)**	Track	7320 **(24'2")**	6.1 **(215)**	78 **(225)**
AP-1200	2JD	85-89	108 **(145)**	13 608 **(30,000)**	Wheel	3048 **(10'0")**	6.2 **(220)**	21.4 **(13.3)**
WE601B	TEC	85-91	78 **(102)**	3856 **(8500)**	N/A	1524 **(5'0")**	N/A	N/A
BG-200A	N/A	89-91	35 **(47)**	6750 **(14,900)**	Wheel	1803 **(5'11")**	3.26 **(116)**	56 **(180)**
BG-210	N/A	90-91	79 **(106)**	10 192 **(22,500)**	Wheel	2438 **(8'0")**	4.76 **(170)**	84 **(275)**
BG-210B	N/A	91-01	80 **(107)**	11 793 **(26,000)**	Wheel	2438 **(8'0")**	4.8 **(170)**	0-21.7 **(0-13.5)**
BG-220	N/A	84-87	58 **(78)**	9752 **(21,500)**	Wheel	2438 **(8'0")**	3.7 **(130)**	88 **(289)**
BG-220B	4ZM	91-94	80 **(108)**	12 483 **(27,525)**	Wheel	2438 **(8'0")**	4.3 **(155)**	88 **(289)**

Paving Products — Asphalt Pavers & Windrow Elevators (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel kW (hp)	Approx. Op. Weight kg (lb)	Drive	Screed Width mm (ft)	Hopper Capacity m^3 (ft^3)	Maximum Op. Speed m/min (ft/min)
BG-225	N/A	84-87	58	11 339	Track	2438	3.7	58
			(78)	**(25,000)**		**(8'0")**	**(130)**	**(188)**
BG-225B	N/A		118	16 400	Track	2438	4.3	57
			(158)	**(36,200)**		**(8'0")**	**(155)**	**(189)**
BG-225C			97	13 917	Track	2400	5	67
			(130)	**(30,655)**		**(8'0")**	**(177)**	**(220)**
BG-230			80	12 111	Wheel	2438	5.5	76
			(107)	**(26,700)**		**(8'0")**	**(195)**	**(250)**
BG500E		10-13	106	15 520	Wheel	2440	6.2	61
			(142)	**(34,220)**		**(8'0")**	**(219)**	**(200)**
BG600D		08-13	129	17 122	Wheel	2440	6.5	61
			(174)	**(37,747)**		**(8'0")**	**(230)**	**(200)**
BG-230D			97	13 307	Wheel	2400	5.5	76
			(130)	**(29,310)**		**(8'0")**	**(195)**	**(250)**
BG-240	N/A	85-86	72	13 154	Wheel	3048	3.7	81
			(96)	**(29,000)**		**(10'0")**	**(130)**	**(265)**
BG-240B	7RL	87-99	86	15 200	Wheel	3048	6.5	81
			(115)	**(33,500)**		**(10'0")**	**(230)**	**(265)**
BG-245	N/A	85-87	72	14 514	Track	3048	5.8	58
			(96)	**(32,000)**		**(10'0")**	**(206)**	**(189)**
BG-245B	3XL	87-96	116	16 080	Track	3048	5.8	55
			(155)	**(35,450)**		**(10'0")**	**(206)**	**(182)**
BG-245C	N/A		130	16 015	Track	3048	6.1	60.1
			(174)	**(35,300)**		**(10'0")**	**(215)**	**(200)**
BG-2455C	N/A		130	16 555	Track	3048	6.1	61
			(174)	**(36,500)**		**(10'0")**	**(215)**	**(200)**
BG555E		10-13	106	16 240	Track	2440	6.2	61
			(142)	**(35,810)**		**(8'0")**	**(219)**	**(200)**
BG655D		08-13	129	18 250	Track	2440	6.5	61
			(174)	**(40,234)**		**(8'0")**	**(230)**	**(200)**
BG1055E		11-13	168	20 076	Track	3000	7.1	61
			(225)	**(44,167)**		**(10'0")**	**(251)**	**(200)**
BG-2455D	N/A	05-11	167	20 330	Track	7320	6.1	78
			(224)	**(44,780)**		**(24'2")**	**(215)**	**(225)**
AP600D		08-14	129	17 122	Wheel	2440	6.5	61
			(174)	**(37,749)**		**(8'0")**	**(230)**	**(200)**
AP655D		07-14	129	18 245	Track	2440	6.5	61
			(174)	**(40,225)**		**(8'0")**	**(230)**	**(200)**

Paving Products — Asphalt Pavers & Windrow Elevators (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel kW (hp)	Approx. Op. Weight kg (lb)	Drive	Screed Width mm (ft)	Hopper Capacity m^3 (ft^3)	Maximum Op. Speed m/min (ft/min)
BG-260	N/A	85-87	106 **(142)**	14 514 **(32,000)**	Wheel	3048 **(10'0")**	5.8 **(206)**	77 **(253)**
BG-260B	N/A		116 **(155)**	14 740 **(32,500)**	Wheel	3048 **(10'0")**	5.8 **(206)**	90 **(296)**
BG1000E		11-13	168 **(225)**	18 427 **(40,539)**	Wheel	3000 **(10'0")**	7.1 **(251)**	61 **(200)**
BG-260D	N/A	05-11	167 **(224)**	17 851 **(39,320)**	Wheel	7320 **(24'2")**	6.1 **(215)**	91 **(300)**
BG-265	N/A	85-87	106 **(142)**	16 782 **(37,000)**	Track	3048 **(10'0")**	5.8 **(206)**	50 **(164)**
BG-265B	7XK	87-98	145 **(195)**	18 380 **(40,570)**	Track	3048 **(10'0")**	5.8 **(206)**	50 **(164)**
BG-270B	N/A		145 **(195)**	15 510 **(34,200)**	Wheel	3048 **(10'0")**	6.5 **(230)**	90 **(296)**
BG-610	N/A	85	58 **(78)**	4394 **(9700)**	N/A	1524 **(5'0")**	N/A	N/A
BG-610A	N/A	86-90	58 **(78)**	4911 **(10,840)**	N/A	1524 **(5'0")**	N/A	N/A
BG-650	N/A		80 **(107)**	7984 **(17 600)**	N/A	N/A	N/A	N/A
BG-710	N/A		111 **(149)**	13 380 **(29,500)**	Wheel	3048 **(10'0")**	10.0 **(80)**	98 **(320)**
BG-730	N/A	87-02	114 **(153)**	14 061 **(31,000)**	Wheel	3048 **(10'0")**	10.0 **(80)**	0-24.1 **(0-15.0)**
BG-750	N/A	87-97	116 **(155)**	17 010 **(37,500)**	Wheel	4270 **(14'0")**	10.0 **(80)**	0-24.1 **(0-15.0)**
MTP-1260	N/A	86-90	58 **(78)**	4911 **(10,840)**	N/A	3048 **(10'0")**	7.7 **(275)**	58 **(189)**
MTP-1265	N/A	88-91	167 **(224)**	25 368 **(56,000)**	N/A	3048 **(10'0")**	11.2 **(400)**	50 **(164)**
AP300		06-14	52 **(70)**	7300 **(16,094)**	Wheel	1700 **(5'7")**	3.8 **(134)**	85 **(279)**
AP1000E		11-14	168 **(225)**	18 427 **(40,539)**	Wheel	3048 **(10'0")**	7.1 **(251)**	61 **(200)**
AP1055E		11-14	168 **(225)**	20 076 **(44,167)**	Track	3048 **(10'0")**	7.1 **(251)**	61 **(200)**
AP300D	N/A		55.5 **(74.4)**	6300 **(13,889)**	Wheel	1700 **(5'7")**	3.8 **(134)**	30 **(98)**
AP500E	N/A	10-15	106 **(142)**	12 590 **(27,760)**	Wheel	2440 **(8'0")**	6.2 **(219)**	61 **(200)**
AP555E	N/A	10-15	106 **(142)**	13 305 **(29,335)**	Track	2440 **(8'0")**	6.2 **(219)**	61 **(200)**



PAVING PRODUCTS — SINGLE DRUM VIBRATORY COMPACTORS

Model	Product Ident. No. Prefix	Years Built	Flywheel kW (hp)	Approx. Op. Weight kg (lb)	Drive	Drum Width mm (in)	Centrifugal Force kg (lb)	Maximum Op. Speed km/h (mph)
CS-323	1TM	85-95	57	4173	Wheel/	1219	5760	0-10.9
			(77)	**(9200)**	Drum	**(48)**	**(12,700)**	**(0-6.8)**
CS-323C		04-10	62	4390	Wheel/	1270	6804	8.9
			(83)	**(9680)**	Drum	**(50)**	**(15,000)**	**(5.5)**
CP-323	6JD	85-95	57	4218	Wheel/	1219	5760	0-10.9
			(77)	**(9300)**	Drum	**(48)**	**(12,700)**	**(0-6.8)**
CP-323C		04-10	62	4745	Wheel/	1270	6804	8.9
			(83)	**(10,440)**	Drum	**(50)**	**(15,000)**	**(5.5)**
CS-431	6MD	85-87	52	6110	Wheel	1680	7260	21.0
			(70)	**(13,480)**		**(66)**	**(16,000)**	**(13.0)**
CS-431B	1XF	88-94	76.5	6312	Wheel	1680	11 235	12.8
			(102)	**(13,915)**		**(66)**	**(24,746)**	**(8.0)**
CS-431C	9XL	94-01	78	6509	Wheel/	1680	13 609	12.8
			(105)	**(14,349)**	Drum	**(66)**	**(30,000)**	**(8.0)**
CS-433	6ND	85-87	60	6720	Wheel/	1524	7260	10.0
			(80)	**(14,820)**	Drum	**(60)**	**(16,000)**	**(6.0)**
CP-433	6NP	85-87	60	6750	Wheel/	1524	7260	10.0
			(80)	**(14,870)**	Drum	**(60)**	**(16,000)**	**(6.0)**
CS-433B	4FK	88-94	76.5	6448	Wheel/	1680	11 235	12.8
			(102)	**(14,215)**	Drum	**(66)**	**(24,746)**	**(8.0)**
CS-433C	3TM	94-01	78	6773	Wheel/	1680	13 609	12.8
			(105)	**(14,931)**	Drum	**(66)**	**(30,000)**	**(8.0)**
CS-433E		04-10	75	6745	Wheel/	1700	13 608	11.5
			(100)	**(14,875)**	Drum	**(66)**	**(30,000)**	**(7.1)**
CP-433B	1MG	88-94	76.5	6668	Wheel/	1680	11 235	12.8
			(102)	**(15,225)**	Drum	**(66)**	**(24,746)**	**(8.0)**
CP-433C	2JM	94-01	78	7075	Wheel/	1680	13 609	12.8
			(105)	**(15,597)**	Drum	**(66)**	**(30,000)**	**(8.0)**
CP-433E		04-10	75	7145	Wheel/	1700	13 608	11.5
			(100)	**(15,750)**	Drum	**(66)**	**(30,000)**	**(7.1)**
CS44	N/A		75	6900	Wheel/	1676	13 600	12.3
			(100)	**(15,212)**	Drum	**(5'6")**	**(30,000)**	**(7.6)**
CP44	N/A		75	7295	Wheel/	1676	13 600	12.3
			(100)	**(16,083)**	Drum	**(5'6")**	**(30,000)**	**(7.6)**
CS-531	3WM	93-95	108	9310	Wheel	2134	22 680	12.8
			(145)	**(20,500)**		**(84)**	**(50,000)**	**(8.0)**
CS-531C	5ZN	95-00	108	9300	Wheel	2134	24 091	12.8
			(145)	**(20,450)**		**(84)**	**(53,000)**	**(8.0)**
CS-531D	3AZ	98-99	108	9650	Rear Wheel	2130	27 124	12.7
	4MZ	99-04	**(145)**	**(21,230)**		**(84)**	**(60,000)**	**(7.8)**
	AGH	01-03						

Paving Products — Single Drum Vibratory Compactors (cont'd)

Model	Product Ident. No. Prefix	Years Built	Flywheel kW (hp)	Approx. Op. Weight kg (lb)	Drive	Drum Width mm (in)	Centrifugal Force kg (lb)	Maximum Op. Speed km/h (mph)
CS-533	3BL	93-95	108	10 110	Wheel/	2134	22 680	12.8
			(145)	**(22,500)**	Drum	**(84)**	**(50,000)**	**(8.0)**
CS-533C	2WN	95-00	108	9500	Wheel/	2134	24 091	12.8
			(145)	**(20,900)**	Drum	**(84)**	**(53,000)**	**(8.0)**
CS-533D	AET	00-03	108	9960	Drum/	2130	27 124	12.7
	5CZ	00-04	**(145)**	**(21,912)**	Rear Wheel	**(84)**	**(60,000)**	**(7.8)**
CS54		07-13	97	10 840	Wheel/	2134	23 860	11.1
			(130)	**(23,898)**	Drum	**(84)**	**(52,600)**	**(6.9)**
CP-533	3ZL	93-95	108	11 470	Wheel/	2134	22 680	12.8
			(145)	**(25,250)**	Drum	**(84)**	**(50,000)**	**(8.0)**
CP-533C	3XN	95-00	108	10 180	Wheel/	2134	24 091	12.8
			(145)	**(22,400)**	Drum	**(84)**	**(53,000)**	**(8.0)**
CP-533D	6AZ	01-04	108	10 240	Drum/	2130	27 124	13.2
	AFC	00-03	**(145)**	**(22,528)**	Rear Wheel	**(84)**	**(60,000)**	**(8.1)**
CP54		07-13	97	11 530	Wheel/	2134	23 860	11.1
			(130)	**(25,419)**	Drum	**(84)**	**(52,600)**	**(6.9)**
CS-551	6ZD	85-89	115	10 428	Wheel	2130	18 150	12.1
	8AD		**(155)**	**(22,990)**		**(84)**	**(40,000)**	**(7.5)**
CS-553	7AD	85-89	115	10 782	Wheel/	2130	18 150	10.5
			(155)	**(23,770)**	Drum	**(84)**	**(40,000)**	**(6.5)**
CP-553	7BD	85-89	115	12 247	Wheel/	2130	22 680	10.5
			(155)	**(27,000)**	Drum	**(84)**	**(50,000)**	**(6.5)**
CS-563	8XF	89-95	108	11 130	Wheel/	2134	22 680	12.8
			(145)	**(24,500)**	Drum	**(84)**	**(50,000)**	**(8.0)**
CS-563C	4KN	95-00	108	11 215	Wheel/	2134	24 091	12.8
			(145)	**(24,700)**	Drum	**(84)**	**(53,000)**	**(8.0)**
CS-563D	9MW	98-02	108	10 875	Wheel/	2130	27 216	12.7
			(145)	**(23,975)**	Drum	**(84)**	**(60,000)**	**(7.8)**
CS56		07-13	116	11 414	Wheel/	2134	28 712	11.4
			(156)	**(25,164)**	Drum	**(84)**	**(63,300)**	**(7.0)**
CP-563	1YJ	89-95	108	11 580	Wheel/	2134	22 680	12.8
			(145)	**(25,800)**	Drum	**(84)**	**(50,000)**	**(8.0)**
CP-563C	5JN	95-00	108	11 670	Wheel/	2134	24 091	12.8
			(145)	**(25,700)**	Drum	**(84)**	**(53,000)**	**(8.0)**
CP-563D	9ZW	98-02	108	11 275	Wheel/	2130	27 216	13.2
			(145)	**(24,856)**	Drum	**(84)**	**(60,000)**	**(8.1)**
CP56		07-13	116	11 361	Wheel/	2134	28 712	11.4
			(156)	**(25,047)**	Drum	**(84)**	**(63,300)**	**(7.0)**