Item	Substance	Category
229	Dipropylene glycol monomethyl ether [13429-07-7; 13588-28-8;20324-32-7; 34590-94-8; 55956-21-3]	II
230	Diquat [85-00-7; 2764-72-9; 6385-62-2]	III
231	Disulfiram [97-77-8]	II
232	Disulfoton [298-04-4]	IV
233	Diuron [330-54-1]	I-C
234	Divinyl benzene [1321-74-0]	I-B
235	Emery, Td [12415-34-8]	I-C
236	Endosulfan [115-29-7]	IV
237	Endrin [72-20-8]	II
238	Enflurane [13838-16-9]	II
239	Epichlorohydrin [106-89-8]	IV
240	EPN [2104-64-5]	IV
241	Ethane [74-84-0]	I-C
242	Ethanol [64-17-5]	I-B
243	Ethanolamine (2-aminoethanol; monoethanolamine) [141-43-5]	III
244	Ethion [563-12-2]	IV
245	2-Ethoxyethanol (EGEE) [110-80-5]	IV
246	2-Ethoxyethyl acetate [111-15-9]	IV
247	Ethyl acetate [141-78-6]	I-B
248	Ethyl acrylate [140-88-5]	III
249	Ethyl amyl ketone [541-85-5]	I-B
250	Ethyl benzene [100-41-4]	III
251	Ethyl bromide [74-96-4]	IV
252	Ethyl butyl ketone [106-35-4]	II

Item	Substance	Category
253	Ethyl chloride [75-00-3]	IV
254	Ethyl formate [109-94-4]	I-B
255	Ethyl mercaptan [75-08-1]	I-B
256	Ethyl silicate [78-10-4]	III
257	Ethyl ether [60-29-7]	I-B
258	Ethylamine [75-04-7]	I-B
259	Ethylene [74-85-1]	I-C
260	Ethylene chlorohydrin [107-07-3]	I-A
261	Ethylene diamine [107-15-3]	III
262	Ethylene glycol[107-21-1]	I-A
263	Ethylene glycol dinitrate [628-96-6]	I-A
264	Ethylene glycol dimethyl ether [110-71-4]	IV
265	Ethyleneimine [151-56-4]	IV
266	Ethylene oxide [75-21-8]	III
267	Ethylidene norbornene [16219-75-3]	I-A
268	N-Ethylmorpholine [100-74-3]	II
269	Fenamiphos [22224-92-6]	IV
270	Fensulfothion [115-90-2]	IV
271	Fenthion [55-38-9]	IV
272	Ferbam [14484-64-1]	I-B
273	Ferrovanadium (dust) [12604-58-9]	I-B
274	Fibres, Artificial Vitreous Mineral Fibres, Fibrous glass, continuous filament	I-C
275	Fibres, Artificial Vitreous Mineral Fibres, Insulation wool fibres, Glass wool	I-B

Item	Substance	Category
276	Fibres, Artificial Vitreous Mineral Fibres, Insulation wool fibres, Rock wool	I-B
277	Fibres, Artifical Vitreous Mineral Fibres, Insulation wool fibres, Slag wool	I-B
278	Fibres, Artificial Vitreous Mineral Fibres, Refractory fibres (ceramic or others)	III
279	Fibres, Artificial Vitreous Mineral Fibres, Special purpose glass fibres	III
280	Fluorides (as F)	III
281	Fluorine [7782-41-4]	I-B
282	Fonofos [944-22-9]	IV
283	Formaldehyde [50-00-0]	IV
284	Formamide [75-12-7]	III
285	Formic acid [64-18-6]	I-B
286	Furfural [98-01-1]	I-B
287	Furfuryl alcohol [98-00-0]	I-B
288	Gasoline [86290-81-5]	II
289	Germanium tetrahydride [7782-65-2]	II
290	Glutaraldehyde [111-30-8]	I-A
291	Glycidol [556-52-5]	I-B
292	Grain dust (oat, wheat, barley)	IV
293	Graphite (all forms except graphite fibers), Rd [7782-42-5]	III
294	Hafnium [7440-58-6]	III
295	Halothane [151-67-7]	IV
296	Helium [7440-59-7]	I-C
297	Heptachlor [76-44-8]	IV
298	Heptachlor epoxide [1024-57-3]	III
299	n-Heptane [142-82-5]	II
300	Hexachlorobenzene [118-74-1]	III
301	Hexachlorobutadiene [87-68-3]	III
302	Hexachlorocyclopentadiene [77-47-4]	IV
303	Hexachloroethane [67-72-1]	III
304	Hexachloronaphthalene [1335-87-1]	III
305	Hexafluoroacetone [684-16-2]	IV
306	Hexamethyl phosphoramide [680-31-9]	III
307	n-Hexane	IV
308	Hexane (commercial, <54% n-hexane) [64742-49-0; 64742-89-8] and branched isomers [75-83-2; 79-29-8; 107-83-5; 96-14-0]	I-C
309	1,6-Hexanediamine (1,6-diaminohexane) [124-09-4]	I-B
310	sec-Hexyl acetate [108-84-9]	I-B
311	Hexylene glycol [107-41-5]	I-A
312	Hydrazine [302-01-2]	III
313	Hydrogen [1333-74-0]	I-C
314	Hydrogen bromide [10035-10-6]	I-A
315	Hydrogen chloride [7647-01-0]	I-A
316	Hydrogen cyanide [74-90-8] and cyanide salts [143-33-9; 151-50-8; 592-01-8] as CN	I-A
317	Hydrogen fluoride (as F) [7664-39-3]	I-A

Item	Substance	Category
318	Hydrogen peroxide [7722-84-1]	I-B
319	Hydrogen selenide (as Se) [7783-07-5]	IV
320	Hydrogenated terphenyls (nonirradiated) [61788-32-7]	III
321	Hydroquinone [123-31-9]	IV
322	2-Hydroxypropyl acrylate [999-61-1]	I-B
323	Indene [95-13-6]	I-B
324	Indium [7440-74-6] and compounds (as In)	IV
325	Iodine [7553-56-2] and Iodides, as I	I-A
326	Iodoform [75-47-8]	II
327	Iron pentacarbonyl (as Fe) [13463-40-6]	II
328	Iron salts, soluble (as Fe)	I-B
329	Iron oxide dust and fume (Fe2O3) [1309-37-1], as Fe	III
330	Isoamyl alcohol [123-51-3]	II
331	Isobutyl alcohol (Isobutanol) [78-83-1]	I-B
332	Isocyanate oligomers	III
333	Isooctyl alcohol [26952-21-6]	II
334	Isophorone [78-59-1]	I-A
335	Isophorone diisocyanate [4098-71-9]	III
336	2- Isopropoxyethanol [109-59-1]	III
337	Isopropyl acetate [108-21-4]	I-B
338	Isopropyl alcohol (2-propanol) [67-63-0]	II
339	Isopropyl glycidyl ether (IGE) [4016-14-2]	III
340	Isopropyl ether (diisopropyl ether) [108-20-3]	I-B
341	Isopropylamine [75-31-0]	I-B
342	N-Isopropylaniline [768-52-5]	II
343	Kaolin, Rd [1332-58-7]	III
344	Ketene [463-51-4]	II
345	LPG (Liquefied petroleum gas) [68476-85-7]	I-C
346	Lead [7439-92-1] and inorganic compounds as Pb	III
347	Lead arsenate (as Pb3(AsO4)2) [7784-40-9]	IV
348	Lead chromate [7758-97-6] as Cr (VI)	III
349	Lead tetraethyl [78-00-2] (as Pb)	III
350	Lead tetramethyl (as Pb) [75-74-1]	III
351	Lindane [58-89-9]	IV
352	Lithium hydride [7580-67-8]	I-B
353	Magnesium oxide [1309-48-4]	II
354	Malathion [121-75-5]	IV
355	Maleic anhydride [108-31-6]	IV
356	Manganese [7439-96-5], elemental and inorganic compounds, (as Mn),	IV
357	Manganese cyclopentadienyl tricarbonyl (as Mn) [12079-65-1]	IV
358	Manganese methyl cyclopentadienyl tricarbonyl (as Mn) [12108-13-3]	IV

Item	Substance	Category
359	Mercury [7439-97-6], Alkyl compounds (as Hg)	IV
360	Mercury [7439-97-6], aryl compounds as Hg	III
361	Mercury [7439-97-6], elemental and inorganic compounds (as Hg)	III
362	Mercury [7439-97-6], mercury vapor (as Hg)	III
363	Mesityl oxide [141-79-7]	I-B
364	Methacrylic acid [79-41-4]	I-B
365	Methane [74-82-8]	I-C
366	Methomyl [16752-77-5]	IV
367	Methanol [67-56-1]	IV
368	Methoxychlor [72-43-5]	IV
369	2-Methoxyethanol (EGME) [109-86-4]	IV
370	2-Methoxyethyl acetate (EGMEA) [110-49-6]	IV
371	4-Methoxyphenol [150-76-5]	I-B
372	1-Methoxy-2-propanol [107-98-2]	IV
373	Methyl acetate [79-20-9]	II
374	Methyl acetylene [74-99-7]	I-C
375	Methyl acetylene-propadiene mixture (MAPP) [59355-75-8]	I-C
376	Methyl acrylate [96-33-3]	III
377	Methyl n-amyl ketone [110-43-0]	I-B
378	Methyl bromide [74-83-9]	IV
379	Methyl tert-butyl ether [1634-04-4]	IV
380	Methyl n-butyl ketone [591-78-6]	III
381	Methyl chloride [74-87-3]	IV
382	Methyl chloroform [71-55-6]	II
383	Methyl 2-cyanoacrylate [137-05-3]	III
384	Methyl demeton [8022-00-2]	IV
385	Methyl ethyl ketone (MEK) [78-93-3]	I-B
386	Methyl ethyl ketone peroxide [1338-23-4]	I-A
387	Methyl formate [107-31-3]	I-B
388	Methyl hydrazine [60-34-4]	I-A
389	Methyl iodide [74-88-4]	IV
390	Methyl isoamyl ketone [110-12-3]	I-B
391	Methyl isobutyl ketone [108-10-1]	I-B
392	Methyl isocyanate [624-83-9]	III
393	Methyl isopropyl ketone [563-80-4]	I-B
394	Methyl isobutyl carbinol (methyl amyl alcohol) [108-11-2]	I-B
395	Methyl mercaptan [74-93-1]	I-B
396	Methyl methacrylate (monomer) [80-62-6]	I-B
397	Methyl parathion [298-00-0]	IV
398	Methyl propyl ketone [107-87-9]	II
399	Methyl silicate [681-84-5]	II
400	alpha-Methyl styrene [98-83-9]	II
401	Methylacrylonitrile [126-98-7]	IV
402	Methylal [109-87-5]	I-B
403	Methylamine [74-89-5]	I-B

Item	Substance	Category
404	N-Methylaniline [100-61-8]	IV
405	Methylcyclohexane [108-87-2]	I-B
406	Methylcyclohexanol [25639-42-3]	III
407	Methylcyclohexanone, all isomers [583-60-8; 589-92-4; 591-24-2; 1331-22-2]	I-B
408	4,4'-Methylene bis (2-chloroaniline) (MOCA) [101-14-4]	IV
409	Methylene bis (4-cyclohexylisocyanate) [5124-30-1]	III
410	4,4'-Methylene dianiline [101-77-9]	III
411	Methylene bisphenyl isocyanate (MDI) [101-68-8]	III
412	Metribuzin [21087-64-9]	II
413	Mevinphos (Phosdrin) [7786-34-7]	IV
414	Mica [12001-26-2]	III
415	Mineral oil, excluding metal working fluids	III
416	Molybdenum [7439-98-7] (as Mo)	I-C
417	Monocrotophos [6923-22-4]	IV
418	Morpholine [110-91-8]	I-B
419	Naled [300-76-5]	IV
420	Naphthalene [91-20-3]	I-B
421	-Naphthylamine [91-59-8]	III
422	Neon [7440-01-9]	I-C
423	Nickel [7440-02-0], Metal	III
424	Nickel [7440-02-0] (as Ni)	III
425	Nickel carbonyl [13463-39-3] (as Ni)	II
426	Nickel subsulfide [12035-72-2]	III
427	Nicotine [54-11-5]	II
428	Nitrapyrin [1929-82-4]	I-C
429	Nitric acid [7697-37-2]	II
430	Nitric oxide (nitrogen monoxide) [10102-43-9]	II
431	p-Nitroaniline [100-01-6]	IV
432	Nitrobenzene [98-95-3]	IV
433	p-Nitrochlorobenzene [100-00-5]	IV
434	4-Nitrodiphenyl [92-93-3]	III
435	Nitroethane [79-24-3]	I-B
436	Nitrogen [7727-37-9]	I-C
437	Nitrogen dioxide [10102-44-0]	IV
438	Nitrogen trifluoride [7783-54-2]	II
439	Nitroglycerin (NG) [55-63-0]	II
440	Nitromethane [75-52-5]	IV
441	1-Nitropropane [108-03-2]	III
442	2-Nitropropane [79-46-9]	III
443	N-Nitrosodimethylamine [62-75-9]	III
444	Nitrotoluene (all isomers) [88-72-2; 99-08-1; 99-99-0]	II
445	Nitrous oxide [10024-97-2]	III
446	Nonane [111-84-2]	II
447	Octachloronaphthalene [2234-13-1]	III
448	Octane [111-65-9]	II

Item	Substance	Category
449	Osmium tetroxide (as Os) [20816-12-0]	I-B
450	Oxalic acid, anhydrous [144-62-7] and dihydrate [6153-56-6]	I-B
451	Oxygen difluoride [7783-41-7]	I-A
452	Paraffin wax, fume [8002-74-2]	I-B
453	Paraquat [4685-14-7], as the cation	III
454	Parathion [56-38-2]	IV
455	Particulates (insoluble or poorly soluble) Not Otherwise Classified (PNOC)	I-C
456	Pentaborane [19624-22-7]	II
457	Pentachloronaphthalene [1321-64-8]	III
458	Pentachloronitrobenzene [82-68-8]	III
459	Pentachlorophenol [87-86-5]	III
460	Pentaerythritol [115-77-5]	I-C
461	Pentane, all isomers [78-78-4; 109-66-0; 463-82-1]	II
462	Pentyl acetate, all isomers [123-92-2; 620-11-1; 624-41-9; 625-16-1; 626-38-0; 628-63-7]	I-B
463	Perchloromethyl mercaptan [594-42-3]	II
464	Perchloryl fluoride [7616-94-6]	IV
465	Perfluoroisobutylene [382-21-8]	I-A
466	Phenol [108-95-2]	IV
467	Phenothiazine [92-84-2]	III
468	Phenyl ether, vapour [101-84-8]	I-B
469	Phenyl glycidyl ether (PGE) [122-60-1]	III
470	Phenyl mercaptan [108-98-5]	I-B
471	meta-Phenylenediamine [108-45-2]	III
472	ortho-Phenylenediamine [95-54-5]	III
473	p-Phenylenediamine [106-50-3]	III
474	Phenylhydrazine [100-63-0]	III
475	n-Phenyl-ß-naphthylamine [135-88-6]	III
476	Phenylphosphine [638-21-1]	I-A
477	Phorate [298-02-2]	IV
478	Phosgene [75-44-5]	II
479	Phosphine [7803-51-2]	II
480	Phosphoric acid [7664-38-2]	I-B
481	Phosphorus (yellow) [12185-10-3]	I-B
482	Phosphorus oxychloride [10025-87-3]	I-B
483	Phosphorus pentachloride [10026-13-8]	I-B
484	Phosphorus pentasulfide [1314-80-3]	I-B
485	Phosphorus trichloride [7719-12-2]	I-B
486	Phthalic anhydride [85-44-9]	III
487	m-Phthalodinitrile [626-17-5]	I-C
488	Picloram [1918-02-1]	I-C
489	Picric acid [88-89-1]	III
490	Pindone [83-26-1]	III

Item	Substance	Category
491	Platinum [7440-06-4], Metal	III
492	Platinum [7440-06-4], Soluble salts (as Pt)	III
493	Portland cement [65997-15-1]	I-B
494	Potassium hydroxide [1310-58-3]	I-A
495	Propane [74-98-6]	I-C
496	Propane sultone [1120-71-4]	III
497	Propargyl alcohol [107-19-7]	I-B
498	-Propiolactone [57-57-8]	III
499	Propionic acid [79-09-4]	I-B
500	Propoxur (baygon) [114-26-1]	IV
501	n-Propyl acetate [109-60-4]	I-B
502	n-Propyl alcohol (n-Propanol) [71-23-8]	I-B
503	n-Propyl nitrate [627-13-4]	II
504	Propylene [115-07-1]	I-C
505	Propylene dichloride (1,2-dichloropropane) [78-87-5]	IV
506	Propylene glycol dinitrate [6423-43-4]	IV
507	Propylene imine [75-55-8]	III
508	Propylene oxide [75-56-9]	III
509	Pyrethrum [8003-34-7]	III
510	Pyridine [110-86-1]	III
511	Resorcinol [108-46-3]	II
512	Rhodium [7440-16-6], Metal and insoluble compounds (as Rh)	III
513	Rhodium [7440-16-6], Soluble compounds (as Rh)	III
514	Ronnel [299-84-3]	IV
515	Rosin core solder pyrolysis products (as Formaldehyde) [8050-09-7]	III
516	Rotenone [83-79-4]	IV
517	Selenium and compounds (as Se) [7782-49-2]	IV
518	Selenium hexafluoride (as Se) [7783-79-1]	IV
519	Sesone [136-78-7]	III
520	Silica, Amorphous — Diatomaceous earth (uncalcined) [61790-53-2]	I-C
521	Silica, Amorphous — fume [69012-64-2]	III
522	Silica, Amorphous — gel	I-C
523	Silica, Crystalline — -quartz [14808-60-7; 1317-95-9] and cristobalite [14464-46-1]	III
524	Silicon carbide [409-21-2] (nonfibrous)	I-C
525	Silicon tetrahydride [7803-62-5]	II
526	Silver [7440-22-4], Metal, dust and fume	III
527	Silver [7440-22-4], Soluble compounds (as Ag)	III
528	Sodium azide [26628-22-8], as sodium azide, hydrazoic acid vapour	I-A
529	Sodium bisulfite [7631-90-5]	I-B
530	Sodium fluoroacetate [62-74-8]	II
531	Sodium hydroxide [1310-73-2]	I-A
532	Sodium metabisulfite [7681-57-4]	I-B

Item	Substance	Category
533	Starch [9005-25-8]	III
534	Stoddard solvent [8052-41-3]	IV
535	Strontium chromate (as Cr) [7789-06-2]	III
536	Strychnine [57-24-9]	II
537	Styrene (monomer) [100-42-5]	IV
538	Subtilisins [1395-21-7; 9014-01-1] (Proteolytic enzymes as 100 % pure crystalline enzyme)	I-C
539	Sucrose [57-50-1]	I-C
540	Sulfometuron methyl [74222-97-2]	III
541	Sulfotep [3689-24-5]	IV
542	Sulfur hexafluoride [2551-62-4]	I-C
543	Sulfur monochloride [10025-67-9]	I-A
544	Sulfur pentafluoride [5714-22-7]	I-A
545	Sulfur tetrafluoride [7783-60-0]	I-A
546	Sulfuric acid [7664-93-9]	IV
547	Sulfuryl fluoride [2699-79-8]	III
548	Sulprofos [35400-43-2]	IV
549	2,4,5-T [93-76-5]	I-C
550	Talc [14807-96-6] , fibrous	III
551	Talc [14807-96-6], non-fibrous	III
552	Tellurium [13494-80-9] and compounds (as Te), excluding hydrogen telluride	IV
553	Tellurium hexafluoride [7783-80-4] (as Te)	II
554	Temephos [3383-96-8]	IV
555	Tetraethyl pyrophosphate (TEPP) [107-49-3]	IV
556	Terephthalic acid [100-21-0]	I-C
557	Terphenyls (o-, m-, p- isomers) [26140-60-3]	I-A
558	1,1,2,2-Tetrabromoethane [79-27-6]	IV
559	1,1,1,2-Tetrachloro-2,2-difluoroethane [76-11-9]	IV
560	1,1,2,2-Tetrachloro-1, 2-difluoroethane [76-12-0]	IV
561	1,1,2,2-Tetrachloroethane [79-34-5]	IV
562	Tetrachloroethylene (perchloroethylene) [127-18-4]	IV
563	Tetrachloronaphthalene [1335-88-2]	III
564	Tetrahydrofuran [109-99-9]	I-B
565	Tetramethyl succinonitrile [3333-52-6]	II
566	Tetranitromethane [509-14-8]	IV
567	Tetryl [479-45-8]	III
568	Thallium, elemental [7440-28-0], and compounds (as Tl)	III
569	4,4'-Thiobis (6-tert-butyl-m-cresol)	I-C
570	Thioglycolic acid [68-11-1]	I-B
571	Thionyl chloride [7719-09-7]	I-A
572	Thiram® [137-26-8]	III
573	Tin [7440-31-5], Metal	III
574	Tin [7440-31-5], Organic compounds (as Sn)	III

Item	Substance	Category
575	Tin [7440-31-5], Oxide and inorganic compounds, except SnH4 (as Sn)	III
576	Titanium dioxide [13463-67-7]	I-C
577	o-Tolidine [119-93-7]	III
578	Toluene [108-88-3]	IV
579	Toluene diisocyanate, 2,4- or 2,6- (or as	III
580	a mixture) [584-84-9; 91-08-7]	
581	o-Toluidine [95-53-4]	IV
582	m-Toluidine [108-44-1]	II
583	p-Toluidine [106-49-0]	IV
584	Tributyl phosphate [126-73-8]	I-B
585	Trichloroacetic acid [76-03-9]	I-B
586	1,2,4-Trichlorobenzene [120-82-1]	I-B
587	1,1,2-Trichloroethane [79-00-5]	IV
588	Trichloroethylene [79-01-6]	II
589	Trichlorofluoromethane [75-69-4]	I-A
590	Trichloronaphthalene [1321-65-9]	III
591	1,2,3-Trichloropropane [96-18-4]	III
592	1,1,2-Trichloro-1,2,2-trifluoroethane [76-13-1]	II
593	Tri-o-cresyl phosphate [78-30-8]	III
594	Triethanolamine [102-71-6]	III
595	Triethylamine [121-44-8]	IV
596	Trifluorobromomethane [75-63-8]	I-C
597	1,3,5-Triglycidyl-s-triazinetrione [2451-62-9]	III
598	Trimellitic anhydride [552-30-7]	III
599	Trimethyl benzene, isomers [25551-13-7; 526-73-8; 95-63-6; 108-67-8]	III
600	Trimethyl phosphite [121-45-9]	I-B
601	Trimethylamine [75-50-3]	I-B
602	2,4,6-Trinitrotoluene (TNT) [118-96-7]	III
603	Triphenyl amine [603-34-9]	I-C
604	Triphenyl phosphate [115-86-6]	IV
605	Tungsten [7440-33-7] (as W)	IV
606	Turpentine [8006-64-2] and selected monoterpenes [80-56-8; 127-91-3; 13466-78-9]	I-B
607	Uranium [7440-61-1] (natural), Insoluble compounds (as U)	III
608	Uranium (natural) [7440-61-1], Soluble compounds (as U)	III
609	n-Valeraldehyde [110-62-3]	I-B
610	Vanadium pentoxide [1314-62-1] as V	I-B
611	Vinyl acetate [108-05-4]	I-B
612	Vinyl bromide [593-60-2]	III
613	Vinyl chloride (monomer) [75-01-4]	III
614	Vinyl cyclohexene dioxide [106-87-6]	III
615	Vinyl toluene [25013-15-4]	I-B
616	Warfarin [81-81-2]	IV
617	Wood dust	III

Item	Substance	Category
618	Xylene (o-, m-, p- isomers) [1330-20-7; 95-47-6; 108-38-3; 106-42-3]	II
619	m-Xylene-alpha, alpha'-diamine [1477-55-0]	I-A
620	Xylidine (mixed isomers) [1300-73-8]	III
621	Yttrium [7440-65-5], metal and compounds (as Y) [7440-65-5]	III
622	Zinc chloride fume [7646-85-7]	II
623	Zinc chromates [13530-65-9;11103-86-9; 37300-23-5] (as Cr)	III
624	Zinc Oxide [1314-13-2]	II
625	Zinc Stearate [557-05-1]	I-C
626	Zirconium [7440-67-7] and compounds (as Zr)	I-C

TABLE OF CONTENTS

3.0	Roles and Responsibilities	3
3.1	Impairment and Conduct	4
3.2	General Safety Rules	4
3.3	Hazardous Working Conditions	5
3.4	Hazardous Atmosphere – Confined Space	7
3.5	Fire Prevention	11
3.6	First Aid	11
3.7	Mine Rescue	12
3.8	Emergency Training	14
3.9	Fire Fighting	15
3.10	Underground Fire Fighting	15
3.11	Underground Coal Fire Fighting	16
3.12	Gas Detectors	17
3.13	Evacuation	17

PERSONNEL SAFETY

Roles and Responsibilities

Manager's Responsibilities

3.0.1 The manager is responsible for ensuring that all activities on the mine site are conducted in a manner that assures the health and safety of persons at the mine.

Supervisor's Responsibilities

3.0.2 (1) A supervisor must ensure that the work the supervisor performs, or over which the supervisor has supervision, is carried out in a manner that assures the health and safety of persons at the mine.

(2) Without limiting subsection (1), a supervisor

(a) must follow safe work procedures and act safely in the workplace at all times,

(b) must ensure the health and safety of the workers under the supervisor's direct supervision,

(c) must, in respect of the requirements that apply to the work over which the supervisor has supervision,

(i) know the requirements,

(ii) meet the requirements, if performing all or part of the work, and

(iii) ensure the requirements are met by the workers performing the work under the supervisor's direct supervision, and

(d) must respond appropriately when becoming aware of an unsafe situation.

Worker's Responsibilities

3.0.3 (1) A worker must ensure that the work the worker performs is carried out in a manner that assures the health and safety of persons at the mine.

(2) Without limiting subsection (1), a worker must

(a) follow safe work procedures and act safely in the workplace at all times,

(b) only carry out the work for which the worker is adequately trained, and

(c) be alert to hazards and report them immediately to the supervisor or manager.

Contractor's Responsibilities

3.0.4 (1) A contractor must ensure that the work the contractor performs, or over which the contractor has supervision, as set out in section 25 of the Act, is carried out in a manner that assures the health and safety of persons at the mine.

(2) Without limiting subsection (1), a contractor must
(a) follow safe work procedures and act safely in the workplace at all times,
(b) ensure the health and safety of the workers under the direct supervision of the contractor, if any, and
(c) be alert to hazards and report them immediately to the supervisor or manager.

Impairment and Conduct

Impaired Persons

3.1.1 No person may enter, remain, or be knowingly permitted to enter or remain in any mine if, in the opinion of management, the person's ability is so impaired, including by way of fatigue, that the person's health or safety, or that of another person, may be endangered.

Drugs and Liquor

3.1.2 (1) A person must not possess intoxicating liquor, cannabis or illegal drugs in or about a mine.

(2) In subsection (1), "cannabis" means cannabis as defined in the *Cannabis Control and Licensing Act*, but does not include medical cannabis or industrial hemp as defined in that Act.

Improper Conduct

3.1.3 A person must not engage in any improper or foolhardy behavior such such as bullying and harassment, sexual harassment, violence, horseplay, scuffling, fighting, playing practical jokes, or other conduct that might create or constitute a hazard to the person or any other person.

Tampering with Safety Devices and Equipment

3.1.4 No person shall, without cause, render ineffective any device, equipment, or material provided for the protection of the health and safety of persons employed in, on or about a mine, or the safety of the public.

General Safety Rules

Age

3.2.1 The manager shall not employ any person under the age of 18 years at a mine except for the purpose of training that person.

Tallying

3.2.2 (1) The manager shall implement an effective system to account for all persons on the mining property.

(2) A written copy of the system implemented, in accordance with 3.2.2 (1) shall be made available to an inspector on request.

Working Alone

3.2.3 When a worker is working alone and may not be able to secure assistance in the event of an injury or other misfortune, the manager shall ensure that a means exists for checking the well-being of the worker and that the interval between checks does not exceed 2.5 hours.

Transportation of Persons

3.2.4 (1) No person shall be transported in the box of a pickup truck, and no person shall ride in a standing position.

(2) No person shall board or leave any vehicle while that vehicle is in motion.

Hazardous Working Conditions

Hazardous Work

3.3.1 The manager or a person authorized by the manager shall personally supervise all work involved in correcting an unusual hazard and such work shall be carried out in accordance with safe working practices and in compliance with this code, and a plan approved by the manager.

Falling Objects

3.3.2 No persons shall be allowed in any location at a mine where persons are working overhead unless adequate protection is provided for their safety.

Drowning Hazard

3.3.3 (1) The manager must ensure that a safe work plan is developed by a qualified person, in consultation with the Occupational Health and Safety Committee and appropriate workers, and implemented before any work begins where drowning may be a risk.

(2) The safe work plan must include the following:

(a) identification of all relevant hazards;

(b) an evaluation of the risk level created by each hazard identified in paragraph (a);

(c) identification of all controls that, when implemented, are intended to mitigate the hazards referred to in paragraph (a);

(d) a requirement to have a spotter if identified as a control under paragraph (c);

(e) identification of safety equipment and safety devices relevant to each task to be performed;

(f) subject to subsections (3) and (4), requirements for the use, storage, maintenance and inspection of the safety equipment and safety devices referred to in paragraph (e);

(g) emergency procedures;

(h) a rescue plan, including a means for orientation, such as a light or beacon, to identify safe egress when work is done at night.

(3) The manager must provide the following personal protective equipment and safety devices to workers working where drowning may be a risk:
  (a) personal floatation devices, accepted by Transport Canada, that do not create an increased risk when worn, as identified in the safe work plan;
  (b) lifebuoys, accepted by Transport Canada, that are
    (i) equipped with heaving lines of adequate length, and
    (ii) placed at conspicuous locations;
  (c) with respect to workers in or on mobile equipment, or non-self-propelled barges or dredges, which have a cab, the following items that must be accessible and secured in the cab for the purpose of emergency egress:
    (i) a glass-breaking tool;
    (ii) a seatbelt cutter;
    (iii) an alternate source of air;
    (iv) a whistle.

(4) The manager must ensure that safety equipment and safety devices, identified in the safe work plan or subsection (3), are
  (a) readily available in safe operating condition, and
  (b) regularly inspected and maintained.

(5) The manager must ensure that all workers working where there is a risk of drowning are trained for the work they are performing.

Moving Machinery and Electrical Contact

3.3.4 Where there is a risk of a worker coming into contact with moving parts of machinery or with electrically energized equipment, or where the work process is such that a similar hazard exists

(1) the clothing of the workers shall fit closely about the body,

(2) dangling neckwear, bracelets, wrist-watches, rings, or similar articles shall not be worn,

(3) the wearing of medic-alert bracelets is permitted when such bracelets are used with transparent rubber band that fit snugly over the bracelets, and

(4) cranial and facial hair shall be confined, or worn at a length which will prevent it from being snagged or caught in the work process.

Materials Handling

3.3.5 Where a materials handling task endangers the safety of the persons doing the work, the manager shall ensure that

(1) the physical parameters of the handling task are redesigned, or

(2) mechanical lifting aids or personal protective equipment is provided, or

(3) the work area where the work is carried out is redesigned to eliminate unsafe conditions relating to floor surfaces, lighting, or obstruction to materials handling, or

(4) a combination of (1), (2), or (3) is implemented.

Avalanche Safety Program

3.3.6 (1) The mine manager must ensure that a written avalanche risk assessment is conducted in accordance with the *Technical Aspects of Snow Avalanche Risk Management – Resources and Guidelines for Avalanche Practitioners in Canada (2016)* in areas where a person may be exposed to an avalanche as determined with reference to chapter 3 of the *Land Managers Guide to Snow Avalanche Hazards in Canada (2002)*.

(2) If avalanche risk is determined under subsection (1), no work may be conducted in the area of avalanche risk until an avalanche safety program is developed by a qualified professional, a professional member of the Canadian Avalanche Association or a person who has qualifications acceptable to the chief inspector.

(3) If eliminating avalanche risk is not practical, the avalanche safety program must include measures and procedures to minimize those risks to provide

(a) monitoring of weather, snow and avalanche conditions,

(b) implementation of closures, temporary evacuations or other measures, as specified in the avalanche safety program, and

(c) safe work procedures to be followed by persons working at the mine.

(4) The avalanche safety program must be integrated with the Mine Emergency Response Plan (MERP) referred to in section 3.7.1 (1) of this code.

Hazardous Atmosphere – Confined Space

Work in Confined Spaces

3.4.1 The mine manager shall ensure that

(a) written procedures are developed and implemented for work in confined spaces in consultation with the OHSC or worker representative, as applicable,

(b) an inventory of all confined spaces is maintained,

(c) each confined space is signed and secured from entry, where practicable, and

(d) each person who is assigned duties or responsibilities related to entry into a confined space is adequately instructed and trained in confined space entry.

Safe Work Procedures to Include

3.4.2 The procedures required under section 3.4.1 shall include all of the following:

(a) assignment of responsibilities, including those of the stand-by person;
(b) a hazard assessment;
(c) the issuance of suitable entry permits identifying
  (i) the supervisor of record,
  (ii) the confined space and the work activities
  (iii) to which it applies,
  (iv) the workers who are inside the space,
  (v) the required precautions for the space,
  (vi) the time of expiration of the permit, and
  (vii) the gas readings results and conditions found in the confined space;
(d) the use of lifelines and harnesses designed for the purpose for which it is intended and that meet the following standards:
  (i) CAN/CSA-Z259.1-05 Body Belts and Saddles for Work;
  (ii) CAN/CSA-Z259.2.1-98 (R2004) Fall Arrest Vertical Lifeline and Rails;
  (iii) CAN/CSA-Z259.2.2-98 (R2004) Self Retracting Device for Personal Fall Arrest Systems;
  (iv) CAN/CSA-Z259.2.3-79 Descent Control Devices;
  (v) CAN/CSA-Z259.20-06 Full Body Harnesses;
  (vi) CAN/CSA-Z259.11-05 Energy Absorbers and Lanyards;
  (vii) CAN/CSA-Z259.12-06 Connecting Components for Personal Fall Arrest Systems ;
  (viii) CAN/CSA-Z259.13-04 Flexible Horizontal Lifeline Systems;
  (ix) CAN/CSA-Z259.16-04 Design of Active Fall Protection Systems;
(e) when lifelines and harnesses cannot be used, sufficient resources with respiratory equipment capable of performing a rescue shall be stationed outside the confined space;
(f) maintenance of an effective means of communication between persons inside and outside the confined space, and between the person outside the confined space and emergency services;
(g) specified time intervals for making visual contact with persons inside the confined space;
(h) specific procedures to be followed whenever welding or burning operations are to be carried out in the confined space;
(i) appropriate breathing apparatus and persons trained in its use and readily available at every confined space in which persons are working,

(j) compressed air used for breathing complying with the requirements of CSA Standard CAN-3-Z1 80.1M85 Series;

(k) lockout, disconnection, blanking or blinding of pipes carrying substances that could be hazardous to the persons entering the confined space in accordance with section 4.11; blanking and blinding shall comply with engineering standards acceptable to the chief inspector;

(l) an Emergency Response Plan and, for facilities without onsite rescue capability, the owner, agent or manager shall make arrangements with an emergency response agency, such as a fire department, detailing the services that are to be provided.

(2) A cylinder of compressed gas is not permitted inside a confined space except for a cylinder of compressed air supplied to a respirator, medical resuscitation equipment, handheld aerosol spray containers, fire extinguishers, or other equipment acceptable to the chief inspector.

(3) If any of the information in section 3.4.2 (1) (c) changes, the manager shall amend the permit.

(4) Records of the permits shall be kept for a minimum of one year.

(5) Electrical tools and equipment used in a confined space shall be

(a) grounded or double-insulated and so marked, and

(b) protected by an approved ground fault circuit interrupter if wet or damp conditions exist inside the space.

(6) Electrical equipment used in a confined space where a hazardous atmosphere is or may be present shall meet the requirements of Section 18 (Hazardous Location) of the *Canadian Electrical Code* Part 1 CAN/CSA C22.1-06.

Test of Confined Space

3.4.3 (1) A person without self-contained breathing apparatus shall not enter a confined space in which a harmful atmosphere might exist or develop until

(a) tests have been made to determine the nature and quantity of harmful vapours, gases, fumes, mists, dusts, and the oxygen content of the atmosphere inside the confined space and these test results shall be recorded by the manager,

(b) the written work procedures under section 3.4.1 (a) have been read and understood by the person and the required emergency and rescue procedures are in place, and

(c) the confined space is being ventilated continuously by a mechanical ventilation system.

(2) A ventilation system for the control of airborne contaminants shall be designed, installed and maintained in accordance with established engineering practices and specified in the written procedures.

(3) If a contaminant is produced in the confined space, it shall be controlled at the sources by a local exhaust ventilation system if practicable, by general ventilation, or by a combination of both.

Test of Intervals

3.4.4 Tests of the atmosphere inside the confined space shall be continuous during the work process to ensure that the quality of the air does not deteriorate and the test results shall be recorded as required by section 3.4.3 (1) (a).

Confined Space Ventilation

3.4.5 Where tests made under 3.4.3 and 3.4.4 or any other test or examination indicates a harmful atmosphere or the presence of a harmful substance, the confined space shall be ventilated or cleaned, or both, and retested or re-examined to ensure that no person without self-contained breathing apparatus is allowed to enter the confined space unless

(1) the atmosphere or substance in the confined space is no longer considered harmful according to the acceptable standards prescribed in part 2 of the code, and

(2) the oxygen content of the atmosphere inside the confined space is not less than 19.5%.

Wearing of Protective Equipment

3.4.6 (1) Where tests under sections 3.4.3 and 3.4.4 indicate the presence of a hazardous atmosphere and it is not practical to provide a safe, respirable atmosphere

(a) the persons entering the confined space shall

(i) wear self-contained breathing apparatus and personal protective equipment, or

(ii) have an approved supplied air system equipped with an emergency escape bottle, and wear personal protective equipment,

(b) the concentration of flammable substances shall be maintained below 20% of the lower explosive limit as determined by continuous testing, and

(c) all possible sources of ignition shall be eliminated or controlled, and only non-sparking tools may be used where flammable substances exist.

(2) If inerting is required or utilized, persons entering the confined space shall adhere to established engineering practices.

Fire Prevention

Open Flame Underground

3.5.1 No person shall

(1) light or build a fire in an underground mine, or

(2) weld, cut by the use of heat or flame, or use a blowtorch in an underground coal mine without the written permission of the chief inspector, and

(3) the manager of an underground coal mine may submit for approval by the chief inspector a procedure for cutting and welding underground, and once this procedure is approved need only notify an inspector for future cutting and welding within the parameters of the approval.

Prohibited Articles

3.5.2 No person shall possess while underground in a coal mine or in any part of a mine designated by the manager

(1) a match or apparatus of any kind for creating an open flame or spark, or

(2) cigarettes, cigars, or smoking materials in any form.

Designation of Fire Hazard Areas

3.5.3 Fire hazard areas shall be identified by warning signs, and persons shall not smoke, use open flame lamps, matches, or other means of producing heat or fire in designated fire hazard areas.

First Aid

First Aid Supplies and Services

3.6.1 The manager must ensure that first aid supplies and services, as required by the Workers' Compensation Board, are provided and maintained at the mine site.

3.6.2 An inspector may order an increase in the first aid supplies or services required by section 3.6.1.

Means of Communication

3.6.3 The manager must ensure that a means of communication that is acceptable to an inspector, and by which the services of a physician can be obtained expeditiously, is provided at the mine site.

Exploration First Aid

3.6.4 The manager for exploration activities must ensure that,

(a) at a mine site with mechanical disturbance, there are

(i) a stretcher, a naloxone kit, an automated external defibrillator and an epinephrine auto injector, and

(ii) provision for continuous and consistent emergency communication,

(b) at each drill at an exploration drill site, and during each shift, at least 2 members of the drill crew have

(i) a valid intermediate first aid certificate and transportation endorsement, or

(ii) an equivalent standard acceptable to the chief inspector, and

(c) at each drill or drilling area at a helicopter supported drilling exploration site, there is an emergency shelter, appropriate for the site environment, that has necessary provisions for at least 2 days.

Mine Rescue

Mine Emergency Response Plan

3.7.1 (1) The manager must ensure that a Mine Emergency Response Plan (MERP) is developed, filed with the chief inspector, followed in the case of emergency, kept up to date and kept at the mine.

(2) The Mine Emergency Response Plan must

(a) outline the response procedures that are essential for effective and timely management of an emergency situation,

(b) contain all of the elements required in the "*Mine Emergency Response Plan Guidelines for the Mining Industry*", as amended from time to time,

(c) include the emergency preparedness and response plans as required under section 10.6.10 of this code regarding tailings storage facilities, and

(d) include affected communities and First Nations in the identification of potential hazards, emergency communications and responses.

(3) The manager must ensure that annual testing of the effectiveness of the Mine Emergency Response Plan is conducted and that First Nations are included in the annual testing of the plan for hazards identified.

(4) A record of the annual testing referred to in subsection (3) must be included in the annual report submitted to the chief inspector.

Underground

3.7.2 (1) At an underground mine, the manager shall establish and maintain certified and equipped underground mine rescue personnel who have the qualifications specified in section 3.7.7 (1).

(2) Mine rescue personnel referred to in subsection (1) must be deployed as follows:
   (a) where the number of employees underground at one time is greater than 50, 2 teams;
   (b) where the number of employees underground at one time is less than 50, but greater than 10, 1 team;
   (c) where there are 10 or less employees working underground at any one time, 4 persons.

Surface at Underground Mine

3.7.4 At all underground mines where a surface fire can compromise people, plant, or equipment the manager shall ensure sufficient trained personnel and equipment are available to provide fire suppression capability for the site.

Open Pit

3.7.5 The manager of an open pit mine employing more than 25 persons per shift shall ensure that
   (1) there is one fully trained and equipped mine rescue team, and
   (2) on every shift where more than 10 persons are working, there are four persons trained in mine rescue procedures.

Team Complement

3.7.6 The normal complement of a mine rescue team shall be 6 qualified members, one of whom shall be the team captain, one the vice captain, and one the coordinator who shall remain at the fresh air base at all times.

Mine Rescue Teams

3.7.7 A person shall not be considered as a qualified member of a mine rescue team unless
   (1) the person possesses a valid mine rescue certificate and a valid St. John standard first aid certificate and transportation endorsement or an equivalent standard acceptable to the chief inspector, free from a beard, moustache, or sideburns that could interfere with the facepiece seal of any breathing apparatus,
   (2) considered competent to act as a mine rescue team member by the person appointed as a trainer under section 3.7.9, and
   (3) medically fit for the nature of the work required.

Mine Rescue Records

3.7.8 The manager shall ensure a record of all mine rescue training is maintained at the mine site, and shall
   (1) ensure the logbook is maintained by the qualified person appointed by the manager, to conduct the training,

(2) contain the particulars of the training, including the names of those participating and the trainer, and

(3) shall note the condition of all equipment used during the training.

3.7.9 The manager shall

(1) appoint a qualified person as a trainer for mine rescue team members,

(2) ensure that all mine rescue team members practice as a team for not less than 8 hours during each 3 month the mine operates, and

(3) ensure that all mine rescue personnel are not underground at any one time except for rescue work or training.

Type of Breathing Apparatus

3.7.10 Where self-contained breathing apparatus is required it shall be of a type approved by a recognized certification agency, and suitable for the intended work.

Mine Plans for Rescue Purposes

3.7.11 The manager shall ensure that the plans required under part 6 of the code are readily available for the use of mine rescue teams.

3.7.12 The manager shall appoint a qualified person

(1) to be responsible for the care and maintenance of all rescue apparatus,

(2) the entries into a logbook to be kept at the mine recording the condition of all equipment used for mine rescue or fire fighting, and

(3) the care of the rescue equipment storage room, and equipment caches.

Rescue Station

3.7.13 The chief inspector may establish mine rescue stations at places the chief inspector considers necessary, all of which shall be equipped and maintained by the government under the direction of the chief inspector.

Emergency Training

Hoistroom Breathing Air and Training

3.8.1 (1) One or more units of self-contained breathing apparatus and a fully charged cylinder of compressed air containing not less than 8.5 cubic meters of free air at normal local atmospheric conditions shall be maintained in every hoist room.

(2) Every hoist operator and cage tender who may be required to use demand breathing apparatus shall be responsible for ensuring that the apparatus is always readily available to them while they are underground.