C-121-1 Series Roundabout Right-Turn Truck Signs		
 C-121-1  C-121-Ta  C-121-Tb	Sign sizes (mm) C-121-1 (750 x 750) C-121-Ta (750 x 300) C-121-Tb (750 x 300)	The signs in the C-121 series should be used to convey the right-turn path for trucks in a roundabout. The right-turn movement is typically the most challenging for trucks in roundabouts. If the work activity encroaches into the space needed by right-turning trucks in the roundabout, it may still be possible to allow trucks to make the right-turn manoeuvre by instructing drivers to continue around the roundabout so that they re-approach the exit at a wider angle.
C-128 Series Construction Speed Limit Ahead		
 C-128	Sign sizes (mm) C-128-x (900 x 900) C-128-xx (1200 x 1200)	The CONSTRUCTION SPEED LIMIT AHEAD C-128 is used in advance of R-003 and R-004 Construction Speed Zone signs to replace any transition speed zones installed for speed reductions in excess of 30 km/h. They can also be used to provide additional emphasis, where deemed necessary, of a Construction Speed Zone. See *Section 2.4.5: Transition Speed Zones* for additional guidelines on how this sign should be used.

C-129 Series Added Lane		
 C-129-L	Sign sizes (mm) C-129-L (750 x 750) C-129-Lx (900 x 900) C-129-Lxx (1200 x 1200)	The ADDED LANE C-129-L sign warns motorists of the convergence of two roads, or approaches, where an additional lane (generally 1 km or longer) is added to the mainline highway such that merging is not necessary. The sign placement should be based on site conditions so that it is visible by motorists on both approaches. If this is not possible, signs should be erected on both approaches.
 C-129-R	C-129-R (750 x 750) C-129-Rx (900 x 900) C-129-Rxx (1200 x 1200)	

C-130 **Lane Closed Ahead** **C-130-Ta/Tb Distance Tabs**		
 C-130-L  C-130-R  C-130-Ta  C-130-Tb	Sign sizes (mm) C-130-L/R (750 x 750) C-130-L/Rx (900 x 900) C-130-L/Rxx (1200 x 1200)* C-130-Ta/Tb (600 x 300) C-130-Ta/Tbx (750 x 400) C-130-Ta/Tbxx (900 x 450)*	The LANE CLOSED AHEAD C-130-L/R sign should be used in temporary conditions to indicate that the left or right lane is closed ahead on a roadway that has two or more lanes travelling in the same direction. The C-130-L/R sign should be repeated where the speed limit in the advance warning area is 70 km/h or higher, such as shown in *Section 8.6: Right Lane Closed* and *Section 8.7: Left Lane Closed.* The upstream sign of the pair should also display a bottom-mounted distance tab indicating the distance to the beginning of the lane closure taper. C-130-L/R signs are generally placed on the right shoulder, but where adequate space is available on the left or median side, the signing should be repeated on the median across from the right shoulder signage. On conventional highways, the C-130-T distance tab should generally display: • 200 m - for speed limits of 70 or 80 km/h • 400 m - for speed limits of 90 or 100 km/h • 600 m - for speed limits of 110 or 120 km/h The XX KM C-130-Tb distance tab may be used to provide additional warning for all signs in this series.

C-132 Two-Way Traffic Ahead		
 C-132	Sign sizes (mm) C-132 (750 x 750) C-132-x (900 x 900)*	The TWO-WAY TRAFFIC AHEAD C-132 sign is used to warn drivers of a temporary, undivided, two-lane, two-way roadway. A typical application is where one roadway of a divided highway is closed and the other roadway must carry traffic in both directions. Appropriate signing and other devices should be used to merge traffic on a multilane, one-way roadway into a single lane well in advance of the point where that traffic enters the two-way roadway. A C-132 sign should be mounted on the right of the single lane section and, if space is available, on the left as well. See the TWO-WAY TRAFFIC R-010 sign for information on two-way signing at the beginning of a two-lane, two-way roadway.

C-134 Road Narrows Ahead		
 C-134	Sign sizes (mm) C-134 (750 x 750) C-134-xx (1200 x 1200)	The ROAD NARROWS AHEAD C-134 sign should be used on two-way roads in advance of a temporary reduction in the width of either or both lanes that makes it necessary to warn drivers so that they may pass safely. The reduced width at which safe passing is still possible will depend on such factors as traffic composition, traffic speed and volume, highway alignment, sight distance, etc., but it will generally be about 5.5 metres. If the reduced width is too narrow for safe passing, even at reduced speeds, a one-way operation must be implemented. The C-134 sign is not intended for use on narrow minor roads that have low travel speeds and carry little traffic.
C-135 Narrow Structure Ahead **C-135-Ta One Lane Tab**		
 C-135  C-135-Ta	Sign sizes (mm) C-135 (750 x 750) C-135-x (900 x 900) C-135-Ta (600 x 300) C-135-Tax (750 x 400)	The NARROW STRUCTURE AHEAD C-135 sign is used on a two-lane, two-way roadway in advance of a bridge that has a temporary clear deck width of 5.5 metres or more but less width than the roadway approach. Where the temporary clear width of a bridge deck is less than 5.5 metres, ONE LANE C-135-Ta tabs are placed below the C-135 signs, and a YIELD TO ONCOMING TRAFFIC R-056-1 sign is erected on the approach with the best sight distance across the bridge. Depending on road conditions, such as traffic composition, traffic speed and volume, approach alignment, sight distance, etc., it may be appropriate to designate some bridges as one-way even when the temporary clear deck width is 5.5 metres or more.

C-136 Merging Traffic Ahead		
 C-136-L  C-136-R	Sign sizes (mm) C-136-L (750 x 750) C-136-Lx (900 x 900) C-136-R (750 x 750) C-136-Rx (900 x 900)	The MERGING TRAFFIC AHEAD C-136-L/R sign should be used in advance of all temporary on-ramps and acceleration lanes under repair. The sign is required to warn traffic on the main roadway, regardless of whether the ramp traffic is controlled by a YIELD R-002 sign or a MERGE C-137-1 sign.
C-137-1 Merge		
 C-137-1	Sign sizes (mm) C-137-1 (750 x 750)* C-137-1x (900 x 900)*	The MERGE C-137-1 sign should be used at a temporary freeway on-ramp where there is an acceleration lane of sufficient length for vehicles to reach the freeway speed limit before entering a through lane.
C-137-2 Alternate When Merging		
 C-137-2	Sign sizes (mm) C-137-2 (750 x 750) C-137-2x (900 x 900)	The ALTERNATE WHEN MERGING C-137-2 sign may be used in conjunction with the MERGE C-137-1 sign. It is positioned downstream of the C-137-1 sign at the merge point, which is usually immediately ahead of the beginning of the acceleration lane taper. The C-137-2 sign may also be used to manage merging situations created by lane drops in high-volume areas.

C-137-5LR Merge Arrow		
 C-137-5L  C-137-5R	Sign sizes (mm) C-137-5L (750 x 750) C-137-5Lx (900 x 900) C-137-5R (750 x 750) C-137-5Rx (900 x 900)	The MERGE ARROW C-137-5L and C-137-5R signs are used to indicate the merge point. They are used in zipper merge situations as outlined in *Section 9.18: Lane Closure with Zipper Merge Signing (Queues < 800 m)* and *Section 9.19: Lane Closure with Zipper Merge Signing (Queues ≥ 800 m)*.

C-137-7 and C-137-8 Through Traffic Merge Left/Right		
 C-137-7  C-137-8	Sign sizes (mm) C-137-7 (750 x 750) C-137-7x (900 x 900) C-137-7xx (1200 x 1200) C-137-8 (750 x 750) C-137-8x (900 x 900) C-137-8xx (1200 x 1200)	A THROUGH TRAFFIC MERGE LEFT C-037-7 sign or a THROUGH TRAFFIC MERGE RIGHT C-037-8 sign is used ahead of a lane closure at a multilane intersection where the typical lane assignment is disrupted by the lane closure. For example, it is used at a multilane intersection where a through lane is closed and drivers must use either the right lane or the left lane to go through the intersection. The C-037-7 and C-037-8 signs are typically positioned following the initial CREW WORKING AHEAD C-004 or CONSTRUCTION AHEAD C-018-1A sign, and may be used either singly or in pairs. When the signs are used in pairs, the upstream sign should include a distance tab.

C-138-LR Zipper Merge		
 C-138-L  C-138-R	Sign sizes (mm) C-138-L (1220 x 1830) C-138-R (1220 x 1830)	The ZIPPER MERGE C-138-LR sign, may be used at merge locations in addition to—or instead of—the ALTERNATE WHEN MERGING C-137-2 sign to promote efficient merging behaviour in congested conditions. The C-138-LR sign should typically be positioned at the merge point, immediately in advance of the beginning of the acceleration lane taper. See *Section 9.18: Lane Closure with Zipper Merge Signing (Queues < 800 m)* and *Section 9.19: Lane Closure with Zipper Merge Signing (Queues ≥ 800 m)* for illustrations on how these signs should be placed. *continued →*

C-138-T Zipper Merge (Optional Tabs to Enhance Information on the Parent Sign)		
	Sign sizes (mm)	See *Section 9.18: Lane Closure with Zipper Merge Signing (Queues < 800 m)* and *Section 9.19: Lane Closure with Zipper Merge Signing (Queues ≥ 800 m)* for illustrations on how these tabs should be applied with the C-138LR ZIPPER MERGE parent sign.
 C-138-Ta	C-138-Ta (1220 x 915)	The ALTERNATE WHEN MERGING C-138-Ta tab or the USE BOTH LANES TO MERGE POINT C-138-Tb tab should be used below the sign when the sign is positioned in advance of the merge point because of sight distance problems, conflicts with other signs, or the absence of appropriate mounting space.
 C-138-Tb	C-138-Tb (1220 x 1220)	The USE BOTH LANES DURING BACKUPS C-138-Tc tab is used if long queues are expected. It may be repeated every 1 to 2 km, based on local site conditions, for the estimated maximum queue distance.
 C-138-Tc	C-138-Tc (1220 x 1220)	The TAKE TURNS C-138-Td tab encourages drivers, both merging and those on the main line, to zipper merge and utilize both lanes until a merge point. This tab is used in conjunction with the MERGE ARROW C-137-5LR and/or ZIPPER MERGE C-138-LR signs and are mounted below the parent sign.
 C-138-Td	C-138-Td (1220 x 610)	The TAKE TURNS AT MERGE C-138-Te tab may be used in conjunction with the ROADWAY/LANE CLOSED AHEAD C-030 series signs and is mounted below the parent sign.
 C-138-Te	C-138-Te (1220 x 610)	The MERGE LIKE A ZIPPER C-138-Tf tab may be used in conjunction with the ZIPPER MERGE C-138-LR sign and is mounted below the parent sign.
 C-138-Tf	C-138-Tf (1220 x 610)	

C-141 Slippery Ahead When Wet		
 C-141	Sign sizes (mm) C-141 (750 x 750) C-141-x (900 x 900)	The SLIPPERY AHEAD WHEN WET C-141 sign should be used when there is a possibility of rain or heavy dew on work that has rendered a finished or unfinished road surface potentially more slippery than normal. It may also be required for confirmation on long sections. When appropriate, the C-141 sign may be used in conjunction with the FRESH OIL C-014 sign or other warning-type signs.
C-149 Pavement Ends		
 C-149	Sign sizes (mm) C-149 (750 x 750) C-149-x (900 x 900)	The PAVEMENT ENDS C-149 sign should be used where an asphalt, concrete, or other finished pavement surface ends and a gravel or dirt section begins. If the start of a paved section of roadway appears to be a hazard, the sign may be flipped to warn of the end of a gravel section.

C-154 Hazard Markers		
 C-154-D  C-154-L  C-154-R	Sign sizes (mm) C-154-D (300 x 900) C-154-L (300 x 900) C-154-R (300 x 900)	HAZARD C-154 markers should be used to mark: • The inside edge of temporary obstructions—such as bridge end posts—that encroach into a through lane or onto the normal shoulder of a highway. • The ends or corners of traffic islands that face, and are adjacent to, oncoming traffic. The hazard marker stripes slope downward towards the side or sides of the obstruction by which traffic is allowed to pass: • DOUBLE HAZARD C-154-D markers are used where traffic travelling in one direction is allowed to proceed to both the left and the right of an obstruction. • HAZARD LEFT C-154-L markers are used to mark obstructions on the driver's left. • HAZARD RIGHT C-154-R markers are used to mark obstructions on the driver's right. When used to mark obstructions like bridge end posts, the C-154-L/R markers are positioned to mark the inside edge of the obstructions. C-154-L/R markers are mounted on posts immediately in advance of the obstruction being identified, and generally with the bottom of the markers about one metre above the level of the travelled roadway. These are low-mounted devices placed very close to traffic. They will therefore become dirty more quickly than other signs and will require more frequent cleaning, especially to maintain effectiveness at night.
C-162 Chevron Alignment Marker		
 C-162	Sign sizes (mm) C-162 (600 x 750) C-162-x (750 x 900) C-162-xx (900 x 1200)*	CHEVRON ALIGNMENT C-162 markers may be used on the outside of temporary but severe changes in horizontal alignment in conjunction with advance warning signs and other delineation devices. C-162 markers must be placed so that at least three are used and two of them are always visible to drivers as they negotiate the change in alignment.

C-170 Logging Trucks Crossing/Entering Highway		
 C-170-L  C-170-R	Sign sizes (mm) C-170-L (750 x 750) C-170-Lx (900 x 900) C-170-R (750 x 750) C-170-Rx (900 x 900)	The LOGGING TRUCKS CROSSING/ENTERING HIGHWAY C-170-L/R sign should be used temporarily in advance of logging road accesses where logging trucks frequently cross, enter, or leave a roadway. The direction of the sign indicates the direction from which the logging truck will enter the roadway. A NO PASSING FOR 150 m C-172-T sign may be post-mounted below a C-170-L/R sign for the direction of travel in which normal pavement markings indicate that overtaking is permissible. A second C-170-L/R sign and, if required, a C-172-T sign, may be placed on the left shoulder if this is considered necessary. C-170-L/R signs and C-172-T signs should be covered or removed whenever truck hauls are not in progress.

C-172 Trucks Crossing/Entering Highway		
 C-172-L  C-172-R	Sign sizes (mm) C-172-L (750 x 750) C-172-Lx (900 x 900) C-172-R (750 x 750) C-172-Rx (900 x 900)	The TRUCKS CROSSING/ENTERING HIGHWAY C-172-L/R sign should be used temporarily in advance of gravel pit accesses, haul road crossings, etc., where long and/or slow-moving trucks frequently cross, enter, or leave a roadway. The direction of the sign indicates the direction from which the truck will enter the roadway. A NO PASSING FOR 150 m C-172-T sign may be post-mounted below the C-172-L/R sign for the direction of travel in which normal pavement markings indicate that overtaking is permissible. A second C-172-L/R sign and, if required, a C-172-T sign, may be placed on the left shoulder if this is considered necessary. C-172 and C-172-T signs should be covered or removed whenever truck hauls are not in progress.

C-172-T No Passing for 150 m		
 C-172-T	Sign sizes (mm) C-172-T (600 x 450) C-172-Tx (750 x 600)	The NO PASSING FOR 150 m C-172-T sign is used only immediately below C-170-L/R and C-172-L/R signs. It is not required where overtaking is already prohibited by a barrier line, but it should be used in locations where the normal pavement markings permit passing.

C-180 Cattle Drive		
 C-180	Sign sizes (mm) C-180 (750 x 750) C-180-x (900 x 900)	The CATTLE DRIVE C-180 sign should be used instead of the CREW WORKING AHEAD C-004 sign for traffic control involving cattle drives.
C-183 Series Bike Hazard		
 C-183  C-183-Ta  C-183-Tb  C-183-Tc	Sign sizes (mm) C-183 (450 x 450) C-183-Ta (400 x 200) C-183-Tb (400 x 200) C-183-Tc (400 x 200)	The BIKE HAZARD C-183 series is typically used on local or low-speed arterial roadways to advise cyclists of potentially hazardous road conditions in the work zone, including changes to the pavement surface that could affect stability. The BIKE HAZARD C-183 sign should be assembled with the appropriate tab to provide specific information: • Use the CYCLISTS USE CAUTION C-183a tab to tell the cyclist what to do. • Use the UNEVEN ROAD C-183b tab or the UNEVEN PATHWAY C-183c tab to describe the nature of the hazard. The C-183 sign and tab should be erected just in advance of the hazard, subject to practical field limitations.
C-184 Cyclist Right-of-Way		
 C-184	Sign sizes (mm) C-184 (750 x 750) C-184x (900 x 900) C-184xx (1200 x 1200)	The CYCLIST RIGHT-OF-WAY “Take the Lane” C-184 sign is to be used where there is limited space for side-by-side vehicle and cyclist operations, and the cyclist should use the centre of the travel lane. It should be used only on low-speed roadways for a limited distance (typically less than 150 metres).

C-185-1 Smoke Ahead
C-185-1 Tabs



C-185-1



C-185-1Ta



C-185-1Tb

Sign sizes (mm)

C-185-1 (750 x 750)

C-185-1x (900 x 900)

C-185-1Ta (600 x 300)

C-185-1Ta-x (750 x 450)

C-185-1Tb (600 x 300)

C-185-1Tb-x (750 x 450)

The SMOKE AHEAD C-185-1 sign should be placed in advance of an area where smoke from a nearby forest fire or controlled burn may obscure the view ahead for drivers.

The appropriate CONTROLLED BURN C-185-1Ta tab or FOREST FIRE C-185-1Tb tab must accompany the SMOKE AHEAD sign.

The C-185-1 sign and tab should be positioned so that they are seen by drivers who have not yet encountered smoke on the roadway but may be able to see it in the distance. Depending on the situation and the severity of the smoke hazard, the C-185-1 sign may be followed by additional signage, such as the REDUCE SPEED C-032 sign or the PREPARE TO STOP C-029 sign.

Signs in this series may also be used with the ROAD CLOSED R-012 sign.

Depending on the wind conditions, the C-185-1 sign may have to be adjusted frequently to remain in advance of the smoke.

C-185-2 Reduced Visibility Hazard
C-185-2 Tabs


C-185-2



C-185-2Ta



C-185-2Tb

Sign sizes (mm)

C-185-2 (750 x 750)

C-185-2x (900 x 900)

C-185-2Ta (600 x 300)

C-185-2Ta-x (750 x 450)

C-185-2Tb (600 x 300)

C-185-2Tb-x (750 x 450)

The REDUCED VISIBILITY HAZARD C-185-2 sign may be used where visibility is reduced by temporary conditions like dust, smoke, or other blowing or suspended particulate matter.

If the reduced visibility is expected to continue over two or more kilometres, the signs should be used in conjunction with appropriate tabs such as SMOKE C-185-2Ta and/or REDUCED VISIBILITY NEXT XX KM C-185-2Tb tabs explaining the reason for the reduced visibility and the distance over which it will be encountered.

The sign should not be used in a work zone as a substitute for dust control methods.

C-185-3 Use Headlights – Extreme Dust		
 C-185-3	Sign sizes (mm) C-185-3 (750 x 750) C-185-3x (900 x 900)	The USE HEADLIGHTS – EXTREME DUST C-185-3 sign should be used when a severe dust condition obscures the view ahead for drivers. This may occur on seal coat or graveling operations. To the extent possible, the sign should be positioned in advance of the point at which drivers encounter the dust condition. It may have to be repositioned frequently because of changing wind and weather conditions.
C-185-4 Fire Activity		
 C-185-4A  C-185-4B	Sign sizes (mm) C-185-4A (750 x 750) C-185-4Ax (900 x 900) C-185-4Axx (1200 x 1200) C-185-4B (750 x 750) C-185-4Bx (900 x 900) C-185-4Bxx (1200 x 1200)	The FIRE ACTIVITY C-185-4B sign may be used in advance of an area with fire activity. It warns motorists of the potential for fire fighting personnel and equipment adjacent to the roadway. It may also warn of smoke and limited visibility. The FIRE ACTIVITY AHEAD C-185-4A sign may be used in conjunction with the FIRE ACTIVITY C-185-4B sign to provide additional warning.

C-187 Turn on Headlights in Tunnel **C-187-T Tunnel Lighting Work in Progress Tab**		
 C-187	Sign sizes (mm) C-187 (750 x 750)* C-187-x (900 x 900)*	The TURN ON HEADLIGHTS IN TUNNEL C-187 sign and the TUNNEL LIGHTING WORK IN PROGRESS C-187-T tab should be used in advance of tunnels in which workers are present and normal tunnel lighting may be affected.
 C-187-T	C-187-T (600 x 450)* C-187-Tx (750 x 450)*	

C-190 Evacuation Route **C-190 Tabs**		
 C-190	Sign sizes (mm) C-190 (750 x 750)* C-190-x (900 x 900)*	The EVACUATION ROUTE C-190 signs and tabs should be used in the event of a natural disaster or other event that requires the evacuation of an area. They should be set up to guide drivers along the evacuation route out of the affected area. The setup for C-190 signs is similar to that for detour route signs, with appropriate directional arrows used in advance of and, where necessary for confirmation, beyond all decision points along the evacuation route to assure drivers that they are following the intended path.
 C-190-TaA	C-190-TaA (600 x 300)* C-190-TaA-x (750 x 400)*	
 C-190-TaLR	C-190-TaLR (600 x 300)* C-190-TaLR-x (750 x 400)*	

C-201 Road Closed Ahead Local Traffic Only		
 C-201-1  C-201-2  C-201-3	Sign sizes (mm) C-201-1 (1220 x 610) C-201-1x (1830 x 915) C-201-2 (1220 x 610) C-201-2x (1830 x 915) C-201-3 (1220 x 406) C-201-3x (1830 x 610)	The ROAD CLOSED XXX M AHEAD LOCAL TRAFFIC ONLY C-201-1 and ROAD CLOSED XX KM AHEAD LOCAL TRAFFIC ONLY C-201-2 may be used to provide additional warning to motorists of a road closure ahead. The ROAD CLOSED LOCAL TRAFFIC ONLY C-201-3 sign may be placed on the barricade at the beginning of the road closure to indicate that the road is closed, and only local traffic may is allowed. The “LOCAL TRAFFIC ONLY” text may be replaced with custom messaging such as road closure times or dates to provide more information representing local conditions to the road user. See *Section 19.6: Roadway Closure with Detour (≤ 60 km/h)* and *Section 19.7: Roadway Closure with Detour (≥ 70 km/h)* for additional guidance on signing road closures.
C-202 Sidewalk Closed		
 C-202	Sign sizes (mm) C-202 (900 x 450) C-202-x (1200 x 600) C-202-xx (1830 x 915)	The SIDEWALK CLOSED C-202 sign should be used where it is necessary to close a sidewalk. It should be placed on a barricade immediately in advance of the closed area, on both approaches to the closed area.

C-203 Sidewalk Closed – Cross Here		
 C-203-L	Sign sizes (mm) C-203-L (900 x 450) C-203-Lx (1200 x 600) C-203-Lxx (1830 x 915)	The SIDEWALK CLOSED – CROSS HERE C-203-L/R sign is usually mounted on a barricade. It is positioned in advance of the sidewalk closure at an appropriate crossing location so that pedestrians are directed to an appropriate crossing facility, usually an existing intersection or mid-block crosswalk.
 C-203-R	C-203-R (900 x 450) C-203-Rx (1200 x 600) C-203-Rxx (1830 x 915)	
C-204 Exit Open		
 C-204	Sign sizes (mm) C-204 (1200 x 900)	The EXIT OPEN C-204 sign is used in advance of an exit ramp that is open but for which the open status may not be clear to drivers because of road work taking place in the immediate vicinity of the ramp. This sign may be placed as a standalone sign or mounted below a guide sign for the exit.
C-205-A Exit Closed Ahead		
 C-205-A	Sign sizes (mm) C-205-A (750 x 750) C-205-Ax (900 x 900) C-205-Axx (1200 x 1200)	The EXIT CLOSED AHEAD C-205-A sign should be used in advance of a temporarily closed exit ramp. In areas where there are two or more exits in close proximity, a C-130-T distance tab may be used with the C-205-A sign to provide clarity about which exit is closed.

B-C-002 Bicycle Lane Closed		
 B-C-002	Sign sizes (mm) B-C-002 (450 x 450)*	The BICYCLE LANE CLOSED B-C-002 sign should be used where a bicycle lane or route is temporarily closed. Wherever possible, this sign should be accompanied by BICYCLE DETOUR B-C-004 signs to direct cyclists around the closed area.

B-C-004 Bicycle Detour		
 B-C-004-1A  B-C-004-1L  B-C-004-1R  B-C-004-2	Sign sizes (mm) B-C-004-1A (450 x 450)* B-C-004-1L (450 x 450)* B-C-004-1R (450 x 450)* B-C-004-2 (450 x 450)*	The appropriate BICYCLE DETOUR B-C-004 sign should be used immediately in advance of all decision points along a cycling detour route. Confirmation signs should also be placed following decision points to assure cyclists that they are following the intended route. • The BICYCLE DETOUR AHEAD B-C-004-1A sign may be used after a BICLYCLE LANE CLOSED B-C-002 sign to indicate that the detour is ahead, and as a confirmation sign along the detour route. • The BICYCLE DETOUR LEFT B-C-004-1L and BICYCLE DETOUR RIGHT B-C-004-1R signs should be used to indicate decision points along the detour route. • At the end of the detour, the BICYCLE DETOUR ENDS B-C-004-2 sign should be used to indicate that cyclists are now returned to the original route. • The B-C-004 tabs indicate distances related to the detour route: - Tab B-C-004-Ta should be used at the beginning of the detour to inform cyclists of the overall length of the detour. - Tabs B-C-004-Tb and B-C-004-Tc may be used in conjunction with the appropriate B-C-004-1 sign to indicate the distance between decision points for improved cyclist navigation. *continued →*

B-C-004 Bicycle Detour (continued)		
 B-C-004-Ta  B-C-004-Tb  B-C-004-Tc	Sign sizes (mm) B-C-004 Ta (400 x 200)* B-C-004 Tb (400 x 200)* B-C-004 Tc (400 x 200)*	Where the detour route for drivers and cyclists is the same, bicycle detour signs are not necessary because cyclists may follow the general purpose C-005 and C-006 construction detour signs.
B-C-020 Bicycles and Pedestrians Slow **B-C-020-T Watch for Pedestrians Tab**		
 B-C-020  B-C-020-T	Sign sizes (mm) B-C-020 (450 x 450)* B-C-020-T (400 x 200)*	The BICYCLE AND PEDESTRIANS SLOW B-C-020 sign should be used where pedestrian-cyclist interaction is changed because of construction activity. Examples of situations where this sign should be used are: • a shared path that is narrowed during construction • a formerly exclusive cycling facility that is now temporarily shared with pedestrians • a location at which pedestrians may be unexpectedly crossing a cycling facility The WATCH FOR PEDESTRIANS B-C-020-T tab should be used in conjunction with the B-C-020 sign to clarify why cyclists are expected to slow.

B.2.2 Regulatory Signs

Regulatory signs impose legal requirements and may not be used without permission from the Road Authority. They are typically either square or rectangular—with the long dimension vertical—and typically display black messages on white backgrounds or vice versa.

R-001 Stop **R-001 Tabs**		
	Sign sizes (mm)	The STOP R-001 sign may be required to assign the normal right-of-way rule at temporary intersections.
 R-001	R-001 (750 x 750) R-001-x (900 x 900) R-001-xx (1200 x 1200)	The R-001 sign should be mounted at a height of approximately 1.5 to 2.0 metres and in approximately the same position as a permanent STOP sign. Where all approaches to a three- or four-leg temporary intersection are controlled by R-001 signs, the signs should be supplemented with R-001 tabs indicating the number of approaches involved. If a temporary STOP sign is not clearly visible for the safe stopping distance on the approach, a STOP AHEAD C-111 sign is required to alert drivers to the upcoming R-001 sign. A STOP AHEAD C-111 sign may also be needed if a temporary STOP sign is to be installed at a location where drivers would not normally expect to find one.
 R-001-Ta	R-001-Ta (450 x 250) R-001-Tax (600 x 300) R-001-Taxx (750 x 400)	
 R-001-Tb	R-001-Tb (450 x 250) R-001-Tbx (600 x 300) R-001-Tbxx (750 x 400)	
 R-001-Tc	R-001-Tc (450 x 250) R-001-Tcx (600 x 300) R-001-Tcxx (750 x 400)	

R-002 Yield		
 R-002	Sign sizes (mm) R-002 (900 x 900) R-002-x (1200 x 1200)	The YIELD R-002 sign may be used in temporary situations where the normal right-of-way rule cannot be applied safely but where a STOP R-001 sign would be overly restrictive. An example of appropriate use of an R-002 sign would be at a temporary freeway on-ramp or other such one-way approach that merges with a through roadway at a narrow angle. A MERGE C-137-1 sign is used instead of a YIELD R-002 sign if an acceleration lane of sufficient length exists for on ramp traffic to reach the through roadway speed limit before entering a through lane. The YIELD R-002 sign should be mounted at a height of approximately 1.5 to 2.0 metres and in approximately the same position as a permanent YIELD sign.

R-003 Maximum XX km/h Ahead **R-004 Maximum XX km/h**		
 R-003  R-004	Sign sizes (mm) R-003 (600 x 750) R-003-x (750 x 900) R-003-xx (900 x 1200) R-004 (600 x 750) R-004-x (750 x 900) R-004-xx (900 x 1200)	The MAXIMUM SPEED AHEAD R-003 and MAXIMUM SPEED R-004 signs are mounted above C-080-T series tabs (ex. CONSTRUCTION SPEED ZONE) to implement a regulatory Speed Zone where the need for and speed limit of such a zone has been established by the Road Authority. The R-004 and C-080-T assembly shows the approved speed limit, marks the beginning of the Speed Zone, and is used for confirmation throughout the zone. The R-003 and C-080-T combination, showing the same speed limit, is placed upstream of the beginning of the zone. Wherever possible on freeways and other one-way roadways, secondary assemblies should also be mounted on the median or left side. A confirmatory R-004 and C-080-T assembly should be erected 300 to 600 metres downstream of the beginning of the Speed Zone. Other confirmatory assemblies may be required beyond all intervening intersections and on-ramps, and at other intermediate positions on long, uninterrupted rural sections. The oversized R-003 and R-004 signs with C-080-T tabs may be used occasionally at the beginning of other Speed Zones if additional emphasis is required. The standard-sized 600 x 750 mm R-004 sign may be used for confirmation within the zone. The end of a Speed Zone is indicated by an R-004 sign showing the normal maximum speed. Where the end of the Construction Speed Zone coincides with the end of a work zone, the R-004 is preceded by a WORK ZONE ENDS C-088 sign.