


R-010 Two-Way Traffic		
 R-010	Sign sizes (mm) R-010 (600 x 750)	The TWO-WAY TRAFFIC R-010 signs are required on both sides of a two-lane, two-way roadway at the point where the two-way section begins. In advance of that point, TWO-WAY TRAFFIC C-132 or W-020 signs must be used to provide advance warning to drivers that the one-way roadway will become a two-lane, two-way roadway. Confirmatory R-010 signs should be installed every 1.0 to 1.5 kilometres along the two-way roadway, and beyond as considered necessary. Locations beyond access points should also be considered for placement of R-010 signs. Special care is required where one direction of a divided roadway is being used temporarily to carry two-way traffic because, among other things, the normal pavement markings are not the correct colours. The R-010 sign should be used at locations where a divided highway illusion may cause drivers to think they are on a one-way roadway when in fact they are on a two-lane, two-way roadway. Typical situations requiring R-010 signs are: • construction sites where an expressway or freeway becomes a two-lane highway • locations where grading for a full-width expressway or freeway has been completed but only two lanes are operational • locations where a centreline or median crossover is being implemented
R-012 Road Closed **R-012-T Local Traffic Only Tab**		
 R-012	Sign sizes (mm) R-012 (600 x 450) R-012x (900 x 600) R-012xx	The ROAD CLOSED R-012 sign is used to mark any roadway that has been temporarily closed to all public traffic for the purpose of road construction or maintenance, or because of a temporary emergency condition such as high water or a slide. Barricades should be used to close off the travelled roadway as detailed in *Section 4.5.8: Barricades.*

 R-012-T	(1200 x 900) R-012-T (600 x 300)	An R-012 sign should be mounted on the highest rail of a barricade placed as close as possible to the centre of the travelled roadway. The LOCAL TRAFFIC ONLY R-012-T tab is used with the R-012 sign if access to private property is being maintained for local traffic along the closed section. In these cases, the positioning of barricades at the closure point should leave enough room at one or both sides for local traffic to enter and leave the closed section safely. The R-012-T tab is erected immediately below or to the right of the R-012 sign.
R-014 Keep Left/Right		
 R-014-L  R-014-R	Sign sizes (mm) R-014-L (600 x 750) R-014-R (600 x 750)	The KEEP LEFT/RIGHT R-014-L/R sign may be used in temporary situations in which traffic must be diverted from its normal path and there is no opportunity to use channelizing devices. Such situations can occur in the vicinity of intersections, as shown in *Section 11.12: Two-Lane Closure – Multilane Intersection*.

R-015 Turn Control Left/Right **R-017-2 No Straight Through** **R-018 Turn**		
 R-015-L  R-015-R  R-017-2  R-018	Sign sizes (mm) R-015-L (600 x 600) R-015-Lx (750 x 750) R-015-Lxx (900 x 900)* R-015-R (600 x 600) R-015-Rx (750 x 750) R-015-Rxx (900 x 900)* R-017-2 (600 x 600) R-017-2x (750 x 750) R-017-2xx (900 x 900)* R-018 (600 x 600) R-018-x (750 x 750)	The TURN CONTROL signs are used at intersections in both temporary and permanent situations to indicate to approaching traffic that the specified turning or through movements are either prohibited (R-015-L/R and R-017-2) or allowed (R-018). At intersections without traffic signals, the signs are normally post-mounted. At intersections with traffic signals, the signs should be positioned in the vicinity of the applicable traffic signal heads. TURN CONTROL signs apply to all traffic approaching an intersection. These signs should not be confused with, or substituted for, LANE USE signs, which regulate traffic in individual lanes.


R-016-2LR All Traffic Right/Left		
 R-016-2L	Sign sizes (mm) R-016-2L (600 x 600) R-016-2Lx (750 x 750)	The ALL TRAFFIC RIGHT/LEFT R-016-2L sign is used to indicate that the only movements allowed or available for all traffic is the direction as indicated on the sign (left or right).
 R-019-2R	R-016-2R (600 x 600) R-016-2Rx (750 x 750)	

R-019 Series U-Turn		
	Sign sizes (mm)	The NO U-TURN R-019-1 sign is used to prevent and/or reiterate to motorists that U-turns are prohibited. This sign may also be used with the EXCEPT MAINTENANCE AND AUTHORIZED VEHICLES R-019-Ta tab at emergency turn around locations where only service and authorized vehicles are allowed to perform U-turns at the break in concrete median barrier. The U-TURN PERMITTED R-019-2 sign may be used to indicate a location where U-turns are permitted, such as for road closures with a dedicated U-turn location for all traffic. In this instance, the ALL TRAFFIC R-019-Tb tab, installed below the U-TURN PERMITTED R-019-2 sign is also recommended. The U-TURN ROUTE AHEAD R-019-3 sign indicates to drivers that there is an established U-turn route or location ahead and provides additional warning so that sufficient time is given to prepare for that maneuver if required. A R-019-Tc or R-019-Td distance tab, installed below the U-TURN ROUTE AHEAD R-019-3 sign is recommended to provide information to, and better prepare drivers for the U-turn location ahead. *continued →*
 R-019-1	R-019-1 (600 x 600) R-019-1x (750 x 750) R-019-1xx (900 x 900)	
 R-019-2	R-019-2 (600 x 600) R-019-2x (750 x 750) R-019-2xx (900 x 900)	
 R-019-3	R-019-3 (600 x 600) R-019-3x (750 x 750) R-019-3xx (900 x 900)	
 R-019-Ta	R-019-Ta (600 x 450) R-019-Tax (750 x 600) R-019-Taxx (900 x 600)	

R-019 Series U-Turn (continued)		
 R-019-Tb	Sign sizes (mm) R-019-Tb (600 x 300) R-019-Tbx (750 x 400) R-019-Tbxx (900 x 450)	The ALL TRAFFIC R-019-Tb may be used with any of the turn control signs in this series to emphasize that the turn control as specified by the parent sign is to be applied to all approaching traffic regardless of vehicle/road user type. The X00 M R-019-Tc and XX KM R-019-Td distance tabs may be used with any of the signs in the regulatory series to provide additional distance information. See *Section 19.3: Roadway Closure – Two-Lane, Two-Way Roadway* and *Section 19.4: Roadway Closure – Multilane Roadway* for how these signs may be used.
 R-019-Tc	R-019-Tc (600 x 300) R-019-Tcx (750 x 400) R-019-Tcxx (900 x 450)	
 R-019-Td	R-019-Td (600 x 300) R-019-Tdx (750 x 400) R-019-Tdxx (900 x 450)	

R-020 No Passing for XXX m		
 R-020	Sign sizes (mm) R-020 (600 x 450) R-020-x (750 x 600)	The NO PASSING FOR XXX m R-020 sign is used only immediately below DO NOT PASS R-022-1 signs when the passing prohibition is relatively short (i.e., ≤ 900 metres). It is not required where overtaking is already prohibited by a barrier line, but should be used in locations where the normal pavement markings permit passing.
R-022-1 Do Not Pass **R-023 Passing Permitted**		
 R-022-1  R-023	Sign sizes (mm) R-022-1 (600 x 600) R-022-1x (750 x 750) R-022-1xx (900 x 900)* R-023 (600 x 600) R-023-x (750 x 750) R-023-xx (900 x 900)	This pair of signs may be used temporarily on two- or three-lane, two-way roadways where it is necessary to reinforce barrier line markings or where normally permitted passing should be prohibited due to construction activity. A PASSING PERMITTED R-023 sign should always be used in conjunction with a preceding DO NOT PASS R-022-1 sign to mark the end of the No Passing Zone. If the section of road over which passing is prohibited is of considerable length, one or more intermediate R-022-1 signs may be required for confirmation.

R-025 Stop Line		
 R-025-L	Sign sizes (mm) R-025-L (450 x 600)	The STOP LINE RIGHT R-025-R sign is required only at temporary traffic signal or temporary lane control signal installations where a stop line cannot be placed or where an installed stop line needs additional emphasis. It should generally be post-mounted at the intended stop location and to the right of approaching traffic. On a one-way roadway or in other situations where more than one lane approaches the temporary signal from the same direction, a STOP LINE LEFT R-025-L sign should be post-mounted on the left side of approaching traffic if a secure location can be found for it. When properly positioned, the arrows on R-025 signs always point inward towards the travelled roadway.
 R-025-R	R-025-R (450 x 600)	
R-056-1 Yield to Oncoming Traffic		
 R-056-1	Sign sizes (mm) R-056-1 (750 x 900)* R-056-1x (900 x 1200)*	The YIELD TO ONCOMING TRAFFIC R-056-1 sign is used to control a single-lane traffic section on what is principally or usually a two-lane, two-way roadway. It is used with other signs, such as: • C-030-8 Single Lane Traffic • C-135 Narrow Structure Ahead • C-135-Ta One Lane tab The R-056-1 sign is displayed for only one direction of travel, and should be used only where adequate sight distance, low traffic volumes, and low speeds make it unnecessary to use Traffic Control Persons, temporary traffic signals, or temporary lane control signals. It may also be used on the rear of a work vehicle involved in continuously slow-moving work on a two-lane, two-way roadway.

R-082 and R-083 Lane Use		
 R-082-L  R-082-R1  R-083-L  R-083-R	Sign sizes (mm) R-082-L (750 x 750) R-082-Lx (900 x 900)* R-082-R1 (750 x 750) R-082-R1x (900 x 900)* R-083-L (750 x 750) R-083-Lx (900 x 900)* R-083-R (750 x 750) R-083-Rx (900 x 900)*	The LANE USE R-082-L, R-082-R1, R-083-L, and R-083-R signs are used for both temporary and permanent situations to indicate that drivers should use a specific lane on an approach to an intersection. LANE USE signs regulate the lane assignments on approaches to intersections, and should be used where the movement is contrary to either driver expectations or the normal rules of the road. Unlike TURN CONTROL signs, these signs are placed in advance of intersections and apply only to specific lanes. For short-duration operations, they may be post-mounted or placed on a temporary sign stand, preferably at least 25 metres in advance of the intersection. For long-duration work, they should be either post-mounted or preferably mounted at a minimum height of 5.5 metres over the centre of the lane or lanes to which they apply. The R-082-L, R-082-R1, R-083-L, and R-083-R signs may be used in a shoulder application when overhead mounting is not practical. A RIGHT LANE or LEFT LANE tab should be mounted below the sign if post-mounted on the shoulder of the roadway.
R-082-R2 Right Lane Must Turn Right		
 R-082-R2	Sign sizes (mm) R-082-R2u (600 x 750) R-082-R2 (750 x 900) R-082-R2x (900 x 1200)*	The RIGHT LANE MUST TURN RIGHT R-082-R2 sign may be used instead of the LANE USE R-082-R1 sign described above if no suitable location can be found to display the R-082-R1 sign.

B-R-101 Series Cycling Restriction		
 B-R-101-1	Sign sizes (mm) B-R-101-1 600 x 600	The BICYCLE PROHIBITED B-R-101-1 sign and the WALK BICYCLE B-R-101-2 sign may be used to convey a cycling restriction: • The BICYCLE PROHIBITED B-R-101-1 sign indicates that bicycle riding is prohibited beyond this point. • The WALK BICYCLE B-R-101-2 sign is intended for cycling restrictions that are limited in length and where it is feasible to have cyclists dismount and walk their bikes. The B-R-101-Tb tab or the B-R-101-Tc tab should be used in conjunction with the WALK BICYCLE B-R-101-2 sign to provide additional direction to cyclists.
 B-R-101-2	B-R-101-2 600 x 600	
 B-R-101-Tb	B-R-101-Tb 600 x 300	
 B-R-101-Tc	B-R-101-Tc 600 x 300	



This page is intentionally blank.

B.2.3 Other Signs

P-081 Idle Reduction

 P-081-1	Sign sizes (mm) P-081-1 (600 x 750)*	**Rehabilitation or Expansion Projects:** If required by special provisions in the project contract, the IDLE REDUCTION – TURN ENGINE OFF P-081-1 sign or the IDLE REDUCTION – NO IDLING P-081-2 sign can be incorporated into work zone traffic control signage where queues form under the direction of a Traffic Control Person or traffic control devices during daylight hours.
 P-081-2	P-081-2 (600 x 750)*	**Smaller Projects:** Projects under $500,000 in value can incorporate P-081 signs into work zone traffic control signage if: • the project duration is expected to exceed three weeks; • the project is located in a high-traffic area; and • the Road Authority approves the use of these signs.
 P-081-Ta	P-081-Ta (600 x 300)*	**Installation Instructions:** The sign must be placed downstream of the TRAFFIC CONTROL PERSON AHEAD C-001-1 sign.
 P-081-Tb	P-081-Tb (600 x 300)*	The DAYLIGHT HOURS ONLY P-081-Tb tab must be installed if traffic stoppages occur before—or extend beyond—daylight hours. In the event of prolonged stoppages that result in long traffic queues, additional P-081-1 or P-081-2 signs must be placed upstream as required.
 P-081-Tc	P-081-Tc (600 x 300)*	**Exceptions:** The use of Idle Reduction signs for traffic control is not recommended if temperatures are consistently below freezing or during night-time projects involving traffic stoppages unless the queue area is lit. The intent of the signs is to encourage drivers to reduce greenhouse gas emissions from idling vehicles. The signs should not be used in circumstances where they could decrease road safety, adversely affect human health, or impede workers' ability to do their jobs.

W-132 Share the Road		
 W-132-1  W-132-1T	Sign sizes (mm) W-132-1u (600 x 600) W-132-1 (750 x 750) W-132-1x (900 x 900) W-132-1Tu (450 x 300) W-132-1T (600 x 300) W-132-1Tx (750 x 450)	The SHARE THE ROAD W-132-1 sign is used to warn motorists that they are to provide adequate driving space for cyclists and other vehicles on the road. The sign also advises motorists and cyclists to use extra caution on the upcoming stretch of road. The W-132-1 sign is to be used where bicycles and motor vehicles share the roadway in a side-by-side operation, such as on narrow lanes or where a road configuration changes, as when a paved shoulder or bicycle lane is discontinued. The SHARE THE ROAD W-132-1T tab may be used to enhance road users' understanding of the W-132-1 sign.
C-186 Command Centre		
 C-186  C-186-Ta	Sign sizes (mm) See Catalogue	The C-186 COMMAND CENTRE sign may be used to indicate a command centre where travellers may report to during emergency operations or evacuations such as wildfire or flooding. The C-186-Ta OFFICE tab may be used in conjunction with the C-186 COMMAND CENTRE sign to indicate the office location within a command centre. Directional arrows may also be used with these signs to direct travellers to the command centre or command centre office location. See the Catalogue of Standard Traffic Signs for more information.

C-326 Series Runaway Lane Closed		
 C-326 Hinged  C-326-OL Series	Sign sizes (mm) C-326 (2440 x 915) C-326-OL (300 x 300)	The RUNAWAY LANE CLOSED C-236 sign is one option available for informing truck drivers of a runaway lane closure. It is typically used for long-duration work extending over multiple days in areas where there are multiple runaway lanes. The C-326 signs are used in conjunction with RUNAWAY LANE CLOSED C-067 signs, and may require alteration of the existing W-322 and W-323 runaway lane signs in order to provide a unique letter identifier for each runaway lane. The C-326 sign should be positioned at the upstream brake check location, in advance of the hill, below an existing STEEP GRADE AHEAD sign as shown at the top of the left column here. Other options for providing advance notice of a runaway lane closure include the use of variable message signs (VMS) and customized signs. Advance notice of a runaway lane closure should be provided at—or in advance of—the nearest upstream brake check location. C-326 signs, VMS, and customized signs may be used in combination.
Zx-030 Traffic Pattern Change (custom sign)		
  Zx-030	Sign sizes (mm) Zx-030 (custom)	For Ministry projects with centreline or median crossovers and counterflow operations, a custom TRAFFIC PATTERN CHANGE Zx-030 sign may also be used as a supplement. Up arrows are used to indicate the direction of travel, and an “X” is used to indicate a lane is closed or for opposing traffic. Use of a down arrow requires approval from the Ministry’s Traffic Operations Engineering team.  Use of a custom Z-sign requires approval from the Road Authority. For additional guidance or use of this custom sign, contact the Ministry’s Traffic and Highway Safety Engineering team.

This page is intentionally blank.

Appendix C: Templates for Traffic Management Plans

Appendix Contents

Templates for Traffic Management and Traffic Control Plans C-1

Template for Category 1 Traffic Management Plan C-3

Daily Sign Check Form C-7

Template for Category 2 and 3 Traffic Management Plans C-9

Daily Traffic Control Log C-27

This page is intentionally blank.

Appendix C: Templates for Traffic Management Plans

Appendix C contains four templates:

1. **Template for Category 1 Traffic Management Plan:** This template is designed to assist Project Supervisors and Traffic Control Supervisors in assessing traffic control factors and developing a site-appropriate Traffic Management Plan for a Category 1 project.
2. **Daily Sign Check Form:** This form is designed for recording information about the periodic sign checks carried out each day during the course of a project.
3. **Template for Category 2 and 3 Traffic Management Plans:** This template sets out a fundamental approach for organizing and developing Traffic Management Plans for Category 2 and Category 3 projects, and is designed to assist Prime Contractors and Ministry staff with the development and review of Traffic Management Plans for Category 2 and Category 3 projects.
4. **Sample Daily Traffic Control Log:** This sample shows the information which should be recorded about the day's traffic control set up during the course of a project.

As indicated throughout this Manual, the requirements for each project will vary with the characteristics of the traffic, the roadway, and the project itself, and with the contract provisions and conditions established by the Ministry for the Prime Contractor. Each Traffic Management Plan must reflect those project-specific characteristics, provisions, and conditions.

This page is intentionally blank.

1. This form is designed to assist Project Supervisors and Traffic Control Supervisors in assessing traffic control factors and developing a Category 1 Traffic Management Plan appropriate to the work site.
2. The purpose of traffic control is to clearly direct and control the flow of traffic with as little disruption to the normal traffic flow as possible.
3. The misuse, overuse, or deficient use of traffic control devices can increase traffic hazards for workers on this and other work sites. All unnecessary signs must be turned or removed as soon as possible. For details, see the **Ministry's Traffic Management Manual for Work on Roadways**.

IMPLEMENTATION PLAN	
Date	**Site Name**
Exact Site Location	
Project Supervisor	**Organization**
Traffic Control Supervisor	**Organization**
Traffic Control Person(s)	**Employer**
Description of Work Activity	

CONSIDER:	**Site Factors**
Road alignment: windy, straight, hilly, banked, etc.	
Road type: divided, undivided, number of lanes.	
Sight distance: signs, trees, buildings, and other obstructions to driver sight lines.	
Approaches: hills, curves, intersections, accesses.	
Site length: total length, active length.	
Regulated speed:	
Average daily traffic volumes:	
Traffic types: local, tourist, commercial, emergency, bus, etc.	
Shoulder types and widths:	
Surrounding land uses: commercial, industrial, residential, etc.	
Residential areas: driveways, school buses, etc.	
Weather conditions: clear, icy, wet, foggy, limited visibility, etc.	
Other: _____	
_____	
_____	

CONSIDER:	**Procedural Factors**
Work on roadway	
Work off roadway	
Site access and egress	
Stationary work site	
Continually slow-moving work site	
Amount of work site activity	
Activity changes as work progresses	
Hours of work – day / night	
Other: _____	
_____	
_____	
_____	

TRAFFIC CONTROL PLAN CONSIDERATIONS

Traffic Control Hierarchy: Consider traffic control devices such as signs, barricades, delineators, flashing arrow boards, changeable message signs, cones, and other traffic control methods before using Traffic Control Persons.

Temporary / Construction Speed Zones: Keep reduced speed zones as small as possible. Temporary Speed Zones should not extend more than 1 km outside the active work area.

Site Factors: Traffic control decisions should reflect site factors identified on the previous page.

CONSIDER:	**Traffic Control Plan**
Site and procedural factors	
Types of traffic control devices	
Spacing of devices	
Advanced warning area	
Transition area	
Buffer area	
Work area	
Termination area	
Delineation during off hours	
Moving signs	
Turning and removing signs	
Checking devices	
Traffic Control Persons:	
- qualifications	
- hours of work	
- communications	
- relief	
- site instructions, location	
Other: _____	
_____	
_____	

Site Diagram

Persons Involved in Developing Traffic Plan		
Attended site discussion of plan:		
Name	Organization	Signature

INCIDENT MANAGEMENT PLAN (if required)

PUBLIC INFORMATION PLAN (if required)

DAILY SIGN CHECK FORM

Project Name and Number			**Project Location**	
Type of Work			**Highway Location**	
Date yyyy/mm/dd	**Time of Inspection**	**Location and Deficiency Type**	**Comments**	**Initials**

This side of the page may be used for additional records if necessary.

Date yyyy/mm/dd	Time of Inspection	Location and Deficiency Type	Comments	Initials