

BOOK A DOCTOR SYSTEM

Create Database Connection

The backend establishes a MongoDB connection before starting the Express server. The connection logic is implemented in **server/src/config/db.js** using Mongoose.

Database Connection File (server/src/config/db.js)

```
const mongoose = require("mongoose");

const connectDB = async () => {
  try {
    const conn = await mongoose.connect(
      process.env.MONGO_URI
    );

    console.log(
      `MongoDB Connected: ${conn.connection.host}`
    );
  } catch (error) {
    console.error(error.message);
    process.exit(1);
  }
};

module.exports = connectDB;
```

Calling the Connection from server.js

```
require("dotenv").config();

const app = require("./src/app");
const connectDB = require("./src/config/db");

const PORT = process.env.PORT || 5000;

connectDB();

app.listen(PORT, () => {
  console.log(`Server running on port ${PORT}`);
});
```

Connection Flow

1. Load environment variables from the **.env** file.
2. Read the MongoDB connection string (MONGO_URI).
3. Call **connectDB()** before starting the server.
4. Mongoose connects to MongoDB and prints the host name.
5. If the connection fails, the server exits safely to prevent runtime errors.

Result

After a successful connection, all backend modules (Users, Appointments, Authentication, Doctor Management, and Admin Dashboard) interact with MongoDB through Mongoose.