

Exp13

WORKING WITH TRIGGER

```
-----  
-- PROGRAM 1 : Trigger to Enforce Referential Integrity  
-- Prevent deletion of a parent record if child records exist  
-----
```

```
-- Parent and child tables
```

```
CREATE TABLE department (  
    dept_id NUMBER PRIMARY KEY,  
    dept_name VARCHAR2(50)  
);
```

```
CREATE TABLE employee (  
    emp_id NUMBER PRIMARY KEY,  
    emp_name VARCHAR2(50),  
    dept_id NUMBER REFERENCES department(dept_id)  
);
```

```
-- Trigger
```

```
CREATE OR REPLACE TRIGGER trg_prevent_parent_delete  
BEFORE DELETE ON department  
FOR EACH ROW
```

```
DECLARE
```

```
    v_count NUMBER;
```

```
BEGIN
```

```
    SELECT COUNT(*) INTO v_count
```

```
    FROM employee
```

```
    WHERE dept_id = :OLD.dept_id;
```

```
IF v_count > 0 THEN
```

```
    RAISE_APPLICATION_ERROR(-20001, 'Cannot delete department with existing employees.');
```

```
END IF;
```

END;

/

-- PROGRAM 2 : Trigger to Prevent Duplicate Values in a Column

-- Table for duplicate check

```
CREATE TABLE books (  
    book_id NUMBER PRIMARY KEY,  
    title VARCHAR2(100),  
    isbn VARCHAR2(20)  
);
```

-- Trigger to check duplicate ISBN

CREATE OR REPLACE TRIGGER trg_check_duplicate_isbn

BEFORE INSERT OR UPDATE ON books

FOR EACH ROW

DECLARE

v_count NUMBER;

BEGIN

SELECT COUNT(*) INTO v_count

FROM books

WHERE isbn = :NEW.isbn

AND (book_id != :NEW.book_id OR :NEW.book_id IS NULL);

IF v_count > 0 THEN

RAISE_APPLICATION_ERROR(-20002, 'Duplicate ISBN not allowed!');

END IF;

END;

/

-- PROGRAM 3 : Trigger to Restrict Insertion if Total Value Exceeds Threshold

-- Table for sales

```
CREATE TABLE sales (  
    sale_id NUMBER PRIMARY KEY,  
    amount NUMBER  
);
```

-- Trigger to restrict total amount > 10000

```
CREATE OR REPLACE TRIGGER trg_restrict_total_sales  
BEFORE INSERT ON sales
```

```
DECLARE
```

```
    v_total NUMBER;
```

```
    v_threshold CONSTANT NUMBER := 10000;
```

```
BEGIN
```

```
    SELECT NVL(SUM(amount),0) INTO v_total FROM sales;
```

```
    IF (v_total + :NEW.amount) > v_threshold THEN
```

```
        RAISE_APPLICATION_ERROR(-20003, 'Cannot insert: Total sales exceed 10000.');
```

```
    END IF;
```

```
END;
```

```
/
```

-- PROGRAM 4 : Trigger to Capture Column Changes into an Audit Table

-- Main table

```
CREATE TABLE employees_audit_test (  
    emp_id NUMBER PRIMARY KEY,  
    emp_name VARCHAR2(50),  
    salary NUMBER  
);
```

-- Audit table

```
CREATE TABLE employees_audit_log (  
    audit_id NUMBER GENERATED ALWAYS AS IDENTITY,  
    emp_id NUMBER,  
    old_salary NUMBER,  
    new_salary NUMBER,  
    changed_on DATE,  
    changed_by VARCHAR2(50)  
);
```

-- Trigger to capture changes

```
CREATE OR REPLACE TRIGGER trg_audit_salary_change  
AFTER UPDATE OF salary ON employees_audit_test  
FOR EACH ROW  
BEGIN  
    INSERT INTO employees_audit_log(emp_id, old_salary, new_salary, changed_on, changed_by)  
    VALUES(:OLD.emp_id, :OLD.salary, :NEW.salary, SYSDATE, USER);  
END;  
/  
-----
```

-- PROGRAM 5 : Trigger to Record User Activity (INSERT, UPDATE, DELETE)

-- Table to monitor

```
CREATE TABLE product (  
    product_id NUMBER PRIMARY KEY,  
    product_name VARCHAR2(50),  
    price NUMBER  
);
```

-- Audit log table

```
CREATE TABLE product_audit (  
    product_id NUMBER PRIMARY KEY,  
    product_name VARCHAR2(50),  
    price NUMBER,  
    audit_id NUMBER GENERATED ALWAYS AS IDENTITY,  
    audit_date DATE,  
    audit_user VARCHAR2(50)
```

```
log_id NUMBER GENERATED ALWAYS AS IDENTITY,  
operation_type VARCHAR2(10),  
product_id NUMBER,  
product_name VARCHAR2(50),  
price NUMBER,  
action_date DATE,  
performed_by VARCHAR2(50)  
);
```

-- Trigger to record user activity

```
CREATE OR REPLACE TRIGGER trg_product_activity  
AFTER INSERT OR UPDATE OR DELETE ON product  
FOR EACH ROW  
BEGIN
```

```
    IF INSERTING THEN
```

```
        INSERT INTO product_audit(operation_type, product_id, product_name, price, action_date,  
performed_by)
```

```
        VALUES('INSERT', :NEW.product_id, :NEW.product_name, :NEW.price, SYSDATE, USER);
```

```
    ELSIF UPDATING THEN
```

```
        INSERT INTO product_audit(operation_type, product_id, product_name, price, action_date,  
performed_by)
```

```
        VALUES('UPDATE', :NEW.product_id, :NEW.product_name, :NEW.price, SYSDATE, USER);
```

```
    ELSIF DELETING THEN
```

```
        INSERT INTO product_audit(operation_type, product_id, product_name, price, action_date,  
performed_by)
```

```
        VALUES('DELETE', :OLD.product_id, :OLD.product_name, :OLD.price, SYSDATE, USER);
```

```
    END IF;
```

```
END;
```

```
/
```

-- END OF ALL PROGRAMS
