Rajalakshmi Engineering College

Name: Gowtham P 🎷

Email: 241501060@rajalakshmi.edu.in

Roll no: 241501060 Phone: 8838517270

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 1_COD_Question 5

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Imagine you are tasked with developing a simple GPA management system using a singly linked list. The system allows users to input student GPA values, insertion should happen at the front of the linked list, delete record by position, and display the updated list of student GPAs.

Input Format

The first line of input contains an integer n, representing the number of students.

The next n lines contain a single floating-point value representing the GPA of each student.

The last line contains an integer position, indicating the position at which a student record should be deleted. Position starts from 1.

Output Format

After deleting the data in the given position, display the output in the format "GPA: " followed by the GPA value, rounded off to one decimal place.

241501060

241501060

Refer to the sample output for formatting specifications.

Sample Test Case

```
Input: 4
    3.8
    3.2
    3.5
   4.1
    Output: GPA: 4.1
    GPA: 3.2
    GPA: 3.8
    Answer
    #include<stdio.h>
    #include<stdlib.h>
    struct Node{
      float gpa;
      struct Node* next;
    int main(){
      struct Node *head, *temp, *newNode;
      int n;
      float gpa;
      scanf("%d", &n);
      for(int i=0; i<n; i++){
        newNode = (struct Node*) malloc (sizeof(struct Node));
        scanf("%f", &newNode->qpa);
if(head == NULL){
head = new*
        // newNode -> next = NULL;
           head = newNode;
```

```
2415010 Selse{
                                                                              24,150,1060
                                                    24,150,1060
           newNode -> next = head;
           head = newNode;
       int position;
       scanf("%d", &position);
       if(position == 1){
         head = head -> next;
       }else{
         temp = head;
         int indx = 1;
                                                                              24,150,1060
        while(temp->next != NULL){
           if(position == indx+1) break;
           temp = temp->next;
           indx++;
         temp->next = temp->next->next;
       temp = head;
       while(temp != NULL){
         printf("GPA: %.1f\n",temp->gpa);
         temp = temp -> next;
       }
                                                    24,150,1060
                                                                       Marks: 10/10
     Status: Correct
```

24,150,1060

247501060

241501060

241501060