```
fprintf('\n');
clearvars -except function_list hw_pub toolsPath
close all
CelestialConstants; % import useful constants
e = 0.15;
a = 2*6378; % km
mu = 3.986e5; % km3/s2
n = sqrt(mu/a/a/a);
d2r = pi/180;
cases = {'A'; 'B'; 'C'; 'D'; 'E'; 'F'};
f = \{ 0.00' \};
E = \{ '0.00' \};
M = \{ 0.00' \};
T = \{ '0.00' \};
f = [f; '30.00'];
E = [E; num2str(f2E(30*d2r,e)/d2r, '%.2f')];
M = [M; num2str(E2M(f2E(30*d2r,e),e)/d2r, '%.2f')];
T = [T; num2str(E2M(f2E(30*d2r,e),e)/n/60, '%.2f')];
f = [f; num2str(E2f(200*d2r,e)/d2r, '%.2f')];
E = [E; '200.00'];
M = [M; num2str(E2M(200*d2r,e)/d2r, '%.2f')];
T = [T; num2str(E2M(200*d2r,e)/n/60, '%.2f')];
f = [f; '90.00'];
E = [E; num2str(f2E(90*d2r,e)/d2r, '%.2f')];
M = [M; num2str(E2M(f2E(90*d2r,e),e)/d2r, '%.2f')];
T = [T; num2str(E2M(f2E(90*d2r,e),e)/n/60, '%.2f')];
f = [f; num2str(E2f(M2E(270*d2r,e),e)/d2r, '%.2f')];
E = [E; num2str(M2E(270*d2r,e)/d2r, '%.2f')];
M = [M; '270.00'];
T = [T; num2str(270*d2r/n/60, '%.2f')];
f = [f; num2str(E2f(E2M(n*25*60,e),e)/d2r, '%.2f')];
E = [E; num2str(E2M(n*25*60,e)/d2r, '%.2f')];
M = [M; num2str(n*25*60/d2r, '%.2f')];
T = [T; '25.00'];
imshow(imread('HW2 P1 graphic1.jpg'));
% disp(table(cases, f, E, M, T))%, 'VariableNames', ...
      {'Case', 'True Anom (deg)', 'Eccentric Anom (deg)', ...
      'Mean Anom (deg)', 'T-Tp (min)'}))
્ટ
% f
응 표
% M
```

% T

Case	True Anom (deg)	Eccentric Anom (deg)	Mean Anom (deg)	Time Since Periapse (min)
Α	0	0	0	0
В	30	25.95	22.18	14.73
С	197.24	200	202.94	134.71
D	90	81.37	72.88	48.37
Е	253.06	261.5	270	179.22
F	37.36	32.41	37.66	25

```
fprintf('\n');
clearvars -except function_list hw_pub toolsPath
close all
hp = 321; %km
ha = 551; %km
f = 330*pi/180; %rad
delta t = 65*60; %min
Re = 6378; %km
mu = 3.986e5; %km3/s2
a = (hp + Re + Re + ha)/2;
e = (a-hp-Re)/a;
n = sqrt(mu/a/a/a);
M0 = E2M(f2E(f,e),e);
M_deploy = M0 + n*delta_t;
if M_deploy > 2*pi
    M_deploy = M_deploy - 2*pi;
end
f_deploy = E2f(M2E(M_deploy,e), e);
fprintf('Shuttle true anom at satellite deployment: %.2f deg\n',...
    f_deploy*180/pi)
        Shuttle true anom at satellite deployment: 220.50 deg
```

```
fprintf('\n');
clearvars -except function list hw pub toolsPath
close all
CelestialConstants; % import useful constants
hp actual = 798; %km
ha actual = 817; %km
hp planned = 794; %km
ha_planned = 814; %km
a_actual = (hp_actual + ha_actual + 2*Earth.R)/2;
a_planned = (hp_planned + ha_planned + 2*Earth.R)/2;
e_actual = 1-(hp_actual+Earth.R)/a_actual;
e_planned = 1-(hp_planned+Earth.R)/a_planned;
P_actual = 2*pi*sqrt(a_actual*a_actual*a_actual/Earth.mu);
P_planned = 2*pi*sqrt(a_planned*a_planned*a_planned/Earth.mu);
fprintf('Semimajor axis:\n')
fprintf('\t%.2f km difference\n', abs(a_planned-a_actual))
fprintf('\t%.2f%% error\n\n', abs(a_planned-a_actual)/a_planned*100)
fprintf('Eccentricity:\n')
fprintf('\t%.6f difference\n', abs(e planned-e actual))
fprintf('\t%.2f%% error\n\n', abs(e_planned-e_actual)/e_planned*100)
fprintf('Period:\n')
fprintf('\t%.2f s difference\n', abs(P_planned-P_actual))
fprintf('\t%.2f%% error\n\n', abs(P_planned-P_actual)/P_planned*100)
        Semimajor axis:
         3.50 km difference
         0.05% error
        Eccentricity:
         0.000070 difference
         5.05% error
        Period:
         4.43 s difference
         0.07% error
```

```
fprintf('\n');
clearvars -except function list hw pub toolsPath
close all
CelestialConstants; % import useful constants
r = [-5650; -2650; 2850]; %km
v = [2.415; -7.032; -1.796]; %km/s
[a,e,i,RAAN,w,f] = cart20E(r,v,Earth.mu);
rp = a*(1-e);
hp = rp - Earth.R;
ra = a*(1+e);
ha = ra - Earth.R;
specific_energy = norm(v)*norm(v)/2-Earth.mu/norm(r);
h = cross(r,v);
fpa = atan2(e*sin(f), 1+e*cos(f));
fprintf('a. Semi-major axis: %.2f km\n', a)
fprintf('b. Eccentricity: %.2f\n', e)
fprintf('c. Perigee altitude: %.2f km\n', hp)
fprintf(' Apogee altitude: %.2f km\n', ha)
fprintf('d. Specific energy: %.2f J/kg\n', specific_energy)
fprintf('e. Angular momentum: %.2f \ km2/s\n', h(1))
fprintf('
                               %.2f \text{ km}2/\text{s}\n', h(2))
fprintf('
                               %.2f \text{ km}2/s\n', h(3))
fprintf('f. Inclination: %.2f deg\n', i*180/pi)
fprintf('b. Flight path angle: %.2f deg\n', fpa*180/pi)
        a. Semi-major axis: 6908.95 km
        b. Eccentricity: 0.01
        c. Perigee altitude: 479.70 km
           Apogee altitude: 582.20 km
        d. Specific energy: -28.85 J/kg
        e. Angular momentum: 24800.60 km2/s
                               -3264.65 \text{ km}2/\text{s}
                              46130.55 km2/s
        f. Inclination: 28.47 deg
        b. Flight path angle: -0.14 deg
```

```
fprintf('\n');
clearvars -except function_list hw_pub toolsPath
close all
CelestialConstants; % import useful constants
a = 0.387; %AU
e = 0.205;
TU2days = 365.25/(2*pi);
P = 2*pi*sqrt(a*a*a)*TU2days; %s
ra = a*(1+e);
rp = a*(1-e);
vp = sqrt(2/rp - 1/a)*au2km/TU2days/day2sec;
fprintf('Aphelion = %.3f AU\n',ra);
fprintf('Perihelion = %.3f AU\n',rp);
fprintf('Perihelion speed = %.1f km/s\n', vp);
        Aphelion = 0.466 AU
        Perihelion = 0.308 AU
        Perihelion speed = 58.9 km/s
```

CelestialConstants

Table of Contents

Description
Earth
Celestial units
Physical constants

Description

All sorts of constants for orbital mechanics purposes

fcnPrintQueue(mfilename('fullpath')) % Add this code to code app

Earth

```
Earth.mu = 3.986e5; %km3/s2
Earth.R = 6378; %km
```

Celestial units

au2km = 149597870.7;

Physical constants

day2sec = 86400;

```
function E = f2E( f, e )
%f2E True anomaly (f) to eccentric anomaly (E)
% Only valid for e < 1
% units in radians
fcnPrintQueue(mfilename('fullpath')) % Add this code to code app
% Vallado eqn 2-9
E = acos((e + cos(f))/(1+e*cos(f)));
if f > pi
    E = 2*pi - E;
end
```

```
function M = E2M( E, e )
%E2M Eccentric anomaly (E) to mean anomaly (M)
% units in radians
fcnPrintQueue(mfilename('fullpath')) % Add this code to code app
% Vallado eqn 2-4
M = E-e*sin(E);
```

```
function f = E2f( E, e )
%E2f Eccentric anomaly (E) to true anomaly (f)
% Only valid for e < 1
% units in radians
fcnPrintQueue(mfilename('fullpath')) % Add this code to code app
% Vallado eqn 2-10
f = acos((cos(E) - e)/(1-e*cos(E)));
if E > pi
    f = 2*pi - f;
end
```

```
function E = M2E( M, e )
%M2E Mean anom (M) to eccentric anom (E)
fcnPrintQueue(mfilename('fullpath')) % Add this code to code app

tol = 1e-5;

if (M < 0 && M > -pi) || M > pi
        E_1 = M - e;
else
        E_1 = M + e;
end

E = E_1 + tol + 1;
while abs(E_1-E) > tol
        E = E_1;
        E_1 = E - (E - e*sin(E) - M)/(1 - e*cos(E));
end
```

```
function [a,e,i,RAAN,w,f] = cart20E( r, v ,mu)
%cart2OE return classical orbital elements from cartesian coords
% Only valid for e < 1
% units in radians
fcnPrintQueue(mfilename('fullpath')) % Add this code to code app
h = cross(r,v);
n = cross([0;0;1],h);
ecc\_vec = ((norm(v)*norm(v)-mu/norm(r))*r - dot(r,v)*v)/mu;
e = norm(ecc_vec);
a = 0;
if e < 1.0
    specific_energy = norm(v)*norm(v)/2-mu/norm(r);
    a = -mu/2/specific_energy;
end
i = acos(h(3)/norm(h));
RAAN = acos(n(1)/norm(n));
if n(2) < 0
    RAAN = 2*pi-RAAN;
end
w = acos(dot(n,ecc_vec)/(norm(n)*norm(ecc_vec)));
if ecc_vec(3) < 0
    w = 2*pi-w;
end
f = acos(dot(ecc_vec,r)/(norm(ecc_vec)*norm(r)));
if dot(r,v) < 0
    f = 2*pi-f;
end
```

```
function fcnPrintQueue( filename )
global function_list;
if exist('function_list', 'var')
    file_in_list = 0;
    for idx = 1:length(function_list)
        if strcmp(function_list(idx), filename);
            file_in_list = 1;
            break
        end
    end
    if ~file_in_list
        function_list, filename];
    end
end
end
end
end
end
```