



## Lab 20.2: Examining System V IPC Activity

**System V IPC** is a rather old method of **Inter Process Communication** that dates back to the early days of **UNIX**. It involves three mechanisms:

1. Shared Memory Segments
2. Semaphores
3. Message Queues

More modern programs tend to use **POSIX IPC** methods for all three of these mechanisms, but there are still plenty of **System V IPC** applications found in the wild.

To get an overall summary of **System V IPC** activity on your system, do:

```
$ ipcs
```

```
----- Message Queues -----
key          msqid      owner      perms      used-bytes   messages

----- Shared Memory Segments -----
key          shmid      owner      perms      bytes       nattch     status
0x01114703  0          root       600        1000        6
0x00000000  98305      coop       600        4194304     2          dest
0x00000000  196610     coop       600        4194304     2          dest
0x00000000  23068675   coop       700        1138176     2          dest
0x00000000  23101444   coop       600        393216      2          dest
0x00000000  23134213   coop       600        524288      2          dest
0x00000000  24051718   coop       600        393216      2          dest
0x00000000  23756807   coop       600        524288      2          dest
0x00000000  24018952   coop       600        67108864    2          dest
0x00000000  23363593   coop       700        95408       2          dest
0x00000000  1441811    coop       600        2097152     2          dest

----- Semaphore Arrays -----
key          semid      owner      perms      nsems
0x00000000  98304      apache     600        1
0x00000000  131073     apache     600        1
0x00000000  163842     apache     600        1
0x00000000  196611     apache     600        1
0x00000000  229380     apache     600        1
```

Note almost all of the currently running shared memory segments have a key of 0 (also known as `IPC_PRIVATE`) which means they are only shared between processes in a parent/child relationship. Furthermore, all but one are marked for destruction when there are no further attachments.

One can gain further information about the processes that have created the segments and last attached to them with:

```
$ ipcs -p
```

```

----- Message Queues PIDs -----
msqid      owner      lspid      lrpid

----- Shared Memory Creator/Last-op PIDs -----
shmids     owner      cpid       lpids
0          root      1023       1023
98305      coop      2265       18780
196610     coop      2138       18775
23068675   coop      989        1663
23101444   coop      989        1663
23134213   coop      989        1663
24051718   coop      20573      1663
23756807   coop      10735      1663
24018952   coop      17875      1663
23363593   coop      989        1663
1441811    coop      2048       20573

```

Thus, by doing:

```
$ ps aux |grep -e 20573 -e 2048
```

```

coop      2048  5.3  3.7 1922996 305660 ?      Rl   Oct27  77:07 /usr/bin/gnome-shell
coop      20573  1.9  1.7 807944 141688 ?      Sl   09:56   0:01 /usr/lib64/thunderbird/thunderbird
coop      20710  0.0  0.0 112652  2312 pts/0  S+   09:57   0:00 grep --color=auto -e 20573 -e 2048

```

we see **thunderbird** is using a shared memory segment created by **gnome-shell**.

Perform these steps on your system and identify the various resources being used and by who. Are there any potential **leaks** (shared resources no longer being used by any active processes) on the system? For example, doing:

```
$ ipcs
```

```

.....
----- Shared Memory Segments -----
key      shmids     owner      perms      bytes      nattch     status
.....
0x00000000 622601     coop      600        2097152    2          dest
0x0000001a 13303818   coop      666        8196       0
.....

```

shows a shared memory segment with no attachments and not marked for destruction. Thus it might persist forever, leaking memory if no subsequent process attaches to it.