# www.MINEPORTAL.in

(All Mining Solutions)

- > ONLINE TEST SERIES FOR
- DGMS COAL/METAL FIRST & SECOND CLASS
- GATE MINING
- COAL INDIA EXAMS
- OTHER MINING EXAMS
- > ONLINE ORDER MINING BOOKS AT GREAT DISCOUNT
- > FREE STUDY MATERIAL
- > WHATSAPP CHAT SUPPORT FOR MINING EXAMS & OUERY RELATED TO MINING

VISITING SITE- www.MINEPORTAL.in

CALL/WHATSAPP- 8804777500


fb- www.fb.com/mineportal.in

EMAIL- INFO@MINEPORTAL.IN


# U/G Metalliferous Mining Lab

"JORA HOIST – A method of Raising"

## 1. Introduction to Raising methods




\*\*Jora Hoist/Lift method was developed by Boliden Mining Co. It became popular in early 1960s.



## 2. Mechanism of Jora Hoist technique

Fig - Setup for Raising with the Jora Lift/Hoist



- 1. Winch for rope
- 2. Winch skid
- 3. Drilling platform
- 4. Telescopic stabilizer
- 5. Hoist with rope
- 6. 19 mm dia rope
- 7. Automatic hole real
- 8. Rope hole

### 3. Salient features

#### **Platforms:**

- 1.6m x1.6m size
- Standard protection canopy

#### **Safety equipment:**

- Safety roof
- Breakers
- Rescue apparatus
- Telephone


#### **Required preparation work:**

Raise station

### 4. Stages

- 1. Drilling a large dia. hole at the center of the intended raise to get through into the lower level.
- 2. From the upper level a cage is suspended using a steel rope that can be hoisted up and down using a winch.
- 3. Flat surface at top of cage is used as the working platform to carry out drilling and blasting operations.
- 4. Telescopic stabilizers/jacks on the sides are activated to fix the cage against the raise sides.
- 5. Parallel holes are drilled around the central hole.
- 6. Before blasting, the hoist is lowered down to the lower access for its protection.
- 7. Blasting is carried out from a safe distance.
- 8. After mucking and ventilation, the cage is scaled up and the cycle of unit operations continue.

# 5. Sequence of unit operations



- 1. **Drilling:** Parallel holes are drilled around the central hole.
- 2. Charging: Drilled holes charged with explosive.
- **3. Blasting:** Before blasting operation, cage is lowered under safe access prepared for it beforehand. The blast is then triggered from a safe location.
- **4. Ventilation:** The face is cleaned with an air and water mixture sprayed through jets.
- **5. Scaling:** The working platform is scaled upward and the cycle continues.

### 6. Driving Figures

#### \*\*Typical driving figures by Jora Hoist raising technique:

[figures based on a real mine practice]

Dimension of raises: 2 X 2 m

Advance : 2.2 m per cycle

Output: 1.54 - 1.65 m per shift [4 shifts = 3 complete cycles]

Explosives: 13.4 Kg/m

\*\*Source: "Techniques in Underground Mining: Selections from Underground Mining Method" - by Richard E. Gertsch, Richard Lee Bullock, Page-297.

# 6. Applicability

### **Conditions for applicability of Jora Hoist raising technique:**

- 1. Two levels available as access to the intended raise site.
- 2. Suitable for vertical raises only.

### 7. Advantages

#### **Advantages of Jora Hoist method of raising:**

- Low cost.
- Simple technique. Easily understood.
- Less development work required prior to raising operation.
- Simple drilling & blasting used. Cheap & flexibility. Does not require expensive drilling consumable.
- Confirmation of ground conditions is not required.
- Can efficiently mine through the hardest of rock types.
- Easy installation.
- Minimal preparation time.
- No excessive power demands.
- No requirement for reinforced concrete foundations.

### 8. Limitations

#### <u>Limitations/Disadvantages of Jora Hoist method of raising:</u>

- Requirement of access at both ends of the intended raise.
- Necessity of a large capacity drill to drill the central large diameter hole.
- Damage to the rope during blasting.
- Tedious hoisting operation.
- Slow advance rate.
- Method limited to drivage of only vertical raises.
- Outdated method as compared to Alimak Raise Climber.