

LIS007780609B2

(12) United States Patent

Blomberg

(10) Patent No.: US (45) Date of Patent:

US 7,780,609 B2 Aug. 24, 2010

(54) TEMPORARY THRESHOLD SHIFT DETECTOR

(76) Inventor: Leslie David Blomberg, 20 Pleasant St.,

Montpelier, VT (US) 05602

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

- (21) Appl. No.: 11/823,351
- (22) Filed: Jun. 27, 2007
- (65) **Prior Publication Data**

US 2008/0015464 A1 Jan. 17, 2008

Related U.S. Application Data

- (60) Provisional application No. 60/816,839, filed on Jun. 27, 2006.
- (51) Int. Cl. A61B 5/00 (2006.01) A61B 5/12 (2006.01)
- (52) **U.S. Cl.** 600/559; 73/585
- (58) **Field of Classification Search** 600/559; 73/585

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,718,763 A *	2/1973	Cannon et al 73/585
3,970,785 A	7/1976	Meyer
4,024,499 A *	5/1977	Bosscher 340/146.2
4,107,465 A *	8/1978	Charlebois et al 73/585
4,284,847 A *	8/1981	Besserman 73/585
4,748,598 A *	5/1988	Kopke 367/13
5,143,081 A *	9/1992	Young et al 600/554

5,928,160	A	7/1999	Clark
6,350,243	B1	2/2002	Johnson
7,210,353	B2 *	5/2007	Braun et al 73/585
7,288,072	B2 *	10/2007	Stott et al 600/559
7,370,533	B2*	5/2008	Davis 73/585
7,464,595	B2 *	12/2008	Davis 73/585
2002/0078750	A1*	6/2002	Wright et al 73/585
2003/0070485	A1*	4/2003	Johansen et al 73/585
2004/0074304	A1*	4/2004	Braun et al 73/585
2004/0127812	A1*	7/2004	Micheyl et al 600/559
2005/0085744	A1*	4/2005	Beverina et al 600/558
2005/0192514	A1*	9/2005	Kearby et al 600/559
2006/0058701	A1*	3/2006	Bolles et al 600/558
2006/0153395	A1*	7/2006	van Den Heuvel et al 381/60
2006/0277999	A1*	12/2006	Raviv 73/585
2007/0135730	A1*	6/2007	Cromwell et al 600/559
2007/0204694	A1*	9/2007	Davis
2007/0204695	A1*	9/2007	Gross et al
2007/0276285	A1*	11/2007	Burrows et al 600/559
2008/0167575	A1*	7/2008	Cronin et al 600/559
2008/0194984	A1*	8/2008	Keefe 600/559

* cited by examiner

Primary Examiner—Max Hindenburg
Assistant Examiner—Sean P Dougherty
(74) Attorney, Agent, or Firm—James Marc Leas

(57) ABSTRACT

A method of detecting a change in hearing of a user includes providing a sound generating device for providing both a content audio signal and a hearing test audio signal. The sound generating device is used to provide hearing test audio sounds of different loudnesses around a threshold of hearing of the user. None of these sounds is calibrated to a prespecified decibel level. A first threshold of hearing is determined at a first time and a second threshold of hearing is determined at a second time. The first threshold of hearing is compared with the second threshold of hearing.

24 Claims, 20 Drawing Sheets

