

Predefined native! values

all

USAGE:

ALL conds

DESCRIPTION:

Evaluates and returns the last value if all are truthy; else NONE.
ALL is a native! value.

ARGUMENTS:

conds [block!]

>> help all

USAGE:

ALL conds

DESCRIPTION:

Evaluates and returns the last value if all are truthy; else NONE.
ALL is a native! value.

ARGUMENTS:

conds [block!]

any

USAGE:

ANY conds

DESCRIPTION:

Evaluates and returns the first truthy value, if any; else NONE.
ANY is a native! value.

ARGUMENTS:

conds [block!]

arccosine

USAGE:

ARCCOSINE cosine

DESCRIPTION:

Returns the trigonometric arccosine (in degrees by default in range [0,180]).
ARCCOSINE is a native! value.

ARGUMENTS:

cosine [number!] "in range [-1,1]."

REFINEMENTS:

/radians => Angle is returned in radians [0,pi].

RETURNS:

[float!]

arcsine

USAGE:

ARCSINE sine

DESCRIPTION:

Returns the trigonometric arcsine (in degrees by default in range [-90,90]).
ARCSINE is a native! value.

ARGUMENTS:

sine [number!] "in range [-1,1]."

REFINEMENTS:

/radians => Angle is returned in radians [-pi/2,pi/2].

RETURNS:

[float!]

arctangent

USAGE:

ARCTANGENT tangent

DESCRIPTION:

Returns the trigonometric arctangent (in degrees by default in range [-90,90]).
ARCTANGENT is a native! value.

ARGUMENTS:

tangent [number!] "in range [-inf,+inf]."

REFINEMENTS:

/radians => Angle is returned in radians [-pi/2,pi/2].

RETURNS:

[float!]

arctangent2

USAGE:

ARCTANGENT2 y x

DESCRIPTION:

Returns the smallest angle between the vectors (1,0) and (x,y) in degrees by default (-180,180].

ARCTANGENT2 is a native! value.

ARGUMENTS:

y [number!]

x [number!]

REFINEMENTS:

/radians => Angle is returned in radians (-pi,pi].

RETURNS:

[float!]

as

USAGE:

AS type spec

DESCRIPTION:

Coerce a series into a compatible datatype without copying it.

AS is a native! value.

ARGUMENTS:

type [datatype! block! paren! any-path! any-string!] "The datatype or example value."

spec [block! paren! any-path! any-string!] "The series to coerce."

as-money

USAGE:

AS-MONEY currency amount

DESCRIPTION:

Combine currency code and amount into a monetary value.

AS-MONEY is a native! value.

ARGUMENTS:

currency [word!]

amount [integer! float!]

RETURNS:
[money!]

as-pair

USAGE:
AS-PAIR x y

DESCRIPTION:
Combine X and Y values into a pair.
AS-PAIR is a native! value.

ARGUMENTS:

x	[integer! float!]
y	[integer! float!]

bind

USAGE:
BIND word context

DESCRIPTION:
Bind words to a context; returns rebound words.
BIND is a native! value.

ARGUMENTS:

word	[block! any-word!]
context	[any-word! any-object! function!]

REFINEMENTS:
/copy => Deep copy blocks before binding.

RETURNS:
[block! any-word!]

break

USAGE:
BREAK

DESCRIPTION:
Breaks out of a loop, while, until, repeat, foreach, etc.
BREAK is a native! value.

REFINEMENTS:

/return	=>	Forces the loop function to return a value.
value		[any-type!]

browse

USAGE:

BROWSE url

DESCRIPTION:

Open web browser to a URL or file manager to a local file.
BROWSE is a native! value.

ARGUMENTS:

url	[url! file!]
-----	--------------

call

USAGE:

CALL cmd

DESCRIPTION:

Executes a shell command to run another process.
CALL is a native! value.

ARGUMENTS:

cmd	[string! file!] "A shell command or an executable file."
-----	--

REFINEMENTS:

/wait	=>	Runs command and waits for exit.
/show	=>	Force the display of system's shell window (Windows only).
/console	=>	Runs command with I/O redirected to console (CLI console only at present).
/shell	=>	Forces command to be run from shell.
/input	=>	
in		[string! file! binary!] "Redirects in to stdin."
/output	=>	
out		[string! file! binary!] "Redirects stdout to out."
/error	=>	
err		[string! file! binary!] "Redirects stderr to err."

RETURNS:

0 if success, -1 if error, or a process ID.
[integer!]

case

USAGE:

CASE cases

DESCRIPTION:

Evaluates the block following the first truthy condition.
CASE is a native! value.

ARGUMENTS:

cases [block!] "Block of condition-block pairs."

REFINEMENTS:

/all => Test all conditions, evaluating the block following each truthy condition.

catch

USAGE:

CATCH block

DESCRIPTION:

Catches a throw from a block and returns its value.
CATCH is a native! value.

ARGUMENTS:

block [block!] "Block to evaluate."

REFINEMENTS:

/name => Catches a named throw.
word [word! block!] "One or more names."

checksum

USAGE:

CHECKSUM data method

DESCRIPTION:

Computes a checksum, CRC, hash, or HMAC.
CHECKSUM is a native! value.

ARGUMENTS:

data [binary! string! file!]
method [word!] {MD5 SHA1 SHA256 SHA384 SHA512 CRC32 TCP ADLER32 hash.}

REFINEMENTS:

/with => Extra value for HMAC key or hash table size; not compatible with TCP/CRC32/ADLER32 methods.

spec [any-string! binary! integer!] {String or binary for MD5/SHA* HMAC key, integer for hash table size.}

RETURNS:

[integer! binary!]

compliment?

USAGE:

COMPLEMENT? bits

DESCRIPTION:

Returns TRUE if the bitset is complemented.

COMPLEMENT? is a native! value.

ARGUMENTS:

bits [bitset!]

compose

USAGE:

COMPOSE value

DESCRIPTION:

Returns a copy of a block, evaluating only parens.

COMPOSE is a native! value.

ARGUMENTS:

value [block!]

REFINEMENTS:

/deep => Compose nested blocks.

/only => Compose nested blocks as blocks containing their values.

/into => Put results in out block, instead of creating a new block.

out [any-block!] "Target block for results, when /into is used."

compress

USAGE:

COMPRESS data

DESCRIPTION:

compresses data. return GZIP format (RFC 1952) by default.

COMPRESS is a native! value.

ARGUMENTS:

data [any-string! binary!]

REFINEMENTS:

/zlib => Return ZLIB format (RFC 1950).

/deflate => Return DEFLATE format (RFC 1951).

construct

USAGE:

CONSTRUCT block

DESCRIPTION:

Makes a new object from an unevaluated spec; standard logic words are evaluated.
CONSTRUCT is a native! value.

ARGUMENTS:

block [block!]

REFINEMENTS:

/with => Use a prototype object.

object [object!] "Prototype object."

/only => Don't evaluate standard logic words.

context?

USAGE:

CONTEXT? word

DESCRIPTION:

Returns the context to which a word is bound.
CONTEXT? is a native! value.

ARGUMENTS:

word [any-word!] "Word to check."

RETURNS:

[object! function! none!]

continue

USAGE:

CONTINUE

DESCRIPTION:

Throws control back to top of loop.
CONTINUE is a native! value.

cosine

USAGE:

COSINE angle

DESCRIPTION:

Returns the trigonometric cosine.
COSINE is a native! value.

ARGUMENTS:

angle [number!]

REFINEMENTS:

/radians => Angle is specified in radians.

RETURNS:

[float!]

debase

USAGE:

DEBASE value

DESCRIPTION:

Decodes binary-coded string (BASE-64 default) to binary value.
DEBASE is a native! value.

ARGUMENTS:

value [string!] "The string to decode."

REFINEMENTS:

/base => Binary base to use.
base-value [integer!] "The base to convert from: 64, 58, 16, or 2."

decompress

USAGE:

DECOMPRESS data

DESCRIPTION:

Decompresses data. Data in GZIP format (RFC 1952) by default.
DECOMPRESS is a native! value.

ARGUMENTS:

data [binary!]

REFINEMENTS:

/zlib => Data in ZLIB format (RFC 1950).
size [integer!] "Uncompressed data size. Use 0 if don't know."
/deflate => Data in DEFLATE format (RFC 1951).
size [integer!] "Uncompressed data size. Use 0 if don't know."

dehex

USAGE:

DEHEX value

DESCRIPTION:

Converts URL-style hex encoded (%xx) strings.
DEHEX is a native! value.

ARGUMENTS:

value [any-string!]

RETURNS:

Always return a string.
[string!]

difference

USAGE:

DIFFERENCE set1 set2

DESCRIPTION:

Returns the special difference of two data sets.
DIFFERENCE is a native! value.

ARGUMENTS:

set1 [block! hash! string! bitset! typeset! date!]
set2 [block! hash! string! bitset! typeset! date!]

REFINEMENTS:

/case => Use case-sensitive comparison.
/skip => Treat the series as fixed size records.
size [integer!]

RETURNS:

[block! hash! string! bitset! typeset! time!]

do

USAGE:

DO value

DESCRIPTION:

Evaluates a value, returning the last evaluation result.
DO is a native! value.

ARGUMENTS:

value [any-type!]

REFINEMENTS:

/expand => Expand directives before evaluation.
/args => If value is a script, this will set its system/script/args.
 arg "Args passed to a script (normally a string)."
/next => Do next expression only, return it, update block word.
 position [word!] "Word updated with new block position."

does

USAGE:

DOES body

DESCRIPTION:

Defines a function with no arguments or local variables.
DOES is a native! value.

ARGUMENTS:

body [block!]

either

USAGE:

EITHER cond true-blk false-blk

DESCRIPTION:

If conditional expression is truthy, evaluate the first branch; else evaluate the alternative.
EITHER is a native! value.

ARGUMENTS:

cond [any-type!]

```
true-blk      [block!]  
false-blk     [block!]
```

enbase

USAGE:

```
ENBASE value
```

DESCRIPTION:

Encodes a string into a binary-coded string (BASE-64 default).
ENBASE is a native! value.

ARGUMENTS:

```
value          [binary! string!] "If string, will be UTF8 encoded."
```

REFINEMENTS:

```
/base          => Binary base to use.  
base-value     [integer!] "The base to convert from: 64, 58, 16, or 2."
```

enhex

USAGE:

```
ENHEX value
```

DESCRIPTION:

Encode URL-style hex encoded (%xx) strings.
ENHEX is a native! value.

ARGUMENTS:

```
value          [any-string!]
```

RETURNS:

Always return a string.
[string!]

equal?

USAGE:

```
EQUAL? value1 value2
```

DESCRIPTION:

Returns TRUE if two values are equal.
EQUAL? is a native! value.

ARGUMENTS:

```
value1      [any-type!]
value2      [any-type!]
```

exclude

USAGE:

```
EXCLUDE set1 set2
```

DESCRIPTION:

Returns the first data set less the second data set.
EXCLUDE is a native! value.

ARGUMENTS:

```
set1      [block! hash! string! bitset! typeset!]
set2      [block! hash! string! bitset! typeset!]
```

REFINEMENTS:

```
/case      => Use case-sensitive comparison.
/skip      => Treat the series as fixed size records.
size       [integer!]
```

RETURNS:

```
[block! hash! string! bitset! typeset!]
```

exit

USAGE:

```
EXIT
```

DESCRIPTION:

Exits a function, returning no value.
EXIT is a native! value.

exp

USAGE:

```
EXP value
```

DESCRIPTION:

Raises E (the base of natural logarithm) to the power specified.
EXP is a native! value.

ARGUMENTS:

```
value      [number!]
```

RETURNS:
[float!]

extend

USAGE:
EXTEND obj spec

DESCRIPTION:
Extend an object or map value with list of key and value pairs.
EXTEND is a native! value.

ARGUMENTS:
obj [object! map!]
spec [block! hash! map!]

REFINEMENTS:
/case => Use case-sensitive comparison.

forall

USAGE:
FORALL 'word body

DESCRIPTION:
Evaluates body for all values in a series.
FORALL is a native! value.

ARGUMENTS:
'word [word!] "Word referring to series to iterate over."
body [block!]

foreach

USAGE:
FOREACH 'word series body

DESCRIPTION:
Evaluates body for each value in a series.
FOREACH is a native! value.

ARGUMENTS:
'word [word! block!] "Word, or words, to set on each iteration."
series [series! map!]

body [block!]

forever

USAGE:

FOREVER body

DESCRIPTION:

Evaluates body repeatedly forever.
FOREVER is a native! value.

ARGUMENTS:

body [block!]

func

USAGE:

FUNC spec body

DESCRIPTION:

Defines a function with a given spec and body.
FUNC is a native! value.

ARGUMENTS:

spec [block!]
body [block!]

function

USAGE:

FUNCTION spec body

DESCRIPTION:

Defines a function, making all set-words found in body, local.
FUNCTION is a native! value.

ARGUMENTS:

spec [block!]
body [block!]

REFINEMENTS:

/extern => Exclude words that follow this refinement.

get

USAGE:

GET word

DESCRIPTION:

Returns the value a word refers to.
GET is a native! value.

ARGUMENTS:

word [any-word! any-path! object!]

REFINEMENTS:

/any => If word has no value, return UNSET rather than causing an error.
/case => Use case-sensitive comparison (path only).

RETURNS:

[any-type!]

get-env

USAGE:

GET-ENV var

DESCRIPTION:

Returns the value of an OS environment variable (for current process).
GET-ENV is a native! value.

ARGUMENTS:

var [any-string! any-word!] "Variable to get."

RETURNS:

[string! none!]

greater-or-equal?

USAGE:

GREATER-OR-EQUAL? value1 value2

DESCRIPTION:

Returns TRUE if the first value is greater than or equal to the second.
GREATER-OR-EQUAL? is a native! value.

ARGUMENTS:

value1 [any-type!]

value2 [any-type!]

greater

USAGE:

GREATER? value1 value2

DESCRIPTION:

Returns TRUE if the first value is greater than the second.
GREATER? is a native! value.

ARGUMENTS:

value1 [any-type!]
value2 [any-type!]

has

USAGE:

HAS vars body

DESCRIPTION:

Defines a function with local variables, but no arguments.
HAS is a native! value.

ARGUMENTS:

vars [block!]
body [block!]

if

USAGE:

IF cond then-blk

DESCRIPTION:

If conditional expression is truthy, evaluate block; else return NONE.
IF is a native! value.

ARGUMENTS:

cond [any-type!]
then-blk [block!]

in

USAGE:

IN object word

DESCRIPTION:

Returns the given word bound to the object's context.
IN is a native! value.

ARGUMENTS:

object	[any-object!]
word	[any-word!]

intersect

USAGE:

INTERSECT set1 set2

DESCRIPTION:

Returns the intersection of two data sets.
INTERSECT is a native! value.

ARGUMENTS:

set1	[block! hash! string! bitset! typeset!]
set2	[block! hash! string! bitset! typeset!]

REFINEMENTS:

/case	=> Use case-sensitive comparison.
/skip	=> Treat the series as fixed size records.
size	[integer!]

RETURNS:

[block! hash! string! bitset! typeset!]

lesser-or-equal?

USAGE:

LESSER-OR-EQUAL? value1 value2

DESCRIPTION:

Returns TRUE if the first value is less than or equal to the second.
LESSER-OR-EQUAL? is a native! value.

ARGUMENTS:

value1	[any-type!]
--------	-------------

value2 [any-type!]

lesser?

USAGE:

LESSER? value1 value2

DESCRIPTION:

Returns TRUE if the first value is less than the second.
LESSER? is a native! value.

ARGUMENTS:

value1 [any-type!]
value2 [any-type!]

list-env

USAGE:

LIST-ENV

DESCRIPTION:

Returns a map of OS environment variables (for current process).
LIST-ENV is a native! value.

RETURNS:

[map!]

log-10

USAGE:

LOG-10 value

DESCRIPTION:

Returns the base-10 logarithm.
LOG-10 is a native! value.

ARGUMENTS:

value [number!]

RETURNS:

[float!]

log-2

USAGE:

LOG-2 value

DESCRIPTION:

Return the base-2 logarithm.

LOG-2 is a native! value.

ARGUMENTS:

value [number!]

RETURNS:

[float!]

log-e

USAGE:

LOG-E value

DESCRIPTION:

Returns the natural (base-E) logarithm of the given value.

LOG-E is a native! value.

ARGUMENTS:

value [number!]

RETURNS:

[float!]

loop

USAGE:

LOOP count body

DESCRIPTION:

Evaluates body a number of times.

LOOP is a native! value.

ARGUMENTS:

count [integer! float!]

body [block!]

lowercase

USAGE:

LOWERCASE string

DESCRIPTION:

Converts string of characters to lowercase.

LOWERCASE is a native! value.

ARGUMENTS:

string [any-string! char!] "Value to convert (modified when series)."

REFINEMENTS:

/part => Limits to a given length or position.

limit [number! any-string!]

RETURNS:

[any-string! char!]

max

USAGE:

MAX value1 value2

DESCRIPTION:

Returns the greater of the two values.

MAX is a native! value.

ARGUMENTS:

value1 [scalar! series!]

value2 [scalar! series!]

min

USAGE:

MIN value1 value2

DESCRIPTION:

Returns the lesser of the two values.

MIN is a native! value.

ARGUMENTS:

value1 [scalar! series!]

value2 [scalar! series!]

NaN?

USAGE:

NAN? value

DESCRIPTION:

Returns TRUE if the number is Not-a-Number.

NAN? is a native! value.

ARGUMENTS:

value [number!]

RETURNS:

[logic!]

negative?

USAGE:

NEGATIVE? number

DESCRIPTION:

Returns TRUE if the number is negative.

NEGATIVE? is a native! value.

ARGUMENTS:

number [number! money! time!]

RETURNS:

[logic!]

new-line

USAGE:

NEW-LINE position value

DESCRIPTION:

Sets or clears the new-line marker within a list series.

NEW-LINE is a native! value.

ARGUMENTS:

position [any-list!] "Position to change marker (modified)."
value [logic!] "Set TRUE for newline."

REFINEMENTS:

/all => Set/clear marker to end of series.
/skip => Set/clear marker periodically to the end of the series.

size [integer!]

RETURNS:
[any-list!]

new-line?

USAGE:
NEW-LINE? position

DESCRIPTION:
Returns the state of the new-line marker within a list series.
NEW-LINE? is a native! value.

ARGUMENTS:
position [any-list!] "Position to change marker."

RETURNS:
[any-list!]

not

USAGE:
NOT value

DESCRIPTION:
Returns the logical complement of a value (truthy or falsy).
NOT is a native! value.

ARGUMENTS:
value [any-type!]

not-equal?

USAGE:
NOT-EQUAL? value1 value2

DESCRIPTION:
Returns TRUE if two values are not equal.
NOT-EQUAL? is a native! value.

ARGUMENTS:
value1 [any-type!]
value2 [any-type!]

now

USAGE:

NOW

DESCRIPTION:

Returns date and time.
NOW is a native! value.

REFINEMENTS:

/year	=> Returns year only.
/month	=> Returns month only.
/day	=> Returns day of the month only.
/time	=> Returns time only.
/zone	=> Returns time zone offset from UTC (GMT) only.
/date	=> Returns date only.
/weekday	=> Returns day of the week as integer (Monday is day 1).
/yearday	=> Returns day of the year (Julian).
/precise	=> High precision time.
/utc	=> Universal time (no zone).

RETURNS:

[date! time! integer!]

parse

USAGE:

PARSE input rules

DESCRIPTION:

Process a series using dialected grammar rules.
PARSE is a native! value.

ARGUMENTS:

input	[binary! any-block! any-string!]
rules	[block!]

REFINEMENTS:

/case	=> Uses case-sensitive comparison.
/part	=> Limit to a length or position.
length	[number! series!]
/trace	=>
callback	[function! [event [word!] match? [logic!] rule [block!] input [series!] stack [block!] return: [logic!]]]

RETURNS:

[logic! block!]

positive?

USAGE:
 POSITIVE? number

DESCRIPTION:
 Returns TRUE if the number is positive.
 POSITIVE? is a native! value.

ARGUMENTS:
 number [number! money! time!]

RETURNS:
 [logic!]

prin

USAGE:
 PRIN value

DESCRIPTION:
 Outputs a value.
 PRIN is a native! value.

ARGUMENTS:
 value [any-type!]

print

USAGE:
 PRINT value

DESCRIPTION:
 Outputs a value followed by a newline.
 PRINT is a native! value.

ARGUMENTS:
 value [any-type!]

recycle

USAGE:
 RECYCLE

DESCRIPTION:

Recycles unused memory.
 RECYCLE is a native! value.

REFINEMENTS:

/on => Turns on garbage collector.
 /off => Turns off garbage collector.

reduce

USAGE:

REDUCE value

DESCRIPTION:

Returns a copy of a block, evaluating all expressions.
 REDUCE is a native! value.

ARGUMENTS:

value [any-type!]

REFINEMENTS:

/into => Put results in out block, instead of creating a new block.
 out [any-block!] "Target block for results, when /into is used."

remove-each

USAGE:

REMOVE-EACH 'word data body

DESCRIPTION:

Removes values for each block that returns truthy value.
 REMOVE-EACH is a native! value.

ARGUMENTS:

'word [word! block!] "Word or block of words to set each time."
 data [series!] "The series to traverse (modified)."
 body [block!] {Block to evaluate (return truthy value to remove).}

repeat

USAGE:

REPEAT 'word value body

DESCRIPTION:

Evaluates body a number of times, tracking iteration count.

REPEAT is a native! value.

ARGUMENTS:

'word	[word!] "Iteration counter; not local to loop."
value	[integer! float!] "Number of times to evaluate body."
body	[block!]

return

USAGE:

RETURN value

DESCRIPTION:

Returns a value from a function.

RETURN is a native! value.

ARGUMENTS:

value	[any-type!]
-------	-------------

same?

USAGE:

SAME? value1 value2

DESCRIPTION:

Returns TRUE if two values have the same identity.

SAME? is a native! value.

ARGUMENTS:

value1	[any-type!]
value2	[any-type!]

set

USAGE:

SET word value

DESCRIPTION:

Sets the value(s) one or more words refer to.

SET is a native! value.

ARGUMENTS:

word	[any-word! block! object! any-path!] "Word, object, map path or block of words to set."
value	[any-type!] "Value or block of values to assign to words."

REFINEMENTS:

/any	=> Allow UNSET as a value rather than causing an error.
/case	=> Use case-sensitive comparison (path only).
/only	=> Block or object value argument is set as a single value.
/some	=> None values in a block or object value argument, are not set.

RETURNS:

[any-type!]

set-env

USAGE:

SET-ENV var value

DESCRIPTION:

Sets the value of an operating system environment variable (for current process).
SET-ENV is a native! value.

ARGUMENTS:

var	[any-string! any-word!] "Variable to set."
value	[string! none!] "Value to set, or NONE to unset it."

shift

USAGE:

SHIFT data bits

DESCRIPTION:

Perform a bit shift operation. Right shift (decreasing) by default.
SHIFT is a native! value.

ARGUMENTS:

data	[integer!]
bits	[integer!]

REFINEMENTS:

/left	=> Shift bits to the left (increasing).
/logical	=> Use logical shift (unsigned, fill with zero).

RETURNS:

[integer!]

sign?

USAGE:

SIGN? number

DESCRIPTION:

Returns sign of N as 1, 0, or -1 (to use as a multiplier).

SIGN? is a native! value.

ARGUMENTS:

number [number! money! time!]

RETURNS:

[integer!]

sine

USAGE:

SINE angle

DESCRIPTION:

Returns the trigonometric sine.

SINE is a native! value.

ARGUMENTS:

angle [number!]

REFINEMENTS:

/radians => Angle is specified in radians.

RETURNS:

[float!]

size?

USAGE:

SIZE? file

DESCRIPTION:

Returns the size of a file content.

SIZE? is a native! value.

ARGUMENTS:

file [file!]

RETURNS:

[integer! none!]

square-root

USAGE:

SQUARE-ROOT value

DESCRIPTION:

Returns the square root of a number.
SQUARE-ROOT is a native! value.

ARGUMENTS:

value [number!]

RETURNS:

[float!]

stats

USAGE:

STATS

DESCRIPTION:

Returns interpreter statistics.
STATS is a native! value.

REFINEMENTS:

/show => TBD:.
/info => Output formatted results.

RETURNS:

[integer! block!]

strict-equal?

USAGE:

STRICT-EQUAL? value1 value2

DESCRIPTION:

Returns TRUE if two values are equal, and also the same datatype.
STRICT-EQUAL? is a native! value.

ARGUMENTS:

value1 [any-type!]

value2 [any-type!]

switch

USAGE:

SWITCH value cases

DESCRIPTION:

Evaluates the first block following the value found in cases.
SWITCH is a native! value.

ARGUMENTS:

value [any-type!] "The value to match."
cases [block!]

REFINEMENTS:

/default => Specify a default block, if value is not found in cases.
case [block!] "Default block to evaluate."

tangent

USAGE:

TANGENT angle

DESCRIPTION:

Returns the trigonometric tangent.
TANGENT is a native! value.

ARGUMENTS:

angle [number!]

REFINEMENTS:

/radians => Angle is specified in radians.

RETURNS:

[float!]

throw

USAGE:

THROW value

DESCRIPTION:

Throws control back to a previous catch.
THROW is a native! value.

ARGUMENTS:
value [any-type!] "Value returned from catch."

REFINEMENTS:
/name => Throws to a named catch.
word [word!]

to-hex

USAGE:
TO-HEX value

DESCRIPTION:
Converts numeric value to a hex issue! datatype (with leading # and 0's).
TO-HEX is a native! value.

ARGUMENTS:
value [integer!]

REFINEMENTS:
/size => Specify number of hex digits in result.
length [integer!]

RETURNS:
[issue!]

to-local-file

USAGE:
TO-LOCAL-FILE path

DESCRIPTION:
Converts a Red file path to the local system file path.
TO-LOCAL-FILE is a native! value.

ARGUMENTS:
path [file! string!]

REFINEMENTS:
/full => Prepends current dir for full path (for relative paths only).

RETURNS:
[string!]

transcode

USAGE:

TRANSCODE src

DESCRIPTION:

Translates UTF-8 binary source to values. Returns one or several values in a block.

TRANSCODE is a native! value.

ARGUMENTS:

src [binary! string!] {UTF-8 input buffer; string argument will be UTF-8 encoded.}

REFINEMENTS:

/next => Translate next complete value (blocks as single value).
/one => Translate next complete value, returns the value only.
/prescan => Prescans only, do not load values. Returns guessed type.
/scan => Scans only, do not load values. Returns recognized type.
/part => Translates only part of the input buffer.
length [integer! binary!] "Length in bytes or tail position."
/into => Optionally provides an output block.
dst [block!]
/trace =>
callback [function! [event [word!] input [binary! string!] type [word! datatype!] line [integer!] token return: [logic!]]]

RETURNS:

[block!]

try

USAGE:

TRY block

DESCRIPTION:

Tries to DO a block and returns its value or an error.

TRY is a native! value.

ARGUMENTS:

block [block!]

REFINEMENTS:

/all => Catch also BREAK, CONTINUE, RETURN, EXIT and THROW exceptions.

type?

USAGE:

TYPE? value

DESCRIPTION:

Returns the datatype of a value.

TYPE? is a native! value.

ARGUMENTS:

value [any-type!]

REFINEMENTS:

/word => Return a word value, rather than a datatype value.

union

USAGE:

UNION set1 set2

DESCRIPTION:

Returns the union of two data sets.

UNION is a native! value.

ARGUMENTS:

set1 [block! hash! string! bitset! typeset!]

set2 [block! hash! string! bitset! typeset!]

REFINEMENTS:

/case => Use case-sensitive comparison.

/skip => Treat the series as fixed size records.

size [integer!]

RETURNS:

[block! hash! string! bitset! typeset!]

unique

USAGE:

UNIQUE set

DESCRIPTION:

Returns the data set with duplicates removed.

UNIQUE is a native! value.

ARGUMENTS:

set [block! hash! string!]

REFINEMENTS:

/case => Use case-sensitive comparison.
/skip => Treat the series as fixed size records.
size [integer!]

RETURNS:

[block! hash! string!]

unless

USAGE:

UNLESS cond then-blk

DESCRIPTION:

If conditional expression is falsy, evaluate block; else return NONE.
UNLESS is a native! value.

ARGUMENTS:

cond [any-type!]
then-blk [block!]

unset

USAGE:

UNSET word

DESCRIPTION:

Unsets the value of a word in its current context.
UNSET is a native! value.

ARGUMENTS:

word [word! block!] "Word or block of words."

until

USAGE:

UNTIL body

DESCRIPTION:

Evaluates body until it is truthy.
UNTIL is a native! value.

ARGUMENTS:

body [block!]

uppercase

USAGE:

UPPERCASE string

DESCRIPTION:

Converts string of characters to uppercase.
UPPERCASE is a native! value.

ARGUMENTS:

string [any-string! char!] "Value to convert (modified when series)."

REFINEMENTS:

/part => Limits to a given length or position.
limit [number! any-string!]

RETURNS:

[any-string! char!]

value?

USAGE:

VALUE? value

DESCRIPTION:

Returns TRUE if the word has a value.
VALUE? is a native! value.

ARGUMENTS:

value

RETURNS:

[logic!]

wait

USAGE:

WAIT value

DESCRIPTION:

Waits for a duration in seconds or specified time.
WAIT is a native! value.

ARGUMENTS:
value [number! time! block! none!]

REFINEMENTS:
/all => Returns all events in a block.

while

USAGE:
WHILE cond body

DESCRIPTION:
Evaluates body as long as condition block evaluates to truthy value.
WHILE is a native! value.

ARGUMENTS:
cond [block!] "Condition block to evaluate on each iteration."
body [block!] "Block to evaluate on each iteration."

while

USAGE:
WHILE cond body

DESCRIPTION:
Evaluates body as long as condition block evaluates to truthy value.
WHILE is a native! value.

ARGUMENTS:
cond [block!] "Condition block to evaluate on each iteration."
body [block!] "Block to evaluate on each iteration."

zero?

USAGE:
ZERO? value

DESCRIPTION:
Returns TRUE if the value is zero.
ZERO? is a native! value.

ARGUMENTS:
value [number! money! pair! time! char! tuple!]

RETURNS:

[logic!]