

Часть этой страницы могла быть машинно переведена или переведена с помощью искусственного интеллекта.



[Главная страница](#) / [REST API](#) / [Приложения](#) / [GitHub Apps](#)

REST API теперь версия. Дополнительные сведения см. в разделе "[О управлении версиями API](#)".

Конечные точки REST API для GitHub Apps

Использование REST API для взаимодействия с GitHub Apps

Сведения о GitHub Apps

Если вы используете приложение с GitHub Actions и хотите изменить файлы рабочего процесса, необходимо пройти проверку подлинности от имени пользователя с помощью токена OAuth, который включает область `workflow`. Пользователь должен иметь разрешение администратора или разрешение на запись в репозиторий, содержащий файл рабочего процесса. Дополнительные сведения см. в разделе [Области для приложений OAuth](#).

На этой странице перечислены конечные точки, к которым можно получить доступ при проверке подлинности в виде GitHub App. Дополнительные сведения см. в разделе [Аутентификация как приложение GitHub](#).

Список конечных точек, требующих проверки подлинности, см. в разделе [Конечные точки REST API для GitHub App установок](#) для установки GitHub App.

Get the authenticated app

Returns the GitHub App associated with the authentication credentials used. To see how many app installations are associated with this GitHub App, see the `installations_count` in the



response. For more details about your app's installations, see the "[List installations for the authenticated app](#)" endpoint.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «Get the authenticated app»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

HTTP-коды статуса ответа для «Get the authenticated app»

200

OK

Примеры кода для «Get the authenticated app»

Код состояния	Description
GET /app cURL JavaScript Интерфейс командной строки GitHub curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2026-03-10" \ https://api.github.com/app	

Response

Пример отклика	Схема ответа
Status: 200 { "id": 1, "slug": "octoapp", "client_id": "Iv1.ab1112223334445c", "node_id": "MDExOk1udGVncmF0aw9uMQ==", "owner": {	

```
"login": "octocat",
"id": 1,
"node_id": "MDQ6VXNlcjE=",
"avatar_url": "https://github.com/images/error/octocat_happy.gif",
"gravatar_id": "",
"url": "https://api.github.com/users/octocat",
"html_url": "https://github.com/octocat",
"followers_url": "https://api.github.com/users/octocat/followers",
"following_url": "https://api.github.com/users/octocat/following{/other_user}",
"gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
"starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}",
"subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
"organizations_url": "https://api.github.com/users/octocat/orgs",
"repos_url": "https://api.github.com/users/octocat/repos",
"events_url": "https://api.github.com/users/octocat/events{/privacy}",
"received_events_url": "https://api.github.com/users/octocat/received_events",
"type": "User",
"site_admin": false
},
"name": "Octocat App",
"description": "",
"external_url": "https://example.com",
"html_url": "https://github.com/apps/octoapp",
"created_at": "2017-07-08T16:18:44-04:00",
"updated_at": "2017-07-08T16:18:44-04:00",
"permissions": {
  "metadata": "read",
  "contents": "read",
  "issues": "write",
  "single_file": "write"
},
"events": [
  "push",
  "pull_request"
```

Create a GitHub App from a manifest

Use this endpoint to complete the handshake necessary when implementing the [GitHub App Manifest flow](#). When you create a GitHub App with the manifest flow, you receive a temporary code used to retrieve the GitHub App's id, pem (private key), and webhook_secret.

Детализированные токены доступа для «Create a GitHub App from a manifest»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «Create a GitHub App from a manifest»

Заголовки

accept string
Setting to application/vnd.github+json is recommended.

Параметры пути

code string Обязательное поле

HTTP-коды статуса ответа для «Create a GitHub App from a manifest»

201	Created
404	Resource not found
422	Validation failed, or the endpoint has been spammed.

Примеры кода для «Create a GitHub App from a manifest»

Пример запроса

POST /app-manifests/{code}/conversions

cURL

JavaScript

Интерфейс командной строки GitHub

curl -L \
-X POST \
-H "Accept: application/vnd.github+json" \
-H "Authorization: Bearer <YOUR-TOKEN>" \
-H "X-GitHub-API-Version: 2026-03-10" \
https://api.github.com/app-manifests/CODE/conversions

Код состояния	Description
---------------	-------------

Status: 201

```
{
  "id": 1,
  "slug": "octoapp",
  "node_id": "MDxOk1udGVncmF0aW9uMQ==",
  "owner": {
    "login": "github",
    "id": 1,
    "node_id": "MDEyOk9yZ2FuaXphdGlvbjE=",
    "url": "https://api.github.com/orgs/github",
    "repos_url": "https://api.github.com/orgs/github/repos",
    "events_url": "https://api.github.com/orgs/github/events",
    "avatar_url": "https://github.com/images/error/octocat_happy.gif",
    "gravatar_id": "",
    "html_url": "https://github.com/octocat",
    "followers_url": "https://api.github.com/users/octocat/followers",
    "following_url": "https://api.github.com/users/octocat/following{/other_user}",
    "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
    "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}",
    "subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
    "organizations_url": "https://api.github.com/users/octocat/orgs",
    "received_events_url": "https://api.github.com/users/octocat/received_events",
    "type": "User",
    "site_admin": true
  },
  "name": "Octocat App",
  "description": "",
  "external_url": "https://example.com",
  "html_url": "https://github.com/apps/octoapp",
  "created_at": "2017-07-08T16:18:44-04:00",
  "updated_at": "2017-07-08T16:18:44-04:00",
  "permissions": {
    "metadata": "read",
    "contents": "read",
    "issues": "write",
    "single_file": "write"
  },
  "events": [
    "push",
    "pull_request"
  ],
  "client_id": "Iv1.8a61f9b3a7aba766",
```

List installation requests for the authenticated app

Lists all the pending installation requests for the authenticated GitHub App.

Детализированные токены доступа для «List installation requests for the authenticated app»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «List installation requests for the authenticated app»

Заголовки

accept string
Setting to application/vnd.github+json is recommended.

Параметры запроса

per_page integer
The number of results per page (max 100). For more information, see "[Using pagination in the REST API](#)."
По умолчанию.: 30

page integer
The page number of the results to fetch. For more information, see "[Using pagination in the REST API](#)."
По умолчанию.: 1

HTTP-коды статуса ответа для «List installation requests for the authenticated app»

200	List of integration installation requests
304	Not modified
401	Requires authentication

Примеры кода для «List installation requests for the authenticated app»

Пример запроса

GET /app/installation-requests

cURL

JavaScript

Интерфейс командной строки GitHub



```
curl -L \  
-H "Accept: application/vnd.github+json" \  
-H "Authorization: Bearer <YOUR-TOKEN>" \  
-H "X-GitHub-API-Version: 2026-03-10" \  
https://api.github.com/app/installation-requests
```

Код состояния

Description

List of integration installation requests

Пример отклика

Схема ответа

Status: 200

```
[  
  {  
    "id": 25381,  
    "node_id": "MDEyOkludGVncmF0aW9uMTIzNDU2Nzg5MA==",  
    "account": {  
      "login": "octo-org",  
      "id": 6811672,  
      "node_id": "MDEyOk9yZ2FuaXphdGlvbjY4MTE2NzI=",  
      "avatar_url": "https://avatars3.githubusercontent.com/u/6811672?v=4",  
      "gravatar_id": "",  
      "url": "https://api.github.com/users/octo-org",  
      "html_url": "https://github.com/octo-org",  
      "followers_url": "https://api.github.com/users/octo-org/followers",  
      "following_url": "https://api.github.com/users/octo-org/following{/other_user}",  
      "gists_url": "https://api.github.com/users/octo-org/gists{/gist_id}",  
      "starred_url": "https://api.github.com/users/octo-org/starred{/owner}/{repo}",  
      "subscriptions_url": "https://api.github.com/users/octo-org/subscriptions",  
      "organizations_url": "https://api.github.com/users/octo-org/orgs",  
      "repos_url": "https://api.github.com/users/octo-org/repos",  
      "events_url": "https://api.github.com/users/octo-org/events{/privacy}",  
      "received_events_url": "https://api.github.com/users/octo-org/received_events",  
      "type": "Organization",  
      "site_admin": false  
    },  
    "requester": {  
      "id": 1,  
      "node_id": "MDQ6VXNlcjE=",  
      "avatar_url": "https://github.com/images/error/octocat_happy.gif",  
      "gravatar_id": "",  
      "url": "https://api.github.com/users/octocat",  
      "html_url": "https://github.com/octocat",  
      "followers_url": "https://api.github.com/users/octocat/followers",  
      "following_url": "https://api.github.com/users/octocat/following{/other_user}",  
      "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",  
      "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}",
```

```
"subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
"organizations_url": "https://api.github.com/users/octocat/orgs",
"repos_url": "https://api.github.com/users/octocat/repos",
"events_url": "https://api.github.com/users/octocat/events{/privacy}",
"received_events_url": "https://api.github.com/users/octocat/received_events",
"type": "User",
```

List installations for the authenticated app

The permissions the installation has are included under the `permissions` key.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «List installations for the authenticated app»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «List installations for the authenticated app»

Заголовки

`accept` string

Setting to `application/vnd.github+json` is recommended.

Параметры запроса

`per_page` integer

The number of results per page (max 100). For more information, see "[Using pagination in the REST API](#)."

По умолчанию.: 30

`page` integer

The page number of the results to fetch. For more information, see "[Using pagination in the REST API](#)."

По умолчанию.: 1

`since` string

Only show results that were last updated after the given time. This is a timestamp in [ISO 8601](#) format: YYYY-MM-DDTHH:MM:SSZ .

outdated string

HTTP-коды статуса ответа для «List installations for the authenticated app»

200 The permissions the installation has are included under the permissions key.

Примеры кода для «List installations for the authenticated app»

Пример запроса

GET /app/installations

cURL

JavaScriptИнтерфейс командной строки GitHub

📄

curl -L \

Код состояния	Description
HTTP/1.1 200 OK	

The permissions the installation has are included under the permissions key.

Пример отклика

Схема ответа

Status: 200

[
 {
 "id": 1,
 "account": {
 "login": "octocat",
 "id": 1,
 "node_id": "MDQ6VXNlcjE=",
 "avatar_url": "https://github.com/images/error/octocat_happy.gif",
 "gravatar_id": "",
 "url": "https://api.github.com/users/octocat",
 "html_url": "https://github.com/octocat",
 "followers_url": "https://api.github.com/users/octocat/followers",

```
"following_url": "https://api.github.com/users/octocat/following{/other_user}",
"gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
"starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}",
"subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
"organizations_url": "https://api.github.com/users/octocat/orgs",
"repos_url": "https://api.github.com/users/octocat/repos",
"events_url": "https://api.github.com/users/octocat/events{/privacy}",
"received_events_url": "https://api.github.com/users/octocat/received_events",
"type": "User",
"site_admin": false
},
"access_tokens_url": "https://api.github.com/app/installations/1/access_tokens",
"repositories_url": "https://api.github.com/installation/repositories",
"html_url": "https://github.com/organizations/github/settings/installations/1",
"app_id": 1,
"target_id": 1,
"target_type": "Organization",
"permissions": {
  "checks": "write",
  "metadata": "read",
  "contents": "read"
},
"events": [
  "push",
  "pull_request"
],
"single_file_name": "config.yaml",
"has_multiple_single_files": true,
"single file paths": [
```

Get an installation for the authenticated app

Enables an authenticated GitHub App to find an installation's information using the installation id.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «Get an installation for the authenticated app»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «Get an installation for the authenticated app»

Заголовки

accept string

Setting to application/vnd.github+json is recommended.

Параметры пути

installation_id integer **Обязательное поле**

The unique identifier of the installation.

HTTP-коды статуса ответа для «Get an installation for the authenticated app»

200	OK
404	Resource not found

Примеры кода для «Get an installation for the authenticated app»

Пример запроса

```
GET /app/installations/{installation_id}
```

Код состояния	Description
<pre>curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2026-03-10" \ https://api.github.com/app/installations/1</pre>	

Response

Пример отклика

Схема ответа

Status: 200

```
{  
  "id": 1,  
  "account": {  
    "login": "octocat",
```

```

    "id": 1,
    "node_id": "MDQ6VXNlcjE=",
    "avatar_url": "https://github.com/images/error/octocat_happy.gif",
    "gravatar_id": "",
    "url": "https://api.github.com/users/octocat",
    "html_url": "https://github.com/octocat",
    "followers_url": "https://api.github.com/users/octocat/followers",
    "following_url": "https://api.github.com/users/octocat/following{/other_user}",
    "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
    "starred_url": "https://api.github.com/users/octocat/starred{/owner}{/repo}",
    "subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
    "organizations_url": "https://api.github.com/users/octocat/orgs",
    "repos_url": "https://api.github.com/users/octocat/repos",
    "events_url": "https://api.github.com/users/octocat/events{/privacy}",
    "received_events_url": "https://api.github.com/users/octocat/received_events",
    "type": "User",
    "site_admin": false
  },
  "access_tokens_url": "https://api.github.com/app/installations/1/access_tokens",
  "repositories_url": "https://api.github.com/installation/repositories",
  "html_url": "https://github.com/organizations/github/settings/installations/1",
  "app_id": 1,
  "target_id": 1,
  "target_type": "Organization",
  "permissions": {
    "checks": "write",
    "metadata": "read",
    "contents": "read"
  },
  "events": [
    "push",
    "pull_request"
  ],
  "single_file_name": "config.yaml",
  "has_multiple_single_files": true,
  "single_file_paths": [
    "config.yml"
  ]
}

```

Delete an installation for the authenticated app

Uninstalls a GitHub App on a user, organization, or enterprise account. If you prefer to temporarily suspend an app's access to your account's resources, then we recommend the [Suspend an app installation](#) endpoint.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «Delete an installation for the authenticated app»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «Delete an installation for the authenticated app»

Заголовки

accept string
Setting to application/vnd.github+json is recommended.

Параметры пути

installation_id integer **Обязательное поле**
The unique identifier of the installation.

HTTP-коды статуса ответа для «Delete an installation for the authenticated app»

202	Accepted
404	Resource not found

Примеры кода для «Delete an installation for the authenticated app»

Пример запроса

```
DELETE /app/installations/{installation_id}
```

Код состояния	Description
<pre>curl -L \ -X DELETE \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2026-03-10" \ https://api.github.com/app/installations/1</pre>	

Response

Status: 202

Create an installation access token for an app

Creates an installation access token that enables a GitHub App to make authenticated API requests for the app's installation on an organization or individual account. Installation tokens expire one hour from the time you create them. Using an expired token produces a status code of `401 - Unauthorized`, and requires creating a new installation token. By default the installation token has access to all repositories that the installation can access.

Note

Starting April 27, 2026, GitHub began a staged rollout of a stateless format (`ghs_APPID_JWT`) to all newly minted GitHub App installation tokens, making them more performant and improving the reliability of our API surface. If your application expects or relies on installation tokens being exactly 40 characters long, it may not handle this new token format correctly. You can now validate your apps and workflows using a temporary request header that lets you enable the token format on demand. For more information about the temporary header, see [the GitHub blog](#).

Optionally, you can use the `repositories` or `repository_ids` body parameters to specify individual repositories that the installation access token can access. If you don't use `repositories` or `repository_ids` to grant access to specific repositories, the installation access token will have access to all repositories that the installation was granted access to. The installation access token cannot be granted access to repositories that the installation was not granted access to. Up to 500 repositories can be listed in this manner.

Optionally, use the `permissions` body parameter to specify the permissions that the installation access token should have. If `permissions` is not specified, the installation access token will have all of the permissions that were granted to the app. The installation access token cannot be granted permissions that the app was not granted.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «Create an installation access token for an app»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «Create an installation access token for an app»

Заголовки

`accept` `string`
Setting to `application/vnd.github+json` is recommended.

Параметры пути

`installation_id` `integer` **Обязательное поле**
The unique identifier of the installation.

Параметры запроса

`repositories` `array of strings`
List of repository names that the token should have access to

`repository_ids` `array of integers`
List of repository IDs that the token should have access to

`permissions` `object`
The permissions granted to the fine-grained access token.

► Properties of `permissions`

HTTP-коды статуса ответа для «Create an installation access token for an app»

Код состояния	Description
201	Created
401	Requires authentication

Код состояния	Description
403	Forbidden
404	Resource not found
422	Validation failed, or the endpoint has been spammed.

Примеры кода для «Create an installation access token for an app»

Пример запроса

POST /app/installations/{installation_id}/access_tokens

cURL

JavaScript

Интерфейс командной строки GitHub

```
curl -L \
  -X POST \
  -H "Accept: application/vnd.github+json" \
  -H "Authorization: Bearer <YOUR-TOKEN>" \
  -H "X-GitHub-API-Version: 2026-03-10" \
  https://api.github.com/app/installations/1/access_tokens \
  -d '{"repositories":["Hello-World"],"permissions":{"issues":"write","contents":"read"}}'
```

Response

Пример отклика

Схема ответа

Status: 201

```
{
  "token": "ghs_16C7e42F292c6912E7710c838347Ae178B4a",
  "expires_at": "2016-07-11T22:14:10Z",
  "permissions": {
    "issues": "write",
    "contents": "read"
  },
  "repository_selection": "selected",
  "repositories": [
    {
      "id": 1296269,
      "node_id": "MDEwOlJlcG9zaXRvcnkxMjk2MjY5",
      "name": "Hello-World",
      "full_name": "octocat/Hello-World",
      "owner": {
        "login": "octocat",
```

```

    "id": 1,
    "node_id": "MDQ6VXNlcjE=",
    "avatar_url": "https://github.com/images/error/octocat_happy.gif",
    "gravatar_id": "",
    "url": "https://api.github.com/users/octocat",
    "html_url": "https://github.com/octocat",
    "followers_url": "https://api.github.com/users/octocat/followers",
    "following_url": "https://api.github.com/users/octocat/following{/other_user}",
    "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
    "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}",
    "subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
    "organizations_url": "https://api.github.com/users/octocat/orgs",
    "repos_url": "https://api.github.com/users/octocat/repos",
    "events_url": "https://api.github.com/users/octocat/events{/privacy}",
    "received_events_url": "https://api.github.com/users/octocat/received_events",
    "type": "User",
    "site_admin": false
  },
  "private": false,
  "html_url": "https://github.com/octocat/Hello-World",
  "description": "This your first repo!",
  "fork": false,
  "url": "https://api.github.com/repos/octocat/Hello-World",
  "archive_url": "https://api.github.com/repos/octocat/Hello-World/{archive_format}
{/ref}"

```

Suspend an app installation

Suspends a GitHub App on a user, organization, or enterprise account, which blocks the app from accessing the account's resources. When a GitHub App is suspended, the app's access to the GitHub API or webhook events is blocked for that account.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «Suspend an app installation»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «Suspend an app installation»

Заголовки

accept string

Setting to application/vnd.github+json is recommended.

Параметры пути

installation_id integer **Обязательное поле**

The unique identifier of the installation.

HTTP-коды статуса ответа для «Suspend an app installation»

Код состояния	Description
204	No Content
404	Resource not found

Примеры кода для «Suspend an app installation»

Пример запроса

PUT /app/installations/{installation_id}/suspended

cURL

JavaScript

Интерфейс командной строки GitHub



curl -L \
-X PUT \
-H "Accept: application/vnd.github+json" \
-H "Authorization: Bearer <YOUR-TOKEN>" \
-H "X-GitHub-API-Version: 2026-03-10" \
https://api.github.com/app/installations/1/suspended

Response

Status: 204

Unsuspend an app installation

Removes a GitHub App installation suspension.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «Unsuspend an app installation»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «Unsuspend an app installation»

Заголовки

accept string
Setting to application/vnd.github+json is recommended.

Параметры пути

installation_id integer **Обязательное поле**
The unique identifier of the installation.

HTTP-коды статуса ответа для «Unsuspend an app installation»

Код состояния	Description
204	No Content
404	Resource not found

Примеры кода для «Unsuspend an app installation»

Пример запроса

DELETE

/app/installations/{installation_id}/suspended

cURL

JavaScript

Интерфейс командной строки GitHub



```
curl -L \  
-X DELETE \  

```

```
-H "Accept: application/vnd.github+json" \  
-H "Authorization: Bearer <YOUR-TOKEN>" \  
-H "X-GitHub-API-Version: 2026-03-10" \  
https://api.github.com/app/installations/1/suspended
```

Response

Status: 204

Create a scoped access token

Use a non-scoped user access token to create a repository-scoped and/or permission-scoped user access token. You can specify which repositories the token can access and which permissions are granted to the token.

Invalid tokens will return 404 NOT FOUND .

Базовая аутентификация для «Create a scoped access token»

Для использования этой конечной точки необходимо использовать [обычную проверку подлинности](#) . Используйте приложение `client_id` в качестве имени пользователя и `client_secret` пароля.

Параметры для «Create a scoped access token»

Заголовки

`accept` string

Setting to `application/vnd.github+json` is recommended.

Параметры пути

`client_id` string **Обязательное поле**

The client ID of the GitHub app.

Параметры запроса

<code>access_token</code> <code>string</code> Обязательное поле
The access token used to authenticate to the GitHub API.
<code>target</code> <code>string</code>
The name of the user or organization to scope the user access token to. Required unless <code>target_id</code> is specified.
<code>target_id</code> <code>integer</code>
The ID of the user or organization to scope the user access token to. Required unless <code>target</code> is specified.
<code>repositories</code> <code>array of strings</code>
The list of repository names to scope the user access token to. <code>repositories</code> may not be specified if <code>repository_ids</code> is specified.
<code>repository_ids</code> <code>array of integers</code>
The list of repository IDs to scope the user access token to. <code>repository_ids</code> may not be specified if <code>repositories</code> is specified.
<code>permissions</code> <code>object</code>
The permissions granted to the fine-grained access token.

► Properties of `permissions`

HTTP-коды статуса ответа для «Create a scoped access token»

Код состояния	Description
200	OK
401	Requires authentication
403	Forbidden
404	Resource not found
422	Validation failed, or the endpoint has been spammed.

Примеры кода для «Create a scoped access token»

Пример запроса

POST /applications/{client_id}/token/scoped

cURL

JavaScript



```
curl -L \
-X POST \
-H "Accept: application/vnd.github+json" \
-u "<YOUR_CLIENT_ID>:<YOUR_CLIENT_SECRET>" \
-H "X-GitHub-API-Version: 2026-03-10" \
https://api.github.com/applications/Iv1.8a61f9b3a7aba766/token/scoped \
-d
'{"access_token":"e72e16c7e42f292c6912e7710c838347ae178b4a","target":"octocat","permissions":{"metadata":"read","issues":"write","contents":"read"}}'
```

Response

Пример отклика

Схема ответа

Status: 200

```
{
  "id": 1,
  "url": "https://api.github.com/authorizations/1",
  "scopes": [],
  "token": "ghu_16C7e42F292c6912E7710c838347Ae178B4a",
  "token_last_eight": "Ae178B4a",
  "hashed_token": "25f94a2a5c7fbaf499c665bc73d67c1c87e496da8985131633ee0a95819db2e8",
  "app": {
    "url": "https://example.com",
    "name": "my github app",
    "client_id": "Iv1.8a61f9b3a7aba766"
  },
  "note": "optional note",
  "note_url": "http://optional/note/url",
  "updated_at": "2011-09-06T20:39:23Z",
  "created_at": "2011-09-06T17:26:27Z",
  "fingerprint": "jklmnop12345678",
  "expires_at": "2011-09-08T17:26:27Z",
  "user": {
    "login": "octocat",
    "id": 1,
    "node_id": "MDQ6VXNlcnJE=",
    "avatar_url": "https://github.com/images/error/octocat_happy.gif",
    "gravatar_id": "",
    "url": "https://api.github.com/users/octocat",
    "html_url": "https://github.com/octocat",
```

```
"followers_url": "https://api.github.com/users/octocat/followers",
"following_url": "https://api.github.com/users/octocat/following{/other_user}",
"gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
"starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}",
"subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
"organizations_url": "https://api.github.com/users/octocat/orgs",
"repos_url": "https://api.github.com/users/octocat/repos",
"events_url": "https://api.github.com/users/octocat/events{/privacy}",
"received_events_url": "https://api.github.com/users/octocat/received_events",
"type": "User",
"site_admin": false
},
"installation": {
  "permissions": {
```

Get an app

Note

The `:app_slug` is just the URL-friendly name of your GitHub App. You can find this on the settings page for your GitHub App (e.g., https://github.com/settings/apps/:app_slug).

Детализированные токены доступа для «Get an app»

Эта конечная точка работает со следующими точными типами маркеров:

- [Жетоны доступа пользователей приложения GitHub](#)
- [Токены доступа к установке приложений GitHub](#)
- [Точные личные маркеры доступа](#)

Для тонкого маркера не требуются разрешения.

Эту конечную точку можно использовать без проверки подлинности, если запрашиваются только общедоступные ресурсы.

Параметры для «Get an app»

Заголовки

`accept` string

Setting to `application/vnd.github+json` is recommended.

Параметры пути

app_slug string Обязательное поле

HTTP-коды статуса ответа для «Get an app»

Код состояния	Description
200	OK
403	Forbidden
404	Resource not found

Примеры кода для «Get an app»

Пример запроса

GET /apps/{app_slug}

cURL

JavaScript

Интерфейс командной строки GitHub



```
curl -L \
-H "Accept: application/vnd.github+json" \
-H "X-GitHub-API-Version: 2026-03-10" \
https://api.github.com/apps/APP_SLUG
```

Response

Пример отклика

Схема ответа

Status: 200

```
{
  "id": 1,
  "slug": "octoapp",
  "client_id": "Iv1.ab1112223334445c",
  "node_id": "MDExOk1udGVncmF0aW9uMQ==",
  "owner": {
    "login": "octocat",
    "id": 1,
```

```

"node_id": "MDQ6VXNlcjE=",
"avatar_url": "https://github.com/images/error/octocat_happy.gif",
"gravatar_id": "",
"url": "https://api.github.com/users/octocat",
"html_url": "https://github.com/octocat",
"followers_url": "https://api.github.com/users/octocat/followers",
"following_url": "https://api.github.com/users/octocat/following{/other_user}",
"gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
"starred_url": "https://api.github.com/users/octocat/starred{/owner}{/repo}",
"subscriptions_url": "https://api.github.com/users/octocat/subscriptions",
"organizations_url": "https://api.github.com/users/octocat/orgs",
"repos_url": "https://api.github.com/users/octocat/repos",
"events_url": "https://api.github.com/users/octocat/events{/privacy}",
"received_events_url": "https://api.github.com/users/octocat/received_events",
"type": "User",
"site_admin": false
},
"name": "Octocat App",
"description": "",
"external_url": "https://example.com",
"html_url": "https://github.com/apps/octoapp",
"created_at": "2017-07-08T16:18:44-04:00",
"updated_at": "2017-07-08T16:18:44-04:00",
"permissions": {
  "metadata": "read",
  "contents": "read",
  "issues": "write",
  "single_file": "write"
},
"events": [
  "push",
  "pull_request"
]
1

```

Get an organization installation for the authenticated app

Enables an authenticated GitHub App to find the organization's installation information.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «Get an organization installation for the authenticated app»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «Get an organization installation for the authenticated app»

Заголовки

accept string
Setting to application/vnd.github+json is recommended.

Параметры пути

org string **Обязательное поле**
The organization name. The name is not case sensitive.

HTTP-коды статуса ответа для «Get an organization installation for the authenticated app»

Код состояния	Description
200	OK

Примеры кода для «Get an organization installation for the authenticated app»

Пример запроса

GET /orgs/{org}/installation

cURL

JavaScript

Интерфейс командной строки GitHub



curl -L \
-H "Accept: application/vnd.github+json" \
-H "Authorization: Bearer <YOUR-TOKEN>" \
-H "X-GitHub-API-Version: 2026-03-10" \
https://api.github.com/orgs/ORG/installation

Response

Пример отклика

Схема ответа

Status: 200

{
 "id": 1,
 "account": {

```

"login": "github",
"id": 1,
"node_id": "MDEyOk9yZ2FuaXphdGlvbjE=",
"avatar_url": "https://github.com/images/error/hubot_happy.gif",
"gravatar_id": "",
"url": "https://api.github.com/orgs/github",
"html_url": "https://github.com/github",
"followers_url": "https://api.github.com/users/github/followers",
"following_url": "https://api.github.com/users/github/following{/other_user}",
"gists_url": "https://api.github.com/users/github/gists{/gist_id}",
"starred_url": "https://api.github.com/users/github/starred{/owner}/{repo}",
"subscriptions_url": "https://api.github.com/users/github/subscriptions",
"organizations_url": "https://api.github.com/users/github/orgs",
"repos_url": "https://api.github.com/orgs/github/repos",
"events_url": "https://api.github.com/orgs/github/events",
"received_events_url": "https://api.github.com/users/github/received_events",
"type": "Organization",
"site_admin": false
},
"repository_selection": "all",
"access_tokens_url": "https://api.github.com/app/installations/1/access_tokens",
"repositories_url": "https://api.github.com/installation/repositories",
"html_url": "https://github.com/organizations/github/settings/installations/1",
"app_id": 1,
"client_id": "Iv1.ab1112223334445c",
"target_id": 1,
"target_type": "Organization",
"permissions": {
  "checks": "write",
  "metadata": "read",
  "contents": "read"
},
"events": [
  "push",
  "pull_request"
],
"created_at": "2018-02-09T20:51:14Z",
"updated_at": "2018-02-09T20:51:14Z"

```

Get a repository installation for the authenticated app

Enables an authenticated GitHub App to find the repository's installation information. The installation's account type will be either an organization or a user account, depending which account the repository belongs to.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «Get a repository installation for the authenticated app»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «Get a repository installation for the authenticated app»

Заголовки

`accept` `string`
Setting to `application/vnd.github+json` is recommended.

Параметры пути

`owner` `string` **Обязательное поле**
The account owner of the repository. The name is not case sensitive.

`repo` `string` **Обязательное поле**
The name of the repository without the `.git` extension. The name is not case sensitive.

HTTP-коды статуса ответа для «Get a repository installation for the authenticated app»

Код состояния	Description
200	OK
301	Moved permanently
404	Resource not found

Примеры кода для «Get a repository installation for the authenticated app»

Пример запроса

`GET /repos/{owner}/{repo}/installation`

`cURL`

JavaScript

Интерфейс командной строки GitHub

```
curl -L \  
  -H "Accept: application/vnd.github+json" \  
  -H "Authorization: Bearer <YOUR-TOKEN>" \  

```

-H "X-GitHub-API-Version: 2026-03-10" \
https://api.github.com/repos/OWNER/REPO/installation

Response

Пример отклика

Схема ответа

Status: 200

```
{
  "id": 1,
  "account": {
    "login": "github",
    "id": 1,
    "node_id": "MDEyOk9yZ2FuaXphdGlvbjE=",
    "avatar_url": "https://github.com/images/error/hubot_happy.gif",
    "gravatar_id": "",
    "url": "https://api.github.com/orgs/github",
    "html_url": "https://github.com/github",
    "followers_url": "https://api.github.com/users/github/followers",
    "following_url": "https://api.github.com/users/github/following{/other_user}",
    "gists_url": "https://api.github.com/users/github/gists{/gist_id}",
    "starred_url": "https://api.github.com/users/github/starred{/owner}/{repo}",
    "subscriptions_url": "https://api.github.com/users/github/subscriptions",
    "organizations_url": "https://api.github.com/users/github/orgs",
    "repos_url": "https://api.github.com/orgs/github/repos",
    "events_url": "https://api.github.com/orgs/github/events",
    "received_events_url": "https://api.github.com/users/github/received_events",
    "type": "Organization",
    "site_admin": false
  },
  "repository_selection": "all",
  "access_tokens_url": "https://api.github.com/app/installations/1/access_tokens",
  "repositories_url": "https://api.github.com/installation/repositories",
  "html_url": "https://github.com/organizations/github/settings/installations/1",
  "app_id": 1,
  "client_id": "Iv1.ab1112223334445c",
  "target_id": 1,
  "target_type": "Organization",
  "permissions": {
    "checks": "write",
    "metadata": "read",
    "contents": "read"
  },
  "events": [
    "push",
    "pull_request"
  ],
  "created_at": "2018-02-09T20:51:14Z",
  "updated_at": "2018-02-09T20:51:14Z",
}
```

Get a user installation for the authenticated app

Enables an authenticated GitHub App to find the user’s installation information.

You must use a [JWT](#) to access this endpoint.

Детализированные токены доступа для «Get a user installation for the authenticated app»

Эта конечная точка не работает с пользовательскими токенами доступа GitHub App, токенами доступа для установки GitHub App или детализированными персональными токенами доступа.

Параметры для «Get a user installation for the authenticated app»

Заголовки

accept string
Setting to application/vnd.github+json is recommended.

Параметры пути

username string **Обязательное поле**
The handle for the GitHub user account.

HTTP-коды статуса ответа для «Get a user installation for the authenticated app»

Код состояния	Description
200	OK

Примеры кода для «Get a user installation for the authenticated app»

Пример запроса

GET

/users/{username}/installation

cURL

JavaScript

Интерфейс командной строки GitHub

```
curl -L \
-H "Accept: application/vnd.github+json" \
-H "Authorization: Bearer <YOUR-TOKEN>" \
-H "X-GitHub-API-Version: 2026-03-10" \
https://api.github.com/users/USERNAME/installation
```

Response

Пример отклика

Схема ответа

Status: 200

```
{
  "id": 1,
  "account": {
    "login": "github",
    "id": 1,
    "node_id": "MDEyOk9yZ2FuaXphdGlvbjE=",
    "avatar_url": "https://github.com/images/error/hubot_happy.gif",
    "gravatar_id": "",
    "url": "https://api.github.com/orgs/github",
    "html_url": "https://github.com/github",
    "followers_url": "https://api.github.com/users/github/followers",
    "following_url": "https://api.github.com/users/github/following{/other_user}",
    "gists_url": "https://api.github.com/users/github/gists{/gist_id}",
    "starred_url": "https://api.github.com/users/github/starred{/owner}/{repo}",
    "subscriptions_url": "https://api.github.com/users/github/subscriptions",
    "organizations_url": "https://api.github.com/users/github/orgs",
    "repos_url": "https://api.github.com/orgs/github/repos",
    "events_url": "https://api.github.com/orgs/github/events",
    "received_events_url": "https://api.github.com/users/github/received_events",
    "type": "Organization",
    "site_admin": false
  },
  "repository_selection": "all",
  "access_tokens_url": "https://api.github.com/app/installations/1/access_tokens",
  "repositories_url": "https://api.github.com/installation/repositories",
  "html_url": "https://github.com/organizations/github/settings/installations/1",
  "app_id": 1,
  "client_id": "Iv1.ab1112223334445c",
  "target_id": 1,
  "target_type": "Organization",
  "permissions": {
    "checks": "write",
    "metadata": "read",
    "contents": "read"
  },
  "events": [
    "push",
    "pull_request"
  ],
  "created_at": "2018-02-09T20:51:14Z",
  "updated_at": "2018-02-09T20:51:14Z",
  "installation_id": 1,
  "account_id": 1,
  "app_slug": "github",
  "app_name": "GitHub Actions",
  "app_description": "GitHub Actions is a workflow automation tool that integrates with over 100 GitHub Actions to help you build and run your code. You can use GitHub Actions to build and test your code, or to deploy your code to production. GitHub Actions is a powerful tool that can help you automate your workflow and improve your productivity."
}
```

Юридические услуги

Некоторые из этих содержимого могут быть переведены на компьютер или ИИ.

© 2026 GitHub, Inc. [Условия](#) [Конфиденциальность](#) [Состояние](#) [Цены](#) [Экспертные службы](#)
[Блог](#)