The Journal of Open Source Software

# LogicalQ: A toolkit for quantum circuit development with generalized quantum error mitigation, detection, and correction

**Rasmit Devkota**[1,2], **Ben Hagan**[3], **Nolan Heffner**[1,2], **Younos Hashem**[1], **Noah Song**[2], **Arhan Deshpande**[1], **Fiyin Makinde**[4], **Richard Yu**[2,5], **Alisa Petrusinskaia**[5], **Zhixin Song**[1], **David Lloyd George**[6], **and Lance Lampert**[6]

**1** School of Physics, College of Sciences, Georgia Institute of Technology, Atlanta, GA **2** School of Mathematics, College of Science, Georgia Institute of Technology, Atlanta, GA **3** Ming Hsieh Department of Electrical and Computer Engineering, Viterbi School of Engineering, University of Southern California, Los Angeles, CA **4** School of Electrical and Computer Engineering, College of Engineering, Georgia Institute of Technology, Atlanta, GA **5** School of Computer Science, College of Computing, Georgia Institute of Technology, Atlanta, GA **6** Department of Physics, Duke University, Durham, NC

**DOI:** 10.xxxxxx/draft

**Software**

- Review
- Repository
- Archive

**Editor:** Open Journals

**Reviewers:**

- @openjournals

**Submitted:** 01 January 1970
**Published:** unpublished

**License**
Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

DRAFT

## Summary

`LogicalQ` is a Python toolkit for quantum circuit development with generalized quantum error mitigation, detection, and correction (QEMDAC). `LogicalQ` inherits many of its data structures from, and thus is designed to interface well with, the `Qiskit` and `Qiskit Aer` packages (Javadi-Abhari et al., 2024).

The source code for `LogicalQ` is available on GitHub. It can be installed via `pip` from the pypi index. Its documentation is hosted publicly.

## Statement of need

Quantum computing presents a new model for computation which may significantly accelerate discovery in many fields, from physics (Feynman, 1982) to cryptography (P. W. Shor, 1994) to economics (Herman et al., 2023). However, the current era of quantum hardware is still noisy, and quantum error mitigation (QEM) (Viola & Lloyd, 1998), quantum error detection (QED) (Leung et al., 1999), and quantum error correction (QEC) (Peter W. Shor, 1995) techniques are necessary for the execution of utility-scale algorithms with any reasonable fidelity. Although there exist a number of libraries which allow researchers with some background to run experiments focused on QEC, there is no unified framework for general QEMDAC which is accessible to quantum computing researchers of any background and simultaneously supports the convenient implementation of quantum algorithms.

Many of the necessary components for QEMDAC have been formalized mathematically such that algorithms can be designed to construct these components for general classes of error control techniques (Gottesman, 1997). `LogicalQ`, like many existing QEMDAC libraries, uses such generalized constructions to meet any use case and application.

A comparison of existing libraries is made in Table 1. We choose to compare features which may be desirable to researchers in quantum algorithms. Note that we define external two-way interoperability to be with any external general-purpose quantum computing tool such as `QASM` or `Qiskit`, but not just another QEMDAC tool.

The Journal of Open Source Software

**Table 1:** Comparison of `LogicalQ` with other major QEMDAC packages; `stim` is due to (Gidney, 2021), `mqt-qecc` is due to (Wille et al., 2024), `PECOS` is due to (Ryan-Anderson, n.d.), `stac` is due to (Khalid, 2024), and `tqec` is due to (tqec, n.d.).

| Feature | `LogicalQ` | `stim` | `mqt-qecc` | `PECOS` | `stac` | `tqec` |
|---|---|---|---|---|---|---|
| Stabilizer code QEC | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| qLDPC-oriented QEC | ✓ | × | ✓ | × | × | × |
| Arbitrary logical Clifford gates | ✓ | × | × | ✓ | ✓ | × |
| Arbitrary logical non-Clifford gates | ✓ | × | × | ✓ | ✓ | × |
| Advanced decoders | × | ✓ | ✓ | ✓ | × | ✓ |
| Arbitrary noise model support | ✓ | × | × | ✓ | × | ✓ |
| Optimized QEC cycle scheduling | ✓ | × | × | × | × | × |
| Experiment suite | ✓ | × | × | ✓ | × | ✓ |
| Logical state analysis | ✓ | × | × | × | × | ✓ |
| External two-way interoperability | ✓ | ✓ | × | × | ✓ | × |
| Cloud hardware interfaces | ✓ | × | × | × | × | × |

In summary, many of the existing libraries are notable for their high-performance simulations and advanced implementations of certain features, but none support the full functionality required for QEMDAC applied to quantum algorithms research, especially on cloud hardware. `LogicalQ` is also unique in that it has a suite of experiments for testing QEMDAC which serves as a quick set of tests for researchers studying noise control.

`LogicalQ` was designed to accelerate the application of QEMDAC in quantum algorithm development, so its core design principle is maximizing user capability for implementing complex quantum circuits and using QEMDAC. The combination of generalized quantum error correction functionality, compatibility with libraries such as Qiskit, existence of numerous demo notebooks, and overall usability will increase accessibility to quantum error-corrected research and enable deeper study into the application of quantum error correction.

Furthermore, QEMDAC techniques can make analysis of quantum computation results difficult because they utilize overhead resources which exponentially increase the size of experiment outputs. There is a need for tools which can parse QEMDAC results without requiring researchers to understand the often-complex mathematics of these techniques. Although many of the necessary tools are not particularly lengthy or convoluted in their implementation, `LogicalQ` provides a single toolkit which handles the complexities of the QEMDAC workflow to avoid user error when constructing circuit components or performing mathematical analyses.

# Functionality

`LogicalQ` consists of various modules which provide functionality for the construction of QEMDAC components as well as their application and analysis.

A general flowchart of library structure is shown in Figure 1.

DRAFT

The Journal of Open Source Software




**Figure 1:** LogicalQ Architecture

The `Logical` module lies at the heart of the library with the `LogicalCircuit` class, which inherits from the `QuantumCircuit` class in `Qiskit` and extends it with a variety of QEMDAC features. A `LogicalCircuit` can be constructed from a `Qiskit` `QuantumCircuit` via the `from_physical_circuit` method, which enables easy integration of `LogicalQ` into existing workflows. The `optimize_qec_cycle_indices` method of `LogicalCircuit` performs cost accounting based on a constraint model and effective threshold in order to construct an optimal list of QEC cycle indices.

The `Logical` module also contains the `LogicalStatevector` and `LogicalDensityMatrix` classes, which inherit from the `Statevector` and `DensityMatrix` classes in `Qiskit` respectively and enable representation and analysis of quantum states at either the logical level or physical level. `Logical` also contains the `logical_state_fidelity` function which is designed to support mixed-type fidelity comparisons, such as the fidelity of a physical density matrix and a logical statevector.

The `Benchmarks` module contains constructors for many of the most commonly-used benchmarking circuits in quantum computation, including randomized benchmarking and quantum volume. These functions expose parameters such as qubit counts, circuit lengths, and random selection seeds to the user so that they can be directly integrated into controlled tests and experiments. We also include common useful algorithms such as quantum teleportation in our set of benchmarks to encourage application-oriented performance testing, an important concept in the current stage of QEMDAC research.

The `Experiments` module contains a variety of experiments which can be used to study QEMDAC techniques. Experiment data can be analyzed with functions from the `Analysis` module. Experiments are designed in such a way that they can be composed in order to build more complex experiment workflows.

The `Execution` module contains the `execute_circuits` function, which provides a single interface for both simulator and hardware backends with smart handling of complex aspects such as backend communication, hardware models, and transpilation. This minimizes the amount of hardware optimization and compatibility users have to consider themselves when using the library.

The `Estimators` module contains special experiments which are used in QED and QEC cycle scheduling. In particular, this includes effective threshold estimation and constraint model construction. These are core aspects of our optimized QEMDAC protocol which were designed around multiple iterations of testing and benchmarking.

The `Library` modules contain utilties such as quantum codes for QED and QEC, hardware models for modelling quantum devices, special gates for benchmarking, and dynamical decoupling sequences for QEM. Many of these are essential for any QEMDAC workflow,

DRAFT

so users can easily access them within our library without having to rely on other sources which may have inconsistent standards.

# Software Design

LogicalQ is built in Python as it is a language of choice among researchers who require effective solutions for their work without compromising computational efficiency; to this end, we actively use tools such as parallel processing in our core code to maximize computational efficiency without requiring users to be familiar with the technical details of such tools. In order to ease the transition into using LogicalQ, it follows the same conventions of popular libraries such as Qiskit and pytket wherever possible. At the same time, we also maintain compatibility with the conventions used in the QEMDAC community, especially the mathematical and experimental conventions which researchers would desire when choosing a computational tool to complement their theoretical and experimental work. We have used our demo notebooks and test cases to better understand how our codebase would be used in different contexts, including both theoretical QEMDAC research and applied experimental studies, and this has allowed us to balance the needs of various use cases in each method a user can call. Because QEMDAC research ranges from pure theory to computation to experiment, `LogicalQ` accordingly accommodates each of these approaches to allow for more coherence in mixed-domain projects.

# Research Impact

`LogicalQ` development has largely been driven by an ongoing research project to optimize the scheduling of QEMDAC components in quantum circuits, with the motivation of performing fault-tolerant Hamiltonian simulations of lattice gauge theories and other physical models on quantum hardware. Specific examples include the Kogut-Susskind and Isotropic Heisenberg models. This work involves code switching between QEC and QED codes depending on the error-criticality of a part of a circuit, made less complex by `LogicalQ`'s generalized framework for stabilizer codes. There is also ongoing work on genetic algorithm-based optimization of physical and logical dynamical decoupling sequences for applications in modelling biological processes such as protein folding. This work is all open-source and can be viewed through the demo notebooks on GitHub which are used for experimentation. These demo notebooks, among the many others, demonstrate the quality of our codebase, including many benchmarking notebooks which compare our performance against other techniques. Moreover, the library has also been used outside our primary institution (Georgia Tech) by individuals for their own projects as it allows for a rapid theory-to-implementation workflow.

# Acknowledgements

We acknowledge contributions from the Quantum Computing Association at Georgia Tech.

We would like to thank Jeff Young for serving as the advisor of the Quantum Computing Association at Georgia Tech and this project.

This research was supported in part through research cyberinfrastructure resources and services provided by the Partnership for an Advanced Computing Environment (PACE) at the Georgia Institute of Technology, Atlanta, Georgia, USA (PACE, 2017).

# AI Usage Disclosure

Generative AI was not used in any capacity in software creation, documentation, or paper authoring.

DRAFT

# References


Feynman, R. P. (1982). Simulating physics with computers. *International Journal of Theoretical Physics*, *21*(6–7), 467–488. https://doi.org/10.1007/bf02650179

Gidney, C. (2021). Stim: A fast stabilizer circuit simulator. *Quantum*, *5*, 497. https://doi.org/10.22331/q-2021-07-06-497

Gottesman, D. (1997). *Stabilizer codes and quantum error correction*. arXiv. https://doi.org/10.48550/ARXIV.QUANT-PH/9705052

Herman, D., Googin, C., Liu, X., Sun, Y., Galda, A., Safro, I., Pistoia, M., & Alexeev, Y. (2023). Quantum computing for finance. *Nature Reviews Physics*, *5*(8), 450–465. https://doi.org/10.1038/s42254-023-00603-1

Javadi-Abhari, A., Treinish, M., Krsulich, K., Wood, C. J., Lishman, J., Gacon, J., Martiel, S., Nation, P. D., Bishop, L. S., Cross, A. W., Johnson, B. R., & Gambetta, J. M. (2024). *Quantum computing with Qiskit*. https://doi.org/10.48550/arXiv.2405.08810

Khalid, A. (2024). *Stac*. https://github.com/abdullahkhalids/stac.

Leung, D., Vandersypen, L., Zhou, X., Sherwood, M., Yannoni, C., Kubinec, M., & Chuang, I. (1999). Experimental realization of a two-bit phase damping quantum code. *Physical Review A*, *60*(3), 1924–1943. https://doi.org/10.1103/physreva.60.1924

PACE. (2017). *Partnership for an Advanced Computing Environment (PACE)*. http://www.pace.gatech.edu

Ryan-Anderson, C. (n.d.). *PECOS*. https://github.com/PECOS-packages/PECOS

Shor, P. W. (1994). Algorithms for quantum computation: Discrete logarithms and factoring. *Proceedings 35th Annual Symposium on Foundations of Computer Science*, 124–134. https://doi.org/10.1109/SFCS.1994.365700

Shor, Peter W. (1995). Scheme for reducing decoherence in quantum computer memory. *Phys. Rev. A*, *52*, R2493–R2496. https://doi.org/10.1103/PhysRevA.52.R2493

tqec. (n.d.). *Tqec*. https://github.com/tqec/tqec

Viola, L., & Lloyd, S. (1998). Dynamical suppression of decoherence in two-state quantum systems. *Phys. Rev. A*, *58*, 2733–2744. https://doi.org/10.1103/PhysRevA.58.2733

Wille, R., Berent, L., Forster, T., Kunasaikaran, J., Mato, K., Peham, T., Quetschlich, N., Rovara, D., Sander, A., Schmid, L., Schoenberger, D., Stade, Y., & Burgholzer, L. (2024). The MQT handbook: A summary of design automation tools and software for quantum computing. *IEEE International Conference on Quantum Software (QSW)*. https://doi.org/10.1109/QSW62656.2024.00013


DRAFT