



CPaaS Consolidated API Documentation

Version	Created By	Approved By	Date
V1.0	Bhagyashree Gaikwad		25/02/2026
V2.0	Bhagyashree Gaikwad		04/03/2026
V3.0	Bhagyashree Gaikwad	Nilesh Shinde	09/04/2026

Contents

Overview	4
Token Generation.....	4
API Formation.....	5
SMS Channel API	6
1.1 API Endpoint	7
1.2 Required Headers	7
1.3 Payload Field Details.....	8
1.4 Template API	9
1.5 Open Text API	11
1.6 GET Status API.....	12
1.7 Bulk Send API.....	13
1.8 Common Error Responses	14
WhatsApp Channel API	15
2.1 API Endpoint.....	16
2.2 Headers	17
2.3 Request Body Parameters	17
2.4 Template API With Media	18
2.5 Template API Without Media	19
ORDER RELATED APIs.....	20
2.6 Order Status API	20
2.7 Order Refund API	22
2.8 User Management API `s.....	23
RCS Channel API.....	28
3.1 API Endpoint	29
3.2 Headers	29
3.3 Payload Field details	29
3.4 Template creation Text Type with Buttons.....	31
3.5 Template Creation for Rich Card (Media with Buttons)	34
3.6 Template Creation Card Carousel	38

3.8	Service Send API Vi	42
	Email Channel API	46
4.1	API Endpoint:	47
4.2	Required Headers:	47
4.3	Payload Fields Details:	47
4.4	Template Email API	48
4.5	Open text Email API	50
4.6	Status Check API	51
4.7	Common error Responses	52
	Flow builder API	53
5.1	API Endpoint	54
5.2	Headers	54
5.3	Request Body Parameters	54

Overview

CPaaS+ provides a unified API suite for multi-channel messaging:

- **SMS** (Campaign, Template, Open Text, Bulk, Status)
- **WhatsApp Business** (Templates, Media, User Management, Order events)
- **Email** (Templates, Open Text, OTP, Status)
- **RCS** (Templates & Service sending for VI/Jio)
- **Flow Builder** (Trigger omnichannel flows)

All APIs are **HTTP-based**, in **JSON data format** and secured with **Bearer Token** authentication.

Token Generation

All secured endpoints use a Bearer token in the Authorization header.

Authorization: Bearer <YOUR_TOKEN>

The Token can be generated from your CPaaS+ Portal.

- Go to the **API Tab (Left Side Tool Bar) >> Click "Add new Token" (on Top Right)**
- Enter the **Token Name** and Click **Save**
- Your **New Token is generated** which can be saved and utilized in the API(s)

Sample Token:

90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk

Note: Please copy this API token and save it, as we will not show this again!

Additional Configuration is **Optional**, for added layer of security

- Encryption Algorithm: Select either **AES-256-CBC** or **AES-128-CBC**
- Encryption Key (min 16 Characters): Add your own Key
- Initialization Vector (IV): Can add your own Value, which is optional

API Formation

All API(s) will require the below components

- **Base URL:** <https://api.yourcpaas.com> (This will be the Host of your Web Portal Account)
- **Path:** As defined in each channel

Sample API Endpoint Formation:

<https://api.yourcpaas.com/api/sms/send-msg>

- **Headers:** **Content-Type**, **Authorization**, **accept** (to be used in Campaign API)

SMS Channel API

The CPaaS+ SMS API allows you to programmatically send SMS messages to any mobile number. Whether you're sending a one-time password, a transactional alert, or a bulk message blast for your promotional campaign - the SMS API handles it all through simple REST calls.

SMS API(s) Overview:

API	Endpoint (Path)	Best For
Template Send	/api/sms/template/send	Sending registered templates with dynamic variables
Open Text	/api/sms/send	Sending freeform text messages programmatically
Bulk Send	/api/sms/json	Sending different messages to different numbers in one API call
Status Check	/api/sms/status	Checking request status

1.1 API Endpoint

POST/GET: [{{domain URL}}/api/sms/send](#)

Example - [https://uber.cpaasplus.globeteleservices.com /api/sms/send](https://uber.cpaasplus.globeteleservices.com/api/sms/send)

1.2 Required Headers

Key	Value
Content-Type	application/json
Accept	application/json
Authorization	Bearer <your_token>

1.3 Payload Field Details

Field Name	Required	Description
sender id	Yes	Sender ID name (as registered). (Required only if alias is not provided) The ID found under Template Preview in the SMS Template section.
to	Yes	Recipient numbers (single string or array, max 50). Can be a single number (string format) or an array of numbers.
id	Optional	Unique Message ID returned in response while submitting a request successfully
text	Yes	Message to be delivered
type	Optional	"N" for plain text (default), "U" for Unicode, "A" for auto
product	Optional	"Transactional", "Promotional", "OTP", "Other"
template_id	Optional	DLT template ID
entity_id	Optional	Required for Indian senders (DLT Entity ID)
alias	Yes	(Required only if id is not provided) The template alias value associated with the template.
params	Yes	Parameters defined in the template. If no parameters exist, pass an empty array {}
code	Optional	The Delivery Code of as captured by the operator
Status	Optional	The Status of the Message, values can be 'DELIVRD' 'FAILED'
page	Optional	Assign Page number to fetch data from respective page, default 100 records per page
Per_page	Optional	Total number of records fetched can be max 100, this can be limited to 50,25,10
campaign_id	Yes	The Campaign ID is generated in the Web Portal under 'Campaigns' section once you successfully ran a campaign
message_id	Yes	This is the unique identifier/Message Id of the Request
number	Yes	The Mobile Number passed in the request
from	Optional	The Number of Dynamic values to be passed as defined in the template
code	Optional	The Delivery Code of as captured by the operator
Status	Optional	The Status of the Message, values can be 'DELIVRD' 'FAILED'

page	Optional	Assign Page number to fetch data from respective page, default 100 records per page
Per_page	Optional	Total number of records fetched can be max 100, this can be limited to 50 or 25 or 10
root	Yes	Fallback/default object. Values here are used when a data[] entry is missing from, text, or to fields
data	Yes	Array of individual message objects. Maximum 500 objects per request

Note: The entity_id is mandatory if the sender is based in India

1.4 Template API

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/sms/template/send' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk' \
--data '{
  "alias": "Template ID",
  "to": [
    "91XXXXXXXXXX",
    "91XXXXXXXXXX"
  ],
  "params": {
    "1": "Ben",
    "2": "India"
  }
}'
```

Response:

```
{
  "status": "success",
  "message": "Messages are sent successfully.",
  "data": [
    {
      "status": "submitted",
      "message_id": "8274dfef-6e90-4565-8dc9-f40e646adcf8",
      "number": "91XXXXXXXXXX",
      "units": 1,
      "received_at": "2026-02-27 15:53:46"
    },
    {
      "status": "submitted",
      "message_id": "71a8b330-6641-45d7-94e2-c8f281e505b8",
      "number": "917002088512",
      "units": 1,
      "received_at": "2026-02-27 15:53:46"
    }
  ]
}
```

}
]
}

1.5 Open Text API

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/sms/send' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk' \
--data '{
  "from": "PUSHIN",
  "to": [
    "91XXXXXXXXXX"
  ],
  "text": "Hello User, This is promotional test message."
  "type": "A"
  "product": "Transactional",
  "template_id": "1407172959608329846",
  "entity_id": "1401655950000071757"
}
```

Response:

```
{
  "status": "success",
  "message": "Messages are sent successfully.",
  "data": [
    {
      "status": "submitted",
      "message_id": "fb82db82-97fd-4d93-8055-d6941baf20fb",
      "number": "918999614332",
      "units": 1,
      "received_at": "2026-02-27 15:56:15"
    }
  ]
}
```

1.6 GET Status API

Used to fetch the required Delivery Report (DLR Status) of the submitted message.

curl --location

```
'https://uber.cpaasplus.globeteleservices.com/api/sms/status?number=91XXXXXXXXXX&
id=a7ae8860-1dee-483a-b0c7c34f7a978605&from=DUMMY'91XXXXXXXXXX \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk'
```

Response:

```
{
  "status": "success",
  "data": [
    {
      "message_id": "fb82db82-97fd-4d93-8055-d6941baf20fb",
      "from": "PUSHIN",
      "number": "918999604332",
      "status": "DLT_Failure",
      "code": "101",
      "units": 1,
      "received_at": "2026-02-27 15:56:15",
      "delivered_at": null,
      "failed_at": null
    }
  ],
  "pagination": {
    "total": 1,
    "count": 1,
    "per_page": 100,
    "current_page": 1,
    "total_pages": 1
  }
}
```

Note : code & status Are non-mandatory fields.

1.7 Bulk Send API

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/sms/json' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer {{Bearer Token}}' \
--data '{
  "root": {
    "from": "CPAAS",
    "text": "Hello {{name}}, your order is confirmed.",
    "to": ["91XXXXXXXXXX"]
  },
  "data": [
    {
      "from": "PROMO",
      "text": "Hi John, your OTP is 485923",
      "to": ["91XXXXXXXXXX"]
    },
    {
      "from": "PROMO",
      "text": "Hi Paul, your OTP is 736104",
      "to": ["91XXXXXXXXXX"]
    }
  ]
}'
```

Response:

```
{
  "status": "success",
  "message": "Messages are sent successfully.",
  "data": [
    {
      "status": "submitted",
      "message_id": "5fc76f1d-177b-4af2-9ab5-b214dbad3e81",
      "number": "91XXXXXXXXXX",
      "units": 1,
      "received_at": "2026-03-26 10:15:32"
    },
    {
      "status": "submitted",
      "message_id": "43e3783a-0f4b-4097-9432-1428eb33050d",
      "number": "91XXXXXXXXXX",
      "units": 1,
      "received_at": "2026-03-26 10:15:32"
    }
  ]
}
```

```
]
}
```

1.8 Common Error Responses

HTTP Code	Meaning	Possible Cause
400	Bad Request	Invalid JSON, missing fields
401	Unauthorized	Invalid/missing token
403	Forbidden	Restricted IP
422	Unprocessable Entity/Content	Invalid numbers/field or message content
500	Internal Server Error	Server-side issue

Note: They are Standard HTTP Status Codes, that include 1xx/2xx/3xx/4xx/5xx series

Response Example:

```
{
  "message": "The from field is required.",
  "errors": {
    "from": [
      "The from field is required."
    ]
  }
}
{
  "message": "Unauthenticated."
}
```

Notes:

1. Comment lines are not allowed in the JSON.
2. Only up to 50 numbers are allowed in the to field. (this criterion is for Opentext & Campaign API)
3. For message length:
 - o Plain Text (N): 1 unit = 160 characters
 - o Unicode (U): 1 unit = 70 characte

WhatsApp Channel API

The CPaaS+ WhatsApp API enables you to send template-based and media messages via WhatsApp Business. Manage user blocks, handle order status updates, process refunds, and deliver interactive messages -all through simple REST calls using your approved WABA (WhatsApp Business Account).

WhatsApp API(s) Overview:

API	Endpoint (Path)	Best For
Template Send -With Media	/api/whatsapp/msg	Sending approved WA template with image/video/document
Template Send - Without Media	/api/whatsapp/msg	Sending approved WA template with text-only body
Order Status Update	/api/whatsapp/{{source}}/order-status/update	Updating order status in WhatsApp Commerce flows
Order Refund	/api/whatsapp/GTSadmin/payment/refund	Triggering a payment refund in WhatsApp Commerce
Block User	/api/whatsapp/blocked-members	Blocking a user from receiving WhatsApp messages
Unblock User	/api/whatsapp/blocked-members	Removing a block on a user (DELETE method)
Bulk User Block	/api/whatsapp/blocked-members/import-csv	Bulk block users via CSV file upload
Request Blocked Users	/api/whatsapp/blocked-members	Fetching the list of all blocked users (GET method)
Sync Blocked Users	/api/whatsapp/blocked-members/sync	Syncing blocked user list with the WhatsApp platform

2.1 API Endpoint

POST : {{domain_url}}/api/whatsapp/msg

Example - https:// uber.cpaasplus.globeteleservices.com/api/whatsapp/msg

2.2 Headers

This API is used to send a WhatsApp message using a predefined template.

Request Headers

Header Name	Value	Description
Content-Type	application/json	Specify the format of the request body.
Accept	application/json	Expected response format.
Authorization	Bearer <token>	API access token (replace with a valid token).

2.3 Request Body Parameters

Parameter	Type	Description	Required
source	string	The registered WhatsApp sender number.	Yes
destination	Numeric/string	The recipient's WhatsApp number (with country code).	Yes
template.id	string	The ID of the pre-approved WhatsApp template.	Yes
params	array	List of values to replace dynamic variables in the template. Order must match variable orders in the template.	If variable added in the template.
media_url (upto 10 urls can be added for Media Card & Product Card Carousel)	string	Publicly accessible URL of the media file to be sent (e.g., PDF, image, video).	For Media template.
order_reference_id	string	Unique order identifier from your system to update status for	Yes
status	string	New order status value: confirmed shipped delivered cancelled	Yes
tracking_url	string	Publicly accessible shipment tracking URL to share with customer	Optional
description	string	Additional status description or notes for the customer	Optional
receiver	string	Customer WhatsApp number	Yes

Note – Kindly refer to the above parameters for all the template specifications mentioned ahead in this document.

2.4 Template API With Media

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/whatsapp/msg' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer
90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk' \
--data '{
  "source": "{{WA_SenderID}}",
  "destination": "{{phone}}",
  "template": {
    "id": "{{Your approved WhatsApp Template ID}}"
  },
  "media_url": " https://dummyimage.com/800x600/000/fff.png "
}'
```

Response :

```
{
  "success": true,
  "status": "Submitted",
  "message_id":
"wamid.HBgMOTe4OTk5NjE0ODE2FQIAERgSNUQ3QkI1QzgyNDhENTJCNDAA==",
  "wa_message_id": 250661,
  "timestamp": "2026-02-27 15:32:13"
}
```

Error Codes:

Code	Message	Description
400	Bad Request	Missing or invalid parameters.
401	Unauthorized	Invalid or missing auth token.
500	Internal Server Error	Server-side issue.
422	Required field	For e.g. "The template.id field is required."

2.5 Template API Without Media

```
curl --location --globoff
'https://uber.cpaasplus.globeteleservices.com/api/whatsapp/msg' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer
90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk' \
--data '{
  "source": "{{WA_SenderID}}",
  "destination": "{{phone}}",
  "template": {
    "id": "5ee89304-a0db-4815-87f5-693fb167341a",
    "params": [
      "marie",
      "telecom"
    ]
  }
}'
```

Response :

```
{
  "success": true,
  "status": "Submitted",
  "message_id":
"wamid.HBgMOTe4OTk5NjE0ODE2FQIAERgSNUQ3QkI1QzgyNDhENTJCNDAA==",
  "wa_message_id": 250661,
  "timestamp": "2026-02-27 15:32:13"
}
```

ORDER RELATED APIs

2.6 Order Status API

Note : Processing status is by default status.

Note: Update status From Processing to partially_shipped use below API

- **for partially_shipped Status**

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/whatsapp/{{source}}/order-status/update' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer 90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk' \
--data '{
  "order_reference_id": "ORDER_1771417058_RTk0NjQA",
  "status": "partially_shipped",
  "status_notes": "Thank you for your purchase"
}'
```

Response :

```
{
  "success": "true",
  "message": "partially_shipped "
}
```

Note : source = Sender name / WABA Number

Note: Update status From partially_shipped to shipped use below API

- **for shipped Status**

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/whatsapp/{{source}}/order-status/update' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer 90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk' \
--data '{
  "order_reference_id": "ORDER_1771417058_RTk0NjQA",
  "status": "shipped",
  "status_notes": "Thank you for your purchase"
}'
```

Response:

```
{
  "success": true,
  "message": "Order status updated successfully and notification sent",
  "data": {
    "status_update_id": 251,
  }
}
```

```
"order_reference_id": "ORDER_1767792952_RDc1NTgA",
"previous_status": "partially_shipped",
"current_status": "shipped",
"notification_sent": true
}
}
```

Note: source = Sender name / WABA Number

Note: Update status From shipped to cancelled or completed use below API

- **for Cancelled/Completed Status**

```
curl --location
'https://uber.cpaasplus.globeteleservices.com/api/whatsapp/{{source}}/order-
status/update' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk' \
--data '{
  "order_reference_id": "ORDER_1771417058_RTk0NjQA",
  "status": "completed or cancelled ",
  "status_notes": "Thank you for your purchase"
}'
```

Response:

```
{
  "success": true,
  "message": "Order status updated successfully and notification sent",
  "data": {
    "status_update_id": 62,
    "order_reference_id": "ORDER_1771417058_RTk0NjQA",
    "previous_status": "shipped",
    "current_status": "completed or cancelled ",
    "notification_sent": true
  }
}
```

Note: source = Sender name / WABA Number

Note: We cannot update the status in reverse and only can update status in cancelled or completed.

Sequence : processing >> partially_shipped>> shipped>> completed or cancelled

2.7 Order Refund API

```
curl --location
'https://uber.cpaasplus.globeteleservices.com/api/whatsapp/GTSadmin/payment/refund' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer {{token}}' \
--data '{
  "order_reference_id": "ORDER_1763043873_NzNCQjUA",
  "amount": 1.18,
  "speed": "normal or instant"
}'
```

Response:

```
{
  "success": true,
  "message": "Refund processed successfully. Status: completed",
  "data": {
    "refund_id": 25,
    "refund_status": null,
    "payment_transaction_id": 127,
    "order_reference_id": "ORDER_1772190979_MTg0QUUA",
    "refund_amount": "1.18",
    "currency": "INR"
  }
}
```

Note: Can Only refund cancelled orders, if order is other status received following response

```
{
  "success": false, "message": "Can only refund cancelled orders. Current status: shipped"
```

2.8 User Management API 's

- **Block users**

```
curl --location --globoff '
https://uber.cpaasplus.globeteleservices.com/api/whatsapp/blocked-members' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {{token}}' \
--data '{
  "sender_id": "{{WhatsApp business Number}}",
  "phone_numbers": ["91XXXXXXXXXX"]
}'
```

Response :

```
{
  "success": true,
  "message": "Blocked 1 users, 0 failed",
  "results": [
    {
      "phone_number": "91XXXXXXXXXX",
      "success": true,
      "message": "User blocked successfully"
    }
  ],
  "summary": {
    "total": 1,
    "success": 1,
    "failed": 0
  }
}
```

If user not interacted following response received

```
{
  "success": true,
  "message": "Blocked 1 users, 1 failed",
  "results": [
    {
      "phone_number": "91XXXXXXXXXX",
      "success": true,
      "message": "User blocked successfully"
    },
    {
      "phone_number": "919876543200",
      "success": false,
      "message": "Re-engagement check failed: Failed to block due to re-engagement check failed"
    }
  ],
}
```

```
"summary": {
  "total": 2,
  "success": 1,
  "failed": 1
}
```

Note : If you want to block the user that user should interacted with out system with in 24 hr through Campaign , chatbot.

Note : In array user can pass multiple number with comma separated.

For eg. {

```
"sender_id" : "919001926438",
```

```
"phone_numbers": ["91XXXXXXXXXX", "919876543200"]
```

```
}
```

- **Block users through CSV File**

```
curl --location --globoff ' https://uber.cpaasplus.globeteleservices.com
/api/whatsapp/blocked-members/import-csv' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {{token}}' \
--form 'sender_id="15557702525" \
--form 'csv_file="@postman-cloud:///1f08401e-14f4-4df0-8811-6787aa1bb297"' \
--form 'action="block"
```

Response:

```
{
  "success": true,
  "message": "Blocked 1 users, 2 failed",
  "results": [
    {
      "phone_number": "+91XXXXXXXXXX",
      "success": true,
      "message": "User blocked successfully"
    },
    {
      "phone_number": "+91XXXXXXXXXX",
      "success": false,
      "message": "Re-engagement check failed: Failed to block due to re-engagement check failed"
    },
    {
      "phone_number": "+91XXXXXXXXXX",
      "success": false,
```



```
"message": "Re-engagement check failed: Failed to block due to re-engagement check failed"
}
],
"summary": {
"total_processed": 3,
"file_format": "csv"
}
}
```

- **Get Block users**

```
curl --location --globoff --request GET ' https://uber.cpaasplus.globeteleservices.com
/api/whatsapp/blocked-members?sender_id=15557702525&per_page=1&page=1' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {{token}}' \
--data '{
  "sender_id": "{{WhatsApp Business Account Number}}"
}'
```

Response:

```
{
  "success": true,
  "data": [
    {
      "id": 59,
      "phone_number": "91XXXXXXXXXX",
      "is_blocked": true,
      "blocked_at": "Feb 27, 2026 16:52",
      "blocked_via": "api",
      "created_at": "Feb 27, 2026 11:22",
      "sender_name": "Cerf Telin",
      "waba_number": "919326997346"
    }
  ],
  "pagination": {
    "current_page": 1,
    "last_page": 1,
    "per_page": 15,
    "total": 1
  }
}
```

- **Sync Block users**

```
curl --location --globoff '
https://uber.cpaasplus.globeteleservices.com/api/whatsapp/blocked-members/sync' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {{token}}' \
```

```
--data '{
  "sender_id": "{{WhatsApp Business Account Number}}"
}'
```

Response:

```
{
  "success": true,
  "message": "Sync completed: 0 new, 0 updated, 0 deleted",
  "summary": {
    "new_blocked": 0,
    "updated": 0,
    "deleted": 0,
    "total_api_users": 1
  }
}
```

Note: Use above API to sync block numbers from meta.

- **Unblock Users**

```
curl --location --globoff --request DELETE '{{baseurl}}/api/whatsapp/blocked-members' \
\
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {{token}}' \
--data '{
  "sender_id": "{{WhatsApp Business Account Number}}",
  "phone_numbers": ["91XXXXXXXXXX","917002088560","8736830400"]
}'
```

Response:

```
{
  "success": true,
  "message": "Unblocked 2 users, 0 failed",
  "results": [
    {
      "phone_number": "91XXXXXXXXXX",
      "success": true,
      "message": "User unblocked successfully"
    },
    {
      "phone_number": "91XXXXXXXXXX",
      "success": true,
      "message": "User unblocked successfully"
    }
  ],
  "summary": {
    "total": 2,
  }
}
```

```
"success": 2,  
"failed": 0  
}  
}
```

RCS Channel API

The CPaaS+ RCS (Rich Communication Services) API lets you send rich, interactive messages with images, videos, carousels, and action buttons -delivered natively in the recipient's default messaging app. CPaaS+ supports RCS delivery via VI (Vodafone Idea) and JIO operator networks in India.

RCS API(s) Overview:

API	Endpoint (Path)	Best For
Template	/api/rcs/template/create	Getting Templates approved
Service Send	/api/rcs/send	Sending RCS messages via VI (Vodafone Idea) network
Status Check	/api/rcs/status	Checking delivery status of a sent RCS message

3.1 API Endpoint

POST : `{{Base URL}}/api/rcs/template/create`

Example: <https://uber.cpaasplus.globeteleservices.com/api/rcs/template/create>

3.2 Headers

Request Headers:

Key	Value
Content-Type	application/json
Accept	application/json
Authorization	Bearer <token>

3.3 Payload Field details

Param	Required	Description
name	Yes	Unique template name identifier. Use lowercase with underscores e.g. order_ready_v1
agent_id	Yes	RCS Agent ID from CPaaS+ Portal → RCS → Agents

type	Yes	Template type. Use: text_message
textMessageContent	Yes	The RCS message text body. Use {{variable}} for dynamic values
suggestions	Optional	Array of interactive button objects. Maximum 11 buttons
suggestions[].suggestionType	Yes	Button type: reply url_action dialer_action
suggestions[].displayText	Yes	Button label shown to recipient. Maximum 25 characters
suggestions[].postback	Optional	Value sent to webhook when user taps the button
suggestions[].url	Conditional	Required for url_action type. Target URL when button is tapped
suggestions[].phoneNumber	Conditional	Required for dialer_action type. Phone number
name	Yes	Unique template name identifier
agent_id	Yes	RCS Agent ID from CPaaS+ Portal → RCS → Agents
type	Yes	Template type. Use: rich_card
orientation	Yes	Card layout orientation: HORIZONTAL or VERTICAL
height	Conditional	Card height for Vertical layout: SHORT_HEIGHT MEDIUM_HEIGHT TALL_HEIGHT
width	Optional	Card width: SMALL_WIDTH or MEDIUM_WIDTH
carouselList	Yes	Array of card objects. Minimum 2 cards, Maximum 10 cards
carouselList[].cardTitle	Yes	Card title text. Maximum 200 characters
carouselList[].cardDescription	Optional	Card description text. Maximum 2000 characters
carouselList[].mediaUrl	Optional	Publicly accessible HTTPS image or video URL

carouselList[].suggestions	Optional	Array of button objects. Maximum 4 buttons per card
----------------------------	----------	---

3.4 Template creation Text Type with Buttons

Create an RCS text message template with optional interactive suggestion buttons. Supports Quick Reply, URL Action, and Dialer Action button types. Maximum 11 buttons per text message. Dynamic variables can be included using the {{variable}} format.

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/rcs/template/create' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
40|95Qp7T8TdfeSuElWX2PXz5WjkAFdmqDsXrXU2M2V1bd78ff2' \
--data '{
  "name": "test_template_002",
  "agent_id": "a00e741f-f0d9-4bb9-8e76-832f5cca28f8",
  "type": "text_message",
  "textMessageContent": "Hello {{name}}, your order {{order_id}} is ready for
pickup!",
  "suggestions": [
    {
      "suggestionType": "reply",
      "displayText": "Optout",
      "postback": "opt_out"
    },
    {
      "suggestionType": "url_action",
      "displayText": "View Details",
      "url": "https://example.com/order/{{order_id}}",
      "postback": "view_details"
    },
    {
      "suggestionType": "dialer_action",
      "displayText": "Call Support",
      "phoneNumber": "+91XXXXXXXXXX",
      "postback": "call_support"
    },
    {
      "suggestionType": "reply",
      "displayText": "Opt Out",
      "postback": "opt_out"
    }
  ]
}
```

```
}'
```

Response:

```
{
  "success": true,
  "message": "Template created successfully",
  "data": {
    "templateModel": {
      "id": "403a3f35-1066-481c-bbeb-1adc3b3c16d3",
      "tenant_id": "19f7f544-1dba-4349-98c9-a982eb9055bb",
      "agent_id": "a010585d-61d1-4533-87a5-901b01882218",
      "name": "tops4",
      "description": "Hire verified & professional drivers anytime, anywhere! Enjoy
safe, comfortable & hassle-free rides with 24/7 availability.",
      "category": null,
      "message_type": "text",
      "content_data": {
        "name": "tops4",
        "type": "text",
        "status": "active",
        "createdViaApi": true,
        "lastUpdate": "Apr 03,2026",
        "botId": "68ac0ec1ec220d7409d8670c",
        "textMessageContent": "Hire verified & professional drivers anytime,
anywhere! Enjoy safe, comfortable & hassle-free rides with 24/7 availability.",
        "suggestions": [
          {
            "suggestionType": "reply",
            "displayText": "Optout",
            "postback": "opt_out"
          },
          {
            "suggestionType": "url_action",
            "displayText": "View Details",
            "url": "https://example.com/order/{{order_id}}",
            "postback": "view_details"
          },
          {
            "suggestionType": "dialer_action",
            "displayText": "Call Support",
            "phoneNumber": "+91XXXXXXXXXX",
            "postback": "call_support"
          },
          {
            "suggestionType": "reply",
            "displayText": "Opt Out",
            "postback": "opt_out"
          }
        ]
      }
    }
  }
}
```



```
    }  
  ]  
},  
"variables": {  
  "list": "order_id"  
},  
"file_path": "[]",  
"status": "active",  
"is_public": false,  
"last_used_at": null,  
"created_at": "2026-04-03T10:37:54.000000Z",  
"updated_at": "2026-04-03T10:37:54.000000Z",  
"user_id": 1  
}  
}
```

3.5 Template Creation for Rich Card (Media with Buttons)

Create an RCS Rich Card template combining a media file (image or video) with a title, description, and up to 4 buttons. Supports Horizontal and Vertical layouts. Ideal for product showcases, offers, and visual notifications.

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/rcs/template/create' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
40|95Qp7T8TdfeSuElWX2PXz5WjkAFdmqDsXrXU2M2V1bd78ff2' \
--data '{
  "name": "test_video_2870",
  "agent_id": "a00e741f-f0d9-4bb9-8e76-832f5cca28f8",
  "type": "rich_card",
  "orientation": "VERTICAL",
  "height": "SHORT_HEIGHT",
  "standAlone": {
    "cardTitle": "Special Offer",
    "cardDescription": "Get 50% off on all products. Limited time offer! Use code
SAVE50 at checkout.",
    "mediaUrl": "https://user1.ecpaas.in/whatsapp_files/0d8297e8-8338-436e-a643-
e82dabda2b17.mp4",
    "suggestions": [
      {
        "suggestionType": "url_action",
        "displayText": "Shop Now",
        "url": "https://example.com/shop",
        "postback": "shop_now"
      },
      {
        "suggestionType": "reply",
        "displayText": "Learn More",
```

```

        "postback": "learn_more"
      },
      {
        "suggestionType": "reply",
        "displayText": "Opt Out",
        "postback": "opt_out"
      }, {
        "suggestionType": "reply",
        "displayText": "Learn More",
        "postback": "learn_more"
      }
    ]
  }
}'

```

Response:

```

{
  "success": true,
  "message": "Template created successfully",
  "data": {
    "templateModel": {
      "id": "b61a6464-b7b4-4a7d-93c2-539894385e42",
      "tenant_id": "19f7f544-1dba-4349-98c9-a982eb9055bb",
      "agent_id": "a010585d-61d1-4533-87a5-901b01882218",
      "name": "api26",
      "description": "",
      "category": null,
      "message_type": "rich_card",
      "content_data": {
        "name": "api26",

```

```

"type": "rich_card",
"status": "active",
"createdViaApi": true,
"lastUpdate": "Apr 03,2026",
"botId": "68ac0ec1ec220d7409d8670c",
"orientation": "VERTICAL",
"alignment": "LEFT",
"height": "SHORT_HEIGHT",
"standAlone": {
  "cardTitle": "MarchOFFER",
  "cardDescription": "Get 50% off on all products. Limited time offer! Use
code SAVE50 at checkout.",
  "mediaUrl": "https://user1.ecpaas.in/whatsapp_files/0d8297e8-8338-
436e-a643-e82dabda2b17.mp4",
  "suggestions": [
    {
      "suggestionType": "url_action",
      "displayText": "Shop Now",
      "url": "https://example.com/shop",
      "postback": "shop_now"
    },
    {
      "suggestionType": "reply",
      "displayText": "Learn More",
      "postback": "learn_more"
    },
    {
      "suggestionType": "reply",
      "displayText": "Opt Out",
      "postback": "opt_out"
    }
  ]
}

```

```
{
  "suggestionType": "reply",
  "displayText": "Learn More",
  "postback": "learn_more"
}
]
}
},
"variables": [],
"file_path": "[]",
"status": "active",
"is_public": false,
"last_used_at": null,
"created_at": "2026-04-03T10:48:14.000000Z",
"updated_at": "2026-04-03T10:48:14.000000Z",
"user_id": 1
}
```

3.6 Template Creation Card Carousel

Create a Carousel template with multiple horizontally scrollable cards. Each card can have its own image, title, description, and up to 4 buttons. Minimum 2 cards and maximum 10 cards per carousel.

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/rcs/template/create' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
40|95Qp7T8TdfeSuEIWX2PXz5WjkAFdmqDsXrXU2M2V1bd78ff2' \
--data '{
  "name": "carousel_2870",
  "agent_id": "a00e741f-f0d9-4bb9-8e76-832f5cca28f8",
  "type": "carousel",
  "width": "MEDIUM_WIDTH",
  "height": "MEDIUM_HEIGHT",
  "carouselList": [
    {
      "cardTitle": "Product 1",
      "cardDescription": "Amazing product with great features",
      "mediaUrl": "https://user1.ecpaas.in/whatsapp_files/0d8297e8-8338-436e-
a643-e82dabda2b17.mp4",
      "suggestions": [
        {
          "suggestionType": "url_action",
          "displayText": "Buy Now",
          "url": "https://example.com/product/1",
          "postback": "buy_now_1"
        },
        {
          "suggestionType": "reply",
          "displayText": "Details",
          "postback": "details_1"
        }
      ]
    },
    {
      "cardTitle": "Product 2",
      "cardDescription": "Another great product for you",
      "mediaUrl": "https://dummyimage.com/800x600/000/fff.png",
      "suggestions": [
        {
          "suggestionType": "url_action",
          "displayText": "Buy Now",
          "url": "https://example.com/product/2",
```

```

        "postback": "buy_now_2"
      },
      {
        "suggestionType": "reply",
        "displayText": "Details",
        "postback": "details_2"
      }
    ]
  }
}

```

Response:

```

{
  "success": true,
  "message": "Template created successfully",
  "data": {
    "templateModel": {
      "id": "9e8590cc-f2fa-47c4-9f21-240529cb11ca",
      "tenant_id": "19f7f544-1dba-4349-98c9-a982eb9055bb",
      "agent_id": "a010585d-61d1-4533-87a5-901b01882218",
      "name": "sg_2870",
      "description": "",
      "category": null,
      "message_type": "carousel",
      "content_data": {
        "name": "sg_2870",
        "type": "carousel",
        "status": "active",
        "createdViaApi": true,
        "lastUpdate": "Apr 03,2026",
        "botId": "68ac0ec1ec220d7409d8670c",
        "width": "MEDIUM_WIDTH",
        "height": "MEDIUM_HEIGHT",
        "carouselList": [
          {
            "cardTitle": "Productsg 1",
            "cardDescription": "Amazing product with great features",
            "mediaUrl": "https://user1.ecpaas.in/whatsapp_files/0d8297e8-8338-436e-a643-e82dabda2b17.mp4",
            "suggestions": [
              {
                "suggestionType": "url_action",
                "displayText": "Buy Now",
                "url": "https://example.com/product/1",
                "postback": "buy_now_1"
              }
            ]
          }
        ]
      }
    }
  }
}

```

```

        {
            "suggestionType": "reply",
            "displayText": "Details",
            "postback": "details_1"
        }
    ]
},
{
    "cardTitle": "Product 2",
    "cardDescription": "Another great product for you",
    "mediaUrl": "https://dummyimage.com/800x600/000/fff.png",
    "suggestions": [
        {
            "suggestionType": "url_action",
            "displayText": "Buy Now",
            "url": "https://example.com/product/2",
            "postback": "buy_now_2"
        },
        {
            "suggestionType": "reply",
            "displayText": "Details",
            "postback": "details_2"
        }
    ]
}
]
},
"variables": [],
"file_path": "[]",
"status": "active",
"is_public": false,
"last_used_at": null,
"created_at": "2026-04-03T10:51:34.000000Z",
"updated_at": "2026-04-03T10:51:34.000000Z",
"user_id": 1
}
}
}

```


3.7 Template Creation “text With Media” Type(only supported by Vi)

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/rcs/template/create' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
40|95Qp7T8TdfeSuElWX2PXz5WjkAFdmqDsXrXU2M2V1bd98ff2' \
--data '{
  "name": "test_text_medVi1",
  "agent_id": "a00e741f-f0d9-4bb9-8e76-832f5cca28f8",
  "type": "text_message_with_media",
  "message_content": "Check out our new catalog!",
  "documentUrl": "https://unec.edu.az/application/uploads/2014/12/pdf-sample.pdf",
  "messageOrder": "text_message_at_top",
  "suggestions": [
    {
      "suggestionType": "url_action",
      "displayText": "Download",
      "url": "https://example.com/download",
      "postback": "download"
    }
  ]
}
```

3.8 Service Send API Vi

Send an approved RCS message to a recipient via the API. Supports all RCS message types: plain text with buttons, rich card, and carousel. The structure of the content object must match the message type specified.

API ENDPOINT

POST: `{{Base URL}}/api/rcs/send`

Base URL: `https://uber.cpaasplus.globeteleservices.com/api/rcs/send`

Parameters

The required values need to be passed in the body of the request

Param	Required	Description
botId	Yes	RCS Bot/Agent ID registered on the VI network. Found in CPaaS+ Portal → RCS → Agents
to	Yes	Destination mobile number
message_type	Yes	Type of message: text_message rich_card carousel
content	Yes	Message content object. Structure varies based on message_type selected
text_message	textMessageContent (required), suggestions (optional -max 11 buttons)	Plain text with optional interactive buttons
rich_card	orientation, height, standAlone { cardTitle, mediaUrl, cardDescription, suggestions }	Single rich card with media. Max 4 buttons
carousel	width, height, carouselList [{ cardTitle, mediaUrl, cardDescription, suggestions }]	Multi-card carousel. Min 2 / Max 10 cards. Max 4 buttons per card
reply	Optional	Quick reply button -returns postback value to webhook on tap
url_action	Optional	Opens a URL in the browser when tapped

dialer_action	Optional	Initiates a phone call to the specified phoneNumber
calendar_event	Optional	Creates a calendar event on the recipient device
share_location	Optional	Prompts recipient to share their current location back to the bot
view_location_query	Optional	Opens map with a search query string
view_location_latlong	Optional	Opens map at specified latitude and longitude coordinates

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/rcs/send' \
--header 'Accept : application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
176|04FwCPE4ZHaXyCiYIOCGQDQoYHAtyBd6XAIIm8F3nc187655e1' \
--data ' {
  "agent_id": "a010585d-61d1-4533-87a5-901b01882218",
  "to": ["91XXXXXXXXXX"],
  "message_type": "text",
  "content": {
    "name": "tops4",
    "type": "text_message",
    "botId": "{{BOT ID}}",
    "suggestions": [
      {
        "postback": "{{Value}}",
        "displayText": "{{Button Name}}",
        "suggestionId": "{{Button ID}}",
        "suggestionType": "{{Button Type}}"
      }
    ],
    "textMessageContent": "{{Message Text}}"
  }
}
```

3.9 Service Send API -JIO

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/rcs/send' \
--header 'Accept : application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
167|JscXBWx8YvqGiVwK1dsjJxwIXn3pMZnuZljpvrvyff0fe46c' \
--data '{
  "agent_id": "a010585d-61d1-4533-87a5-901b01882218",
  "to": [
    "91XXXXXXXXXX"
  ],
  "message_type": "text",
  "content": {
    "textMessageContent": "Hello please update the plan Regards, Sanjay"
  }
}'
Response:
{
  "status": "success",
  "message": "Messages submitted successfully.",
  "data": [
    {
      "status": "submitted",
      "message_id": "a1748193-c600-443a-858e-9db0ea906a7b",
      "number": "91XXXXXXXXXX",
      "provider": "jio",
      "received_at": "2026-04-03 17:30:22"
    }
  ]
}
```

3.10 STATUS CHECK API

Check the delivery status of a previously sent RCS message using the message_id returned from the VI or JIO Service Send API.

API ENDPOINT

POST: `{{Base URL}}/api/rcs/status`

Base URL: `https://uber.cpaasplus.globeteleservices.com/api/rcs/status`

PARAMETERS

Param	Required	Description
id	Yes	The unique message_id returned in the RCS Service Send API response

```
curl --location
'https://uber.cpaasplus.globeteleservices.com/api/rcs/status?id=a1748193-c600-443a-858e-9db0ea906a7b' \
--header 'Accept : application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
176|04FwCPE4ZHaXyCiYIOCGQDQoYHAtyBd6XAIm8F3nc18085e1' \
```

Response:

```
{
  "success": true,
  "data": {
    "message_id": "a1748193-c600-443a-858e-9db0ea906a7b",
    "status": "read",
    "status_description": "Unknown status",
    "message_type": "text",
    "priority": null,
    "direction": "outbound",
    "number": "91XXXXXXXXXX",
    "created_at": "2026-04-03 17:30:22",
    "scheduled_at": "2026-04-03 17:30:22",
    "sent_at": "2026-04-03 17:30:23",
    "delivered_at": "2026-04-03 17:30:27",
    "failed_at": null,
    "cancelled_at": null,
    "updated_at": "2026-04-03 17:30:46"
  }
}
```

Email Channel API

The CPaaS+ Email API enables you to send transactional, promotional, and OTP emails programmatically. Supports template-based sends with dynamic variables, open-text emails with HTML content, file attachments, delivery status tracking, and a complete OTP generation and verification flow.

Email API(s) Overview:

API	Endpoint (Path)	Best For
Template Send	/api/email/template/send	Sending pre-built email templates with dynamic variables
Open Text	/api/email/send	Sending custom HTML/text emails without a template
Status Check	/api/email/status	Checking delivery status of a sent email

4.1 API Endpoint:

POST: `{{BaseURL}}/api/email/template/send`

Example: `https://abcd.cpaasplus.com /api/email/template/send`

4.2 Required Headers:

Key	Value
Accept	application/json
Content-Type	application/json
Authorization	Bearer <your_token>

4.3 Payload Fields Details:

Field	Required	Description
service_name	Yes	Email service identifier (must exist in email_services.name)
template_name	Yes	Email template name (must exist in email_templates.name)
from	No	Sender's email address
from_name	No	Name displayed as sender [open text]
to	Yes	Recipient's email address
cc	No	List of email addresses to CC
bcc	No	List of email addresses to BCC
subject	Yes	Subject line of the email
params	No	Variable value in the template
attachments	No	Files to attach to the email
filename	Yes [if use attachment field]	Display name of the file [open text]

type	Yes [if use attachment field]	Type of attachment
content	Yes [if use attachment field]	Attachment content in Base64-encoded format
Response status	Yes	Overall request submission status success/error
message	Yes	Confirmation message from platform (OTP sent successfully).
unique_id	Yes	Session identifier -MUST be stored and passed to OTP Verification API

4.4 Template Email API

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/email/template/send' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
87|90qv8qRSLTtxV9Yqh9ekaS6b54iEm5e8KDvoIOs57055a9ca' \
--data-raw '{
  "service_name": "TESTMAIL",
  "template_name": "Simple template",
  "from": "no-reply@yourdomain.com",
  "from_name": "API TEST",
  "to": "john.doe@yourdomain.com",
  "cc": [
    "sam.mail1@gmail.com",
    "cathy.mail2@gmail.com"
  ],
  "bcc": [
    "oliver.mail1@gmail.com",
    "maxus.mail2@gmail.com"
  ],
  "subject": " Email with template API ",
  "params": [
    "Variable_1",
    "Variable_1"
  ],
  "attachments": [
    {
      "filename": "Test Doc",
      "type": "application/pdf",
      "content": "{{attachmentcontent}}"
    }
  ]
}'
```


Note:

In the attachments, the **content** field should have the file in **Base64 format**. Make sure the file is properly converted; otherwise, the receiver may get a broken or unreadable file

Response:

```
{  
  "status": "Accepted",  
  "message_id": "5ea6cd6c-aced-4ea9-a5c5-4ff277dffe2a",  
  "timestamp": "2025-07-28 18:19:18"  
}
```

```
{  
  "status": false,  
  "message": "Invalid JSON: Syntax error"  
}
```

4.5 Open text Email API

```
curl --location 'https://uber.cpaasplus.globeteleservices.com/api/email/send' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk' \
--data-raw '{
  "account": "TESTMAIL",
  "from": "no-reply@yourdomain.com",
  "from_name": "testqa",
  "to": "john.doe@yourdomain.com",
  "cc": [
    "sam.mail1@gmail.com",
    "cathy.mail2@gmail.com"
  ],
  "bcc": [
    "oliver.mail1@gmail.com",
    "maxus.mail2@gmail.com"
  ],
  "subject": "open text",
  "body": "This is test mail",
  "attachments": [
    {
      "filename": "Test Doc",
      "type": "application/pdf",
      "content": "{{attachmentcontent}}"
    }
  ]
}'
```

Response:

```
{
  "status": "Accepted",
  "hash": "60ce5ed8-0d8f-4142-bbf9-77cf6d655350",
  "timestamp": "2026-02-27 17:28:25"
}
```

4.6 Status Check API

POST: `{{Base URL}}/api/email/status`

Base URL: `https://uber.cpaasplus.globeteleservices.com` (This will be the Host of your Web Portal Account)

Check the delivery status of a previously sent email message using the message_id returned from the send API.

```
curl --location --request GET
'https://uber.cpaasplus.globeteleservices.com/api/email/status' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
90|YWhdfjdshf873111889hsBDCBJ724kmbads0111QtwqrHZk' \
--data '{
  "id" : "f4e6409f-a5a0-4a4c-9952-b57d801bd98b"
}'
```

Response:

```
{
  "message_id": "3f70a02c-305e-4a95-b389-9c4640741684",
  "status": "delivered",
  "timeline": {
    "queued_at": "2026-02-27T12:00:09.000000Z",
    "sent_at": "2026-02-27T12:00:09.000000Z",
    "delivered_at": "2026-02-27T12:00:11.000000Z",
    "opened_at": null,
    "clicked_at": null,
    "bounced_at": null,
    "failed_at": null,
    "unsubscribed_at": null,
    "complained_at": null
  },
  "recipient": "'oliver.mail_1@gmail.com'",
  "subject": "Post deployment 18/2/2026",
  "details": {
    "open_count": 0,
    "click_count": 0
  }
}
```

4.7 Common error Responses

HTTP Code	Meaning	Possible Cause
400	Bad Request	Invalid JSON, missing fields
401	Unauthorized	Invalid/missing token
422	Unprocessable Entity	Invalid numbers/field or message content
500	Internal Server Error	Server-side issue

Flow builder API

The CPaaS+ Flow Builder API lets you programmatically trigger automated omnichannel customer journeys designed in the CPaaS+ Flow Builder visual editor. A single API call can initiate a multi-step flow spanning SMS, WhatsApp, Email, and RCS -with dynamic variable values injected at runtime.

Flow Builder API Overview:

API	Endpoint (Path)	Best For
Message Send API	<code>{{Flow Webhook URL}}</code>	Trigger a published CPaaS+ flow to a specific recipient

5.1 API Endpoint

POST : `https://{{api.yourcpaas.com}}/flow-api/webhook/trigger/{{flow_id}}`

Trigger a published CPaaS+ automated flow for a specific recipient. Pass the recipient's phone number and/or email address along with any dynamic variable values required by the flow. The flow then executes all configured steps automatically sending messages, applying conditions, and managing delays as defined in the Flow Builder.

Note: The Base URL for the Flow Builder API is the unique Webhook URL of the specific flow. It is generated when you publish a flow in CPaaS+ Portal → Flow Builder → Your Flow → Webhook URL.

5.2 Headers

Key	Value
Accept	application/json
Content-Type	application/json
Authorization	Bearer <your_token>

Note: The Base URL for the Flow Builder API is the unique Webhook URL of the specific flow. It is generated when you publish a flow in CPaaS+ Portal → Flow Builder → Your Flow → Webhook URL.

5.3 Request Body Parameters

Field Name	Required	Description
phone	Conditional	Recipient mobile number Required if flow uses SMS or WhatsApp channel
email	Conditional	Recipient email address. Required if flow uses Email channel
var1	Optional	Dynamic variable 1 injected into the flow at runtime e.g. customer name, order ID
var2	Optional	Dynamic variable 2 injected into the flow at runtime e.g. OTP, amount, date

var3	Optional	Dynamic variable 3 injected into the flow at runtime e.g. product name, status
var4	Optional	Dynamic variable 4 injected into the flow at runtime e.g. tracking link, reference number
email	Conditional	Recipient email address. Required if flow uses Email channel
var1	Optional	Dynamic variable 1 injected into the flow at runtime e.g. customer name, order ID

Request:

```
curl --location --request GET 'https://uber.cpaasplus.globeteleservices.com/flow-
api/webhook/trigger/7c258d59-dfc8-4469-85df-666694b94722' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer
151|q2lhA0COYBsSbQ6foJPYuoyEnWRGameATyZyCBL9451fcde1' \
--data '{
  "phone": "91XXXXXXXXXX",
  "email": "test@dumymail.com",
  "var1": "var1",
  "var2": "var2",
  "var3": "var3",
  "var4": "var4"
}'
```

Response:

```
{
  "status": "success",
  "message": "Flow jobs dispatched successfully"
}
```