Simplified GDPR Consent Manager

Unit Test Report

Automated unit and integration tests - server (Jest + Supertest) and client (Vitest + React Testing Library)

#	Name	SRN
1	SUMAN DIDDIMANI	PES1UG24AM409
2	PRADEEP T	PES1UG24AM385
3	VILAS	PES1UG24AM415
4	PRANAAV PRABHAKARAN	PES1UG24AM387

Version	Date	Author	Change Summary
1.0	03-11-2026	Team 6	Report generated from the executed test run (Sprint 3 testing, issue #25)

1. Summary

All automated tests were executed on 03-11-2026 from the main branch (Node 20; database calls replaced by in-memory Prisma test doubles, so the tests need no database). The same commands run in GitHub Actions on every pull request (workflow ci.yml), so a red build blocks merging.

Part	Framework	Test files	Tests	Passed	Failed	Time (s)
Server API	Jest 29 + Supertest	17	172	172	0	19.7
Client UI	Vitest 2 + React Testing Library	8	53	53	0	19.2
Total		25	225	225	0	

Result: 225 of 225 tests passed (100 %).

2. How to reproduce

- npm ci
- npm run db:generate -w server
- npm test -w server (or: npm run test:coverage -w server)
- npm test -w client
- JUnit XML reports were produced with jest-junit and Vitest's junit reporter; raw files are in docs/07-Test-Reports/raw/.

3. Server test suites

Test file	Suite	Tests	Passed	Time (s)
middleware/security.test.ts	CSRF origin check (SEC-7)	12	12	9.00
modules/policies/policies.test.ts	POST /api/v1/policies (FR-13)	16	16	0.96
modules/auth/auth.test.ts	POST /api/v1/auth/register (FR-1, SEC-1)	24	24	1.23
modules/query/query.test.ts	GET /api/v1/consents (FR-18)	14	14	1.50
lib/staticClient.test.ts	serveClient (#18)	3	3	0.41

Test file	Suite	Tests	Passed	Time (s)
modules/consents/consents.test.ts	POST /api/v1/me/consents (FR-7, FR-8, FR-9)	17	17	0.79
modules/purposes/purposes.test.ts	GET /api/v1/purposes (FR-4)	13	13	0.65
modules/audit/integrity.test.ts	verifyIntegrity (#27)	8	8	0.62
modules/notices/notices.test.ts	notices on publish (FR-16)	9	9	0.59
scripts/backup.test.ts	backup (#29)	9	9	0.11
modules/users/admin.test.ts	GET /api/v1/users (SEC-4)	9	9	0.63
modules/users/timeTravel.test.ts	consent state at a past moment (FR-20, #16)	8	8	0.58
app.test.ts	GET /api/v1/health	4	4	0.68
middleware/requireRole.test.ts	requireRole (SEC-2)	9	9	0.64
scripts/seed.test.ts	seed (#10)	3	3	0.12
modules/audit/audit.service.test.ts	canonicalJson	6	6	0.29
lib/emailCrypto.test.ts	e-mail encryption (NFR-10)	8	8	0.11

4. Client test suites

Test file	Suite	Tests	Passed	Time (s)
App.test.tsx	-	3	3	0.20
auth/auth.test.tsx	-	10	10	0.83
components/PolicyNoticeBanner.test.tsx	-	4	4	0.40
pages/AdminUsersPage.test.tsx	-	6	6	0.69
pages/DashboardPage.test.tsx	-	5	5	0.77
pages/DpoConsolePage.test.tsx	-	13	13	1.36
pages/HistoryPage.test.tsx	-	4	4	0.33
pages/policies.test.tsx	-	8	8	0.69

5. Test case list

Every automated test, grouped by file. ✓ = passed.

src/middleware/security.test.ts

Test	ms	
CSRF origin check (SEC-7) blocks a state-changing request coming from another website	108	✓
CSRF origin check (SEC-7) blocks it when only the Referer shows another site	24	✓
CSRF origin check (SEC-7) allows requests from our own front end	24	✓
CSRF origin check (SEC-7) allows same-host requests (front end served by the API in production)	14	✓
CSRF origin check (SEC-7) never blocks read-only requests	22	✓
CSRF origin check (SEC-7) blocks the opaque 'null' origin used by sandboxed attack pages	17	✓
rate limit on login/register (SEC-7, brute force) returns 429 after the limit is reached	442	✓
HTTPS redirect (SEC-5) is off outside production	4	✓
HTTPS redirect (SEC-5) redirects plain HTTP to HTTPS in production	21	✓
other OWASP basics (SEC-7) rejects malformed input before it reaches the database	7	✓
other OWASP basics (SEC-7) sends a Content-Security-Policy and HSTS header	5	✓
other OWASP basics (SEC-7) a custom origin can be configured	5	✓

src/modules/policies/policies.test.ts

Test	ms	
POST /api/v1/policies (FR-13) an ADMIN creates a DRAFT and is recorded as its author	15	✓
POST /api/v1/policies (FR-13) USER and DPO get 403	9	✓
POST /api/v1/policies (FR-13) a duplicate version number gets 409 POLICY_VERSION_TAKEN	8	✓
POST /api/v1/policies (FR-13) validates the input	5	✓
PATCH /api/v1/policies/:id (FR-13, FR-15) a draft can be edited	8	✓
PATCH /api/v1/policies/:id (FR-13, FR-15) a published version is locked: 409 POLICY_LOCKED and the text is unchanged	36	✓
POST /api/v1/policies/:id/publish (FR-14) publishing sets PUBLISHED and the effective date	9	✓
POST /api/v1/policies/:id/publish (FR-14) publishing a new version supersedes the old one, so only one is published	14	✓
POST /api/v1/policies/:id/publish (FR-14) an already published version cannot be published again	12	✓
POST /api/v1/policies/:id/publish (FR-14) a USER cannot publish; an unknown id gets 404	9	✓
reading policies (FR-5) GET /current returns 404 before anything is published	3	✓
reading policies (FR-5) GET /current returns the published version to any logged-in user	9	✓
reading policies (FR-5) GET /policies (all versions) is for ADMIN and DPO only, newest first	11	✓
reading policies (FR-5) GET /:id returns a published version to a logged-in user; needs login	11	✓
reading policies (FR-5) GET /:id hides a DRAFT from a USER (404) but shows it to ADMIN and DPO (FR-13)	17	✓
audit trail (FR-17) creating, editing and publishing are audited with the admin as actor	18	✓

src/modules/auth/auth.test.ts

Test	ms	
POST /api/v1/auth/register (FR-1, SEC-1) creates a USER account, logs it in and never returns the password hash	36	✓
POST /api/v1/auth/register (FR-1, SEC-1) stores only a bcrypt hash, not the password	7	✓
POST /api/v1/auth/register (FR-1, SEC-1) ignores a role sent by the client	6	✓
POST /api/v1/auth/register (FR-1, SEC-1) rejects a duplicate e-mail (case-insensitive) with 409	8	✓
POST /api/v1/auth/register (FR-1, SEC-1) rejects a short password and a bad e-mail with 400	3	✓
POST /api/v1/auth/login (FR-2) logs in with the right password and returns the role	10	✓

Test	ms	
POST /api/v1/auth/login (FR-2) returns the same 401 for a wrong password	10	✓
POST /api/v1/auth/login (FR-2) returns the same 401 for a unknown e-mail	89	✓
POST /api/v1/auth/login (FR-2) refuses a deactivated account	10	✓
GET /api/v1/auth/me and POST /api/v1/auth/logout (FR-3) returns 401 without a session	3	✓
GET /api/v1/auth/me and POST /api/v1/auth/logout (FR-3) returns 401 for a forged token	3	✓
GET /api/v1/auth/me and POST /api/v1/auth/logout (FR-3) returns the user with a valid session	8	✓
GET /api/v1/auth/me and POST /api/v1/auth/logout (FR-3) after logout the OLD cookie no longer works, even if someone kept a copy	9	✓
GET /api/v1/auth/me and POST /api/v1/auth/logout (FR-3) logout without a session is harmless	2	✓
account lockout (SEC-3) locks the account after 5 wrong passwords; the 6th attempt is refused even with the right password	34	✓
account lockout (SEC-3) allows login again once the 15 minutes have passed	34	✓
account lockout (SEC-3) a successful login resets the failure counter	49	✓
session expiry (SEC-3) rejects a token that has expired	9	✓
audit trail (FR-17) records registration, successful and failed logins, lockout and logout	33	✓
audit trail (FR-17) never writes the e-mail address or password into the audit trail (NFR-9)	116	✓
e-mail encryption at rest (NFR-10, #28) stores the e-mail encrypted with a lookup hash, but returns it in plain text	8	✓
e-mail encryption at rest (NFR-10, #28) logs in with the e-mail in any letter case	16	✓
e-mail encryption at rest (NFR-10, #28) an old account with a plain e-mail still logs in and is converted on the way	12	✓
e-mail encryption at rest (NFR-10, #28) the same address cannot be registered twice, whatever the letter case	13	✓

src/modules/query/query.test.ts

Test	ms	
GET /api/v1/consents (FR-18) returns the newest records first with user, purpose and policy version	10	✓
GET /api/v1/consents (FR-18) pages through the results	6	✓
GET /api/v1/consents (FR-18) rejects a page size above 100	5	✓
GET /api/v1/consents (FR-18) is for DPO and ADMIN only	11	✓
GET /api/v1/audit (FR-17, FR-18) lists audit entries newest first, including anonymous failures	5	✓
GET /api/v1/audit (FR-17, FR-18) is read-only: there is no route to change or delete entries	10	✓
GET /api/v1/audit (FR-17, FR-18) a USER cannot read the audit trail	4	✓
search and filter (FR-19, #26) passes every consent filter to the database query	5	✓
search and filter (FR-19, #26) a date-only 'to' includes that whole day; a full time is used as given	1	✓
search and filter (FR-19, #26) empty filters are ignored	1	✓
search and filter (FR-19, #26) filters the audit trail by actor, action, outcome and dates	4	✓
search and filter (FR-19, #26) rejects invalid filter values with 400	10	✓
search and filter (FR-19, #26) injection-looking text is only ever used as a search value (SEC-7)	5	✓
search and filter (FR-19, #26) a full e-mail address is searched through its lookup hash (e-mails are encrypted, NFR-10)	5	✓

src/lib/staticClient.test.ts

Test	ms	
serveClient (#18) in production: serves files, and index.html for app routes like /dashboard	121	✓
serveClient (#18) does nothing in development (Vite serves the app there)	46	✓
serveClient (#18) does nothing when the app was not built	59	✓

src/modules/consents/consents.test.ts

Test	ms	
POST /api/v1/me/consents (FR-7, FR-8, FR-9) grants consent and records the current policy version and time	11	✓

Test	ms	
POST /api/v1/me/consents (FR-7, FR-8, FR-9) withdrawing adds a NEW record; the grant is kept (append-only, FR-11)	7	✓
POST /api/v1/me/consents (FR-7, FR-8, FR-9) granting twice gets 409 CONSENT_UNCHANGED	7	✓
POST /api/v1/me/consents (FR-7, FR-8, FR-9) withdrawing something never granted gets 409	3	✓
POST /api/v1/me/consents (FR-7, FR-8, FR-9) rejects an invalid action or purpose id with 400 (FR-9)	7	✓
POST /api/v1/me/consents (FR-7, FR-8, FR-9) unknown purpose 404, inactive purpose 409	10	✓
POST /api/v1/me/consents (FR-7, FR-8, FR-9) refuses consent while no policy is published	5	✓
POST /api/v1/me/consents (FR-7, FR-8, FR-9) needs a USER login: 401 without, 403 for an ADMIN	5	✓
hash chain and audit (FR-10, FR-11, SEC-6) each record points to the hash of the previous one, starting from genesis	8	✓
hash chain and audit (FR-10, FR-11, SEC-6) writes an audit entry for every decision, in the same transaction	6	✓
hash chain and audit (FR-10, FR-11, SEC-6) if the audit entry fails, the request fails (nothing half-saved is reported as success)	13	✓
GET /api/v1/me/consents (FR-4) shows every active purpose; nothing is pre-ticked	16	✓
GET /api/v1/me/consents (FR-4) shows the latest decision per purpose, only for the logged-in user	19	✓
GET /api/v1/me/consents/history (FR-12) lists every decision newest first, with purpose and policy version	10	✓
GET /api/v1/me/consents/history (FR-12) shows only the logged-in user's own records	4	✓
GET /api/v1/me/consents/history (FR-12) respects ?limit and rejects a bad one	10	✓
GET /api/v1/me/consents/history (FR-12) needs a USER login	4	✓

src/modules/purposes/purposes.test.ts

Test	ms	
GET /api/v1/purposes (FR-4) needs a login	15	✓
GET /api/v1/purposes (FR-4) lists only active purposes, sorted by name	14	✓
GET /api/v1/purposes (FR-4) ?all=true shows deactivated purposes to an ADMIN but not to a USER	8	✓
POST /api/v1/purposes (FR-6) an ADMIN can create a purpose; the code is stored in capitals	5	✓
POST /api/v1/purposes (FR-6) a USER gets 403	3	✓
POST /api/v1/purposes (FR-6) the same code twice gets 409 PURPOSE_CODE_TAKEN	6	✓
POST /api/v1/purposes (FR-6) rejects a bad code and missing fields with 400	4	✓
PATCH /api/v1/purposes/:id and /deactivate (FR-6) an ADMIN can rename a purpose but not change its code	6	✓
PATCH /api/v1/purposes/:id and /deactivate (FR-6) an empty update gets 400	5	✓
PATCH /api/v1/purposes/:id and /deactivate (FR-6) an unknown id gets 404, a malformed id gets 400	5	✓
PATCH /api/v1/purposes/:id and /deactivate (FR-6) deactivating hides the purpose from users but keeps it in the database	8	✓
PATCH /api/v1/purposes/:id and /deactivate (FR-6) a USER cannot edit or deactivate	7	✓
audit trail (FR-17) every admin change writes an audit entry with the admin as actor	7	✓

src/modules/audit/integrity.test.ts

Test	ms	
verifyIntegrity (#27) reports both chains intact, across more than one batch	92	✓
verifyIntegrity (#27) an empty database is fine	0	✓
verifyIntegrity (#27) detects a changed audit entry (someone edited the action in the database)	2	✓
verifyIntegrity (#27) detects a changed consent decision	1	✓
verifyIntegrity (#27) detects a deleted row (the next row no longer links back)	1	✓
verifyIntegrity (#27) detects a row whose hash was recomputed to hide a change	1	✓
GET /api/v1/audit/verify (#27) returns the report and logs that a check was made	7	✓
GET /api/v1/audit/verify (#27) needs DPO or ADMIN	3	✓

src/modules/notices/notices.test.ts

Test	ms	
notices on publish (FR-16) notifies only users with a current grant under an older version	1	✓
notices on publish (FR-16) publishing does not change any existing consent record	0	✓
notices on publish (FR-16) does not create the same notice twice	1	✓
GET /api/v1/me/notices shows the new version and the purposes to review	7	✓
GET /api/v1/me/notices a user without affected consents has no notice	6	✓
POST /api/v1/me/notices/:id/reconfirm adds a new GRANTED record under v2 for each affected purpose and closes the notice	9	✓
POST /api/v1/me/notices/:id/reconfirm cannot answer the same notice twice, or someone else's notice	12	✓
POST /api/v1/me/notices/:id/ack closes the notice without new consent records	4	✓
POST /api/v1/me/notices/:id/ack needs a USER login and a valid id	11	✓

src/scripts/backup.test.ts

Test	ms	
backup (#29) exports every table with row counts and turns BigInt ids into text	2	✓
backup (#29) names files by UTC time, safe for Windows	1	✓
restore (#29) restores into an empty database in foreign-key order and resets the id sequences	3	✓
restore (#29) keeps ids, hashes and dates exactly (so the hash chains stay valid)	1	✓
restore (#29) refuses to restore over existing data	14	✓
restore (#29) rejects files that are not our backups	2	✓
restore (#29) revive leaves unknown fields untouched	1	✓
retention (NFR-8) defaults to 3 years	0	✓
retention (NFR-8) records inside the period are protected, older ones are not	1	✓

src/modules/users/admin.test.ts

Test	ms	
GET /api/v1/users (SEC-4) lists users for an admin, without password hashes	8	✓
GET /api/v1/users (SEC-4) searches by name/e-mail and filters by role	12	✓
GET /api/v1/users (SEC-4) is refused for USER and DPO	7	✓
PATCH /api/v1/users/:id/role (SEC-4) changes the role, ends the user's sessions and audits the change	12	✓
PATCH /api/v1/users/:id/role (SEC-4) an admin cannot change his own role	4	✓
PATCH /api/v1/users/:id/role (SEC-4) rejects unknown roles and users; non-admins are refused	11	✓
PATCH /api/v1/users/:id/role (SEC-4) setting the same role again changes nothing and is not audited	4	✓
deactivate / activate (SEC-4) deactivating blocks the account at once; activating restores it	10	✓
deactivate / activate (SEC-4) an admin cannot deactivate himself	3	✓

src/modules/users/timeTravel.test.ts

Test	ms	
consent state at a past moment (FR-20, #16) before any decision: nothing was given, policy 1.0 was in force	8	✓
consent state at a past moment (FR-20, #16) on 15 Oct: both granted under v1.0	4	✓
consent state at a past moment (FR-20, #16) on 21 Oct: policy 2.0 is in force but the old consents still stand	5	✓
consent state at a past moment (FR-20, #16) exactly at the withdrawal instant the withdrawal counts ('at or before')	7	✓
consent state at a past moment (FR-20, #16) includes purposes deactivated later, but not ones created later	6	✓
consent state at a past moment (FR-20, #16) logs that the DPO looked at the user's data	6	✓
consent state at a past moment (FR-20, #16) rejects future and invalid moments, unknown users, and non-DPO callers	16	✓

Test	ms	
GET /api/v1/users/lookup finds a user by e-mail (case-insensitive) or says 404	12	✓

src/app.test.ts

Test	ms	
GET /api/v1/health returns 200 and db=up when the database answers	35	✓
GET /api/v1/health returns 503 and db=down when the database is unreachable	9	✓
security basics sets security headers and hides the framework	8	✓
security basics returns the standard JSON error for unknown routes	24	✓

src/middleware/requireRole.test.ts

Test	ms	
requireRole (SEC-2) 401 when nobody is logged in	9	✓
requireRole (SEC-2) 403 FORBIDDEN for a USER on an admin route	5	✓
requireRole (SEC-2) lets an ADMIN through	4	✓
requireRole (SEC-2) accepts any of several roles	10	✓
requireRole (SEC-2) refuses to be created without roles	15	✓
requireSelfOrRole (SEC-2: a user sees only his or her own data) a USER can open their own data	4	✓
requireSelfOrRole (SEC-2: a user sees only his or her own data) a USER cannot open someone else's data	3	✓
requireSelfOrRole (SEC-2: a user sees only his or her own data) DPO and ADMIN can open anyone's data	6	✓
denied access is audited (SEC-2, FR-17) writes an ACCESS_DENIED entry	6	✓

src/scripts/seed.test.ts

Test	ms	
seed (#10) creates 3 demo users with hashed passwords, 4 purposes and a published policy 1.0	30	✓
seed (#10) running it a second time adds nothing	9	✓
seed (#10) does not add a policy when one already exists	5	✓

src/modules/audit/audit.service.test.ts

Test	ms	
canonicalJson gives the same text whatever the key order	2	✓
canonicalJson writes dates as ISO strings	0	✓
appendAudit the first entry points to the genesis hash	1	✓
appendAudit each entry points to the hash of the one before (a chain)	1	✓
appendAudit takes the chain lock before reading the last entry	1	✓
appendAudit the stored hash can be recomputed, and any change to the entry is detected	1	✓

src/lib/emailCrypto.test.ts

Test	ms	
e-mail encryption (NFR-10) round-trips, and the stored text does not reveal the address	2	✓
e-mail encryption (NFR-10) encrypting the same address twice gives different text (random IV)	1	✓
e-mail encryption (NFR-10) the lookup hash is the same for the same address in any case, and different for others	1	✓
e-mail encryption (NFR-10) a changed ciphertext is rejected (AES-GCM authentication)	12	✓

Test	ms	
e-mail encryption (NFR-10) plain e-mails from before encryption are returned as they are	1	✓
e-mail encryption (NFR-10) uses EMAIL_ENCRYPTION_KEY when set: data encrypted with one key cannot be read with another	11	✓
log redaction (NFR-9) never writes passwords, e-mails, tokens or cookies to the log	13	✓
UTC timestamps (NFR-13) times are sent as UTC ISO strings ending in Z	1	✓

src/App.test.tsx

Test	ms	
App > renders the home page with the main heading	139	✓
App > shows live API status once the health check returns	41	✓
App > renders the not-found page for unknown routes	21	✓

src/auth/auth.test.tsx

Test	ms	
login (FR-2) > a USER lands on the consent dashboard	234	✓
login (FR-2) > an ADMIN lands on the admin console	105	✓
login (FR-2) > shows the server's message for wrong credentials or a locked account	93	✓
login (FR-2) > asks for both fields before calling the API	44	✓
register (FR-1) > validates the form like the API does	2	✓
register (FR-1) > creates the account and opens the dashboard	138	✓
register (FR-1) > shows 'e-mail already used' from the API	68	✓
protected pages and logout (FR-3) > sends a visitor who is not logged in to the login page	29	✓
protected pages and logout (FR-3) > sends a USER away from the admin console to their own dashboard	30	✓
protected pages and logout (FR-3) > logging out ends the session and returns to the login page	86	✓

src/components/PolicyNoticeBanner.test.tsx

Test	ms	
policy-change notice (#20) > tells the user what changed and which consents were given under the old version	170	✓
policy-change notice (#20) > 'Keep my choices' re-confirms and refreshes the cards	103	✓
policy-change notice (#20) > 'I've reviewed them' closes the notice	77	✓
policy-change notice (#20) > shows nothing when there is no notice	45	✓

src/pages/AdminUsersPage.test.tsx

Test	ms	
Admin: users and roles (#23) > lists users; the admin's own row cannot be changed	259	✓
Admin: users and roles (#23) > changing a role calls the API and shows a confirmation	118	✓
Admin: users and roles (#23) > deactivates an account	128	✓
Admin: users and roles (#23) > searches	93	✓
Admin: users and roles (#23) > the admin tabs link Policies and Users	55	✓
Admin: users and roles (#23) > a DPO cannot open it	34	✓

src/pages/DashboardPage.test.tsx

Test	ms	
Consent Dashboard (#9) > shows one card per purpose; nothing is pre-ticked	390	✓
Consent Dashboard (#9) > Grant calls the API and the card turns to Granted	130	✓
Consent Dashboard (#9) > Withdraw sends WITHDRAWN	63	✓
Consent Dashboard (#9) > shows the API error if saving fails	83	✓
Consent Dashboard (#9) > disables the buttons while no policy is published	96	✓

src/pages/DpoConsolePage.test.tsx

Test	ms	
DPO console (#22) > shows consent records with user, purpose, decision and policy version	306	✓
DPO console (#22) > pages forward	165	✓
DPO console (#22) > switches to the audit trail tab	104	✓
DPO console (#22) > has no edit or delete controls (read-only)	61	✓
DPO console (#22) > a USER is sent away from the DPO console	18	✓
search and filter (#26, FR-19) > sends only the filled-in consent filters and starts again at page 1	99	✓
search and filter (#26, FR-19) > Clear removes the filters	87	✓
search and filter (#26, FR-19) > the audit tab has its own filters	90	✓
search and filter (#26, FR-19) > says when nothing matches	99	✓
Verify integrity (#27, SEC-6) > shows a green result when both chains are intact	89	✓
Verify integrity (#27, SEC-6) > points to the first broken record when something was changed	63	✓
Time travel (#16, FR-20) > looks up the user and shows what they had agreed to at that moment	95	✓
Time travel (#16, FR-20) > shows the API error for an unknown e-mail	84	✓

src/pages/HistoryPage.test.tsx

Test	ms	
Consent history (#19) > shows every decision newest first, grouped by day, with the policy version	223	✓
Consent history (#19) > shows a friendly message when there is no history yet	36	✓
Consent history (#19) > the dashboard links to the history page	69	✓
Consent history (#19) > groupByDay keeps order and splits by calendar day	2	✓

src/pages/policies.test.tsx

Test	ms	
policy page (FR-5) > shows the current version, its date and text	190	✓
policy page (FR-5) > says so when nothing is published yet	29	✓
admin policy editor (FR-13, FR-14, FR-15) > lists versions; published ones are locked, drafts can be edited and published	98	✓
admin policy editor (FR-13, FR-14, FR-15) > creates a new draft with the next version number pre-filled	174	✓
admin policy editor (FR-13, FR-14, FR-15) > publishing asks for confirmation first	93	✓
admin policy editor (FR-13, FR-14, FR-15) > shows field errors from the API	80	✓
admin policy editor (FR-13, FR-14, FR-15) > a USER cannot open the admin screen	24	✓
admin policy editor (FR-13, FR-14, FR-15) > suggests the next major version	1	✓