Cognizant – upGrad Training Program

uGE_DotNet FSD (Python)

Weekly Submission Document – WEEK1

Trainee Information

Name: Gollavilli Thanmayi

Email: thanmayigollavilli@gmail.com

Batch Name: B1_Python

Session Timings: 9.30 AM to 6.30PM

Faculty: Kunal

16/February/2026

PROGRAM 1:

```
<!DOCTYPE html>
<html lang="en">
<head>
   <meta charset="UTF-8">
   <title>My Basic HTML Page</title>
</head>
<body>

   <!-- Heading and Introduction -->
   <h1>Welcome to My Web Page</h1>
   <p>Hello! My name is Thanmayi. I am learning HTML and this is my first basic web page. I enjoy exploring new technologies and improving my web development skills.</p>

   <!-- Unordered List: Hobbies -->
   <h2>My Hobbies</h2>
```

```
<ul>
    <li>Reading books</li>
    <li>Playing football</li>
    <li>Listening to music</li>
    <li>Coding</li>
</ul>

<!-- Ordered List: Daily Routine -->
<h2>My Daily Routine</h2>
<ol>
    <li>Wake up early</li>
    <li>Exercise</li>
    <li>Attend classes</li>
    <li>Study and complete assignments</li>
    <li>Relax and sleep</li>
</ol>

<!-- Table: Student Details -->
<h2>Student Marks</h2>
<table border="1">
    <tr>
        <th>Student Name</th>
        <th>Subject</th>
        <th>Marks</th>
    </tr>
    <tr>
```

```
            <td>John Doe</td>
            <td>Mathematics</td>
            <td>85</td>
        </tr>
        <tr>
            <td>John Doe</td>
            <td>Science</td>
            <td>90</td>
        </tr>
        <tr>
            <td>John Doe</td>
            <td>English</td>
            <td>88</td>
        </tr>
    </table>

</body>
</html>
```

PROGRAM 2:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Spice Delight Restaurant</title>
</head>
```

```
<body>

    <!-- Restaurant Name -->
    <h1 align="center" title="Welcome to Spice Delight">Spice Delight Restaurant</h1>

    <!-- About Section -->
    <p title="About our restaurant">
        Spice Delight is a cozy restaurant offering delicious and freshly prepared meals.
        We serve a variety of traditional and modern dishes made with high-quality ingredients.
        Visit us to enjoy a delightful dining experience!
    </p>

    <!-- Menu Categories -->
    <h2>Menu Categories</h2>
    <ul title="Food Categories">
        <li>Breakfast</li>
        <li>Main Course</li>
        <li>Beverages</li>
        <li>Desserts</li>
    </ul>

    <!-- Price List Table -->
    <h2>Price List</h2>
    <table border="1" align="center" title="Restaurant Menu Table">
        <tr>
            <th>Item Name</th>
```

```
            <th>Category</th>
            <th>Price (₹)</th>
        </tr>
        <tr>
            <td>Paneer Butter Masala</td>
            <td>Main Course</td>
            <td>220</td>
        </tr>
        <tr>
            <td>Veg Biryani</td>
            <td>Main Course</td>
            <td>180</td>
        </tr>
        <tr>
            <td>Masala Dosa</td>
            <td>Breakfast</td>
            <td>90</td>
        </tr>
        <tr>
            <td>Cold Coffee</td>
            <td>Beverages</td>
            <td>120</td>
        </tr>
    </table>

</body>
```

```
</html>
```

PROGRAM 3:

```
<!DOCTYPE html>
<html lang="en">
<head>
   <meta charset="UTF-8">
   <title>Weekly Grocery Checklist</title>
</head>
<body>

   <!-- Main Heading -->
   <h1 title="My Weekly Shopping Plan">Weekly Grocery Checklist</h1>

   <!-- High-Priority Items -->
   <h2>High-Priority Items</h2>
   <ol title="Essential Grocery Items">
      <li>Rice</li>
      <li>Milk</li>
      <li>Vegetables</li>
      <li>Cooking Oil</li>
   </ol>

   <!-- Optional Items -->
   <h2>Optional Items</h2>
   <ul title="Non-Essential Grocery Items">
```

```
        <li>Snacks</li>
        <li>Ice cream</li>
        <li>Soft drinks</li>
    </ul>

</body>
</html>
```

PROGRAM 4:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>About Me Page</title>
</head>
<body>

    <!-- Main Heading -->
    <h1>John Doe</h1>

    <!-- About Me Paragraph -->
    <p>
        Hello! My name is Thanmayi. I am a <b>passionate</b> learner who enjoys
        exploring new technologies. Currently, I am learning <mark>HTML</mark>
        and building simple web pages to improve my skills.
```

```
    </p>

    <!-- Goals Section -->
    <h2>My Goals</h2>
    <ul>
        <li>Master HTML and CSS</li>
        <li>Learn JavaScript</li>
        <li>Build real-world projects</li>
        <li>Become a full-stack developer</li>
        <li>Start a tech career in 2026</li>
    </ul>

    <!-- Footer -->
    <footer>
        <p>Created by John Doe - 2026</p>
    </footer>

</body>
</html>
```

PROGRAM 5:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
    <title>Student Marks Report</title>
</head>
<body>

    <!-- Heading -->
    <h1>Student Marks Report</h1>

    <!-- Marks Table -->
    <table border="1" cellpadding="8">
        <tr>
            <th>Roll No</th>
            <th>Name</th>
            <th>Subject</th>
            <th>Total Marks</th>
            <th>Marks Obtained</th>
            <th>Result</th>
        </tr>

        <tr>
            <td>101</td>
            <td>Amit Sharma</td>
            <td>Mathematics</td>
            <td>100</td>
            <td>85</td>
            <td style="color: green;">Pass</td>
        </tr>
```

```
<tr>
    <td>102</td>
    <td>Priya Verma</td>
    <td>Science</td>
    <td>100</td>
    <td>92</td>
    <td style="color: green;">Pass</td>
</tr>

<tr>
    <td>103</td>
    <td>Rahul Singh</td>
    <td>English</td>
    <td>100</td>
    <td>45</td>
    <td style="color: red;">Fail</td>
</tr>

<tr>
    <td>104</td>
    <td>Sneha Patel</td>
    <td>Computer</td>
    <td>100</td>
    <td>78</td>
    <td style="color: green;">Pass</td>
```

```
    </tr>

    <tr>
        <td>105</td>
        <td>Karan Mehta</td>
        <td>History</td>
        <td>100</td>
        <td>33</td>
        <td style="color: red;">Fail</td>
    </tr>

</table>

<!-- Horizontal Line -->
<hr>

<!-- Ordered List Section -->
<h2>Top 5 Subjects in My Course</h2>
<ol>
    <li>Mathematics</li>
    <li>Science</li>
    <li>Computer Science</li>
    <li>English</li>
    <li>History</li>
</ol>
```

```
</body>
</html>
```

PROGRAM 6:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Restaurant Menu</title>
</head>
<body>

  <!-- Header Section -->
  <header>
    <h1>Spice Garden Restaurant</h1>
    <p>Delicious Food, Warm Hospitality</p>
  </header>

  <!-- Navigation Bar -->
  <nav>
    <a href="#">Home</a> |
    <a href="#">Menu</a> |
    <a href="#">Contact</a>
  </nav>
```

```
<!-- Menu Section -->
<section>
  <h2>Menu Items</h2>

  <table border="1" cellpadding="8">
    <tr>
      <th>Item Name</th>
      <th>Category</th>
      <th>Price (₹)</th>
      <th>Availability</th>
    </tr>

    <tr>
      <td>Tomato Soup</td>
      <td>Starter</td>
      <td>120</td>
      <td>Available</td>
    </tr>

    <tr>
      <td>Paneer Tikka</td>
      <td>Starter</td>
      <td>180</td>
      <td>Available</td>
    </tr>
```

```
<tr>
    <td>Veg Biryani</td>
    <td>Main Course</td>
    <td>250</td>
    <td>Available</td>
</tr>

<tr>
    <td>Butter Naan</td>
    <td>Main Course</td>
    <td>40</td>
    <td>Available</td>
</tr>

<tr>
    <td>Gulab Jamun</td>
    <td>Dessert</td>
    <td>90</td>
    <td>Available</td>
</tr>

<tr>
    <td>Cold Coffee</td>
    <td>Drinks</td>
    <td>150</td>
    <td>Out of Stock</td>
```

```
    </tr>

</table>

<!-- Horizontal Line -->
<hr>

<!-- Recommended Items -->
<h3>Top 5 Recommended Items</h3>
<ol type="1">
    <li>Paneer Tikka</li>
    <li>Veg Biryani</li>
    <li>Tomato Soup</li>
    <li>Gulab Jamun</li>
    <li>Cold Coffee</li>
</ol>

<!-- Offers -->
<h3>Available Offers</h3>
<ul>
    <li>10% discount on orders above ₹500</li>
    <li>Free dessert with family combo</li>
    <li>Buy 1 Get 1 Free on Cold Coffee (Weekdays)</li>
    <li>20% discount for students</li>
    <li>Free home delivery above ₹300</li>
</ul>
```

```
    </section>

    <!-- Footer -->
    <footer>
        <p>Thank you for visiting!</p>
        <p>Contact us: <a href="mailto:info@spicegarden.com">info@spicegarden.com</a></p>
    </footer>

</body>
</html>
```

17/February/2026

NAVIGATION:

PROGRAM 1:

Index1.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Home Page</title>
</head>
<body>
    <nav>
```

```
    <a href="index1.html">Home</a>
    <a href="contact1.html">Contact</a>
</nav>
<br>
<form action="#" method="post">
    <label>Name:</label>
    <input type="text" placeholder="Enter your name" required><br><br>
    <label>Email:</label>
    <input type="email" placeholder="Enter your Email" required><br><br>
    <label>Password:</label>
    <input type="password" placeholder="Enter your Password" required><br><br>
    <label>Gender:</label>
    <input type="radio" name="gender" required>Male
    <input type="radio" name="gender" >Female
    <input type="radio" name="gender">Others
    <br><br>
    <label>Select Course:</label><br>
    <select required>
        <option value="">--Select Course--</option>
        <option>HTML</option>
        <option>CSS</option>
        <option>Javascript</option>
        <option>SQL</option>
        <option>Python</option>
    </select>
    <br><br>
```

```
        <input type="submit" value="Register">
    </form>
</body>
</html>
```

Contact1.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Contact Page</title>
</head>
<body>
    <nav>
        <a href="index1.html">Home</a>
        <a href="contact1.html">Contact</a>
    </nav>
    <h2>Contact Us</h2>
    <p>Email:<a href="mailto:support@gmail.com">support@gmail.com</a></p>
    <p>Phone:<a href="tel:+919834666644">+91 93456 66644</a></p>
</body>
</html>
```

PROGRAM 2:

index2.html:

```
<!DOCTYPE html>
<html lang="en">
```

```
<head>
   <meta charset="UTF-8">
   <title>Coaching Institute - Home</title>
</head>
<body>
   <nav>
      <a href="index2.html">Home</a> |
      <a href="courses2.html">Courses</a> |
      <a href="contact2.html">Contact</a> |
      <a href="#about2">About Section</a> |
      <a href="https://www.facebook.com" target="_blank">Our Facebook</a>
   </nav>
   <h1>Welcome to ABC Coaching Institute</h1>
   <p>We provide quality education for competitive exams.</p>
   <h2 id="about">About Us</h2>
   <p>
      ABC Coaching Institute has been helping students achieve success
      through expert guidance and structured learning programs.
   </p>
</body>
</html>
```

courses2.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
   <meta charset="UTF-8">
```

```
    <title>Coaching Institute - Courses</title>
</head>
<body>
    <nav>
        <a href="index2.html">Home</a> |
        <a href="courses2.html">Courses</a> |
        <a href="contact2.html">Contact</a>
    </nav>
    <h1>Our Courses</h1>
    <h2>Web Development</h2>
    <p>Learn HTML, CSS, and JavaScript from basics to advanced level.</p>
    <h2>Banking Exam Preparation</h2>
    <p>Complete preparation for competitive banking exams.</p>
    <h2>SSC & Government Exams</h2>
    <p>Structured courses for SSC and other government exams.</p>
</body>
</html>
```

contact2.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Coaching Institute - Contact</title>
</head>
<body>
    <nav>
```

```
        <a href="index2.html">Home</a> |
        <a href="courses2.html">Courses</a> |
        <a href="contact2.html">Contact</a>
    </nav>
    <h1>Contact Us</h1>
    <p>Email: info@cvcorpcoaching.com</p>
    <p>Phone: +91 9876533210</p>
    <p>Address: Main Road, Hyderabad</p>
</body>
</html>
```

PROGRAM 3:

student_registration.html

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Student Registration Form</title>
</head>
<body>
    <h1>Student Registration Form</h1>
    <form action="#" method="post">
        <label for="name">Full Name:</label><br>
        <input type="text" id="name" name="name"
               placeholder="Enter your full name" required>
        <br><br>
```

```
        <label for="email">Email:</label><br>
        <input type="email" id="email" name="email"
            placeholder="Enter your email" required>
        <br><br>
        <label for="phone">Phone Number:</label><br>
        <input type="tel" id="phone" name="phone"
            placeholder="Enter 10-digit phone number"
            pattern="[0-9]{10}"
            required>
        <br><br>
        <label for="age">Age:</label><br>
        <input type="number" id="age" name="age"
            min="18" max="60" required>
        <br><br>
        <label for="dob">Date of Birth:</label><br>
        <input type="date" id="dob" name="dob" required>
        <br><br>
        <input type="submit" value="Register">
    </form>
</body>
</html>
```

PROGRAM 4:

Index.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
```

```
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Mini Shopping Website</title>
</head>
<body>
    <nav>
        <a href="index.html">Home</a> |
        <a href="electronics.html" id="electronicsLink">Electronics</a> |
        <a href="checkout.html">Checkout</a>
    </nav>
    <h1>Welcome to MiniShop</h1>
    <p>
        <a href="#categories">Go to Categories</a> |
        <a href="#offers">Go to Offers</a>
    </p>
    <h2 id="categories">Categories</h2>
    <ul>
        <li><a href="electronics.html">Electronics</a></li>
        <li>Fashion</li>
        <li>Grocery</li>
        <li>Sports</li>
    </ul>
    <h2 id="offers">Offers Section</h2>
    <ol>
        <li>10% off on Mobiles</li>
        <li>15% off on Laptops</li>
```

```
        <li>Buy 1 Get 1 on Accessories</li>
        <li>Free Delivery above ₹999</li>
        <li>Extra 5% with UPI Payment</li>
    </ol>
</body>
</html>
```

Electronics.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Electronics-MiniShop</title>
</head>
<body>
    <p>
        <a href="index.html">Home</a> > Electronics
    </p>
    <h1>Electronics</h1>
    <table border="1">
        <tr>
            <th>Product Type</th>
            <th>Items Available</th>
            <th>Discount</th>
        </tr>
        <tr>
```

```
        <td>Mobiles</td>
        <td>50+</td>
        <td>10%</td>
    </tr>
    <tr>
        <td>Laptops</td>
        <td>30+</td>
        <td>15%</td>
    </tr>
    <tr>
        <td>TV</td>
        <td>20+</td>
        <td>12%</td>
    </tr>
    <tr>
        <td>Accessories</td>
        <td>100+</td>
        <td>5%</td>
    </tr>
</table>
<h2>Explore Categories</h2>
<ul>
    <li><a href="mobiles.html">Mobiles</a></li>
    <li><a href="#">Laptops</a></li>
    <li><a href="#">TV</a></li>
</ul>
```

```
</body>
</html>
```

Mobiles.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Mobiles - MiniShopping</title>
</head>
<body>
    <p>
        <a href="index.html">Home</a> >
        <a href="electronics.html">Electronics</a> >
        Mobiles
    </p>
    <h1>Available Mobiles</h1>
    <table border="1">
        <tr>
            <th>Mobile Name</th>
            <th>Price</th>
            <th>Stock</th>
            <th>Rating</th>
        </tr>
        <tr>
            <td>iPhone 14</td>
```

```
    <td>₹70,000</td>
    <td><meter value="30" min="0" max="100"></meter></td>
    <td>4.5/5</td>
  </tr>
  <tr>
    <td>Samsung Galaxy S23</td>
    <td>₹65,000</td>
    <td><meter value="60" min="0" max="100"></meter></td>
    <td>4.3/5</td>
  </tr>
  <tr>
    <td>OnePlus 12</td>
    <td>₹50,000</td>
    <td><meter value="80" min="0" max="100"></meter></td>
    <td>4.4/5</td>
  </tr>
  <tr>
    <td>Redmi Note 13</td>
    <td>₹18,000</td>
    <td><meter value="40" min="0" max="100"></meter></td>
    <td>4.1/5</td>
  </tr>
  <tr>
    <td>Realme Narzo</td>
    <td>₹15,000</td>
    <td><meter value="20" min="0" max="100"></meter></td>
```

```
        <td>4.0/5</td>
      </tr>
    </table>
    <h2>Order Processing</h2>
    <progress value="50" max="100"></progress>
    <p>50% Processing</p>
</body>
</html>
```

Checkout.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Checkout - MiniShop</title>
</head>
<body>
    <p>
      <a href="index.html">Home</a> > Checkout
    </p>
    <h1>Checkout Form</h1>
    <form action="#" method="post">
      <label>Full Name:</label><br>
      <input type="text" required><br><br>
      <label>Address:</label><br>
      <textarea required></textarea><br><br>
```

```
    <label>Email:</label><br>
    <input type="email" required><br><br>
    <label>Payment Method:</label><br>
    <input list="paymentOptions" required>
    <datalist id="paymentOptions">
        <option value="UPI">
        <option value="Card">
        <option value="Cash">
        <option value="NetBanking">
    </datalist>
    <br><br>
    <label>Delivery Date:</label><br>
    <input type="date" required><br><br>
    <label>Coupon Code:</label><br>
    <input type="text" pattern="SHOP[0-9]{3}"
           placeholder="Example: SHOP123">
    <br><br>
    <input type="submit" value="Place Order">
</form>
<script>
    document.addEventListener("DOMContentLoaded", function() {
        var electronicsLink = document.querySelector('a[href="electronics.html"]');
        if (electronicsLink) {
            electronicsLink.addEventListener("click", function() {
                this.style.color = "green";
            });
```

```
        }
    });
  </script>
</body>
</html>
```

CSS:

PROGRAM 1:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Product Features</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      background-color: #f4f6f9;
    }
    .features-section {
      width: 60%;
      margin: 40px auto;
      text-align: center;
    }
    .features-section ul {
      list-style-type: none;
      padding: 0;
```

```
        }
        .feature-item {
            background-color: white;
            color: #333;
            padding: 15px;
            margin: 15px 0;
            border: 2px solid #4CAF50;
            border-radius: 8px;
            transition: 0.3s;
        }
        .feature-item:hover {
            background-color: #4CAF50;
            color: white;
            cursor: pointer;
        }
        h2 {
            color: #2c3e50;
        }
    </style>
</head>
<body>
    <section class="features-section">
        <h2>Product Key Features</h2>
        <ul>
            <li class="feature-item">High Performance Speed</li>
            <li class="feature-item">User-Friendly Interface</li>
```

```
            <li class="feature-item">Secure Data Protection</li>
            <li class="feature-item">Cloud Integration</li>
            <li class="feature-item">24/7 Customer Support</li>
        </ul>
    </section>
</body>
</html>
```

PROGRAM2:

T2-blog.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Responsive Blog Homepage</title>
    <link rel="stylesheet" href="T2-blog.css">
</head>
<body>
    <header class="site-header">
        <h1>My Tech Blog</h1>
        <p>Latest articles and updates in technology</p>
    </header>
    <main class="blog-container">
        <article class="blog-card">
            <h2>Understanding Flexbox</h2>
```

```
        <p>Learn how Flexbox works and how it can simplify your layout designs with flexible alignment.</p>
        <a href="#">Read More</a>
    </article>
    <article class="blog-card">
        <h2>CSS Grid Basics</h2>
        <p>Step-by-step guide to create modern layouts using CSS Grid with ease and responsiveness.</p>
        <a href="#">Read More</a>
    </article>
    <article class="blog-card">
        <h2>Responsive Design Tips</h2>
        <p>Practical techniques to make your website adapt smoothly across desktop, tablet, and mobile screens.</p>
        <a href="#">Read More</a>
    </article>
    <article class="blog-card">
        <h2>Modern Typography</h2>
        <p>Enhance your website’s readability and aesthetics using modern typography techniques.</p>
        <a href="#">Read More</a>
    </article>
    <article class="blog-card">
        <h2>Box Model Explained</h2>
        <p>Understand margins, padding, and borders to create consistent and professional-looking layouts.</p>
        <a href="#">Read More</a>
```

```
        </article>
    </main>
</body>
</html>
```

T2-blog.css:

```
* {
    box-sizing: border-box;
    margin: 0;
    padding: 0;
}

body {
    font-family: Arial, sans-serif;
    background-color: #f0f2f5;
    color: #333;
    line-height: 1.6;
}
.site-header {
    text-align: center;
    padding: 40px 20px;
    background-color: #4CAF50;
    color: white;
}
.site-header h1 {
    margin-bottom: 10px;
}
```

```
.site-header p {
    font-size: 1.1em;
}
.blog-container {
    display: flex;
    flex-wrap: wrap;
    justify-content: space-around;
    padding: 20px;
    gap: 20px;
}
.blog-card {
    background-color: white;
    border: 2px solid #ddd;
    border-radius: 10px;
    padding: 20px;
    flex: 1 1 300px;
    max-width: 350px;
    transition: transform 0.3s, box-shadow 0.3s;
}
.blog-card:hover {
    transform: translateY(-5px);
    box-shadow: 0 5px 15px rgba(0,0,0,0.2);
}
.blog-card h2 {
    margin-bottom: 10px;
    color: #4CAF50;
```

```
}
.blog-card p {
    margin-bottom: 15px;
}
.blog-card a {
    text-decoration: none;
    color: white;
    background-color: #4CAF50;
    padding: 8px 15px;
    border-radius: 5px;
    transition: background-color 0.3s;
}
.blog-card a:hover {
    background-color: #45a049;
}
@media (max-width: 900px) {
    .blog-card {
        flex: 1 1 45%;
    }
}
@media (max-width: 600px) {
    .blog-card {
        flex: 1 1 100%;
    }
}
```

PROGRAM3:

T3-dashboard.html:

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Responsive Dashboard</title>
    <link rel="stylesheet" href="T3-dashboard.css">
</head>
<body>
    <div class="dashboard">


        <nav class="sidebar">
            <h2>Admin Panel</h2>
            <ul>
                <li><a href="#">Dashboard</a></li>
                <li><a href="#">Users</a></li>
                <li><a href="#">Reports</a></li>
                <li><a href="#">Settings</a></li>
            </ul>
        </nav>
        <main class="main-content">
            <h1>Dashboard Overview</h1>
            <div class="cards-container">
                <div class="info-card">
                    <h3>Total Users</h3>
```

```
            <p>1,250</p>
        </div>
        <div class="info-card">
            <h3>Active Sessions</h3>
            <p>345</p>
        </div>
        <div class="info-card">
            <h3>New Orders</h3>
            <p>87</p>
        </div>
        <div class="info-card">
            <h3>Revenue</h3>
            <p>$12,450</p>
        </div>
      </div>
    </main>
  </div>
</body>
</html>
```

T3-dashboard.css:

```
* {
  margin: 0;
  padding: 0;
  box-sizing: border-box;
  font-family: Arial, sans-serif;
}
```

```
.dashboard {
    display: flex;
    min-height: 100vh;
}
.sidebar {
    width: 220px;
    background-color: #2c3e50;
    color: white;
    padding: 20px;
}
.sidebar h2 {
    margin-bottom: 20px;
}
.sidebar ul {
    list-style: none;
}
.sidebar ul li {
    margin-bottom: 15px;
}
.sidebar ul li a {
    color: white;
    text-decoration: none;
    display: block;
    padding: 8px 12px;
    border-radius: 5px;
    transition: background-color 0.3s;
```

```
}
.sidebar ul li a:hover {
    background-color: #34495e;
}
.main-content {
    flex: 1;
    padding: 20px;
    background-color: #ecf0f1;
}
.cards-container {
    display: flex;
    flex-wrap: wrap;
    gap: 20px;
    margin-top: 20px;
}
.info-card {
    flex: 1 1 200px;
    background-color: white;
    padding: 20px;
    border: 2px solid #bdc3c7;
    border-radius: 8px;
    text-align: center;
    transition: transform 0.3s, box-shadow 0.3s;
}
.info-card:hover {
    transform: translateY(-5px);
```

```
    box-shadow: 0 5px 15px rgba(0,0,0,0.2);
}
.info-card h3 {
    margin-bottom: 10px;
    color: #2c3e50;
}
@media (max-width: 900px) {
    .cards-container {
        flex: 1 1 100%;
    }
}
@media (max-width: 600px) {
    .dashboard {
        flex-direction: column;
    }
    .sidebar {
        width: 100%;
        display: flex;
        flex-wrap: wrap;
        justify-content: space-around;
    }
    .sidebar ul {
        display: flex;
        flex-wrap: wrap;
        justify-content: center;
    }
```

```
    .sidebar ul li {
        margin: 5px 10px;
    }
}
```

PROGRAM 4:

T4-navbar.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Sticky Navbar</title>
    <link rel="stylesheet" href="T4-navbar.css">
</head>
<body>
<nav class="navbar">
    <ul>
        <li><a href="#" class="active">Home</a></li>
        <li><a href="#">About</a></li>
        <li><a href="#">Services</a></li>
        <li><a href="#">Portfolio</a></li>
        <li><a href="#">Contact</a></li>
    </ul>
</nav>
<div class="content">
    <h1>Welcome to My Website</h1>
    <p>Scroll down to see the sticky effect.</p>
```

```
    <p>... (repeat content to enable scrolling)</p>
</div>
</body>
</html>
```

T4-navbar.css:

```
body {
    font-family: Arial, sans-serif;
    margin: 0;
}
.navbar {
    position: sticky;
    top: 0;
    background-color: #2c3e50;
    box-shadow: 0 4px 6px rgba(0,0,0,0.3);
    z-index: 100;
}
.navbar ul {
    list-style: none;
    display: flex;
    margin: 0;
    padding: 0;
}
.navbar ul li a {
    color: white;
    text-decoration: none;
    padding: 15px 20px;
```

```
    display: block;
    transition: background 0.3s;
}
.navbar ul li a:hover {
    background-color: #34495e;
}
.navbar ul li a.active {
    background-color: #e67e22;
}
```

PROGRAM 5:

T5-Pricing.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Pricing Plans</title>
    <link rel="stylesheet" href="T5-pricing.css">
</head>
<body>
    <section class="pricing-section">
    <div class="pricing-card">
        <h2>Basic</h2>
        <p class="price">$10/mo</p>
        <ul>
            <li>Feature 1</li>
```

```
            <li>Feature 2</li>
            <li>Feature 3</li>
        </ul>
        <button>Choose Plan</button>
    </div>
    <div class="pricing-card">
        <h2>Standard</h2>
        <p class="price">$20/mo</p>
        <ul>
            <li>Feature 1</li>
            <li>Feature 2</li>
            <li>Feature 3</li>
        </ul>
        <button>Choose Plan</button>
    </div>
    <div class="pricing-card">
        <h2>Premium</h2>
        <p class="price">$30/mo</p>
        <ul>
            <li>Feature 1</li>
            <li>Feature 2</li>
            <li>Feature 3</li>
        </ul>
        <button>Choose Plan</button>
    </div>
</section>
```

```
</body>
</html>
```

T5-Pricing.css:

```
body {
    font-family: Arial, sans-serif;
    margin: 0;
    background: #f0f2f5;
}
.pricing-section {
    display: flex;
    justify-content: space-around;
    flex-wrap: wrap;
    padding: 40px 20px;
    gap: 20px;
}
.pricing-card {
    background: white;
    border: 2px solid #ddd;
    border-radius: 10px;
    padding: 20px;
    flex: 1 1 250px;
    max-width: 300px;
    text-align: center;
    transition: transform 0.3s, box-shadow 0.3s;
}
.pricing-card:hover {
```

```
    transform: scale(1.05);
    box-shadow: 0 5px 15px rgba(0,0,0,0.2);
}
.pricing-card h2 {
    color: #4CAF50;
    margin-bottom: 10px;
}
.pricing-card .price {
    font-size: 1.5em;
    margin-bottom: 10px;
}
.pricing-card ul {
    list-style: none;
    padding: 0;
    margin-bottom: 15px;
}
.pricing-card ul li {
    margin-bottom: 5px;
}
.pricing-card button {
    background-color: #4CAF50;
    color: white;
    padding: 10px 15px;
    border: none;
    border-radius: 5px;
    cursor: pointer;
```

```
    transition: background 0.3s;
}
.pricing-card button:hover {
    background-color: #45a049;
}
@media (max-width: 600px) {
    .pricing-section {
        flex-direction: column;
        align-items: center;
    }
}
```

PROGRAM 6:

T6-gallery.html

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Photo Gallery</title>
    <link rel="stylesheet" href="T6-gallery.css">
</head>
<body>
<section class="gallery">
    <div class="photo">Photo 1</div>
    <div class="photo">Photo 2</div>
    <div class="photo">Photo 3</div>
    <div class="photo">Photo 4</div>
```

```
    <div class="photo">Photo 5</div>
    <div class="photo">Photo 6</div>
    <div class="photo">Photo 7</div>
    <div class="photo">Photo 8</div>
</section>
</body>
</html>
```

T6-gallery.css

```
body {
    font-family: Arial, sans-serif;
    background: #f0f2f5;
    margin: 0;
}
.gallery {
    display: grid;
    grid-template-columns: repeat(4, 1fr);
    gap: 20px;
    padding: 20px;
}
.photo {
    background: white;
    border: 2px solid #ddd;
    border-radius: 10px;
    height: 150px;
    display: flex;
    justify-content: center;
```

```
    align-items: center;
    transition: background 0.3s, transform 0.3s, box-shadow 0.3s;
    cursor: pointer;
}
.photo:hover {
    background-color: #4CAF50;
    color: white;
    transform: translateY(-5px);
    box-shadow: 0 5px 15px rgba(0,0,0,0.2);
}
@media (max-width: 900px) {
    .gallery {
        grid-template-columns: repeat(2, 1fr);
    }
}
@media (max-width: 600px) {
    .gallery {
        grid-template-columns: 1fr;
    }
}
```

PROGRAM7:

T7-sidebar.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
```

```
    <title>Sidebar Layout</title>
    <link rel="stylesheet" href="T7-sidebar.css">
</head>
<body>
<div class="container">
    <header class="header">
        <h1>My Dashboard</h1>
    </header>
    <aside class="sidebar">
        <ul>
            <li><a href="#">Dashboard</a></li>
            <li><a href="#">Users</a></li>
            <li><a href="#">Reports</a></li>
            <li><a href="#">Settings</a></li>
        </ul>
    </aside>
    <main class="main">
        <h2>Main Content Area</h2>
        <p>Lorem ipsum dolor sit amet...</p>
    </main>
    <footer class="footer">
        <p>&copy; 2026 My Dashboard</p>
    </footer>
</div>
</body>
</html>
```

T7-sidebar.css:

```
body, html {
    margin: 0;
    padding: 0;
    font-family: Arial, sans-serif;
}
.container {
    display: flex;
    flex-direction: row;
    min-height: 100vh;
}
.sidebar {
    width: 220px;
    background-color: #2c3e50;
    color: white;
    padding: 20px;
}
.sidebar ul {
    list-style: none;
}
.sidebar ul li {
    margin-bottom: 15px;
}
.sidebar ul li a {
    color: white;
    text-decoration: none;
```

```
    display: block;
    padding: 8px 12px;
    border-radius: 5px;
    transition: background 0.3s;
}
.sidebar ul li a:hover {
    background-color: #34495e;
}
.main {
    flex: 1;
    padding: 20px;
    background-color: #ecf0f1;
}
.header, .footer {
    width: 100%;
    text-align: center;
    padding: 15px;
    background-color: #4CAF50;
    color: white;
}
@media (max-width: 700px) {
    .container {
        flex-direction: column;
    }
    .sidebar {
        width: 100%;
```

```
        display: flex;
        justify-content: space-around;
    }
    .sidebar ul {
        display: flex;
        flex-wrap: wrap;
        justify-content: center;
    }
    .sidebar ul li {
        margin: 5px 10px;
    }

    .main {
        width: 100%;
    }
}
```

18/February/2026:

PROGRAM1:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>ATM Withdrawal</title>
</head>
```

```
<body>
  <h2>ATM Withdrawal Simulation</h2>
  <button onclick="atmWithdraw()">Withdraw</button>
  <p id="result"></p>
  <script>
    let balance = Number(prompt("Enter your account balance:"));
    let withdraw = Number(prompt("Enter withdrawal amount:"));
    function atmWithdraw() {
      let result = document.getElementById("result");
      if (withdraw > balance) {
        result.innerHTML = "Insufficient Balance";
      }
      else if (withdraw <= 0) {
        result.innerHTML = "Invalid Amount";
      }
      else if (withdraw % 100 === 0) {
        balance -= withdraw;
        result.innerHTML = "Withdrawal successful! Remaining Balance: " + balance;
      }
      else {
        result.innerHTML = "Enter amount in multiples of 100";
      }
    }
  </script>
</body>
</html>
```

PROGRAM2:

```
<!DOCTYPE html>
<html lang="en">
<head>
   <meta charset="UTF-8">
   <meta name="viewport" content="width=device-width, initial-scale=1.0">
   <title>Electricity Bill Calculator</title>
</head>
<body>
   <h2>Electricity Bill Calculator</h2>


   <button onclick="calculateBill()">Calculate Bill</button>
   <p id="result"></p>
   <script>
      function calculateBill() {
         let units = Number(prompt("Enter the number of units consumed:"));
         let bill = 0;
         if (units <= 100) {
            bill = units * 2;
         }
         else if (units <= 200) {
            bill = 100 * 2 + (units - 100) * 3;
         }
         else if (units <= 300) {
            bill = 100 * 2 + 100 * 3 + (units - 200) * 5;
         }
```

```
        else {
            bill = 100 * 2 + 100 * 3 + 100 * 5 + (units - 300) * 8;
        }
        document.getElementById("result").innerHTML =
            "Units Consumed: " + units + "<br>" +
            "Total Bill Amount: ₹" + bill;
    }
  </script>
</body>
</html>
```

PROGRAM3:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Weekday Finder</title>
</head>
<body>
  <h2>Weekday Finder</h2>
  <button onclick="findDay()">Find Day</button>
  <p id="result"></p>
  <script>
    function findDay() {
        let dayNumber = Number(prompt("Enter a day number (1-7):"));
        let dayName = "";
```

```
let type = "";
switch(dayNumber) {
    case 1:
        dayName = "Monday";
        type = "Weekday";
        break;
    case 2:
        dayName = "Tuesday";
        type = "Weekday";
        break;
    case 3:
        dayName = "Wednesday";
        type = "Weekday";
        break;
    case 4:
        dayName = "Thursday";
        type = "Weekday";
        break;
    case 5:
        dayName = "Friday";
        type = "Weekday";
        break;
    case 6:
        dayName = "Saturday";
        type = "Weekend";
        break;
```

```
            case 7:
                dayName = "Sunday";
                type = "Weekend";
                break;
            default:
                dayName = "Invalid day number";
                type = "";
        }
        if(type) {
            document.getElementById("result").innerHTML = dayName + " - " + type;
        } else {
            document.getElementById("result").innerHTML = dayName;
        }
    }
  </script>
</body>
</html>
```

PROGRAM4:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Password Validator</title>
</head>
<body>
```

```
<button onclick="validatePassword()">Check Password</button>
<p id="result"></p>
<script>
  function validatePassword() {
    let password = prompt("Enter your password:");
    let hasDigit = false;
    let hasUpper = false;
    if(password.length < 8){
      document.getElementById("result").innerHTML = "Password must be at least 8 characters long";
      return;
    }
    for(let i = 0; i < password.length; i++){
      if(password[i] >= '0' && password[i] <= '9') hasDigit = true;
      if(password[i] >= 'A' && password[i] <= 'Z') hasUpper = true;
    }
    if(!hasDigit){
      document.getElementById("result").innerHTML = "Password must contain a digit";
    } else if(!hasUpper){
      document.getElementById("result").innerHTML = "Password must contain an uppercase letter";
    } else {
      document.getElementById("result").innerHTML = "Strong Password";
    }
  }
</script>
</body>
```

```
</html>
```

PROGRAM5:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Traffic Signal Simulator</title>
</head>
<body>
    <h2>Traffic Signal Simulator</h2>
    <button onclick="trafficSignal()">Check Signal</button>
    <p id="result"></p>
    <script>
        function trafficSignal() {
            let signalColor = prompt("Enter traffic signal color (red, yellow, green):").toLowerCase();
            let output = "";
            switch(signalColor) {
                case "red":
                    output = "Stop";
                    break;
                case "yellow":
                    output = "Get Ready";
                    break;
                case "green":
                    output = "Go";
```

```
                break;
            default:
                output = "Invalid signal color";
                break;
        }
        document.getElementById("result").textContent = output;
    }
  </script>
</body>
</html>
```

PROGRAM6:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Number Analysis Tool</title>
</head>
<body>
  <h2>Number Analysis Tool</h2>
  <button onclick="analyzeNumber()">Analyze Number</button>
  <p id="result"></p>
  <pre id="numbersList"></pre>
  <script>
    function analyzeNumber() {
        let num = Number(prompt("Enter a number:"));
```

```
        let positivity = (num >= 0) ? "Positive" : "Negative";
        let parity;
        if (num % 2 === 0) {
            parity = "Even";
        } else {
            parity = "Odd";
        }
        document.getElementById("result").innerHTML =
            "Number: " + num + "\n" +
            "Positivity: " + positivity + "\n" +
            "Parity: " + parity;
        let numbers = "";
        for (let i = 1; i <= num; i++) {
            numbers += i + " ";
        }
        document.getElementById("numbersList").innerHTML = numbers;
    }
  </script>
</body>
</html>
```

PROGRAM7:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
    <title>Student Profile Manager</title>
    <style>
        #studentProfile {
            border: 2px solid #4CAF50;
            border-radius: 10px;
            padding: 20px;
            width: 300px;
            background-color: #f0fff0;
            font-family: Arial, sans-serif;
            margin-top: 20px;
        }
        #studentProfile h3 {
            text-align: center;
            color: #2E7D32;
        }
        #studentProfile p {
            margin: 5px 0;
        }
    </style>
</head>
<body>
    <h2>Student Profile</h2>
    <input type="number" id="newMarks" placeholder="Enter new marks">
    <button
onclick="updateMarks(Number(document.getElementById('newMarks').value))">Update
Marks</button>
    <div id="studentProfile"></div>
```

```
    <script>
        let student = {
            name: "Alice",
            rollNo: "B123",
            marks: 90
        };
        function updateStudentProfile(studentObj) {
            let profileDiv = document.getElementById("studentProfile");
            profileDiv.innerHTML = `
                <h3>Student Profile</h3>
                <p><strong>Name:</strong> ${studentObj.name}</p>
                <p><strong>Roll No:</strong> ${studentObj.rollNo}</p>
                <p><strong>Marks:</strong> ${studentObj.marks}</p>
            `;
        }
        function updateMarks(newMarks) {
            student.marks = newMarks;
            updateStudentProfile(student);
        }
        updateStudentProfile(student);
    </script>
</body>
</html>
```

PROGRAM8:

TASK8.html:

```
<!DOCTYPE html>
```

```html
<html lang="en">
<head>
   <meta charset="UTF-8">
   <meta name="viewport" content="width=device-width, initial-scale=1.0">
   <title>Filter Passing Marks</title>
</head>
<body>
   <h2>Filter Passing Marks</h2>
   <button onclick="filterMarks()">Show Passed Students</button>
   <p id="originalMarks"></p>
   <p id="passedMarks"></p>
   <p id="passedCount"></p>
   <script src="Task8.js"></script>
</body>
</html>
```

Task8.js:

```javascript
let marks = [35, 70, 88, 45, 92, 60, 25];
function filterMarks() {
   document.getElementById('originalMarks').innerHTML = `Original Marks: ${marks.join(", ")}`;
   let passed = marks.filter(m => m >= 50);
   document.getElementById('passedMarks').innerHTML = `Passed Marks: ${passed.join(", ")}`;
   document.getElementById('passedCount').innerHTML = `Number of Students Passed: ${passed.length}`;
}
```

PROGRAM9:

Task9.html:

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Employee System</title>
</head>
<body>
    <h2>Employee Object System</h2>
    <button onclick="showEmployee()">Show Employee</button>
    <button onclick="increaseSalary(employee, 30)">Increase Salary by 30%</button>
    <div id="employeeDetails"></div>
   <script src="Task9.js"></script>
</body>
</html>
```

Task9.js:

```js
let employee = { name: "Amit", salary: 40000, department: "IT" };
function showEmployee() {
    let status = employee.salary > 50000 ? "Senior Employee" : "Junior Employee";
    document.getElementById('employeeDetails').innerHTML = `
        <p>Name: ${employee.name}</p>
        <p>Salary: ₹${employee.salary}</p>
        <p>Department: ${employee.department}</p>
        <p>Status: ${status}</p>
    `;
}
```

```
function increaseSalary(emp, percentage) {
    emp.salary += emp.salary * percentage / 100;
    showEmployee();
}
```

PROGRAM10:

Task10.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Scope Debug</title>
</head>
<body>
    <h2>Scope Debug Program</h2>
    <button onclick="testScope()">Run Scope Test</button>
    <p id="scopeOutput"></p>
    <script src="Task10.js"></script>
</body>
</html>
```

Task10.js:

```
let globalVar = "I am Global";
function testScope() {
    let localVar = "I am Local";
    let output = `Global: ${globalVar}, Local: ${localVar}`;
    {
```

```
        let blockVar = "I am Block";
        output += `, Block: ${blockVar}`;
    }
    document.getElementById('scopeOutput').innerHTML = output;
    console.log(output);
}
```

PROGRAM11:

Task11.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Theme Changer</title>
</head>
<body>
    <h2>DOM Color Theme Changer</h2>
    <button onclick="changeTheme('dark')">Dark Mode</button>
    <button onclick="changeTheme('light')">Light Mode</button>
    <button onclick="changeTheme('blue')">Blue Mode</button>
    <p id="currentMode"></p>
    <script src="Task11.js"></script>
</body>
</html>
```

Task11.js:

```
function changeTheme(mode) {
```

```
    let body = document.body;
    let currentMode = document.getElementById('currentMode');
    switch(mode) {
        case "dark":
            body.style.backgroundColor = "#333";
            body.style.color = "#fff";
            currentMode.innerHTML = "Current Mode: Dark";
            break;
        case "light":
            body.style.backgroundColor = "#fff";
            body.style.color = "#000";
            currentMode.innerHTML = "Current Mode: Light";
            break;
        case "blue":
            body.style.backgroundColor = "#add8e6";
            body.style.color = "#000";
            currentMode.innerHTML = "Current Mode: Blue";
            break;
        default:
            currentMode.innerHTML = "Invalid Mode";
    }
}
```

PROGRAM12:

Task12.html:

```
<!DOCTYPE html>
<html lang="en">
```

```
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Filter Numbers</title>
</head>
<body>
    <h2>Search Numbers Greater than Input</h2>
    <input type="number" id="userInput" placeholder="Enter a number">
    <button onclick="filterNumbers()">Filter</button>
    <p id="filteredNumbers"></p>
    <script src="Task12.js"></script>
</body>
</html>
```

Task12.js:

```
let numbers = [10, 25, 60, 75, 90, 15, 45, 120];
function filterNumbers() {
    let input = Number(document.getElementById('userInput').value);
    let filtered = numbers.filter(n => n > input).sort((a,b) => a-b);
    document.getElementById('filteredNumbers').innerHTML = `Numbers greater than ${input}:
${filtered.join(", ")}`;
}
```

PROGRAM13:

T13-discountCalculator.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
```

```
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Discount Calculator</title>
</head>
<body>
    <h2>Discount Calculator</h2>
    <input type="number" id="price" placeholder="Enter product price">
    <input type="number" id="discount" placeholder="Enter discount %">
    <button onclick="showDiscount()">Calculate</button>
    <p id="discountResult"></p>
    <script src="T13-discountCalculator.js"></script>
</body>
</html>
```

T13-discountCalculator.js:

```
function calculateDiscount(price, discount) {
    return price - (price * discount / 100);
}
function showDiscount() {
    let price = Number(document.getElementById('price').value);
    let discount = Number(document.getElementById('discount').value);
    let finalPrice = calculateDiscount(price, discount);
    document.getElementById('discountResult').innerHTML = `Final Price: ₹${finalPrice}`;
}
```

19/February/2026:

PROGRAM1:

T19-Task1.html:

```
<!DOCTYPE html>
<html>
<head>
  <title>Location Logger</title>
</head>
<body>
  <h2>Location-Based Weather Logger</h2>
  <button onclick="getLocation()">Get My Location</button>
  <h3>Current Location:</h3>
  <div id="locationOutput"></div>
  <h3>Last 5 Location History:</h3>
  <ul id="historyList"></ul>
  <script src="T19-Task1.js"></script>
</body>
</html>
```

T19-Task1.js:

```
const output = document.getElementById("locationOutput");
const historyList = document.getElementById("historyList");
function getLocation() {
  if (!navigator.geolocation) {
    output.innerHTML = "Geolocation not supported";
    return;
  }
  navigator.geolocation.getCurrentPosition(successCallback, errorCallback, {
    timeout: 10000
```

```
    });
}
function successCallback(position) {
    const latitude = position.coords.latitude;
    const longitude = position.coords.longitude;
    output.innerHTML = `
        Latitude: ${latitude} <br>
        Longitude: ${longitude}
    `;
    saveLocation(latitude, longitude);
}
function errorCallback(error) {
    switch (error.code) {
        case error.PERMISSION_DENIED:
            output.innerHTML = "Permission denied";
            break;
        case error.TIMEOUT:
            output.innerHTML = "Location request timed out";
            break;
        case error.POSITION_UNAVAILABLE:
            output.innerHTML = "Location unavailable";
            break;
        default:
            output.innerHTML = "Unknown error";
    }
}
```

```
function saveLocation(lat, long) {
    let locations = JSON.parse(localStorage.getItem("locations")) || [];
    locations.unshift({
        latitude: lat,
        longitude: long,
        date: new Date().toLocaleString()
    });
    locations = locations.slice(0, 5);
    localStorage.setItem("locations", JSON.stringify(locations));
    displayHistory();
}
function displayHistory() {
    historyList.innerHTML = "";
    let locations = JSON.parse(localStorage.getItem("locations")) || [];
    locations.forEach(loc => {
        let li = document.createElement("li");
        li.textContent = `${loc.latitude}, ${loc.longitude} (${loc.date})`;
        historyList.appendChild(li);
    });
}
window.onload = displayHistory;
```

PROGRAM2:

T19-Task2.html:

```
<!DOCTYPE html>
<html>
<head>
```

```
    <title>Mini Expense Tracker</title>
</head>
<body>
    <h2>Expense Tracker</h2>
    <input type="text" id="title" placeholder="Expense Title">
    <input type="number" id="amount" placeholder="Amount">
    <input type="date" id="date">
    <br><br>
    <button onclick="addExpense()">Add Expense</button>
    <button onclick="viewExpenses()">View Expenses</button>

    <h3>Expense List:</h3>
    <ul id="expenseList"></ul>
    <script src="T19-Task2.js"></script>
</body>
</html>
```

T19-Task2.js:

```
let db;
const request = indexedDB.open("ExpenseDB", 1);
request.onupgradeneeded = function (event) {
    db = event.target.result;
    db.createObjectStore("expenses", { keyPath: "id", autoIncrement: true });
};
request.onsuccess = function (event) {
    db = event.target.result;
};
```

```
request.onerror = function () {
    console.log("Database error");
};
function addExpense() {
    const transaction = db.transaction(["expenses"], "readwrite");
    const store = transaction.objectStore("expenses");
    const expense = {
        title: document.getElementById("title").value,
        amount: document.getElementById("amount").value,
        date: document.getElementById("date").value
    };
    store.add(expense);
    transaction.onerror = () => console.log("Transaction failed");
}
function viewExpenses() {
    const transaction = db.transaction(["expenses"], "readonly");
    const store = transaction.objectStore("expenses");
    const request = store.getAll();
    request.onsuccess = function () {
        const list = document.getElementById("expenseList");
        list.innerHTML = "";
        request.result.forEach(exp => {
            const li = document.createElement("li");
            li.textContent = `${exp.title} - ₹${exp.amount} (${exp.date})`;
            list.appendChild(li);
        });
```

```
    };
}
```

PROGRAM3:

T19-Task3.html:

```
<!DOCTYPE html>
<html>
<head>
    <title>Attendance Tracker</title>
</head>
<body>
    <h2>Attendance Tracker</h2>
    <input type="text" id="name" placeholder="Student Name" required>
    <input type="date" id="date" required>
    <select id="status">
        <option value="Present">Present</option>
        <option value="Absent">Absent</option>
    </select>
    <br><br>
    <button onclick="saveAttendance()">Save Attendance</button>
    <button onclick="showAttendance()">Show Attendance</button>
    <button onclick="clearDatabase()">Clear Attendance Database</button>
    <h3>Attendance Records:</h3>
    <div id="output"></div>
    <script src="T19-Task3.js"></script>
</body>
</html>
```

T19-Task3.js:

```
let db;
const request = indexedDB.open("AttendanceDB", 1);
request.onupgradeneeded = function (e) {
    db = e.target.result;
    db.createObjectStore("attendance", { keyPath: "id", autoIncrement: true });
};
request.onsuccess = function (e) {
    db = e.target.result;
};
function saveAttendance() {
    const name = document.getElementById("name").value;
    const date = document.getElementById("date").value;
    const status = document.getElementById("status").value;
    if (!name || !date) {
        alert("Name and Date required");
        return;
    }
    sessionStorage.setItem("lastStudent", name);
    const transaction = db.transaction(["attendance"], "readwrite");
    const store = transaction.objectStore("attendance");
    store.add({ name, date, status });
}
function showAttendance() {
    const transaction = db.transaction(["attendance"], "readonly");
    const store = transaction.objectStore("attendance");
```

```
    const request = store.getAll();
    request.onsuccess = function () {
        let table = "<table border='1'><tr><th>Name</th><th>Date</th><th>Status</th></tr>";
        request.result.forEach(record => {
            table += `<tr>
                        <td>${record.name}</td>
                        <td>${record.date}</td>
                        <td>${record.status}</td>
                      </tr>`;
        });
        table += "</table>";
        document.getElementById("output").innerHTML = table;
    };
}
function clearDatabase() {
    const transaction = db.transaction(["attendance"], "readwrite");
    const store = transaction.objectStore("attendance");
    store.clear();
}
```

PROGRAM4:

T19-Task4.html:

```
<!DOCTYPE html>
<html>
<head>
    <title>Delivery Location Saver</title>
</head>
```

```
<body>
    <h2>Delivery Location Saver</h2>
    <button onclick="detectLocation()">Detect My Location</button>
    <button onclick="viewHistory()">View Location History</button>
    <h3>Output:</h3>
    <div id="output"></div>
    <script src="T19-Task4.js"></script>
</body>
</html>
```

T19-Task4.js:

```
let db;
const request = indexedDB.open("DeliveryDB", 1);
request.onupgradeneeded = function (e) {
    db = e.target.result;
    db.createObjectStore("deliveryLocations", { keyPath: "id", autoIncrement: true });
};
request.onsuccess = function (e) {
    db = e.target.result;
};
function detectLocation() {
    navigator.geolocation.getCurrentPosition(success, error);
}
function success(position) {
   const latitude = position.coords.latitude;
    const longitude = position.coords.longitude;
    const dateTime = new Date().toLocaleString();
```

```
    document.getElementById("output").innerHTML =
        `Lat: ${latitude} <br> Long: ${longitude}`;
    localStorage.setItem("lastLocation",
        JSON.stringify({ latitude, longitude })
    );
    const transaction = db.transaction(["deliveryLocations"], "readwrite");
    const store = transaction.objectStore("deliveryLocations");
    store.add({ latitude, longitude, dateTime });
}
function error() {
    alert("Location access denied");
}
function viewHistory() {
    const transaction = db.transaction(["deliveryLocations"], "readonly");
    const store = transaction.objectStore("deliveryLocations");
    const request = store.getAll();
    request.onsuccess = function () {
        let output = "";
        request.result.forEach(loc => {
            output += `${loc.latitude}, ${loc.longitude} - ${loc.dateTime}<br>`;
        });
        document.getElementById("output").innerHTML = output;
    };
}
```

PROGRAM5:

T19-Task5.html:

```html
<!DOCTYPE html>
<html>
<head>
   <title>Student Marks Analyzer</title>
</head>
<body>
   <h2>Student Marks Analyzer</h2>
   <button onclick="analyzeMarks()">Analyze Marks</button>
   <div id="output"></div>
   <script src="T19-Task5.js"></script>
</body>
</html>
```

T19-Task5.js:

```js
const marks = [85, 40, 72, 55, 30];
const totalMarks = arr => arr.reduce((acc, curr) => acc + curr, 0);
const averageMarks = arr => totalMarks(arr) / arr.length;
const analyzeMarks = () => {
   const total = totalMarks(marks);
   const avg = averageMarks(marks);
   const result = avg >= 50 ? "Pass" : "Fail";
   document.getElementById("output").innerHTML = `
      Total Marks: ${total} <br>
      Average Marks: ${avg.toFixed(2)} <br>
      Result: ${result}
   `;
};
```

PROGRAM6:

T19-Task6.html:

```
<!DOCTYPE html>
<html>
<head>
   <title>Student Result Analyzer</title>
</head>
<body>
   <h2>Student Result Analyzer</h2>
   <button onclick="sortStudents()">Sort Students by Marks</button>
   <button onclick="filterPassed()">Filter Passed Students</button>
   <button onclick="averageMarks()">Calculate Average Marks</button>
   <button onclick="displayResults()">Display All Results</button>
   <div id="output"></div>
   <script src="T19-Task6.js"></script>
</body>
</html>
```

T19-Task6.js:

```
const students = [
   { name: "Kunal", marks: 85 },
   { name: "Rahul", marks: 40 },
   { name: "Neha", marks: 72 },
   { name: "Amit", marks: 55 },
   { name: "Priya", marks: 30 }
];
const sortStudents = () => {
```

```
    const sorted = [...students].sort((a, b) => b.marks - a.marks);
    displayList(sorted, "Sorted Students");
};
const filterPassed = () => {
    const passed = students.filter(student => student.marks >= 50);
    displayList(passed, "Passed Students");
};
const averageMarks = () => {
    const total = students.reduce((acc, curr) => acc + curr.marks, 0);
    const avg = total / students.length;
    document.getElementById("output").innerHTML = `
        Total Marks: ${total} <br>
        Average Marks: ${avg.toFixed(2)}
    `;
};
const displayResults = () => displayList(students, "All Students");
const displayList = (arr, title) => {
    const html = arr.map(student => {
        const grade = student.marks >= 80 ? "A" :
                      student.marks >= 60 ? "B" :
                      student.marks >= 50 ? "C" : "Fail";
        return `<li>${student.name}: ${student.marks} - ${grade}</li>`;
    }).join("");
    document.getElementById("output").innerHTML = `<h3>${title}</h3><ul>${html}</ul>`;
};
```

PROGRAM7:

T19-Task7.html:

```
<!DOCTYPE html>
<html>
<head>
   <title>Order Tracker</title>
</head>
<body>
   <h2>Order Status Tracker</h2>
   <button onclick="trackCallback()">Track Using Callback</button>
   <button onclick="trackPromise()">Track Using Promise</button>
   <button onclick="trackAsync()">Track Using Async/Await</button>
   <div id="output"></div>
   <script src="T19-Task7.js"></script>
</body>
</html>
```

T19-Task7.js:

```
const orders = [
   { orderId: 101, status: "Placed" },
   { orderId: 102, status: "Shipped" },
   { orderId: 103, status: "Delivered" }
];
const trackOrderCallback = (orderId, callback) => {
   setTimeout(() => {
      const order = orders.find(o => o.orderId === orderId);
      if(order) callback(null, order.status);
      else callback("Order not found", null);
```

```
    }, 2000);
};
const trackCallback = () => {
    const id = parseInt(prompt("Enter Order ID"));
    trackOrderCallback(id, (err, status) => {
        document.getElementById("output").innerHTML = err ? err : `Order ID: ${id} <br>Status: ${status}`;
    });
};
const trackOrderPromise = orderId => new Promise((resolve, reject) => {
    setTimeout(() => {
        const order = orders.find(o => o.orderId === orderId);
        order ? resolve(order.status) : reject("Order not found");
    }, 2000);
});
const trackPromise = () => {
    const id = parseInt(prompt("Enter Order ID"));
    trackOrderPromise(id)
        .then(status => document.getElementById("output").innerHTML = `Order ID: ${id} <br>Status: ${status}`)
        .catch(err => document.getElementById("output").innerHTML = err);
};
const trackOrderAsync = async orderId => {
    try {
        const status = await trackOrderPromise(orderId);
        return status;
    } catch(err) {
```

```
        throw err;
    }
};
const trackAsync = async () => {
    const id = parseInt(prompt("Enter Order ID"));
    try {
        const status = await trackOrderAsync(id);
        document.getElementById("output").innerHTML = `Order ID: ${id} <br>Status: ${status}`;
    } catch(err) {
        document.getElementById("output").innerHTML = err;
    }
};
```

20/February/2026:

PROGRAM1:

destructuring.js:

```
let student={
    id:101,
    name:"Suseela",
    age:23,
    course:"Full Stack",
    address:{
        city:"Bangalore",
        state:"Karnataka"
    }
};
```

```
let {name:studentName, course ,address:{city},country="India"} = student;
console.log("Name:",studentName);
console.log("Course:",course);
console.log("City:",city);
console.log("Country:",country);
```

PROGRAM2:

foodOrderCalculator.js

```
function calculateOrder(price,quantity=1,discount=0) {
   if(price===undefined) {
      console.log('Error: Price is required to calculate the order.');
      return;
   }
   let total=price*quantity;
   let discountAmount=(total*discount)/100;
   let amount=total-discountAmount;
   console.log(`Order Summary:
      Price: ${price}
      Quantity: ${quantity}
      Discount: ${discount}
      Final Amount: ${amount}`);
}
calculateOrder(200);
calculateOrder(200,3);
calculateOrder(200,3,10);
calculateOrder();
```

PROGRAM3:

Index.html:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Simple Calculator</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
    <div class="claculator">
        <h2>Calculator</h2>
        <input type="text" id="result" readonly>
        <div class="buttons">
        <button onclick="clearResult()">C</button>
        <button onclick="deleteLast()">DEL</button>
        <button onclick="appendValue('/')">/</button>
        <button onclick="appendValue('*')">*</button>

        <button onclick="appendValue('7')">7</button>
        <button onclick="appendValue('8')">8</button>
        <button onclick="appendValue('9')">9</button>
        <button onclick="appendValue('-')">-</button>

        <button onclick="appendValue('4')">4</button>
        <button onclick="appendValue('5')">5</button>
```

```
        <button onclick="appendValue('6')">6</button>
        <button onclick="appendValue('+')">+</button>

        <button onclick="appendValue('1')">1</button>
        <button onclick="appendValue('2')">2</button>
        <button onclick="appendValue('3')">3</button>
        <button onclick="calculate()">=</button>

        <button onclick="appendValue('0')" class="zero">0</button>
        <button onclick="appendValue('.')">.</button>
        </div>
    </div>
    <script src="script.js"></script>
</body>
</html>
```

style.css:

```
body {
    font-family: Arial;
    background-color: #f4f4f4;
    display: flex;
    justify-content: center;
    align-items: center;
    height: 100vh;
}
.calculator {
    background-color: white;
```

```
    padding: 20px;
    border-radius: 10px;
    width: 300px;
    box-shadow: 0px 0px 10px gray;
    text-align: center;
}
#result {
    width: 100%;
    height: 50px;
    font-size: 22px;
    margin-bottom: 15px;
    padding: 10px;
    text-align: right;
}
.buttons {
    display: grid;
    grid-template-columns: repeat(4, 1fr);
    gap: 10px;
}
button {
    padding: 15px;
    font-size: 18px;
    cursor: pointer;
    border: none;
    background-color: lightgray;
    border-radius: 5px;
```

```
}
button:hover {
    background-color: gray;
    color: white;
}
.zero {
    grid-column: span 2;
}
```

script.js:

```
let resultBox = document.getElementById("result");
function appendValue(value) {
    let current = resultBox.value;
    if (isOperator(value) && isOperator(current.slice(-1))) {
        return;
    }
    if (value === ".") {
        let lastNumber = current.split(/[\+\-\*\/]/).pop();
        if (lastNumber.includes(".")) {
            return;
        }
    }
    resultBox.value += value;
}
function clearResult() {
    resultBox.value = "";
```

```
}
function deleteLast() {
    resultBox.value = resultBox.value.slice(0, -1);
}
function calculate() {
    let expression = resultBox.value;
    if (expression.trim() === "") {
        alert("Please enter a calculation first!");
        return;
    }
    if (isOperator(expression.slice(-1))) {
        alert("Expression cannot end with an operator!");
        return;
    }
    try {
        let result = Function("return " + expression)();
        resultBox.value = result;
    } catch (error) {
        resultBox.value = "Error";
    }
}
function isOperator(char) {
    return ["+", "-", "*", "/"].includes(char);
}
```

PROGRAM4:

index1.html:

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>User Greeting Card</title>
    <style>
        body {
            font-family: Arial;
            text-align: center;
            margin-top: 50px;
        }
        input {
            padding: 8px;
            margin: 5px;
        }
        button {
            padding: 8px 15px;
            cursor: pointer;
        }
        #output {
            margin-top: 20px;
            font-size: 18px;
            background: #f4f4f4;
            padding: 15px;
            display: inline-block;
```

```
            border-radius: 8px;
        }
    </style>
</head>
<body>
    <h2>User Greeting Card</h2>
    <input type="text" id="name" placeholder="Enter a Name">
    <input type="number" id="age" placeholder="Enter a Age">
    <input type="text" id="city" placeholder="Enter a City">
    <button onclick="generateCard()">Generate Card</button>
    <div id="output"></div>
    <script src="script1.js"></script>
</body>
</html>
```

script.js:

```
function generateCard() {
    let name=document.getElementById("name").value ;
    let age=document.getElementById("age").value ;
    let city=document.getElementById("city").value ;
    let user = {
        name,
        age: Number(age),
        city: city || "India"
    };
    let { name: userName, age: userAge, city: userCity } = user;
    let status = userAge < 18 ? "Minor" : "Adult";
```

```
    document.getElementById("output").innerHTML = `
        <strong>Welcome ${userName}!</strong><br>
        Age: ${userAge} (${status})<br>
        Location: ${userCity}
    `;
}
```