

SANDIA REPORT

SAND2007-xxxx

Unlimited Release

Printed August 2007

DRAFT: Meros User's Guide ^a

Victoria E. Howle, Robert Shuttleworth, Ray Tuminaro

Prepared by

Sandia National Laboratories

Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia is a multiprogram laboratory operated by Sandia Corporation,
a Lockheed Martin Company, for the United States Department of Energy's
National Nuclear Security Administration under Contract DE-AC04-94-AL85000.

Approved for public release; further dissemination unlimited.

^aFor **Meros**TM Version 2.0 in **Trilinos**TM Release 8.0



Sandia National Laboratories

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from
U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831

Telephone: (865) 576-8401
Facsimile: (865) 576-5728
E-Mail: reports@adonis.osti.gov
Online ordering: <http://www.osti.gov/bridge>

Available to the public from
U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Rd
Springfield, VA 22161

Telephone: (800) 553-6847
Facsimile: (703) 605-6900
E-Mail: orders@ntis.fedworld.gov
Online ordering: <http://www.ntis.gov/help/ordermethods.asp?loc=7-4-0#online>



DRAFT: Meros User's Guide[†]

Victoria E. Howle[‡]

Robert Shuttleworth[§]

Ray Tuminaro[¶]

Abstract

meros abstract

[†]For **Meros**[™] Version 2.0 in **Trilinos**[™] Release 8.0

[‡]Sandia National Laboratories, PO Box 969, MS 9159 Livermore, CA 94551, vehowle@sandia.gov.

[§]Applied Mathematics and Scientific Computing Program and Center for Scientific Computation and Mathematical Modeling, University of Maryland, College Park, MD 20742. rshuttle@math.umd.edu

[¶]Sandia National Laboratories, PO Box 969, MS 9159, Livermore, CA 94551, rstumin@sandia.gov.

Contents

1	Notation	6
2	Introduction	7
3	Block Methods	8
3.1	Pressure Convection-Diffusion (PCD)	8
3.2	Least Squares Commutator (LSC)	8
3.3	SIMPLE	9
4	Examples	10

Appendix

A	Meros configure Options	11
---	-------------------------------	----

1 Notation

% a_really_long_command

The character % indicates any LINUX or UNIX shell prompt. Function names are shown as LSCSchurFactory. Names of packages or libraries as reported in small caps, as EPETRA. Mathematical entities are shown in italics.

2 Introduction

Meros is a segregated preconditioning package. Provides scalable block preconditioning for problems that coupled simultaneous solution variables such as Navier-Stokes problems.

Adding a citation to test bib[1].

3 Block Methods

3.1 Pressure Convection-Diffusion (PCD)

Factory for building pressure convection-diffusion style block preconditioner. This class of preconditioners were originally proposed by Kay, Loghin, and Wathen (ref) and Silvester, Elman, Kay, and Wathen (ref).

Meros 1.0 currently implements the PCD preconditioner, a.k.a. Fp preconditioner.

The LDU factors of a saddle point system are given as follows:

$$\begin{bmatrix} A & B^T \\ B & C \end{bmatrix} = \begin{bmatrix} I & \\ BF^{-1} & I \end{bmatrix} \begin{bmatrix} F & \\ & -S \end{bmatrix} \begin{bmatrix} I & F^{-1}B^T \\ & I \end{bmatrix}, \quad (1)$$

where S is the Schur complement $S = BF^{-1}B^T - C$. A pressure convection-diffusion style preconditioner is then given by

$$P^{-1} = \begin{bmatrix} F & B^T \\ & -\tilde{S} \end{bmatrix}^{-1} = \begin{bmatrix} F^{-1} & \\ & I \end{bmatrix} \begin{bmatrix} I & -B^T \\ & I \end{bmatrix} \begin{bmatrix} I & \\ & -\tilde{S}^{-1} \end{bmatrix} \quad (2)$$

where for \tilde{S} is an approximation to the Schur complement S .

To apply the above preconditioner, we need a linear solver on the (0,0) block and an approximation to the inverse of the Schur complement.

To build a concrete preconditioner object, we will also need a 2x2 block Thyra matrix or the 4 separate blocks as either Thyra or Epetra matrices. If Thyra, assumes each block is a Thyra EpetraMatrix.

3.2 Least Squares Commutator (LSC)

Factory for building least squares commutator style block preconditioner.

Note that the LSC preconditioner assumes that we are using a stable discretization an a uniform mesh.

The LDU factors of a saddle point system are given as follows:

$$\begin{bmatrix} A & B^T \\ B & C \end{bmatrix} = \begin{bmatrix} I & \\ BF^{-1} & I \end{bmatrix} \begin{bmatrix} F & \\ & -S \end{bmatrix} \begin{bmatrix} I & F^{-1}B^T \\ & I \end{bmatrix}, \quad (3)$$

where S is the Schur complement $S = BF^{-1}B^T - C$. A pressure convection-diffusion style preconditioner is then given by

$$P^{-1} = \begin{bmatrix} F & B^T \\ & -\tilde{S} \end{bmatrix}^{-1} = \begin{bmatrix} F^{-1} & \\ & I \end{bmatrix} \begin{bmatrix} I & -B^T \\ & I \end{bmatrix} \begin{bmatrix} I & \\ & -\tilde{S}^{-1} \end{bmatrix} \quad (4)$$

where for \tilde{S} is an approximation to the Schur complement S .

To apply the above preconditioner, we need a linear solver on the (0,0) block and an approximation to the inverse of the Schur complement.

To build a concrete preconditioner object, we will also need a 2x2 block Thyra matrix or the 4 separate blocks as either Thyra or Epetra matrices. If Thyra, assumes each block is a Thyra EpetraMatrix.

3.3 SIMPLE

4 Examples

A Meros configure Options

References

- [1] H. C. ELMAN, D. J. SILVESTER, AND A. J. WATHEN, *Finite Elements and Fast Iterative Solvers*, Oxford University Press, Oxford, 2005.

DISTRIBUTION:

1 An Address
99 99th street NW
City, State

3 Some Address
and street
City, State

12 Another Address
On a street
City, State
U.S.A.

1 MS 1319 Rolf Riesen, 1423

1 MS 1110 Another One, 01400

1 M9999 Someone, 01234

2 MS 9018 Central Technical Files, 8944

2 MS 0899 Technical Library, 4536

