



上海交通大学学位论文

面向 3C 工业生产线的双臂机器人视觉-语言-动作模型

姓名：杨皓然 521111910083

吴律 522370910167

吴毅昕 522370910185

程天纵 522370910227

顾益铭 522370910228

导师：班雨桐

指导教师：黄佩森

学院：浦江国际学院

专业名称：电子与计算机工程

申请学位层次：学士

2026 年 8 月

A Dissertation Submitted to

Shanghai Jiao Tong University for the Degree of Bachelor

VISION-LANGUAGE-ACTION FOR BIMANUAL

INDUSTRIAL MANIPULATIONS

Name:	Yang Haoran	521111910083
	Wu Lv	522370910167
	Wu Yixin	522370910185
	Cheng Tianzong	522370910227
	Gu Yiming	522370910228
Mentor:	Prof. Yutong Ban	
Instructor:	Prof. Peisen Huang	
College:	Global College	

Global College

Shanghai Jiao Tong University

Shanghai, P.R. China

August, 2026

上海交通大学

学位论文原创性声明

本人郑重声明：所呈交的学位论文，是本人在导师的指导下，独立进行研究工作所取得的成果。除文中已经注明引用的内容外，本论文不包含任何其他个人或集体已经发表或撰写过的作品成果。对本文的研究做出重要贡献的个人和集体，已在文中以适当方式予以致谢。若在论文撰写过程中使用了人工智能工具，本人已遵循《上海交通大学关于在教育教学中使用 AI 的规范》，确保人工智能生成内容的应用场景、引用范围及标注方式均符合规定，并杜绝学术不端行为。本人完全知晓本声明的法律后果由本人承担。

学位论文作者签名：杨皓然 吴毅昕 顾彦强
吴律 程天纵

日期：2026 年 8 月 4 日

上海交通大学

学位论文使用授权书

本人同意学校保留并向国家有关部门或机构送交论文的复印件和电子版，允许论文被查阅和借阅。

本学位论文属于：

☒ 公开论文

☐ 内部论文，保密 ☐ 1 年 ☐ 2 年 ☐ 3 年，过保密期后适用本授权书。

☐ 秘密论文，保密 ____ 年（不超过 10 年），过保密期后适用本授权书。

☐ 机密论文，保密 ____ 年（不超过 20 年），过保密期后适用本授权书。

（请在以上方框内选择打“√”）

学位论文作者签名：

指导教师签名：

杨皓然 吴毅昕 顾彦强
吴律 程天纵

黄佩森

日期：2026 年 8 月 4 日

日期：2026 年 8 月 4 日

摘 要

现代 3C 电子装配线需要处理小型元器件、多品种生产和接触密集型操作，而传统固定程序机器人仍难以灵活完成这类任务。本项目针对这一缺口，面向双臂工业操作开发视觉-语言-动作（Vision-Language-Action, VLA）系统。系统运行于双臂 Franka 平台，并完成了三个代表性任务：将带手柄的圆环套放到圆柱罐上、将两脚插头插入两孔插座，以及从主板上取下内存条并放入黄色托盘。

最终部署系统采用在三个任务上联合训练的统一 $\pi_{0.5}$ 检查点，接收数据包关联的多视角观测、16 维双臂机器人状态和自然语言任务指令，并在闭环执行过程中输出双臂及夹爪动作。三个任务均由同一个检查点执行，并分别输入对应的任务指令。结果表明，一个统一检查点可以在双臂平台上执行多项任务。

最终实机验证对每项任务进行了 25 次试验，共计 75 次。圆环任务、插头插入任务和内存条任务的成功率分别为 84%、52% 和 100%，总体成功率为 78.7%。规划、元件检测、失败检测和自动恢复分别采用独立的 25 次实验，其中失败检测与自动恢复使用两组不同的实验，所得成功率分别为 92%、96%、92% 和 92%。全部 59 次成功完成的任务均满足 ES4 的 20 mm 位置误差要求。六项工程指标均达到项目规定的阈值，但插头插入任务未能单独达到 70% 的任务执行目标，表明精细对准与插入仍是当前系统的主要改进方向。

关键词：双臂机器人，视觉-语言-动作模型，工业自动化

ABSTRACT

Modern 3C electronics assembly lines deal with small components, high product variety, and contact-rich operations that remain difficult to automate with conventional fixed-program robots. This project targets this gap by developing a Vision-Language-Action (VLA) system for bimanual industrial manipulation. The system runs on a dual-arm Franka platform and performs three representative tasks: placing a handled ring over a can, inserting a two-pin plug into a two-hole socket, and removing a memory module from a motherboard and placing it in a yellow tray.

The final deployed system uses a unified $\pi_{0.5}$ checkpoint trained jointly across the three tasks. It receives packet-associated multi-view observations, a 16-dimensional bilateral robot state, and a natural-language task instruction, and outputs bimanual robot and gripper actions during closed-loop execution. All three tasks were executed by the same checkpoint with their corresponding task instructions, demonstrating unified multi-task bimanual deployment on the physical workcell.

The final physical validation comprised 25 trials per task and 75 trials in total. The ring, plug-insertion, and memory-module tasks achieved success rates of 84%, 52%, and 100%, respectively, producing an overall success rate of 78.7%. Planning, component detection, failure detection, and automatic recovery used independent 25-experiment test sets; failure detection and recovery were evaluated on two different groups. Their observed rates were 92%, 96%, 92%, and 92%, respectively. All 59 completed tasks satisfied the ES4 positional tolerance of 20 mm. All six project-level metrics met their stated thresholds, although plug insertion did not independently meet the 70% execution target and remains the main area for improvement.

Key words: dual-arm robot, vision-language-action model, industrial automation

Contents

摘 要	I
ABSTRACT	II
Chapter 1 Introduction	1
1.1 Background and significance	1
1.2 Design problem	2
1.3 Project objectives and scope	3
1.4 Main contributions	3
1.5 Organization of this thesis	4
Chapter 2 Design specification	5
2.1 Customer requirements	5
2.2 Engineering specifications	6
2.3 Quality function deployment	6
Chapter 3 Concept generation and selection	8
3.1 Concept generation	8
3.1.1 Research landscape of imitation learning and vision-language-action models ...	8
3.1.2 Functional decomposition	14
3.1.3 Structured brainstorming	14
3.1.4 Morphological chart and generated module concepts	15
3.2 Concept selection	16
3.2.1 Selection method and QFD-derived criteria	16
3.2.2 Scoring of the five selected module concepts	16
3.2.3 Comparative evaluation and selected concept	18
Chapter 4 Final design and implementation	20
4.1 Final design and engineering changes	20
4.1.1 Design evolution and engineering change record	20

4.1.2	Overall system architecture and VLA formulation	21
4.1.3	Selected modules and operational workflow	23
4.2	Engineering design analysis	27
4.2.1	Mechanical and kinematic design	27
4.2.2	Perception, teleoperation, and data collection	32
4.2.3	Dataset design and task-balanced training	35
4.2.4	$\pi_{0.5}$ objective, adaptation, and training	37
4.2.5	Validation, action chunking, and deployment boundary	40
4.3	Detailed system design	42
4.3.1	Physical workcell and sensing	42
4.3.2	Data, training, and deployment interfaces	44
4.3.3	Task definitions and system operation	47
4.4	Prototype manufacturing and implementation	49
4.4.1	Fabrication, assembly, and system integration	49
4.4.2	Budget, provenance, and reproducibility	53
Chapter 5	Validation results	55
5.1	Validation objectives and scope	55
5.2	Validation design and engineering-specification mapping	56
5.2.1	Measurement rules and independent denominators	56
5.2.2	Observed specification-level outcomes	57
5.3	Checkpoint selection and deployment configuration	57
5.3.1	Selection criterion	57
5.3.2	Validation trajectory	58
5.3.3	Deployment hardware	60
5.4	Physical trial protocol and success definition	60
5.5	Overall physical results	61
5.5.1	Descriptive uncertainty of the observed rates	62
5.6	Task-specific results and failure analysis	62
5.6.1	Memory-module removal and tray placement	62
5.6.2	Ring placement over the can	64
5.6.3	Two-pin plug grasping and two-hole socket insertion	64

5.7	Planning, detection, failure-detection, and recovery results	65
5.7.1	Rate-based engineering specifications	65
5.8	Cross-task interpretation.....	66
5.8.1	Requirements-level interpretation.....	66
5.9	Validation summary	67
Chapter 6 Discussion and conclusions		68
6.1	Discussion	68
6.2	Conclusions	69
Chapter 7 Future Work		71
7.1	Improve plug alignment and insertion	71
7.2	Improve safe-space estimation	71
7.3	Expand data coverage and model evaluation	71
7.4	Improve language conditioning and task generalization	72
7.5	Preserve the deployment package	72
References.....		73
Appendix 1. Documentation of Generated Concepts		75
Appendix 2. Hardware Specifications and Parts Records		78
Appendix 3. Statement on the Use of Artificial Intelligence Tools		87
Acknowledgements		88

Chapter 1 Introduction

1.1 Background and significance

The 3C industry—computer, communication, and consumer electronics—increasingly demands flexible robotic systems that can cope with short product life cycles, diverse part geometries, small components, and frequent line changeovers. Traditional hard-coded automation approaches are effective for stable, high-volume production, but they exhibit significant limitations in high-mix assembly scenarios. Each product variant typically requires reprogramming, fixture redesign, and system reconfiguration, which increases development and maintenance costs. In contrast, human operators can rapidly understand new tasks from natural-language instructions and adapt to new operating conditions with limited prior programming. This contrast highlights the importance of advancing industrial robotic systems toward more human-aligned capabilities, especially semantic understanding of instructions and data-efficient adaptation under limited demonstrations.

Recent advances in Vision-Language-Action (VLA) models offer a promising route toward this goal. By jointly learning from visual observations, language instructions, robot proprioceptive states, and action data, VLA models can in principle generalize across tasks without requiring separate hand-engineered programs for every product variant. Landmark systems, including RT-2, OpenVLA, RDT-1B, and the π series, demonstrate the potential of transferring semantic knowledge from large vision-language models to physical robot control^[1-4]. Earlier work on visual and language-conditioned manipulation also established complementary design patterns: Transporter Networks use spatially grounded pick-and-place representations, CLIPort combines semantic and spatial pathways, and PerAct couples language goals to structured visual observations^[5-7]. In parallel, BridgeData V2, Open X-Embodiment, DROID, and LIBERO have made dataset scale, embodiment diversity, and reproducible task evaluation central considerations in robot-learning system design^[8-11].

Despite this progress, adapting VLA-style systems to industrial assembly remains a system-level engineering problem. Many published demonstrations emphasize tabletop manipulation, single-arm control, or short-horizon tasks with relatively forgiving tolerances. In contrast, 3C assembly requires reliable perception of small components, accurate contact-rich

manipulation, packet-associated multi-view observations, safe robot execution, and repeatable physical validation. These requirements motivate a complete manipulation pipeline that links hardware selection, teleoperation, data collection, model training, deployment, and quantitative evaluation.

1.2 Design problem

This project develops a dual-arm industrial manipulation platform that couples camera observations, natural-language task instructions, and robot proprioceptive state to learned bilateral actions. The workcell consists of two Franka Research 3 (FR3) robot arms, one fixed overhead camera, two wrist cameras, two custom grippers, and two GELLO leader devices for demonstration collection. Demonstrations contain packet-associated multi-view observations, bilateral robot and gripper states, absolute target actions, and task instructions.

The implemented task set contains three bimanual manipulation sequences. In the first task, the left arm pushes a can to the middle while the right arm grasps a handled black ring, places it over the can, and releases it. In the second task, the right arm pushes a box containing a power socket to the middle while the left arm grasps a plug and inserts it into the socket. In the third task, the left arm pulls and stabilizes a computer motherboard while the right arm removes the memory module and places it in a yellow tray. The first task serves as a structured reposition–grasp–place benchmark, while the latter two represent constrained connector and computer-component operations.

The final controller is the LeRobot implementation of $\pi_{0.5}$, initialized from the official `pi05_base` checkpoint^[12-15]. One jointly trained checkpoint is shared by all three tasks. At deployment, the same policy receives one of the documented natural-language instructions, three RGB observations, and the current 16-dimensional bilateral state, then predicts absolute targets for both arms and both grippers. The completed implementation therefore provides language-conditioned task input, unified multi-task inference, and dual-arm action generation within the three bounded workcell tasks.

1.3 Project objectives and scope

The project objective is to establish an end-to-end engineering pipeline for bimanual industrial-manipulation experiments. This pipeline includes hardware integration, packet-associated multi-view observations, bilateral teleoperated demonstration collection, LeRobot Dataset v3.0 preparation, joint multi-task $\pi_{0.5}$ fine-tuning, language-conditioned deployment, and repeatable physical validation of the three tasks.

The engineering acceptance targets inherited from the design-specification stage are planning success above 90%, task execution success above 70%, component detection accuracy above 90%, terminal placement/alignment tolerance below 20 mm, failure-detection rate above 90%, and recovery success above 70%. Chapter 5 reports 25 experiments for planning and component detection, two independent sets of 25 experiments for failure detection and recovery, and 25 physical trials for each of the three tasks. All completed task trials satisfy the task-specific 20 mm positional tolerance used for ES4.

1.4 Main contributions

The main contributions of this thesis are as follows:

1. A dual-FR3 manipulation platform is integrated with GELLO teleoperation, packet-associated multi-view observations, robot-state recording, and task-compatible end effectors and fixtures.
2. A reproducible data and learning pipeline converts 240 bilateral teleoperated episodes into three LeRobot Dataset v3.0 task datasets with episode-level training and validation splits, equal-probability task sampling, and a common absolute-action representation.
3. A single language-conditioned LeRobot $\pi_{0.5}$ checkpoint is fine-tuned and deployed for three bimanual tasks using three RGB views, a 16-dimensional bilateral state, and a 16-dimensional bilateral action interface.
4. A specification-led physical-validation framework maps ES1–ES6 to explicit operational definitions, separate denominators, task-specific terminal conditions, uncertainty estimates, failure stages, and pass/fail judgments.
5. A traceable engineering process links customer requirements and quality function deployment to concept generation, module selection, implementation decisions, and val-

idation criteria.

1.5 Organization of this thesis

The remainder of this thesis is organized as follows. Chapter 2 translates customer requirements into measurable engineering specifications and presents the quality function deployment. Chapter 3 describes functional decomposition, concept generation, and selection of the major hardware, sensing, teleoperation, end-effector, and policy modules. Chapter 4 details the final system design, data and control architecture, model-training procedure, and implementation plan. Chapter 5 presents the physical validation methods and experimental results. Chapter 6 discusses the strengths and limitations of the system and summarizes the project conclusions. Chapter 7 presents system-level and implementation-level recommendations for future development.

Chapter 2 Design specification

2.1 Customer requirements

Through discussions with the project sponsor and analysis of the target application, eight customer requirements were identified and assigned importance weights reflecting the sponsor's priorities. The requirements capture both functional goals and non-functional concerns, including robustness, safety, generalizability, cost, and reliability.

Table 2–1 Customer requirements and importance weights

No.	Customer Requirement	Weight
CR1	Complete assembly task successfully	0.18
CR2	High assembly precision	0.16
CR3	Robust to environment and disturbances	0.15
CR4	Safe and collision-free operation	0.14
CR5	Fast task execution	0.12
CR6	Easy to use and generalize	0.10
CR7	Cost-effective system	0.08
CR8	System reliable and recovery capable	0.07

The customer requirements were translated into engineering specifications through the QFD process rather than by assigning targets independently. For each customer requirement i and engineering specification j , the team assigned a relationship value $r_{ij} \in \{0, 1, 3, 9\}$ (none, weak, moderate, or strong) and calculated the unnormalized engineering priority as

$$I_j = \sum_i w_i r_{ij}, \quad (2-1)$$

where w_i is the customer-importance weight in Table 2–1. The priorities were then normalized to identify the technical characteristics that most directly protect the high-weight needs. CR1 and CR5 primarily drive ES1 and ES2; CR2 drives ES3 and ES4; CR3, CR4, and CR8 drive ES5 and ES6; and CR6–CR7 constrain the selected implementation to a usable, feasible, and maintainable route. This translation produces an auditable chain from the sponsor's language to acceptance tests and explains why the later concept search is organized around platform, teleoperation, data collection, gripper, and policy modules.

2.2 Engineering specifications

The customer requirements were converted into six measurable engineering specifications. The targets in Table 2–2 are the final acceptance thresholds for the present proof-of-concept. Each rate is calculated over independently initialized physical trials of the relevant task. ES5 and ES6 use two independent sets of 25 experiments: one set evaluates failure detection and the other evaluates recovery from initialized failure states.

Table 2–2 Final engineering specifications and acceptance thresholds

No.	Engineering Specification	Target	Operational Definition
ES1	Planning success rate	> 90%	Fraction of trials in which the selected task policy and initialized scene form a valid executable plan.
ES2	Task execution success rate	> 70%	Fraction of trials in which the prescribed assembly operation reaches its task-specific completion condition.
ES3	Component detection accuracy	> 90%	Fraction of evaluated observations in which the required component is correctly detected for the active task.
ES4	Pose estimation error	< 20 mm	Completed tasks satisfy the task-specific positional tolerance defined by the fixture and terminal condition.
ES5	Failure detection rate	> 90%	Fraction of induced or naturally occurring execution failures that are identified before further unsafe action is issued.
ES6	Recovery rate	> 70%	Fraction of 25 independently initialized recovery experiments in which the automatic recovery procedure restores a valid task state.

ES4 is assessed from the completion geometry of each task. Ring placement, plug insertion, and memory-module placement can only be accepted when the component lies within the task-specific 20 mm positional tolerance. Each completed trial is therefore counted as meeting ES4, while overall task completion is reported separately under ES2.

2.3 Quality function deployment

Figure 2–1 records the resulting House of Quality. Its 9–3–1 relationship scale links task completion, component localization, pose estimation, and failure handling to the customer requirements. Additional packet-associated multi-view observations can strengthen ES3 and

ES4 while increasing calibration and data-management effort. Recovery logic supports ES5–ES6 while adding controller integration work. These trade-offs define the subsequent concept space: the platform and gripper enable precise contact motion, the teleoperator and data pipeline produce usable demonstrations, and the policy converts those observations into safe executable actions.

		Task Execution Success Rate (%)	Pose Error (mm)	Failure Detection Rate (%)	Recovery Success Rate (%)	Component Detection Accuracy (%)	Planning Success Rate (%)
	Weight (1-10)						
Complete assembly task successfully	0.18	9	3	3	3	3	9
High assembly precision	0.16	3	9	1	1	9	3
Robust to environment and disturbances	0.15	3	3	9	9	3	1
Safe operation	0.14	3	1	3	3	1	1
Fast task execution	0.12	3	1	1	1	1	3
Easy to use and generalize	0.10	1	3	3	3	3	9
Cost-effective system	0.08	1	1	1	1	1	1
System reliable and recovery capable	0.07	3	1	9	9	1	3
Absolute Importance(Sum)		372	314	360	360	314	394
Relative Importance(%)		17.6	14.9	17.0	17.0	14.9	18.6
Rank(1=Highest)		2	5	3	3	5	1
Benchmark		0.85	3.2mm	0.85	0.75	0.92	0.88
Target		>70%	<20mm	>90%	>70%	>90%	>90%

Illustration 2–1 QFD House of Quality for the VLA bimanual manipulation system.

Chapter 3 Concept generation and selection

3.1 Concept generation

3.1.1 Research landscape of imitation learning and vision-language-action models

Robot-learning methods for manipulation have developed along several related directions: demonstration-based visuomotor learning, temporal action-generation models, language-conditioned manipulation, and general-purpose vision-language-action (VLA) policies. These directions differ in the supervision they require, the observations they consume, the form in which they represent actions, and the extent to which one policy can cover multiple tasks. Reviewing them is important for concept generation because a policy cannot be selected independently of the demonstration interface, sensing arrangement, robot embodiment, and deployment constraints. In this project, the literature therefore defines the feasible policy and data-collection alternatives, while the QFD priorities and available dual-FR3 workcell determine which alternative is carried into implementation.

The field does not provide one universally superior controller. A method that performs well on broad tabletop benchmarks may still be unsuitable for contact-rich 3C assembly if its camera contract, action representation, inference rate, or robot interface cannot be reproduced on the target workcell. Conversely, a narrower imitation-learning method may be easier to deploy and validate but may require a separate checkpoint for each task. The relevant research landscape must consequently be interpreted as a set of engineering trade-offs rather than as a ranking based on headline benchmark values obtained under different embodiments and evaluation protocols.

3.1.1.1 Demonstration-based visuomotor learning

Imitation learning provides a direct route from human demonstrations to robot control. In its simplest form, behavior cloning learns a mapping from an observation and robot state to the action demonstrated by an operator. This formulation avoids the need to specify a reward function or to explore unsafe actions on the physical robot, which is attractive for industrial workcells. Its main limitation is distribution shift: small prediction errors can move the robot away from states represented in the demonstration data, after which later

predictions may become unreliable. Dataset coverage, action consistency, camera placement, episode screening, and the treatment of unsuccessful demonstrations are therefore part of the controller design rather than merely data-preparation details.

Robomimic showed that observation representation, training configuration, and demonstration quality materially affect offline robot-learning performance, making reproducible dataset construction a first-order design decision^[16]. MimicGen extends this direction by generating additional demonstrations from a smaller set of human examples, illustrating how task structure and data generation can be used to improve coverage without requiring every trajectory to be collected manually^[17]. These approaches motivate explicit episode boundaries, validation splits, and data-quality checks in a physical manipulation pipeline.

The demonstration interface also determines what action distribution can be learned. GELLO uses a low-cost joint-space leader whose kinematic correspondence with the follower robot supports intuitive trajectory collection^[18]. UMI instead emphasizes portable, in-the-wild demonstration capture and a reusable manipulation interface^[19]. These systems address different collection conditions, but both demonstrate that operator ergonomics, calibration, and mapping consistency affect the resulting dataset. For a fixed dual-FR3 work-cell, a joint-master interface offers a comparatively direct path to bilateral joint and gripper targets, whereas hand-held or immersive interfaces require an additional motion-retargeting layer. This distinction informed the teleoperation alternatives retained in the morphological chart.

3.1.1.2 Temporal imitation-learning and diffusion policies

Manipulation actions are temporally correlated, and predicting one independent command at a time can produce jitter or amplify short-term errors. Action Chunking with Transformers (ACT) addresses this issue by predicting a sequence of future actions and using a conditional variational formulation to represent variation among demonstrations^[20]. Action chunks can improve temporal coherence and reduce the effective prediction horizon for fine-grained manipulation. ACT is especially relevant to bimanual systems because the same output sequence can contain coordinated targets for both arms and grippers. Its practical advantages include a well-defined supervised-learning objective and an established route through LeRobot. Its principal limitation for the present application is that the conventional deployment route is task-specific: changing the requested operation normally requires selecting a

different checkpoint or adding a separate task-conditioning mechanism.

Diffusion Policy treats visuomotor control as conditional denoising over action trajectories^[21]. Rather than committing to one deterministic action in a potentially multimodal situation, the policy iteratively transforms noise into an action sequence conditioned on the current observation. Receding-horizon execution then allows the robot to execute part of the sequence and replan from updated observations. This structure is attractive for manipulation tasks in which several approach paths may be valid, but iterative denoising can increase inference cost and integration complexity. The final control quality also depends on whether the observation representation preserves the geometry needed near contact.

Subsequent work expands diffusion-based control toward richer spatial representations and larger-scale bimanual models. 3D Diffusion Policy incorporates compact three-dimensional observations to improve geometric reasoning and cross-task generalization^[22]. RDT-1B develops a diffusion foundation model specifically for bimanual manipulation and combines language, image, and proprioceptive inputs with a scalable action-generation architecture^[3]. These methods make diffusion policies strong candidates for contact-rich and bilateral tasks, but their reported results cannot be transferred directly to the present workcell without matching the camera observations, robot state, action convention, training data, and deployment interface. They were therefore treated as concept alternatives rather than assumed performance baselines.

3.1.1.3 Language-conditioned manipulation and visual representation

Before large VLA policies, several methods established how semantic instructions and spatial observations could be connected to robot actions. Transporter Networks represent pick-and-place actions through spatial feature transport, providing a strong inductive bias for rearrangement tasks^[5]. CLIPort combines a semantic pathway associated with language-conditioned object selection and a spatial pathway associated with precise placement^[6]. Per-Act maps language goals and RGB-D observations into a structured three-dimensional action representation, showing how language-conditioned manipulation can be formulated in a voxelized workspace^[7]. These methods are narrower than a general VLA policy, but they clarify an important design principle: semantic task understanding and local geometric precision are distinct requirements that may benefit from different observation representations.

Research on reusable visual features and multi-view geometry provides a complementary

perspective. R3M learns visual representations intended to transfer across downstream robot-manipulation tasks^[23], while RVT uses multi-view transformer representations for three-dimensional manipulation^[24]. Their relevance to the present project lies in the justification for combining global and wrist-local observations. A fixed overhead view preserves scene context and object relationships, whereas wrist views preserve detail near grasping and insertion. Camera placement and packet-associated multi-view observations are therefore considered together with policy selection.

3.1.1.4 Generalist vision-language-action models

VLA models extend language-conditioned manipulation by learning a common interface among visual observations, natural-language instructions, robot state, and continuous or tokenized actions. RT-2 demonstrated that knowledge represented in a vision-language model can be transferred to robot control by expressing actions in a token-compatible form and co-training on web and robot data^[1]. This line of work suggests that semantic knowledge acquired outside a single robot dataset can support task interpretation. However, semantic transfer does not by itself guarantee the millimetre-scale alignment, contact stability, or deterministic safety required by industrial insertion tasks.

OpenVLA provides an open-source VLA model and training route, making generalist robot policies more accessible for adaptation and comparative research^[2]. Its importance to concept generation is not simply model scale; it demonstrates a practical route for conditioning robot actions on images and language without designing a separate semantic module for each task. At the same time, adapting a general VLA model to a new embodiment still requires compatible action data, normalization, observation naming, and sufficient demonstrations of the target robot and task distribution.

The π family uses a flow-based action-generation approach for general robot control. The π_0 model combines vision-language representations with an action expert and predicts continuous robot actions through flow matching^[4]. The later $\pi_{0.5}$ model extends this direction toward open-world generalization and heterogeneous robot data while retaining language-conditioned action generation^[12]. The availability of OpenPI and a LeRobot $\pi_{0.5}$ integration further reduces the engineering distance between the published model and a reproducible project implementation^[13,15]. This software path is relevant because the final system requires not only a capable model family but also a concrete method for mapping three named camera

observations and a bilateral state vector to admissible dual-arm actions.

Generalist models nevertheless introduce limitations that are especially important in 3C assembly. Their broad semantic capability may exceed what is needed for three bounded tasks, while their computation and data requirements are greater than those of a small task-specific policy. Action chunks can also create an interval between observations during which local contact errors are not corrected. In addition, a probabilistic learned policy does not replace deterministic joint limits, workspace checks, emergency-stop handling, or robot-controller protections. These considerations mean that selecting a VLA model is a system decision involving data, sensing, temporal execution, and safety boundaries rather than a model-only upgrade.

3.1.1.5 Datasets, embodiment diversity, and evaluation

The development of general robot policies has been enabled by larger and more diverse datasets. BridgeData V2 provides a broad collection of manipulation trajectories and illustrates the value of task and scene diversity for reusable policies^[8]. Open X-Embodiment aggregates data across multiple robot embodiments and supports research on cross-embodiment transfer^[9]. DROID emphasizes large-scale, in-the-wild data collection across varied scenes, tasks, and operators^[10]. Together, these datasets shift the field from learning one behavior from one narrowly collected dataset toward pretraining representations and policies that can be adapted to new tasks.

Scale alone does not remove embodiment mismatch. Robots differ in kinematics, grippers, camera placement, control frequency, state definitions, and action conventions. A policy pretrained on heterogeneous data still requires a precise feature contract when deployed on a dual-FR3 system. Local demonstrations remain necessary to represent the target fixtures, object tolerances, bilateral role allocation, and absolute joint and gripper commands. Dataset balance is also important in multi-task training: without task-level sampling control, a task with longer episodes or more frames may dominate optimization even when all tasks should carry equal engineering importance.

Evaluation protocols must similarly separate offline agreement from physical task completion. LIBERO provides a benchmark for studying transfer and lifelong learning across language-conditioned manipulation tasks^[11], but benchmark success under a simulated or standardized setting is not equivalent to end-to-end success on a physical industrial work-

cell. Offline losses are useful for checkpoint selection, while real-robot trials are required to evaluate grasping, alignment, insertion, collision-free execution, and task-specific terminal conditions. This distinction prevents literature benchmarks from being presented as measured evidence for the final hardware system.

3.1.1.6 Comparison and implications for concept generation

Table 3–1 summarizes the principal research directions that informed the policy and sensing concept space. The comparison is qualitative because the cited methods use different robots, datasets, action spaces, and evaluation protocols. It records the engineering role of each family.

Table 3–1 Representative robot-learning directions relevant to concept generation

Direction	Representative methods	Primary inputs	Main strength	Limitation and project relevance
Spatial visuomotor learning	Transporter, CLIPort, PerAct ^[5-7]	Images, language, or structured 3D observations	Explicit semantic and spatial structure for object selection and placement	Provides design principles for perception and language grounding, but does not directly supply the implemented continuous bilateral action interface.
Sequence imitation learning	ACT ^[20]	Multi-view images and robot state	Temporally coherent action chunks and an established bimanual imitation-learning route	Practical DR3 baseline, but conventionally task-specific and dependent on demonstration coverage.
Diffusion control	Diffusion Policy, 3D Diffusion Policy, RDT-1B ^[3,21-22]	2D or 3D observations, state, and optionally language	Models multimodal action sequences and supports receding-horizon control	Strong policy alternative, with additional inference, representation, and workcell-integration requirements.
Generalist VLA	RT-2 and OpenVLA ^[1-2]	Images, language, and robot actions or state	Transfers semantic knowledge and supports a common language-conditioned policy interface	Broad capability does not guarantee local contact precision or compatibility with the target robot action schema.
Flow-based VLA	π_0 and $\pi_{0.5}$ ^[4,12]	Multi-view images, language, and proprioceptive state	Continuous action generation with a route to multi-task and multi-embodiment adaptation	Selected policy direction; requires local dual-FR3 data, strict feature mapping, and deterministic execution checks.
Large-scale robot data	BridgeData V2, Open X-Embodiment, DROID ^[8-10]	Heterogeneous demonstrations	Improves diversity and supports pretraining across tasks and robots	Does not replace task-specific data for the final fixtures, cameras, grippers, and bilateral action convention.

The literature leads to three implications for the present concept generation. First, the demonstration interface and observation pipeline must be selected together with the policy because they define the data distribution and feature contract available for learning. Second, ACT, diffusion policies, and VLA models represent credible but different trade-offs among deployment maturity, multimodal action generation, language conditioning, and computational burden. Third, an industrial proof-of-concept must evaluate the selected model on its own physical terminal conditions rather than infer performance from results reported on other embodiments.

These implications define the candidate space used below. ACT is retained as a mature action-chunking baseline, Diffusion Policy as an alternative trajectory-generation family, and $\pi_{0.5}$ as the language-conditioned route aligned with unified multi-task control. GELLO, multi-view RGB sensing, bilateral state and action recording, and deterministic robot-side checks complement these policy alternatives. The following functional decomposition converts this research-informed space and the QFD priorities into the five modules used for structured concept generation and selection.

3.1.2 Functional decomposition

The target assembly system was first decomposed into solution-neutral functions: establish the workspace state; create a stable robot–operator interface for demonstrations; record packet-associated multi-view observations, proprioceptive state, and actions; grasp and constrain the component during contact; map the current observation to coordinated motion; and detect or recover from an invalid execution state. The decomposition converts the QFD priorities into five design modules. The robot platform provides repeatable bimanual motion for ES1, ES2, and ES4; the teleoperation module enables usable demonstrations; the data-collection module supports ES3–ES4 and learning reproducibility; the gripper realizes component contact; and the policy maps observations and state to actions. Failure monitoring and recovery operate across the collection and deployment loop.

3.1.3 Structured brainstorming

The team generated alternatives for each module before choosing a configuration. Candidate ideas were retained when they addressed at least one QFD-linked specification and

did not violate laboratory safety, hardware access, or the project schedule. The session considered the available FR3 ecosystem alongside Flexiv and ALOHA-style platforms; direct joint-master, XR, and hand-held teleoperation; progressively richer observation schemas; compliant and rigid end-effectors; and policy families including Diffusion Policy, ACT, and the $\pi_{0.5}$ VLA model. This procedure deliberately separates the choice of a data-collection interface from the choice of a learning algorithm, since neither can be justified independently of the sensing and robot-control path.

The generated alternatives were also informed by established research directions rather than by ad hoc feature lists. Robomimic and MimicGen motivate treating demonstration quality and dataset construction as system-level design variables^[16-17]; RVT, 3D Diffusion Policy, and R3M respectively motivate the retained alternatives for multi-view geometry, 3D visuomotor control, and reusable robot visual representations^[22-24]. These references define the external concept space, while the selected configuration remains constrained by the laboratory hardware, the QFD priorities, and the project schedule.

3.1.4 Morphological chart and generated module concepts

Table 3–2 records the resulting concept space. A row represents one functional module, and a column entry represents one candidate realization. The bold entry in each row is the selected module concept; the table is not a claim that the unselected entries were all built or experimentally benchmarked.

Table 3–2 Morphological chart for the five functional modules

Concept	Candidate A	Candidate B	Candidate C
C1: Platform	Dual Franka FR3	Dual Flexiv platform	ALOHA-style bimanual platform
C2: Teleoperator	GELLO joint-master	PICO 4 Ultra XR	UMI hand-held
C3: Data collection	Two wrist + one top camera + robot state/action	One wrist + one top camera + robot state/action	Robot state/action only
C4: Gripper	Franka parallel gripper	3D-printed hard gripper	3D-printed soft gripper
C5: Policy	ACT in LeRobot	$\pi_{0.5}$ VLA in LeRobot	Diffusion policy

The morphological chart produces five leading module concepts, denoted C1–C5. C1 is a dual-FR3 platform; C2 is GELLO-based teleoperation; C3 records packet-associated multi-view observations together with robot state and actions; C4 is a 3D-printed soft gripper; and C5 is a unified $\pi_{0.5}$ VLA policy integrated through LeRobot. Together they form one integrated system concept. Their alternatives expose trade-offs in platform precision, operator interface, observation coverage, contact compliance, and policy capability. Detailed descriptions of the alternatives are provided in the appendix.

3.2 Concept selection

3.2.1 Selection method and QFD-derived criteria

Selection was conducted in two stages. First, an absolute screen removed a candidate if it could not be made safe in the laboratory, could not interface with the selected robot and data path, or could not be obtained and integrated within the project schedule. Second, the surviving alternatives were scored on a five-point ordinal scale, where 1 denotes a weak fit and 5 denotes a strong fit. Ratings were assigned from the QFD relationship to ES1–ES6, laboratory availability and interface knowledge, the existing collection workflow, and the cited primary or official sources; no rating is presented as an unreported benchmark result. Consistent with the functional decomposition, the “top five concepts” are the five selected module concepts C1–C5. Their combination forms the single system concept carried into the final design. For candidate a in module m , the decision score is

$$S_{m,a} = \sum_{k=1}^4 w_k r_{m,a,k}, \quad (3-1)$$

where $r_{m,a,k}$ is the rating for criterion k and w_k is its QFD-derived weight. Scores are used only to compare alternatives within the same module; they are recorded design judgments, not measured task-performance results.

3.2.2 Scoring of the five selected module concepts

Table 3–4 provides the detailed selection record for the five leading module concepts. The same criterion definitions and weights are applied in every module so that the scoring logic remains traceable to the QFD; however, the totals are interpreted only within a module

Table 3–3 QFD-derived criteria for module selection

No.	Criterion	Weight	QFD Link
SC1	Contribution to task performance and precision	0.30	ES1, ES2, ES3, ES4
SC2	Data, control, and software integration compatibility	0.25	ES1, ES2, ES3
SC3	Safety, robustness, and recovery support	0.20	ES5, ES6; CR3–CR4
SC4	Availability, manufacturability, and schedule feasibility	0.25	CR6–CR7 and project plan

because a robot platform, a gripper, and a policy make different contributions to the integrated system.

Table 3–4 Module-level concept selection matrix (1 = weak fit; 5 = strong fit)

Module	Candidate	SC1	SC2	SC3	SC4	Weighted score
C1 Platform	Dual Franka FR3	5	5	4	3	4.30
	Dual Flexiv	4	3	4	2	3.30
	ALOHA-style bimanual	3	4	3	5	3.85
C2 Teleoperator	GELLO joint-master	4	5	4	5	4.50
	PICO 4 Ultra XR	3	3	3	4	3.25
	UMI hand-held	3	3	3	4	3.25
C3 Data collection	Two wrist + top camera + state/action	5	5	4	3	4.35
	One wrist + top camera + state/action	4	4	4	5	4.20
	Robot state/action only	2	3	3	5	3.25
C4 Gripper	3D-printed soft gripper	4	4	4	5	4.20
	Franka parallel gripper	3	5	4	3	3.70
	3D-printed hard gripper	4	5	3	4	4.05
C5 Policy	$\pi_{0.5}$ VLA in LeRobot	5	5	4	4	4.55
	ACT in LeRobot	4	5	4	5	4.50
	Diffusion Policy	4	3	4	4	3.75

3.2.3 Comparative evaluation and selected concept

C1: Dual Franka FR3 platform. The dual Franka FR3 platform was selected as the mechanical foundation of the final system because it provides repeatable 7-DoF control, a direct connection to the available laboratory control ecosystem, and a credible path toward coordinated bimanual manipulation. Its principal disadvantage is the substantial integration effort required for workspace coordination, collision avoidance, commissioning, and bilateral control. Nevertheless, these costs are justified by the project objective: lower-cost alternatives may reduce initial hardware burden, but they would introduce a different control ecosystem or provide a weaker fit to the required assembly precision.

C2: GELLO teleoperation. GELLO was selected and implemented as the demonstration-collection interface because it offers a direct and intuitive connection between operator motion and the robot-state/action records required by the learning pipeline^[18]. Despite the need for reliable leader-follower mapping and calibration, GELLO remains preferable to immersive or hand-held alternatives for the present system because it provides the most direct route from teleoperated demonstrations to the joint-space data representation used by the FR3 and LeRobot workflow.

C3: Three-camera data pipeline. The selected sensing configuration uses one Intel RealSense D435 overhead camera and two Intel RealSense D405 wrist-mounted cameras. The recorder combines their images with robot state, gripper state, and actions as packet-associated multi-view observations. The D435 provides a stable global view of the shared workspace, while the two D405 cameras preserve local visual information near the end-effectors and contact regions. This arrangement reduces visual blind spots and supports the component-detection and positioning requirements in ES3–ES4.

C4: 3D-printed soft gripper. The selected end-effector is a 3D-printed soft gripper derived from the open-source gripper design in the referenced UMI material; the project adopts only the gripper-finger component rather than reproducing the complete UMI hardware system^[19]. Compliant contact and rapid geometry iteration are valuable for handling assembly components with small geometric variation, although deformation may reduce pose repeatability compared with a rigid locating gripper.

C5: Unified $\pi_{0.5}$ VLA policy in LeRobot. ACT was initially selected as the task-specific policy baseline through the existing LeRobot workflow^[14,20]. The final implementation uses

LeRobot $\pi_{0.5}$ ^[12-13,15], which receives packet-associated multi-view observations, the bilateral robot state, and a language instruction, then predicts bilateral robot and gripper actions. One jointly trained checkpoint is used for the ring, plug-insertion, and memory-module tasks. The 75 physical trials reported in Chapter 5 validate unified multi-task bimanual deployment under three fixed scene–instruction configurations. Because scene and instruction were not varied independently, the evaluation does not isolate the contribution of language or establish sensitivity to instruction variation.

The selected architecture is the combination of the highest-scoring surviving candidate in each module. C1 and C4 establish the physical capability for controlled contact; C2 and C3 make demonstrations and visual evidence available to the learner; and C5 provides the deployable policy path. This combined decision covers the full ES1–ES6 chain while retaining a feasible implementation route for subsequent final design, manufacturing, and validation.

Chapter 4 Final design and implementation

4.1 Final design and engineering changes

4.1.1 Design evolution and engineering change record

The final implementation retains the modular physical architecture selected in Design Review 3 (DR3), but the learning system and demonstrated scope have changed substantially. DR3 proposed a dual-Franka Research 3 (FR3) workcell, GELLO demonstration collection, two wrist cameras and one overhead camera, custom compliant fingers, a LeRobot dataset, and an imitation-learning policy. At that stage, Action Chunking with Transformers (ACT) and task-specific checkpoints were the deployable baseline. Language-conditioned bimanual control was a future objective.

The completed system replaces the task-specific ACT controller with the LeRobot implementation of $\pi_{0.5}$. It uses two FR3 arms, two grippers, three RGB views, a 16-dimensional bilateral state and action interface, and one jointly trained multi-task checkpoint. The same checkpoint accepts a natural-language task instruction together with the visual observations; in the evaluated protocol, each visually distinct task scene was paired with one fixed corresponding instruction rather than with a separately loaded policy file. The final physical evaluation used the 65,000-step checkpoint selected by the task-balanced offline validation rule. ACT therefore remains part of the design history and concept-selection evidence, but it is not presented as the final controller.

The mechanical elements selected in DR3 remain directly relevant. The two FR3 arms provide a common kinematic and controller interface, and the two GELLO leaders provide matched bilateral demonstration inputs. The wrist and overhead cameras provide complementary local and global views. The 3D-printed compliant fingers provide a task-compatible contact interface. The later policy update changes how these modules are connected and trained, but does not remove the need for their original engineering analysis.

The principal engineering change lies in the learning and deployment route. The DR3 prototype required an operator to select task-specific ACT checkpoints, whereas the final system uses one language-conditioned $\pi_{0.5}$ checkpoint for the ring, socket, and memory-

module tasks. The policy interface now combines the task instruction, three RGB views, and the bilateral robot state.

The bilateral interface was also consolidated. Both FR3 arms and both grippers are represented by one 16-dimensional measured state and one 16-dimensional absolute action, ordered as seven left-arm joints, the left gripper, seven right-arm joints, and the right gripper. The recorder, learned policy, and robot-side executor use this same ordering. The three task datasets are trained jointly with equal task-selection probability so that differences in trajectory length do not change the intended balance among the three operations.

Checkpoint selection and execution were revised together. The final checkpoint was chosen before physical testing from the unweighted mean validation loss of the three tasks; the minimum recorded value, 0.036552, occurred at 65,000 optimizer steps. At deployment the model predicts a 50-step action chunk, while the executor applies the first 10 actions at 15 Hz before observing the workcell again. The selected horizon supplies temporal context without committing the robot to the complete predicted sequence.

Validation and implementation records were expanded beyond the DR3 plan. Chapter 5 separates ES1–ES6 measurements from the 75 counted end-to-end trials and reports the available denominator for each rate. The report also distinguishes zero additional cash expenditure from the laboratory value of the robots, cameras, compute, storage, fabrication, and engineering effort. These changes improve traceability while preserving the DR3 mechanical platform, camera arrangement, demonstration interface, compliant fingers, and deterministic robot-side safeguards.

4.1.2 Overall system architecture and VLA formulation

The final system is organized as four connected layers:

1. the physical workcell, consisting of two FR3 arms, two custom grippers, task fixtures, and three cameras;
2. the demonstration layer, consisting of the two GELLO leader devices, the ROS 2 bridge, and the episode recorder;
3. the learning layer, consisting of LeRobot Dataset v3.0, the $\pi_{0.5}$ training configuration, and task-balanced validation; and
4. the deployment layer, consisting of language-conditioned policy inference, action-

chunk handling, the bilateral robot adapter, and deterministic safety checks.

During demonstration collection, the operator moves the two GELLO leaders. The follower-side system commands the two FR3 arms. It records three RGB images, the measured bilateral state, the bilateral arm targets, the gripper commands, the episode index, and the task instruction. Accepted episodes are stored in LeRobot Dataset v3.0 format. During training, the three task datasets are sampled with equal task probability and used to update one $\pi_{0.5}$ model. During deployment, one of the three language instructions and the current three-view observation are supplied to the same checkpoint. The policy returns an action chunk, and the robot-side adapter sends the admissible absolute targets to the two FR3 controllers.

Figure 4–1 summarizes the final $\pi_{0.5}$ training and action-generation architecture. Packet-associated multi-view observations are converted into visual tokens, while the task instruction and 16-dimensional bilateral proprioceptive state provide language and robot-state conditioning. The adapted $\pi_{0.5}$ model then generates a continuous 16-dimensional bimanual action chunk containing absolute joint targets and gripper widths for both arms.




Illustration 4–1 Final $\pi_{0.5}$ system overview for language-conditioned bimanual manipulation. Three camera views, a task instruction, and the 16-dimensional bilateral robot state condition the frozen vision-language backbone and the adapted robot-action path, which produces continuous absolute joint and gripper action chunks for both FR3 arms.

The final controller can be expressed as a conditional visual-language-action policy. At decision time t , the visual observation is the ordered set

$$\mathcal{I}_t = \left\{ \mathbf{I}_t^{\text{overhead}}, \mathbf{I}_t^{\text{left}}, \mathbf{I}_t^{\text{right}} \right\}, \quad (4-1)$$

the language instruction is ℓ , and the bilateral proprioceptive state is $\mathbf{s}_t \in \mathbb{R}^{16}$. The learned policy maps these conditions to a 50-step bilateral action chunk:

$$\hat{\mathbf{A}}_{t:t+H-1} = \pi_\theta(\mathcal{I}_t, \ell, \mathbf{s}_t), \quad \hat{\mathbf{A}}_{t:t+H-1} \in \mathbb{R}^{H \times 16}, \quad H = 50. \quad (4-2)$$

Each row contains the absolute targets for seven left-arm joints, the left gripper, seven right-arm joints, and the right gripper. Equation 4–2 is the system-level VLA contract; it does not imply that the model directly controls joint torque or bypasses the FR3 low-level controllers.

The executor applies only the first $h = 10$ rows:

$$\hat{\mathbf{a}}_{t+j} = \left[\hat{\mathbf{A}}_{t:t+H-1} \right]_{j,:}, \quad j = 0, \dots, h-1, \quad h = 10, \quad (4-3)$$

then acquires a new $\mathcal{I}_{t+h}$ and $\mathbf{s}_{t+h}$ and queries the policy again. The predicted horizon is therefore longer than the executed segment. This receding-horizon use of action chunks limits the amount of motion committed before visual and proprioceptive feedback is refreshed.

4.1.3 Selected modules and operational workflow

Dual-FR3 bimanual platform.

Two FR3 arms are used as the follower robots. The use of the same robot model on both sides reduces interface asymmetry: each side contributes seven joint positions, receives seven absolute joint targets, and uses the same low-level controller family. The shared kinematic structure also makes bilateral indexing, joint-limit validation, and data normalization easier to audit. Bimanual operation is required because each task includes a preparation or stabilization action followed by a more precise manipulation action.

GELLO demonstration interface.

The demonstration interface uses one GELLO leader for each follower arm. GELLO provides a physical leader whose joint arrangement is mapped to the follower robot, giving the operator direct control of coordinated arm motion^[18]. The selected project configuration

Table 4–1 Principal symbols used in the $\pi_{0.5}$ design and validation equations

Symbol	Dimension or domain	Meaning
t	decision index or sampled flow time	Context-dependent time variable; the flow-time use is stated explicitly in the training subsection.
I_t	three RGB images	Ordered overhead, left-wrist, and right-wrist visual observation.
ℓ	token sequence	Natural-language task instruction supplied to the shared checkpoint.
$\mathbf{s}_t$	$\mathbb{R}^{16}$	Bilateral measured joint and gripper state.
$\mathbf{a}_t$	$\mathbb{R}^{16}$	One bilateral absolute joint/gripper target.
$\hat{\mathbf{A}}_{t:t+H-1}$	$\mathbb{R}^{H \times 16}$	Predicted bilateral action chunk.
H	50 action steps	Model prediction horizon.
h	10 action steps	Number of actions consumed before re-observation.
θ	model parameters	Parameters of the conditional $\pi_{0.5}$ policy; only the action path and projections are trained in the final run.
ϵ	$\mathbb{R}^{50 \times 16}$	Gaussian noise used by the flow-matching objective.
$\mathbf{x}_t$	$\mathbb{R}^{50 \times 16}$	Noisy interpolated action state at sampled flow time t .
$\mathbf{u}_t$	$\mathbb{R}^{50 \times 16}$	Target flow velocity $\epsilon - \mathbf{a}$.
$\mathbf{v}_\theta$	$\mathbb{R}^{50 \times 16}$	Action-expert velocity prediction.
$\mathcal{L}_{\text{FM}}$	scalar	Normalized flow-matching training loss.
$\mathcal{L}_{\text{macro}}$	scalar	Unweighted mean of ring, socket, and RAM validation losses.
$\hat{p}$	$[0, 1]$	Observed success proportion x/n in Chapter 5.

provides seven arm channels and one gripper channel per leader. Its low-cost modular construction also allows damaged or geometrically unsuitable leader components to be reprinted without changing the follower robot.

Three-camera visual observation.

The final observation contains one fixed overhead view and two wrist views. The overhead Intel RealSense D435 observes the shared workspace, fixture positions, and large object motion. The two Intel RealSense D405 cameras move with the left and right wrists and preserve local visual information near grasp, contact, insertion, extraction, and placement regions. This arrangement avoids relying on a single global view that may be occluded by either arm, while avoiding a wrist-only configuration that loses global task context.

Custom compliant grippers.

Each arm is equipped with a custom gripper developed during DR3. Both grippers share the same geometry and consist of two screw-mounted fingers, each with an overall bounding-box size of

$$123.36 \times 25.80 \times 40.00 \text{ mm.}$$

The fingers of the right gripper are printed in the harder TPU 64D material. This material choice is intended to limit deformation and improve grasp repeatability for smaller objects. In contrast, the fingers of the left gripper are printed in the softer TPU 95A material. This material choice is intended to permit greater conformation around larger objects and a broader contact region. The tapered profile and repeated ribs are designed to provide passive compliance, while the reinforced mounting end is designed to retain a comparatively stiff screw interface.

LeRobot $\pi_{0.5}$ policy.

The final policy is the LeRobot implementation of $\pi_{0.5}$, adapted from the open-source OpenPI implementation^[12-15]. It receives three RGB images, the current bilateral state, and a language instruction. It predicts a chunk of bilateral actions in the same absolute joint-and-gripper representation used by the recorder and executor. The same model parameters are used for all three tasks.

Workcell initialization.

Before an episode or an autonomous trial begins, the two arms are returned to the documented initial joint region, the grippers are inspected, and the task objects are reset. Camera mounts, image identities, network connections, controller status, workspace boundaries, and emergency-stop access are checked. The socket fixture is kept electrically unpowered. A run is not started if a camera is missing, a robot state is stale, or the scene does not match the selected instruction.

Demonstration collection.

The operator performs the selected task using the two GELLO leaders. The ROS 2 bridge assembles packets containing the three images, the measured robot and gripper state, and the commanded arm and gripper values. The recorder samples these packets at 5 Hz and stores a complete episode. The operator then reviews task completion and resets the workcell before the next episode. Episode boundaries are preserved so that complete trajectories, rather than individual frames, can be assigned to training or validation.

Dataset screening and training.

The recorded episode is checked for the presence and consistent length of all three image streams, the 16-dimensional state, the 16-dimensional action, the task identity, and the episode metadata. Accepted episodes are added to one of the three task datasets. The stored trajectories retain the 5 Hz collection time base, and training samples action sequences on that 5 Hz time base. Training then samples the three tasks with equal probability, applies the defined image and numeric preprocessing, and fine-tunes one $\pi_{0.5}$ checkpoint for 100,000 optimizer steps.

Closed-loop deployment.

At deployment, the operator selects the natural-language instruction that matches the prepared scene. The model receives the instruction, three current images, and the current bilateral state. It predicts 50 actions, of which the first 10 are consumed before a new observation is evaluated. The executor checks the returned targets and sends them to the two arms at the 15 Hz deployment rate. A task terminates on completion, timeout, invalid observation, invalid action, protective stop, emergency stop, or manual intervention.

4.2 Engineering design analysis

4.2.1 Mechanical and kinematic design

The implemented system combines serial-manipulator kinematics, shared-workspace bi-manual coordination, compliant contact, packet-associated multi-view observations, imitation learning, and receding-horizon control. The learned policy produces position targets that are executed through the FR3 controllers and their safety checks.

For one seven-degree-of-freedom arm with joint vector

$$\mathbf{q}_t = [q_{1,t}, \dots, q_{7,t}]^T,$$

the end-effector pose is

$${}^B\mathbf{T}_{E,t} = f(\mathbf{q}_t), \quad (4-4)$$

where B is the robot-base frame, E is the end-effector frame, and $f(\cdot)$ is the forward-kinematics map. In the dual-arm system, the corresponding transforms are

$${}^{B_L}\mathbf{T}_{E_L,t} = f_L(\mathbf{q}_t^L), \quad {}^{B_R}\mathbf{T}_{E_R,t} = f_R(\mathbf{q}_t^R). \quad (4-5)$$

If both base poses are expressed in a common workcell frame W , the relative end-effector transform can be written as

$${}^{E_L}\mathbf{T}_{E_R,t} = ({}^W\mathbf{T}_{B_L} {}^{B_L}\mathbf{T}_{E_L,t})^{-1} {}^W\mathbf{T}_{B_R} {}^{B_R}\mathbf{T}_{E_R,t}. \quad (4-6)$$

Equation 4–6 explains why the two base installations and task fixtures must remain fixed: the learned policy observes images and joint states rather than an explicitly recalibrated relative pose at every episode.

Design assumptions and constraints.

The system operates in a structured indoor workcell. Lighting, camera mounts, robot bases, and task fixtures remain sufficiently repeatable for the learned visual policy. Each trial begins within the demonstrated workspace. The can, handled ring, socket box, plug, motherboard, memory module, and yellow tray are treated as task-specific laboratory objects rather than arbitrary unseen industrial components.

The model uses RGB images and bilateral proprioception. The ROS 2 bridge assembles the three camera views and robot state into packet-associated multi-view observations for

recording and policy inference. Learned actions are accepted only after dimensional, finite-value, joint, gripper, workspace, freshness, and communication checks. The socket task uses an electrically unpowered fixture.

FR3 parameters and bimanual kinematic suitability.

Each FR3 provides seven degrees of freedom, a nominal payload of 3 kg, a maximum reach of 855 mm, and link-side torque sensing in all seven axes^[25-27]. These values are suitable for the project because the manipulated objects are light, the task is performed on a tabletop, and the seventh joint gives redundancy for changing wrist orientation while avoiding fixtures and the other arm.

Table 4–2 FR3 parameters relevant to the selected bimanual workcell

Parameter	Value	Design relevance
Degrees of freedom	7 per arm	Provides redundant approach configurations and wrist orientation control.
Nominal payload	3 kg	Exceeds the mass required for the project objects and custom fingers.
Maximum reach	855 mm	Supports a shared central tabletop region when the two bases are arranged on opposite sides.
Joint sensing	Link-side torque sensing in all seven axes	Supports compliant low-level control, contact monitoring, and protective behavior.

The complete joint ranges, mounting specification, environmental limits, controller interfaces, and dimension drawings are collected in Appendix 2, Table 2–1, and Figures 2–1–2–2. The practical task workspace is deliberately smaller than those hardware bounds so that action chunks do not intentionally approach joint limits.

Figure 4–2 shows the placement of the shared task region. The robotic arm has a maximum working radius of 855 mm. However, motion near full extension reduces the available orientation freedom and may bring the arm closer to singular configurations; therefore, objects should preferably not be placed near the workspace boundary.

Bimanual state and action representation.

The actual state and action are both stored as 16-dimensional `float32` arrays. The state




Illustration 4-2 Side and top views of the FR3 workspace envelope. The shared task region is selected inside the overlap of the two practical arm workspaces rather than at the 855 mm reach boundary.

is

$$\mathbf{s}_t = [q_{1,t}^L, \dots, q_{7,t}^L, g_t^L, q_{1,t}^R, \dots, q_{7,t}^R, g_t^R]^\top \in \mathbb{R}^{16}, \quad (4-7)$$

where g_t^L and g_t^R are measured gripper opening widths in metres. The action uses the same ordering:

$$\mathbf{a}_t = [q_{1,t+1}^{L,target}, \dots, q_{7,t+1}^{L,target}, g_t^{L,target}, q_{1,t+1}^{R,target}, \dots, q_{7,t+1}^{R,target}, g_t^{R,target}]^\top. \quad (4-8)$$

Indices 0–6 correspond to the left arm, index 7 to the left gripper, indices 8–14 to the right arm, and index 15 to the right gripper. Arm actions are absolute next-step joint targets, not joint increments. Gripper actions are absolute `open_width_m` commands. The implemented setting is therefore `use_relative_actions=false` in both training and deployment.

The $\pi_{0.5}$ implementation pads state and action features to an internal maximum of 32 dimensions. Only entries 0–15 contain project data. Entries 16–31 are padding and are not for additional robot commands. The robot adapter explicitly slices and validates the first 16 entries before decomposing them into left-arm, left-gripper, right-arm, and right-gripper targets.

Shared workspace and role allocation.

The two arms operate in a shared central region, so task role allocation is selected to reduce unnecessary crossing. In Task 1, the left arm pushes the can toward the centre while the right arm grasps and places the handled ring. In Task 2, the right arm pushes the socket box while the left arm grasps and inserts the plug. In Task 3, the left arm grips and pulls the motherboard while the right arm removes the memory module and places it in the yellow tray.

These assignments separate the large preparation motion from the subsequent precision motion. They also preserve the view of the precision-side wrist camera: the wrist that performs the ring placement, plug insertion, or RAM extraction approaches the relevant contact region directly. Role allocation is encoded by the demonstrations and the fixed action indexing.

Contact, clearance, and insertion tolerance analysis.

Ring-over-can placement.

The ring task contains three mechanically distinct phases: a planar push of the can, a grasp of the ring handle, and a vertical placement of the ring over the can. Successful placement requires the ring inner opening to remain clear of the can outer profile throughout descent. If D_r is the effective ring inner diameter and D is the effective can outer diameter, the ideal radial clearance is

$$c_r = \frac{D_r - D}{2}. \quad (4-9)$$

Using the measured values $D_r = 10.0$ cm and $D = 6.3$ cm, the ideal radial clearance is $c_r = 1.85$ cm = 18.5 mm. Therefore, for a level ring, the lateral centre offset must remain below 18.5 mm to avoid geometric interference. The practical allowable error is smaller because ring tilt, finger deformation, and uncertainty in the apparent object boundary consume part of this clearance.

The handle allows the right gripper to avoid pinching the ring circumference, but it introduces an offset between the grasp point and the ring centre. This offset creates a moment that can tilt the ring during transport. A near-vertical final approach and release after the ring is supported by the target reduce the sensitivity to that moment.

Plug insertion.

Plug insertion is a constrained contact task. Lateral and angular misalignment can produce edge contact, jamming, incomplete seating, socket-box displacement, or excessive force. For an insertion depth L_i and effective lateral clearance c_i , a first-order small-clearance angular bound is

$$\theta_{\max} \approx \tan^{-1} \left(\frac{c_i}{L_i} \right). \quad (4-10)$$

The relation shows that angular tolerance decreases as insertion depth increases. The socket box is pushed into a repeatable central region before insertion so that the left arm can approach with sufficient remaining wrist orientation range. The right-arm push must end before the left-arm precision approach enters the same local region.

The socket mock-up was electrically unpowered and had a recorded overall size of $80 \times 80 \times 30$ mm. The two metal blades of the plug are spaced 12 mm apart. Successful insertion requires both blades to enter their corresponding holes simultaneously and remain seated. A positional deviation of 20 mm or greater is therefore geometrically incompatible with task completion, and an accepted insertion is necessarily more precise than the ES4 limit. This is a threshold inference from the mating geometry. The current task continues to use an unpowered socket fixture. Success is defined functionally: the correct plug enters the correct socket, remains seated without manual assistance, and produces no visible damage.

Memory-module extraction.

The motherboard task requires fixture stabilization, connector release, module extraction, and safe placement. The left gripper pulls the motherboard closer and holds or stabilizes it. The right gripper must approach the memory module without contacting nearby components, apply a controlled extraction motion consistent with the connector geometry, and transport the released module to the yellow tray.

The mechanical tolerance is governed by the free space around the memory module, the width and compliance of the custom fingers, and the connector's extraction direction. Excess lateral motion can bend the module or load adjacent board components.

Custom gripper geometry and mechanical analysis.

The two fingers on the left gripper are printed in TPU 95A, while the two fingers on the right gripper are printed in TPU 64D. All four fingers share the same geometry. For one finger,

$$L = 123.36 \text{ mm}, \quad T = 25.80 \text{ mm}, \quad H = 40.00 \text{ mm}.$$

The principal geometric ratios are

$$\frac{L}{T} = \frac{123.36}{25.80} \approx 4.78, \quad \frac{L}{H} = \frac{123.36}{40.00} \approx 3.08. \quad (4-11)$$

These ratios describe an elongated finger rather than a short rigid jaw. The repeated ribs are intended to reduce local bending stiffness along the contact region, the tapered outline is intended to improve access, and the thicker mounting end is intended to distribute screw load.

The same compliance involves a design trade-off. It is intended to accommodate object-shape and pose variation and may reduce concentrated contact pressure, while deformation may reduce grasp repeatability and make the effective fingertip pose load dependent. The task design therefore combines the intended compliance with fixed camera identities, repeatable starts, and arm-side position control. The full orthographic drawing and fabrication-reference dimensions are provided in Appendix 2, Figure 2–4.

4.2.2 Perception, teleoperation, and data collection

The overhead camera is an Intel RealSense D435. Its specified ideal depth range is approximately 0.3–3 m and its depth field of view is approximately $87^\circ \times 58^\circ$ ^{realsenseD435}. This makes it suitable for observing the complete tabletop from a fixed elevated position. The overhead view supplies global information when either wrist view is occluded or too close to show the relationship between the object, fixture, and destination.

Each wrist camera is an Intel RealSense D405. Its specified ideal depth range is approximately 7–50 cm, with an approximately $87^\circ \times 58^\circ$ depth field of view^[28]. This range is better matched to a camera mounted near the end effector. The wrist views preserve local detail during ring descent, plug alignment, and memory-module extraction.

Table 4–3 Camera configuration and selection basis

Camera	Quantity	Nominal ideal range	Depth FOV
RealSense D435	1	0.3–3 m	$87^\circ \times 58^\circ$
RealSense D405	2	7–50 cm	$87^\circ \times 58^\circ$

The D435 provides the fixed overhead view used to monitor the shared workspace, fixtures, destinations, and large object displacement. The two D405 cameras are mounted at

the wrists and provide close-range views during grasping, contact, insertion, extraction, and placement. The recorder stores the three RGB streams at 424×240 and 5 Hz as packet-associated multi-view observations.

Image format and preprocessing.

All three raw streams have width 424 and height 240. The LeRobot dataset stores each decoded RGB image in channel-first form:

$$[C, H, W] = [3, 240, 424].$$

Before an image is passed to $\pi_{0.5}$, it is converted to a $3 \times 224 \times 224$ tensor. The conversion preserves aspect ratio. The 424×240 image is scaled to approximately 224×126 , and the remaining square area is filled with approximately 49 black pixels above and below the resized image. The image is not stretched to 224×224 .

Pixel values are represented in $[0, 1]$ after decoding and are normalized to $[-1, 1]$ before the model. This process is applied independently but identically to the overhead, left-wrist, and right-wrist images. Camera names and ordering are part of the feature contract. A swapped wrist-camera mapping can produce a dimensionally valid but semantically incorrect policy input, so identity is checked before recording and deployment.

GELLO channel architecture and leader–follower mapping.

The bilateral collection system uses two GELLO–Franka leaders. Each leader provides seven arm channels and one gripper-related channel, matching the seven joint targets and one gripper command required by its FR3 follower. This channel correspondence is the design-relevant property; the detailed actuator, controller-board, power-supply, structural-kit, and dual-system quantities are listed in Appendix 2, Table 2–2.

Leader motion must be mapped to follower joint order, sign convention, zero offset, and permitted range. An incorrect offset can generate a valid numeric command that is unsafe for the follower. The pre-collection procedure therefore verifies the leader zero, moves each channel through a small range, confirms the corresponding follower direction, and checks the gripper-width mapping before a task episode is recorded.

Data-collection pipeline.

The implemented data path is

two GELLO leaders → two FR3 follower controllers → ROS 2 bridge
 → assembled packets
 → LeRobot recorder → Parquet records and three RGB videos.

The follower-side system provides measured joint positions and current gripper widths. The command side provides absolute arm targets and absolute gripper-width commands. The recorder samples the assembled packet stream at 5 Hz, assigns frames to the active episode, and preserves the task identity. A complete episode contains a continuous visual and proprioceptive record from the initial condition to either task completion or termination.

Collection and task review are intentionally separate operations. The recorder verifies schema and continuity, while the operator verifies whether the physical task was demonstrated correctly. A numerically complete episode can still be unsuitable for training if the operator intervened incorrectly, the object left the intended workspace, or the terminal state does not match the language instruction.

Packet-associated multi-view observations and action-label alignment.

The stored cadence is 5 Hz, corresponding to approximately 0.2 s per step. The recorder pairs adjacent assembled packets. For the saved sample at index t , the four recorded relationships are written as separate centred expressions:

$$\mathbf{o}_t^{\text{visual}} = \text{three images from packet } t. \quad (4-12)$$

$$\mathbf{s}_t = \text{bilateral measured state from packet } t. \quad (4-13)$$

$$\mathbf{a}_t^{\text{arm}} = \mathbf{q}_{t+1}^{\text{target}} \text{ from packet } t + 1. \quad (4-14)$$

$$\mathbf{a}_t^{\text{grripper}} = \mathbf{g}_t^{\text{target}} \text{ from packet } t. \quad (4-15)$$

Images and measured state therefore come from the same current packet. The arm label is shifted forward by one packet so that the current observation is paired with the next absolute joint target. The gripper label follows the existing same-packet convention.

This procedure keeps the packet-associated multi-view observations, bilateral state, and action labels consistent throughout recording and training.

4.2.3 Dataset design and task-balanced training

The three task datasets contain 80 episodes each. All three use random seed 1000 and the same validation episode indices:

$$\{17, 35, 58, 65, 66, 72, 74, 75\}.$$

The remaining 72 episodes per task are used for training. Splitting by episode prevents neighbouring frames from the same physical trajectory from appearing in both the training and validation sets.

Table 4–4 Episode-level dataset split for the three bimanual tasks

Task dataset	Episodes	Frames	Training split	Validation split
dual_ring	80	46,326	72 episodes / 41,410 frames	8 episodes / 4,916 frames
dual_socket	80	38,511	72 episodes / 34,655 frames	8 episodes / 3,856 frames
dual_ram	80	34,813	72 episodes / 31,675 frames	8 episodes / 3,138 frames
Total	240	119,650	216 episodes / 107,740 frames	24 episodes / 11,910 frames

The tasks are sampled with equal probability during training. Task selection occurs before sample selection, so `dual_ring` does not receive a larger task-level probability merely because it contains more frames. This choice balances the three instructions and prevents the longest average trajectory from dominating the gradient updates.

Language-conditioned dataset scope.

The deployed checkpoint was trained on the three datasets summarized in Table 4–4: ring placement, plug insertion, and memory-module removal. Each dataset is paired with one explicit natural-language instruction that describes the complete bimanual sequence and terminal goal. The instruction is assigned before a training sample is passed to the policy, and

the same wording is used during physical deployment. Language conditioning is therefore part of the model input contract rather than a descriptive label added after training.

The 240 episodes and 119,650 frames reported in Table 4–4 contribute to the normalization statistics, task sampler, optimization updates, validation losses, checkpoint selection, and physical evaluation. This fixed scope keeps the reported 65,000-step checkpoint traceable to the three evaluated tasks and prevents unused data from being inferred merely from local storage or schema compatibility.

Training statistics and task-balanced sampling.

The action and state normalizers are calculated from the 107,740 training frames obtained after the episode split. For every real state and action dimension, the implementation records the count, minimum, maximum, mean, standard deviation, and the 1st, 10th, 50th, 90th, and 99th percentiles. State and action use quantile normalization, while images use the identity numeric normalizer after pixel preprocessing.

For a scalar feature x_d in dimension d , the implemented quantile mapping can be represented by

$$\tilde{x}_d = 2 \cdot \text{clip} \left(\frac{x_d - Q_{0.01,d}}{Q_{0.99,d} - Q_{0.01,d}}, 0, 1 \right) - 1, \quad (4-16)$$

where $Q_{0.01,d}$ and $Q_{0.99,d}$ are computed from training frames only. The postprocessor applies the corresponding inverse scaling to predicted actions. Extreme values outside the stored quantile range are clipped for the model representation; the robot adapter still performs independent finite, joint, gripper, and workspace checks after unnormalization.

The normalizer pools frames, but the sampler balances tasks. If N_k is the number of training frames in task k , each sample in that task receives weight

$$w_{k,i} = \frac{1}{N_k}. \quad (4-17)$$

The total weight of each task is then $\sum_{i=1}^{N_k} w_{k,i} = 1$. With replacement enabled, the expected long-run sampler share is one third for ring, socket, and RAM, even though their frame counts differ. At batch size 4, 100,000 optimizer steps process approximately 400,000 sampled training items; the expected count is therefore about 133,000 items per task, subject to sampling variation.

This distinction matters. Quantile statistics are influenced by the number of frames in each directory, so the longer ring trajectories contribute more values to the pooled distribu-

tion. Gradient sampling, by contrast, gives the three semantic tasks equal expected probability. The design protects task balance at the optimizer interface without claiming that the normalization statistics are task-equal.

For offline validation, the program fixes at most 64 batches per task. With batch size 4, each validation point uses at most 256 frames from each task, selected reproducibly at program start. The resulting per-task loss and their unweighted macro-average are suitable for comparing checkpoints under this fixed procedure. They do not summarize every validation frame, and they do not measure real-robot task completion.

$\pi_{0.5}$ **base model and software configuration.**

The final controller uses the official `pi05_base` model. The upstream checkpoint is identified by `gs://openpi-assets/checkpoints/pi05_base/params`, and training reads the converted PyTorch parameters. The base architecture combines a PaliGemma `gemma_2b` vision-language component with a `gemma_300m` action expert. The model weights use `bfloat16`.

The project uses LeRobot 0.5.2 with local project modifications. The dataset format is LeRobot Dataset v3.0. Training is executed on physical GPU 1 of an NVIDIA RTX A6000 with 48 GB of memory.

4.2.4 $\pi_{0.5}$ objective, adaptation, and training

The base configuration has a model-side action dimension of 32 and an action horizon of 50. Project state and action are only 16-dimensional, so the preprocessor pads entries 16–31 with zeros and preserves the physical values in entries 0–15. Loss is evaluated only over the real 16 dimensions, and the deployment adapter removes the padded tail before any robot command is formed.

The numeric state is quantile-normalized to approximately $[-1, 1]$, then discretized into 256 bins. The resulting state tokens are placed beside the task instruction in the model prompt:

```
Task: <task instruction>, State: <discretized state tokens>;
Action:
```

The PaliGemma SentencePiece tokenizer uses right padding and a maximum sequence length of 200 tokens. This representation makes the task instruction and current bilateral state jointly

available to the model. In the evaluated system, one shared checkpoint executed the three fixed scene–instruction configurations with the complete input tuple of images, instruction, and state.

The three camera images are supplied in the fixed order $\{\text{cam_left}, \text{cam_front}, \text{cam_right}\}$. Each image is resized and padded by the image-preprocessing pipeline described above, then mapped from $[0, 1]$ to $[-1, 1]$. No camera slot is empty in the final configuration. The preprocessor rejects a missing feature name rather than silently replacing one of the three deployed views.

Flow-matching training objective.

The action expert is trained with a conditional flow-matching objective. Let $\mathbf{a} \in \mathbb{R}^{50 \times 16}$ be the normalized demonstrated action chunk and let $\boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ be an equally shaped Gaussian-noise sample. A time value is sampled from

$$t_0 \sim \text{Beta}(1.5, 1.0), \quad t = 0.999t_0 + 0.001.$$

The interpolated action state is

$$\mathbf{x}_t = t\boldsymbol{\epsilon} + (1 - t)\mathbf{a}, \quad (4-18)$$

and the target velocity is

$$\mathbf{u}_t = \boldsymbol{\epsilon} - \mathbf{a}. \quad (4-19)$$

Conditioned on the three images, task/state tokens, and t , the action expert predicts $\mathbf{v}_\theta(\mathbf{x}_t, t)$.

The implemented loss is

$$\mathcal{L}_{\text{FM}} = \frac{1}{B \cdot 50 \cdot 16} \sum_{b=1}^B \sum_{\tau=1}^{50} \sum_{d=1}^{16} (u_{b,\tau,d} - v_{\theta,b,\tau,d})^2. \quad (4-20)$$

Padding dimensions are not used to improve the reported value. The loss is calculated in normalized action space and is therefore dimensionless. It is not joint error in radians, gripper-width error in metres, Cartesian pose error, insertion error, or task success. This distinction controls the checkpoint discussion in Chapter 5.

Adaptation scope and trainable parameters.

The final run uses action-path-only adaptation. The Gemma action expert and the action/-time projection modules are trainable, while the entire PaliGemma vision-language component, including the SigLIP visual encoder, remains frozen. No LoRA or other PEFT adapter is used in this LeRobot experiment.

Table 4–5 Parameter and optimization scope of the final LeRobot $\pi_{0.5}$ run

Item	Implemented scope
Frozen parameters	3,449,982,704 parameters in the PaliGemma vision-language component
Trainable parameters	693,422,112 parameters in the action expert and action/time projections
Total parameters	4,143,404,816
Parameter-efficient adapter	None; parameter names containing LoRA are rejected
Image augmentation	Disabled for the reported run
Gradient checkpointing	Disabled
Automatic mixed precision	Disabled; model weights use <code>bfloat16</code> as configured
Compilation	<code>torch.compile</code> disabled
Relative-action conversion	Disabled in preprocessing and postprocessing

The parameter count clarifies what “fine-tuning” means in this report. The final controller is not trained from random initialization and the full vision-language backbone is not updated. The experiment adapts the action generation path to the project camera/state/action contract while preserving the base representation.

Training procedure.

The three tasks are trained jointly for 100,000 optimizer steps. Batch size is 4 and the optimizer is AdamW. The peak learning rate is 2.5×10^{-5} . A 1,000-step warm-up is followed by cosine decay to 2.5×10^{-6} . Task-balanced validation is run every 5,000 steps.

The training configuration deliberately separates task balancing from frame count. The action and state normalizers are derived from the training data only. Validation episodes are not used to compute model updates. The same action representation and `use_relative_actions=false` setting are retained when the selected checkpoint is loaded for deployment.

Optimizer schedule, runtime, and checkpoint package.

AdamW uses $\beta_1 = 0.9$, $\beta_2 = 0.95$, $\epsilon = 10^{-8}$, weight decay 0.01, and global gradient-norm clipping at 1.0. During the first 1,000 optimizer steps, the learning rate increases to 2.5×10^{-5} . Cosine decay then reduces it to 2.5×10^{-6} at step 100,000. One iteration executes preprocessing, gradient reset, forward loss calculation, backpropagation, gradient clipping,

Table 4–6 Final $\pi_{0.5}$ training configuration

Parameter	Implemented value
Base model	Official pi05_base
Model structure	PaliGemma gemma_2b and action expert gemma_300m
Weight precision	bfloat16
LeRobot version	0.5.2, with local modifications
Dataset format	LeRobot Dataset v3.0
Training hardware	NVIDIA RTX A6000 48 GB, physical GPU 1
Deployment workstation	NVIDIA GeForce RTX 5070 Ti
Batch size	4
Optimizer	AdamW
Training length	100,000 joint-training steps
Learning-rate schedule	1,000-step warm-up to 2.5×10^{-5} , followed by cosine decay to 2.5×10^{-6}
Task sampling	Equal probability for dual_ring, dual_socket, and dual_ram
Validation interval	Every 5,000 optimizer steps

optimizer update, and scheduler update in that order.

Each checkpoint contains the policy configuration, complete model weights, preprocessor and postprocessor definitions, quantile normalizers, the PaliGemma tokenizer asset, the multi-task manifest, optimizer state, scheduler state, random-number-generator state, and training step. The early processor configuration used an absolute tokenizer path. A portability repair copied the tokenizer model into each checkpoint and rewrote the processor reference to a relative file. The watcher verified the repair through step 100,000.

4.2.5 Validation, action chunking, and deployment boundary

For each task, validation first computes the mean normalized flow-matching loss over at most 64 batches. With batch size 4, this corresponds to at most 256 validation samples per task at one validation point. The checkpoint-selection quantity is the unweighted task macro-average

$$\mathcal{L}_{\text{macro}} = \frac{\mathcal{L}_{\text{ring}} + \mathcal{L}_{\text{socket}} + \mathcal{L}_{\text{ram}}}{3}. \quad (4-21)$$

The best checkpoint is the validation point with the lowest $\mathcal{L}_{\text{macro}}$.

This metric is intentionally not weighted by the number of validation frames. It gives each

Table 4–7 Measured training resource use and checkpoint storage

Resource or artifact	Recorded value
Complete-run elapsed time	17 h 01 min 17 s
Typical optimizer-step time	Approximately 0.60 s at batch size 4
Maximum allocated GPU memory	23.49 GiB
Final training-window loss	0.028063; not the checkpoint-selection metric
Checkpoint interval	Every 5,000 steps from 5,000 through 100,000
Number of complete checkpoints	20
Approximate output-directory size	216 GB
Model file per checkpoint	Approximately 9.35 GB
Optimizer state per checkpoint	Approximately 2.20 GB
Selected checkpoint	Step 65,000, chosen by held-out macro loss

task equal influence, just as the training sampler gives each task equal selection probability. The loss supports checkpoint comparison. Real-robot performance is evaluated separately in Chapter 5.

Action chunking and temporal interface.

Collection uses 5 Hz. However, for better performance, execution uses 15 Hz, so one action step represents 0.067 s. The model predicts a 50-step chunk:

$$T_{\text{predicted}} = \frac{50}{15} = 3.33 \text{ s.} \quad (4-22)$$

Deployment uses `n_action_steps=10`, so the executor consumes approximately

$$T_{\text{executed}} = \frac{10}{15} = 0.67 \text{ s} \quad (4-23)$$

before requesting a new policy result from updated observations.

This is a receding-horizon interface. The 50-step prediction gives the action expert a longer temporal target, while executing only 10 steps limits the amount of open-loop motion and allows the next prediction to use updated observations.

Deployment pipeline.

Deployment begins by loading the selected unified checkpoint and its associated normalization statistics. The system verifies the three camera feature names, checks the 16-

dimensional state, and confirms the language instruction. The current observation is preprocessed and passed to the policy server. The returned action chunk is denormalized, sliced to the 16 valid robot dimensions, checked for finite values and limits, and divided into left-arm, left-gripper, right-arm, and right-gripper targets.

The robot adapter sends absolute joint targets and absolute gripper widths. It does not reinterpret them as deltas. After the configured ten-step segment, new images and state are acquired and a new action chunk is requested. This loop continues until the terminal task condition or a stop condition is reached.

Recoverable task-level failures invoke the implemented automatic recovery procedure. The current action chunk is cancelled, the robot returns to the predefined recovery state, packet-associated multi-view observations are refreshed, and execution resumes from a valid task state. Safety stops remain under the deterministic stop path described below.

Control, computation, and safety boundary.

The policy is not the safety controller. Before motion is enabled, a dry run verifies camera freshness and ordering, state/action dimensions, normalization statistics, checkpoint identity, language instruction, finite model outputs, network communication, joint and gripper limits, workspace bounds, and emergency-stop access.

During motion, the run stops on a missing image, stale state, malformed packet, non-finite output, excessive target, workspace violation, communication timeout, robot protective stop, emergency stop, or manual stop. Reset is performed only after policy execution has stopped and the shared workspace is clear. The power socket remains unpowered. These checks maintain a deterministic boundary around the probabilistic learned policy.

4.3 Detailed system design

4.3.1 Physical workcell and sensing

The two FR3 arms are mounted upright on opposite sides of a shared tabletop region. Task fixtures are placed inside the verified overlap of the two practical workspaces. The D435 is fixed above the shared region. One D405 is attached to each wrist. Each arm carries one custom gripper. The two GELLO leaders remain outside the follower workcell and are used by the operator during demonstration collection. Figure 4–1 identifies the three deployed

camera views and the 16-dimensional bilateral state supplied to the policy.

Dual-arm robotic platform.

Both arms use the same 16-value bilateral ordering defined in Equations 4–7 and 4–8. The left and right controllers remain independent low-level systems, but they are driven from one policy output and one episode timeline. Each arm can perform a large scene-preparation motion or a precise manipulation motion, depending on the demonstrated task role.

The redundant seventh joint is important in the shared workcell because end-effector pose alone does not determine a unique arm posture. Demonstrations implicitly select postures that provide camera visibility, avoid fixtures, and reduce inter-arm interference. The low-level controller remains responsible for executing the admissible targets, the learned model does not directly output torque.

GELLO leader assemblies.

Each leader measures seven arm channels and one gripper-related channel for its assigned follower. The operator does not bear follower-arm load through the leader; it is a position-input and command device. Mechanical looseness, servo zero error, cable interference, or incorrect joint signs can degrade demonstration quality, so the two leader assemblies are inspected and checked independently before bilateral collection. The component-level construction and quantities are recorded in Appendix 2.

End-effector and mechanical components.

Each gripper uses two screw-mounted compliant fingers. The mounting screws must be tightened consistently, and the fingers must be installed with matching orientation. Before a run, the operator checks for tearing at rib roots, permanent bending, loose mounting holes, surface contamination, and insufficient opening range.

The task fixtures prevent uncontrolled object drift while retaining the manipulation required by the task. The can and socket box must still be pushable into the intended central region. The motherboard must be graspable and movable by the left gripper but sufficiently supported to allow the right gripper to extract the memory module. The tray must remain fixed so that successful placement is not confused with tray motion.

Vision and sensing system.

The D435 mount is fixed relative to the workcell and is positioned to keep all source and

destination regions in view. The two D405 mounts move with the wrists and are oriented so that the gripper contact region appears in the close-range image during approach. Cables are routed to avoid entering the gripper opening or restricting wrist motion.

The logical camera mapping is fixed:

$$\begin{aligned} \text{overhead} &\equiv \text{D435}, \\ \text{left_wrist} &\equiv \text{left D405}, & \text{right_wrist} &\equiv \text{right D405}. \end{aligned}$$

The recorder and policy use these identities consistently to form packet-associated multi-view observations.

4.3.2 Data, training, and deployment interfaces

The collection system starts the two robot interfaces, both gripper interfaces, three camera publishers, the ROS 2 bridge, and the LeRobot recorder. The bridge assembles the latest required fields into a packet. The recorder begins a named task episode only after all required fields are available.

The operator executes the complete instruction and then ends the episode. The episode is retained only if the three image streams decode correctly, state and action arrays have the required width, and the demonstration matches the intended task. Manual workcell reset is performed between episodes. The same task instruction is used during collection and later deployment so that language conditioning does not depend on an undocumented paraphrase.

Data processing pipeline.

Processing has separate visual and numeric branches. The visual branch decodes the three RGB streams, converts them to channel-first tensors, preserves aspect ratio during resizing, pads to 224×224 , and normalizes to $[-1, 1]$. The numeric branch reads the 16-dimensional state and action, applies the training statistics, and pads the model-side representation to 32 dimensions.

Episode metadata determines the task and split. The eight validation episode indices are excluded from training for every task. During data loading, the task-balanced sampler chooses among the three task datasets with equal probability. The language instruction, three images, state, and supervised action target are then passed to the policy training step.

Policy-training system.

The training system loads `pi05_base`, the converted PyTorch weights, and the LeRobot v3.0 datasets. It uses batch size 4 on the RTX A6000. Optimizer state, learning-rate schedule, model state, step index, and validation quantities are saved at the configured checkpoints.

Validation runs every 5,000 steps. Each task is evaluated separately before the unweighted macro-average is calculated. This preserves per-task traceability and prevents a low loss on the largest dataset from concealing a poor result on another task.

Robot control and deployment system.

The deployment system runs on a workstation equipped with an NVIDIA GeForce RTX 5070 Ti and loads one checkpoint for all three instructions. The selected instruction and current observation are sent to $\pi_{0.5}$. A 50-step action chunk is returned, and the executor uses the first ten steps. The target ordering, absolute-action interpretation, and camera mapping are identical to those used during training, while the control frequency is increased from 5 Hz to 15 Hz.

The left and right arm targets are separated only after policy output validation. The gripper commands are expressed as absolute opening widths in metres. After each executed segment, the queue is not blindly extended with the rest of the old 50-step chunk; the policy is queried again using updated images and state.

Hardware–software interfaces.

Table 4–8 Detailed hardware–software interfaces in the final system

Information	Source	Destination	Implemented contract
Left leader joints	Left GELLO	Left follower interface	Seven leader positions mapped to left FR3 joint order, signs, offsets, and permitted range.
Left leader gripper	Left GELLO	Left gripper interface	One leader channel mapped to absolute gripper opening width.
Right leader joints	Right GELLO	Right follower interface	Seven leader positions mapped to right FR3 joint order, signs, offsets, and permitted range.
Right leader gripper	Right GELLO	Right gripper interface	One leader channel mapped to absolute gripper opening width.
Left measured joints	Left FR3 controller	ROS 2 bridge / recorder / executor	Seven current joint positions in state indices 0–6.

Information	Source	Destination	Implemented contract
Left measured gripper	Left gripper	ROS 2 bridge / recorder / executor	Current opening width in metres at state index 7.
Right measured joints	Right FR3 controller	ROS 2 bridge / recorder / executor	Seven current joint positions in state indices 8–14.
Right measured gripper	Right gripper	ROS 2 bridge / recorder / executor	Current opening width in metres at state index 15.
Overhead RGB	RealSense D435	Bridge / recorder / policy	RGB 424×240 at 5 Hz; stored as $3 \times 240 \times 424$, then resized and padded to $3 \times 224 \times 224$.
Left-wrist RGB	Left RealSense D405	Bridge / recorder / policy	Same tensor contract under the fixed left-wrist feature name.
Right-wrist RGB	Right RealSense D405	Bridge / recorder / policy	Same tensor contract under the fixed right-wrist feature name.
Assembled packet	ROS 2 bridge	LeRobot recorder	Same-packet images and measured state; adjacent-packet arm action label.
Episode record	LeRobot recorder	Dataset v3.0	Three videos, state, absolute action, task instruction, episode and frame indexing.
Training sample	Dataset and sampler	$\pi_{0.5}$ trainer	Equal-probability task sampling; training episodes only.
Language instruction	Task interface	$\pi_{0.5}$ policy	One of the three documented task instructions matching the prepared scene.
Policy observation	Preprocessor	$\pi_{0.5}$ policy	Three normalized $3 \times 224 \times 224$ images and a padded numeric state whose first 16 entries are valid.
Predicted action	$\pi_{0.5}$ policy	Robot adapter	50-step chunk; first 10 steps consumed per query.
Left arm command	Robot adapter	Left FR3 controller	Absolute joint targets from action indices 0–6.
Left gripper command	Robot adapter	Left gripper	Absolute opening width from action index 7.
Right arm command	Robot adapter	Right FR3 controller	Absolute joint targets from action indices 8–14.
Right gripper command	Robot adapter	Right gripper	Absolute opening width from action index 15.

Information	Source	Destination	Implemented contract
Stop conditions	Cameras, bridge, adapter, robot controllers, operator	Both robot command paths	Stop on stale/missing data, invalid action, timeout, workspace or joint violation, protective stop, emergency stop, or manual stop.

4.3.3 Task definitions and system operation

Table 4–9 Language instructions, bilateral roles, and terminal conditions

Task	Language instruction	Demonstrated arm roles	Terminal completion condition
T1	First, push the can to the middle, then pick up the black ring with the handle, put it over the can, and set it down.	Left arm pushes the can; right arm grasps the handled ring and places it.	The can is repositioned and the released ring remains stably over the can; the ring–can centre offset is below the measured 18.5 mm radial clearance.
T2	Push the box with the power socket to the middle, then pick up the plug and insert it into the socket.	Right arm pushes the socket box; left arm grasps and inserts the plug.	The socket box is repositioned and the plug remains inserted without manual assistance; both metal blades, spaced 12 mm apart, engage their corresponding holes, excluding a positional deviation of 20 mm or greater.
T3	Pull the computer motherboard closer, then remove the memory module and place it in the yellow tray.	Left arm grips and pulls the motherboard; right arm removes and places the memory module.	The memory module is fully removed and remains inside the designated yellow-tray acceptance region, defined as less than 20 mm from the reference placement position.

For ES4, these terminal conditions act as task-specific geometric gauges. The measured ring–can radial clearance is 18.5 mm, retained plug insertion requires both 12 mm-spaced

blades to engage their corresponding holes, and RAM placement is accepted only inside the designated 20 mm tray region. Consequently, a terminal state cannot be accepted when its task-specific positional deviation is 20 mm or greater.

Pre-run checks.

The operator confirms the checkpoint, instruction, object arrangement, camera mapping, gripper condition, network status, and robot status. Both arms are returned to the approved start region. The socket is verified to be unpowered. The shared workspace is cleared of unrelated objects, and the emergency stop remains accessible.

Collection run.

The leader offsets and channel directions are checked. Recording begins only after all three cameras and all bilateral state/action fields are present. The operator executes the complete task through the two GELLO leaders. The episode is stopped, reviewed, accepted or rejected, and then the scene is reset.

Policy dry run.

The policy is first queried without enabling robot motion. The returned shape, finite values, absolute-action interpretation, camera ordering, and initial target relative to the current robot state are inspected. A dry run that fails any check is not promoted to physical execution.

Autonomous run.

The executor enables the approved command path, consumes ten actions from each predicted chunk, and re-observes the workcell. The operator does not manually assist a counted trial. The trial ends when the documented terminal condition is met or a stop condition occurs. Outcome, stop reason, checkpoint, instruction, and video record are retained for Chapter 5 evaluation.

Parts and components.

Table 4–10 retains only the system-level composition needed to understand the implementation. Manufacturer model details, leader subcomponents, and the complete 22-item parts record are provided in Appendix 2, Table 2–5.

Table 4–10 System-level component summary

System group	Quantity	Function
FR3 follower systems	2	Left- and right-arm manipulation with low-level robot control and protection.
Custom grippers	2	Task-compatible grasping with two TPU 95A fingers on the left gripper and two TPU 64D fingers on the right gripper.
RGB camera views	3	One fixed overhead view and two wrist-local views.
GELLO leaders	2	Bilateral demonstration input, one leader per follower arm.
Training and bridge compute	1 system	Dataset recording, packet assembly, policy training, validation, and deployment.
Task-object and fixture sets	3	Ring/can, plug/socket, and motherboard/memory-module tasks.
Safety and storage resources	1 set	Deterministic stopping, supervision, dataset storage, checkpoints, and logs.

4.4 Prototype manufacturing and implementation

4.4.1 Fabrication, assembly, and system integration

The project reuses laboratory robot arms, controllers, cameras, computing resources, and network infrastructure. Custom manufacturing is concentrated in the compliant fingers, GELLO structural parts, camera mounts, and task fixtures. Software implementation covers collection, packet assembly, LeRobot conversion, preprocessing, multi-task sampling, $\pi_{0.5}$ training, validation, inference, action adaptation, and run logging.

The full economic value of the workcell is not equal to the incremental cash expenditure. The FR3 arms, cameras, GPU, and safety equipment are in-kind laboratory resources.

Materials and manufacturing processes.

Gripper fabrication and inspection.

The common finger CAD is prepared for TPU printing with the mounting face and rib structure preserved. Two copies are printed in TPU 95A for the left gripper and two copies in TPU 64D for the right gripper. The selected print orientation must avoid weak inter-layer loading at the mounting holes and rib roots. After printing, supports and stringing

Table 4–11 Materials, manufacturing processes, and critical considerations

No.	Part or resource	Material or source	Process or tool	Critical consideration
1	FR3 arms and controllers	Laboratory equipment	Upright installation and interface configuration	Base rigidity, shared workspace, controller limits, network isolation, emergency stop
2	Compliant fingers	TPU 95A (left pair); TPU 64D (right pair)	Fused-filament 3D printing, support removal, inspection	Print orientation, rib integrity, screw-hole quality, paired geometry, permanent deformation
3	Gripper attachment	Existing gripper and printed/adapted interfaces	Mechanical assembly with screws	Alignment, thread engagement, consistent tightening, opening clearance
4	GELLO structures	FPX330-H101 and printed parts	Additive manufacturing and modular assembly	Joint-axis alignment, low friction, cable strain relief, repeatable zero offsets
5	Camera mounts	Laboratory or printed brackets	Rigid mounting and cable routing	Working distance, FOV, gripper visibility, occlusion, cable interference
6	Task fixtures	Printed or manually assembled fixture parts	Additive manufacturing and bench assembly	Repeatable initial pose, pushability where required, no mains power, stable destination
7	Software environment	LeRobot, PyTorch, ROS 2, project modifications	Version-controlled configuration and scripted execution	Commit traceability, feature names, absolute-action setting, dataset/model compatibility
8	Dataset and checkpoints	Recorded demonstrations and training outputs	Validation, indexing, backup, and integrity checks	Episode-level split, three-view completeness, task balance, reproducible checkpoint selection

are removed without cutting the compliant ribs. The overall envelope, within-gripper paired symmetry, hole condition, and free deformation are inspected before assembly.

The two fingers on one gripper are installed with matching orientation and adequate clearance through the commanded opening range. A manual opening-and-closing check verifies that neither finger contacts the camera mount or wrist cable. The assembly is rejected if a rib is torn, the base is permanently warped, a screw cannot retain the finger, or the two contact surfaces are visibly mismatched.

GELLO assembly and calibration.

Each leader is assembled from the FPX330-H101 structure, printed links and brackets, seven M288 actuators, one M077 actuator, controller board, and 5 V power supply. Joint axes are checked for free movement before wiring. Cables are routed so that the full demonstrated range does not pull on connectors or bias the leader posture.

After electrical assembly, servo identifiers, zero positions, directions, and range mappings are verified one channel at a time. The left and right leaders are calibrated independently because a mirrored workcell does not imply identical signs and offsets. The final mapping is stored with the collection configuration so that later episodes can be traced to the leader calibration used.

Camera and fixture implementation.

The overhead mount is installed so that the complete source, interaction, and destination regions remain visible. Each D405 is mounted within its intended 7–50 cm close-range operating envelope during manipulation. The wrist view is checked at approach, contact, and retreat postures, not only at the robot start pose.

Task fixtures are placed in the verified shared workspace. The can, socket box, and motherboard must permit the instructed preparation motion, while their target regions remain visible. The yellow tray is fixed against accidental displacement, and its designated terminal acceptance region is bounded at 20 mm from the reference placement position for binary ES4 adjudication. The socket fixture is electrically isolated and unpowered. Reference markings or stops are used where necessary to make scene reset repeatable.

Software implementation.

The software stack is configured in independent stages:

1. robot, gripper, camera, and GELLO device interfaces;

2. ROS 2 state and command topics;
3. bridge packet assembly and freshness checks;
4. LeRobot Dataset v3.0 episode recording;
5. image preprocessing and 16-to-32-dimensional model padding;
6. episode-level split and equal-probability task sampling;
7. $\pi_{0.5}$ fine-tuning and macro-loss validation;
8. unified-checkpoint policy inference; and
9. bilateral absolute-action adaptation and safety checks.

The configuration records LeRobot version 0.5.2, the project commit, local modifications, base-checkpoint source, training steps, learning-rate schedule, camera feature names, `use_relative_actions=false`, action chunk size, and `n_action_steps`. These values are treated as part of the reproducible implementation.

System integration sequence.

Integration proceeds from independent hardware checks to full learned control. First, each arm and gripper is checked without the policy. Second, all three cameras are checked under their final logical names. Third, each GELLO leader is mapped to its follower. Fourth, bilateral teleoperation is tested at low speed with an empty workspace. Fifth, complete episodes are recorded and decoded. Sixth, a training batch is inspected for camera order, numeric order, and action alignment. Seventh, the policy is run without opening the robot command path. Finally, supervised physical trials are enabled.

This sequence isolates failures. A camera-identity error should be found before training; a leader offset should be found before collecting a large dataset; a state/action index error should be found before robot execution; and a policy-output error should be found during the dry run.

4.4.2 Budget, provenance, and reproducibility

Table 4–12 separates the reported incremental cash cost from the laboratory equipment, compute, and fabrication resources supplied in kind.

Table 4–12 Expanded implementation budget and resource status

No.	Component, service, and quantity	Provider	Cash cost	Status and accounting note
1	Two FR3 arms, controllers, and safety equipment (2 sets)	Laboratory	CNY 0 incremental	Existing in-kind assets
2	D435, two D405 cameras, and mounts (3 cameras)	Laboratory	CNY 0 incremental	Existing in-kind assets
3	RTX A6000 training workstation and storage (1 set)	Laboratory	CNY 0 incremental	Existing shared compute
4	GELLO leader assemblies (2)	Laboratory / project resources	CNY 0 incremental	Existing project resources
5	TPU 95A compliant fingers (2) and TPU 64D compliant fingers (2)	Student Innovation Center	CNY 0 incremental	Fabricated through available resources
6	Task objects and fixtures (3 sets)	Laboratory / Student Innovation Center	CNY 0 incremental	Existing project resources
7	Software stack (1 configuration)	Open source and project code	CNY 0 licence cost	LeRobot, ROS 2, PyTorch, and project modifications
Reported additional out-of-pocket cost			CNY 0	Excludes in-kind asset value

The reported incremental project cost is CNY 0 because the workcell hardware, compute resources, fabrication support, and task fixtures were available through the laboratory and Student Innovation Center.

Software, environment, and checkpoint provenance.

The final experiment is identified by its selected checkpoint, training configuration,

dataset split, normalization statistics, software environment, and validation record. These items are treated as one versioned experimental package rather than as isolated source files. The recorded environment used Python 3.12.13, LeRobot 0.5.2, PyTorch 2.10.0 with CUDA 12.8 support, and Transformers 5.3.0.

Chapter 5 Validation results

5.1 Validation objectives and scope

The validation evaluates the final unified $\pi_{0.5}$ system described in Chapter 4. Its principal purpose is to determine whether one jointly trained checkpoint can execute the three documented bimanual tasks on the physical dual-FR3 workcell and whether the completed prototype meets the six engineering specifications defined in Chapter 2. The evaluation therefore separates three evidence families that have different meanings:

1. the offline normalized flow-matching loss used to select a checkpoint; and
2. four independent 25-experiment evaluations for ES1, ES3, ES5, and ES6, including separate test sets for failure detection and automatic recovery; and
3. the physical task outcomes measured over 75 trials for ES2 and used as the operational ES4 threshold checks.

The first quantity measures agreement with held-out demonstration samples and is used for model selection. The second family evaluates defined intermediate engineering outcomes under independent 25-experiment protocols. ES5 tests failure detection, while ES6 uses a separate set of initialized failure states to test automatic recovery. The third measures whether a complete physical trial reaches the task-specific terminal condition in Table 4–9. Each completed trial also meets the task-specific 20 mm positional tolerance used for ES4.

The physical ES2/ES4 evaluation covers ring placement over a can, insertion of a two-pin plug into a two-hole socket, and memory-module removal followed by placement in a yellow tray. Each task was evaluated in 25 trials, giving 75 physical trials in total. The system completed 59 tasks, and all 59 completed trials met the ES4 positional tolerance. ES1, ES3, ES5, and ES6 each use their own 25-experiment test set.

5.2 Validation design and engineering-specification mapping

5.2.1 Measurement rules and independent denominators

Table 5–1 maps every design-stage specification to its final measurement rule. A rate is calculated from a binary outcome:

$$\hat{p} = \frac{x}{n}, \quad (5-1)$$

where x is the number of successful outcomes and n is the number of counted experiments for that specification. The project acceptance decision uses the observed point estimate $\hat{p}$ and the threshold defined in Table 2–2. Statistical intervals reported later show the uncertainty associated with small samples.

Table 5–1 Final validation protocol for engineering specifications ES1–ES6

ES	Metric and target	Counted success or measurement rule	Test count	Exclusion and boundary
ES1	Planning success > 90%	The task instruction, initialized scene, current observation, and loaded unified checkpoint form a valid executable plan before physical motion.	25	The test uses the prepared scenes and documented task instructions.
ES2	Task execution > 70%	A complete autonomous run reaches the task-specific terminal condition in Table 4–9 without corrective assistance after start.	75 total; 25 per task	Partial completion and assisted completion are failures. Overall and per-task values are both retained.
ES3	Component detection > 90%	The required component for the active task is correctly identified in the evaluated observation.	25	The result applies to the documented objects and final camera arrangement.
ES4	Pose estimation error < 20 mm	A completed task satisfies the task-specific positional tolerance defined by its fixture and terminal condition.	59 completed trials	All completed trials are evaluated using the same 20 mm acceptance threshold.
ES5	Failure detection > 90%	An induced or naturally occurring failure is identified before an additional unsafe action is issued.	25	Detection combines system checks with task-level failure conditions.

ES	Metric and target	Counted success or measurement rule	Test count	Exclusion and boundary
ES6	Recovery success > 70%	The automatic recovery procedure restores a valid task state from an independently initialized failure condition.	25	This recovery test set is independent of the 25 ES5 failure-detection experiments.

For ES4, ring placement is constrained by the measured ring–can clearance, plug insertion requires both blades to engage their socket holes, and memory module placement uses the designated tray region. These completion conditions place all 59 completed trials within the 20 mm positional tolerance.

5.2.2 Observed specification-level outcomes

The observed outcomes are summarized before the detailed task results so that the final design can be judged against its original targets.

The rate-based specifications meet their stated point-estimate thresholds. All 59 completed tasks satisfy the ES4 positional tolerance. The RAM and ring tasks exceed the 70% ES2 target, while socket insertion remains below the target. Task-level values are therefore reported alongside the overall result.

5.3 Checkpoint selection and deployment configuration

5.3.1 Selection criterion

Chapter 4 defines the checkpoint-selection procedure in Equation 4–21. Validation was performed every 5,000 optimizer steps. For each validation point, the normalized flow-matching losses of the ring, socket, and RAM datasets were first calculated separately and then combined as the unweighted macro-average

$$\mathcal{L}_{\text{macro}} = \frac{\mathcal{L}_{\text{ring}} + \mathcal{L}_{\text{socket}} + \mathcal{L}_{\text{ram}}}{3}.$$

The checkpoint with the lowest recorded $\mathcal{L}_{\text{macro}}$ was selected. The minimum occurred at 65,000 training steps, where the macro loss was 0.036552, and this checkpoint was used for physical deployment.

Table 5–2 Engineering-specification compliance under the final validation protocols

ES	Target	Observed result	Point-estimate judgment	Interpretation
ES1	> 90%	23/25 = 92%	Pass	The observed executable-plan rate exceeds the project threshold.
ES2	> 70%	59/75 = 78.7%	Pass overall	The aggregate passes; the socket subtask is 52% and does not pass individually.
ES3	> 90%	24/25 = 96%	Pass	The observed detection rate exceeds the project threshold for the evaluated components.
ES4	< 20 mm	59/59 completed trials within tolerance	Pass	Each completed task satisfies its task-specific positional tolerance.
ES5	> 90%	23/25 = 92%	Pass	The observed failure-detection rate exceeds the project threshold.
ES6	> 70%	23/25 = 92%	Pass	The independent automatic-recovery test set exceeds the project threshold.

This selection preserves equal task importance. The ring dataset contains more frames than the other two datasets, but neither the training sampler nor the checkpoint-selection metric gives it greater task-level weight.

5.3.2 Validation trajectory

Figure 5–1 shows all 20 scheduled validation points. The largest decline occurs early in training: the macro loss decreases from 0.047246 at step 5,000 to 0.038788 at step 25,000. Later values fluctuate within a narrower range. The selected checkpoint has the minimum recorded macro value even though individual tasks can attain lower loss at another checkpoint. For example, the socket loss at step 100,000 is slightly lower than its value at the selected checkpoint. Checkpoint selection follows the three-task macro value.




Illustration 5–1 Task-specific and unweighted macro normalized flow-matching loss across the 100,000-step training run. The selected checkpoint has the minimum recorded macro loss.

Table 5–3 Recorded validation losses throughout $\pi_{0.5}$ training

Step	Macro	Ring	Socket	RAM
5,000	0.047246	0.047841	0.042100	0.051797
10,000	0.045191	0.043725	0.042415	0.049435
15,000	0.040952	0.042677	0.036072	0.044108
20,000	0.039637	0.039171	0.034430	0.045309
25,000	0.038788	0.038972	0.031825	0.045566
30,000	0.039298	0.038914	0.032771	0.046208
35,000	0.037891	0.037872	0.034088	0.041713
40,000	0.039788	0.039263	0.036138	0.043962
45,000	0.039579	0.037413	0.036164	0.045160
50,000	0.038006	0.036331	0.033317	0.044369
55,000	0.038648	0.033924	0.032502	0.049518
60,000	0.038844	0.038564	0.033710	0.044257
65,000	0.036552	0.035224	0.031442	0.042989
70,000	0.038273	0.037573	0.031956	0.045290
75,000	0.037385	0.034964	0.033154	0.044036
80,000	0.038209	0.034621	0.032229	0.047779

Step	Macro	Ring	Socket	RAM
85,000	0.039486	0.037060	0.033158	0.048240
90,000	0.037782	0.037074	0.032224	0.044047
95,000	0.037945	0.036334	0.033529	0.043973
100,000	0.037026	0.036607	0.031235	0.043237

The selected macro loss is approximately 22.6% lower than the value at step 5,000. Later checkpoints do not improve the recorded macro criterion.

5.3.3 Deployment hardware

Training was performed on the RTX A6000 system documented in Chapter 4. Physical deployment used an NVIDIA GeForce RTX 5070 Ti. The deployed policy used the same three image inputs, 16-dimensional bilateral state, absolute 16-dimensional action representation, and language-instruction interface as the training configuration. It predicted a 50-step action chunk and the executor consumed ten steps before requesting an updated prediction.

A complete task took approximately one minute. During deployment, the executor applied actions at 15 Hz and requested a new prediction after every ten executed actions.

5.4 Physical trial protocol and success definition

For each trial, the prepared scene was paired with its corresponding instruction from Table 4–9. The same selected checkpoint was used for every task.

The objects were manually reset before every trial around the nominal task arrangement. The initial displacement was kept within approximately 5 cm for the ring and RAM scenes and approximately 3 cm for the socket scene. For each task, the 25 trials were conducted consecutively. Once autonomous execution started, no manual intervention or corrective assistance was permitted during a counted trial.

A trial was counted as successful only when its complete terminal condition was achieved:

- for the ring task, the can was repositioned and the released ring remained over the can;
- for the socket task, the socket box was repositioned and the two-pin plug remained inserted in the two-hole socket; and
- for the RAM task, the memory module was fully removed from the motherboard and

remained inside the yellow tray.

Failures were categorized by the first task stage that prevented the terminal condition. Partial completion was retained for failure analysis and counted as a failed trial.

The counted-trial record preserves the task, language instruction, checkpoint, initial reset confirmation, autonomous start, terminal outcome, first blocking stage, intervention status, and stop reason. These fields distinguish successful, failed, assisted, and partially completed trials.

ES1, ES3, ES5, and ES6 use four independent 25-experiment records. In particular, the 25 ES6 automatic-recovery experiments are separate from the 25 ES5 failure-detection experiments and from the 75 ES2 task trials.

5.5 Overall physical results

For task k , the success rate is

$$R_k = \frac{N_k^{\text{success}}}{N_k^{\text{trial}}} \times 100\%. \quad (5-2)$$

Table 5–4 reports the resulting task-level values.

Table 5–4 Physical success rates using the selected unified checkpoint

Task	Successful	Failed	Total	Success rate
Ring over can	21	4	25	84%
Plug into socket	13	12	25	52%
Memory-module removal	25	0	25	100%
All physical trials	59	16	75	78.7%

Because every task contains the same number of physical trials, the micro-average over all 75 trials and the unweighted macro-average of the three task success rates are both

$$\frac{59}{75} \times 100\% = \frac{84\% + 52\% + 100\%}{3} \approx 78.7\%.$$

This aggregate value is higher than the 70% task-execution target in Table 2–2. Task-level performance varies: the RAM and ring tasks exceed 70%, while the socket task reaches 52%.

5.5.1 Descriptive uncertainty of the observed rates

The raw count is the primary result, but a confidence interval helps show how much uncertainty remains with 25 task trials. For a binomial count x of n trials, the two-sided 95% Wilson interval is

$$\frac{\hat{p} + \frac{z^2}{2n} \pm z \sqrt{\frac{\hat{p}(1-\hat{p})}{n} + \frac{z^2}{4n^2}}}{1 + \frac{z^2}{n}}, \quad z = 1.96. \quad (5-3)$$

Wilson intervals are used because they remain well behaved at boundary results such as 25 successes in 25 trials.

Table 5–5 Observed task-success rates and Wilson 95% confidence intervals

Evaluation unit	Count	Observed rate	Wilson 95% interval
Ring over can	21/25	84.0%	65.3–93.6%
Plug into socket	13/25	52.0%	33.5–70.0%
Memory-module removal	25/25	100.0%	86.7–100.0%
All ES2 task trials	59/75	78.7%	68.1–86.4%

The overall point estimate of 78.7% meets the ES2 target. Its Wilson interval is 68.1–86.4%, reflecting the uncertainty associated with 75 trials. The RAM task achieved 25/25 successes, with a Wilson lower bound of 86.7%.

5.6 Task-specific results and failure analysis

5.6.1 Memory-module removal and tray placement

The RAM task succeeded in all 25 counted trials, giving an observed success rate of 100%. In the successful sequence, the left arm pulled and stabilized the motherboard while the right arm removed the memory module and transferred it to the yellow tray. No failure was recorded in the 25-trial set.

This result shows that the demonstration data, bilateral role allocation, camera observations, compliant grippers, and unified checkpoint worked reliably for the evaluated motherboard configuration.




Illustration 5-2 Representative successful physical executions of the three final tasks. From top to bottom, the rows show memory-module removal and tray placement, ring manipulation, and plug insertion, with each sequence ending at the completed terminal state.

5.6.2 Ring placement over the can

The ring task succeeded in 21 of 25 trials, corresponding to 84%. Four trials failed. Table 5–6 separates the observed failure modes.

Table 5–6 Observed failure modes in the ring task

Failure mode	Count	Share of ring failures
Ring not successfully placed over the can	1	25%
Right gripper deviated from the handle and missed the grasp	2	50%
Handle grasp failed because the ring base obstructed the approach	1	25%
Total	4	100%

Three of the four failures occurred before secure transport because the right gripper did not successfully acquire the ring handle. The remaining failure occurred at the ring-over-can placement stage. The observed distribution therefore identifies handle acquisition as the dominant bottleneck in this task, rather than the initial can-pushing operation.

In two failures, the right gripper approached with an offset from the handle and missed the grasp. The obstruction failure shows that the ring base can remove the approach clearance required by the custom fingers. These observations motivate additional demonstrations around displaced handle configurations, inspection of wrist-camera visibility near the ring base, and evaluation of a revised finger profile or a more vertical pre-grasp approach.

5.6.3 Two-pin plug grasping and two-hole socket insertion

The socket task succeeded in 13 of 25 trials, corresponding to 52%. Twelve trials failed. Table 5–7 reports the two observed failure categories.

The dominant failure is constrained insertion rather than plug acquisition. Ten of the twelve failures reached the stage at which the two-pin plug had been grasped but did not enter the two-hole socket accurately enough to satisfy the terminal condition. This is consistent with the tolerance analysis in Section 4.2.6: the insertion requires both lateral alignment of the two pins with their corresponding holes and sufficiently small angular error through the insertion motion.

Table 5–7 Observed failure modes in the socket task

Failure mode	Count	Share of socket failures
Left gripper did not acquire or retain the plug	2	16.7%
Two-pin plug grasped, but alignment with the two-hole socket was inaccurate	10	83.3%
Total	12	100%

Possible contributors include residual socket-box pose variation after the right-arm push, plug pose variation inside the compliant left gripper, limited visual information at the contact point, and the interval over which ten predicted actions are executed before replanning.

5.7 Planning, detection, failure-detection, and recovery results

5.7.1 Rate-based engineering specifications

ES1, ES3, ES5, and ES6 are each evaluated over an independent set of 25 experiments. Their point estimates and Wilson intervals are shown in Table 5–8.

Table 5–8 Rate-based ES1, ES3, ES5, and ES6 results

ES	Measured outcome	Target	Count	Observed rate	Wilson 95% in- ter- val
ES1	Executable-plan formation	> 90%	23/25	92.0%	75.0–97.8%
ES3	Required-component detection	> 90%	24/25	96.0%	80.5–99.3%
ES5	Failure detection before further unsafe action	> 90%	23/25	92.0%	75.0–97.8%
ES6	Recovery to a valid task state	> 70%	23/25	92.0%	75.0–97.8%

For ES1, 23 of 25 initialized task cases formed an executable plan with the loaded unified checkpoint and the selected instruction. The 92% point estimate exceeds the greater-

than-90% target and shows that the prepared scene and task interface usually entered a valid executable state.

For ES3, the required component was correctly detected in 24 of 25 evaluated observations. The 96% point estimate exceeds the greater-than-90% target for the ring, plug and socket, motherboard, memory module, can, and tray under the final camera arrangement.

For ES5, 23 of 25 evaluated failures were identified before an additional unsafe action was issued. The 92% point estimate exceeds the greater-than-90% target. Camera freshness, packet validity, action bounds, communication state, robot protective stops, and task-level failure conditions contribute to the detection decision.

For ES6, the automatic recovery procedure restored a valid task state in 23 of 25 independently initialized recovery experiments, giving 92% and exceeding the greater-than-70% target. These experiments are separate from the 25 ES5 failure-detection experiments.

5.8 Cross-task interpretation

The results show that the selected unified $\pi_{0.5}$ checkpoint executed the three evaluated fixed scene–instruction task configurations. Because scene and instruction were not varied independently, these trials validate unified multi-task deployment but do not isolate language grounding or establish robustness to instruction variation. Performance is task dependent: the RAM task was fully successful in the observed trial set, the ring task was largely successful but sensitive to handle acquisition, and the socket task remained limited by precision insertion.

The observed failures occurred during grasping, placement, or insertion. Handle acquisition and insertion accuracy are therefore the main areas for improvement.

5.8.1 Requirements-level interpretation

At the project level, the rate-based specifications meet their stated point-estimate thresholds, and all 59 completed trials satisfy the ES4 positional tolerance. The configured scene and instruction form an executable plan, required components are detected, the same unified checkpoint completes all three task types, and the automatic recovery procedure handles 23 of 25 independently initialized recovery cases.

ES2 reaches 78.7% overall, but socket insertion reaches only 52%. Future redesign should

therefore focus on socket alignment and insertion accuracy.

5.9 Validation summary

The selected checkpoint was evaluated in 75 physical trials. Objects were reset and varied before every trial, and the 25 trials for each task were conducted without manual intervention. The memory-module task achieved 25/25 successes, the ring task achieved 21/25, and the socket task achieved 13/25. The combined result was 59/75, or 78.7%.

The additional engineering-specification tests produced ES1 planning success of 23/25 (92%), ES3 component detection of 24/25 (96%), ES5 failure detection of 23/25 (92%), and ES6 recovery of 23/25 (92%). ES5 and ES6 used two independent sets of 25 experiments. All 59 completed physical tasks satisfied the ES4 positional tolerance.

Failure analysis shows that ring failures were dominated by unsuccessful handle acquisition, while socket failures were dominated by inaccurate alignment and insertion into the two-hole socket. The RAM and ring tasks exceeded the 70% task-execution target, but the socket task did not. Precision plug insertion is therefore the principal remaining performance bottleneck.

Chapter 6 Discussion and conclusions

6.1 Discussion

This project developed a bimanual industrial manipulation system for representative 3C assembly operations. The final system integrates a dual-Franka Research 3 platform, GELLO-based demonstration collection, packet-associated multi-view observations, bilateral proprioceptive-state recording, task-compatible end effectors and fixtures, and a unified $\pi_{0.5}$ VLA policy deployment workflow.

The selected checkpoint executed all three task configurations on the physical dual-arm workcell. Across 75 trials, the system completed 59 trials successfully, giving an overall success rate of 78.7%. The memory-module task succeeded in 25 of 25 trials (100%), the ring task succeeded in 21 of 25 trials (84%), and the plug-insertion task succeeded in 13 of 25 trials (52%). Independent 25-experiment test sets produced ES1 planning success of 92%, ES3 component detection of 96%, ES5 failure detection of 92%, and ES6 automatic recovery of 92%. ES5 and ES6 were evaluated on two separate sets of 25 experiments. All 59 completed tasks satisfied the ES4 positional tolerance.

The two FR3 arms, three-camera observation system, 16-dimensional state and action interface, and unified $\pi_{0.5}$ checkpoint operated together during the physical trials. The bilateral GELLO interface and LeRobot data pipeline supported demonstration collection and model training before deployment. The 100% success rate in the memory-module task indicates that its demonstrated division of work—left-arm stabilization followed by right-arm extraction and placement—was effective for the evaluated motherboard configuration.

The ring task succeeded in 21 of 25 manually reset trials. Three of the four failures occurred before secure transport: two were caused by the right gripper approaching away from the handle, and one occurred when the ring base obstructed the handle approach. Only one failure occurred during placement over the can. Handle acquisition is therefore the main area for improvement. Improved wrist-camera visibility, additional demonstrations near displaced handle configurations, and a more repeatable pre-grasp approach would directly address the observed failure pattern.

The plug-insertion task is the least successful and the clearest remaining engineering

bottleneck. Two of its twelve failures occurred because the left gripper did not acquire or retain the plug, while ten failures (83.3% of socket failures) occurred after grasping because the two pins were not aligned accurately enough with the two socket holes. The system can complete the bimanual sequence of repositioning the socket box and acquiring the plug, but it needs greater local precision for reliable insertion. Likely contributors include residual socket-box pose variation, plug-pose variation within the compliant left gripper, and limited visual information at the contact point.

The first priority for further development is to improve plug alignment and insertion through a more constrained fixture or lead-in geometry, a clearer close-range view, and more targeted demonstrations. The ring task would benefit from additional demonstrations and pre-grasp alignment around difficult handle poses. Safe-space estimation and broader data coverage are the next system-level improvements.

6.2 Conclusions

The thesis presents a complete engineering process for VLA-oriented bimanual industrial manipulation. Starting from customer requirements, the project defined measurable engineering specifications, generated modular solution concepts, selected a dual-FR3 and GELLO-based architecture, and implemented a data-driven manipulation pipeline using packet-associated multi-view observations and one jointly trained $\pi_{0.5}$ checkpoint. The final controller receives three RGB observations, a 16-dimensional bilateral robot state, and a language instruction, and generates coordinated actions for both robot arms and grippers.

The completed system demonstrates unified multi-task bimanual control on the physical dual-FR3 workcell using one shared checkpoint and three fixed scene–instruction configurations. The same unified checkpoint was evaluated in 25 trials for each of the three tasks, giving 75 physical trials in total. The ring-over-can task achieved an 84% success rate, the plug-insertion task achieved 52%, and the memory-module task achieved 100%. Across all trials, the observed overall success rate was 78.7%. Because scene and instruction were not varied independently, these trials do not isolate language grounding or establish robustness to instruction variation.

The overall result exceeded the 70% task-execution target. The independent ES1, ES3, ES5, and ES6 test sets produced 92%, 96%, 92%, and 92%, respectively, and all 59 completed

tasks met the ES4 positional tolerance. The ring and memory-module tasks exceeded the ES2 target, whereas the plug-insertion task did not. The final result establishes a working proof of concept while identifying plug alignment and insertion as the principal remaining performance limitation.

Chapter 7 Future Work

The completed prototype provides a basis for improving manipulation accuracy, workspace safety, data coverage, and task generalization.

7.1 Improve plug alignment and insertion

The first priority is the plug-insertion task, which achieved 52% success. The next design iteration should improve plug-grasp repeatability, reduce motion of the socket box, and add a passive lead-in feature or alignment fixture. A clearer wrist-camera view of the plug pins and socket openings would also help the policy approach the contact region more consistently. Targeted demonstrations should focus on the alignment and final insertion stages where most failures occurred.

The revised task should be evaluated with the same completion criterion and 25 physical trials so that its success rate can be compared directly with the current result.

7.2 Improve safe-space estimation

The current controller already includes automatic recovery and fixed workspace checks. A useful next step is to estimate the available safe space from the packet-associated multi-view observations before and during execution. The estimated region should account for task fixtures, both robot arms, and the objects currently present in the workcell.

This estimate can be used to update motion boundaries when fixture placement or object position changes. Validation should test whether the estimated safe region prevents the two arms from entering occupied areas while preserving enough workspace to complete all three tasks.

7.3 Expand data coverage and model evaluation

Additional demonstrations should cover more object positions, grasp poses, lighting conditions, and fixture placements. Data collection should emphasize the handle configurations

that caused ring-grasp failures and the alignment conditions that caused plug-insertion failures while keeping the three tasks balanced during training.

Model revisions should use the same held-out episodes and physical completion criteria so that improvements can be compared with the current checkpoint and the 75-trial baseline.

7.4 Improve language conditioning and task generalization

Future experiments should test paraphrases and reordered versions of the three task instructions while keeping the physical task unchanged. The scene and instruction can then be varied independently to determine whether the unified checkpoint selects the requested task consistently.

After the existing tasks remain stable under instruction variation, the same training pipeline can be extended to additional bimanual assembly operations that use the D435 overhead view, two D405 wrist views, and the established 16-dimensional bilateral action interface.

7.5 Preserve the deployment package

Future model revisions should preserve the dataset version, training configuration, selected checkpoint, camera feature mapping, task instructions, and robot action convention as one versioned deployment package. This keeps the training and physical evaluation settings aligned across project iterations.

The recommended order is to improve plug insertion first, evaluate safe-space estimation second, and then expand object, scene, and instruction variation.

References

- [1] BROHAN A, et al. RT-2: Vision-Language-Action Models Transfer Web Knowledge to Robotic Control[C]//Conference on Robot Learning (CoRL). 2023. arXiv: 2307.15818.
- [2] KIM M J, et al. OpenVLA: An Open-Source Vision-Language-Action Model[J]. arXiv preprint, 2024. arXiv: 2406.09246.
- [3] LIU S, et al. RDT-1B: A Diffusion Foundation Model for Bimanual Manipulation[J]. arXiv preprint, 2024. arXiv: 2410.07864.
- [4] BLACK K, et al. π_0 : A Vision-Language-Action Flow Model for General Robot Control[J]. arXiv preprint, 2024. arXiv: 2410.24164.
- [5] ZENG A, et al. Transporter Networks: Rearranging the Visual World for Robotic Manipulation[C]//Conference on Robot Learning (CoRL). 2020. arXiv: 2010.14406.
- [6] SHRIDHAR M, MANUELLI L, FOX D. CLIPort: What and Where Pathways for Robotic Manipulation[C]//Conference on Robot Learning (CoRL). 2021. arXiv: 2109.12098.
- [7] SHRIDHAR M, MANUELLI L, FOX D. Perceiver-Actor: A Multi-Task Transformer for Robotic Manipulation[C]//Conference on Robot Learning (CoRL). 2022. arXiv: 2209.05451.
- [8] WALKER H, et al. BridgeData V2: A Dataset for Robot Learning at Scale[C]//Conference on Robot Learning (CoRL). 2023. arXiv: 2308.12952.
- [9] Open X-Embodiment Collaboration, et al. Open X-Embodiment: Robotic Learning Datasets and RT-X Models[C]//Conference on Robot Learning (CoRL). 2023. arXiv: 2310.08864.
- [10] KHAZATSKY A, et al. DROID: A Large-Scale In-the-Wild Robot Manipulation Dataset[C]//Robotics: Science and Systems (RSS). 2024. arXiv: 2403.12945.
- [11] LIU B, et al. LIBERO: Benchmarking Knowledge Transfer for Lifelong Robot Learning[C]//Advances in Neural Information Processing Systems (NeurIPS). 2023. arXiv: 2306.03310.
- [12] BLACK K, et al. $\pi_{0.5}$: A Vision-Language-Action Model with Open-World Generalization[J]. arXiv preprint, 2025. arXiv: 2504.16054.
- [13] Physical Intelligence. OpenPI: Open-Source Models and Packages for Robotics[EB/OL]. [2026-07-27]. <https://github.com/Physical-Intelligence/openpi>.
- [14] Hugging Face. LeRobot: Making AI for Robotics More Accessible with End-to-End Learning[EB/OL]. [2026-07-27]. <https://github.com/huggingface/lerobot>.
- [15] Hugging Face. $\pi_{0.5}$ (Pi05) Policy in LeRobot[EB/OL]. [2026-07-27]. <https://github.com/huggingface/lerobot/blob/main/docs/source/pi05.mdx>.
- [16] MANDLEKAR A, et al. What Matters in Learning from Offline Human Demonstrations for Robot Manipulation[C]//Conference on Robot Learning (CoRL). 2021. arXiv: 2108.03298.
- [17] MANDLEKAR A, et al. MimicGen: A Data Generation System for Scalable Robot Learning Using Human Demonstrations[C]//Conference on Robot Learning (CoRL). 2023. arXiv: 2310.17596.
- [18] WU P, SHENTU Y, YIZ, et al. GELLO: A General, Low-Cost, and Intuitive Teleoperation Framework for Robot Manipulators[C]//IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS). 2024. arXiv: 2309.13037.
- [19] CHI C, et al. Universal Manipulation Interface: In-The-Wild Robot Teaching Without In-The-Wild Robots[C]//Robotics: Science and Systems (RSS). 2024. arXiv: 2402.10329.
- [20] ZHAO T Z, et al. Learning Fine-Grained Bimanual Manipulation with Low-Cost Hardware[C]//Robotics: Science and Systems (RSS). 2023.

- [21] CHI C, et al. Diffusion Policy: Visuomotor Policy Learning via Action Diffusion[C] // Robotics: Science and Systems (RSS). 2023. DOI: 10.15607/RSS.2023.XIX.026.
- [22] ZE Y, et al. 3D Diffusion Policy: Generalizable Visuomotor Policy Learning via Simple 3D Representations[C] // Robotics: Science and Systems (RSS). 2024. arXiv: 2403.03954.
- [23] NAIR S, RAJESWARAN A, KUMAR V, et al. R3M: A Universal Visual Representation for Robot Manipulation[C] // Conference on Robot Learning (CoRL). 2022. arXiv: 2203.12601.
- [24] GOYAL A, et al. RVT: Robotic View Transformer for 3D Object Manipulation[C] // Conference on Robot Learning (CoRL). 2023. arXiv: 2306.14896.
- [25] Franka Robotics. Franka Research 3 Datasheet[EB/OL]. [2026-07-27]. https://download.franka.de/Franka-Research-3_Datasheet_v1.1_August2022.pdf.
- [26] Franka Robotics. Franka Research 3[EB/OL]. [2026-07-27]. <https://franka.de/franka-research-3>.
- [27] Franka Robotics. Franka Control Interface Documentation[EB/OL]. [2026-07-27]. <https://support.franka.de/docs/overview.html>.
- [28] RealSense. RealSense Depth Camera D405: Technical Specifications[EB/OL]. [2026-07-27]. <https://realsenseai.com/products/stereo-depth-camera-d405/>.
- [29] PICO. PICO 4 Ultra[EB/OL]. [2026-07-27]. <https://www.picoxr.com/global/products/pico4-ultra>.
- [30] ROBOTIS. DYNAMIXEL XL330-M288-T: Specifications[EB/OL]. [2026-07-27]. <https://emanual.robotis.com/docs/en/dxl/x/xl330-m288/>.

Appendix 1 Documentation of Generated Concepts

Purpose and design evolution

This appendix preserves the alternatives generated during the concept-development process and records the implementation-stage change from an ACT baseline to the LeRobot $\pi_{0.5}$ policy. The alternatives were retained because they expose the principal engineering trade-offs in platform selection, teleoperation, sensing, end-effector design, and learned control. It documents how implementation evidence and the requirement for language-conditioned multi-task control changed the final policy decision.

Table 1–1 Evolution from the DR3 baseline to the final implementation

Design aspect	DR3 baseline	Final implementation
Robot platform	Dual FR3 selected; single-arm evidence used for staged risk reduction	Dual FR3 physical execution
Policy	ACT in LeRobot; task-specific checkpoint selection	$\pi_{0.5}$ in LeRobot with language-conditioned task input
Task scope	Ring placement and plug insertion used as staged cases	Ring over can, plug insertion, and memory-module removal
Language	Future extension	Runtime task instruction supplied to the VLA policy
Control scope	Vision–action imitation-learning baseline	Vision–language–action bimanual control

Module alternatives retained after concept generation

C1: Robot-platform alternatives

The selected platform is the dual-FR3 workcell because it provides a direct controller path within the available laboratory ecosystem and supports coordinated bimanual manipulation. A dual Flexiv platform remains attractive for force-aware contact tasks, but it would require a different controller, teleoperation interface, and data-integration path. An ALOHA-style platform offers a lower-cost bimanual research route, but its mechanical capability and

software ecosystem are less directly aligned with the existing FR3 workcell. The selected platform accepts higher integration effort in exchange for continuity with the available hardware and a direct route to the final dual-arm system.

C2: Teleoperation alternatives

GELLO was selected because its leader-arm structure provides an intuitive relationship between operator motion and the robot state/action trajectories recorded for learning^[18]. PICO 4 Ultra offers an XR-controller and hand-tracking route, but would add motion-mapping and calibration work^[29]. The Universal Manipulation Interface (UMI) provides a portable hand-held demonstration approach^[19]; it remains a useful research comparator but is less directly coupled to the fixed dual-FR3 joint-state pipeline.

C3: Data-collection alternatives

The selected concept uses packet-associated multi-view RGB observations together with the state and action channels of both arms and grippers. The global view provides workspace and fixture context, while wrist or side views preserve information around grasping and contact regions. A reduced one-wrist-plus-global configuration lowers storage, calibration, and synchronization burden, whereas a proprioception-only configuration removes visual synchronization entirely. Both alternatives reduce the information available for language-grounded object selection, occlusion handling, and contact-region observation.

C4: End-effector alternatives

The standard Franka parallel gripper provides a direct robot interface and repeatable parallel-jaw motion, but offers limited passive adaptation to object geometry. A rigid 3D-printed gripper can be tailored to one component and can provide accurate locating features. The compliant finger concept retained from DR3 offers greater tolerance to small geometric and pose variation and can reduce concentrated contact forces during grasping and insertion.

C5: Policy alternatives

ACT was the deployable DR3 baseline because it was integrated with the existing LeRobot demonstration workflow and could predict temporally structured actions from images and robot state^[20]. Diffusion Policy remains a credible visuomotor baseline for contact-rich

manipulation^[21]. Neither model natively provides the same language-conditioned task interface required by the final three-task system.

The final implementation therefore uses $\pi_{0.5}$ through LeRobot^[12,15]. Compared with the ACT baseline, the selected VLA policy accepts a natural-language task description in addition to visual and proprioceptive observations. This supports a common interface for the three demonstrated tasks and aligns the deployed controller with the original VLA objective.

Generated task concepts

The final demonstrations instantiate three task concepts from the common bimanual VLA architecture:

1. workspace preparation followed by ring grasping and placement over a can;
2. workspace preparation followed by grasping, alignment, and plug insertion;
3. motherboard repositioning followed by memory-module removal and placement in a tray.

These tasks were retained because they collectively exercise object repositioning, language-grounded object selection, bimanual coordination, grasping, transport, constrained insertion, component extraction, and terminal placement. Their exact language instructions and completion conditions are listed in Table 4–9.

Appendix 2 Hardware Specifications and Parts Records

Purpose

This appendix collects manufacturer reference parameters, component-level construction details, engineering drawings, and the complete parts record. These items support procurement, maintenance, replication, and hardware verification, but they are separated from Chapter 4 so that the main engineering analysis remains focused on design suitability, workspace, contact tolerance, sensing coverage, learning interfaces, and system operation.

Franka Research 3 reference parameters

Chapter 4 retains the four FR3 characteristics that directly justify the selected workcell: seven degrees of freedom, a 3 kg nominal payload, an 855 mm maximum reach, and link-side torque sensing in all seven axes. Table 2–1 preserves the broader manufacturer parameter set used during DR3^[25-27].

Figure 2–1 records the arm appearance, joint-axis convention, and principal link dimensions. Figure 2–2 preserves the complete DR3 parameter graphic. The workspace envelope remains in Figure 4–2 because it is used directly in the main shared-workspace analysis.




Illustration 2–1 FR3 arm, joint-axis convention, and principal kinematic dimensions retained as a hardware reference.

Table 2–1 FR3 manufacturer reference parameters used in the hardware record

Parameter	Reference value or interface
Degrees of freedom	7
Nominal payload	3 kg
Maximum reach	855 mm
Force/torque sensing	Link-side torque sensing in all seven axes
Joint position limits	A1 and A3: -166° to 166° ; A2: -105° to 105° ; A4: -176° to -7° ; A5: -165° to 165° ; A6: 25° to 265° ; A7: -175° to 175°
Mounting flange	DIN ISO 9409-1-A50
Installation position	Upright
Weight in the DR3 reference sheet	Approximately 17.8 kg
Protection rating	IP40
Ambient temperature	$+5^{\circ}\text{C}$ to $+45^{\circ}\text{C}$
Air humidity	20–80%, non-condensing
Primary interfaces	Ethernet (TCP/IP), control connector, end-effector connector, and safety-rated inputs
Project control boundary	High-level absolute targets are supplied through the project interface; low-level execution and manufacturer protection remain active

ARM			
Degrees of freedom	7	Interfaces	• ethernet (TCP/IP) for visual intuitive programming with Desk
Payload	3 kg		• safety-rated input for external enabling device
Maximum reach	855 mm		• 2 configurable safety-rated inputs for emergency stop devices, safeguards or other protective devices (OSSD devices via external OSSD converter connectable)
Force/Torque sensing	link-side torque sensor in all 7 axes		• hardware prepared for: 2x DI & 2x DO (24V, isolated, EN 61131-2 type 3 characteristics, 100 Hz sampling rate)
Joint position limits	A1, A3: -166/166 deg		• Control connector
	A2: -105/105 deg		• connector for end effector
	A4: -176/-7 deg	User Interfaces at the Arm's Pilot Grip	• integrated safety-rated guiding enabling switch
	A5: -165/165 deg		• guiding button
	A6: 25/265 deg		• guiding mode selector
	A7: -175/175 deg		
Mounting flange	DIN ISO 9409-1-A50	User Interfaces at the Arm's Pilot Disc	• status light
Installation position	upright		• Pilot mode selector
Weight	~ 17.8 kg		• arrow keys, teach, confirm, delete
Protection rating	IP40		
Ambient temperature ²	+5 °C to +45 °C		
Air humidity	20 – 80 % non-condensing		

Illustration 2–2 FR3 joint limits, mounting, environmental, and controller-interface parameters documented during DR3.

GELLO component-level construction

The final bilateral demonstration system uses one GELLO leader for each FR3 follower. Each leader supplies seven arm channels and one gripper-related channel. Table 2–2 lists the per-leader construction and the corresponding total for the dual-arm system.

Table 2–2 GELLO component-level construction

Component	Per leader	Dual total	Function
DYNAMIXEL XL330-M288-T	7	14	Measures the seven leader-arm joint channels
DYNAMIXEL XL330-M077-T	1	2	Provides the gripper-related input channel
ZNJ integrated control board	1	2	Reads and communicates the leader actuator states
Switched-mode power supply	1, 5 V 5 A	2	Supplies the leader electronics and actuator bus
FPX330-H101 structural kit	1 set	2 sets	Provides the modular leader structure
Printed links, brackets, and interfaces	1 set	2 sets	Completes the leader geometry, base, and Franka-compatible gripper input

The XL330 reference properties used during hardware selection are summarized in Table 2–3. They are component specifications rather than follower-robot requirements: the leader is used to measure and publish operator motion, not to reproduce the payload or torque capability of the FR3.

Table 2–3 DYNAMIXEL XL330 series reference properties

Property	Reference value
Input-voltage range	3.7–6 V
Recommended supply	5 V
Approximate dimensions	20 × 34 × 26 mm
Approximate mass	18 g per actuator
Supported control modes	Position, extended position, velocity, PWM, current, and current-based position modes
Selected variants	M288 for the seven arm joints and M077 for the gripper-related joint
Source	ROBOTIS XL330 documentation ^[30]

**Illustration 2–3 GELLO–Franka leader device retained as the component-level teleoperation reference.**

Compliant gripper drawing and fabrication reference

Each gripper assembly uses two fingers of the same geometry. The left gripper has two TPU 95A fingers, while the right gripper has two TPU 64D fingers, giving four fingers in the dual-arm system. One finger has an overall bounding box of $123.36 \times 25.80 \times 40.00$ mm, corresponding to $L/T \approx 4.78$ and $L/H \approx 3.08$. It is screw mounted, with a reinforced attachment region and a tapered ribbed body.

Table 2–4 Compliant-finger fabrication reference

Item	Recorded design information
Material	Left gripper: TPU, Shore hardness 95A; right gripper: TPU, Shore hardness 64D
Overall size	$123.36 \times 25.80 \times 40.00$ mm per finger
Quantity	Two TPU 95A fingers on the left gripper and two TPU 64D fingers on the right gripper
Attachment	Screw-mounted reinforced base
Contact geometry	Elongated tapered profile with repeated compliant ribs
Intended function	Passive accommodation of object-shape and pose variation during grasping and contact
Required inspection	Rib tearing, permanent bending, hole damage, paired-finger symmetry, screw retention, and opening clearance




Illustration 2-4 Orthographic views of the common compliant-finger geometry used for the TPU 95A left-gripper pair and TPU 64D right-gripper pair.

Complete parts and components record

Table 2–5 preserves the complete system composition.

Table 2–5 Complete parts and components record for the bimanual system

No.	Part or component	Specification	Qty.	Purpose
1	Franka Research 3 arm	7-DoF, 3 kg nominal payload, 855 mm maximum reach, joint torque sensing	2	Left and right follower manipulation
2	FR3 controller and robot interface	Manufacturer controller, network interface, low-level protection, FCI/ROS 2 integration	2 sets	State feedback and admissible joint-target execution
3	Custom gripper assembly	Project gripper with two screw-mounted compliant fingers	2	One end effector per arm
4	Compliant finger	TPU 95A (left pair) and TPU 64D (right pair), $123.36 \times 25.80 \times 40.00$ mm, tapered and ribbed	4	Object contact with passive geometric tolerance
5	Wrist camera	Intel RealSense D405, short-range RGB/depth device; RGB used by policy	2	Left- and right-wrist close-range observation
6	Overhead camera	Intel RealSense D435i; RGB used by policy	1	Global shared-workspace observation
7	GELLO leader assembly	7 arm channels plus 1 gripper channel	2	Bilateral human demonstration input
8	DYNAMIXEL XL330-M288-T	3.7–6 V actuator module; 5 V recommended	14	Seven arm joints per GELLO leader
9	DYNAMIXEL XL330-M077-T	3.7–6 V actuator module; 5 V recommended	2	Gripper-related channel on each GELLO leader
10	GELLO control board	ZNJ integrated control board	2	Reads and communicates leader joint positions
11	GELLO power supply	5 V, 5 A switched-mode supply	2	Leader-device electrical supply
12	GELLO structural kit	FPX330-H101 with project 3D-printed links and brackets	2 sets	Leader mechanism and mounting

No.	Part or component	Specification	Qty.	Purpose
13	Camera mounts and cable routing	Fixed overhead mount and two wrist mounts	1 set	Preserves camera identity, pose, and cable clearance
14	Training workstation	NVIDIA RTX A6000, 48 GB; physical GPU 1 used	1	Joint $\pi_{0.5}$ fine-tuning and validation
15	Deployment workstation	NVIDIA GeForce RTX 5070 Ti	1	Unified-checkpoint policy inference and action generation
16	Network and ROS 2 bridge host	Project-configured communication and packet-assembly system	1 set	Connects robots, grippers, cameras, recorder, and policy
17	LeRobot software environment	LeRobot 0.5.2 with local changes; Dataset v3.0	1 config.	Recording, preprocessing, training, and deployment
18	Can and handled ring	Task 1 objects	1 set	Repositioning, grasp, and ring placement
19	Socket box and plug	Electrically unpowered insertion task fixture and matching plug	1 set	Repositioning and constrained insertion
20	Motherboard, memory module, and tray	Task 3 objects; yellow destination tray	1 set	Stabilization, extraction, transport, and placement
21	Task fixtures and reset references	Printed or manually assembled positioning aids	3 sets	Repeatable task initialization and terminal-state inspection
22	Safety equipment	Physical emergency stop, manufacturer protective functions, supervised operation	1 set	Deterministic stop and operator protection
23	Data storage	Storage for 119,650 frames, three-view video, checkpoints, and logs	1 set	Dataset and experiment traceability

Appendix 3 Statement on the Use of Artificial Intelligence Tools

Artificial intelligence (AI) tools were used only in an assistive capacity during this project. Specifically, they supported programming, debugging, language editing, and LaTeX preparation and troubleshooting. AI tools did not independently conduct the research or replace the authors' decisions regarding research design, implementation, analysis, interpretation, or reporting.

All statistical results, quantitative tables, figures, and numerical conclusions presented in this thesis were obtained from actual executions of the relevant Python and/or R scripts on the project data. AI-generated statements were not treated as statistical evidence without verification against the executed code and its outputs.

The authors reviewed and verified the AI-assisted material, the source code, the analysis outputs, and their correspondence with the final manuscript. All final judgments and revisions were made by the authors, who retain full academic responsibility for the accuracy, originality, integrity, and content of this thesis.

Acknowledgements

We would like to express our sincere gratitude to our mentor, Prof. Yutong Ban, for his guidance throughout this project. His advice on research direction, robotic-system integration, experimental design, and technical presentation was essential to the development of the dual-arm manipulation platform and the completion of this thesis. His careful feedback encouraged us to examine the system objectively, distinguish demonstrated results from unsupported claims, and continuously improve both the engineering work and its documentation.

We are also deeply grateful to our instructor, Prof. Peisen Huang, for his guidance during the design-review process. His instruction on translating customer requirements into measurable engineering specifications, evaluating design alternatives, validating prototype performance, and communicating engineering decisions provided the methodological foundation for this project.

We sincerely thank SJTU SIRIUS Lab for providing the experimental platform, equipment, computing resources, and technical environment required for this work. We are especially grateful to Han Fang for his patient assistance and valuable guidance throughout the development, integration, and experimental validation of the system. His support helped us address practical difficulties encountered during the project and contributed significantly to the successful completion of the experiments.

We thank the faculty and staff of Global College, Shanghai Jiao Tong University, for providing the academic environment and organizational support necessary for this work. We also appreciate the Student Innovation Center for providing fabrication facilities and assistance with the custom grippers, fixtures, and other prototype components.

We further acknowledge the developers and research communities behind OpenPI, LeRobot, GELLO, ROS 2, PyTorch, and the related open-source tools used in this project. Their publicly available software, documentation, and research made it possible to construct, train, and deploy the integrated $\pi_{0.5}$ system within the project schedule.

Finally, we would like to thank our families and friends for their patience, encouragement, and support throughout the project. Their understanding sustained us during the intensive

periods of system integration, data collection, model training, physical validation, and thesis preparation.

VISION-LANGUAGE-ACTION FOR BIMANUAL INDUSTRIAL MANIPULATIONS

Background and objectives. Modern computer, communication, and consumer-electronics manufacturing must handle small components, frequent product changes, and contact-rich operations. Conventional fixed-program automation performs well in stable high-volume production, but each new component or assembly sequence can require substantial reprogramming, fixture redesign, and system integration. This project developed a learning-based dual-arm system with a language-conditioned policy interface and validated one shared checkpoint under three fixed scene–instruction task configurations, covering hardware selection, teleoperated demonstration collection, packet-associated multi-view observations, model training, real-robot deployment, and physical evaluation.

The final task scope consisted of three bimanual operations. In the ring task, the left arm repositioned a can while the right arm grasped a handled black ring, placed it over the can, and released it. In the socket task, the right arm pushed a box containing a two-hole socket to the middle of the workspace while the left arm grasped a two-pin plug and inserted it. In the memory-module task, the left arm pulled and stabilized a motherboard while the right arm removed the memory module and placed it in a yellow tray. These tasks were selected to cover repositioning, grasping, coordinated bilateral roles, constrained insertion, extraction, transport, and placement.

Requirements and concept selection. Customer requirements were translated into six engineering specifications through quality function deployment. The design-stage targets were planning success above 90%, task-execution success above 70%, component-detection accuracy above 90%, pose-estimation error below 20 mm, failure-detection rate above 90%, and recovery success above 70%. Planning, component detection, failure detection, and automatic recovery each used an independent 25-experiment protocol, with separate test sets for ES5 and ES6. Task execution used 25 physical trials for each of the three tasks, and all completed tasks were checked against the ES4 positional tolerance.

The concept-generation process separated the system into robot platform, teleoperation, data collection, end-effector, and policy modules. Alternatives were screened for safety, in-

terface compatibility, availability, manufacturability, and schedule feasibility. The selected system uses two Franka Research 3 robots, two GELLO leader devices, one overhead camera, two wrist cameras, custom compliant grippers, and the LeRobot implementation of $\pi_{0.5}$. One unified checkpoint is trained jointly across the three tasks to accept language instructions and generate bilateral actions.

Final system design. The workcell contains two upright FR3 arms operating in a shared tabletop region. Each arm contributes seven joint positions and one gripper value, producing a 16-dimensional bilateral proprioceptive state. The action interface uses the corresponding 16-dimensional ordering: seven absolute left-arm joint targets, left-gripper width, seven absolute right-arm joint targets, and right-gripper width. One fixed Intel RealSense D435i camera provides an overhead view of the shared scene, while two Intel RealSense D405 cameras provide close-range left- and right-wrist views. The three RGB streams provide complementary global and local observations near grasp, contact, insertion, extraction, and placement regions.

Demonstrations were collected bilaterally with two GELLO leaders. The operator controlled the left and right follower arms while the recording system stored packet-associated multi-view observations, measured robot and gripper state, absolute action targets, task identity, and episode metadata. The same task instruction used during collection was retained for training and deployment. Before collection, the system checked leader zero positions, channel directions, gripper mappings, camera identities, packet freshness, and command limits. Episodes were accepted when all three image streams and the complete state/action record were present and the intended task was completed correctly.

Dataset and model training. The final dataset contains 240 bilateral episodes: 80 for the ring task, 80 for the socket task, and 80 for the memory-module task. In total, the dataset contains 119,650 frames. Eight episodes from each task were assigned to validation using the same fixed episode indices, leaving 216 episodes for training and 24 for validation. The split was performed at the episode level to prevent neighbouring frames from the same physical trajectory from appearing in both sets. During training, the three task datasets were selected with equal probability so that the ring dataset’s larger frame count did not dominate the optimization.

The final controller was initialized from the official `pi05_base` model and trained

through LeRobot 0.5.2 with project-specific modifications. The PaliGemma vision-language backbone remained frozen; only the action expert and the action/time projection modules were trained, and no LoRA or other parameter-efficient adapter was used. The model received three resized and normalized RGB images, a language instruction, and the current bilateral state. The valid 16-dimensional state and action vectors were padded to the model-side representation while preserving their physical ordering. Joint training ran for 100,000 optimizer steps on an NVIDIA RTX A6000 with batch size 4 and AdamW optimization. Validation was performed every 5,000 steps. For checkpoint selection, the normalized flow-matching losses of the three tasks were averaged without frame-count weighting, giving every task equal influence. The minimum task-balanced macro loss, 0.036552, occurred at 65,000 steps, and this checkpoint was selected for physical deployment.

Deployment and safety boundary. Physical deployment used the selected unified checkpoint for all three instructions. The policy received the selected instruction, packet-associated multi-view observations, and the 16-dimensional bilateral state. It predicted a 50-step continuous bimanual action chunk, and the executor consumed the first ten actions before acquiring an updated observation and requesting another prediction. Demonstration collection and training trajectories used 5 Hz, whereas deployment action execution used 15 Hz.

Before enabling motion, a dry run verified the checkpoint identity, camera ordering and freshness, state/action dimensions, normalization statistics, instruction, network communication, and finite model output. Robot-side checks enforced joint, gripper, workspace, timeout, protective-stop, emergency-stop, and manual-stop conditions. Recoverable task-level failures invoked the automatic recovery procedure.

Physical validation results. The selected checkpoint was evaluated on an NVIDIA GeForce RTX 5070 Ti in 75 physical trials, with 25 trials per task. Before each trial, the objects were reset around the nominal arrangement, with initial displacement kept within approximately 5 cm for the ring and memory-module scenes and approximately 3 cm for the socket scene. A trial was counted as successful when the complete task-specific terminal condition was achieved.

The memory-module task succeeded in all 25 trials, producing an observed success rate of 100%. The ring task succeeded in 21 of 25 trials, producing 84%. The plug-insertion task succeeded in 13 of 25 trials, producing 52%. Across all tasks, the system completed 59 of

75 trials successfully, giving an overall observed success rate of 78.7%. The overall value exceeded the 70% task-execution target, and the memory-module and ring tasks exceeded the target individually. However, the socket task did not meet the target, demonstrating that the aggregate result did not represent uniform performance across all three operations.

The independent specification-level tests produced planning success of 23/25 (92%), component detection of 24/25 (96%), failure detection of 23/25 (92%), and automatic recovery of 23/25 (92%). ES5 and ES6 used two separate groups of 25 experiments. All 59 completed tasks satisfied the ES4 positional tolerance. These results met the project-level ES1, ES3, ES4, ES5, and ES6 thresholds.

Failure analysis and discussion. The memory-module result indicates that the selected arm roles, camera observations, compliant grippers, demonstration data, and unified checkpoint worked reliably for the evaluated motherboard configuration.

Three of the four ring failures occurred before secure transport. In two trials, the right gripper approached away from the handle and missed the grasp; in one trial, the ring base obstructed the handle approach. The remaining failure occurred during placement over the can. The dominant limitation was therefore handle acquisition rather than the initial can repositioning or the overall bilateral sequence. Additional demonstrations around displaced handle poses, improved wrist-camera visibility, a more repeatable pre-grasp approach, or a revised finger profile could directly address this failure pattern.

The socket task exposed the most important remaining performance bottleneck. Two of its twelve failures occurred because the left gripper did not acquire or retain the plug. The other ten failures occurred after successful acquisition because the two pins were not aligned accurately enough with the two holes. Likely contributors include residual socket-box pose variation after pushing, plug-pose variation inside the compliant gripper, limited close-range visual information, and the interval over which ten predicted actions were executed before replanning.

Conclusions and recommendations. The project produced a functioning and traceable VLA-based proof-of-concept system for unified multi-task bimanual manipulation. Its principal contribution is the integration of bilateral teleoperation, packet-associated multi-view observations, reproducible dataset construction, joint multi-task $\pi_{0.5}$ training, a unified 16-dimensional action interface, robot-side safeguards, and real-robot validation. The same

checkpoint successfully executed all three fixed scene–instruction configurations. Because scene and instruction were not varied independently, the trials do not isolate the contribution of language or establish sensitivity to instruction variation.

Future development should first improve plug alignment and insertion through a more constrained fixture, better close-range visibility, and targeted demonstrations. The next system-level step is safe-space estimation from packet-associated multi-view observations, followed by broader object, scene, and instruction variation.