

Some Simple SPOOKY Data Analysis

Yujie Hu

January 31, 2018

Introduction

This files contains text mining analysis of the SPOOKY data. You should be able to put this file in the `doc` folder of your `Project 1` repository and it should just run (provided you have `multiplot.R` in the `libs` folder and `spooky.csv` in the `data` folder).

Content Table

Part 1 Data Preparation

- 1.Setup the Libraries
- 2.Read Data
- 3.Data Structure Overview
- 4.Data Cleaning

Part 2 Data Exploraion

- 1.Unigram
 - Word Frequency & Word Cloud
 - TF-IDF
- 2.Bigram
 - TF-IDF
 - First Two Words(Will be used for sentence generation)
- 3.Trigram
 - Without Stopwords
 - With Stopwords
- 4.Feature Engineering
 - Sentence Ingredients
 - Sentence Seasoning(Punctuations)
- 5.Sentence Generation

Part 3 Data Prediction

- 1.Logistics Regression
 - Multinomial Logistics Regression
 - Binary Logistics Regression
- 2.LDA Topic Modeling

Part 1 Data Preparation

1.Setup the Libraries

First we want to install and load libraries we need along the way. Note that the following code is completely reproducible – you don't need to add any code on your own to make it run.

```
packages.used <- c("ggplot2", "dplyr", "tibble", "tidyr", "stringr", "tidytext", "topicmodels", "wordcloud")

# check packages that need to be installed.
packages.needed <- setdiff(packages.used, intersect(installed.packages()[,1], packages.used))

# install additional packages
if(length(packages.needed) > 0) {
  install.packages(packages.needed, dependencies = TRUE, repos = 'http://cran.us.r-project.org')
}

library(ggplot2)
library(dplyr)
library(tibble)
library(tidyr)
library(stringr)
library(tidytext)
library(topicmodels)
library(wordcloud)
library(ggthemes)

source("../libs/multiplot.R")
```

2.Read Data

The following code assumes that the dataset `spooky.csv` lives in a `data` folder (and that we are inside a `docs` folder).

```
spooky <- read.csv('../data/spooky.csv', as.is = TRUE)
```

3.Data Structure Overview

Let's first remind ourselves of the structure of the data.

```
head(spooky)
```

```
##           id
## 1 id26305
## 2 id17569
## 3 id11008
## 4 id27763
## 5 id12958
## 6 id22965
##
## 1
## 2
## 3
```

```
## 4
## 5
## 6 A youth passed in solitude, my best years spent under your gentle and feminine fosterage, has so r
##   author
## 1    EAP
## 2    HPL
## 3    EAP
## 4    MWS
## 5    HPL
## 6    MWS
```

```
summary(spooky)
```

```
##           id           text           author
## Length:19579   Length:19579   Length:19579
## Class :character Class :character Class :character
## Mode  :character Mode  :character Mode  :character
```

```
fillColor = "#FFA07A"
fillColor2 = "#F1C40F"
```

We see from the above that each row of our data contains a unique ID, a single sentence text excerpt, and an abbreviated author name. HPL is Lovecraft, MWS is Shelly, and EAP is Poe. We finally note that there are no missing values, and we change author name to be a factor variable, which will help us later on.

```
sum(is.na(spooky))
```

```
## [1] 0
```

```
spooky$author <- as.factor(spooky$author)
```

4.Data Cleaning

We first use the `unnest_tokens()` function to drop all punctuation and transform all words into lower case. At least for now, the punctuation isn't really important to our analysis – we want to study the words. In addition, `tidytext` contains a dictionary of stop words, like “and” or “next”, that we will get rid of for our analysis, the idea being that the non-common words (... maybe the SPOOKY words) that the authors use will be more interesting. If this is new to you, here's a textbook that can help: *Text Mining with R; A Tidy Approach*. It teaches the basic handling of natural language data in R using tools from the “tidyverse”. The tidy text format is a table with one token per row, where a token is a word.

```
spooky_wrd <- unnest_tokens(spooky, word, text)
spooky_wrdnew <- anti_join(spooky_wrd, stop_words, by = "word")
```

Part 2 Data Exploration

1.Unigram

1.1 Word Frequency & Word Cloud

Now we study some of the most common words in the entire data set. With the Tutourial in class, we see that “time”, “life”, and “night” all appear frequently.

Then, I also plotted wordcloud for each author to compare their differences in word using.

```

#Wordcloud for each wuthor
#Function to generate dataset for each author
get_common_words_by_author <- function(x, author, remove.stopwords = FALSE){
  if(remove.stopwords){
    x <- x %>% dplyr::anti_join(stop_words)
  }

  x[x$author == author,] %>%
    dplyr::count(word, sort = TRUE)
}

words_EAP <- get_common_words_by_author(x = spooky_wrd,
                                         author = "EAP",
                                         remove.stopwords = TRUE)
words_HPL <- get_common_words_by_author(x = spooky_wrd,
                                         author = "HPL",
                                         remove.stopwords = TRUE)
words_MWS <- get_common_words_by_author(x = spooky_wrd,
                                         author = "MWS",
                                         remove.stopwords = TRUE)

pal <- brewer.pal(6,"Dark2")
layout(matrix(c(1,2,3),1,3,byrow = T))
par(mar = c(0,0,0,0))
#EAP
wordcloud(words_EAP$word,words_EAP$n,max.words = 50,colors =pal)
#HPL
wordcloud(words_HPL$word,words_HPL$n,max.words = 50,colors =pal)
#MWS
wordcloud(words_MWS$word,words_MWS$n,max.words = 50,colors =pal)

```



Compared to the overall word frequency,

- * **EAP** used words “length”, “head”, “left”, “matter” (EAP focused more on part of human? Has more word description about human’s organ? like “haed”, “eye”, “feet”, “body”, “hand”)
 - * **HPL** used words “house”, “heard”, “strange”, “street”, “told”, “door” (seems like HPL has more scenary description and created a background place for the horrible story)
 - * **MWS** used words “love”, “heart”, “raymond”, “death”, “father”, “mind” (MWS used more inner feeling and more abstract word like “spirit”, “hope”...)
- more often.

1.2 TF-IDF


TF stands for term frequency or how often a word appears in a text and it is what is studied above in the word cloud. IDF stands for inverse document frequency, and it is a way to pay more attention to words that are rare within the entire set of text data that is more sophisticated than simply removing stop words. Multiplying these two values together calculates a term's tf-idf, which is the frequency of a term adjusted for how rarely it is used. We'll use tf-idf as a heuristic index to indicate how frequently a certain author uses a word relative to the frequency that all the authors use the word. Therefore we will find words that are characteristic for a specific author, a good thing to have if we are interested in solving the author identification problem.

```
frequency <- count(spooky_wrdnew, author, word)
tf_idf <- bind_tf_idf(frequency, word, author, n)

tf_idf <- arrange(tf_idf, desc(tf_idf))
tf_idf <- mutate(tf_idf, word = factor(word, levels = rev(unique(word))))
tf_idf_30 <- top_n(tf_idf, 30, tf_idf)

ggplot(tf_idf_30) +
  geom_col(aes(word, tf_idf, fill = author)) +
  labs(x = NULL, y = "TF-IDF values") +
  theme(legend.position = "top", axis.text.x = element_text(angle=45, hjust=1, vjust=0.9))
```


author EAP HPL MWS



Note that in the above, many of the words recognized by their tf-idf scores are names. This makes sense – if we see text referencing Raymond, Idris, or Perdita, we know almost for sure that MWS is the author. But some non-names stand out. EAP often uses “monsieur” and “jupiter” while HPL uses the words “bearded” and “attic” more frequently than the others. We can also look at the most characteristic terms per author.

```
tf_idf <- ungroup(top_n(group_by(tf_idf, author), 20, tf_idf))
```

```
ggplot(tf_idf) +
  geom_col(aes(word, tf_idf, fill = author)) +
  labs(x = NULL, y = "tf-idf") +
  theme(legend.position = "none") +
  facet_wrap(~ author, ncol = 3, scales = "free") +
  coord_flip() +
  labs(y = "TF-IDF values")
```



Too many arcane words in this section.... I have a hard time searching their meanings, Still Couldn't Understand what they want to convey without context...

2. Bigrams

2.1 TF-IDF

Let's start with those bigrams. We can extract all of those pairs in a very similar way as the individual words using our magical *tidytext* scissors. Here are a few random examples that will change every time we run this part:

```
t2 <- spooky %>% select(author, text) %>% unnest_tokens(bigram, text, token = "ngrams", n = 2)
sample_n(t2, 5)
```

```
##      author    bigram
## 102044    EAP fell upon
```

```
## 477195    MWS    sobs do
## 328001    HPL said that
## 460831    MWS    by some
## 50660     EAP him might
```

In order to filter out the stop words we need to *separate* the bigrams first, and then later *unite* them back together after the filtering. *Separate/unite* are also the names of the corresponding *dplyr* functions:

```
bi_sep <- t2 %>%
  separate(bigram, c("word1", "word2"), sep = " ")

bi_filt <- bi_sep %>%
  filter(!word1 %in% stop_words$word) %>%
  filter(!word2 %in% stop_words$word)

# for later
bigram_counts <- bi_filt %>%
  count(word1, word2, sort = TRUE)

t2 <- bi_filt %>%
  unite(bigram, word1, word2, sep = " ")
```

Now we can extract the TF-IDF values.

```
t2_tf_idf <- t2 %>%
  count(author, bigram) %>%
  bind_tf_idf(bigram, author, n) %>%
  arrange(desc(tf_idf))
```

And then we plot the bigrams with the highest TF-IDF values per *author* and we see that ...

```
t2_tf_idf %>%
  arrange(desc(tf_idf)) %>%
  mutate(bigram = factor(bigram, levels = rev(unique(bigram)))) %>%
  group_by(author) %>%
  top_n(10, tf_idf) %>%
  ungroup() %>%
  ggplot(aes(bigram, tf_idf, fill = author)) +
  geom_col() +
  labs(x = NULL, y = "TF-IDF values") +
  theme(legend.position = "none") +
  facet_wrap(~ author, ncol = 3, scales = "free") +
  coord_flip()
```



Um... I have the indistinct feeling that both Poe and Lovecraft are laughing at us. If there is only one thing in the world that should make you feel uneasy, it's probably laughter from those two.

We also find:

- Besides cruel humour, for Poe it's all about "chess players" and "tea pots". We've also got a few more names and, apparently, a fair share of "Orang Utan" appearances.
- Lovecraft sets the scene with "ancient houses" and "shunned houses" during the "seventeenth century". Also he has a couple of characteristic character names.
- So has Mary Shelly, who seems to really like "Lord Raymond". Well, everybody loves Raymond, don't they? We also find a few turns of phrase that are typical for her, such as "fellow creatures", "hours passed", or "ill fated". *Let's hope that the latter is not an omen for our own expedition into the heart of the darkness ...*

2.2 First Two Words(Will be used for sentence generation)

Let's find how these authors start their sentence with. Does anyone of them have some special writing style to surprise you at the first sight?

I will use these first words to generate sentence for each author in the Part 2 (5). Hope It could seem like their own style and become another "spooky novel"

```
spooky$first_two<-word(spooky$text, 1,2, sep=" ")
spooky_first_two<-spooky%>%
  count(author,first_two)%>%
  arrange(desc(n,author))
```



```


spooky_first_two1 <- ungroup(top_n(group_by(spooky_first_two, author), 20, n))

p1<-spooky_first_two1 %>%
  ggplot(aes(reorder(first_two,n), n, fill = author), position = position_stack(reverse = TRUE)) +
  geom_col() +
  labs(x = NULL, y = "Number of Appearance") +
  theme(legend.position = "none",axis.text.x = element_text(angle=45, hjust=1, vjust=0.9))

p2<-spooky_first_two1 %>%
  ggplot(aes(reorder(first_two,n), n, fill = author), position = position_stack(reverse = TRUE)) +
  geom_col() +
  labs(x = NULL, y = "Number of Appearance") +
  theme(legend.position = "none")+
  facet_wrap(~ author, ncol = 3, scales = "free") +
  coord_flip()

layout <- matrix(c(1, 2), 2, 1, byrow = TRUE)
multiplot(p1, p2, layout = layout)

```



“It was” is the most popular way to start the sentence for all of these authors. Then come “In the”, “I was”, “I had”, “It is”, “He was”, “There was”. Seems like my writing style... Simple and nothing special. But when we have a closer look for each author, there comes difference!

- EAP and HPL have very similar Starting Words, EAP used more “In the” and “It is” than HPL. Sounds like EAP has more to explain in the sentence and stored lots of information.
- EAP seems like the most normal author when starting the sentence, EAP almost has no “own” starting words while HPL has a preference for “As the”, “It had”, “There were”, “Then he”, “The old”, “I did”

- MWS seems has her own style to start the sentence. MWS used a small percentage common words for starting. She showed a strong love to start with “I was”, “I shall”, “I had”, “We were”, “I cannot”, “But I”... She usually start with Personal Pronouns especially “I”. Maybe MWS make more efforts to make readers has similar feeling with her or help readers get addicted to her stories?

According to the frequency, I would select “It was” for EAP and HPL to generate “their” sentences. “I was” will be prepared for MWS

3. Trigrams

3.1 Without Stopwords

Three is a magical number. A terrible number. There were 3 witches to foretell Macbeth his blood-drenched destiny. The devil hound Cerberus has 3 heads. The number of the beast is 3 times the number 3+3. All these warning signs try to reach our conscience as we prepare to repeat the same analysis we had done for bigrams on their cousins thrice removed: trigrams.

Blind for knowledge, yielding to the call of power just like the sorcerer’s apprentice, we continue our study. We crave to know more. A little spark of reason and self-preservation is trying to make itself heard against the raging thirst in our brains, but it burns ever weaker as the candle, is it still a candle?, shines brighter and brighter.

Extracting trigrams follows the same procedure as for bigrams. Again we filter out stop words and include a few random examples:

```
t3 <- spooky %>% select(author, text) %>% unnest_tokens(trigram, text, token = "ngrams", n = 3)

tri_sep <- t3 %>%
  separate(trigram, c("word1", "word2", "word3"), sep = " ")

tri_filt <- tri_sep %>%
  filter(!word1 %in% stop_words$word) %>%
  filter(!word2 %in% stop_words$word) %>%
  filter(!word3 %in% stop_words$word)

# for later
trigram_counts <- tri_filt %>%
  count(word1, word2, word3, sort = TRUE)

t3 <- tri_filt %>%
  unite(trigram, word1, word2, word3, sep = " ")

sample_n(t3, 5)

##      author      trigram
## 6201    HPL    powerful acetylene lamp
## 8499    HPL      glaring red eyes
## 5872    HPL impressions abruptly vanished
## 3838    EAP      gum elastic bag
## 11345   MWS    taking london conquering
```

And here is the corresponding TF-IDF plot for the most characteristic terms:


```
t3_tf_idf <- t3 %>%
  count(author, trigram) %>%
  bind_tf_idf(trigram, author, n) %>%
```

```

arrange(desc(tf_idf))

t3_tf_idf %>%
  arrange(desc(tf_idf)) %>%
  mutate(trigram = factor(trigram, levels = rev(unique(trigram)))) %>%
  group_by(author) %>%
  top_n(5, tf_idf) %>%
  ungroup() %>%
  ggplot(aes(trigram, tf_idf, fill = author)) +
  geom_col() +
  labs(x = NULL, y = "TF-IDF values") +
  theme(legend.position = "none") +
  facet_wrap(~ author, ncol = 3, scales = "free") +
  coord_flip()

```



We find:

- More scary laughter and characteristic names from Poe and Lovecraft. Feel free to admit that you also read “Eric Moreland Clapton” at first glance in HPL’s list. I like the imagery of a “horned waning moon”.
- Curiously, Mary Shelley does not seem to have particularly typical phrases she repeats more often than others. The ones she does use suggest a penchant for body language, especially the eyes.
- Most importantly, though, we find out that Raymond was from Galifrey. That might explain why he’s so popular and why he manages to exert such a strong influence on Shelley’s writing.

3.2 With Stopwords

This time let's put stopwords into consideration and see whether it could add more interests in their expression.

```
trigram_counts2 <- tri_sep %>%
  count(word1, word2, word3, sort = TRUE)

t31 <- tri_sep %>%
  unite(trigram, word1, word2, word3, sep = " ")

t3_tf_idf1 <- t31 %>%
  count(author, trigram) %>%
  bind_tf_idf(trigram, author, n) %>%
  arrange(desc(tf_idf))

t3_tf_idf1 %>%
  arrange(desc(tf_idf)) %>%
  mutate(trigram = factor(trigram, levels = rev(unique(trigram)))) %>%
  group_by(author) %>%
  top_n(5, tf_idf) %>%
  ungroup() %>%
  ggplot(aes(trigram, tf_idf, fill = author)) +
  geom_col() +
  labs(x = NULL, y = "TF-IDF values") +
  theme(legend.position = "none") +
  facet_wrap(~ author, ncol = 3, scales = "free") +
  coord_flip() +
  scale_fill_brewer(palette = 'Accent')
```



We find:

- EAP and HPL are still similar in their writing style. Their trigrams are almost all conjunctions which don't have much information
- EAP used "three or four" frequently, Checking back to the original sentences, what follows the quantitative amount is usually time("weeks", "hours", "days"...). Seems like EAP tends to describe things vaguely and create some unclear concepts for reader to guess?
- HPL are fond of house! Could he afford his own house back to his time? The high house price made him scary??
- MWS gives more information on this part. My father?? My fellow creatures?? I entreat you?? She really loves using person prons in the sentence. Her trigram doesn't seem could be compiled to a spooky novel... It made me feel warm...

4.Feature Engineering

We'll do some simple numerical summaries of the data to provide some nice visualizations. Here we add some Features to the **spooky** datasets. The features are

- Number of commas, semicolons, colons, questions
- Number of blanks, others
- Number of words beginning with Capitals, words with Capitals
- Number of words, stopwords, negation words
- Sentence length(characters); Word length(characters)

We may find some traces how these author *cooking* their horrible books!

Some these features have been borrowed from Kagglar *jayjay* 's kernel found here. Great work jayjay!

```
createFE = function(ds)
{
  ds = ds %>%
  mutate(Ncommas = str_count(ds$text, ",")) %>%
  mutate(Nsemicolumns = str_count(ds$text, ";")) %>%
  mutate(Ncolons = str_count(ds$text, ":")) %>%
  mutate(Nblank = str_count(ds$text, " ")) %>%
  mutate(Nother = str_count(ds$text, "[\\\\.\\.\\.]")) %>%
  mutate(Ncapitalfirst = str_count(ds$text, "[A-Z][a-z]")) %>%
  mutate(Ncapital = str_count(ds$text, "[A-Z]")) %>%
  mutate(Nquestion = str_count(ds$text, "\\?"))

  return(ds)
}
spooky_feature = createFE(spooky)
```


4.1 Sentence Ingredients

Here comes their “Sentence Ingredients”! This part tell us How Much Special Ingredients they Add in Their Stories.

First is the number of Capital they used

```
spooky_feature %>%
  group_by(author) %>%
  summarise(SumCapital = sum(Ncapital, na.rm = TRUE)) %>%
  ungroup() %>%
  mutate(author = reorder(author, SumCapital)) %>%


  ggplot(aes(x = author, y = SumCapital)) +
  geom_bar(stat='identity', colour="white", fill = fillColor) +
  geom_text(aes(x = author, y = 1, label = paste0("(", SumCapital, ")", sep="")),
            hjust=0, vjust=.5, size = 4, colour = 'black',
            fontface = 'bold') +
  labs(x = 'author',
       y = 'Capital Letters',
       title = 'Total Number of Capital Letters') +
  coord_flip() +
  theme_bw()
```



- Seems like EAP used more Capital Letters, But there are also more sentence included in the dataset written by EAP. (EAP, HPL, MWS : 7900, 5635, 6044) After Calculating the Capital Letters Per Sentence, HPL won! EAP and MWS have an average of 2.2 per sentence while HPL has 2.4.

Next comes the number of words in a sentence.

```
spooky_feature$Nwords <- sapply(gregexpr("\\W+", spooky_feature$text), length) + 1
ggplot(spooky_feature) +
  geom_boxplot(aes(x=author, y=Nwords, fill=author))
```




- HPL has a relatively long sentence than others while MWS occasionally write some extremely long sentence.
- HPL is very stable and have a steady performance when add words into his stories while MWS seems very flexible and sometimes may has A Burst of Inspiration??

Then comes number of stopwords in a sentence

```
nostopword<-as.data.frame(table(spooky_wrdnew$id))
names(nostopword)<-c("id","num_of_nostop_wrd")
spooky_feature<-merge(spooky_feature,nostopword,by="id",all=T)
spooky_feature$num_of_nostop_wrd[is.na(spooky_feature$num_of_nostop_wrd)]<-0
spooky_feature$Nstop<-spooky_feature$Nwords - spooky_feature$num_of_nostop_wrd

ggplot(spooky_feature) +
  geom_density_ridges(aes(Nstop, author, fill = author)) +
  scale_x_log10() +
  theme(legend.position = "none") +
  labs(x = "Number of StopWords")
```

- MWS used less stopwords than other two, which could also be found from her trigram.

At last, it is the number of negation words in a sentence

Negation Words:

Different from negative words in sentiment analysis, including:

Negative words: no, not, none, no one, nobody, nothing, neither, nowhere, never

Negative Adverbs: hardly, scarcely, barely


Negative verbs: doesn't, isn't, wasn't, shouldn't, wouldn't, couldn't, won't, can't, don't

Others: little, few, nor, neither... nor, without, unless, but for, but that, in the absence of, regardless of, instead of, exclusive of, short of, rather than, anything but, any more than, would no more... than

I didn't find an existing word list for this... So I just generated some by myself. Correct me if I am wrong.

```
negation<-c("no","not","none","nobody","nothing","neither","nowhere","never","hardly","scarcely","barely")
spooky_wrd$negation <- spooky_wrd$word %in% negation
negationwrld<-as.data.frame(table(spooky_wrd$id[spooky_wrd$negation==T] ))
names(negationwrld)<-c("id","num_of_negation_wrd")
spooky_feature<-merge(spooky_feature,negationwrld,by="id",all=T)
spooky_feature$num_of_negation_wrd[is.na(spooky_feature$num_of_negation_wrd)]<-0

ggplot(spooky_feature) +
  geom_boxplot(aes(x=author, y=num_of_negation_wrd,fill=author))
```



- They almost have the same performance and only EAP may use a little more negation words.

Overall, we could find HPL has a very good writing habit, moderate length, moderate Words, Good example for us. He may never added too much butter to his bread...

4.2 Sentence Seasoning(Punctuations)

After checking their ingredients, what did they put for the “Flavour”?

The bar plot shows the authors with the Total Number of Commas,SemiColons,Colons,Questions used by them.

Still, be careful because EAP appeared more often than others.

```
p1<-spooky_feature %>%
  group_by(author) %>%
  summarise(SumCommas = sum(Ncommas,na.rm = TRUE)) %>%
  ungroup() %>%
  mutate(author = reorder(author,SumCommas)) %>%

ggplot(aes(x = author,y = SumCommas)) +
  geom_bar(stat='identity',colour="white", fill = fillColor2) +
  geom_text(aes(x = author, y = 1, label = paste0("(",SumCommas,")",sep="")),
            hjust=0, vjust=.5, size = 4, colour = 'black',
            fontface = 'bold') +
  labs(x = 'author',
       y = 'Commas',
       title = 'Total Number of Commas') +
```

```

coord_flip() +
theme_bw()

p2<-spooky_feature %>%
group_by(author) %>%
summarise(SumSemiColons = sum(Nsemicolumns,na.rm = TRUE)) %>%
ungroup() %>%
mutate(author = reorder(author,SumSemiColons)) %>%

ggplot(aes(x = author,y = SumSemiColons)) +
geom_bar(stat='identity',colour="white", fill = fillColor) +
geom_text(aes(x = author, y = 1, label = paste0("(",SumSemiColons,")",sep="")),
          hjust=0, vjust=.5, size = 4, colour = 'black',
          fontface = 'bold') +
labs(x = 'author',
     y = 'SemiColons',
     title = 'Total Number of SemiColons') +
coord_flip() +
theme_bw()

p3<-spooky_feature %>%
group_by(author) %>%
summarise(SumColons = sum(Ncolons,na.rm = TRUE)) %>%
ungroup() %>%
mutate(author = reorder(author,SumColons)) %>%


ggplot(aes(x = author,y = SumColons)) +
geom_bar(stat='identity',colour="white", fill = fillColor2) +
geom_text(aes(x = author, y = 1, label = paste0("(",SumColons,")",sep="")),
          hjust=0, vjust=.5, size = 4, colour = 'black',
          fontface = 'bold') +
labs(x = 'author',
     y = 'Colons',
     title = 'Total Number of Colons') +
coord_flip() +
theme_bw()

p4<-spooky_feature %>%
group_by(author) %>%
summarise(SumQuestions = sum(Nquestion,na.rm = TRUE)) %>%
ungroup() %>%
mutate(author = reorder(author,SumQuestions)) %>%

ggplot(aes(x = author,y = SumQuestions)) +
geom_bar(stat='identity',colour="white", fill = fillColor) +
geom_text(aes(x = author, y = 1, label = paste0("(",SumQuestions,")",sep="")),
          hjust=0, vjust=.5, size = 4, colour = 'black',
          fontface = 'bold') +
labs(x = 'author',
     y = 'Questions',
     title = 'Total Number of Questions') +
coord_flip() +
theme_bw()

```

```
layout <- matrix(c(1, 2, 3, 4), 2, 2, byrow = TRUE)
multiplot(p1, p2, p3, p4, layout = layout)
```



- HPL cherishes his Commas, Colons and Questions and only used little seasoning...
- MWS is almost wasting Semicolons and Colons compared to others...

5.Sentence Generation

```
##trigram of authors
trigrams_EAP <- spooky %>%
  filter(author == "EAP") %>%
  unnest_tokens(trigram, text, token = "ngrams", to_lower = TRUE, n = 3) %>%
  separate(trigram, c("word1", "word2", "word3"), sep = " ") %>%
  count(word1, word2, word3, sort = TRUE)
trigrams_HPL <- spooky %>%
  filter(author == "HPL") %>%
  unnest_tokens(trigram, text, token = "ngrams", to_lower = TRUE, n = 3) %>%
  separate(trigram, c("word1", "word2", "word3"), sep = " ") %>%
  count(word1, word2, word3, sort = TRUE)
trigrams_MWS <- spooky %>%
  filter(author == "MWS") %>%
  unnest_tokens(trigram, text, token = "ngrams", to_lower = TRUE, n = 3) %>%
  separate(trigram, c("word1", "word2", "word3"), sep = " ") %>%
  count(word1, word2, word3, sort = TRUE)
```

```

##may be a grap here about

##sentence generator
return_third_word <- function( woord1, woord2,authordata){
  woord <- authordata %>%
    filter(~word1 == woord1, ~word2 == woord2) %>%
    sample_n(1, weight = n) %>%
    .[["word3"]]
  if(length(woord) == 0){
    bleh <- filter_(authordata, ~word1 == woord2) %>%
      sample_n(1, weight = n)
    warning("no word found, adding ", bleh, "to", woord1 , woord2)
    woord <- bleh
  }
  woord
}

generate_sentence <- function(word1, word2,authordata, sentencelength =5, debug =FALSE){
  #input validation
  if(sentencelength <3)stop("I need more to work with")
  sentencelength <- sentencelength -2
  # starting
  sentence <- c(word1, word2)
  woord1 <- word1
  woord2 <- word2
  for(i in seq_len(sentencelength)){
    if(debug == TRUE)print(i)
    word <- return_third_word( woord1, woord2, authordata )
    sentence <- c(sentence, word)
    woord1 <- woord2
    woord2 <- word
  }
  output <-paste(sentence, collapse = " ")
  output
}

#generate_sentence("the", "man",trigrams_EAP, 15)
#generate_sentence("the", "man",trigrams_HPL, 15)
#generate_sentence("the", "man",trigrams_MWS, 15)

## find the first two world used most frequently by author.
## compile their psycho profile starting with their sanguan life world man value

```

Part 3 Data Prediction

1.Logistics Regression

1.1 Multinomial Logistics Regression...

I tried to use “Ncommas”, “Nsemicolumns”, “Ncolons”, “Ncapital”, “Nquestion”, “Nwords”, “num_of_negation_wrd”, “sen_length” to predict the author... but stuck in this part... I listed some material I used for the code but I still didn’t understand the principle of Multinomial Logistics Regression enough...

Please Correct me

How to: Multinomial regression models in R

R examples

How to: Multinomial regression models in R

First I added sentence length(characters) and word length(characters) to dataset.


```
spooky$sen_length <- str_length(spooky$text)
spooky_wrdnew$word_length <- str_length(spooky_wrdnew$word)
```

Used correlation plots to delete variables.

You may need to download the package **corrplot** to run the code.


```
spooky_feature$sen_length<-spooky$sen_length
regressiondata<-spooky_feature[,c(-1,-2,-4,-8,-9,-10,-14)]
#install.packages("corrplot")
library(corrplot)

## corrplot 0.84 loaded
m<-cor(regressiondata[,2:10])
corrplot(m, type = "upper", order = "hclust", tl.col = "black", tl.srt = 45,method = "number")
```



I found number of words has a high correlation with number of stopwords,so I deleted the number of stop words from the variables. Correlation again.

```
regressiondata<-regressiondata[,-8]
m1<-cor(regressiondata[,2:9])
corrplot.mixed(m1, lower.col = "black", number.cex = .7)
```



Separate dataset into train and test.

```
set.seed(4243)
sample<-sample.int(n=nrow(regressiondata),size=floor(0.75*nrow(regressiondata)),replace=F)
train<-regressiondata[sample, ]
test<-regressiondata[-sample, ]
```

Here comes my nightmare...

You may need to download the package *nnet* to run the code.

```
library(nnet)
mult<-multinom(author~.,data=train)
```

```
## # weights: 30 (18 variable)
## initial value 16132.022847
## iter 10 value 15332.423553
## iter 20 value 15015.983491
## final value 14950.268598
## converged
```

```
summary(mult)
```

```
## Call:
## multinom(formula = author ~ ., data = train)
##
## Coefficients:
## (Intercept) Ncommas Nsemicolumns Ncolons Ncapital Nquestion
## HPL -0.8207949 -0.4862400 -0.06941065 -1.310410 0.04778457 -0.6865236
## MWS -0.3103486 -0.1403601 0.89018293 0.823182 -0.03857027 0.1706454
## Nwords num_of_negation_wrd sen_length
```

```
## HPL 0.048469110          -0.1007914 1.950072e-04
## MWS 0.007439843          -0.2169053 8.165399e-05
##
## Std. Errors:
##      (Intercept)      Ncommas Nsemicolumns      Ncolons      Ncapital      Nquestion
## HPL 0.05385794 0.01707620 0.05119468 0.1948332 0.01115532 0.10309479
## MWS 0.05190771 0.01445629 0.04381850 0.1132898 0.01206451 0.07436598
##      Nwords num_of_negation_wrd      sen_length
## HPL 0.002117827          0.03255599 0.0002083105
## MWS 0.002087648          0.03229003 0.0002033088
##
## Residual Deviance: 29900.54
## AIC: 29936.54
```

Used stepwise to get a better model.

```
stepmult<-step(mult,trace=0)
```

```
## trying - Ncommas
## trying - Nsemicolumns
## trying - Ncolons
## trying - Ncapital
## trying - Nquestion
## trying - Nwords
## trying - num_of_negation_wrd
## trying - sen_length
## # weights: 27 (16 variable)
## initial value 16132.022847
## iter 10 value 15275.822528
## iter 20 value 14950.860610
## final value 14950.705466
## converged
## trying - Ncommas
## trying - Nsemicolumns
## trying - Ncolons
## trying - Ncapital
## trying - Nquestion
## trying - Nwords
## trying - num_of_negation_wrd
```

```
summary(stepmult)
```

```
## Call:
## multinom(formula = author ~ Ncommas + Nsemicolumns + Ncolons +
##      Ncapital + Nquestion + Nwords + num_of_negation_wrd, data = train)
##
## Coefficients:
##      (Intercept)      Ncommas Nsemicolumns      Ncolons      Ncapital      Nquestion
## HPL -0.7921388 -0.4861095 -0.06888915 -1.311544 0.04790534 -0.6851465
## MWS -0.2983307 -0.1403305 0.89031166 0.822829 -0.03851129 0.1709427
##      Nwords num_of_negation_wrd
## HPL 0.048465823          -0.1015623
## MWS 0.007437416          -0.2171735
##
## Std. Errors:
##      (Intercept)      Ncommas Nsemicolumns      Ncolons      Ncapital      Nquestion
```



```
## HPL 0.04424272 0.01707352 0.05118760 0.1948402 0.01115685 0.10306357
## MWS 0.04243888 0.01445593 0.04381364 0.1132716 0.01206482 0.07435822
##      Nwords num_of_negation_wrd
## HPL 0.002117582 0.03254416
## MWS 0.002087562 0.03228028
##
## Residual Deviance: 29901.41
## AIC: 29933.41
```

Predict the result of test set

```
# put into test dataset
result<-predict(stepmult,test)
head(result)
```

```
## [1] EAP MWS EAP HPL EAP MWS
## Levels: EAP HPL MWS
```

```
resultprob<-predict(stepmult,test,"probs")
head(resultprob)
```

```
##      EAP      HPL      MWS
## 3 0.4025806 0.3410807 0.2563388
## 5 0.2681899 0.2706456 0.4611645
## 6 0.4635858 0.2419635 0.2944507
## 8 0.1960105 0.5187672 0.2852223
## 9 0.3853511 0.3273241 0.2873248
## 20 0.2662128 0.2817404 0.4520467
```

Show the final comparison of predicted & true author

```
# prediction for test
n<-table(test$author,result)
n
```

```
##      result
##      EAP  HPL  MWS
## EAP 1449  278  212
## HPL  767  482  183
## MWS  854  224  446
```

```
Percentage<-c(n[,1]/sum(n[,1]),n[,2]/sum(n[,2]),n[,3]/sum(n[,3]))
Category<-levels(test$author)
rbind(Category,Percentage)
```

```
##      [,1]      [,2]      [,3]
## Category "EAP"      "HPL"      "MWS"
## Percentage "0.747292418772563" "0.33659217877095" "0.292650918635171"
```

```
accuracy<-sum(diag(n))/nrow(test)
accuracy
```

```
## [1] 0.4855975
```

- seems like EAP has a better predict rate? But the table of result showed that it is because almost 80% of predicted author are EAP. HPL is hard to detect??
- overall accuracy rate 44.6%. Not better than guess...
- tried Binary Logistics regression next part.

1.2 Binary Logistics Regression

Logistic regression could be used on our data to make binary choices like is it MSW or not. While it seems like one should be able to use three logistic regression models (MSW or not, EAP or not, HPL or not) to classify the text, it won't necessarily be the case that the results of the three models agree.

I will show one example (EAP or Not) here and give the result of other two.

Prepare the dataset

```
EAPorNot<-regressiondata
EAPorNot$author<-as.character(EAPorNot$author)
EAPorNot$author[which(EAPorNot$author!="EAP")]<-"Others"
EAPorNot$author<-as.factor(EAPorNot$author)

set.seed(4243)
sample1<-sample.int(n=nrow(EAPorNot),size=floor(0.75*nrow(EAPorNot)),replace=F)
train1<-EAPorNot[sample1, ]
test1<-EAPorNot[-sample1, ]
```

Conduct regression

```
glm<-glm(author ~.,family="binomial",data=train1)
summary(glm)

##
## Call:
## glm(formula = author ~ ., family = "binomial", data = train1)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -3.7154  -1.2463   0.7887   1.0193   2.2923
##
## Coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    0.1340426  0.0440862   3.040  0.00236 **
## Ncommas        -0.2923348  0.0126411 -23.126 < 2e-16 ***
## Nsemicolumns    0.5101122  0.0394025  12.946 < 2e-16 ***
## Ncolons          0.2064721  0.1089542   1.895  0.05809 .
## Ncapital         0.0066564  0.0095035   0.700  0.48366
## Nquestion       -0.1364122  0.0686392  -1.987  0.04688 *
## Nwords           0.0270190  0.0017473  15.463 < 2e-16 ***
## num_of_negation_wrd -0.1614936  0.0269465  -5.993 2.06e-09 ***
## sen_length       0.0001296  0.0001734   0.747  0.45489
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
##      Null deviance: 19834  on 14683  degrees of freedom
## Residual deviance: 18906  on 14675  degrees of freedom
## AIC: 18924
##
## Number of Fisher Scoring iterations: 4

#stepwise
stepglm<-step(glm,direction = "both",trace=0)
```

```
summary(stepglm)
```

```
##
## Call:
## glm(formula = author ~ Ncommas + Nsemicolumns + Ncolons + Nquestion +
##      Nwords + num_of_negation_wrd, family = "binomial", data = train1)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -3.7336  -1.2482   0.7886   1.0185   2.3045
##
## Coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    0.158930   0.035011   4.539 5.64e-06 ***
## Ncommas        -0.291922   0.012631 -23.112 < 2e-16 ***
## Nsemicolumns    0.509494   0.039370  12.941 < 2e-16 ***
## Ncolons         0.213036   0.108510   1.963  0.0496 *
## Nquestion      -0.131956   0.068416  -1.929  0.0538 .
## Nwords         0.027318   0.001696  16.107 < 2e-16 ***
## num_of_negation_wrd -0.161581  0.026932  -6.000 1.98e-09 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
##      Null deviance: 19834  on 14683  degrees of freedom
## Residual deviance: 18907  on 14677  degrees of freedom
## AIC: 18921
##
## Number of Fisher Scoring iterations: 4
```

```
#deleted number of capital words and sentence length
```

Predict results

```
real <- test1$author
predict. <- predict.glm(stepglm,type='response',newdata=test1)
#Return 1 when the possibility > mean predicted value
summary(predict.)
```

```
##      Min.  1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.002249 0.532458 0.593824 0.596185 0.663149 1.000000
```

```
predict =ifelse(predict.>mean(predict.),1,0)
##accuracy
res <- data.frame(real,predict)
eap<-table(real,predict =ifelse(predict>mean(predict.),'EAP','Others'))
eap
```

```
##      predict
## real      EAP Others
##  EAP      702  1237
##  Others 1686  1270
```

```
accuracy = sum(diag(eap))/nrow(test)
accuracy
```

[1] 0.4028601

- 40.29% accuracy for EPA. Seems inaccoring with the Multinomial Regression... Do they have relationship???
- I also conducted Binary for HPL and MWS, their predicted accuracy results is about 57.18% and 53.75% almost guessing...

2.LDA Topic Modeling