

Initialize git repository, stage all files and create empty .gitignore

Author: Marcos de Carvalho

Date: 2026-04-25

Initializes a new git repository in current directory, stages all existing files, and creates an empty .gitignore file.

Language

git

Category

version-control

Command

```
git init && git add . && touch .gitignore
```

Explanation

This command sequence creates a new git repository (git init), adds all files in the current directory to the staging area (git add .), and creates an empty .gitignore file (touch .gitignore) for future ignore patterns.

Tags

git, version-control, repository, init, gitignore

Dependencies

git

Arguments

1. **DIRECTORY** (Optional): Directory where to initialize repository
Default: .

Examples

1. `git init && git add . && touch .gitignore` - Initialize repository in current directory
2. `cd /path/to/project && git init && git add . && touch .gitignore` - Initialize repository in specific directory

Output

```
Initialized empty Git repository in /home/user/project/.git/
```

Notes

- The `.gitignore` file is empty after creation; you should add patterns to ignore unnecessary files
- If `.gitignore` already exists, `touch` command updates its timestamp
- Use `git status` to verify files are staged

Warnings

- `git add .` stages all files including potentially sensitive data
- Review staged files before committing

See Also

- `git-commit-initial`
- `git-ignore-patterns`

Status

reviewed

Safety

safe

Shell

posix

Platforms

linux, gnu-linux, freebsd, openbsd, netbsd

Created At

2026-04-25

Updated At

2026-04-25