

```
nerName "contosobackups" -TargetBlobName "conto
backup-AzApiManagement -ResourceGroupName "Cont
osoGroup02" -Name "ContosoApi" -StorageContext
$StorageContext -TargetContainerName "contosoba
ckups" -TargetBlobName "contobas

bash
gustavo [ ~ ]$ MYSQL_HOST=t9-2022630278-bd.mysql
l.database.azure.com
gustavo [ ~ ]$ MYSQL_USER=x
gustavo [ ~ ]$ MYSQL_PASS=Aaaaaaaaaaaa0
gustavo [ ~ ]$ |
```

Figura 10.6 Creación de variables de entorno para ingresar a MySQL

Para GU:

```
gustavo [ ~ ]$ MYSQL_PASS=Aaaaaaaaaaaa0
gustavo [ ~ ]$ az aks get-credentials -n t9-2022630278-aks -g t9-2022
630278-rg
az aks get-credentials -n t9-2022630278-aks -g t9-2022
630278-rg
A different object named t9-2022630278-aks already exists in your kub
econfig file.
Overwrite? (y/n): n
A different object named t9-2022630278-aks already exists in contexts
in your kubeconfig file.
gustavo [ ~ ]$ kubectl create secret generic mysql-credentials-gu \
--from-literal=Server="$MYSQL_HOST" \
--from-literal=UserID="$MYSQL_USER" \
--from-literal=Password="$MYSQL_PASS" \
--from-literal=Database="t9_2022630278_bdgu" \
-n t9-2022630278
secret/mysql-credentials-gu created
gustavo [ ~ ]$ |
```

```
Command Prompt x Azure Cloud Shell x + v
A different object named t9-2022630278-aks already exists in contexts
in your kubeconfig file.
gustavo [ ~ ]$ kubectl create secret generic mysql-credentials-gu \
--from-literal=Server="$MYSQL_HOST" \
--from-literal=UserID="$MYSQL_USER" \
--from-literal=Password="$MYSQL_PASS" \
--from-literal=Database="t9_2022630278_bdgu" \
-n t9-2022630278
secret/mysql-credentials-gu created
gustavo [ ~ ]$ kubectl create secret generic mysql-credentials-ga \
--from-literal=Server="$MYSQL_HOST" \
--from-literal=UserID="$MYSQL_USER" \
--from-literal=Password="$MYSQL_PASS" \
--from-literal=Database="t9_2022630278_bdga" \
-n t9-2022630278
secret/mysql-credentials-ga created
gustavo [ ~ ]$ |
```

Figura 10.8 Creación de secretos para gu

Para GC:

```
Command Prompt x Azure Cloud Shell x + v
-n t9-2022630278
secret/mysql-credentials-gu created
gustavo [ ~ ]$ kubectl create secret generic mysql-credentials-ga \
--from-literal=Server="$MYSQL_HOST" \
--from-literal=UserID="$MYSQL_USER" \
--from-literal=Password="$MYSQL_PASS" \
--from-literal=Database="t9_2022630278_bdga" \
-n t9-2022630278
secret/mysql-credentials-ga created
gustavo [ ~ ]$ kubectl create secret generic mysql-credentials-gc \
--from-literal=Server="$MYSQL_HOST" \
--from-literal=UserID="$MYSQL_USER" \
--from-literal=Password="$MYSQL_PASS" \
--from-literal=Database="t9_2022630278_bdgc" \
-n t9-2022630278
secret/mysql-credentials-gc created
gustavo [ ~ ]$ |
```

Figura 10.9 Creación de secretos para gc

Verifica que existen:

- `kubectl get secrets`
- `kubectl describe secret mysql-credentials-gu`
- `kubectl describe secret mysql-credentials-ga`
- `kubectl describe secret mysql-credentials-gc`

```
secret/mysql-credentials-gc created
gustavo [ ~ ]$ kubectl get secrets
NAME                                TYPE      DATA      AGE
mysql-credentials-ga                Opaque    4           77s
mysql-credentials-gc                Opaque    4           52s
mysql-credentials-gu                Opaque    4          2m54s
gustavo [ ~ ]$ kubectl describe secret mysql-credentials-gu
Name:                                mysql-credentials-gu
Namespace:                          t9-2022630278
Labels:                              <none>
Annotations:                         <none>


Type:  Opaque

Data
====
Database:  18 bytes
```

```
mysql-credentials-gc                Opaque    4           52s
mysql-credentials-gu                Opaque    4          2m54s
gustavo [ ~ ]$ kubectl describe secret mysql-credentials-gu
Name:                                mysql-credentials-gu
Namespace:                          t9-2022630278
Labels:                              <none>
Annotations:                         <none>

Type:  Opaque

Data
====
Database:  18 bytes
Password:  12 bytes
Server:    41 bytes
UserID:    1 bytes
gustavo [ ~ ]$ |
```



```
Server: 41 bytes
UserID: 1 bytes
gustavo [ ~ ]$ kubectl describe secret mysql-credentials-ga
Name: mysql-credentials-ga
Namespace: t9-2022630278
Labels: <none>
Annotations: <none>

Type: Opaque

Data
====
Database: 18 bytes
Password: 12 bytes
Server: 41 bytes
UserID: 1 bytes
gustavo [ ~ ]$ |

Server: 41 bytes
UserID: 1 bytes
gustavo [ ~ ]$ kubectl describe secret mysql-credentials-gc
Name: mysql-credentials-gc
Namespace: t9-2022630278
Labels: <none>
Annotations: <none>

Type: Opaque

Data
====
Database: 18 bytes
Password: 12 bytes
Server: 41 bytes
UserID: 1 bytes
gustavo [ ~ ]$ |
```

Figura 10.9 Verificar secretos

- Se instaló el ConfigMap ms-config con USERS_URL, COMPRAS_URL y ROOT.

```
Command Prompt x Azure Cloud Shell x + v
Type: Opaque

Data
====
Database: 18 bytes
Password: 12 bytes
Server: 41 bytes
UserID: 1 bytes
gustavo [ ~ ]$ kubectl create configmap ms-config \
  --from-literal=USERS_URL="http://t9-2022630278-gu-svc.t9-2022630278
  .svc.cluster.local" \
  --from-literal=COMPRAS_URL="http://t9-2022630278-gc-svc.t9-20226302
  78.svc.cluster.local" \
  --from-literal=ROOT="/mnt/webfiles" \
  -n t9-2022630278
configmap/ms-config created
gustavo [ ~ ]$ |
```

Figura 10.10 Creación de secretos para urls

- Se accedió a la sección de configuración de cada Deployment para validar envFrom y env apuntando a Secrets y ConfigMaps.


```
Command Prompt x Azure Cloud Shell x + v
gustavo [ ~ ]$ kubectl get secrets -n t9-2022630278
NAME                                TYPE      DATA      AGE
mysql-credentials-ga               Opaque    4           4m51s
mysql-credentials-gc               Opaque    4           4m26s
mysql-credentials-gu               Opaque    4           6m28s
gustavo [ ~ ]$ kubectl describe secret mysql-credentials-gu -n t9-2022630278
kubectl describe secret mysql-credentials-gu -n t9-2022630278
Name:                               mysql-credentials-gu
Namespace:                          t9-2022630278
Labels:                              <none>
Annotations:                         <none>

Type: Opaque


Data
====
Database: 18 bytes
Password: 12 bytes
Server: 41 bytes
UserID: 1 bytes

Command Prompt x Azure Cloud Shell x + v
Data
====
Database: 18 bytes
Password: 12 bytes
Server: 41 bytes
UserID: 1 bytes
gustavo [ ~ ]$ kubectl get configmap ms-config -n t9-2022630278 -o yaml
apiVersion: v1
data:
  COMPRAS_URL: http://t9-2022630278-gc-svc.t9-2022630278.svc.cluster.local
  ROOT: /mnt/webfiles
  USERS_URL: http://t9-2022630278-gu-svc.t9-2022630278.svc.cluster.local
kind: ConfigMap
metadata:
  creationTimestamp: "2025-12-22T18:22:40Z"
  name: ms-config
  namespace: t9-2022630278
  resourceVersion: "297341"
  uid: a3499418-796e-4836-8c7a-1572ab7a20e2
gustavo [ ~ ]$ |
```

Figura 10.10 ConfigMaps y Secrets del namespace del proyecto con variables de entorno aplicadas

8.1 Crear PV y PVC para Azure Files (front-end)

- Se realizaron los Portal > Storage account > t92022630278sa > Access keys > copia la key1
- Cloud Shell:
 - `kubectl create secret generic azure-file-secret -n t9-2022630278 --from-literal=azurestorageaccountname=t92022630278sa --from-literal=azurestorageaccountkey=<KEY1>`



```
gustavo [ ~ ]$ kubectl get configmap ms-config -n t9-2022630278 -o yaml
apiVersion: v1
data:
  COMPRAS_URL: http://t9-2022630278-gc-svc.t9-2022630278.svc.cluster.local
  ROOT: /mnt/webfiles
  USERS_URL: http://t9-2022630278-gu-svc.t9-2022630278.svc.cluster.local
kind: ConfigMap
metadata:
  creationTimestamp: "2025-12-22T18:22:40Z"
  name: ms-config
  namespace: t9-2022630278
  resourceVersion: "297341"
  uid: a3499418-796e-4836-8c7a-1572ab7a20e2
gustavo [ ~ ]$ kubectl create secret generic azure-file-secret -n t9-2022630278 --from-literal=azurestorageaccountname=t92022630278sa --from-literal=azurestorageaccountkey=ynaCzUMP54ISklrv3CxXwNvW7HHihqB5RXXNhMwwjo6UQmfj2bD54k1JfFbOyNEMuvCJ0ZbuZ6Ri+AStOjhXMw==
secret/azure-file-secret created
gustavo [ ~ ]$
```

Figura 10.11 Creación del secreto para la llave

2. Aplica PV/PVC:


```
Command Prompt x Azure Cloud Shell x + v
gustavo [ ~ ]$ cat > k8s/pv-pvc.yaml <<EOF
apiVersion: v1
kind: PersistentVolume
metadata:
  name: t9-webfiles-pv
spec:
  capacity:
    storage: 5Gi
  accessModes:
    - ReadWriteMany
  persistentVolumeReclaimPolicy: Retain
  csi:
    driver: file.csi.azure.com
    volumeHandle: t9-webfiles-pv
    volumeAttributes:
      shareName: ${SHARE_NAME}
    nodeStageSecretRef:
      name: azure-file-secret
      namespace: ${NS}
---
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: t9-webfiles-pvc
spec:
  volumeName: t9-webfiles-pv
  capacity:
    storage: 5Gi
  accessModes:
    - ReadWriteMany
  resources:
    requests:
      storage: 5Gi
gustavo [ ~ ]$ kubectl apply -f k8s/pv-pvc.yaml
persistentvolume/t9-webfiles-pv created
persistentvolumeclaim/t9-webfiles-pvc created
gustavo [ ~ ]$ kubectl get pv
NAME                CAPACITY   ACCESS MODES   RECLAIM POLICY   STATUS   CLAIM   STORAGECLASS   VOLUMEATTRIBUTESCLASS   REASON   AGE
t9-webfiles-pv      5Gi        RWX            Retain           Available         default        <unset>                                8s
gustavo [ ~ ]$ kubectl get pvc
NAME                STATUS      VOLUME          CAPACITY   ACCESS MODES   STORAGECLASS   VOLUMEATTRIBUTESCLASS   AGE
t9-webfiles-pvc     Pending    t9-webfiles-pv   5Gi        RWX            default        <unset>                  47s
gustavo [ ~ ]$ kubectl get pv -n t9-2022630278
NAME                CAPACITY   ACCESS MODES   RECLAIM POLICY   STATUS   CLAIM   STORAGECLASS   VOLUMEATTRIBUTESCLASS   REASON   AGE
t9-webfiles-pv      5Gi        RWX            Retain           Available         default        <unset>                                84s
gustavo [ ~ ]$ kubectl get pvc -n t9-2022630278
NAME                STATUS      VOLUME          CAPACITY   ACCESS MODES   STORAGECLASS   VOLUMEATTRIBUTESCLASS   AGE
t9-webfiles-pvc     Pending    t9-webfiles-pv   5Gi        RWX            default        <unset>                  97s
gustavo [ ~ ]$
```

```
Command Prompt x Azure Cloud Shell x + v
gustavo [ ~ ]$ kubectl get pv
NAME                CAPACITY   ACCESS MODES   RECLAIM POLICY   STATUS   CLAIM   STORAGECLASS   VOLUMEATTRIBUTESCLASS   REASON   AGE
t9-webfiles-pv      5Gi        RWX            Retain           Available         default        <unset>                                8s
gustavo [ ~ ]$ kubectl get pvc
NAME                STATUS      VOLUME          CAPACITY   ACCESS MODES   STORAGECLASS   VOLUMEATTRIBUTESCLASS   AGE
t9-webfiles-pvc     Pending    t9-webfiles-pv   5Gi        RWX            default        <unset>                  47s
gustavo [ ~ ]$ kubectl get pv -n t9-2022630278
NAME                CAPACITY   ACCESS MODES   RECLAIM POLICY   STATUS   CLAIM   STORAGECLASS   VOLUMEATTRIBUTESCLASS   REASON   AGE
t9-webfiles-pv      5Gi        RWX            Retain           Available         default        <unset>                                84s
gustavo [ ~ ]$ kubectl get pvc -n t9-2022630278
NAME                STATUS      VOLUME          CAPACITY   ACCESS MODES   STORAGECLASS   VOLUMEATTRIBUTESCLASS   AGE
t9-webfiles-pvc     Pending    t9-webfiles-pv   5Gi        RWX            default        <unset>                  97s
gustavo [ ~ ]$
```

```
Command Prompt x Azure Cloud Shell x Azure Cloud Shell x + v
VERBOSE: Authenticating to Azure ...
VERBOSE: Building your Azure drive ...
PS /home/gustavo> az aks get-credentials -n t9-2022630278-aks -g t9-2022630278-rg
A different object named t9-2022630278-aks already exists in your kubeconfig file.
Overwrite? (y/n): n
A different object named t9-2022630278-aks already exists in contexts in your kubeconfig file.
PS /home/gustavo> az account set --subscription fd58a3da-fcef-47d1-ac0e-5b891faa4251
PS /home/gustavo> bash
gustavo [ ~ ]$ kubectl get secrets
NAME                                TYPE      DATA      AGE
azure-file-secret                   Opaque    2           134m
mysql-credentials-ga                Opaque    4           142m
mysql-credentials-gc                Opaque    4           142m
mysql-credentials-gu                Opaque    4           144m
gustavo [ ~ ]$ ls
k8s  Microsoft
gustavo [ ~ ]$ cd ~ /k8s
bash: cd: too many arguments
gustavo [ ~ ]$ cd k8s
gustavo [ ~/k8s ]$ ls
pvc.yaml  pv-pvc.yaml  pv.yaml
gustavo [ ~/k8s ]$ cd ..
gustavo [ ~ ]$ kubectl get pvc -n t9-2022630278
NAME                                STATUS    VOLUME      CAPACITY   ACCESS MODES   STORAGECLASS   VOLUMEATTRIBUTESCLASS   A
GE
t9-webfiles-pvc                    Bound    t9-webfiles-pv  5Gi        RWX              <unset>          <unset>                  6
1m
gustavo [ ~ ]$ |
```

Figura 10.12 virificacion de estatus de los yaml

4. Montar el PVC en el microservicio “Servidor web”

- En el Deployment del servicio web (t9-2022630278-sw), monta el PVC y usa ROOT=/mnt/webfiles. Si ya tienes tu manifiesto, revisa que tenga esto: