

# Mid-term Report: River Network Detection Project

Srinivasan M (IMT2021058)      Siddharth Kothari (IMT2021019)  
Sankalp Kothari (IMT2021028)

October 14, 2024

## 1 Summary of Accomplishments

### 1.1 Code Completion for Training

- Identified and rectified a few errors which were present in the codes after summer.
- Few errors included the number of corrupted pixels exceeding the threshold, caused due to incorrect procedure while corrupting, an example of which is shown in Figure 1




Figure 1: Wrong corruption model

### 1.2 Retraining of Vanilla UNet

- Retrained the Vanilla UNet model to allow for a 70:10:20 train:val:test split, with 20 epochs.
- The results show a very good performance for the UNet model without any corruption. They are shown in Table 1

### 1.3 Adversarial Training

- Started Adversarial Training for the UNet Model with the same train test split as provided for the Vanilla UNet.
- 1/3rd of the training and validation data is corrupted using Erosion, 1/3rd by Dilation, and 1/3rd is kept untouched.
- Randomness is brought about in the corruption by introducing randomness in the size of the kernel window used for erosion and dilation, with higher kernel sizes preferred for images with a higher white pixel ration for erosion, and vice versa.
- The results for adversarial training are shown in Table 1

### 1.4 Visualisations

- Began Qualitative and Quantitative analysis of the results using Visualisations.
- Wrote codes to visualise the training of each of the models across epochs to observe the variation in accuracies, and observe the effect of the corruption levels.

- Wrote codes to visualise the predicted masks and expected masks for the test data to perform qualitative analysis of results. Some results are given below.

## 1.5 Work on the Paper

- Started writing the paper, and written all of the work done so far in the paper.
- The paper primarily consists of our work with making the dataset using NDWI Index [15], preprocessing techniques [3, 13, 8, 7], training approaches [12], models used, and our results with adversarial training. All qualitative and quantitative results so far have been included in the paper.
- We also dive deep into related works [9, 10, 1, 16, 14] and provide some background theory on a number of techniques that we use in the paper.

## 1.6 Readings

We are currently looking into other models of corruption, for which we are currently reading other papers. Some links to papers we are currently reading include -

- Unsupervised Domain Adaptation for Remote Sensing Image Semantic Segmentation Using Region and Category Adaptive Domain Discriminator [2].
- Domain Adaptation using NDWI index for Water-land Semantic Segmentation [4].
- VQUNet: Vector Quantization U-Net for Defending Adversarial Attacks by Regularizing Unwanted Noise [5].
- Bit-Flip Attack: Crushing Neural Network With Progressive Bit Search [11].
- Metapoison: Practical general-purpose clean-label data poisoning [6].

## 2 Next Steps

1. We need to now begin experimentation with a few more corruption models and techniques, whose results we can include in the paper.
2. We are currently looking into more types of corruption, including more traditional types such as rotation etc, and other corruption techniques outside of erosion and dilation. We are currently looking into these possible methods.

## 3 Results and Inferences

### 3.1 Quantitative Results

Table 1 shows the results for the various metrics, for the various levels of corruption tested so far. The results clearly suggest that the model is able to adjust well to even moderate levels of corruption, being able to tolerate upto 12% corruption without loss in accuracy, while accuracy falls considerably for a higher corruption.

Table 1: Performance Metrics of U-Net Model

Metric	Clean UNet	2% corruption	12 % corruption	20 % corruption
Average Dice Coefficient	0.7696	0.7748	0.7693	0.0541
Average IoU	0.8230	0.8252	0.8224	0.4150
Average Pixel Accuracy	0.9554	0.9546	0.9546	0.8045
Average Precision	0.8959	0.8959	0.8989	0.7425
Average Recall	0.8688	0.8734	0.8641	0.5134
Average F1 Score	0.8652	0.8677	0.8646	0.4642
Average Specificity	0.9708	0.968	0.9748	0.9988
Model's Overall Accuracy	0.9554	0.9546	0.9546	0.8045






Figure 2: Epoch Data for all the three models




Figure 3: Image, actual mask, predicted without thresholding, and predicted mask for 20% corruption model




Figure 4: Image, actual mask, predicted without thresholding, and predicted mask for 12% corruption model

### 3.2 Training Trends and Inferences

The validation accuracy trends for all the three models shown in Figure 2 indicate that the model does not overfit, as is also indicated by the decreasing training accuracy as the corruption level increases. However, the model with 22% corruption is not able to perform well on the test data, unlike the models with 12 % corruption, and 2 % corruption.

This suggests that the model is able to tolerate and not overfit to only certain levels of corruption, while performance degradation occurs at higher levels.

### 3.3 Qualitative Examples

The example images shown in Figures 3, 4 and 5 indicate that with the increase in corruption levels, it becomes increasingly difficult for the model to distinguish land from water, although a little distinguishing is possible before the threshold is applied. To get a proper mask, we will need adaptive thresholding, otherwise the model with higher corruption will not work well.




Figure 5: Image, actual mask, predicted without thresholding, and predicted mask for 2% corruption model

## References

- [1] Derrick Bonafilia, Beth Tellman, Tyler Anderson, and Erica Issenberg. Sen1floods11: a georeferenced dataset to train and test deep learning flood algorithms for sentinel-1. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, pages 835–845, 2020.
- [2] Xiaoshu Chen, Shaoming Pan, and Yanwen Chong. Unsupervised domain adaptation for remote sensing image semantic segmentation using region and category adaptive domain discriminator. *IEEE Transactions on Geoscience and Remote Sensing*, 60:1–13, 2022.
- [3] Anthony Freeman. Radiometric calibration of sar image data. 2010.
- [4] Cheng Gu, Wenxin Hu, and Wei Zheng. Domain adaptation using ndwi index for water-land semantic segmentation. In *Proceedings of the 2021 3rd International Conference on Big Data Engineering, BDE '21*, page 90–96, New York, NY, USA, 2021. Association for Computing Machinery.
- [5] Zhixun He and Mukesh Singhal. Vqunet: Vector quantization u-net for defending adversarial attacks by regularizing unwanted noise. In *Proceedings of the 2024 7th International Conference on Machine Vision and Applications*, volume 17 of *ICMVA 2024*, page 69–76. ACM, March 2024.

- [6] W Ronny Huang, Jonas Geiping, Liam Fowl, Gavin Taylor, and Tom Goldstein. Metapoison: Practical general-purpose clean-label data poisoning. *Advances in Neural Information Processing Systems*, 33:12080–12091, 2020.
- [7] Dr Kumar. Urban objects detection from c-band synthetic aperture radar (sar) satellite images through simulating filter properties. *Scientific Reports*, 11, 03 2021.
- [8] J. Lee, L. Jurkevich, Piet Dewaele, Patrick Wambacq, and A. Oosterlinck. Speckle filtering of synthetic aperture radar images: A review. *Remote Sensing Reviews*, 8, 02 1994.
- [9] Christopher B. Obida, George A. Blackburn, James D. Whyatt, and Kirk T. Semple. River network delineation from sentinel-1 sar data. *International Journal of Applied Earth Observation and Geoinformation*, 83:101910, 2019.
- [10] Conor O’Sullivan, Ambrish Kashyap, Seamus Coveney, Xavier Monteys, and Soumyabrata Dev. Enhancing coastal water body segmentation with landsat irish coastal segmentation (lics) dataset. *Remote Sensing Applications: Society and Environment*, 36:101276, 2024.
- [11] Adnan Siraj Rakin, Zhezhi He, and Deliang Fan. Bit-flip attack: Crushing neural network with progressive bit search. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, October 2019.
- [12] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation, 2015.
- [13] H. Wakabayashi, K. Motohashi, T. Kitagami, B. Tjahjono, S. Dewayani, D. Hidayat, and C. Hongo. Flooded area extraction of rice paddy field in indonesia using sentinel-1 sar data. *The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, XLII-3:73–76, 2019.
- [14] Leena Warmedinger, Martin Huber, Mira Anand, Bernhard Lehner, Carolin Walper, Larissa Gorzawski, Michele Thieme, Birgit Wessel, and Achim Roth. The new hydrographic hydrosheds database derived from the tandem-x dem. In *IGARSS 2023 - 2023 IEEE International Geoscience and Remote Sensing Symposium*, pages 1485–1488, 2023.
- [15] Marc Wieland, Florian Fichtner, Sandro Martinis, Sandro Groth, Christian Krullikowski, Simon Plank, and Mahdi Motagh. S1s2-water: A global dataset for semantic segmentation of water bodies from sentinel-1 and sentinel-2 satellite images. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 17:1084–1099, 2024.
- [16] Dai Yamazaki, Daiki Ikeshima, Jeison Sosa, Paul Bates, George Allen, and Tamlin Pavelsky. Merit hydro: A high-resolution global hydrography map based on latest topography dataset. *Water Resources Research*, 55, 06 2019.