

CIS 371 Web Application Programming

TypeScript IV



Lecturer: **Dr. Yong Zhuang**

TypeScript Functions (& Lambdas)

Important Takeaway Concept

- *Assigned to a variable*
- *Passed as an argument to another function*
- *Returned as a value from other functions*

JS & TS allow variables of type Function

JS & TS variables can hold either data or code

- *JS & TS variables can be assigned typical data values like numbers, strings, and objects,*
- *or they can be assigned functions*

Three variations of Function Declarations

```
function plus2 (a:number, b:number): number {  
  return a + b;  
}
```

named

```
const plus2 = function (a:number, b:number): number {  
  return a + b;  
}
```

anonymous func

```
const plus2 = (a:number, b:number) : number => {  
  return a + b;  
}
```

lambda function

Any of these function declarations can be invoked using ONE syntax:

```
let out:number;  
out = plus2(5.0, 2.9);
```

Vars of "function" type

typeless AND 1-line return contraction

```
const plus2 = (a, b) => a + b
```

Fat Arrow fns: single-line return contraction

```
const plusTwo = (a:number, b:number) : number => {  
  const sum = a + b;  
  return sum;  
}
```

no 'function' keyword.

```
const plusTwo = (a:number, b:number) : number => {  
  return a + b;  
}
```

If 'return' can be the only statement

```
const plusTwo = (a:number, b:number) : number => a + b;  
const plusTwo = (a,b) => a + b;    // typeless
```

implicit return

omit both the curly braces {} and the 'return' keyword.

Variables of func type

plus20 and plus22 are variables that hold your DATA

```
const plus20 = "+20";  
const plus22 = { positive: true, value: 22 }
```

```
const plus2 = function (a:number, b:number): number {  
    return a + b;  
}  
  
const plusTwo = (a:number, b:number) : number => {  
    return a + b;  
}
```

*plus2 and plusTwo are variables that hold your **CODE***

```
console.log(typeof plus20); // string  
console.log(typeof plus22); // object  
console.log(typeof plus2);  // function  
console.log(typeof plusTwo); // function
```

Functions as Arguments (to another Fn)

Array.sort()

```
const atoms = ["Neon", "Iron", "Calcium", "Hydrogen"]
console.log(atoms.sort())
// ["Calcium", "Hydrogen", "Iron", "Neon"]
```

```
const primes = [23, 17, 5, 101, 19]
const sorted_nums = primes.sort()
console.log(sorted_nums)
```




[101, 17, 19, 23, 5]

Array.prototype.sort()

The `sort()` method of `Array` instances sorts the elements of an array [in place](#) and returns the reference to the same array, now sorted. The default sort order is ascending, built upon converting the elements into strings, then comparing their sequences of UTF-16 code units values.

[Online Doc](#)

Array.sort() builtin behavior



To fix this **“bug”**, we have to tell `sort()` the **collating order between two data items**

Array.sort() with collating order

```
function numericOrder(a:number, b:number): number {  
    if (a < b) return -1;           // any negative number  
    else if (a > b) return +1;      // any positive number  
    else return 0;  
}
```

```
const primes = [23, 17, 5, 101, 19]  
const sorted_nums = primes.sort(numericOrder)  
console.log(sorted_nums) // [5, 17, 19, 23, 101] Ok
```

The collating function must return a **number**

- Negative when the “first” item should be placed BEFORE the “second” item
- Positive when the “first” item should be placed AFTER the “second” item
- Zero when the order of the two items is irrelevant

Array.sort() on objects

```
type Language = {  
  name: string;  yearCreated: number  
}  
  
const langs: Language[] = [  
  { name: "C", yearCreated: 1970},  
  { name: "JavaScript", yearCreated: 1995},  
  { name: "Fortran", yearCreated: 1954}  
]  
  
function orderByName(a:Language, b:Language): number {  
  return a.name.localeCompare(b.name)  
}  
  
function orderByYear(a:Language, b:Language): number {  
  return a.yearCreated - b.yearCreated  
}  
  
langs.sort(orderByName)
```

*The collating function takes two parameters of type Language but must **return a number***

Array.sort() on objects

```
type Language = {  
  name: string;  yearCreated: number  
}  
  
const langs: Language[] = [  
  { name: "C", yearCreated: 1970},  
  { name: "JavaScript", yearCreated: 1995},  
  { name: "Fortran", yearCreated: 1954}  
]  
  
function orderByName(a:string, b:string): number {  
  return a.localeCompare(b)  
}  
  
function orderByYear(a:number, b:number): number {  
  return a - b  
}  
  
langs.sort(orderByName)
```

The collating function must take two parameters of type Language

Array.sort() on objects

```
type Language = {  
    name: string;  yearCreated: number  
}  
  
const langs: Language[] = [  
    { name: "C", yearCreated: 1970},  
    { name: "JavaScript", yearCreated: 1995},  
    { name: "Fortran", yearCreated: 1954}  
]
```

```
function orderByName(a:Language, b:Language): number {  
    return a.name.localeCompare(b.name)  
}  
  
langs.sort(orderByName)
```

Option 1: named function

```
langs.sort(  
    function (a:Language, b:Language): number {  
        return a.name.localeCompare(b.name)  
    }  
)
```

Option 2: unnamed function

```
langs.sort(  
    (a:Language, b:Language): number => {  
        return a.name.localeCompare(b.name)  
    }  
)
```

Option 3: lambda function

```
langs.sort(  
    (a, b) => a.name.localeCompare(b.name)  
)
```

Opt 4: typeless lambda & 1-line return contraction

Function Optional Parameters/Arguments

```
// whoAmI can be called with 2, 3, or 4 args
const whoAmI = (name: string, age: number, occupation?: string, spouse?: string): void => {
    console.log("Work as", occupation);
    console.log("Spouse name:", spouse ?? "N/A")
}
```

whoAmI("Andy", 22);	// Work as undefined
	// Spouse name: N/A
whoAmI("Bob", 43, "banker");	// Work as banker
	// Spouse name: N/A
whoAmI("Chuck", 31, undefined, "Cindy");	// Work as undefined
	// Spouse name Cindy
whoAmI("Chuck", 31, null, "Cindy");	// Work as null
	// Spouse name Cindy

Function Parameter Default Value

```
const whoAmI = (name: string, age: number, occupation: string = "Student", spouse?: string):  
void => {  
    console.log("Work as", occupation);  
    console.log("Spouse name:", spouse ?? "N/A")  
}
```

whoAmI("Andy", 22);	// Work as undefined
	// Spouse name: N/A
whoAmI("Bob", 43, "banker");	// Work as banker
	// Spouse name: N/A
whoAmI("Chuck", 31, undefined, "Cindy");	// Work as Student
	// Spouse name Cindy
whoAmI("Chuck", 31, null, "Cindy");	// Work as null
	// Spouse name Cindy

Array Operations

Array high-order functions

- `Array.every()`, `Array.some()`
- `Array.find()`, `findIndex()`
- `Array.filter()`, `Array.map()`, `Array.flatMap()`
- `Array.forEach()`
- `Array.reduce()`
- ... and many others
- `flatMap()` is available in ES2019

```
// tsconfig.json {  
  "compilerOptions": {  
    "target": "ES2019",  
    // other options go here  
  }  
  ...  
}
```

Array high-order functions

```
type Shape = {  
  color: string;  
  numSides: number;  
  sideDims: Array<number>; // the length of each side  
};
```

```
let shapes: Array<Shape> = [_____]
```



Array.some(): do we have any green shape?



shapes.some (?????) → Yes

```
function isGreen(s: Shape): boolean {  
  return s.color === "green"  
}
```

```
const someGreen = shapes.some(isGreen);  
console.log(someGreen); // true
```

- Purpose: Test if at least one element in the array passes the test implemented by the provided function.
- Return value: **A Boolean** (true if at least one passes the test, otherwise false).

```
const someGreen = shapes.some(function (s: Shape): boolean {  
  return s.color === "green";  
}); // Anonymous function
```

```
const someGreen = shapes.some((s: Shape): boolean => {  
  return s.color === "green";  
}); // Anonymous fat arrow
```

```
const someGreen = shapes.some((s: Shape): boolean => s.color === "green");  
// 1 line return elimination
```

```
const someGreen = shapes.some((s) => s.color === "green");  
// No explicit type
```

Array.some(): do we have any green shape?



shapes.some (?????) → Yes

Incorrect!!!

```
function isGreen(col: string): boolean {  
    return col === "green";  
}  
  
const someGreen = shapes.some(isGreen);  
console.log(someGreen); // true
```

***// isGreen must take a Shape as its input parameter
// NOT a string!!!***

Array.every(): are all shapes triangle?



```
function isTriangle(s: Shape): boolean {  
    return s.numSides === 3;  
}  
  
const allTriangle = shapes.every(isTriangle);  
console.log(allTriangle); // false
```

- Purpose: Tests whether all elements in the array pass the test implemented by the provided function.
- Return value: **A Boolean** (true if every element passes the test, otherwise false).

`shapes.every (?????)`

```
const allTriangle = shapes.every(function (s: Shape): boolean {  
    return s.numSides === 3;           // Anonymous function  
});  
  
const allTriangle = shapes.every((s: Shape): boolean => {  
    return s.numSides === 3;           // Anonymous fat arrow  
});  
  
const allTriangle = shapes.every((s: Shape): boolean => s.numSides === 3);  
                                     // 1 line return elimination  
  
const allTriangle = shapes.every((s) => s.numSides === 3);  
                                     // No explicit type
```

Array.forEach(): inspect all shapes



```
function printShape(s: Shape): void {  
  console.log("# of sides", s.numSides);  
}
```

```
shapes.forEach(printShape);
```

`shapes.forEach (?????)`

- Purpose: Executes a provided function once for each array element.
- Return value: **undefined**.

```
shapes.forEach(function (s: Shape): void {  
  console.log("# of sides", s.numSides);  
}); // Anonymous function
```

```
shapes.forEach((s: Shape): void => {  
  console.log("# of sides", s.numSides);  
}); // Anonymous fat arrow
```

```
shapes.forEach((s) => {  
  console.log("# of sides", s.numSides);  
}); // No explicit type
```

Array.findIndex(): where is ...?



```
function isTriangle(s: Shape): boolean {  
    return s.numSides === 3;  
}
```

```
const idxTriangle = shapes.findIndex(isTriangle);  
console.log(idxTriangle); // 1
```

- Purpose: To find the index of the **first element** in the array that satisfies a provided testing function.
- Return value: the index of the **first element** in the array that passes the test. If **no elements** pass the test, it returns **-1**.

```
const idxTriangle = shapes.findIndex(function (s: Shape): boolean {  
    return s.numSides === 3;  
});  
  
const idxTriangle = shapes.findIndex((s: Shape): boolean => {  
    return s.numSides === 3;  
});  
  
const idxTriangle = shapes.findIndex((s: Shape): boolean => s.numSides === 3);  
  
const idxTriangle = shapes.findIndex((s) => s.numSides === 3);
```