192425192

G Vishnu Madhav

EXP31:

```
#include <stdio.h>

#include <string.h>

#include <stdint.h>


static const int
IP[64]={58,50,42,34,26,18,10,2,60,52,44,36,28,20,12,4,62,54,46,38,30,22,14,6,64,56,48,40,32,24,16,8,57,49,41,33,25,17,9,1,59,51,43,35,27,19,11,3,61,53,45,37,29,21,13,5,63,55,47,39,31,23,15,7};

static const int
FP[64]={40,8,48,16,56,24,64,32,39,7,47,15,55,23,63,31,38,6,46,14,54,22,62,30,37,5,45,13,53,21,61,29,36,4,44,12,52,20,60,28,35,3,43,11,51,19,59,27,34,2,42,10,50,18,58,26,33,1,41,9,49,17,57,25};

static const int
EX[48]={32,1,2,3,4,5,4,5,6,7,8,9,8,9,10,11,12,13,12,13,14,15,16,17,16,17,18,19,20,21,20,21,22,23,24,25,24,25,26,27,28,29,28,29,30,31,32,1};

static const int
PP[32]={16,7,20,21,29,12,28,17,1,15,23,26,5,18,31,10,2,8,24,14,32,27,3,9,19,13,30,6,22,11,4,25};

static const int
PC1[56]={57,49,41,33,25,17,9,1,58,50,42,34,26,18,10,2,59,51,43,35,27,19,11,3,60,52,44,36,63,55,47,39,31,23,15,7,62,54,46,38,30,22,14,6,61,53,45,37,29,21,13,5,28,20,12,4};

static const int
PC2[48]={14,17,11,24,1,5,3,28,15,6,21,10,23,19,12,4,26,8,16,7,27,20,13,2,41,52,31,37,47,55,30,40,51,45,33,48,44,49,39,56,34,53,46,42,50,36,29,32};

static const int SHIFTS[16]={1,1,2,2,2,2,2,2,1,2,2,2,2,2,2,1};

static const int SB[8][64]={

{14,4,13,1,2,15,11,8,3,10,6,12,5,9,0,7,0,15,7,4,14,2,13,1,10,6,12,11,9,5,3,8,4,1,14,8,13,6,2,11,15,12,9,7,3,10,5,0,15,12,8,2,4,9,1,7,5,11,3,14,10,0,6,13},

{15,1,8,14,6,11,3,4,9,7,2,13,12,0,5,10,3,13,4,7,15,2,8,14,12,0,1,10,6,9,11,5,0,14,7,11,10,4,13,1,5,8,12,6,9,3,2,15,13,8,10,1,3,15,4,2,11,6,7,12,0,5,14,9},

{10,0,9,14,6,3,15,5,1,13,12,7,11,4,2,8,13,7,0,9,3,4,6,10,2,8,5,14,12,11,15,1,13,6,4,9,8,15,3,0,11,1,2,12,5,10,14,7,1,10,13,0,6,9,8,7,4,15,14,3,11,5,2,12},
```

```
{7,13,14,3,0,6,9,10,1,2,8,5,11,12,4,15,13,8,11,5,6,15,0,3,4,7,2,12,1,10,14,9,10,6,9,0,12,11,7,
13,15,1,3,14,5,2,8,4,3,15,0,6,10,1,13,8,9,4,5,11,12,7,2,14},

{2,12,4,1,7,10,11,6,8,5,3,15,13,0,14,9,14,11,2,12,4,7,13,1,5,0,15,10,3,9,8,6,4,2,1,11,10,13,7,
8,15,9,12,5,6,3,0,14,11,8,12,7,1,14,2,13,6,15,0,9,10,4,5,3},

{12,1,10,15,9,2,6,8,0,13,3,4,14,7,5,11,10,15,4,2,7,12,9,5,6,1,13,14,0,11,3,8,9,14,15,5,2,8,12,
3,7,0,4,10,1,13,11,6,4,3,2,12,9,5,15,10,11,14,1,7,6,0,8,13},

{4,11,2,14,15,0,8,13,3,12,9,7,5,10,6,1,13,0,11,7,4,9,1,10,14,3,5,12,2,15,8,6,1,4,11,13,12,3,7,
14,10,15,6,8,0,5,9,2,6,11,13,8,1,4,10,7,9,5,0,15,14,2,3,12},

{13,2,8,4,6,15,11,1,10,9,3,14,5,0,12,7,1,15,13,8,10,3,7,4,12,5,6,11,0,14,9,2,7,11,4,1,9,12,14,
2,0,6,10,13,15,3,5,8,2,1,14,7,4,10,8,13,15,12,9,0,3,5,6,11}};


static void permute(const int *t,int n,const unsigned char *in,unsigned char *out){
    int i; for(i=0;i<n;i++) out[i]=in[t[i]-1];
}
static void to_bits(const unsigned char *b,int n,unsigned char *bits){
    int i; for(i=0;i<n*8;i++) bits[i]=(b[i/8]>>(7-i%8))&1;
}
static void from_bits(const unsigned char *bits,int n,unsigned char *b){
    int i; memset(b,0,n); for(i=0;i<n*8;i++) b[i/8]|=bits[i]<<(7-i%8);
}
static void des_ksched(const unsigned char key[8],unsigned char sk[16][48]){
    unsigned char kb[64],cd[56],c[28],d[28],t[28];
    int r,i,s;
    to_bits(key,8,kb); permute(PC1,56,kb,cd);
    memcpy(c,cd,28); memcpy(d,cd+28,28);
    for(r=0;r<16;r++){
        for(s=0;s<SHIFTS[r];s++){
            memcpy(t,c,28); for(i=0;i<28;i++) c[i]=t[(i+1)%28];
            memcpy(t,d,28); for(i=0;i<28;i++) d[i]=t[(i+1)%28];
        }
        memcpy(cd,c,28); memcpy(cd+28,d,28); permute(PC2,48,cd,sk[r]);
    }
```

```
}
static void des_crypt(const unsigned char in[8],unsigned char out[8],unsigned char sk[16]
[48],int dec){
   unsigned char b[64],ip[64],L[32],R[32],e[48],f[32],s[32],pre[64],ob[64];
   int r,i,j,row,col,v; unsigned char tmp;
   to_bits(in,8,b); permute(IP,64,b,ip);
   memcpy(L,ip,32); memcpy(R,ip+32,32);
   for(r=0;r<16;r++){
      const unsigned char *k=sk[dec?15-r:r];
      permute(EX,48,R,e); for(i=0;i<48;i++) e[i]^=k[i];
      for(j=0;j<8;j++){
         row=(e[6*j]<<1)|e[6*j+5];
         col=(e[6*j+1]<<3)|(e[6*j+2]<<2)|(e[6*j+3]<<1)|e[6*j+4];
         v=SB[j][row*16+col];
         for(i=0;i<4;i++) s[4*j+i]=(v>>(3-i))&1;
      }
      permute(PP,32,s,f);
      for(i=0;i<32;i++){ tmp=R[i]; R[i]=L[i]^f[i]; L[i]=tmp; }
   }
   memcpy(pre,R,32); memcpy(pre+32,L,32);
   permute(FP,64,pre,ob); from_bits(ob,8,out);
}
/* convenience: one 8-byte block with an 8-byte key */
static void des_block(const unsigned char in[8],unsigned char out[8],const unsigned char
key[8],int dec){
   unsigned char sk[16][48]; des_ksched(key,sk); des_crypt(in,out,sk,dec);
}
static void phex(const char *label,const unsigned char *b,int n){
   int i; printf("%s",label); for(i=0;i<n;i++) printf("%02X",b[i]); printf("\n");
}
```

```
/* CMAC subkey generation for a b-byte block:
   K1 = L << 1           if MSB(L) = 0,   K1 = (L << 1) XOR Rb   if MSB(L) = 1
   K2 = K1 << 1 (same rule applied to K1)
   Rb = 0x1B for 64-bit blocks   (x^64  + x^4 + x^3 + x + 1)
   Rb = 0x87 for 128-bit blocks  (x^128 + x^7 + x^2 + x + 1)                  */
static void dbl(const unsigned char *in, unsigned char *out, int b, unsigned char Rb) {
    int i, msb = in[0] >> 7;
    for (i = 0; i < b; i++) out[i] = (in[i] << 1) | (i + 1 < b ? in[i + 1] >> 7 : 0);
    if (msb) out[b - 1] ^= Rb;
}

int main() {
    unsigned char key[8] = {0x13,0x34,0x57,0x79,0x9B,0xBC,0xDF,0xF1};
    unsigned char zero[8] = {0}, L64[8], K1[16], K2[16];
    unsigned char L128[16] =
{0x7D,0xF7,0x6B,0x0C,0x1A,0xB8,0x99,0xB3,0x3E,0x42,0xF0,0x47,0xB9,0x1B,0x54,0x6
F};

    printf("a) Constants: 64-bit block  -> Rb = 0x1B (00011011)\n");
    printf("              128-bit block -> Rb = 0x87 (10000111)\n\n");

    printf("b) 64-bit block (cipher: DES), L = E(K, 0^64)\n");
    des_block(zero, L64, key, 0);
    phex("   L  = ", L64, 8);
    dbl(L64, K1, 8, 0x1B);  phex("   K1 = ", K1, 8);
    dbl(K1, K2, 8, 0x1B);   phex("   K2 = ", K2, 8);

    printf("\n   128-bit block (L from AES-128 with the standard CMAC test key)\n");
    phex("   L  = ", L128, 16);
    dbl(L128, K1, 16, 0x87);  phex("   K1 = ", K1, 16);
    dbl(K1, K2, 16, 0x87);    phex("   K2 = ", K2, 16);
```

```
    printf("\n   The left shift multiplies L by x in GF(2^b). If the top bit was 1 the\n");
    printf("   result overflows x^b, which is reduced modulo the irreducible polynomial\n");
    printf("   by XORing the constant Rb. K1 = L.x and K2 = L.x^2.\n");
    return 0;
}
```

OUTPUT:

```
a) Constants: 64-bit block  -> Rb = 0x1B (00011011)
              128-bit block -> Rb = 0x87 (10000111)

b) 64-bit block (cipher: DES), L = E(K, 0^64)
   L  = 948A43F98A834F7E
   K1 = 291487F315069EE7
   K2 = 52290FE62A0D3DCE

   128-bit block (L from AES-128 with the standard CMAC test key)
   L  = 7DF76B0C1AB899B33E42F047B91B546F
   K1 = FBEED618357133667C85E08F7236A8DE
   K2 = F7DDAC306AE266CCF90BC11EE46D513B

   The left shift multiplies L by x in GF(2^b). If the top bit was 1 the
   result overflows x^b, which is reduced modulo the irreducible polynomial
   by XORing the constant Rb. K1 = L.x and K2 = L.x^2.
```