

# Foundations of Computing

## Lecture 12

Arkady Yerukhimovich

February 28, 2023

# Outline

- 1 Lecture 10+11 Review
- 2 Models of Computation
- 3 The Turing Machine
- 4 Formalizing Turing Machines


# Lecture 10+11 Review

- Equivalence of CFGs and PDAs
- CFL Pumping Lemma
- Using the CFL Pumping Lemma

# Outline

- 1 Lecture 10+11 Review
- 2 Models of Computation
- 3 The Turing Machine
- 4 Formalizing Turing Machines


# Finite Automata



Recall:

- An NFA/DFA has no external storage
- Only memory must be encoded in the finite number of states
- Can only recognize regular languages


# Pushdown Automata (PDA)



A PDA consists of:

- An NFA for a control unit
- A Stack for storage

# Pushdown Automata (PDA)



A PDA consists of:

- An NFA for a control unit
- A Stack for storage

Recall:

- Can only access memory in LIFO fashion
- Can only recognize context-free languages

# A Model for General Computation

## Question

All the prior models of computation couldn't recognize some simple languages. Can we develop a computation model that captures all languages that can be computed on any computer?

## Our Goal


One model to rule them all!




# Outline

- 1 Lecture 10+11 Review
- 2 Models of Computation
- 3 The Turing Machine**
- 4 Formalizing Turing Machines

# The Turing Machine




# The Turing Machine



Key Differences:

- A TM can read and write to its tape


# The Turing Machine



Key Differences:

- A TM can read and write to its tape
- The read/write head can move to the right and to the left


# The Turing Machine



## Key Differences:

- A TM can read and write to its tape
- The read/write head can move to the right and to the left
- No separate input tape, input written onto memory tape at start


# The Turing Machine



## Key Differences:

- A TM can read and write to its tape
- The read/write head can move to the right and to the left
- No separate input tape, input written onto memory tape at start
- The memory tape is infinite

# The Turing Machine



## Key Differences:

- A TM can read and write to its tape
- The read/write head can move to the right and to the left
- No separate input tape, input written onto memory tape at start
- The memory tape is infinite
- Control FA has accept and reject states that are immediately output if entered

# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

An Algorithm for  $M$ :

On input string  $s$  (written on the tape):



# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

An Algorithm for  $M$ :

On input string  $s$  (written on the tape):

- 1 Scan the input to check that it contains exactly one  $\#$  symbol, if not reject.

# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

An Algorithm for  $M$ :

On input string  $s$  (written on the tape):

- 1 Scan the input to check that it contains exactly one  $\#$  symbol, if not reject.
- 2 Zigzag to corresponding positions on each side of the  $\#$  and see if they contain same symbol. If not, reject. Cross off symbols as they are checked

# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

An Algorithm for  $M$ :

On input string  $s$  (written on the tape):

- 1 Scan the input to check that it contains exactly one  $\#$  symbol, if not reject.
- 2 Zigzag to corresponding positions on each side of the  $\#$  and see if they contain same symbol. If not, reject. Cross off symbols as they are checked
- 3 When all symbols to the left of  $\#$  have been crossed off, check that no uncrossed-off symbols remain to the right of  $\#$ . If any symbols remain, reject, otherwise accept.

# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

Recognizing  $s = 011000\#011000$ :

# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

Recognizing  $s = 011000\#011000$ :

011000#011000  $\sqcup \dots$

# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

Recognizing  $s = 011000\#011000$ :

011000#011000  $\sqcup \dots$

x11000#011000  $\sqcup \dots$

# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

Recognizing  $s = 011000\#011000$ :

011000#011000  $\sqcup \dots$

x11000#011000  $\sqcup \dots$

x11000#x11000  $\sqcup \dots$

# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

Recognizing  $s = 011000\#011000$ :

011000#011000  $\sqcup \dots$

x11000#011000  $\sqcup \dots$

x11000#x11000  $\sqcup \dots$

xx1000#x11000  $\sqcup \dots$



# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

Recognizing  $s = 011000\#011000$ :

```
011000#011000 ⊐ ...  
x11000#011000 ⊐ ...  
x11000#x11000 ⊐ ...  
xx1000#x11000 ⊐ ...  
...  
xxxxxx#xxxxxx ⊐ ...
```

# An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

Recognizing  $s = 011000\#011000$ :

011000#011000  $\sqcup \dots$

x11000#011000  $\sqcup \dots$

x11000#x11000  $\sqcup \dots$

xx1000#x11000  $\sqcup \dots$

$\dots$

xxxxxx#xxxxxx  $\sqcup \dots$

*accept*

What is an algorithm?

## What is an algorithm?

- A collection of simple instructions for carrying out some task

## What is an algorithm?

- A collection of simple instructions for carrying out some task
- A process according to which it can be determined by a finite number of operations – Hilbert 1900

## What is an algorithm?

- A collection of simple instructions for carrying out some task
- A process according to which it can be determined by a finite number of operations – Hilbert 1900

Algorithms are critical to understand solutions / complexity of a problem

## What is an algorithm?

- A collection of simple instructions for carrying out some task
- A process according to which it can be determined by a finite number of operations – Hilbert 1900

Algorithms are critical to understand solutions / complexity of a problem

- To show how to solve a problem, we design an algorithm

## What is an algorithm?

- A collection of simple instructions for carrying out some task
- A process according to which it can be determined by a finite number of operations – Hilbert 1900

Algorithms are critical to understand solutions / complexity of a problem

- To show how to solve a problem, we design an algorithm
- To reason about languages accepted by NFA/PDA, we designed algorithms



## What is an algorithm?

- A collection of simple instructions for carrying out some task
- A process according to which it can be determined by a finite number of operations – Hilbert 1900

Algorithms are critical to understand solutions / complexity of a problem

- To show how to solve a problem, we design an algorithm
- To reason about languages accepted by NFA/PDA, we designed algorithms
- How can we reason about the limits of what an algorithm can compute?

## Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

## Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Observations:

## Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Observations:

- While unproven, all modern computers satisfy Church-Turing thesis

## Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Observations:

- While unproven, all modern computers satisfy Church-Turing thesis
- To prove that some problem cannot be solved by an algorithm, enough to reason about Turing Machines

## Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Observations:

- While unproven, all modern computers satisfy Church-Turing thesis
- To prove that some problem cannot be solved by an algorithm, enough to reason about Turing Machines
- This means that Turing Machines give an abstraction to capture “feasible computation”

## Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Observations:

- While unproven, all modern computers satisfy Church-Turing thesis
- To prove that some problem cannot be solved by an algorithm, enough to reason about Turing Machines
- This means that Turing Machines give an abstraction to capture “feasible computation”

# Outline

- 1 Lecture 10+11 Review
- 2 Models of Computation
- 3 The Turing Machine
- 4 Formalizing Turing Machines**



# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:

# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:

- 1  $Q$  – set of states

# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:

- 1  $Q$  – set of states
- 2  $\Sigma$  – input alphabet (not including blank symbol  $\sqcup$ )

# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:

- 1  $Q$  – set of states
- 2  $\Sigma$  – input alphabet (not including blank symbol  $\sqcup$ )
- 3  $\Gamma$  – tape alphabet, where  $\sqcup \in \Gamma$  and  $\Sigma \subseteq \Gamma$

# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:

- 1  $Q$  – set of states
- 2  $\Sigma$  – input alphabet (not including blank symbol  $\sqcup$ )
- 3  $\Gamma$  – tape alphabet, where  $\sqcup \in \Gamma$  and  $\Sigma \subseteq \Gamma$
- 4  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$  – transition function

# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:

- 1  $Q$  – set of states
- 2  $\Sigma$  – input alphabet (not including blank symbol  $\sqcup$ )
- 3  $\Gamma$  – tape alphabet, where  $\sqcup \in \Gamma$  and  $\Sigma \subseteq \Gamma$
- 4  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$  – transition function
- 5  $q_0 \in Q$  – start state
- 6  $q_{accept} \in Q$  – accept state
- 7  $q_{reject} \in Q$  – reject state

Transition function:  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:

- 1  $Q$  – set of states
- 2  $\Sigma$  – input alphabet (not including blank symbol  $\sqcup$ )
- 3  $\Gamma$  – tape alphabet, where  $\sqcup \in \Gamma$  and  $\Sigma \subseteq \Gamma$
- 4  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$  – transition function
- 5  $q_0 \in Q$  – start state
- 6  $q_{accept} \in Q$  – accept state
- 7  $q_{reject} \in Q$  – reject state

Transition function:  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

On state  $q$  and tape input  $\gamma$ :

# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:

- ①  $Q$  – set of states
- ②  $\Sigma$  – input alphabet (not including blank symbol  $\sqcup$ )
- ③  $\Gamma$  – tape alphabet, where  $\sqcup \in \Gamma$  and  $\Sigma \subseteq \Gamma$
- ④  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$  – transition function
- ⑤  $q_0 \in Q$  – start state
- ⑥  $q_{accept} \in Q$  – accept state
- ⑦  $q_{reject} \in Q$  – reject state

Transition function:  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

On state  $q$  and tape input  $\gamma$ :

- move control to state  $q'$ ,



# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:

- ①  $Q$  – set of states
- ②  $\Sigma$  – input alphabet (not including blank symbol  $\sqcup$ )
- ③  $\Gamma$  – tape alphabet, where  $\sqcup \in \Gamma$  and  $\Sigma \subseteq \Gamma$
- ④  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$  – transition function
- ⑤  $q_0 \in Q$  – start state
- ⑥  $q_{accept} \in Q$  – accept state
- ⑦  $q_{reject} \in Q$  – reject state

Transition function:  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

On state  $q$  and tape input  $\gamma$ :

- move control to state  $q'$ ,
- write  $\gamma'$  to the tape,

# Turing Machine – Formal Definition

A Turing machine is a 7-tuple:


- ①  $Q$  – set of states
- ②  $\Sigma$  – input alphabet (not including blank symbol  $\sqcup$ )
- ③  $\Gamma$  – tape alphabet, where  $\sqcup \in \Gamma$  and  $\Sigma \subseteq \Gamma$
- ④  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$  – transition function
- ⑤  $q_0 \in Q$  – start state
- ⑥  $q_{accept} \in Q$  – accept state
- ⑦  $q_{reject} \in Q$  – reject state

Transition function:  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

On state  $q$  and tape input  $\gamma$ :


- move control to state  $q'$ ,
- write  $\gamma'$  to the tape,
- and move the tape head one spot to either Left or Right

# Computing on a Turing Machine



## Configuration of a TM


# Computing on a Turing Machine



## Configuration of a TM

- Describes the state of a TM computation


# Computing on a Turing Machine



## Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head


# Computing on a Turing Machine



## Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example:  $01q_310$

# Computing on a Turing Machine




## Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example:  $01q_310$

Definitions:

- Configuration  $C_1$  **yields**  $C_2$ , if  $M$  can go from  $C_1$  to  $C_2$  in a single step

# Computing on a Turing Machine



## Configuration of a TM


- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example:  $01q_310$

## Definitions:

- Configuration  $C_1$  **yields**  $C_2$ , if  $M$  can go from  $C_1$  to  $C_2$  in a single step
- start configuration of  $M$  on input  $s$  – configuration  $q_0s$



# Computing on a Turing Machine




## Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example:  $01q_310$

## Definitions:

- Configuration  $C_1$  **yields**  $C_2$ , if  $M$  can go from  $C_1$  to  $C_2$  in a single step
- start configuration of  $M$  on input  $s$  – configuration  $q_0s$
- accepting configuration – any config with state  $q_{accept}$

# Computing on a Turing Machine




## Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example:  $01q_310$

## Definitions:

- Configuration  $C_1$  **yields**  $C_2$ , if  $M$  can go from  $C_1$  to  $C_2$  in a single step
- start configuration of  $M$  on input  $s$  – configuration  $q_0s$
- accepting configuration – any config with state  $q_{accept}$
- rejecting configuration – any config with state  $q_{reject}$

# Computing on a Turing Machine




## Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example:  $01q_310$

## Definitions:

- Configuration  $C_1$  **yields**  $C_2$ , if  $M$  can go from  $C_1$  to  $C_2$  in a single step
- start configuration of  $M$  on input  $s$  – configuration  $q_0s$
- accepting configuration – any config with state  $q_{accept}$
- rejecting configuration – any config with state  $q_{reject}$
- halting configuration – accepting or rejecting configs

# Computing on a Turing Machine



## Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example:  $01q_310$

## Definitions:

- Configuration  $C_1$  **yields**  $C_2$ , if  $M$  can go from  $C_1$  to  $C_2$  in a single step
- start configuration of  $M$  on input  $s$  – configuration  $q_0s$
- accepting configuration – any config with state  $q_{accept}$
- rejecting configuration – any config with state  $q_{reject}$
- halting configuration – accepting or rejecting configs

# Computing on a Turing Machine

A TM accepts an input  $s$  if there exists a sequence of configs  $C_1, C_2, \dots, C_k$  where

# Computing on a Turing Machine

A TM accepts an input  $s$  if there exists a sequence of configs  $C_1, C_2, \dots, C_k$  where

- 1  $C_1$  is the start configuration of  $M$  on input  $s$

# Computing on a Turing Machine

A TM accepts an input  $s$  if there exists a sequence of configs  $C_1, C_2, \dots, C_k$  where

- 1  $C_1$  is the start configuration of  $M$  on input  $s$
- 2 Each  $C_i$  yields  $C_{i+1}$

# Computing on a Turing Machine

A TM accepts an input  $s$  if there exists a sequence of configs  $C_1, C_2, \dots, C_k$  where

- 1  $C_1$  is the start configuration of  $M$  on input  $s$
- 2 Each  $C_i$  yields  $C_{i+1}$
- 3  $C_k$  is an accepting configuration



# Computing on a Turing Machine

A TM accepts an input  $s$  if there exists a sequence of configs  $C_1, C_2, \dots, C_k$  where

- ①  $C_1$  is the start configuration of  $M$  on input  $s$
- ② Each  $C_i$  yields  $C_{i+1}$
- ③  $C_k$  is an accepting configuration

## Language $L(M)$

The collection of strings that  $M$  accepts

# Characterizing Computability of Languages

# Characterizing Computability of Languages

Definition: Recursively enumerable languages

# Characterizing Computability of Languages

## Definition: Recursively enumerable languages

A language  $L$  is *Turing-recognizable* or *recursively enumerable* if some TM  $M$  recognizes it

## Definition: Recursively enumerable languages

A language  $L$  is *Turing-recognizable* or *recursively enumerable* if some TM  $M$  recognizes it

- $M$  halts and accepts all strings in  $L$

## Definition: Recursively enumerable languages

A language  $L$  is *Turing-recognizable* or *recursively enumerable* if some TM  $M$  recognizes it

- $M$  halts and accepts all strings in  $L$
- $M$  may not halt on strings not in  $L$  – does not necessarily have to reject

# Characterizing Computability of Languages

## Definition: Recursively enumerable languages

A language  $L$  is *Turing-recognizable* or *recursively enumerable* if some TM  $M$  recognizes it

- $M$  halts and accepts all strings in  $L$
- $M$  may not halt on strings not in  $L$  – does not necessarily have to reject

## Definition: Decidable languages

A language  $L$  is *decidable* or *recursive* if some TM  $M$  decides it

# Characterizing Computability of Languages

## Definition: Recursively enumerable languages

A language  $L$  is *Turing-recognizable* or *recursively enumerable* if some TM  $M$  recognizes it

- $M$  halts and accepts all strings in  $L$
- $M$  may not halt on strings not in  $L$  – does not necessarily have to reject

## Definition: Decidable languages

A language  $L$  is *decidable* or *recursive* if some TM  $M$  decides it

- $M$  halts on all inputs, accepting those in  $L$  and rejecting those not in  $L$



# Another Example

Consider  $L = \{0^{2^n} \mid n \geq 0\}$

TM algorithm  $M$  for recognizing  $L$ :

On input  $s$ :

# Another Example

Consider  $L = \{0^{2^n} \mid n \geq 0\}$

TM algorithm  $M$  for recognizing  $L$ :

On input  $s$ :

- 1 If the tape has exactly one 0, accept

# Another Example

Consider  $L = \{0^{2^n} \mid n \geq 0\}$

TM algorithm  $M$  for recognizing  $L$ :

On input  $s$ :

- 1 If the tape has exactly one 0, accept
- 2 If the tape has an odd number of 0's, greater than 1, reject

# Another Example

Consider  $L = \{0^{2^n} \mid n \geq 0\}$

TM algorithm  $M$  for recognizing  $L$ :

On input  $s$ :

- 1 If the tape has exactly one 0, accept
- 2 If the tape has an odd number of 0's, greater than 1, reject
- 3 Sweep left to right across tape, crossing out every other 0

# Another Example

Consider  $L = \{0^{2^n} \mid n \geq 0\}$

TM algorithm  $M$  for recognizing  $L$ :

On input  $s$ :

- 1 If the tape has exactly one 0, accept
- 2 If the tape has an odd number of 0's, greater than 1, reject
- 3 Sweep left to right across tape, crossing out every other 0
- 4 Return the head to the left-hand end of the tape

# Another Example

Consider  $L = \{0^{2^n} \mid n \geq 0\}$

TM algorithm  $M$  for recognizing  $L$ :

On input  $s$ :

- 1 If the tape has exactly one 0, accept
- 2 If the tape has an odd number of 0's, greater than 1, reject
- 3 Sweep left to right across tape, crossing out every other 0
- 4 Return the head to the left-hand end of the tape
- 5 Go to step 1

# Another Example

Consider  $L = \{0^{2^n} \mid n \geq 0\}$

TM algorithm  $M$  for recognizing  $L$ :

On input  $s$ :

- 1 If the tape has exactly one 0, accept
- 2 If the tape has an odd number of 0's, greater than 1, reject
- 3 Sweep left to right across tape, crossing out every other 0
- 4 Return the head to the left-hand end of the tape
- 5 Go to step 1


# Making $M$ Formal

- $Q = \{q_1, q_2, q_3, q_4, q_5, q_a, q_r\}$
- $\Sigma = \{0\}$
- $\Gamma = \{0, x, \sqcup\}$
- $\delta :$



# Making $M$ Formal

- $Q = \{q_1, q_2, q_3, q_4, q_5, q_a, q_r\}$
- $\Sigma = \{0\}$
- $\Gamma = \{0, x, \sqcup\}$
- $\delta :$



# Running $M$ on $w = 0000$

