

Foundations of Computing

Lecture 18 – Exam Review

Arkady Yerukhimovich

March 25, 2025

Outline

- 1 Lecture 17 Review
- 2 Turing Machines
- 3 Languages Recognized by TMs
- 4 Undecidable Languages
- 5 Proofs by Reduction
- 6 Kolmogorov Complexity


Lecture 17 Review

- Review of Reductions
- Types of Reductions – Mapping reductions, Turing reductions
- A brief intro into Kolmogorov complexity


Outline

- 1 Lecture 17 Review
- 2 Turing Machines**
- 3 Languages Recognized by TMs
- 4 Undecidable Languages
- 5 Proofs by Reduction
- 6 Kolmogorov Complexity

The Turing Machine




The Turing Machine



Key Differences:

- A TM can read and write to its tape


The Turing Machine



Key Differences:

- A TM can read and write to its tape
- The read/write head can move to the right and to the left


The Turing Machine



Key Differences:

- A TM can read and write to its tape
- The read/write head can move to the right and to the left
- No separate input tape, input written onto memory tape at start


The Turing Machine



Key Differences:

- A TM can read and write to its tape
- The read/write head can move to the right and to the left
- No separate input tape, input written onto memory tape at start
- The memory tape is infinite

The Turing Machine



Key Differences:

- A TM can read and write to its tape
- The read/write head can move to the right and to the left
- No separate input tape, input written onto memory tape at start
- The memory tape is infinite
- Control FA has accept and reject states. If entered, TM halts and outputs.

An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

An Algorithm for M :

On input string s (written on the tape):

An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

An Algorithm for M :

On input string s (written on the tape):

- 1 Scan the input to check that it contains exactly one $\#$ symbol, if not reject.

An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

An Algorithm for M :

On input string s (written on the tape):

- 1 Scan the input to check that it contains exactly one $\#$ symbol, if not reject.
- 2 Zigzag to corresponding positions on each side of the $\#$ and see if they contain same symbol. If not, reject. Cross off symbols as they are checked

An Example: TM To Recognize $L = \{w\#w \mid w \in \{0,1\}^*\}$

An Algorithm for M :

On input string s (written on the tape):

- 1 Scan the input to check that it contains exactly one $\#$ symbol, if not reject.
- 2 Zigzag to corresponding positions on each side of the $\#$ and see if they contain same symbol. If not, reject. Cross off symbols as they are checked
- 3 When all symbols to the left of $\#$ have been crossed off, check that no uncrossed-off symbols remain to the right of $\#$. If any symbols remain, reject, otherwise accept.

Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Observations:

Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Observations:

- While unproven, all modern computers satisfy Church-Turing thesis

Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Observations:

- While unproven, all modern computers satisfy Church-Turing thesis
- To prove that some problem cannot be solved by an algorithm, enough to reason about Turing Machines

Church-Turing Thesis (1936)

Anything that can be computed by an algorithm can be computed by a Turing Machine

Observations:

- While unproven, all modern computers satisfy Church-Turing thesis
- To prove that some problem cannot be solved by an algorithm, enough to reason about Turing Machines
- This means that Turing Machines give an abstraction to capture “feasible computation”

Turing Machine – Formal Definition

A Turing machine M is a 7-tuple:

- 1 Q – set of states

Turing Machine – Formal Definition

A Turing machine M is a 7-tuple:

- 1 Q – set of states
- 2 Σ – input alphabet (not including blank symbol \sqcup)

Turing Machine – Formal Definition

A Turing machine M is a 7-tuple:

- 1 Q – set of states
- 2 Σ – input alphabet (not including blank symbol \sqcup)
- 3 Γ – tape alphabet, where $\sqcup \in \Gamma$ and $\Sigma \subseteq \Gamma$

Turing Machine – Formal Definition

A Turing machine M is a 7-tuple:

- 1 Q – set of states
- 2 Σ – input alphabet (not including blank symbol \sqcup)
- 3 Γ – tape alphabet, where $\sqcup \in \Gamma$ and $\Sigma \subseteq \Gamma$
- 4 $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$ – transition function

Turing Machine – Formal Definition

A Turing machine M is a 7-tuple:

- 1 Q – set of states
- 2 Σ – input alphabet (not including blank symbol \sqcup)
- 3 Γ – tape alphabet, where $\sqcup \in \Gamma$ and $\Sigma \subseteq \Gamma$
- 4 $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$ – transition function
- 5 $q_0 \in Q$ – start state
- 6 $q_{accept} \in Q$ – accept state
- 7 $q_{reject} \in Q$ – reject state

Initial State on input s :

M starts in state q_0 with $s\sqcup$ on the tape and tape head on s_0 .

Transition function: $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

Turing Machine – Formal Definition

A Turing machine M is a 7-tuple:

- 1 Q – set of states
- 2 Σ – input alphabet (not including blank symbol \sqcup)
- 3 Γ – tape alphabet, where $\sqcup \in \Gamma$ and $\Sigma \subseteq \Gamma$
- 4 $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$ – transition function
- 5 $q_0 \in Q$ – start state
- 6 $q_{accept} \in Q$ – accept state
- 7 $q_{reject} \in Q$ – reject state

Initial State on input s :

M starts in state q_0 with $s\sqcup$ on the tape and tape head on s_0 .

Transition function: $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

On state q and tape input γ :

Turing Machine – Formal Definition

A Turing machine M is a 7-tuple:

- ① Q – set of states
- ② Σ – input alphabet (not including blank symbol \sqcup)
- ③ Γ – tape alphabet, where $\sqcup \in \Gamma$ and $\Sigma \subseteq \Gamma$
- ④ $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$ – transition function
- ⑤ $q_0 \in Q$ – start state
- ⑥ $q_{accept} \in Q$ – accept state
- ⑦ $q_{reject} \in Q$ – reject state

Initial State on input s :

M starts in state q_0 with $s\sqcup$ on the tape and tape head on s_0 .

Transition function: $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

On state q and tape input γ :

- move control to state q' ,

Turing Machine – Formal Definition

A Turing machine M is a 7-tuple:

- ① Q – set of states
- ② Σ – input alphabet (not including blank symbol \sqcup)
- ③ Γ – tape alphabet, where $\sqcup \in \Gamma$ and $\Sigma \subseteq \Gamma$
- ④ $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$ – transition function
- ⑤ $q_0 \in Q$ – start state
- ⑥ $q_{accept} \in Q$ – accept state
- ⑦ $q_{reject} \in Q$ – reject state

Initial State on input s :

M starts in state q_0 with $s\sqcup$ on the tape and tape head on s_0 .

Transition function: $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

On state q and tape input γ :

- move control to state q' ,
- write γ' to the tape,

Turing Machine – Formal Definition

A Turing machine M is a 7-tuple:

- ① Q – set of states
- ② Σ – input alphabet (not including blank symbol \sqcup)
- ③ Γ – tape alphabet, where $\sqcup \in \Gamma$ and $\Sigma \subseteq \Gamma$
- ④ $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$ – transition function
- ⑤ $q_0 \in Q$ – start state
- ⑥ $q_{accept} \in Q$ – accept state
- ⑦ $q_{reject} \in Q$ – reject state

Initial State on input s :


M starts in state q_0 with $s\sqcup$ on the tape and tape head on s_0 .

Transition function: $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$

On state q and tape input γ :


- move control to state q' ,
- write γ' to the tape,
- and move the tape head one spot to either Left or Right

Computing on a Turing Machine



Configuration of a TM


Computing on a Turing Machine



Configuration of a TM

- Describes the state of a TM computation


Computing on a Turing Machine



Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head


Computing on a Turing Machine



Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example: $01q_310$

Computing on a Turing Machine




Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example: $01q_310$

Definitions:

- Configuration C_1 **yields** C_2 , if M can go from C_1 to C_2 in a single step

Computing on a Turing Machine




Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example: $01q_310$

Definitions:

- Configuration C_1 **yields** C_2 , if M can go from C_1 to C_2 in a single step
- start configuration of M on input s – configuration q_0s

Computing on a Turing Machine




Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example: $01q_310$

Definitions:

- Configuration C_1 **yields** C_2 , if M can go from C_1 to C_2 in a single step
- start configuration of M on input s – configuration q_0s
- accepting configuration – any config with state q_{accept}

Computing on a Turing Machine




Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example: $01q_310$

Definitions:

- Configuration C_1 **yields** C_2 , if M can go from C_1 to C_2 in a single step
- start configuration of M on input s – configuration q_0s
- accepting configuration – any config with state q_{accept}
- rejecting configuration – any config with state q_{reject}

Computing on a Turing Machine




Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example: $01q_310$

Definitions:

- Configuration C_1 **yields** C_2 , if M can go from C_1 to C_2 in a single step
- start configuration of M on input s – configuration q_0s
- accepting configuration – any config with state q_{accept}
- rejecting configuration – any config with state q_{reject}
- halting configuration – accepting or rejecting configs

Computing on a Turing Machine




Configuration of a TM

- Describes the state of a TM computation
- Current state of control, state of tape, location of tape head
- Example: $01q_310$

Definitions:

- Configuration C_1 **yields** C_2 , if M can go from C_1 to C_2 in a single step
- start configuration of M on input s – configuration q_0s
- accepting configuration – any config with state q_{accept}
- rejecting configuration – any config with state q_{reject}
- halting configuration – accepting or rejecting configs

Full Specification: Running M on $w = 0000$



Outline

- 1 Lecture 17 Review
- 2 Turing Machines
- 3 Languages Recognized by TMs**
- 4 Undecidable Languages
- 5 Proofs by Reduction
- 6 Kolmogorov Complexity

Characterizing Computability of Languages

Definition: Recursively enumerable languages

Characterizing Computability of Languages

Definition: Recursively enumerable languages

A language L is *Turing-recognizable* or *recursively enumerable* if some TM M recognizes it

Characterizing Computability of Languages

Definition: Recursively enumerable languages

A language L is *Turing-recognizable* or *recursively enumerable* if some TM M recognizes it

- M halts and accepts all strings in L

Characterizing Computability of Languages

Definition: Recursively enumerable languages

A language L is *Turing-recognizable* or *recursively enumerable* if some TM M recognizes it

- M halts and accepts all strings in L
- M may not halt on strings not in L – does not necessarily have to reject

Characterizing Computability of Languages

Definition: Recursively enumerable languages

A language L is *Turing-recognizable* or *recursively enumerable* if some TM M recognizes it

- M halts and accepts all strings in L
- M may not halt on strings not in L – does not necessarily have to reject

Definition: Decidable languages

A language L is *decidable* or *recursive* if some TM M decides it

Characterizing Computability of Languages

Definition: Recursively enumerable languages

A language L is *Turing-recognizable* or *recursively enumerable* if some TM M recognizes it

- M halts and accepts all strings in L
- M may not halt on strings not in L – does not necessarily have to reject

Definition: Decidable languages

A language L is *decidable* or *recursive* if some TM M decides it

- M halts on all inputs, accepting those in L and rejecting those not in L

Take Away

You should be able to show that a language is decidable or Turing-recognizable by designing a TM algorithm.

Important TM Notation / Observations

- TM always takes a string as input
 - Sometimes we want to talk about a TM taking another type of input (e.g., a graph, a FA, a TM)
 - To do so, we must serialize the object into a string
 - Notation: $\langle G \rangle$

Important TM Notation / Observations

- TM always takes a string as input
 - Sometimes we want to talk about a TM taking another type of input (e.g., a graph, a FA, a TM)
 - To do so, we must serialize the object into a string
 - Notation: $\langle G \rangle$
- We can “mark” cells on the tape
 - Notation: \dot{x}
 - Technically, this is adding a symbol to Γ

Important TM Notation / Observations

- TM always takes a string as input
 - Sometimes we want to talk about a TM taking another type of input (e.g., a graph, a FA, a TM)
 - To do so, we must serialize the object into a string
 - Notation: $\langle G \rangle$
- We can “mark” cells on the tape
 - Notation: \dot{x}
 - Technically, this is adding a symbol to Γ
- Can use multiple tapes if it's useful

Important TM Notation / Observations

- TM always takes a string as input
 - Sometimes we want to talk about a TM taking another type of input (e.g., a graph, a FA, a TM)
 - To do so, we must serialize the object into a string
 - Notation: $\langle G \rangle$
- We can “mark” cells on the tape
 - Notation: \dot{x}
 - Technically, this is adding a symbol to Γ
- Can use multiple tapes if it's useful
- Can give a machine as an input to another machine
 - All machines we have seen can be written as finite tuples, e.g. $(Q, \Sigma, \Gamma, \delta, q_0, q_{accept}, q_{reject})$
 - So, we can write this as a string and pass it to a TM
 - TM can then run the machine from this description

Important TM Notation / Observations

- TM always takes a string as input
 - Sometimes we want to talk about a TM taking another type of input (e.g., a graph, a FA, a TM)
 - To do so, we must serialize the object into a string
 - Notation: $\langle G \rangle$
- We can “mark” cells on the tape
 - Notation: \dot{x}
 - Technically, this is adding a symbol to Γ
- Can use multiple tapes if it's useful
- Can give a machine as an input to another machine
 - All machines we have seen can be written as finite tuples, e.g. $(Q, \Sigma, \Gamma, \delta, q_0, q_{accept}, q_{reject})$
 - So, we can write this as a string and pass it to a TM
 - TM can then run the machine from this description
 - A TM that accepts any TM and runs it is called a *universal TM*

Specification of a Turing Machine

There are several levels of detail for specifying a TM

- ① Full specification
 - Give full detail of transition function δ
 - This is very tedious

Specification of a Turing Machine

There are several levels of detail for specifying a TM

① Full specification

- Give full detail of transition function δ
- This is very tedious

② Turing Machine Algorithm specification

- Explain algorithmically what happens on the tape
- For example, scan the tape until you find a #, zig-zag on the tape, etc.
- Don't bother specifying a DFA for the control state

Specification of a Turing Machine

There are several levels of detail for specifying a TM

① Full specification

- Give full detail of transition function δ
- This is very tedious

② Turing Machine Algorithm specification

- Explain algorithmically what happens on the tape
- For example, scan the tape until you find a #, zig-zag on the tape, etc.
- Don't bother specifying a DFA for the control state

③ Algorithm specification

- Give algorithm in pseudocode
- Don't explicitly spell out what happens on the tape

Turing Machine Variants

- Multi-tape Turing Machine
- Nondeterministic Turing Machine


What You Need to Know

- Be able to explain what the variant is
- Know whether it is equivalent to standard TM
- Be able to explain why

We have seen many examples of decidable languages:

- Languages about strings
- Languages about DFAs/NFAs/CFGs – know which ones are decidable and which are not, why
- Be comfortable with TM's that take another machine as input

Relationships Among Language Classes



Outline

- 1 Lecture 17 Review
- 2 Turing Machines
- 3 Languages Recognized by TMs
- 4 Undecidable Languages**
- 5 Proofs by Reduction
- 6 Kolmogorov Complexity

Preliminaries – Countable and Uncountable Sets

Intuition: Countable sets are ones where we can arrange elements into a “first element”, “second element”, and so on.

Preliminaries – Countable and Uncountable Sets

Intuition: Countable sets are ones where we can arrange elements into a “first element”, “second element”, and so on.

- An infinite set A is *countably infinite* if it has the same cardinality as the natural numbers: $\mathcal{N} = 1, 2, 3, \dots$

Preliminaries – Countable and Uncountable Sets

Intuition: Countable sets are ones where we can arrange elements into a “first element”, “second element”, and so on.

- An infinite set A is *countably infinite* if it has the same cardinality as the natural numbers: $\mathcal{N} = 1, 2, 3, \dots$
- A set A is countable if it is finite or countably infinite

Preliminaries – Countable and Uncountable Sets

Intuition: Countable sets are ones where we can arrange elements into a “first element”, “second element”, and so on.

- An infinite set A is *countably infinite* if it has the same cardinality as the natural numbers: $\mathcal{N} = 1, 2, 3, \dots$
- A set A is countable if it is finite or countably infinite
- A set that is not countable is *uncountable*

Diagonalization

Real Numbers

The set of real numbers (\mathcal{R}) is uncountable

Proof: By diagonalization

Diagonalization

Real Numbers

The set of real numbers (\mathcal{R}) is uncountable

Proof: By diagonalization

- Assume that \mathcal{R} is countable

Diagonalization

Real Numbers

The set of real numbers (\mathcal{R}) is uncountable

Proof: By diagonalization

- Assume that \mathcal{R} is countable
- Then there is a one-to-one and onto mapping f from \mathcal{N} to \mathcal{R}

Diagonalization

Real Numbers

The set of real numbers (\mathcal{R}) is uncountable

Proof: By diagonalization

- Assume that \mathcal{R} is countable
- Then there is a one-to-one and onto mapping f from \mathcal{N} to \mathcal{R}

n	$f(n)$
1	1.234...
2	3.141...
3	5.556...
\vdots	\vdots

Diagonalization

Real Numbers

The set of real numbers (\mathcal{R}) is uncountable

Proof: By diagonalization

- Assume that \mathcal{R} is countable
- Then there is a one-to-one and onto mapping f from \mathcal{N} to \mathcal{R}

n	$f(n)$
1	1.234...
2	3.141...
3	5.556...
\vdots	\vdots

- We construct a value $x \in \mathcal{R}$ s.t $x \neq f(n)$ for any n
Idea: For all $i \in \mathcal{N}$, make $x_i \neq f(i)_i$

Diagonalization

Real Numbers

The set of real numbers (\mathcal{R}) is uncountable

Proof: By diagonalization

- Assume that \mathcal{R} is countable
- Then there is a one-to-one and onto mapping f from \mathcal{N} to \mathcal{R}

n	$f(n)$
1	1.234...
2	3.141...
3	5.556...
\vdots	\vdots

- We construct a value $x \in \mathcal{R}$ s.t $x \neq f(n)$ for any n
Idea: For all $i \in \mathcal{N}$, make $x_i \neq f(i)_i$
- Contradiction – f is not mapping between \mathcal{R} and \mathcal{N}

A_{TM} is Turing-recognizable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

A_{TM} is Turing-recognizable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine $M_{A_{TM}}$

$M_{A_{TM}}$: On input $\langle M, w \rangle$,

- 1 Run M on input w

A_{TM} is Turing-recognizable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine $M_{A_{TM}}$

$M_{A_{TM}}$: On input $\langle M, w \rangle$,

- 1 Run M on input w
- 2 If M halts, halt and output what M outputs

A_{TM} is Turing-recognizable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine $M_{A_{TM}}$

$M_{A_{TM}}$: On input $\langle M, w \rangle$,

- ① Run M on input w
- ② If M halts, halt and output what M outputs

Correctness:

- For any input $\langle M, w \rangle \in A_{TM}$, M is a TM, and $M(w)$ halts and outputs 1.

A_{TM} is Turing-recognizable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine $M_{A_{TM}}$

$M_{A_{TM}}$: On input $\langle M, w \rangle$,

- ① Run M on input w
- ② If M halts, halt and output what M outputs

Correctness:

- For any input $\langle M, w \rangle \in A_{TM}$, M is a TM, and $M(w)$ halts and outputs 1.
- Hence, $M_{A_{TM}}$, also halts and outputs 1

A_{TM} is Turing-recognizable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine $M_{A_{TM}}$

$M_{A_{TM}}$: On input $\langle M, w \rangle$,

- ① Run M on input w
- ② If M halts, halt and output what M outputs

Correctness:

- For any input $\langle M, w \rangle \in A_{TM}$, M is a TM, and $M(w)$ halts and outputs 1.
- Hence, $M_{A_{TM}}$, also halts and outputs 1
- Thus, $M_{A_{TM}}$ accepts all inputs in A_{TM}

A_{TM} is Turing-recognizable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine $M_{A_{TM}}$

$M_{A_{TM}}$: On input $\langle M, w \rangle$,

- ① Run M on input w
- ② If M halts, halt and output what M outputs

Correctness:

- For any input $\langle M, w \rangle \in A_{TM}$, M is a TM, and $M(w)$ halts and outputs 1.
- Hence, $M_{A_{TM}}$, also halts and outputs 1
- Thus, $M_{A_{TM}}$ accepts all inputs in A_{TM}
- Note that $M_{A_{TM}}$ may not halt on all inputs – doesn't decide A_{TM}

A_{TM} is Undecidable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

A_{TM} is Undecidable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

A_{TM} is Undecidable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that A_{TM} is decided by TM H

$$H(\langle M, w \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ accepts } w \\ \text{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

A_{TM} is Undecidable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that A_{TM} is decided by TM H

$$H(\langle M, w \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ accepts } w \\ \text{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

- Use H to build a TM D that checks whether a TM M accepts its own description, and then does the opposite:

A_{TM} is Undecidable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that A_{TM} is decided by TM H

$$H(\langle M, w \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ accepts } w \\ \text{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

- Use H to build a TM D that checks whether a TM M accepts its own description, and then does the opposite:

On Input $\langle M \rangle$, where M is a TM

- Run H on input $\langle M, \langle M \rangle \rangle$
- Output the opposite of what H outputs

A_{TM} is Undecidable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that A_{TM} is decided by TM H

$$H(\langle M, w \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ accepts } w \\ \text{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

- Use H to build a TM D that checks whether a TM M accepts its own description, and then does the opposite:

On Input $\langle M \rangle$, where M is a TM

- Run H on input $\langle M, \langle M \rangle \rangle$
- Output the opposite of what H outputs

$$D(\langle M \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ does not accept } \langle M \rangle \\ \text{reject} & \text{if } M \text{ accepts } \langle M \rangle \end{cases}$$

A_{TM} is Undecidable

$$A_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that A_{TM} is decided by TM H

$$H(\langle M, w \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ accepts } w \\ \text{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

- Use H to build a TM D that checks whether a TM M accepts its own description, and then does the opposite:

On Input $\langle M \rangle$, where M is a TM

- Run H on input $\langle M, \langle M \rangle \rangle$
- Output the opposite of what H outputs

$$D(\langle M \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ does not accept } \langle M \rangle \\ \text{reject} & \text{if } M \text{ accepts } \langle M \rangle \end{cases}$$

- Now consider what happens if we run D on $\langle D \rangle$

$$D(\langle D \rangle) = \begin{cases} \text{accept} & \text{if } D \text{ does not accept } \langle D \rangle \\ \text{reject} & \text{if } D \text{ accepts } \langle D \rangle \end{cases}$$

How Is This a Diagonalization?

	$\langle M_1 \rangle$	$\langle M_2 \rangle$	$\langle M_3 \rangle$	\dots	$\langle D \rangle$	\dots
M_1	<u>accept</u>	reject	accept		accept	
M_2	reject	<u>reject</u>	reject	\dots	accept	\dots
M_3	accept	accept	<u>accept</u>		reject	
\vdots		\vdots		\ddots		
D	reject	accept	reject		?	

- We have defined D to do the opposite of what M_i does on input $\langle M_i \rangle$
- But what does D do on input $\langle D \rangle$??

Outline

- 1 Lecture 17 Review
- 2 Turing Machines
- 3 Languages Recognized by TMs
- 4 Undecidable Languages
- 5 Proofs by Reduction**
- 6 Kolmogorov Complexity

Main Observation

Suppose that $A \leq B$, then:

Main Observation

Suppose that $A \leq B$, then:

- If A is undecidable
- B must also be undecidable

Main Observation

Suppose that $A \leq B$, then:

- If A is undecidable
- B must also be undecidable

Proof: (by contradiction)

Main Observation

Suppose that $A \leq B$, then:

- If A is undecidable
- B must also be undecidable

Proof: (by contradiction)

- Suppose that B is decidable

Main Observation

Suppose that $A \leq B$, then:

- If A is undecidable
- B must also be undecidable

Proof: (by contradiction)

- Suppose that B is decidable
- Since $A \leq B$, there exists an algorithm (i.e., a reduction) that uses a solution to B to solve A

Main Observation

Suppose that $A \leq B$, then:

- If A is undecidable
- B must also be undecidable

Proof: (by contradiction)

- Suppose that B is decidable
- Since $A \leq B$, there exists an algorithm (i.e., a reduction) that uses a solution to B to solve A
- But, this means that A is decidable by running the machine for B as needed by the reduction

Undecidability of HALT

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Undecidability of HALT

$$HALT_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w\}$$

Theorem: *HALT* is undecidable

Undecidability of HALT

$$HALT_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w\}$$

Theorem: $HALT$ is undecidable

Proof Sketch:

- We show that $A_{TM} \leq HALT$

Undecidability of HALT

$$HALT_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w\}$$

Theorem: *HALT* is undecidable

Proof Sketch:

- We show that $A_{TM} \leq HALT$
- Since we know that A_{TM} is undecidable, this shows that *HALT* is also undecidable

Undecidability of HALT

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Theorem: $HALT$ is undecidable

Proof Sketch:

- We show that $A_{TM} \leq HALT$
- Since we know that A_{TM} is undecidable, this shows that $HALT$ is also undecidable

Proof:

Construct reduction R that decides A_{TM} given a TM D that decides $HALT$

Undecidability of HALT

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Theorem: $HALT$ is undecidable

Proof Sketch:

- We show that $A_{TM} \leq HALT$
- Since we know that A_{TM} is undecidable, this shows that $HALT$ is also undecidable

Proof:

Construct reduction R that decides A_{TM} given a TM D that decides $HALT$

On input $\langle M, w \rangle$, R does the following:

Undecidability of HALT

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Theorem: $HALT$ is undecidable

Proof Sketch:

- We show that $A_{TM} \leq HALT$
- Since we know that A_{TM} is undecidable, this shows that $HALT$ is also undecidable

Proof:

Construct reduction R that decides A_{TM} given a TM D that decides $HALT$

On input $\langle M, w \rangle$, R does the following:

- Run $D(\langle M, w \rangle)$

Undecidability of $HALT$

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Theorem: $HALT$ is undecidable

Proof Sketch:

- We show that $A_{TM} \leq HALT$
- Since we know that A_{TM} is undecidable, this shows that $HALT$ is also undecidable

Proof:

Construct reduction R that decides A_{TM} given a TM D that decides $HALT$

On input $\langle M, w \rangle$, R does the following:

- Run $D(\langle M, w \rangle)$
- If D rejects – $M(w)$ doesn't halt – halt and reject

Undecidability of HALT

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Theorem: $HALT$ is undecidable

Proof Sketch:

- We show that $A_{TM} \leq HALT$
- Since we know that A_{TM} is undecidable, this shows that $HALT$ is also undecidable

Proof:

Construct reduction R that decides A_{TM} given a TM D that decides $HALT$

On input $\langle M, w \rangle$, R does the following:

- Run $D(\langle M, w \rangle)$
- If D rejects – $M(w)$ doesn't halt – halt and reject
- if D accepts – $M(w)$ halts – Simulate $M(w)$ until it halts

Undecidability of HALT

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Theorem: *HALT* is undecidable

Proof Sketch:

- We show that $A_{TM} \leq HALT$
- Since we know that A_{TM} is undecidable, this shows that *HALT* is also undecidable

Proof:

Construct reduction R that decides A_{TM} given a TM D that decides *HALT*

On input $\langle M, w \rangle$, R does the following:

- Run $D(\langle M, w \rangle)$
- If D rejects – $M(w)$ doesn't halt – halt and reject
- if D accepts – $M(w)$ halts – Simulate $M(w)$ until it halts
- Output whatever M output

Importance of Algorithms

Algorithms

Algorithms are critical for understanding decidability of problems

Importance of Algorithms

Algorithms

Algorithms are critical for understanding decidability of problems

- 1 To show that a problem is decidable – give an algorithm that always terminates and outputs the answer

Algorithms

Algorithms are critical for understanding decidability of problems

- 1 To show that a problem is decidable – give an algorithm that always terminates and outputs the answer
- 2 To show that a problem is undecidable – give an algorithm (a reduction) that shows that this problem can be used to solve one of the undecidable problems

What You Need to Know

You should be able to:

- Understand which direction a reduction should go

What You Need to Know

You should be able to:

- Understand which direction a reduction should go
- Understand implications of such a reduction

What You Need to Know

You should be able to:

- Understand which direction a reduction should go
- Understand implications of such a reduction
- Give a reduction between two related languages


Reduction Types

Know the difference between:

- Mapping reductions
- Turing reductions

Know what each one implies

Mapping Reductions



Mapping Reduction Properties

Mapping reductions are very useful:

Mapping Reduction Properties

Mapping reductions are very useful:

- ① If $A \leq_m B$
 - If B is decidable then A is decidable

Mapping Reduction Properties

Mapping reductions are very useful:

- ① If $A \leq_m B$
 - If B is decidable then A is decidable
 - If A is undecidable then B is undecidable

Mapping Reduction Properties

Mapping reductions are very useful:

- ① If $A \leq_m B$
 - If B is decidable then A is decidable
 - If A is undecidable then B is undecidable
- ② If $A \leq_m B$
 - If B is Turing-recognizable then

Mapping Reduction Properties

Mapping reductions are very useful:

- ① If $A \leq_m B$
 - If B is decidable then A is decidable
 - If A is undecidable then B is undecidable
- ② If $A \leq_m B$
 - If B is Turing-recognizable then A is Turing-recognizable

Mapping Reduction Properties

Mapping reductions are very useful:

① If $A \leq_m B$

- If B is decidable then A is decidable
- If A is undecidable then B is undecidable

② If $A \leq_m B$

- If B is Turing-recognizable then A is Turing-recognizable
- If A is not Turing-recognizable then B is not Turing-recognizable

Turing Reductions

Definition

Language A is Turing reducible to language B ($A \leq_T B$) if can use a decider for B to decide A .

Turing Reductions

Definition

Language A is Turing reducible to language B ($A \leq_T B$) if can use a decider for B to decide A .

- The reduction may make multiple calls to decider for B and may not directly use the result.

Turing Reduction Properties

Turing reductions are more general than mapping reductions:

Turing Reduction Properties

Turing reductions are more general than mapping reductions:

- 1 If $A \leq_m B$, then $A \leq_T B$

Turing Reduction Properties

Turing reductions are more general than mapping reductions:

- 1 If $A \leq_m B$, then $A \leq_T B$
- 2 If $A \leq_T B$, then it is not necessarily the case that $A \leq_m B$

Turing Reduction Properties

Turing reductions are more general than mapping reductions:

- ① If $A \leq_m B$, then $A \leq_T B$
- ② If $A \leq_T B$, then it is not necessarily the case that $A \leq_m B$
 - In particular, $L_{TM} \leq_T \overline{L_{TM}}$, but $L_{TM} \not\leq_m \overline{L_{TM}}$

Turing Reduction Properties

Turing reductions are more general than mapping reductions:

- ① If $A \leq_m B$, then $A \leq_T B$
- ② If $A \leq_T B$, then it is not necessarily the case that $A \leq_m B$
 - In particular, $L_{TM} \leq_T \overline{L_{TM}}$, but $L_{TM} \not\leq_m \overline{L_{TM}}$

But, they have weaker implications than mapping reductions:

Turing Reduction Properties

Turing reductions are more general than mapping reductions:

- ① If $A \leq_m B$, then $A \leq_T B$
- ② If $A \leq_T B$, then it is not necessarily the case that $A \leq_m B$
 - In particular, $L_{TM} \leq_T \overline{L_{TM}}$, but $L_{TM} \not\leq_m \overline{L_{TM}}$

But, they have weaker implications than mapping reductions:

- ③ If $A \leq_T B$
 - If B is decidable then A is decidable

Turing Reduction Properties

Turing reductions are more general than mapping reductions:

- ① If $A \leq_m B$, then $A \leq_T B$
- ② If $A \leq_T B$, then it is not necessarily the case that $A \leq_m B$
 - In particular, $L_{TM} \leq_T \overline{L_{TM}}$, but $L_{TM} \not\leq_m \overline{L_{TM}}$

But, they have weaker implications than mapping reductions:

- ③ If $A \leq_T B$
 - If B is decidable then A is decidable
 - If A is not decidable, then B is not decidable

Turing Reduction Properties

Turing reductions are more general than mapping reductions:

- ① If $A \leq_m B$, then $A \leq_T B$
- ② If $A \leq_T B$, then it is not necessarily the case that $A \leq_m B$
 - In particular, $L_{TM} \leq_T \overline{L_{TM}}$, but $L_{TM} \not\leq_m \overline{L_{TM}}$

But, they have weaker implications than mapping reductions:

- ③ If $A \leq_T B$
 - If B is decidable then A is decidable
 - If A is not decidable, then B is not decidable
- ④ If $A \leq_T B$
 - If B is Turing-recognizable A is not necessarily Turing-recognizable

Turing Reduction Properties

Turing reductions are more general than mapping reductions:

- ① If $A \leq_m B$, then $A \leq_T B$
- ② If $A \leq_T B$, then it is not necessarily the case that $A \leq_m B$
 - In particular, $L_{TM} \leq_T \overline{L_{TM}}$, but $L_{TM} \not\leq_m \overline{L_{TM}}$

But, they have weaker implications than mapping reductions:

- ③ If $A \leq_T B$
 - If B is decidable then A is decidable
 - If A is not decidable, then B is not decidable
- ④ If $A \leq_T B$
 - If B is Turing-recognizable A is not necessarily Turing-recognizable
 - If A is not Turing-recognizable, cannot say if B is Turing-recognizable

Outline

- 1 Lecture 17 Review
- 2 Turing Machines
- 3 Languages Recognized by TMs
- 4 Undecidable Languages
- 5 Proofs by Reduction
- 6 Kolmogorov Complexity**

Kolmogorov Complexity

Definition

Consider $x \in \{0, 1\}^*$.

Definition

Consider $x \in \{0, 1\}^*$.

- 1 The minimal description of x ($d(x)$) is the shortest string $\langle M, w \rangle$ such that TH M on input w halts with x on its tape

Kolmogorov Complexity

Definition

Consider $x \in \{0, 1\}^*$.

- 1 The minimal description of x ($d(x)$) is the shortest string $\langle M, w \rangle$ such that TM M on input w halts with x on its tape
- 2 The Kolmogorov complexity of x is

$$K(x) = |d(x)|$$

Kolmogorov Complexity

Definition

Consider $x \in \{0, 1\}^*$.

- 1 The minimal description of x ($d(x)$) is the shortest string $\langle M, w \rangle$ such that TM M on input w halts with x on its tape
- 2 The Kolmogorov complexity of x is

$$K(x) = |d(x)|$$

- $K(x)$ is the minimal description of x

Kolmogorov Complexity

Definition

Consider $x \in \{0, 1\}^*$.

- 1 The minimal description of x ($d(x)$) is the shortest string $\langle M, w \rangle$ such that TM M on input w halts with x on its tape
- 2 The Kolmogorov complexity of x is

$$K(x) = |d(x)|$$

- $K(x)$ is the minimal description of x
- This captures the “amount of information” in x

What You Need to Know

- Basic definition of Kolmogorov complexity
- Be able to find rough bounds on Kolmogorov complexity
- Don't need to be able to prove anything