

# Foundations of Computing

## Lecture 21

Arkady Yerukhimovich

April 8, 2025

# Outline

- 1 Lecture 20 Review
- 2 A Review of  $\mathcal{P}$  and  $\mathcal{NP}$
- 3 Polynomial-Time Reductions
- 4  $\mathcal{NP}$ -Completeness
- 5  $\mathcal{NP}$ -Completeness Using Reductions

# Lecture 20 Review

- Verifying vs. Deciding
- The Complexity Class  $\mathcal{NP}$

$$\mathcal{NP} = \bigcup_k \text{NTIME}(n^k)$$

# Outline

- 1 Lecture 20 Review
- 2 A Review of  $\mathcal{P}$  and  $\mathcal{NP}$
- 3 Polynomial-Time Reductions
- 4  $\mathcal{NP}$ -Completeness
- 5  $\mathcal{NP}$ -Completeness Using Reductions

- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :

- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :
  - For  $x \in L$ ,  $M(x)$  halts and outputs 1

- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :
  - For  $x \in L$ ,  $M(x)$  halts and outputs 1
  - For  $x \notin L$ ,  $M(x)$  halts and outputs 0

- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :
  - For  $x \in L$ ,  $M(x)$  halts and outputs 1
  - For  $x \notin L$ ,  $M(x)$  halts and outputs 0
  - Runtime of  $M$  is  $O(\text{poly}(|x|))$  for all  $x$  – worst case



- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :
  - For  $x \in L$ ,  $M(x)$  halts and outputs 1
  - For  $x \notin L$ ,  $M(x)$  halts and outputs 0
  - Runtime of  $M$  is  $O(\text{poly}(|x|))$  for all  $x$  – worst case
- $L \in \mathcal{NP}$  if there is a poly-time verifier DTM  $V$ :

- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :
  - For  $x \in L$ ,  $M(x)$  halts and outputs 1
  - For  $x \notin L$ ,  $M(x)$  halts and outputs 0
  - Runtime of  $M$  is  $O(\text{poly}(|x|))$  for all  $x$  – worst case
- $L \in \mathcal{NP}$  if there is a poly-time verifier DTM  $V$ :
  - For  $x \in L$ , there exists  $w \in \{0, 1\}^{\text{poly}(|x|)}$  s.t.  $V(x, w) = 1$

- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :
  - For  $x \in L$ ,  $M(x)$  halts and outputs 1
  - For  $x \notin L$ ,  $M(x)$  halts and outputs 0
  - Runtime of  $M$  is  $O(\text{poly}(|x|))$  for all  $x$  – worst case
- $L \in \mathcal{NP}$  if there is a poly-time verifier DTM  $V$ :
  - For  $x \in L$ , there exists  $w \in \{0, 1\}^{\text{poly}(|x|)}$  s.t.  $V(x, w) = 1$
  - For  $x \notin L$ , for all  $w \in \{0, 1\}^{\text{poly}(|x|)}$ ,  $V(x, w) = 0$

- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :
  - For  $x \in L$ ,  $M(x)$  halts and outputs 1
  - For  $x \notin L$ ,  $M(x)$  halts and outputs 0
  - Runtime of  $M$  is  $O(\text{poly}(|x|))$  for all  $x$  – worst case
- $L \in \mathcal{NP}$  if there is a poly-time verifier DTM  $V$ :
  - For  $x \in L$ , there exists  $w \in \{0, 1\}^{\text{poly}(|x|)}$  s.t.  $V(x, w) = 1$
  - For  $x \notin L$ , for all  $w \in \{0, 1\}^{\text{poly}(|x|)}$ ,  $V(x, w) = 0$
  - $w$  is a witness to  $x \in L$

- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :
  - For  $x \in L$ ,  $M(x)$  halts and outputs 1
  - For  $x \notin L$ ,  $M(x)$  halts and outputs 0
  - Runtime of  $M$  is  $O(\text{poly}(|x|))$  for all  $x$  – worst case
- $L \in \mathcal{NP}$  if there is a poly-time verifier DTM  $V$ :
  - For  $x \in L$ , there exists  $w \in \{0, 1\}^{\text{poly}(|x|)}$  s.t.  $V(x, w) = 1$
  - For  $x \notin L$ , for all  $w \in \{0, 1\}^{\text{poly}(|x|)}$ ,  $V(x, w) = 0$
  - $w$  is a witness to  $x \in L$

## Why Do We Study These?

- $L \in \mathcal{P}$  if there is a poly-time DTM  $M$  that decides  $L$ :
  - For  $x \in L$ ,  $M(x)$  halts and outputs 1
  - For  $x \notin L$ ,  $M(x)$  halts and outputs 0
  - Runtime of  $M$  is  $O(\text{poly}(|x|))$  for all  $x$  – worst case
- $L \in \mathcal{NP}$  if there is a poly-time verifier DTM  $V$ :
  - For  $x \in L$ , there exists  $w \in \{0, 1\}^{\text{poly}(|x|)}$  s.t.  $V(x, w) = 1$
  - For  $x \notin L$ , for all  $w \in \{0, 1\}^{\text{poly}(|x|)}$ ,  $V(x, w) = 0$
  - $w$  is a witness to  $x \in L$

## Why Do We Study These?

Both  $\mathcal{P}$  and  $\mathcal{NP}$  contain many useful languages

# Why are $\mathcal{P}$ and $\mathcal{NP}$ Interesting?

$\mathcal{P}$

- $\mathcal{P}$  captures the class of efficiently decidable languages

# Why are $\mathcal{P}$ and $\mathcal{NP}$ Interesting?

$\mathcal{P}$

- $\mathcal{P}$  captures the class of efficiently decidable languages
- Can determine membership in  $L$  for all inputs



# Why are $\mathcal{P}$ and $\mathcal{NP}$ Interesting?

$\mathcal{P}$

- $\mathcal{P}$  captures the class of efficiently decidable languages
- Can determine membership in  $L$  for all inputs

$\mathcal{NP}$

- $\mathcal{NP}$  captures the class of problems where there exists a short proof that  $x \in L$

# Why are $\mathcal{P}$ and $\mathcal{NP}$ Interesting?

## $\mathcal{P}$

- $\mathcal{P}$  captures the class of efficiently decidable languages
- Can determine membership in  $L$  for all inputs

## $\mathcal{NP}$

- $\mathcal{NP}$  captures the class of problems where there exists a short proof that  $x \in L$
- Can prove  $x \in L$  for all inputs, but can't lie that a string not in  $L$  is in the language

# Why are $\mathcal{P}$ and $\mathcal{NP}$ Interesting?

## $\mathcal{P}$

- $\mathcal{P}$  captures the class of efficiently decidable languages
- Can determine membership in  $L$  for all inputs

## $\mathcal{NP}$

- $\mathcal{NP}$  captures the class of problems where there exists a short proof that  $x \in L$
- Can prove  $x \in L$  for all inputs, but can't lie that a string not in  $L$  is in the language

## $\mathcal{NP}$ -Completeness

There are problems in  $\mathcal{NP}$  that are as hard as any other problem in  $\mathcal{NP}$

# Outline

- 1 Lecture 20 Review
- 2 A Review of  $\mathcal{P}$  and  $\mathcal{NP}$
- 3 Polynomial-Time Reductions
- 4  $\mathcal{NP}$ -Completeness
- 5  $\mathcal{NP}$ -Completeness Using Reductions

# Mapping Reductions

## Mapping Reduction

Language  $A$  is mapping reducible to language  $B$  ( $A \leq_m B$ ) if there is a computable function  $f : \Sigma^* \rightarrow \Sigma^*$ , where for every  $x$ ,

$$x \in A \iff f(x) \in B$$

# Mapping Reductions

## Mapping Reduction

Language  $A$  is mapping reducible to language  $B$  ( $A \leq_m B$ ) if there is a computable function  $f : \Sigma^* \rightarrow \Sigma^*$ , where for every  $x$ ,

$$x \in A \iff f(x) \in B$$

## Poly-time Mapping Reduction

Language  $A$  is poly-time mapping reducible to language  $B$  ( $A \leq_P B$ ) if there is a poly-time computable function  $f : \Sigma^* \rightarrow \Sigma^*$ , where for every  $x$ ,

$$x \in A \iff f(x) \in B$$

# Mapping Reductions

## Mapping Reduction

Language  $A$  is mapping reducible to language  $B$  ( $A \leq_m B$ ) if there is a computable function  $f : \Sigma^* \rightarrow \Sigma^*$ , where for every  $x$ ,

$$x \in A \iff f(x) \in B$$

## Poly-time Mapping Reduction

Language  $A$  is poly-time mapping reducible to language  $B$  ( $A \leq_P B$ ) if there is a poly-time computable function  $f : \Sigma^* \rightarrow \Sigma^*$ , where for every  $x$ ,

$$x \in A \iff f(x) \in B$$

- Poly-time reductions give an efficient way to convert membership testing in  $A$  to membership testing in  $B$

# Mapping Reductions

## Mapping Reduction

Language  $A$  is mapping reducible to language  $B$  ( $A \leq_m B$ ) if there is a computable function  $f : \Sigma^* \rightarrow \Sigma^*$ , where for every  $x$ ,

$$x \in A \iff f(x) \in B$$

## Poly-time Mapping Reduction


Language  $A$  is poly-time mapping reducible to language  $B$  ( $A \leq_P B$ ) if there is a poly-time computable function  $f : \Sigma^* \rightarrow \Sigma^*$ , where for every  $x$ ,

$$x \in A \iff f(x) \in B$$

- Poly-time reductions give an efficient way to convert membership testing in  $A$  to membership testing in  $B$
- If  $B$  has a poly-time solution so does  $A$



# Poly-time Mapping Reductions



$f$  runs in time  $\text{poly}(|x|)$  on all inputs  $x$

# Why Poly-Time Reductions

## Theorem

If  $A \leq_P B$  and  $B \in \mathcal{P}$ , then  $A \in \mathcal{P}$

# Why Poly-Time Reductions

## Theorem

If  $A \leq_P B$  and  $B \in \mathcal{P}$ , then  $A \in \mathcal{P}$

Proof:

# Why Poly-Time Reductions

## Theorem

If  $A \leq_P B$  and  $B \in \mathcal{P}$ , then  $A \in \mathcal{P}$

Proof:

- Let  $M$  be the poly-time TM deciding  $B$

# Why Poly-Time Reductions

## Theorem

If  $A \leq_P B$  and  $B \in \mathcal{P}$ , then  $A \in \mathcal{P}$

Proof:

- Let  $M$  be the poly-time TM deciding  $B$
- Let  $f$  be the poly-time reduction from  $A$  to  $B$

# Why Poly-Time Reductions

## Theorem

If  $A \leq_P B$  and  $B \in \mathcal{P}$ , then  $A \in \mathcal{P}$

Proof:

- Let  $M$  be the poly-time TM deciding  $B$
- Let  $f$  be the poly-time reduction from  $A$  to  $B$
- Can construct  $M'$  deciding  $A$ :

# Why Poly-Time Reductions

## Theorem

If  $A \leq_P B$  and  $B \in \mathcal{P}$ , then  $A \in \mathcal{P}$

Proof:

- Let  $M$  be the poly-time TM deciding  $B$
- Let  $f$  be the poly-time reduction from  $A$  to  $B$

- Can construct  $M'$  deciding  $A$ :

$M'$  = On input  $x$ :

- 1 Compute  $f(x)$
- 2 Run  $M(f(x))$  and output whatever  $M$  outputs

if  $x \in A \Rightarrow f(x) \in B$

if  $x \notin A \Rightarrow f(x) \notin B$

# Why Poly-Time Reductions

## Theorem

If  $A \leq_P B$  and  $B \in \mathcal{P}$ , then  $A \in \mathcal{P}$

Proof:

- Let  $M$  be the poly-time TM deciding  $B$
- Let  $f$  be the poly-time reduction from  $A$  to  $B$
- Can construct  $M'$  deciding  $A$ :  
     $M'$  = On input  $x$ :
  - 1 Compute  $f(x)$
  - 2 Run  $M(f(x))$  and output whatever  $M$  outputs
    - If  $x \in A$ ,  $f(x) \in B$  so  $M$  accepts



# Why Poly-Time Reductions

## Theorem

If  $A \leq_P B$  and  $B \in \mathcal{P}$ , then  $A \in \mathcal{P}$

Proof:

- Let  $M$  be the poly-time TM deciding  $B$
- Let  $f$  be the poly-time reduction from  $A$  to  $B$
- Can construct  $M'$  deciding  $A$ :  
 $M'$  = On input  $x$ :
  - 1 Compute  $f(x)$
  - 2 Run  $M(f(x))$  and output whatever  $M$  outputs
  - If  $x \in A$ ,  $f(x) \in B$  so  $M$  accepts
  - If  $x \notin A$ ,  $f(x) \notin B$ , so  $M$  rejects

# Why Poly-Time Reductions

## Theorem

If  $A \leq_P B$  and  $B \in \mathcal{P}$ , then  $A \in \mathcal{P}$

Proof:

- Let  $M$  be the poly-time TM deciding  $B$
- Let  $f$  be the poly-time reduction from  $A$  to  $B$
- Can construct  $M'$  deciding  $A$ :  
 $M' =$  On input  $x$ :
  - 1 Compute  $f(x)$
  - 2 Run  $M(f(x))$  and output whatever  $M$  outputs
  - If  $x \in A$ ,  $f(x) \in B$  so  $M$  accepts
  - If  $x \notin A$ ,  $f(x) \notin B$ , so  $M$  rejects
  - Since both  $f$  and  $M$  are poly-time,  $M(f(x))$  is also poly-time

# Using Poly-Time Reductions to Prove Hardness

## Theorem

If  $A \leq_P B$  and  $A \notin \mathcal{P}$ , then  $B \notin \mathcal{P}$

Assume  $B \in \mathcal{P}$

# Outline

- 1 Lecture 20 Review
- 2 A Review of  $\mathcal{P}$  and  $\mathcal{NP}$
- 3 Polynomial-Time Reductions
- 4  $\mathcal{NP}$ -Completeness
- 5  $\mathcal{NP}$ -Completeness Using Reductions

## Definition

A language  $B$  is  $\mathcal{NP}$ -complete if

- $B \in \mathcal{NP}$
- For every language  $A \in \mathcal{NP}$ ,  $A \leq_P B$

## Definition

A language  $B$  is  $\mathcal{NP}$ -complete if

- $B \in \mathcal{NP}$
- For every language  $A \in \mathcal{NP}$ ,  $A \leq_P B$
- $B$  is “as hard” as any language in  $\mathcal{NP}$

## Definition

A language  $B$  is  $\mathcal{NP}$ -complete if

- $B \in \mathcal{NP}$
  - For every language  $A \in \mathcal{NP}$ ,  $A \leq_P B$
- 
- $B$  is “as hard” as any language in  $\mathcal{NP}$
  - To study hardness of  $\mathcal{NP}$ , enough to study hardness of some  $\mathcal{NP}$ -complete problem

# $\mathcal{NP}$ -Completeness

## Definition

A language  $B$  is  $\mathcal{NP}$ -complete if

- $B \in \mathcal{NP}$
  - For every language  $A \in \mathcal{NP}$ ,  $A \leq_P B$
- 
- $B$  is “as hard” as any language in  $\mathcal{NP}$
  - To study hardness of  $\mathcal{NP}$ , enough to study hardness of some  $\mathcal{NP}$ -complete problem

## Theorem

If  $B$  is  $\mathcal{NP}$ -complete and  $B \in \mathcal{P}$ , then  $\mathcal{P} = \mathcal{NP}$



# $\mathcal{NP}$ -Completeness

## Definition

A language  $B$  is  $\mathcal{NP}$ -complete if

- $B \in \mathcal{NP}$
  - For every language  $A \in \mathcal{NP}$ ,  $A \leq_P B$
- 
- $B$  is “as hard” as any language in  $\mathcal{NP}$
  - To study hardness of  $\mathcal{NP}$ , enough to study hardness of some  $\mathcal{NP}$ -complete problem

## Theorem

If  $B$  is  $\mathcal{NP}$ -complete and  $B \in \mathcal{P}$ , then  $\mathcal{P} = \mathcal{NP}$

## Theorem

If  $B$  is  $\mathcal{NP}$ -complete and  $B \leq_P C$  for  $C \in \mathcal{NP}$ , then  $C$  is  $\mathcal{NP}$ -complete

# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- 1  $SAT \in \mathcal{NP}$

# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- 1  $SAT \in \mathcal{NP}$
- 2 For each  $A \in \mathcal{NP}$ ,  $A \leq_P SAT$

# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ①  $SAT \in \mathcal{NP}$
- ② For each  $A \in \mathcal{NP}$ ,  $A \leq_P SAT$ 
  - Need to design reduction  $f$  from  $A$  to  $SAT$

# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ①  $SAT \in \mathcal{NP}$
- ② For each  $A \in \mathcal{NP}$ ,  $A \leq_P SAT$ 
  - Need to design reduction  $f$  from  $A$  to  $SAT$
  - $f$  takes an input  $x$  and produces formula  $\phi$

# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ①  $SAT \in \mathcal{NP}$
- ② For each  $A \in \mathcal{NP}$ ,  $A \leq_P SAT$ 
  - Need to design reduction  $f$  from  $A$  to  $SAT$
  - $f$  takes an input  $x$  and produces formula  $\phi$ 
    - If  $x \in A$  then  $\phi$  is satisfiable



# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ①  $SAT \in \mathcal{NP}$
- ② For each  $A \in \mathcal{NP}$ ,  $A \leq_P SAT$ 
  - Need to design reduction  $f$  from  $A$  to  $SAT$
  - $f$  takes an input  $x$  and produces formula  $\phi$ 
    - If  $x \in A$  then  $\phi$  is satisfiable
    - If  $x \notin A$  then  $\phi$  is not satisfiable

# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ①  $SAT \in \mathcal{NP}$
- ② For each  $A \in \mathcal{NP}$ ,  $A \leq_P SAT$ 
  - Need to design reduction  $f$  from  $A$  to  $SAT$
  - $f$  takes an input  $x$  and produces formula  $\phi$ 
    - If  $x \in A$  then  $\phi$  is satisfiable
    - If  $x \notin A$  then  $\phi$  is not satisfiable
  - Idea: Let  $\phi$  be a formula simulating  $\mathcal{NP}$  machine for  $A$  on input  $x$

# SAT is $\mathcal{NP}$ -Complete

## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ①  $SAT \in \mathcal{NP}$
- ② For each  $A \in \mathcal{NP}$ ,  $A \leq_P SAT$ 
  - Need to design reduction  $f$  from  $A$  to  $SAT$
  - $f$  takes an input  $x$  and produces formula  $\phi$ 
    - If  $x \in A$  then  $\phi$  is satisfiable
    - If  $x \notin A$  then  $\phi$  is not satisfiable
  - Idea: Let  $\phi$  be a formula simulating  $\mathcal{NP}$  machine for  $A$  on input  $x$ 
    - That is,  $\phi$  corresponds to the Boolean logic done by this machine

# SAT is $\mathcal{NP}$ -Complete


## SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ①  $SAT \in \mathcal{NP}$
- ② For each  $A \in \mathcal{NP}$ ,  $A \leq_P SAT$ 
  - Need to design reduction  $f$  from  $A$  to  $SAT$
  - $f$  takes an input  $x$  and produces formula  $\phi$ 
    - If  $x \in A$  then  $\phi$  is satisfiable
    - If  $x \notin A$  then  $\phi$  is not satisfiable
  - Idea: Let  $\phi$  be a formula simulating  $\mathcal{NP}$  machine for  $A$  on input  $x$ 
    - That is,  $\phi$  corresponds to the Boolean logic done by this machine
    - Since any computation can be represented as a Boolean computation, this is always possible

# Execution of Turing Machine $M$ deciding $A$



#	$q_0$	$x_1$	$x_2$	$\dots$	$x_n$	$\square$	$\dots$	$\square$	#
#									#
#									#
#									#

Table: Tableau of configurations of  $M$

# Execution of Turing Machine $M$ deciding $A$

#	$q_0$	$x_1$	$x_2$	$\dots$	$x_n$	$\sqcup$	$\dots$	$\sqcup$	#
#									#
#									#
#									#

Table: Tableau of configurations of  $M$

- Every row is a configuration of  $M$

# Execution of Turing Machine $M$ deciding $A$

#	$q_0$	$x_1$	$x_2$	$\dots$	$x_n$	$\sqcup$	$\dots$	$\sqcup$	#
#									#
#									#
#									#

Table: Tableau of configurations of  $M$

- Every row is a configuration of  $M$
- Two consecutive rows represent a valid transition if they follow rules of  $M$

# Execution of Turing Machine $M$ deciding $A$

#	$q_0$	$x_1$	$x_2$	$\dots$	$x_n$	$\sqcup$	$\dots$	$\sqcup$	#
#									#
#									#
#									#

Table: Tableau of configurations of  $M$

- Every row is a configuration of  $M$
- Two consecutive rows represent a valid transition if they follow rules of  $M$
- Every cell contains  $\#$ , or a state  $q \in Q$ , or a tape symbol  $\in \Gamma$



# Execution of Turing Machine $M$ deciding $A$

#	$q_0$	$x_1$	$x_2$	$\dots$	$x_n$	$\sqcup$	$\dots$	$\sqcup$	#
#									#
#									#
#									#

Table: Tableau of configurations of  $M$

- Every row is a configuration of  $M$
- Two consecutive rows represent a valid transition if they follow rules of  $M$
- Every cell contains #, or a state  $q \in Q$ , or a tape symbol  $\in \Gamma$
- $M$  accepts  $x$  if a row of this tableau is in  $q_{accept}$

# SAT is $\mathcal{NP}$ -Complete

Given input  $x$  that we want to check if  $x \in A$

We need to build a formula  $\phi$  that checks the following four things:

# SAT is $\mathcal{NP}$ -Complete

Given input  $x$  that we want to check if  $x \in A$

We need to build a formula  $\phi$  that checks the following four things:

- 1 Every cell contains a valid character in  $C = Q \cup \Gamma \cup \{\#\}$

# SAT is $\mathcal{NP}$ -Complete

Given input  $x$  that we want to check if  $x \in A$

We need to build a formula  $\phi$  that checks the following four things:

- 1 Every cell contains a valid character in  $C = Q \cup \Gamma \cup \{\#\}$
- 2 Top row is the start configuration (on input  $x$ )

# SAT is $\mathcal{NP}$ -Complete

Given input  $x$  that we want to check if  $x \in A$

We need to build a formula  $\phi$  that checks the following four things:

- 1 Every cell contains a valid character in  $C = Q \cup \Gamma \cup \{\#\}$
- 2 Top row is the start configuration (on input  $x$ )
- 3 Some row is in  $q_{accept}$

# SAT is $\mathcal{NP}$ -Complete

Given input  $x$  that we want to check if  $x \in A$

We need to build a formula  $\phi$  that checks the following four things:

- 1 Every cell contains a valid character in  $C = Q \cup \Gamma \cup \{\#\}$
- 2 Top row is the start configuration (on input  $x$ )
- 3 Some row is in  $q_{accept}$
- 4 Every pair of adjacent rows represents a valid transition of  $M$

# SAT is $\mathcal{NP}$ -Complete

- 1 Every cell contains a valid character in  $C = Q \cup \Gamma \cup \{\#\}$

# SAT is $\mathcal{NP}$ -Complete

- 1 Every cell contains a valid character in  $C = Q \cup \Gamma \cup \{\#\}$ 
  - For  $1 \leq i, j \leq n^k$ , and  $s \in C$ , let  $x_{i,j,s} = 1$  if  $cell[i,j] = s$



# SAT is $\mathcal{NP}$ -Complete

- 1 Every cell contains a valid character in  $C = Q \cup \Gamma \cup \{\#\}$ 
  - For  $1 \leq i, j \leq n^k$ , and  $s \in C$ , let  $x_{i,j,s} = 1$  if  $cell[i,j] = s$
  - The following equation  $\phi_{i,j}^{cell}$  guarantees that a cell has a valid value

$$\phi_{i,j}^{cell} = \underbrace{\left( \bigvee_{s \in C} x_{i,j,s} \right)}_{\text{cell } i,j \text{ has at least 1 value}} \wedge \underbrace{\left( \bigwedge_{s,t \in C, s \neq t} (\overline{x_{i,j,s}} \vee \overline{x_{i,j,t}}) \right)}_{\text{cell } i,j \text{ has at most 1 value}}$$

# SAT is $\mathcal{NP}$ -Complete

- 1 Every cell contains a valid character in  $C = Q \cup \Gamma \cup \{\#\}$ 
  - For  $1 \leq i, j \leq n^k$ , and  $s \in C$ , let  $x_{i,j,s} = 1$  if  $cell[i,j] = s$
  - The following equation  $\phi_{i,j}^{cell}$  guarantees that a cell has a valid value

$$\phi_{i,j}^{cell} = \underbrace{\left( \bigvee_{s \in C} x_{i,j,s} \right)}_{\text{cell } i,j \text{ has at least 1 value}} \wedge \underbrace{\left( \bigwedge_{s,t \in C, s \neq t} (\overline{x_{i,j,s}} \vee \overline{x_{i,j,t}}) \right)}_{\text{cell } i,j \text{ has at most 1 value}}$$

- Now, we just take the AND over all  $n^{2k}$  cells in the tableau

# SAT is $\mathcal{NP}$ -Complete

- 2 Top row is the start configuration

# SAT is $\mathcal{NP}$ -Complete

- 2 Top row is the start configuration
- Define a formula  $\phi_{start}$  that checks that all the cells in the top row are correct

$$\phi_{start} = x_{1,1,\#} \wedge x_{1,2,q_0} \cdots \wedge x_{1,n^k,\#}$$

# SAT is $\mathcal{NP}$ -Complete

- ③ Some row is in  $q_{accept}$

# SAT is $\mathcal{NP}$ -Complete

- 3 Some row is in  $q_{\text{accept}}$
- Define a formula  $\phi_{\text{accept}}$  that checks that some row contains  $q_{\text{accept}}$

$$\phi_{\text{accept}} = \bigvee_{1 \leq i, j \leq n^k} x_{i,j, \text{q}_{\text{accept}}}$$

# SAT is $\mathcal{NP}$ -Complete

- ④ Every pair of adjacent rows represents a valid transition of  $M$


# SAT is $\mathcal{NP}$ -Complete

- ④ Every pair of adjacent rows represents a valid transition of  $M$ 
  - We need to define what is a valid move between two configurations



# SAT is $\mathcal{NP}$ -Complete

- ④ Every pair of adjacent rows represents a valid transition of  $M$ 
  - We need to define what is a valid move between two configurations
  - If the control head is not next to some cell, that cell will not change



# SAT is $\mathcal{NP}$ -Complete

- ④ Every pair of adjacent rows represents a valid transition of  $M$ 
  - We need to define what is a valid move between two configurations
  - If the control head is not next to some cell, that cell will not change
  - For cells after control head, can write to the cell and move left or right (depending on  $M$ )

# SAT is $\mathcal{NP}$ -Complete

- ④ Every pair of adjacent rows represents a valid transition of  $M$ 
  - We need to define what is a valid move between two configurations
  - If the control head is not next to some cell, that cell will not change
  - For cells after control head, can write to the cell and move left or right (depending on  $M$ )
  - Every  $2 \times 3$  cell window can be checked to follow these rules

# SAT is $\mathcal{NP}$ -Complete

- ④ Every pair of adjacent rows represents a valid transition of  $M$ 
  - We need to define what is a valid move between two configurations
  - If the control head is not next to some cell, that cell will not change
  - For cells after control head, can write to the cell and move left or right (depending on  $M$ )
  - Every  $2 \times 3$  cell window can be checked to follow these rules
  - Now just take the  $\wedge$  over all possible 6-cell windows

# SAT is $\mathcal{NP}$ -Complete

- Finally, need to check that this reduction runs in poly time (in  $n = |x|$ )

# SAT is $\mathcal{NP}$ -Complete

- Finally, need to check that this reduction runs in poly time (in  $n = |x|$ )
- Recall that the tableau has size  $n^k \times n^k$ , so  $n^{2k}$  cells

# SAT is $\mathcal{NP}$ -Complete

- Finally, need to check that this reduction runs in poly time (in  $n = |x|$ )
- Recall that the tableau has size  $n^k \times n^k$ , so  $n^{2k}$  cells
- $\phi_{cell}$  has fixed size for each cell, so  $O(n^{2k})$  total

# SAT is $\mathcal{NP}$ -Complete

- Finally, need to check that this reduction runs in poly time (in  $n = |x|$ )
- Recall that the tableau has size  $n^k \times n^k$ , so  $n^{2k}$  cells
- $\phi_{cell}$  has fixed size for each cell, so  $O(n^{2k})$  total
- $\phi_{start}$  has fixed size for each cell in top row, so  $O(n^k)$  total



# SAT is $\mathcal{NP}$ -Complete

- Finally, need to check that this reduction runs in poly time (in  $n = |x|$ )
- Recall that the tableau has size  $n^k \times n^k$ , so  $n^{2k}$  cells
- $\phi_{cell}$  has fixed size for each cell, so  $O(n^{2k})$  total
- $\phi_{start}$  has fixed size for each cell in top row, so  $O(n^k)$  total
- $\phi_{move}$  and  $\phi_{accept}$  have fixed size for each cell, so  $O(n^{2k})$  total

# SAT is $\mathcal{NP}$ -Complete

- Finally, need to check that this reduction runs in poly time (in  $n = |x|$ )
- Recall that the tableau has size  $n^k \times n^k$ , so  $n^{2k}$  cells
- $\phi_{cell}$  has fixed size for each cell, so  $O(n^{2k})$  total
- $\phi_{start}$  has fixed size for each cell in top row, so  $O(n^k)$  total
- $\phi_{move}$  and  $\phi_{accept}$  have fixed size for each cell, so  $O(n^{2k})$  total
- Summing up, we see  $|\phi| = O(n^{2k})$

# SAT is $\mathcal{NP}$ -Complete

- Finally, need to check that this reduction runs in poly time (in  $n = |x|$ )
- Recall that the tableau has size  $n^k \times n^k$ , so  $n^{2k}$  cells
- $\phi_{cell}$  has fixed size for each cell, so  $O(n^{2k})$  total
- $\phi_{start}$  has fixed size for each cell in top row, so  $O(n^k)$  total
- $\phi_{move}$  and  $\phi_{accept}$  have fixed size for each cell, so  $O(n^{2k})$  total
- Summing up, we see  $|\phi| = O(n^{2k})$
- Since  $k = O(1)$ , this is polynomial in  $n$

# Outline

- 1 Lecture 20 Review
- 2 A Review of  $\mathcal{P}$  and  $\mathcal{NP}$
- 3 Polynomial-Time Reductions
- 4  $\mathcal{NP}$ -Completeness
- 5  $\mathcal{NP}$ -Completeness Using Reductions

1.  $L \in \mathcal{NP}$

2.  $\text{SAT} \leq_p L$

# $\mathcal{NP}$ -Completeness Using Reductions

To prove that some language  $L$  is  $\mathcal{NP}$ -Complete, we need to prove:

# $\mathcal{NP}$ -Completeness Using Reductions

To prove that some language  $L$  is  $\mathcal{NP}$ -Complete, we need to prove:

①  $L \in \mathcal{NP}$

# $\mathcal{NP}$ -Completeness Using Reductions

To prove that some language  $L$  is  $\mathcal{NP}$ -Complete, we need to prove:

- 1  $L \in \mathcal{NP}$
- 2  $L$  is no easier than an  $\mathcal{NP}$ -Complete problem

# $\mathcal{NP}$ -Completeness Using Reductions

To prove that some language  $L$  is  $\mathcal{NP}$ -Complete, we need to prove:

- 1  $L \in \mathcal{NP}$
- 2  $L$  is no easier than an  $\mathcal{NP}$ -Complete problem

$$SAT \leq_P L$$



# The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment

# The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

# The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

## 3-CNF formulas

- A literal is a (possibly negated) Boolean variable –  $x$  or  $\bar{x}$

# The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

## 3-CNF formulas

- A literal is a (possibly negated) Boolean variable –  $x$  or  $\bar{x}$
- A clause is several literals connected with  $\vee$ 's –  $x_1 \vee \bar{x}_2 \vee x_3$

# The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

## 3-CNF formulas

- A literal is a (possibly negated) Boolean variable –  $x$  or  $\bar{x}$
- A clause is several literals connected with  $\vee$ 's –  $x_1 \vee \bar{x}_2 \vee x_3$
- A Boolean formula is in conjunctive normal form (CNF) if it consists of clauses connected by  $\wedge$ 's

$$(x_1 \vee \bar{x}_2 \vee x_3 \vee x_4) \wedge (\bar{x}_3 \vee x_5)$$

# The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

## 3-CNF formulas

- A literal is a (possibly negated) Boolean variable –  $x$  or  $\bar{x}$
- A clause is several literals connected with  $\vee$ 's –  $x_1 \vee \bar{x}_2 \vee x_3$
- A Boolean formula is in conjunctive normal form (CNF) if it consists of clauses connected by  $\wedge$ 's

$$(x_1 \vee \bar{x}_2 \vee x_3 \vee x_4) \wedge (\bar{x}_3 \vee x_5)$$

- A Boolean formula is a 3-CNF if all the clauses have exactly 3 literals

$$(x_1 \vee \bar{x}_2 \vee x_3) \wedge (\bar{x}_3 \vee x_4 \vee x_5) \wedge (\bar{x}_1 \vee x_4 \vee x_2)$$

# The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

## 3-CNF formulas

- A literal is a (possibly negated) Boolean variable –  $x$  or  $\bar{x}$
- A clause is several literals connected with  $\vee$ 's –  $x_1 \vee \bar{x}_2 \vee x_3$
- A Boolean formula is in conjunctive normal form (CNF) if it consists of clauses connected by  $\wedge$ 's

$$(x_1 \vee \bar{x}_2 \vee x_3 \vee x_4) \wedge (\bar{x}_3 \vee x_5)$$

- A Boolean formula is a 3-CNF if all the clauses have exactly 3 literals

$$(x_1 \vee \bar{x}_2 \vee x_3) \wedge (\bar{x}_3 \vee x_4 \vee x_5) \wedge (\bar{x}_1 \vee x_4 \vee x_2)$$

## 3-SAT

$$3SAT = \{ \langle \phi \rangle \mid \phi \text{ is a satisfiable 3-CNF formula} \}$$

# The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

## 3-CNF formulas

- A literal is a (possibly negated) Boolean variable –  $x$  or  $\bar{x}$
- A clause is several literals connected with  $\vee$ 's –  $x_1 \vee \bar{x}_2 \vee x_3$
- A Boolean formula is in conjunctive normal form (CNF) if it consists of clauses connected by  $\wedge$ 's

$$(x_1 \vee \bar{x}_2 \vee x_3 \vee x_4) \wedge (\bar{x}_3 \vee x_5)$$

- A Boolean formula is a 3-CNF if all the clauses have exactly 3 literals

$$(x_1 \vee \bar{x}_2 \vee x_3) \wedge (\bar{x}_3 \vee x_4 \vee x_5) \wedge (\bar{x}_1 \vee x_4 \vee x_2)$$

## 3-SAT

$$3\text{SAT} = \{ \langle \phi \rangle \mid \phi \text{ is a satisfiable 3-CNF formula} \}$$

Can show that 3SAT is  $\mathcal{NP}$ -complete using similar proof to SAT



# Recall The Clique Problem

## Clique

A clique in an undirected graph is a subset of nodes s.t. every two nodes are connected by an edge. A  $k$ -clique is a clique containing  $k$  nodes

$$CLIQUE = \{ \langle G, k \rangle \mid G \text{ is an undirected graph with a } k\text{-clique} \}$$

## Goal:

Prove that CLIQUE is  $\mathcal{NP}$ -complete

# Recall The Clique Problem

## Clique

A clique in an undirected graph is a subset of nodes s.t. every two nodes are connected by an edge. A  $k$ -clique is a clique containing  $k$  nodes

$$CLIQUE = \{ \langle G, k \rangle \mid G \text{ is an undirected graph with a } k\text{-clique} \}$$

## Goal:

Prove that CLIQUE is  $\mathcal{NP}$ -complete

- 1 CLIQUE  $\in \mathcal{NP}$
- 2  $3SAT \leq_P CLIQUE$

# $3\text{SAT} \leq_P \text{CLIQUE}$

- Need to show reduction  $f$  from 3SAT formula  $\phi$  to  $\langle G, k \rangle$  where

# $3\text{SAT} \leq_P \text{CLIQUE}$

- Need to show reduction  $f$  from 3SAT formula  $\phi$  to  $\langle G, k \rangle$  where
  - If  $\phi$  is satisfiable,  $G$  has a clique of size  $k$

# $3\text{SAT} \leq_P \text{CLIQUE}$


- Need to show reduction  $f$  from 3SAT formula  $\phi$  to  $\langle G, k \rangle$  where
  - If  $\phi$  is satisfiable,  $G$  has a clique of size  $k$
  - If  $\phi$  is not satisfiable,  $G$  has no clique of size  $k$

# $3\text{SAT} \leq_P \text{CLIQUE}$

- Need to show reduction  $f$  from 3SAT formula  $\phi$  to  $\langle G, k \rangle$  where
  - If  $\phi$  is satisfiable,  $G$  has a clique of size  $k$
  - If  $\phi$  is not satisfiable,  $G$  has no clique of size  $k$
- Consider  $\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2)$


# $3SAT \leq_P CLIQUE$

- Need to show reduction  $f$  from 3SAT formula  $\phi$  to  $\langle G, k \rangle$  where
  - If  $\phi$  is satisfiable,  $G$  has a clique of size  $k$
  - If  $\phi$  is not satisfiable,  $G$  has no clique of size  $k$
- Consider  $\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2)$



# 3SAT $\leq_P$ CLIQUE

- Need to show reduction  $f$  from 3SAT formula  $\phi$  to  $\langle G, k \rangle$  where
  - If  $\phi$  is satisfiable,  $G$  has a clique of size  $k$
  - If  $\phi$  is not satisfiable,  $G$  has no clique of size  $k$
- Consider  $\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2)$




- If  $\phi$  is satisfiable then  $G$  has a  $k$ -clique



# $3SAT \leq_P CLIQUE$

- Need to show reduction  $f$  from 3SAT formula  $\phi$  to  $\langle G, k \rangle$  where
  - If  $\phi$  is satisfiable,  $G$  has a clique of size  $k$
  - If  $\phi$  is not satisfiable,  $G$  has no clique of size  $k$
- Consider  $\phi = (x_1 \vee \bar{x}_1 \vee x_2) \wedge (\bar{x}_1 \vee \bar{x}_2 \vee \bar{x}_2) \wedge (\bar{x}_1 \vee x_2 \vee x_2)$



- If  $\phi$  is satisfiable then  $G$  has a  $k$ -clique
- If  $G$  has a  $k$ -clique then  $\phi$  is satisfiable