

# Foundations of Computing

## Lecture 16

Arkady Yerukhimovich

March 21, 2023

- 1 Lecture 15 Review
- 2 An Undecidable Language
- 3 Reducibility
- 4 Where Are We Now?

# Lecture 15 Review

- Languages about Machines
- Countable and Uncountable Sets
  - Diagonalization
- Proving  $L_{TM}$  is Undecidable

# Outline

- 1 Lecture 15 Review
- 2 An Undecidable Language**
- 3 Reducibility
- 4 Where Are We Now?

# $L_{TM}$ is Turing-recognizable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

# $L_{TM}$ is Turing-recognizable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine  $M_{L_{TM}}$

$M_{L_{TM}}$ : On input  $\langle M, w \rangle$ ,

- 1 Run  $M$  on input  $w$

# $L_{TM}$ is Turing-recognizable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine  $M_{L_{TM}}$

$M_{L_{TM}}$ : On input  $\langle M, w \rangle$ ,

- 1 Run  $M$  on input  $w$
- 2 If  $M$  halts, halt and output what  $M$  outputs

# $L_{TM}$ is Turing-recognizable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine  $M_{L_{TM}}$

$M_{L_{TM}}$ : On input  $\langle M, w \rangle$ ,

- ① Run  $M$  on input  $w$
- ② If  $M$  halts, halt and output what  $M$  outputs

Correctness:

- For any input  $\langle M, w \rangle \in L_{TM}$ ,  $M$  is a TM, and  $M(w)$  halts and outputs 1.



# $L_{TM}$ is Turing-recognizable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine  $M_{L_{TM}}$

$M_{L_{TM}}$ : On input  $\langle M, w \rangle$ ,

- ① Run  $M$  on input  $w$
- ② If  $M$  halts, halt and output what  $M$  outputs

Correctness:

- For any input  $\langle M, w \rangle \in L_{TM}$ ,  $M$  is a TM, and  $M(w)$  halts and outputs 1.
- Hence,  $M_{L_{TM}}$ , also halts and outputs 1

# $L_{TM}$ is Turing-recognizable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine  $M_{L_{TM}}$

$M_{L_{TM}}$ : On input  $\langle M, w \rangle$ ,

- ① Run  $M$  on input  $w$
- ② If  $M$  halts, halt and output what  $M$  outputs

Correctness:

- For any input  $\langle M, w \rangle \in L_{TM}$ ,  $M$  is a TM, and  $M(w)$  halts and outputs 1.
- Hence,  $M_{L_{TM}}$ , also halts and outputs 1
- Thus,  $M_{L_{TM}}$  accepts all inputs in  $L_{TM}$

# $L_{TM}$ is Turing-recognizable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By construction of machine  $M_{L_{TM}}$

$M_{L_{TM}}$ : On input  $\langle M, w \rangle$ ,

- ① Run  $M$  on input  $w$
- ② If  $M$  halts, halt and output what  $M$  outputs

Correctness:

- For any input  $\langle M, w \rangle \in L_{TM}$ ,  $M$  is a TM, and  $M(w)$  halts and outputs 1.
- Hence,  $M_{L_{TM}}$ , also halts and outputs 1
- Thus,  $M_{L_{TM}}$  accepts all inputs in  $L_{TM}$
- Note that  $M_{L_{TM}}$  may not halt on all inputs – doesn't decide  $L_{TM}$

# $L_{TM}$ is Undecidable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

# $L_{TM}$ is Undecidable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

# $L_{TM}$ is Undecidable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that  $L_{TM}$  is decided by TM  $H$

$$H(\langle M, w \rangle) = \begin{cases} \textit{accept} & \text{if } M \text{ accepts } w \\ \textit{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

# $L_{TM}$ is Undecidable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that  $L_{TM}$  is decided by TM  $H$

$$H(\langle M, w \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ accepts } w \\ \text{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

- Use  $H$  to build a TM  $D$  that checks whether a TM  $M$  accepts its own description, and then does the opposite:

# $L_{TM}$ is Undecidable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that  $L_{TM}$  is decided by TM  $H$

$$H(\langle M, w \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ accepts } w \\ \text{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

- Use  $H$  to build a TM  $D$  that checks whether a TM  $M$  accepts its own description, and then does the opposite:

**D:** On Input  $\langle M \rangle$ , where  $M$  is a TM

- Run  $H$  on input  $\langle M, \langle M \rangle \rangle$
- Output the opposite of what  $H$  outputs



# $L_{TM}$ is Undecidable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that  $L_{TM}$  is decided by TM  $H$

$$H(\langle M, w \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ accepts } w \\ \text{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

- Use  $H$  to build a TM  $D$  that checks whether a TM  $M$  accepts its own description, and then does the opposite:

On Input  $\langle M \rangle$ , where  $M$  is a TM

- Run  $H$  on input  $\langle M, \langle M \rangle \rangle$
- Output the opposite of what  $H$  outputs

$$D(\langle M \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ does not accept } \langle M \rangle \\ \text{reject} & \text{if } M \text{ accepts } \langle M \rangle \end{cases}$$

# $L_{TM}$ is Undecidable

$$L_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) = 1\}$$

Proof: By contradiction

- Assume that  $L_{TM}$  is decided by TM  $H$

$$H(\langle M, w \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ accepts } w \\ \text{reject} & \text{if } M \text{ does not accept } w \end{cases}$$

- Use  $H$  to build a TM  $D$  that checks whether a TM  $M$  accepts its own description, and then does the opposite:

- On Input  $\langle M \rangle$ , where  $M$  is a TM
  - Run  $H$  on input  $\langle M, \langle M \rangle \rangle$
  - Output the opposite of what  $H$  outputs

$$D(\langle M \rangle) = \begin{cases} \text{accept} & \text{if } M \text{ does not accept } \langle M \rangle \\ \text{reject} & \text{if } M \text{ accepts } \langle M \rangle \end{cases}$$

- Now consider what happens if we run  $D$  on  $\langle D \rangle$

$$D(\langle D \rangle) = \begin{cases} \text{accept} & \text{if } D \text{ does not accept } \langle D \rangle \\ \text{reject} & \text{if } D \text{ accepts } \langle D \rangle \end{cases}$$

# How Is This a Diagonalization?

	$\langle M_1 \rangle$	$\langle M_2 \rangle$	$\langle M_3 \rangle$	$\dots$	$\langle D \rangle$	$\dots$
$M_1$	<u>accept</u>	reject	accept		accept	
$M_2$	reject	<u>reject</u>	reject	$\dots$	accept	$\dots$
$M_3$	accept	accept	<u>accept</u>		reject	
$\vdots$		$\vdots$		$\ddots$		
$D$	reject	accept	reject		<u>?</u>	

- We have defined  $D$  to do the opposite of what  $M_i$  does on input  $\langle M_i \rangle$
- But what does  $D$  do on input  $\langle D \rangle$ ??

# A Turing-unrecognizable Language

$\overline{L_{TM}}$

The language

$$\overline{L_{TM}} = \{\langle M, w \rangle \mid M \text{ is a TM and } M(w) \neq 1\}$$

is not Turing-recognizable

# Outline

- 1 Lecture 15 Review
- 2 An Undecidable Language
- 3 Reducibility**
- 4 Where Are We Now?

# Another Way to Prove Undecidability

## Reductions Between Problems

# Another Way to Prove Undecidability

## Reductions Between Problems

There is a reduction from a problem  $A$  to a problem  $B$  if we can use a solution to problem  $B$  to solve problem  $A$

$$A \leq B$$

# Another Way to Prove Undecidability

## Reductions Between Problems

There is a reduction from a problem  $A$  to a problem  $B$  if we can use a solution to problem  $B$  to solve problem  $A$

$$A \leq B$$

Examples:

- 1 Finding area of a rectangle  $\leq$  Finding its length and width



# Another Way to Prove Undecidability

## Reductions Between Problems

There is a reduction from a problem  $A$  to a problem  $B$  if we can use a solution to problem  $B$  to solve problem  $A$

$$A \leq B$$

Examples:

- 1 Finding area of a rectangle  $\leq$  Finding its length and width
- 2 Finding temperature outside  $\leq$  Reading a thermometer

# Another Way to Prove Undecidability

## Reductions Between Problems

There is a reduction from a problem  $A$  to a problem  $B$  if we can use a solution to problem  $B$  to solve problem  $A$

$$A \leq B$$

Examples:

- ① Finding area of a rectangle  $\leq$  Finding its length and width
- ② Finding temperature outside  $\leq$  Reading a thermometer

Observations:

# Another Way to Prove Undecidability

## Reductions Between Problems

There is a reduction from a problem  $A$  to a problem  $B$  if we can use a solution to problem  $B$  to solve problem  $A$

$$A \leq B$$

Examples:

- ① Finding area of a rectangle  $\leq$  Finding its length and width
- ② Finding temperature outside  $\leq$  Reading a thermometer

Observations:

- Reductions not always symmetrical:  $A \leq B$  does not mean  $B \leq A$

# Another Way to Prove Undecidability

## Reductions Between Problems

There is a reduction from a problem  $A$  to a problem  $B$  if we can use a solution to problem  $B$  to solve problem  $A$

$$A \leq B$$

Examples:

- ① Finding area of a rectangle  $\leq$  Finding its length and width
- ② Finding temperature outside  $\leq$  Reading a thermometer

Observations:

- Reductions not always symmetrical:  $A \leq B$  does not mean  $B \leq A$
- For now, no restriction on how the reduction works

# Another Way to Prove Undecidability

## Reductions Between Problems

There is a reduction from a problem  $A$  to a problem  $B$  if we can use a solution to problem  $B$  to solve problem  $A$

$$A \leq B$$

Examples:

- ① Finding area of a rectangle  $\leq$  Finding its length and width
- ② Finding temperature outside  $\leq$  Reading a thermometer

Observations:

- Reductions not always symmetrical:  $A \leq B$  does not mean  $B \leq A$
- For now, no restriction on how the reduction works

## Intuition

$A \leq B$  means that:

# Another Way to Prove Undecidability

## Reductions Between Problems

There is a reduction from a problem  $A$  to a problem  $B$  if we can use a solution to problem  $B$  to solve problem  $A$

$$A \leq B$$

Examples:

- ① Finding area of a rectangle  $\leq$  Finding its length and width
- ② Finding temperature outside  $\leq$  Reading a thermometer

Observations:

- Reductions not always symmetrical:  $A \leq B$  does not mean  $B \leq A$
- For now, no restriction on how the reduction works

## Intuition

$A \leq B$  means that:

- problem  $A$  is no harder than problem  $B$ .

# Another Way to Prove Undecidability

## Reductions Between Problems

There is a reduction from a problem  $A$  to a problem  $B$  if we can use a solution to problem  $B$  to solve problem  $A$

$$A \leq B$$

Examples:

- ① Finding area of a rectangle  $\leq$  Finding its length and width
- ② Finding temperature outside  $\leq$  Reading a thermometer

Observations:

- Reductions not always symmetrical:  $A \leq B$  does not mean  $B \leq A$
- For now, no restriction on how the reduction works

## Intuition

$A \leq B$  means that:

- problem  $A$  is no harder than problem  $B$ .
- Equivalently, problem  $B$  is no easier than problem  $A$

## Main Observation

Suppose that  $A \leq B$ , then:



## Main Observation

Suppose that  $A \leq B$ , then:

- If  $A$  is undecidable
- $B$  must also be undecidable

## Main Observation

Suppose that  $A \leq B$ , then:

- If  $A$  is undecidable
- $B$  must also be undecidable

Proof: (by contradiction)

## Main Observation

Suppose that  $A \leq B$ , then:

- If  $A$  is undecidable
- $B$  must also be undecidable

Proof: (by contradiction)

- Suppose that  $B$  is decidable

## Main Observation

Suppose that  $A \leq B$ , then:

- If  $A$  is undecidable
- $B$  must also be undecidable

Proof: (by contradiction)

- Suppose that  $B$  is decidable
- Since  $A \leq B$ , there exists an algorithm (i.e., a reduction) that uses a solution to  $B$  to solve  $A$

## Main Observation

Suppose that  $A \leq B$ , then:

- If  $A$  is undecidable
- $B$  must also be undecidable

Proof: (by contradiction)

- Suppose that  $B$  is decidable
- Since  $A \leq B$ , there exists an algorithm (i.e., a reduction) that uses a solution to  $B$  to solve  $A$
- But, this means that  $A$  is decidable by running the machine for  $B$  as needed by the reduction

# Undecidability of HALT

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

# Undecidability of HALT

$$HALT_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w\}$$

Theorem: *HALT* is undecidable

# Undecidability of HALT

$$HALT_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w\}$$

Theorem: *HALT* is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq HALT$



# Undecidability of HALT

$$HALT_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w\}$$

Theorem:  $HALT$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq HALT$
- Since we know that  $L_{TM}$  is undecidable, this shows that  $HALT$  is also undecidable

# Undecidability of HALT

$$HALT_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w\}$$

Theorem: *HALT* is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq HALT$
- Since we know that  $L_{TM}$  is undecidable, this shows that *HALT* is also undecidable

Proof:

Construct algorithm *S* that decides  $L_{TM}$  given a TM *R* that decides *HALT*

# Undecidability of HALT

$$HALT_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w\}$$

Theorem:  $HALT$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq HALT$
- Since we know that  $L_{TM}$  is undecidable, this shows that  $HALT$  is also undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $HALT$

On input  $\langle M, w \rangle$ ,  $S$  does the following:

# Undecidability of HALT

$$HALT_{TM} = \{\langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w\}$$

Theorem:  $HALT$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq HALT$
- Since we know that  $L_{TM}$  is undecidable, this shows that  $HALT$  is also undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $HALT$

On input  $\langle M, w \rangle$ ,  $S$  does the following:

- Run  $R(\langle M, w \rangle)$

# Undecidability of HALT

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Theorem:  $HALT$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq HALT$
- Since we know that  $L_{TM}$  is undecidable, this shows that  $HALT$  is also undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $HALT$

On input  $\langle M, w \rangle$ ,  $S$  does the following:

- Run  $R(\langle M, w \rangle)$
- If  $R$  rejects –  $M(w)$  doesn't halt – halt and reject

# Undecidability of HALT

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Theorem: *HALT* is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq HALT$
- Since we know that  $L_{TM}$  is undecidable, this shows that *HALT* is also undecidable

Proof:

Construct algorithm *S* that decides  $L_{TM}$  given a TM *R* that decides *HALT*

On input  $\langle M, w \rangle$ , *S* does the following:

- Run  $R(\langle M, w \rangle)$
- If *R* rejects –  $M(w)$  doesn't halt – halt and reject
- if *R* accepts –  $M(w)$  halts – Simulate  $M(w)$  until it halts

# Undecidability of $HALT$

$$HALT_{TM} = \{ \langle M, w \rangle \mid M \text{ is a TM and } M \text{ halts on input } w \}$$

Theorem:  $HALT$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq HALT$
- Since we know that  $L_{TM}$  is undecidable, this shows that  $HALT$  is also undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $HALT$

On input  $\langle M, w \rangle$ ,  $S$  does the following:

- Run  $R(\langle M, w \rangle)$
- If  $R$  rejects –  $M(w)$  doesn't halt – halt and reject
- if  $R$  accepts –  $M(w)$  halts – Simulate  $M(w)$  until it halts
- Output whatever  $M$  output

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$



# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq REGULAR_{TM}$

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq REGULAR_{TM}$
- Specifically, reduction builds a TM  $M_2$  s.t.

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq REGULAR_{TM}$
- Specifically, reduction builds a TM  $M_2$  s.t.
  - If  $M$  accepts  $w$ ,  $M_2$  recognizes  $\Sigma^*$  – regular language

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq REGULAR_{TM}$
- Specifically, reduction builds a TM  $M_2$  s.t.
  - If  $M$  accepts  $w$ ,  $M_2$  recognizes  $\Sigma^*$  – regular language
  - If  $M$  does not accept  $w$ ,  $M_2$  recognizes  $\{0^n 1^n\}$  – not regular

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof Sketch:

- We show that  $L_{TM} \leq REGULAR_{TM}$
- Specifically, reduction builds a TM  $M_2$  s.t.
  - If  $M$  accepts  $w$ ,  $M_2$  recognizes  $\Sigma^*$  – regular language
  - If  $M$  does not accept  $w$ ,  $M_2$  recognizes  $\{0^n 1^n\}$  – not regular
- If we can decide whether  $M_2$  recognizes a regular language or not, can use that to decide whether  $M$  accepts  $w$  or not

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof:

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $REGULAR_{TM}$



# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $REGULAR_{TM}$

On input  $\langle M, w \rangle$ :

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $REGULAR_{TM}$

On input  $\langle M, w \rangle$ :

- 1 Construct TM  $M_2$  s.t. on input  $x$

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $REGULAR_{TM}$

On input  $\langle M, w \rangle$ :

- 1 Construct TM  $M_2$  s.t. on input  $x$ 
  - 1 If  $x = 0^n 1^n$ , accept

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $REGULAR_{TM}$

On input  $\langle M, w \rangle$ :

- 1 Construct TM  $M_2$  s.t. on input  $x$ 
  - 1 If  $x = 0^n 1^n$ , accept
  - 2 If  $x$  does not have this form, run  $M(w)$  and accept if it accepts

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $REGULAR_{TM}$

On input  $\langle M, w \rangle$ :

- 1 Construct TM  $M_2$  s.t. on input  $x$ 
  - 1 If  $x = 0^n 1^n$ , accept
  - 2 If  $x$  does not have this form, run  $M(w)$  and accept if it accepts
- 2 Run  $R$  on input  $\langle M_2 \rangle$

# Other Undecidable Languages

$$REGULAR_{TM} = \{\langle M \rangle \mid M \text{ is a TM and } L(M) \text{ is a regular language}\}$$

Theorem:  $REGULAR_{TM}$  is undecidable

Proof:

Construct algorithm  $S$  that decides  $L_{TM}$  given a TM  $R$  that decides  $REGULAR_{TM}$

On input  $\langle M, w \rangle$ :

- 1 Construct TM  $M_2$  s.t. on input  $x$ 
  - 1 If  $x = 0^n 1^n$ , accept
  - 2 If  $x$  does not have this form, run  $M(w)$  and accept if it accepts
- 2 Run  $R$  on input  $\langle M_2 \rangle$
- 3 Output what  $R$  outputs

# Other Undecidable Languages

$$\text{EMPTY-STRING}_{\text{TM}} = \{\langle M \rangle \mid M \text{ is a TM and } M(\epsilon) = 1\}$$

Assume  $R$  that decides

$$L_{\text{TM}} \leq \text{EMPTY-STRING}_{\text{TM}}$$

$$L_{\text{TM}} = \langle M, u \rangle \text{ accept if } M(u) = 1$$

S, Given  $\langle M, u \rangle$

$M_u(\epsilon)$ : write  $u$  onto its tape

Run  $M(u)$  accept. if it accepts

$$\text{Run } R(\langle M_u \rangle)$$