

Cryptography

Lecture 11

Arkady Yerukhimovich

October 2, 2024

- 1 Lecture 10 Review
- 2 Secrecy vs. Integrity (Chapter 3.7)
- 3 Message Authentication Code (MAC) (Chapters 4.1, 4.2, 4.3.1)

Lecture 10 Review

- CCA Security
- PRF+OTP is not CCA secure
- Padding oracle attack on CBC mode

- 1 Lecture 10 Review
- 2 Secrecy vs. Integrity (Chapter 3.7)
- 3 Message Authentication Code (MAC) (Chapters 4.1, 4.2, 4.3.1)

Why CPA security is not enough

- We have seen two attacks against CPA-secure schemes:
 - ① Attack against PRF+OTP
 - ② Padding oracle attack against CBC-mode encryption

Why CPA security is not enough

- We have seen two attacks against CPA-secure schemes:
 - ① Attack against PRF+OTP
 - ② Padding oracle attack against CBC-mode encryption
- In both these attacks, \mathcal{A} modifies received ciphertext to something whose decryption reveals information about original message

Why CPA security is not enough

- We have seen two attacks against CPA-secure schemes:
 - ① Attack against PRF+OTP
 - ② Padding oracle attack against CBC-mode encryption
- In both these attacks, \mathcal{A} modifies received ciphertext to something whose decryption reveals information about original message
- This is called *malleability*

Why CPA security is not enough

- We have seen two attacks against CPA-secure schemes:
 - ① Attack against PRF+OTP
 - ② Padding oracle attack against CBC-mode encryption
- In both these attacks, \mathcal{A} modifies received ciphertext to something whose decryption reveals information about original message
- This is called *malleability*
- Need to ensure only validly encrypted ciphertexts can be decrypted

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality
- Often confidentiality is not enough

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality
- Often confidentiality is not enough
 - Possible to change content of encrypted messages

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality
- Often confidentiality is not enough
 - Possible to change content of encrypted messages
 - Often want to know who sent the message

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality
- Often confidentiality is not enough
 - Possible to change content of encrypted messages
 - Often want to know who sent the message
- Need to guarantee *integrity* of messages

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality
- Often confidentiality is not enough
 - Possible to change content of encrypted messages
 - Often want to know who sent the message
- Need to guarantee *integrity* of messages

Example:

- Consider a transaction sent from a client to a bank

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality
- Often confidentiality is not enough
 - Possible to change content of encrypted messages
 - Often want to know who sent the message
- Need to guarantee *integrity* of messages

Example:

- Consider a transaction sent from a client to a bank
- The bank needs to be sure that:
 - 1 The transaction was sent by the user holding the account

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality
- Often confidentiality is not enough
 - Possible to change content of encrypted messages
 - Often want to know who sent the message
- Need to guarantee *integrity* of messages

Example:

- Consider a transaction sent from a client to a bank
- The bank needs to be sure that:
 - 1 The transaction was sent by the user holding the account
 - 2 The amounts in the transaction were not modified in transit

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality
- Often confidentiality is not enough
 - Possible to change content of encrypted messages
 - Often want to know who sent the message
- Need to guarantee *integrity* of messages

Example:

- Consider a transaction sent from a client to a bank
- The bank needs to be sure that:
 - 1 The transaction was sent by the user holding the account
 - 2 The amounts in the transaction were not modified in transit
- Integrity guarantees are needed even if transaction is public

Secrecy vs. Integrity

- Encryption hides content of message – confidentiality
- Often confidentiality is not enough
 - Possible to change content of encrypted messages
 - Often want to know who sent the message
- Need to guarantee *integrity* of messages

Example:

- Consider a transaction sent from a client to a bank
- The bank needs to be sure that:
 - 1 The transaction was sent by the user holding the account
 - 2 The amounts in the transaction were not modified in transit
- Integrity guarantees are needed even if transaction is public

We Need Integrity

Confidentiality alone is insufficient to secure information

- 1 Lecture 10 Review
- 2 Secrecy vs. Integrity (Chapter 3.7)
- 3 Message Authentication Code (MAC) (Chapters 4.1, 4.2, 4.3.1)

Our Goal

Ensure that \mathcal{A} cannot modify or create new (valid) messages without being detected.

Our Goal

Ensure that \mathcal{A} cannot modify or create new (valid) messages without being detected.

- This should hold even if \mathcal{A} sees many valid messages beforehand

Our Goal

Ensure that \mathcal{A} cannot modify or create new (valid) messages without being detected.

- This should hold even if \mathcal{A} sees many valid messages beforehand
- Cannot modify or recombine messages to produce a new one

Our Goal

Ensure that \mathcal{A} cannot modify or create new (valid) messages without being detected.

- This should hold even if \mathcal{A} sees many valid messages beforehand
- Cannot modify or recombine messages to produce a new one
- Need an “integrity tag” that can be used to check authenticity

MAC Functionality

A Message Authentication Scheme (MAC) consists of:

- $\text{Gen}(1^n)$: Outputs key k with $|k| \geq n$ (usually $k \leftarrow \{0, 1\}^n$)
- $\text{Mac}_k(m)$: Outputs a tag $t \leftarrow \text{Mac}_k(m)$
- $\text{Verify}_k(m, t)$: Outputs 1 if t is a valid tag for m , and 0 otherwise

MAC Functionality

A Message Authentication Scheme (MAC) consists of:

- $\text{Gen}(1^n)$: Outputs key k with $|k| \geq n$ (usually $k \leftarrow \{0, 1\}^n$)
- $\text{Mac}_k(m)$: Outputs a tag $t \leftarrow \text{Mac}_k(m)$
- $\text{Verify}_k(m, t)$: Outputs 1 if t is a valid tag for m , and 0 otherwise

Correctness

For all k output by Gen and all messages m , $\text{Verify}_k(m, \text{Mac}_k(m)) = 1$

MAC Functionality

A Message Authentication Scheme (MAC) consists of:

- $\text{Gen}(1^n)$: Outputs key k with $|k| \geq n$ (usually $k \leftarrow \{0, 1\}^n$)
- $\text{Mac}_k(m)$: Outputs a tag $t \leftarrow \text{Mac}_k(m)$
- $\text{Verify}_k(m, t)$: Outputs 1 if t is a valid tag for m , and 0 otherwise

Correctness

For all k output by Gen and all messages m , $\text{Verify}_k(m, \text{Mac}_k(m)) = 1$

Canonical Verify

If Mac is deterministic, Verify can compute $\text{Mac}_k(m)$, check equality to t .

MAC Unforgeability

Let $\Pi = (\text{Gen}, \text{Mac}, \text{Verify})$ be a MAC. Consider the following game between an adversary \mathcal{A} and a challenger:

MAC Unforgeability

Let $\Pi = (\text{Gen}, \text{Mac}, \text{Verify})$ be a MAC. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{MacForge}_{\mathcal{A}, \Pi}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$, and gives \mathcal{A} an oracle $\text{Mac}_k(\cdot)$

MAC Unforgeability

Let $\Pi = (\text{Gen}, \text{Mac}, \text{Verify})$ be a MAC. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{MacForge}_{\mathcal{A}, \Pi}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$, and gives \mathcal{A} an oracle $\text{Mac}_k(\cdot)$
- $\mathcal{A}^{\text{Mac}_k(\cdot)}(1^n)$ outputs (m, t) (let Q be set of Mac queries made by \mathcal{A})

MAC Unforgeability

Let $\Pi = (\text{Gen}, \text{Mac}, \text{Verify})$ be a MAC. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{MacForge}_{\mathcal{A}, \Pi}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$, and gives \mathcal{A} an oracle $\text{Mac}_k(\cdot)$
- $\mathcal{A}^{\text{Mac}_k(\cdot)}(1^n)$ outputs (m, t) (let Q be set of Mac queries made by \mathcal{A})
- We say that $\text{MacForge}_{\mathcal{A}, \Pi}(n) = 1$ (i.e., \mathcal{A} wins) if
 - $\text{Verify}_k(m, t) = 1$
 - $m \notin Q$

MAC Unforgeability

Let $\Pi = (\text{Gen}, \text{Mac}, \text{Verify})$ be a MAC. Consider the following game between an adversary \mathcal{A} and a challenger:

MacForge $_{\mathcal{A}, \Pi}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$, and gives \mathcal{A} an oracle $\text{Mac}_k(\cdot)$
- $\mathcal{A}^{\text{Mac}_k(\cdot)}(1^n)$ outputs (m, t) (let Q be set of Mac queries made by \mathcal{A})
- We say that $\text{MacForge}_{\mathcal{A}, \Pi}(n) = 1$ (i.e., \mathcal{A} wins) if
 - $\text{Verify}_k(m, t) = 1$
 - $m \notin Q$ (m, t) $\notin Q$

Definition: A MAC $\Pi = (\text{Gen}, \text{Mac}, \text{Verify})$ is *unforgeable* if for all PPT \mathcal{A} it holds that

$$\Pr[\text{MacForge}_{\mathcal{A}, \Pi}(n) = 1] \leq \text{negl}(n)$$

Observations and Variants

- \mathcal{A} can query for a mac on any message of its choice

Observations and Variants

- \mathcal{A} can query for a mac on any message of its choice
- \mathcal{A} WINS if he outputs valid tag on any message *he hasn't queried*

Observations and Variants

- \mathcal{A} can query for a mac on any message of its choice
- \mathcal{A} WINS if he outputs valid tag on any message *he hasn't queried*
- This does not prevent replay attacks, generating new tag t' for message m for which \mathcal{A} has a tag t is not a forgery

Observations and Variants

- \mathcal{A} can query for a mac on any message of its choice
- \mathcal{A} WINS if he outputs valid tag on any message *he hasn't queried*
- This does not prevent replay attacks, generating new tag t' for message m for which \mathcal{A} has a tag t is not a forgery

Strong MAC

Same definition as before, except Q contains (m, t) pairs and \mathcal{A} wins if $(m, t) \notin Q$.

- Now \mathcal{A} WINS if he produces a new tag even for m for which he already has a tag

Observations and Variants

- \mathcal{A} can query for a mac on any message of its choice
- \mathcal{A} WINS if he outputs valid tag on any message *he hasn't queried*
- This does not prevent replay attacks, generating new tag t' for message m for which \mathcal{A} has a tag t is not a forgery

Strong MAC

Same definition as before, except Q contains (m, t) pairs and \mathcal{A} wins if $(m, t) \notin Q$.

- Now \mathcal{A} WINS if he produces a new tag even for m for which he already has a tag
- Observation: Let Π be a secure MAC that uses *canonical verify*, then Π is a strong MAC.

Unforgeable MAC from a PRF

PRF-based MAC (Fixed Length MAC)

- $\text{Gen}(1^n): k \leftarrow \{0, 1\}^n$

Unforgeable MAC from a PRF

PRF-based MAC (Fixed Length MAC)

- $\text{Gen}(1^n)$: $k \leftarrow \{0, 1\}^n$
- $\text{Mac}_k(m)$: Given $m \in \{0, 1\}^n$, compute $t = F_k(m)$

Unforgeable MAC from a PRF

PRF-based MAC (Fixed Length MAC)

- $\text{Gen}(1^n)$: $k \leftarrow \{0, 1\}^n$
- $\text{Mac}_k(m)$: Given $m \in \{0, 1\}^n$, compute $t = F_k(m)$
- $\text{Verify}_k(m, t)$: Compute $t' = F_k(m)$ output 1 iff $t = t'$

Unforgeable MAC from a PRF

PRF-based MAC (Fixed Length MAC)

- $\text{Gen}(1^n)$: $k \leftarrow \{0, 1\}^n$
- $\text{Mac}_k(m)$: Given $m \in \{0, 1\}^n$, compute $t = F_k(m)$
- $\text{Verify}_k(m, t)$: Compute $t' = F_k(m)$ output 1 iff $t = t'$

Observations:

- Since $F_k(m)$ is unpredictable (without knowing k), \mathcal{A} can't find tag for new message

Unforgeable MAC from a PRF

PRF-based MAC (Fixed Length MAC)

- $\text{Gen}(1^n)$: $k \leftarrow \{0, 1\}^n$
- $\text{Mac}_k(m)$: Given $m \in \{0, 1\}^n$, compute $t = F_k(m)$
- $\text{Verify}_k(m, t)$: Compute $t' = F_k(m)$ output 1 iff $t = t'$

Observations:

- Since $F_k(m)$ is unpredictable (without knowing k), \mathcal{A} can't find tag for new message
- We use canonical verify, so this is strong MAC

Unforgeable MAC from a PRF

PRF-based MAC (Fixed Length MAC)

- $\text{Gen}(1^n)$: $k \leftarrow \{0, 1\}^n$
- $\text{Mac}_k(m)$: Given $m \in \{0, 1\}^n$, compute $t = F_k(m)$
- $\text{Verify}_k(m, t)$: Compute $t' = F_k(m)$ output 1 iff $t = t'$

Observations:

- Since $F_k(m)$ is unpredictable (without knowing k), \mathcal{A} can't find tag for new message
- We use canonical verify, so this is strong MAC
- For proof, compare to the case where f is a random function

Theorem

PRF-based MAC (Π) is unforgeable for n -bit messages.

Theorem

PRF-based MAC (Π) is unforgeable for n -bit messages.

Proof (sketch):

Let $\tilde{\Pi} = (\tilde{\text{Gen}}, \tilde{\text{Mac}}, \tilde{\text{Verify}})$ be Π with random function f in place of F_k .

- 1 Prove by reduction that for any PPT \mathcal{A} , its probability of forgery changes by a negligible amount when switch from Π to $\tilde{\Pi}$

Theorem

PRF-based MAC (Π) is unforgeable for n -bit messages.

Proof (sketch):

Let $\tilde{\Pi} = (\tilde{\text{Gen}}, \tilde{\text{Mac}}, \tilde{\text{Verify}})$ be Π with random function f in place of F_k .

- ① Prove by reduction that for any PPT \mathcal{A} , its probability of forgery changes by a negligible amount when switch from Π to $\tilde{\Pi}$
 - Assume \mathcal{A}_c that distinguishes between Π and $\tilde{\Pi}$ in MacForge game

Theorem

PRF-based MAC (Π) is unforgeable for n -bit messages.

Proof (sketch):

Let $\tilde{\Pi} = (\tilde{\text{Gen}}, \tilde{\text{Mac}}, \tilde{\text{Verify}})$ be Π with random function f in place of F_k .

- ① Prove by reduction that for any PPT \mathcal{A} , its probability of forgery changes by a negligible amount when switch from Π to $\tilde{\Pi}$
 - Assume \mathcal{A}_c that distinguishes between Π and $\tilde{\Pi}$ in MacForge game
 - \mathcal{A}_r receives \mathcal{O} which is either f or F_k . He answers \mathcal{A}_c 's $\text{Mac}_k(\cdot)$ queries with $t = \mathcal{O}(m)$.

Theorem

PRF-based MAC (Π) is unforgeable for n -bit messages.

Proof (sketch):

Let $\tilde{\Pi} = (\tilde{\text{Gen}}, \tilde{\text{Mac}}, \tilde{\text{Verify}})$ be Π with random function f in place of F_k .

- ① Prove by reduction that for any PPT \mathcal{A} , its probability of forgery changes by a negligible amount when switch from Π to $\tilde{\Pi}$
 - Assume \mathcal{A}_c that distinguishes between Π and $\tilde{\Pi}$ in MacForge game
 - \mathcal{A}_r receives \mathcal{O} which is either f or F_k . He answers \mathcal{A}_c 's $\text{Mac}_k(\cdot)$ queries with $t = \mathcal{O}(m)$.
 - If $\mathcal{O} = F_k$, this is exactly Π . if $\mathcal{O} = f$, this is exactly $\tilde{\Pi}$

Theorem

PRF-based MAC (Π) is unforgeable for n -bit messages.

Proof (sketch):

Let $\tilde{\Pi} = (\tilde{\text{Gen}}, \tilde{\text{Mac}}, \tilde{\text{Verify}})$ be Π with random function f in place of F_k .

- ① Prove by reduction that for any PPT \mathcal{A} , its probability of forgery changes by a negligible amount when switch from Π to $\tilde{\Pi}$
 - Assume \mathcal{A}_c that distinguishes between Π and $\tilde{\Pi}$ in MacForge game
 - \mathcal{A}_r receives \mathcal{O} which is either f or F_k . He answers \mathcal{A}_c 's $\text{Mac}_k(\cdot)$ queries with $t = \mathcal{O}(m)$.
 - If $\mathcal{O} = F_k$, this is exactly Π . if $\mathcal{O} = f$, this is exactly $\tilde{\Pi}$
 - If \mathcal{A}_c outputs forgery, \mathcal{A}_r outputs "PRF". Succeeds with same advantage that \mathcal{A}_c has

Theorem

PRF-based MAC (Π) is unforgeable for n -bit messages.

Proof (sketch):

Let $\tilde{\Pi} = (\tilde{\text{Gen}}, \tilde{\text{Mac}}, \tilde{\text{Verify}})$ be Π with random function f in place of F_k .

- 1 Prove by reduction that for any PPT \mathcal{A} , its probability of forgery changes by a negligible amount when switch from Π to $\tilde{\Pi}$
- 2 Prove that $\tilde{\Pi}$ is an unforgeable MAC

Theorem

PRF-based MAC (Π) is unforgeable for n -bit messages.

Proof (sketch):

Let $\tilde{\Pi} = (\tilde{\text{Gen}}, \tilde{\text{Mac}}, \tilde{\text{Verify}})$ be Π with random function f in place of F_k .

- ① Prove by reduction that for any PPT \mathcal{A} , its probability of forgery changes by a negligible amount when switch from Π to $\tilde{\Pi}$
- ② Prove that $\tilde{\Pi}$ is an unforgeable MAC
 - Note that for any $m \notin Q$, $t = f(m)$ is uniformly random

Theorem

PRF-based MAC (Π) is unforgeable for n -bit messages.

Proof (sketch):

Let $\tilde{\Pi} = (\tilde{\text{Gen}}, \tilde{\text{Mac}}, \tilde{\text{Verify}})$ be Π with random function f in place of F_k .

- ① Prove by reduction that for any PPT \mathcal{A} , its probability of forgery changes by a negligible amount when switch from Π to $\tilde{\Pi}$
- ② Prove that $\tilde{\Pi}$ is an unforgeable MAC
 - Note that for any $m \notin Q$, $t = f(m)$ is uniformly random
 - Thus,

$$\Pr[\text{MacForge}_{\mathcal{A}, \tilde{\Pi}}(n) = 1] \leq 2^{-n}$$

Authenticating Longer Messages

- So far, only showed how to authenticate n -bit messages

Authenticating Longer Messages

- So far, only showed how to authenticate n -bit messages
- Just like with encryption, we need to be able to authenticate arbitrary length messages

Authenticating Longer Messages

- So far, only showed how to authenticate n -bit messages
- Just like with encryption, we need to be able to authenticate arbitrary length messages
- We will explore how to do this in today's quiz.