

Foundations of Computing

Lecture 21

Arkady Yerukhimovich

April 9, 2024

Outline

- 1 Lecture 20 Review
- 2 A Review of \mathcal{P} and \mathcal{NP}
- 3 Polynomial-Time Reductions
- 4 \mathcal{NP} -Completeness
- 5 \mathcal{NP} -Completeness Using Reductions

Lecture 20 Review

- Verifying vs. Deciding
- The Complexity Class \mathcal{NP}

$$\mathcal{NP} = \bigcup_k \text{NTIME}(n^k)$$

Outline

- 1 Lecture 20 Review
- 2 A Review of \mathcal{P} and \mathcal{NP}
- 3 Polynomial-Time Reductions
- 4 \mathcal{NP} -Completeness
- 5 \mathcal{NP} -Completeness Using Reductions

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :
 - For $x \in L$, $M(x)$ halts and outputs 1

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :
 - For $x \in L$, $M(x)$ halts and outputs 1
 - For $x \notin L$, $M(x)$ halts and outputs 0

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :
 - For $x \in L$, $M(x)$ halts and outputs 1
 - For $x \notin L$, $M(x)$ halts and outputs 0
 - Runtime of M is $O(\text{poly}(|x|))$ for all x – worst case

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :
 - For $x \in L$, $M(x)$ halts and outputs 1
 - For $x \notin L$, $M(x)$ halts and outputs 0
 - Runtime of M is $O(\text{poly}(|x|))$ for all x – worst case
- $L \in \mathcal{NP}$ if there is a poly-time verifier DTM V :

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :
 - For $x \in L$, $M(x)$ halts and outputs 1
 - For $x \notin L$, $M(x)$ halts and outputs 0
 - Runtime of M is $O(\text{poly}(|x|))$ for all x – worst case
- $L \in \mathcal{NP}$ if there is a poly-time verifier DTM V :
 - For $x \in L$, there exists $w \in \{0, 1\}^{\text{poly}(|x|)}$ s.t. $V(x, w) = 1$

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :
 - For $x \in L$, $M(x)$ halts and outputs 1
 - For $x \notin L$, $M(x)$ halts and outputs 0
 - Runtime of M is $O(\text{poly}(|x|))$ for all x – worst case
- $L \in \mathcal{NP}$ if there is a poly-time verifier DTM V :
 - For $x \in L$, there exists $w \in \{0, 1\}^{\text{poly}(|x|)}$ s.t. $V(x, w) = 1$
 - For $x \notin L$, for all $w \in \{0, 1\}^{\text{poly}(|x|)}$, $V(x, w) = 0$

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :
 - For $x \in L$, $M(x)$ halts and outputs 1
 - For $x \notin L$, $M(x)$ halts and outputs 0
 - Runtime of M is $O(\text{poly}(|x|))$ for all x – worst case
- $L \in \mathcal{NP}$ if there is a poly-time verifier DTM V :
 - For $x \in L$, there exists $w \in \{0, 1\}^{\text{poly}(|x|)}$ s.t. $V(x, w) = 1$
 - For $x \notin L$, for all $w \in \{0, 1\}^{\text{poly}(|x|)}$, $V(x, w) = 0$
 - w is a witness to $x \in L$

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :
 - For $x \in L$, $M(x)$ halts and outputs 1
 - For $x \notin L$, $M(x)$ halts and outputs 0
 - Runtime of M is $O(\text{poly}(|x|))$ for all x – worst case
- $L \in \mathcal{NP}$ if there is a poly-time verifier DTM V :
 - For $x \in L$, there exists $w \in \{0, 1\}^{\text{poly}(|x|)}$ s.t. $V(x, w) = 1$
 - For $x \notin L$, for all $w \in \{0, 1\}^{\text{poly}(|x|)}$, $V(x, w) = 0$
 - w is a witness to $x \in L$

Why Do We Study These?

- $L \in \mathcal{P}$ if there is a poly-time DTM M that decides L :
 - For $x \in L$, $M(x)$ halts and outputs 1
 - For $x \notin L$, $M(x)$ halts and outputs 0
 - Runtime of M is $O(\text{poly}(|x|))$ for all x – worst case
- $L \in \mathcal{NP}$ if there is a poly-time verifier DTM V :
 - For $x \in L$, there exists $w \in \{0, 1\}^{\text{poly}(|x|)}$ s.t. $V(x, w) = 1$
 - For $x \notin L$, for all $w \in \{0, 1\}^{\text{poly}(|x|)}$, $V(x, w) = 0$
 - w is a witness to $x \in L$

Why Do We Study These?

Both \mathcal{P} and \mathcal{NP} contain many useful languages

Why are \mathcal{P} and \mathcal{NP} Interesting?

\mathcal{P}

- \mathcal{P} captures the class of efficiently decidable languages

Why are \mathcal{P} and \mathcal{NP} Interesting?

\mathcal{P}

- \mathcal{P} captures the class of efficiently decidable languages
- Can determine membership in L for all inputs

Why are \mathcal{P} and \mathcal{NP} Interesting?

\mathcal{P}

- \mathcal{P} captures the class of efficiently decidable languages
- Can determine membership in L for all inputs

\mathcal{NP}

- \mathcal{NP} captures the class of problems where there exists a short proof that $x \in L$

Why are \mathcal{P} and \mathcal{NP} Interesting?

\mathcal{P}

- \mathcal{P} captures the class of efficiently decidable languages
- Can determine membership in L for all inputs

\mathcal{NP}

- \mathcal{NP} captures the class of problems where there exists a short proof that $x \in L$
- Can prove $x \in L$ for all inputs, but can't prove that a string not in L is in the language

Why are \mathcal{P} and \mathcal{NP} Interesting?

\mathcal{P}

- \mathcal{P} captures the class of efficiently decidable languages
- Can determine membership in L for all inputs

\mathcal{NP}

- \mathcal{NP} captures the class of problems where there exists a short proof that $x \in L$
- Can prove $x \in L$ for all inputs, but can't prove that a string not in L is in the language

\mathcal{NP} -Completeness

There are problems in \mathcal{NP} that are as hard as any other problem in \mathcal{NP}

Outline

- 1 Lecture 20 Review
- 2 A Review of \mathcal{P} and \mathcal{NP}
- 3 Polynomial-Time Reductions
- 4 \mathcal{NP} -Completeness
- 5 \mathcal{NP} -Completeness Using Reductions

Mapping Reductions

Mapping Reduction

Language A is mapping reducible to language B ($A \leq_m B$) if there is a computable function $f : \Sigma^* \rightarrow \Sigma^*$, where for every x ,

$$x \in A \iff f(x) \in B$$

Mapping Reductions

Mapping Reduction

Language A is mapping reducible to language B ($A \leq_m B$) if there is a computable function $f : \Sigma^* \rightarrow \Sigma^*$, where for every x ,

$$x \in A \iff f(x) \in B$$

Poly-time Mapping Reduction

Language A is poly-time mapping reducible to language B ($A \leq_P B$) if there is a poly-time computable function $f : \Sigma^* \rightarrow \Sigma^*$, where for every x ,

$$x \in A \iff f(x) \in B$$

Mapping Reductions

Mapping Reduction

Language A is mapping reducible to language B ($A \leq_m B$) if there is a computable function $f : \Sigma^* \rightarrow \Sigma^*$, where for every x ,

$$x \in A \iff f(x) \in B$$

Poly-time Mapping Reduction

Language A is poly-time mapping reducible to language B ($A \leq_P B$) if there is a poly-time computable function $f : \Sigma^* \rightarrow \Sigma^*$, where for every x ,

$$x \in A \iff f(x) \in B$$

- Poly-time reductions give an efficient way to convert membership testing in A to membership testing in B

Mapping Reductions

Mapping Reduction

Language A is mapping reducible to language B ($A \leq_m B$) if there is a computable function $f : \Sigma^* \rightarrow \Sigma^*$, where for every x ,

$$x \in A \iff f(x) \in B$$


Poly-time Mapping Reduction

Language A is poly-time mapping reducible to language B ($A \leq_P B$) if there is a poly-time computable function $f : \Sigma^* \rightarrow \Sigma^*$, where for every x ,

$$x \in A \iff f(x) \in B$$

- Poly-time reductions give an efficient way to convert membership testing in A to membership testing in B
- If B has a poly-time solution so does A

Poly-time Mapping Reductions



f runs in time $\text{poly}(|x|)$ on all inputs x

Why Poly-Time Reductions

Theorem

If $A \leq_P B$ and $B \in \mathcal{P}$, then $A \in \mathcal{P}$

Why Poly-Time Reductions

Theorem

If $A \leq_P B$ and $B \in \mathcal{P}$, then $A \in \mathcal{P}$

Proof:

Why Poly-Time Reductions

Theorem

If $A \leq_P B$ and $B \in \mathcal{P}$, then $A \in \mathcal{P}$

Proof:

- Let M be the poly-time TM deciding B

Why Poly-Time Reductions

Theorem

If $A \leq_P B$ and $B \in \mathcal{P}$, then $A \in \mathcal{P}$

Proof:

- Let M be the poly-time TM deciding B
- Let f be the poly-time reduction from A to B

Why Poly-Time Reductions

Theorem

If $A \leq_P B$ and $B \in \mathcal{P}$, then $A \in \mathcal{P}$

Proof:

- Let M be the poly-time TM deciding B
- Let f be the poly-time reduction from A to B
- Can construct M' deciding A :

Why Poly-Time Reductions

Theorem

If $A \leq_P B$ and $B \in \mathcal{P}$, then $A \in \mathcal{P}$

Proof:

- Let M be the poly-time TM deciding B
- Let f be the poly-time reduction from A to B
- Can construct M' deciding A :
 $M' =$ On input x :
 - 1 Compute $f(x)$
 - 2 Run $M(f(x))$ and output whatever M outputs

Why Poly-Time Reductions

Theorem

If $A \leq_P B$ and $B \in \mathcal{P}$, then $A \in \mathcal{P}$

Proof:

- Let M be the poly-time TM deciding B
- Let f be the poly-time reduction from A to B
- Can construct M' deciding A :
 $M' =$ On input x :
 - 1 Compute $f(x)$
 - 2 Run $M(f(x))$ and output whatever M outputs
 - If $x \in A$, $f(x) \in B$ so M accepts

Why Poly-Time Reductions

Theorem

If $A \leq_P B$ and $B \in \mathcal{P}$, then $A \in \mathcal{P}$

Proof:

- Let M be the poly-time TM deciding B
- Let f be the poly-time reduction from A to B
- Can construct M' deciding A :
 M' = On input x :
 - 1 Compute $f(x)$
 - 2 Run $M(f(x))$ and output whatever M outputs
 - If $x \in A$, $f(x) \in B$ so M accepts
 - If $x \notin A$, $f(x) \notin B$, so M rejects

Why Poly-Time Reductions

Theorem

If $A \leq_P B$ and $B \in \mathcal{P}$, then $A \in \mathcal{P}$

Proof:

- Let M be the poly-time TM deciding B
- Let f be the poly-time reduction from A to B
- Can construct M' deciding A :
 $M' =$ On input x :
 - 1 Compute $f(x)$
 - 2 Run $M(f(x))$ and output whatever M outputs
 - If $x \in A$, $f(x) \in B$ so M accepts
 - If $x \notin A$, $f(x) \notin B$, so M rejects
 - Since both f and M are poly-time, $M(f(x))$ is also poly-time

Using Poly-Time Reductions to Prove Hardness

Theorem

If $A \leq_P B$ and $A \notin \mathcal{P}$, then $B \notin \mathcal{P}$

Outline

- 1 Lecture 20 Review
- 2 A Review of \mathcal{P} and \mathcal{NP}
- 3 Polynomial-Time Reductions
- 4 \mathcal{NP} -Completeness
- 5 \mathcal{NP} -Completeness Using Reductions

Definition

A language B is \mathcal{NP} -complete if

- $B \in \mathcal{NP}$
- For every language $A \in \mathcal{NP}$, $A \leq_P B$

Definition

A language B is \mathcal{NP} -complete if

- $B \in \mathcal{NP}$
- For every language $A \in \mathcal{NP}$, $A \leq_P B$
- B is “as hard” as any language in \mathcal{NP}

Definition

A language B is \mathcal{NP} -complete if

- $B \in \mathcal{NP}$
 - For every language $A \in \mathcal{NP}$, $A \leq_P B$
-
- B is “as hard” as any language in \mathcal{NP}
 - To study hardness of \mathcal{NP} , enough to study hardness of some \mathcal{NP} -complete problem

\mathcal{NP} -Completeness

Definition

A language B is \mathcal{NP} -complete if

- $B \in \mathcal{NP}$
 - For every language $A \in \mathcal{NP}$, $A \leq_P B$
-
- B is “as hard” as any language in \mathcal{NP}
 - To study hardness of \mathcal{NP} , enough to study hardness of some \mathcal{NP} -complete problem

Theorem

If B is \mathcal{NP} -complete and $B \in \mathcal{P}$, then $\mathcal{P} = \mathcal{NP}$

\mathcal{NP} -Completeness

Definition

A language B is \mathcal{NP} -complete if

- $B \in \mathcal{NP}$
 - For every language $A \in \mathcal{NP}$, $A \leq_P B$
-
- B is “as hard” as any language in \mathcal{NP}
 - To study hardness of \mathcal{NP} , enough to study hardness of some \mathcal{NP} -complete problem

Theorem

If B is \mathcal{NP} -complete and $B \in \mathcal{P}$, then $\mathcal{P} = \mathcal{NP}$

Theorem

If B is \mathcal{NP} -complete and $B \leq_P C$ for $C \in \mathcal{NP}$, then C is \mathcal{NP} -complete

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

SAT is \mathcal{NP} -Complete

SAT Problem

$$\text{SAT} = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- 1 $\text{SAT} \in \mathcal{NP}$

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- 1 $SAT \in \mathcal{NP}$
- 2 For each $A \in \mathcal{NP}$, $A \leq_P SAT$

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ① $SAT \in \mathcal{NP}$
- ② For each $A \in \mathcal{NP}$, $A \leq_P SAT$
 - Need to design reduction f from A to SAT

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ① $SAT \in \mathcal{NP}$
- ② For each $A \in \mathcal{NP}$, $A \leq_P SAT$
 - Need to design reduction f from A to SAT
 - f takes an input x and produces formula ϕ

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ① $SAT \in \mathcal{NP}$
- ② For each $A \in \mathcal{NP}$, $A \leq_P SAT$
 - Need to design reduction f from A to SAT
 - f takes an input x and produces formula ϕ
 - If $x \in A$ then ϕ is satisfiable

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ① $SAT \in \mathcal{NP}$
- ② For each $A \in \mathcal{NP}$, $A \leq_P SAT$
 - Need to design reduction f from A to SAT
 - f takes an input x and produces formula ϕ
 - If $x \in A$ then ϕ is satisfiable
 - If $x \notin A$ then ϕ is not satisfiable

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ① $SAT \in \mathcal{NP}$
- ② For each $A \in \mathcal{NP}$, $A \leq_P SAT$
 - Need to design reduction f from A to SAT
 - f takes an input x and produces formula ϕ
 - If $x \in A$ then ϕ is satisfiable
 - If $x \notin A$ then ϕ is not satisfiable
 - Idea: Let ϕ be a formula simulating \mathcal{NP} machine for A on input x

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ① $SAT \in \mathcal{NP}$
- ② For each $A \in \mathcal{NP}$, $A \leq_P SAT$
 - Need to design reduction f from A to SAT
 - f takes an input x and produces formula ϕ
 - If $x \in A$ then ϕ is satisfiable
 - If $x \notin A$ then ϕ is not satisfiable
 - Idea: Let ϕ be a formula simulating \mathcal{NP} machine for A on input x
 - That is, ϕ corresponds to the Boolean logic done by this machine

SAT is \mathcal{NP} -Complete

SAT Problem

$$SAT = \{\langle \phi \rangle \mid \phi \text{ is a satisfiable Boolean formula}\}$$

Proof Idea:

- ① $SAT \in \mathcal{NP}$
- ② For each $A \in \mathcal{NP}$, $A \leq_P SAT$
 - Need to design reduction f from A to SAT
 - f takes an input x and produces formula ϕ
 - If $x \in A$ then ϕ is satisfiable
 - If $x \notin A$ then ϕ is not satisfiable
 - Idea: Let ϕ be a formula simulating \mathcal{NP} machine for A on input x
 - That is, ϕ corresponds to the Boolean logic done by this machine
 - Since any computation can be represented as a Boolean computation, this is always possible

Execution of Turing Machine M deciding A

#	q_0	x_1	x_2	\dots	x_n	\sqcup	\dots	\sqcup	#
#									#
#									#
#									#

Table: Tableau of configurations of M

Execution of Turing Machine M deciding A

#	q_0	x_1	x_2	\dots	x_n	\sqcup	\dots	\sqcup	#
#									#
#									#
#									#

Table: Tableau of configurations of M

- Every row is a configuration of M

Execution of Turing Machine M deciding A

#	q_0	x_1	x_2	\dots	x_n	\sqcup	\dots	\sqcup	#
#									#
#									#
#									#

Table: Tableau of configurations of M

- Every row is a configuration of M
- Two consecutive rows represent a valid transition if they follow rules of M

Execution of Turing Machine M deciding A

#	q_0	x_1	x_2	\dots	x_n	\sqcup	\dots	\sqcup	#
#									#
#									#
#									#

Table: Tableau of configurations of M

- Every row is a configuration of M
- Two consecutive rows represent a valid transition if they follow rules of M
- Every cell contains #, or a state $q \in Q$, or a tape symbol $\in \Gamma$

Execution of Turing Machine M deciding A

#	q_0	x_1	x_2	\dots	x_n	\sqcup	\dots	\sqcup	#
#									#
#									#
#									#

Table: Tableau of configurations of M

- Every row is a configuration of M
- Two consecutive rows represent a valid transition if they follow rules of M
- Every cell contains #, or a state $q \in Q$, or a tape symbol $\in \Gamma$
- M accepts x if a row of this tableau is in q_{accept}

SAT is \mathcal{NP} -Complete

Given input x that we want to check if $x \in A$

We need to build a formula ϕ that checks the following four things:

SAT is \mathcal{NP} -Complete

Given input x that we want to check if $x \in A$

We need to build a formula ϕ that checks the following four things:

- 1 Every cell contains a valid character in $C = Q \cup \Gamma \cup \{\#\}$

SAT is \mathcal{NP} -Complete

Given input x that we want to check if $x \in A$

We need to build a formula ϕ that checks the following four things:

- 1 Every cell contains a valid character in $C = Q \cup \Gamma \cup \{\#\}$
- 2 Top row is the start configuration (on input x)

SAT is \mathcal{NP} -Complete

Given input x that we want to check if $x \in A$

We need to build a formula ϕ that checks the following four things:

- 1 Every cell contains a valid character in $C = Q \cup \Gamma \cup \{\#\}$
- 2 Top row is the start configuration (on input x)
- 3 Some row is in q_{accept}

SAT is \mathcal{NP} -Complete

Given input x that we want to check if $x \in A$

We need to build a formula ϕ that checks the following four things:

- 1 Every cell contains a valid character in $C = Q \cup \Gamma \cup \{\#\}$
- 2 Top row is the start configuration (on input x)
- 3 Some row is in q_{accept}
- 4 Every pair of adjacent rows represents a valid transition of M

SAT is \mathcal{NP} -Complete

- 1 Every cell contains a valid character in $C = Q \cup \Gamma \cup \{\#\}$

SAT is \mathcal{NP} -Complete

- 1 Every cell contains a valid character in $C = Q \cup \Gamma \cup \{\#\}$
 - For $1 \leq i, j \leq n^k$, and $s \in C$, let $x_{i,j,s} = 1$ if $cell[i, j] = s$

SAT is \mathcal{NP} -Complete

- 1 Every cell contains a valid character in $C = Q \cup \Gamma \cup \{\#\}$
 - For $1 \leq i, j \leq n^k$, and $s \in C$, let $x_{i,j,s} = 1$ if $cell[i,j] = s$
 - The following equation $\phi_{i,j}^{cell}$ guarantees that a cell has a valid value

$$\phi_{i,j}^{cell} = \underbrace{\left(\bigvee_{s \in C} x_{i,j,s} \right)}_{\text{cell } i,j \text{ has at least 1 value}} \wedge \underbrace{\left(\bigwedge_{s,t \in C, s \neq t} (\overline{x_{i,j,s}} \vee \overline{x_{i,j,t}}) \right)}_{\text{cell } i,j \text{ has at most 1 value}}$$

SAT is \mathcal{NP} -Complete

- 1 Every cell contains a valid character in $C = Q \cup \Gamma \cup \{\#\}$
 - For $1 \leq i, j \leq n^k$, and $s \in C$, let $x_{i,j,s} = 1$ if $cell[i,j] = s$
 - The following equation $\phi_{i,j}^{cell}$ guarantees that a cell has a valid value

$$\phi_{i,j}^{cell} = \underbrace{\left(\bigvee_{s \in C} x_{i,j,s} \right)}_{\text{cell } i,j \text{ has at least 1 value}} \wedge \underbrace{\left(\bigwedge_{s,t \in C, s \neq t} (\overline{x_{i,j,s}} \vee \overline{x_{i,j,t}}) \right)}_{\text{cell } i,j \text{ has at most 1 value}}$$

- Now, we just take the AND over all n^{2k} cells in the tableau

SAT is \mathcal{NP} -Complete

- 2 Top row is the start configuration

SAT is \mathcal{NP} -Complete

- 2 Top row is the start configuration
- Define a formula ϕ_{start} that checks that all the cells in the top row are correct

$$\phi_{start} = x_{1,1,\#} \wedge x_{1,2,q_0} \cdots \wedge x_{1,n^k,\#}$$

SAT is \mathcal{NP} -Complete

- ③ Some row is in q_{accept}

SAT is \mathcal{NP} -Complete

- 3 Some row is in q_{accept}
 - Define a formula ϕ_{accept} that checks that some row contains q_{accept}

$$\phi_{\text{accept}} = \bigvee_{1 \leq i, j \leq n^k} x_{i,j,q_{\text{accept}}}$$

SAT is \mathcal{NP} -Complete

- ④ Every pair of adjacent rows represents a valid transition of M

SAT is \mathcal{NP} -Complete

- ④ Every pair of adjacent rows represents a valid transition of M
 - We need to define what is a valid move between two configurations

SAT is \mathcal{NP} -Complete

- ④ Every pair of adjacent rows represents a valid transition of M
 - We need to define what is a valid move between two configurations
 - If the control head is not next to some cell, that cell will not change

SAT is \mathcal{NP} -Complete

- ④ Every pair of adjacent rows represents a valid transition of M
 - We need to define what is a valid move between two configurations
 - If the control head is not next to some cell, that cell will not change
 - For cells after control head, can write to the cell and move left or right (depending on M)

SAT is \mathcal{NP} -Complete

- ④ Every pair of adjacent rows represents a valid transition of M
 - We need to define what is a valid move between two configurations
 - If the control head is not next to some cell, that cell will not change
 - For cells after control head, can write to the cell and move left or right (depending on M)
 - Every 2×3 cell window can be checked to follow these rules

SAT is \mathcal{NP} -Complete

- ④ Every pair of adjacent rows represents a valid transition of M
 - We need to define what is a valid move between two configurations
 - If the control head is not next to some cell, that cell will not change
 - For cells after control head, can write to the cell and move left or right (depending on M)
 - Every 2×3 cell window can be checked to follow these rules
 - Now just take the \wedge over all possible 6-cell windows

SAT is \mathcal{NP} -Complete

- Finally, need to check that this reduction runs in poly time (in $n = |x|$)

SAT is \mathcal{NP} -Complete

- Finally, need to check that this reduction runs in poly time (in $n = |x|$)
- Recall that the tableau has size $n^k \times n^k$, so n^{2k} cells

SAT is \mathcal{NP} -Complete

- Finally, need to check that this reduction runs in poly time (in $n = |x|$)
- Recall that the tableau has size $n^k \times n^k$, so n^{2k} cells
- ϕ_{cell} has fixed size for each cell, so $O(n^{2k})$ total

SAT is \mathcal{NP} -Complete

- Finally, need to check that this reduction runs in poly time (in $n = |x|$)
- Recall that the tableau has size $n^k \times n^k$, so n^{2k} cells
- ϕ_{cell} has fixed size for each cell, so $O(n^{2k})$ total
- ϕ_{start} has fixed size for each cell in top row, so $O(n^k)$ total

SAT is \mathcal{NP} -Complete

- Finally, need to check that this reduction runs in poly time (in $n = |x|$)
- Recall that the tableau has size $n^k \times n^k$, so n^{2k} cells
- ϕ_{cell} has fixed size for each cell, so $O(n^{2k})$ total
- ϕ_{start} has fixed size for each cell in top row, so $O(n^k)$ total
- ϕ_{move} and ϕ_{accept} have fixed size for each cell, so $O(n^{2k})$ total

SAT is \mathcal{NP} -Complete

- Finally, need to check that this reduction runs in poly time (in $n = |x|$)
- Recall that the tableau has size $n^k \times n^k$, so n^{2k} cells
- ϕ_{cell} has fixed size for each cell, so $O(n^{2k})$ total
- ϕ_{start} has fixed size for each cell in top row, so $O(n^k)$ total
- ϕ_{move} and ϕ_{accept} have fixed size for each cell, so $O(n^{2k})$ total
- Summing up, we see $|\phi| = O(n^{2k})$

SAT is \mathcal{NP} -Complete

- Finally, need to check that this reduction runs in poly time (in $n = |x|$)
- Recall that the tableau has size $n^k \times n^k$, so n^{2k} cells
- ϕ_{cell} has fixed size for each cell, so $O(n^{2k})$ total
- ϕ_{start} has fixed size for each cell in top row, so $O(n^k)$ total
- ϕ_{move} and ϕ_{accept} have fixed size for each cell, so $O(n^{2k})$ total
- Summing up, we see $|\phi| = O(n^{2k})$
- Since $k = O(1)$, this is polynomial in n

Outline

- 1 Lecture 20 Review
- 2 A Review of \mathcal{P} and \mathcal{NP}
- 3 Polynomial-Time Reductions
- 4 \mathcal{NP} -Completeness
- 5 \mathcal{NP} -Completeness Using Reductions

The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment

The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

3-CNF formulas

- A literal is a (possibly negated) Boolean variable – x or \bar{x}

The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

3-CNF formulas

- A literal is a (possibly negates) Boolean variable – x or \bar{x}
- A clause is several literals connected with \vee 's – $x_1 \vee \bar{x}_2 \vee x_3$

The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

3-CNF formulas

- A literal is a (possibly negated) Boolean variable – x or \bar{x}
- A clause is several literals connected with \vee 's – $x_1 \vee \bar{x}_2 \vee x_3$
- A Boolean formula is in conjunctive normal form (CNF) if it consists of clauses connected by \wedge 's

$$(x_1 \vee \bar{x}_2 \vee x_3 \vee x_4) \wedge (\bar{x}_3 \vee x_5)$$

The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

3-CNF formulas

- A literal is a (possibly negated) Boolean variable – x or \bar{x}
- A clause is several literals connected with \vee 's – $x_1 \vee \bar{x}_2 \vee x_3$
- A Boolean formula is in conjunctive normal form (CNF) if it consists of clauses connected by \wedge 's

$$(x_1 \vee \bar{x}_2 \vee x_3 \vee x_4) \wedge (\bar{x}_3 \vee x_5)$$

- A Boolean formula is a 3-CNF if all the clauses have exactly 3 literals

$$(x_1 \vee \bar{x}_2 \vee x_3) \wedge (\bar{x}_3 \vee x_4 \vee x_5) \wedge (\bar{x}_1 \vee x_4 \vee x_2)$$

The 3SAT Problem

- Recall that SAT asks if a Boolean formula has a satisfying assignment
- 3SAT asks the same question for 3-CNF formulas

3-CNF formulas

- A literal is a (possibly negated) Boolean variable – x or \bar{x}
- A clause is several literals connected with \vee 's – $x_1 \vee \bar{x}_2 \vee x_3$
- A Boolean formula is in conjunctive normal form (CNF) if it consists of clauses connected by \wedge 's

$$(x_1 \vee \bar{x}_2 \vee x_3 \vee x_4) \wedge (\bar{x}_3 \vee x_5)$$

- A Boolean formula is a 3-CNF if all the clauses have exactly 3 literals

$$(x_1 \vee \bar{x}_2 \vee x_3) \wedge (\bar{x}_3 \vee x_4 \vee x_5) \wedge (\bar{x}_1 \vee x_4 \vee x_2)$$

3-SAT

$$3\text{SAT} = \{ \langle \phi \rangle \mid \phi \text{ is a satisfiable 3-CNF formula} \}$$

Can show that 3SAT is \mathcal{NP} -complete using similar proof to SAT

$3\text{SAT} \leq_P \text{CLIQUE}$

- Need to show reduction f from 3SAT formula ϕ to $\langle G, k \rangle$ where

$3\text{SAT} \leq_P \text{CLIQUE}$

- Need to show reduction f from 3SAT formula ϕ to $\langle G, k \rangle$ where
 - If ϕ is satisfiable, G has a clique of size k

$3\text{SAT} \leq_P \text{CLIQUE}$


- Need to show reduction f from 3SAT formula ϕ to $\langle G, k \rangle$ where
 - If ϕ is satisfiable, G has a clique of size k
 - If ϕ is not satisfiable, G has no clique of size k

$3\text{SAT} \leq_P \text{CLIQUE}$

- Need to show reduction f from 3SAT formula ϕ to $\langle G, k \rangle$ where
 - If ϕ is satisfiable, G has a clique of size k
 - If ϕ is not satisfiable, G has no clique of size k
- Consider $\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2)$


3SAT \leq_P CLIQUE

- Need to show reduction f from 3SAT formula ϕ to $\langle G, k \rangle$ where
 - If ϕ is satisfiable, G has a clique of size k
 - If ϕ is not satisfiable, G has no clique of size k
- Consider $\phi = (x_1 \vee \bar{x}_1 \vee x_2) \wedge (\bar{x}_1 \vee \bar{x}_2 \vee \bar{x}_2) \wedge (\bar{x}_1 \vee x_2 \vee x_2)$



3SAT \leq_P CLIQUE


- Need to show reduction f from 3SAT formula ϕ to $\langle G, k \rangle$ where
 - If ϕ is satisfiable, G has a clique of size k
 - If ϕ is not satisfiable, G has no clique of size k
- Consider $\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2)$



- If ϕ is satisfiable then G has a k -clique

3SAT \leq_P CLIQUE

- Need to show reduction f from 3SAT formula ϕ to $\langle G, k \rangle$ where
 - If ϕ is satisfiable, G has a clique of size k
 - If ϕ is not satisfiable, G has no clique of size k
- Consider $\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2)$



- If ϕ is satisfiable then G has a k -clique
- If G has a k -clique then ϕ is satisfiable