

Cryptography

Lecture 9

Arkady Yerukhimovich

September 25, 2024

- 1 Lecture 8 Review
- 2 Security of PRF+OTP (Chapter 3.5.2)
- 3 Modes of Operation (Chapter 3.6.2)

Lecture 8 Review

- Quiz on PRFs
- Started proof of CPA-security for PRF+OTP

- 1 Lecture 8 Review
- 2 Security of PRF+OTP (Chapter 3.5.2)
- 3 Modes of Operation (Chapter 3.6.2)

CPA-Secure Encryption from a PRF

PRF+OTP Encryption (Π)

- $\text{Gen}(1^n)$: $k \leftarrow \{0, 1\}^n$
- $\text{Enc}(k, m)$: Choose $r \leftarrow \{0, 1\}^n$, output $c = (r, F_k(r) \oplus m)$
- $\text{Dec}(k, c)$: Parse c as (r, c') , compute $m = F_k(r) \oplus c'$

Theorem

If F is a secure PRF, then PRF+OTP is CPA-secure

To prove security from a PRF, we often do the following:

- ① Consider the scheme where F_k is replaced by a random function f
 - Show by reduction to security of PRF, that \mathcal{A} can't tell we made this change.
 - So, \mathcal{A} 's success probability must be (essentially) the same in this and original variant.

To prove security from a PRF, we often do the following:

- ① Consider the scheme where F_k is replaced by a random function f
 - Show by reduction to security of PRF, that \mathcal{A} can't tell we made this change.
 - So, \mathcal{A} 's success probability must be (essentially) the same in this and original variant.
- ② Use a probabilistic argument to prove that scheme is unconditionally secure when using a random function f .
 - Random function is essentially a collection of 2^n OTPs
 - Proof is similar to proof of OTP, but need to account for probability of collision in r

Security of PRF+OTP: Step 1

Define the following encryption scheme $\tilde{\Pi}$:

$\tilde{\Pi}$ Encryption Scheme

- $\widetilde{\text{Gen}}(1^n)$: $f \leftarrow \mathcal{F}_n$ (the set of functions $\{0, 1\}^n \rightarrow \{0, 1\}^n$)
 - $\widetilde{\text{Enc}}(k, m)$: Choose $r \leftarrow \{0, 1\}^n$, output $c = (r, f(r) \oplus m)$
 - $\widetilde{\text{Dec}}(k, c)$: Parse c as (r, c') , compute $m = f(r) \oplus c'$
-
- Observe that this is exactly PRF+OTP with F_k replaced by f
 - This encryption is not efficient as we cannot evaluate a random function
 - But, it is useful as a “thought experiment” in the proof as it gives us a target for security

Security of PRF+OTP: Step 1

$\tilde{\Pi}$ Encryption Scheme

- $\widetilde{\text{Gen}}(1^n)$: $f \leftarrow \mathcal{F}_n$ (the set of functions $\{0, 1\}^n \rightarrow \{0, 1\}^n$)
- $\widetilde{\text{Enc}}(k, m)$: Choose $r \leftarrow \{0, 1\}^n$, output $c = (r, f(r) \oplus m)$
- $\widetilde{\text{Dec}}(k, c)$: Parse c as (r, c') , compute $m = f(r) \oplus c'$

Lemma: For any PPT \mathcal{A}

$$\left| \Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{cpa}(n) = 1] - \Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{cpa}(n) = 1] \right| \leq \text{negl}(n)$$

A Story of Two Games

Security of PRF+OTP: Proof of Lemma

Lemma

For any PPT \mathcal{A}

$$\left| \Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{cpa}(n) = 1] - \Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{cpa}(n) = 1] \right| \leq \text{negl}(n)$$

We prove this lemma by reduction:

Security of PRF+OTP: Proof of Lemma

Lemma

For any PPT \mathcal{A}

$$\left| \Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cpa}}(n) = 1] - \Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \right| \leq \text{negl}(n)$$

We prove this lemma by reduction:

- Assume there is a PPT \mathcal{A}_c that breaks this lemma

Security of PRF+OTP: Proof of Lemma

Lemma

For any PPT \mathcal{A}

$$\left| \Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cpa}}(n) = 1] - \Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \right| \leq \text{negl}(n)$$

We prove this lemma by reduction:

- Assume there is a PPT \mathcal{A}_c that breaks this lemma
 - \mathcal{A}_c is a CPA-security adversary
 - What we care about is the difference in probability that \mathcal{A}_c wins the CPA-security game when playing with Π vs. $\tilde{\Pi}$.

Security of PRF+OTP: Proof of Lemma

Lemma

For any PPT \mathcal{A}

$$\left| \Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cpa}}(n) = 1] - \Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \right| \leq \text{negl}(n)$$

We prove this lemma by reduction:

- Assume there is a PPT \mathcal{A}_c that breaks this lemma
 - \mathcal{A}_c is a CPA-security adversary
 - What we care about is the difference in probability that \mathcal{A}_c wins the CPA-security game when playing with Π vs. $\tilde{\Pi}$.
- Use this to construct \mathcal{A}_r that breaks PRF security of F_k

The Two Adversaries

$PRF_{\mathcal{D},F}(n)$

- The challenger chooses $b \leftarrow \{0, 1\}$.
If $b = 0$, he chooses $f \leftarrow \mathcal{F}_n$ and gives \mathcal{D} an oracle $\mathcal{O} = f$.
If $b = 1$, he chooses $k \leftarrow \{0, 1\}^n$, and gives \mathcal{D} an oracle $\mathcal{O} = F_k$.
- With access to oracle \mathcal{O} , the distinguisher \mathcal{D} outputs a bit b'
- $PRF_{\mathcal{D},F}(n) = 1$ (i.e., \mathcal{D} wins) if $b' = b$

$\text{PrivK}_{\mathcal{A},n}^{\text{cpa}}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot)}$ outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A},n}^{\text{cpa}}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

The Two Adversaries

$PRF_{\mathcal{D},F}(n)$

- The challenger chooses $b \leftarrow \{0, 1\}$.
If $b = 0$, he chooses $f \leftarrow \mathcal{F}_n$ and gives \mathcal{D} an oracle $\mathcal{O} = f$.
If $b = 1$, he chooses $k \leftarrow \{0, 1\}^n$, and gives \mathcal{D} an oracle $\mathcal{O} = F_k$.
- With access to oracle \mathcal{O} , the distinguisher \mathcal{D} outputs a bit b'
- $PRF_{\mathcal{D},F}(n) = 1$ (i.e., \mathcal{D} wins) if $b' = b$

$\text{PrivK}_{\mathcal{A},n}^{\text{cpa}}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot)}$ outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A},n}^{\text{cpa}}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

We have to consider two adversaries, \mathcal{A}_r and \mathcal{A}_c

The Two Adversaries

$PRF_{\mathcal{D},F}(n)$

- The challenger chooses $b \leftarrow \{0, 1\}$.
If $b = 0$, he chooses $f \leftarrow \mathcal{F}_n$ and gives \mathcal{D} an oracle $\mathcal{O} = f$.
If $b = 1$, he chooses $k \leftarrow \{0, 1\}^n$, and gives \mathcal{D} an oracle $\mathcal{O} = F_k$.
- With access to oracle \mathcal{O} , the distinguisher \mathcal{D} outputs a bit b'
- $PRF_{\mathcal{D},F}(n) = 1$ (i.e., \mathcal{D} wins) if $b' = b$

$\text{PrivK}_{\mathcal{A},n}^{\text{cpa}}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot)}$ outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A},n}^{\text{cpa}}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

We have to consider two adversaries, \mathcal{A}_f and \mathcal{A}_c

- The PRF adversary \mathcal{A}_f :

The Two Adversaries

$PRF_{\mathcal{D},F}(n)$

- The challenger chooses $b \leftarrow \{0,1\}$.
If $b = 0$, he chooses $f \leftarrow \mathcal{F}_n$ and gives \mathcal{D} an oracle $\mathcal{O} = f$.
If $b = 1$, he chooses $k \leftarrow \{0,1\}^n$, and gives \mathcal{D} an oracle $\mathcal{O} = F_k$.
- With access to oracle \mathcal{O} , the distinguisher \mathcal{D} outputs a bit b'
- $PRF_{\mathcal{D},F}(n) = 1$ (i.e., \mathcal{D} wins) if $b' = b$

$\text{PrivK}_{\mathcal{A},n}^{\text{cpa}}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0,1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot)}$ outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A},n}^{\text{cpa}}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

We have to consider two adversaries, \mathcal{A}_r and \mathcal{A}_c

- The PRF adversary \mathcal{A}_r :
 - \mathcal{A}_r is playing the PRF security game

The Two Adversaries

$PRF_{\mathcal{D},F}(n)$

- The challenger chooses $b \leftarrow \{0,1\}$.
If $b = 0$, he chooses $f \leftarrow \mathcal{F}_n$ and gives \mathcal{D} an oracle $\mathcal{O} = f$.
If $b = 1$, he chooses $k \leftarrow \{0,1\}^n$, and gives \mathcal{D} an oracle $\mathcal{O} = F_k$.
- With access to oracle \mathcal{O} , the distinguisher \mathcal{D} outputs a bit b'
- $PRF_{\mathcal{D},F}(n) = 1$ (i.e., \mathcal{D} wins) if $b' = b$

$PrivK_{\mathcal{A},n}^{cpa}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0,1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot)}$ outputs a guess bit b'
- We say that $PrivK_{\mathcal{A},n}^{cpa}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

We have to consider two adversaries, \mathcal{A}_r and \mathcal{A}_c

- The PRF adversary \mathcal{A}_r :
 - \mathcal{A}_r is playing the PRF security game
 - \mathcal{A}_r is given oracle $\mathcal{O} : \{0,1\}^n \rightarrow \{0,1\}^n$ where either $\mathcal{O} = F_k(\cdot)$ (a PRF), or $\mathcal{O} = f(\cdot)$ (a random function)

The Two Adversaries

$PRF_{\mathcal{D},F}(n)$

- The challenger chooses $b \leftarrow \{0,1\}$.
If $b = 0$, he chooses $f \leftarrow \mathcal{F}_n$ and gives \mathcal{D} an oracle $\mathcal{O} = f$.
If $b = 1$, he chooses $k \leftarrow \{0,1\}^n$, and gives \mathcal{D} an oracle $\mathcal{O} = F_k$.
- With access to oracle \mathcal{O} , the distinguisher \mathcal{D} outputs a bit b'
- $PRF_{\mathcal{D},F}(n) = 1$ (i.e., \mathcal{D} wins) if $b' = b$

$PrivK_{\mathcal{A},n}^{cpa}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0,1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot)}$ outputs a guess bit b'
- We say that $PrivK_{\mathcal{A},n}^{cpa}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

We have to consider two adversaries, \mathcal{A}_r and \mathcal{A}_c

- The PRF adversary \mathcal{A}_r :
 - \mathcal{A}_r is playing the PRF security game
 - \mathcal{A}_r is given oracle $\mathcal{O} : \{0,1\}^n \rightarrow \{0,1\}^n$ where either $\mathcal{O} = F_k(\cdot)$ (a PRF), or $\mathcal{O} = f(\cdot)$ (a random function)
- The CPA-security adversary \mathcal{A}_c (who breaks the lemma):

The Two Adversaries

$PRF_{\mathcal{D},F}(n)$

- The challenger chooses $b \leftarrow \{0,1\}$.
If $b = 0$, he chooses $f \leftarrow \mathcal{F}_n$ and gives \mathcal{D} an oracle $\mathcal{O} = f$.
if $b = 1$, he chooses $k \leftarrow \{0,1\}^n$, and gives \mathcal{D} an oracle $\mathcal{O} = F_k$.
- With access to oracle \mathcal{O} , the distinguisher \mathcal{D} outputs a bit b'
- $PRF_{\mathcal{D},F}(n) = 1$ (i.e., \mathcal{D} wins) if $b' = b$

$PrivK_{\mathcal{A},\Pi}^{cpa}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0,1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot)}$ outputs a guess bit b'
- We say that $PrivK_{\mathcal{A},\Pi}^{cpa}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

We have to consider two adversaries, \mathcal{A}_r and \mathcal{A}_c

- The PRF adversary \mathcal{A}_r :
 - \mathcal{A}_r is playing the PRF security game
 - \mathcal{A}_r is given oracle $\mathcal{O} : \{0,1\}^n \rightarrow \{0,1\}^n$ where either $\mathcal{O} = F_k(\cdot)$ (a PRF), or $\mathcal{O} = f(\cdot)$ (a random function)
- The CPA-security adversary \mathcal{A}_c (who breaks the lemma):
 - \mathcal{A}_c plays the CPA-security game against either Π or $\tilde{\Pi}$

The Two Adversaries

$PRF_{\mathcal{D},F}(n)$

- The challenger chooses $b \leftarrow \{0,1\}$.
If $b = 0$, he chooses $f \leftarrow \mathcal{F}_n$ and gives \mathcal{D} an oracle $\mathcal{O} = f$.
if $b = 1$, he chooses $k \leftarrow \{0,1\}^n$, and gives \mathcal{D} an oracle $\mathcal{O} = F_k$.
- With access to oracle \mathcal{O} , the distinguisher \mathcal{D} outputs a bit b'
- $PRF_{\mathcal{D},F}(n) = 1$ (i.e., \mathcal{D} wins) if $b' = b$

$PrivK_{\mathcal{A},n}^{cpa}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0,1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot)}$ outputs a guess bit b'
- We say that $PrivK_{\mathcal{A},n}^{cpa}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

We have to consider two adversaries, \mathcal{A}_r and \mathcal{A}_c

- The PRF adversary \mathcal{A}_r :
 - \mathcal{A}_r is playing the PRF security game
 - \mathcal{A}_r is given oracle $\mathcal{O} : \{0,1\}^n \rightarrow \{0,1\}^n$ where either $\mathcal{O} = F_k(\cdot)$ (a PRF), or $\mathcal{O} = f(\cdot)$ (a random function)
- The CPA-security adversary \mathcal{A}_c (who breaks the lemma):
 - \mathcal{A}_c plays the CPA-security game against either Π or $\tilde{\Pi}$
 - to answer encryption queries – The $\text{Enc}(\cdot)$ oracle given to \mathcal{A}_c in Π uses F_k and the oracle in $\tilde{\Pi}$ uses f

The Two Adversaries

$PRF_{D,F}(n)$

- The challenger chooses $b \leftarrow \{0, 1\}$.
If $b = 0$, he chooses $f \leftarrow \mathcal{F}_n$ and gives \mathcal{D} an oracle $\mathcal{O} = f$.
if $b = 1$, he chooses $k \leftarrow \{0, 1\}^n$, and gives \mathcal{D} an oracle $\mathcal{O} = F_k$.
- With access to oracle \mathcal{O} , the distinguisher \mathcal{D} outputs a bit b'
- $PRF_{D,F}(n) = 1$ (i.e., \mathcal{D} wins) if $b' = b$

$PrivK_{A,n}^{CPA}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot)}$ outputs a guess bit b'
- We say that $PrivK_{A,n}^{CPA}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

We have to consider two adversaries, \mathcal{A}_r and \mathcal{A}_c

- The PRF adversary \mathcal{A}_r :
 - \mathcal{A}_r is playing the PRF security game
 - \mathcal{A}_r is given oracle $\mathcal{O} : \{0, 1\}^n \rightarrow \{0, 1\}^n$ where either $\mathcal{O} = F_k(\cdot)$ (a PRF), or $\mathcal{O} = f(\cdot)$ (a random function)
- The CPA-security adversary \mathcal{A}_c (who breaks the lemma):
 - \mathcal{A}_c plays the CPA-security game against either Π or $\tilde{\Pi}$
 - to answer encryption queries – The $\text{Enc}(\cdot)$ oracle given to \mathcal{A}_c in Π uses F_k and the oracle in $\tilde{\Pi}$ uses f
 - We care about the *difference* in \mathcal{A}_c 's WIN probability

Constructing $\mathcal{A}_r^{\mathcal{O}}$: Intuition

- \mathcal{A}_r needs to use \mathcal{A}_c to win PRF game

Constructing $\mathcal{A}_r^{\mathcal{O}}$: Intuition

- \mathcal{A}_r needs to use \mathcal{A}_c to win PRF game
- \mathcal{A}_r acts as the challenger for \mathcal{A}_c in CPA-security game

Constructing $\mathcal{A}_r^{\mathcal{O}}$: Intuition

- \mathcal{A}_r needs to use \mathcal{A}_c to win PRF game
- \mathcal{A}_r acts as the challenger for \mathcal{A}_c in CPA-security game
 - \mathcal{A}_r must answer \mathcal{A}_c 's $\text{Enc}(\cdot)$ queries (i.e., simulate the Enc oracle)
 - \mathcal{A}_r must produce the challenge ciphertext c

Constructing $\mathcal{A}_r^{\mathcal{O}}$: Intuition

- \mathcal{A}_r needs to use \mathcal{A}_c to win PRF game
- \mathcal{A}_r acts as the challenger for \mathcal{A}_c in CPA-security game
 - \mathcal{A}_r must answer \mathcal{A}_c 's $\text{Enc}(\cdot)$ queries (i.e., simulate the Enc oracle)
 - \mathcal{A}_r must produce the challenge ciphertext c
- If \mathcal{A}_c WINS, \mathcal{A}_r must use that to win the game against his challenger

Constructing $\mathcal{A}_r^{\mathcal{O}}$

① Pre-Challenge

Run $\mathcal{A}_c(1^n)$ and when \mathcal{A}_c asks $\text{Enc}(m)$ query

- Choose $r \leftarrow \{0, 1\}^n$, query $y = \mathcal{O}(r)$, return $c = (r, y \oplus m)$ to \mathcal{A}_c

Constructing $\mathcal{A}_r^{\mathcal{O}}$

1 Pre-Challenge

Run $\mathcal{A}_c(1^n)$ and when \mathcal{A}_c asks $\text{Enc}(m)$ query

- Choose $r \leftarrow \{0, 1\}^n$, query $y = \mathcal{O}(r)$, return $c = (r, y \oplus m)$ to \mathcal{A}_c

2 Challenge

When \mathcal{A}_c outputs (m_0, m_1)

- Choose $b \leftarrow \{0, 1\}$
- Choose $r \leftarrow \{0, 1\}^n$, query $y = \mathcal{O}(r)$, return $c = (r, y \oplus m_b)$ as the challenge

Constructing $\mathcal{A}_r^{\mathcal{O}}$

1 Pre-Challenge

Run $\mathcal{A}_c(1^n)$ and when \mathcal{A}_c asks $\text{Enc}(m)$ query

- Choose $r \leftarrow \{0, 1\}^n$, query $y = \mathcal{O}(r)$, return $c = (r, y \oplus m)$ to \mathcal{A}_c

2 Challenge

When \mathcal{A}_c outputs (m_0, m_1)

- Choose $b \leftarrow \{0, 1\}$
- Choose $r \leftarrow \{0, 1\}^n$, query $y = \mathcal{O}(r)$, return $c = (r, y \oplus m_b)$ as the challenge

3 Post-Challenge

Continue answering Enc queries until \mathcal{A}_c outputs guess b'

- Output 1 (“PRF”) if $b = b'$, and 0 otherwise.

Observation

- If \mathcal{O} is f , then \mathcal{A}_r is simulating $\tilde{\Pi}$
- If \mathcal{O} is F_k , then \mathcal{A}_r is simulating Π

Analysis of \mathcal{A}_r 's success

There are two cases to analyze:

Analysis of \mathcal{A}_r 's success

There are two cases to analyze:

- Case 1: $\mathcal{O} = F_k$ (i.e., $b = 1$ in PRF game)

Analysis of \mathcal{A}_r 's success

There are two cases to analyze:

- Case 1: $\mathcal{O} = F_k$ (i.e., $b = 1$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $F_k(r) \oplus m$

Analysis of \mathcal{A}_r 's success

There are two cases to analyze:

- Case 1: $\mathcal{O} = F_k$ (i.e., $b = 1$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $F_k(r) \oplus m$
 - This is exactly the CPA-security game vs. Π

Analysis of \mathcal{A}_r 's success

There are two cases to analyze:

- Case 1: $\mathcal{O} = F_k$ (i.e., $b = 1$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $F_k(r) \oplus m$
 - This is exactly the CPA-security game vs. Π
 - Since \mathcal{A}_r output 1 when \mathcal{A}_c WINS, we have

$$\Pr_{k \leftarrow \{0,1\}^n} [\mathcal{A}_r^{F_k(\cdot)}(1^n) = 1] = \Pr[\text{PrivK}_{\mathcal{A}_c, \Pi}^{cpa}(n) = 1]$$

Analysis of \mathcal{A}_r 's success

There are two cases to analyze:

- Case 1: $\mathcal{O} = F_k$ (i.e., $b = 1$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $F_k(r) \oplus m$
 - This is exactly the CPA-security game vs. Π
 - Since \mathcal{A}_r output 1 when \mathcal{A}_c WINS, we have

$$\Pr_{k \leftarrow \{0,1\}^n} [\mathcal{A}_r^{F_k(\cdot)}(1^n) = 1] = \Pr[\text{PrivK}_{\mathcal{A}_c, \Pi}^{cpa}(n) = 1]$$

- Case 2: $\mathcal{O} = f$ (i.e., $b = 0$ in PRF game)

Analysis of \mathcal{A}_r 's success

There are two cases to analyze:

- Case 1: $\mathcal{O} = F_k$ (i.e., $b = 1$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $F_k(r) \oplus m$
 - This is exactly the CPA-security game vs. Π
 - Since \mathcal{A}_r output 1 when \mathcal{A}_c WINS, we have

$$\Pr_{k \leftarrow \{0,1\}^n} [\mathcal{A}_r^{F_k(\cdot)}(1^n) = 1] = \Pr[\text{PrivK}_{\mathcal{A}_c, \Pi}^{cpa}(n) = 1]$$

- Case 2: $\mathcal{O} = f$ (i.e., $b = 0$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $f(r) \oplus m$

Analysis of \mathcal{A}_r 's success

There are two cases to analyze:

- Case 1: $\mathcal{O} = F_k$ (i.e., $b = 1$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $F_k(r) \oplus m$
 - This is exactly the CPA-security game vs. Π
 - Since \mathcal{A}_r output 1 when \mathcal{A}_c WINS, we have

$$\Pr_{k \leftarrow \{0,1\}^n} [\mathcal{A}_r^{F_k(\cdot)}(1^n) = 1] = \Pr[\text{PrivK}_{\mathcal{A}_c, \Pi}^{cpa}(n) = 1]$$

- Case 2: $\mathcal{O} = f$ (i.e., $b = 0$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $f(r) \oplus m$
 - This is exactly the CPA-security game vs. $\tilde{\Pi}$

Analysis of \mathcal{A}_r 's success

There are two cases to analyze:

- Case 1: $\mathcal{O} = F_k$ (i.e., $b = 1$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $F_k(r) \oplus m$
 - This is exactly the CPA-security game vs. Π
 - Since \mathcal{A}_r output 1 when \mathcal{A}_c WINS, we have

$$\Pr_{k \leftarrow \{0,1\}^n} [\mathcal{A}_r^{F_k(\cdot)}(1^n) = 1] = \Pr[\text{PrivK}_{\mathcal{A}_c, \Pi}^{cpa}(n) = 1]$$

- Case 2: $\mathcal{O} = f$ (i.e., $b = 0$ in PRF game)
 - \mathcal{A}_r answers all Enc queries and produces c with $f(r) \oplus m$
 - This is exactly the CPA-security game vs. $\tilde{\Pi}$
 - Since \mathcal{A}_r output 1 when \mathcal{A}_c WINS, we have

$$\Pr_{f \leftarrow \mathcal{F}_n} [\mathcal{A}_r^{f(\cdot)}(1^n) = 1] = \Pr[\text{PrivK}_{\mathcal{A}_c, \tilde{\Pi}}^{cpa}(n) = 1]$$

Analysis of \mathcal{A}_r 's success

- We assumed that \mathcal{A}_c breaks the lemma – i.e. has different success probability vs. Π and $\tilde{\Pi}$

$$\left| \Pr[\text{PrivK}_{\mathcal{A}_c, \Pi}^{cpa}(n) = 1] - \Pr[\text{PrivK}_{\mathcal{A}_c, \tilde{\Pi}}^{cpa}(n) = 1] \right| > 1/\text{poly}(n)$$

Analysis of \mathcal{A}_r 's success

- We assumed that \mathcal{A}_c breaks the lemma – i.e. has different success probability vs. Π and $\tilde{\Pi}$

$$\left| \Pr[\text{PrivK}_{\mathcal{A}_c, \Pi}^{cpa}(n) = 1] - \Pr[\text{PrivK}_{\mathcal{A}_c, \tilde{\Pi}}^{cpa}(n) = 1] \right| > 1/\text{poly}(n)$$

- By the last slide, this implies that

$$\left| \Pr_{k \leftarrow \{0,1\}^n}[\mathcal{A}_r^{F_k(\cdot)}(1^n) = 1] - \Pr_{f \leftarrow \mathcal{F}_n}[\mathcal{A}_r^{f(\cdot)}(1^n) = 1] \right| > 1/\text{poly}(n)$$

Analysis of \mathcal{A}_r 's success

- We assumed that \mathcal{A}_c breaks the lemma – i.e. has different success probability vs. Π and $\tilde{\Pi}$

$$\left| \Pr[\text{PrivK}_{\mathcal{A}_c, \Pi}^{cpa}(n) = 1] - \Pr[\text{PrivK}_{\mathcal{A}_c, \tilde{\Pi}}^{cpa}(n) = 1] \right| > 1/\text{poly}(n)$$

- By the last slide, this implies that

$$\left| \Pr_{k \leftarrow \{0,1\}^n}[\mathcal{A}_r^{F_k(\cdot)}(1^n) = 1] - \Pr_{f \leftarrow \mathcal{F}_n}[\mathcal{A}_r^{f(\cdot)}(1^n) = 1] \right| > 1/\text{poly}(n)$$

- That is, \mathcal{A}_r is able to distinguish between $F_k(\cdot)$ and $f(\cdot)$. But, we know that F_k is a PRF.

Contradiction!

To prove security from a PRF, we often do the following:

- ✓ Consider the scheme where F_k is replaced by a random function f
 - Show by reduction to security of PRF, that \mathcal{A} can't tell we made this change.
 - So, \mathcal{A} 's success probability must be (essentially) the same in this and original variant.
- ② Use a probabilistic argument to prove that scheme is unconditionally secure when using a random function f .
 - Random function is essentially a collection of 2^n OTPs
 - Proof is similar to proof of OTP, but need to account for probability of collision in r

Proving CPA-security of $\tilde{\Pi}$

Lemma

For any \mathcal{A} making at most $q(n)$ queries to $\text{Enc}(\cdot)$

$$\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \leq 1/2 + \frac{q(n)}{2^n}$$

Proving CPA-security of $\tilde{\Pi}$

Lemma

For any \mathcal{A} making at most $q(n)$ queries to $\text{Enc}(\cdot)$

$$\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \leq 1/2 + \frac{q(n)}{2^n}$$

- Recall that $\tilde{\Pi}$ encrypts as $c = (r, f(r) \oplus m)$

Proving CPA-security of $\tilde{\Pi}$

Lemma

For any \mathcal{A} making at most $q(n)$ queries to $\text{Enc}(\cdot)$

$$\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \leq 1/2 + \frac{q(n)}{2^n}$$

- Recall that $\tilde{\Pi}$ encrypts as $c = (r, f(r) \oplus m)$
- Let r^* be the randomness used to encrypt the challenge

Proving CPA-security of $\tilde{\Pi}$

Lemma

For any \mathcal{A} making at most $q(n)$ queries to $\text{Enc}(\cdot)$

$$\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \leq 1/2 + \frac{q(n)}{2^n}$$

- Recall that $\tilde{\Pi}$ encrypts as $c = (r, f(r) \oplus m)$
- Let r^* be the randomness used to encrypt the challenge
- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries

Proving CPA-security of $\tilde{\Pi}$

Lemma

For any \mathcal{A} making at most $q(n)$ queries to $\text{Enc}(\cdot)$

$$\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \leq 1/2 + \frac{q(n)}{2^n}$$

- Recall that $\tilde{\Pi}$ encrypts as $c = (r, f(r) \oplus m)$
- Let r^* be the randomness used to encrypt the challenge
- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - \mathcal{A} knows nothing about $f(r^*)$, so $f(r^*)$ is random (good OTP)
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$

Proving CPA-security of $\tilde{\Pi}$

Lemma

For any \mathcal{A} making at most $q(n)$ queries to $\text{Enc}(\cdot)$

$$\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \leq 1/2 + \frac{q(n)}{2^n}$$

- Recall that $\tilde{\Pi}$ encrypts as $c = (r, f(r) \oplus m)$
- Let r^* be the randomness used to encrypt the challenge
- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - \mathcal{A} knows nothing about $f(r^*)$, so $f(r^*)$ is random (good OTP)
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries

Proving CPA-security of $\tilde{\Pi}$

Lemma

For any \mathcal{A} making at most $q(n)$ queries to $\text{Enc}(\cdot)$

$$\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] \leq 1/2 + \frac{q(n)}{2^n}$$

- Recall that $\tilde{\Pi}$ encrypts as $c = (r, f(r) \oplus m)$
- Let r^* be the randomness used to encrypt the challenge
- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - \mathcal{A} knows nothing about $f(r^*)$, so $f(r^*)$ is random (good OTP)
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - \mathcal{A} learns value of $f(r^*)$ (he sees $c = (r^*, c')$, computes $f(r^*) = c' \oplus m$)
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$

Proving CPA-security of $\tilde{\Pi}$

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$

Proving CPA-security of $\tilde{\Pi}$

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$

Claim: $\Pr[\text{Case 2}] \leq \text{negl}(n)$

Proving CPA-security of $\tilde{\Pi}$

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$

Claim: $\Pr[\text{Case 2}] \leq \text{negl}(n)$

- We said that \mathcal{A} makes at most $q(n) = \text{poly}(n)$ Enc queries

Proving CPA-security of $\tilde{\Pi}$

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$

Claim: $\Pr[\text{Case 2}] \leq \text{negl}(n)$

- We said that \mathcal{A} makes at most $q(n) = \text{poly}(n)$ Enc queries
- On each Enc query, randomness $r_i \leftarrow \{0, 1\}^n$

Proving CPA-security of $\tilde{\Pi}$

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$

Claim: $\Pr[\text{Case 2}] \leq \text{negl}(n)$

- We said that \mathcal{A} makes at most $q(n) = \text{poly}(n)$ Enc queries
- On each Enc query, randomness $r_i \leftarrow \{0, 1\}^n$
- In encrypting challenge, $r^* \leftarrow \{0, 1\}^n$

Proving CPA-security of $\tilde{\Pi}$

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$

Claim: $\Pr[\text{Case 2}] \leq \text{negl}(n)$

- We said that \mathcal{A} makes at most $q(n) = \text{poly}(n)$ Enc queries
- On each Enc query, randomness $r_i \leftarrow \{0, 1\}^n$
- In encrypting challenge, $r^* \leftarrow \{0, 1\}^n$
- So,

$$\Pr[r^* \in \{r_1, \dots, r_{q(n)}\}] \leq \sum_{i=1}^{q(n)} \Pr[r^* = r_i] = \frac{q(n)}{2^n} \leq \text{negl}(n)$$

Proving CPA-security of $\tilde{\Pi}$: Putting It Together

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$
 - Occurs with probability at most $q(n)/2^n$

Proving CPA-security of $\tilde{\Pi}$: Putting It Together

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$
 - Occurs with probability at most $q(n)/2^n$

$$\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] = \Pr[\mathcal{A} \text{ WINS} \wedge \text{Case 1}] + \Pr[\mathcal{A} \text{ WINS} \wedge \text{Case 2}]$$

Proving CPA-security of $\tilde{\Pi}$: Putting It Together

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$
 - Occurs with probability at most $q(n)/2^n$

$$\begin{aligned}\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{cpa}(n) = 1] &= \Pr[\mathcal{A} \text{ WINS} \wedge \text{Case 1}] + \Pr[\mathcal{A} \text{ WINS} \wedge \text{Case 2}] \\ &\leq \Pr[\mathcal{A} \text{ WINS} \mid \text{Case 1}] \cdot \Pr[\text{Case 1}] + \Pr[\text{Case 2}]\end{aligned}$$

Proving CPA-security of $\tilde{\Pi}$: Putting It Together

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$
 - Occurs with probability at most $q(n)/2^n$

$$\begin{aligned}\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] &= \Pr[\mathcal{A} \text{ WINS} \wedge \text{Case 1}] + \Pr[\mathcal{A} \text{ WINS} \wedge \text{Case 2}] \\ &\leq \Pr[\mathcal{A} \text{ WINS} \mid \text{Case 1}] \cdot \Pr[\text{Case 1}] + \Pr[\text{Case 2}] \\ &\leq \Pr[\mathcal{A} \text{ WINS} \mid \text{Case 1}] + \Pr[\text{Case 2}]\end{aligned}$$

Proving CPA-security of $\tilde{\Pi}$: Putting It Together

- Case 1: r^* is never used when answering \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1/2$
- Case 2: r^* is used when answering one of \mathcal{A} 's Enc queries
 - $\Pr[\mathcal{A} \text{ outputs } b = b'] = 1$
 - Occurs with probability at most $q(n)/2^n$

$$\begin{aligned}\Pr[\text{PrivK}_{\mathcal{A}, \tilde{\Pi}}^{\text{cpa}}(n) = 1] &= \Pr[\mathcal{A} \text{ WINS} \wedge \text{Case 1}] + \Pr[\mathcal{A} \text{ WINS} \wedge \text{Case 2}] \\ &\leq \Pr[\mathcal{A} \text{ WINS} \mid \text{Case 1}] \cdot \Pr[\text{Case 1}] + \Pr[\text{Case 2}] \\ &\leq \Pr[\mathcal{A} \text{ WINS} \mid \text{Case 1}] + \Pr[\text{Case 2}] \\ &\leq 1/2 + \frac{q(n)}{2^n}\end{aligned}$$

Finishing Proof of CPA-security of PRF+OTP

- ✓ Consider the scheme where F_k is replaced by a random function f
 - We showed that any PPT \mathcal{A} has only a $\text{negl}(n)$ advantage in distinguishing the two games
- ✓ Use a probabilistic argument to prove that scheme is unconditionally secure when using a random function f .
 - We showed that PPT \mathcal{A} WINS with probability $\leq 1/2 + q(n)/2^n$

Finishing Proof of CPA-security of PRF+OTP

- ✓ Consider the scheme where F_k is replaced by a random function f
 - We showed that any PPT \mathcal{A} has only a $\text{negl}(n)$ advantage in distinguishing the two games
- ✓ Use a probabilistic argument to prove that scheme is unconditionally secure when using a random function f .
 - We showed that PPT \mathcal{A} WINS with probability $\leq 1/2 + q(n)/2^n$

Combining these two statements, we get that for any PPT \mathcal{A} ,

$$\Pr[\text{PrivK}_{\mathcal{A}, \text{PRF+OTP}}^{\text{cpa}}(n) = 1] \leq 1/2 + \frac{q(n)}{2^n} + \text{negl}(n)$$

- 1 Lecture 8 Review
- 2 Security of PRF+OTP (Chapter 3.5.2)
- 3 Modes of Operation (Chapter 3.6.2)

Encrypting Long Messages

CPA-secure encryption allows us to

- Encrypt many messages using the same key k

Encrypting Long Messages

CPA-secure encryption allows us to

- Encrypt many messages using the same key k
- Encrypt messages longer than the key k

Encrypting Long Messages

CPA-secure encryption allows us to

- Encrypt many messages using the same key k
- Encrypt messages longer than the key k

Are we done?

Encrypting Long Messages

Consider how we encrypt long messages:

Encrypting Long Messages

Consider how we encrypt long messages:

- Break m into blocks m_1, \dots, m_ℓ such that $|m_i| = n$
- Encrypt each block separately using key k .

Encrypting Long Messages

Consider how we encrypt long messages:

- Break m into blocks m_1, \dots, m_ℓ such that $|m_i| = n$
- Encrypt each block separately using key k .

Now, suppose we do this using PRF+OTP encryption

Encrypting Long Messages

Consider how we encrypt long messages:

- Break m into blocks m_1, \dots, m_ℓ such that $|m_i| = n$
- Encrypt each block separately using key k .

Now, suppose we do this using PRF+OTP encryption

$$\begin{aligned}\text{Enc}_k(m) &= \text{Enc}_k(m_1), \text{Enc}_k(m_2), \dots, \text{Enc}_k(m_\ell) \\ &= (r_1, F_k(r_1) \oplus m_1), (r_2, F_k(r_2) \oplus m_2), \dots, (r_\ell, F_k(r_\ell) \oplus m_\ell)\end{aligned}$$

Encrypting Long Messages

Consider how we encrypt long messages:

- Break m into blocks m_1, \dots, m_ℓ such that $|m_i| = n$
- Encrypt each block separately using key k .

Now, suppose we do this using PRF+OTP encryption

$$\begin{aligned}\text{Enc}_k(m) &= \text{Enc}_k(m_1), \text{Enc}_k(m_2), \dots, \text{Enc}_k(m_\ell) \\ &= (r_1, F_k(r_1) \oplus m_1), (r_2, F_k(r_2) \oplus m_2), \dots, (r_\ell, F_k(r_\ell) \oplus m_\ell)\end{aligned}$$

The problem:

Encrypting Long Messages

Consider how we encrypt long messages:

- Break m into blocks m_1, \dots, m_ℓ such that $|m_i| = n$
- Encrypt each block separately using key k .

Now, suppose we do this using PRF+OTP encryption

$$\begin{aligned}\text{Enc}_k(m) &= \text{Enc}_k(m_1), \text{Enc}_k(m_2), \dots, \text{Enc}_k(m_\ell) \\ &= (r_1, F_k(r_1) \oplus m_1), (r_2, F_k(r_2) \oplus m_2), \dots, (r_\ell, F_k(r_\ell) \oplus m_\ell)\end{aligned}$$

The problem:

- $|c| = 2|m|$ (we have doubled the length of plaintext)

Encrypting Long Messages

Consider how we encrypt long messages:

- Break m into blocks m_1, \dots, m_ℓ such that $|m_i| = n$
- Encrypt each block separately using key k .

Now, suppose we do this using PRF+OTP encryption

$$\begin{aligned}\text{Enc}_k(m) &= \text{Enc}_k(m_1), \text{Enc}_k(m_2), \dots, \text{Enc}_k(m_\ell) \\ &= (r_1, F_k(r_1) \oplus m_1), (r_2, F_k(r_2) \oplus m_2), \dots, (r_\ell, F_k(r_\ell) \oplus m_\ell)\end{aligned}$$

The problem:

- $|c| = 2|m|$ (we have doubled the length of plaintext)
- This is very problematic when sending big files (e.g., movies) or for HD encryption

Encrypting Long Messages

Consider how we encrypt long messages:

- Break m into blocks m_1, \dots, m_ℓ such that $|m_i| = n$
- Encrypt each block separately using key k .

Now, suppose we do this using PRF+OTP encryption

$$\begin{aligned}\text{Enc}_k(m) &= \text{Enc}_k(m_1), \text{Enc}_k(m_2), \dots, \text{Enc}_k(m_\ell) \\ &= (r_1, F_k(r_1) \oplus m_1), (r_2, F_k(r_2) \oplus m_2), \dots, (r_\ell, F_k(r_\ell) \oplus m_\ell)\end{aligned}$$

The problem:

- $|c| = 2|m|$ (we have doubled the length of plaintext)
- This is very problematic when sending big files (e.g., movies) or for HD encryption

The Question

How do we encrypt long messages without this 2X increase in size

Block-Cipher Modes of Operations

- Modes of operation study how to encrypt many block messages without blow-up in size

Block-Cipher Modes of Operations

- Modes of operation study how to encrypt many block messages without blow-up in size
- Combine PRFs, Boolean operations, and randomness to achieve this

Block-Cipher Modes of Operations

- Modes of operation study how to encrypt many block messages without blow-up in size
- Combine PRFs, Boolean operations, and randomness to achieve this
- Can think of them as other ways to turn PRF into CPA-secure encryption

Modes of Operations: Important Properties

- Ciphertext length – what is the increase between $|c|$ and $|m|$

Modes of Operations: Important Properties

- Ciphertext length – what is the increase between $|c|$ and $|m|$
- Pre-computation – can some part of encryption procedure be computed without m

Modes of Operations: Important Properties

- Ciphertext length – what is the increase between $|c|$ and $|m|$
- Pre-computation – can some part of encryption procedure be computed without m
- Encryption/Decryption parallelism - can we encrypt/decrypt only part of m , or encrypt blocks in parallel


Modes of Operations: Important Properties

- Ciphertext length – what is the increase between $|c|$ and $|m|$
- Pre-computation – can some part of encryption procedure be computed without m
- Encryption/Decryption parallelism - can we encrypt/decrypt only part of m , or encrypt blocks in parallel
- PRF Inverse – do we need to be able to invert the PRF (i.e., do we need a PRP)


Modes of Operations: Important Properties

- Ciphertext length – what is the increase between $|c|$ and $|m|$
- Pre-computation – can some part of encryption procedure be computed without m
- Encryption/Decryption parallelism - can we encrypt/decrypt only part of m , or encrypt blocks in parallel
- PRF Inverse – do we need to be able to invert the PRF (i.e., do we need a PRP)
- Security - want at least CPA-security

Electronic Code Book (ECB) Mode




Electronic Code Book (ECB) Mode



- Ciphertext length: $|c| = |m|$
- Pre-computation: N/A
- Parallelism: Can encrypt/decrypt blocks in parallel
- PRF Inverse: Need to compute inverse to decrypt
- Security: ??

Electronic Code Book (ECB) Mode



- Ciphertext length: $|c| = |m|$
- Pre-computation: N/A
- Parallelism: Can encrypt/decrypt blocks in parallel
- PRF Inverse: Need to compute inverse to decrypt
- Security: NOT SECURE
 - ECB Mode is deterministic
 - Can tell if two blocks are the same

Electronic Code Book (ECB) Mode: How bad is it?




Figure: Original Image

Electronic Code Book (ECB) Mode: How bad is it?





Figure: Original Image Figure: ECB-encrypted

Electronic Code Book (ECB) Mode: How bad is it?






Figure: Original Image Figure: ECB-encrypted


Warning

Never use ECB mode

Cipher Block Chaining (CBC) Mode




Cipher Block Chaining (CBC) Mode




- Ciphertext length: $|c| = |m| + 1$ blocks
- Pre-computation: N/A
- Parallelism: Encryption / Decryption sequential
- PRF inverse: Need to compute inverse to decrypt
- Security: CPA-secure

Output Feedback (OFB) Mode




Output Feedback (OFB) Mode




- Ciphertext length: $|c| = |m| + 1$ blocks
- Pre-computation: Can pre-compute entire pad
- Parallelism: If have pad, all encryption/decryption can be parallel
- PRF inverse: No need to compute inverse to decrypt
- Security: CPA-secure

Counter (CTR) Mode



Counter (CTR) Mode



- Ciphertext length: $|c| = |m| + 1$ blocks
- Pre-computation: Can pre-compute entire pad (or any part of pad)
- Parallelism: Can encrypt/decrypt any blocks in parallel
- PRF inverse: No need to compute inverse to decrypt
- Security: CPA-secure