

Cryptography

Lecture 10

Arkady Yerukhimovich

September 30, 2024

1 ⁹ ~~Lecture 8~~ Review

2 Chosen-ciphertext Attack (CCA) Security (Chapter 3.7)

3 Importance of CCA Security (Chapter 3.7)

Lecture 8 Review

- Proof of CPA-security for PRF+OTP
- Modes of operations

- 1 Lecture 8 Review
- 2 Chosen-ciphertext Attack (CCA) Security (Chapter 3.7)
- 3 Importance of CCA Security (Chapter 3.7)

Chosen-ciphertext Attack

- CPA security captures scenario where \mathcal{A} may trick parties to encrypt messages on his behalf

Chosen-ciphertext Attack

- CPA security captures scenario where \mathcal{A} may trick parties to encrypt messages on his behalf
- But what if \mathcal{A} can also trick parties to decrypt (some) ciphertexts for him.

Chosen-ciphertext Attack

- CPA security captures scenario where \mathcal{A} may trick parties to encrypt messages on his behalf
- But what if \mathcal{A} can also trick parties to decrypt (some) ciphertexts for him.
 - May be enough to just get partial decryptions
 - Security against such an attack is not addressed by CPA security

Chosen-ciphertext Attack

- CPA security captures scenario where \mathcal{A} may trick parties to encrypt messages on his behalf
- But what if \mathcal{A} can also trick parties to decrypt (some) ciphertexts for him.
 - May be enough to just get partial decryptions
 - Security against such an attack is not addressed by CPA security
- Want undecrypted messages to remain secure

Is PRF+OTP CCA Secure?

PRF+OTP Encryption

- $\text{Gen}(1^n)$: $k \leftarrow \{0, 1\}^n$
- $\text{Enc}(k, m)$: Choose $r \leftarrow \{0, 1\}^n$, output $c = (r, F_k(r) \oplus m)$
- $\text{Dec}(k, c)$: Parse c as (r, c') , compute $m = F_k(r) \oplus c'$

Is this CCA Secure?

Is PRF+OTP CCA Secure?

PRF+OTP Encryption

- $\text{Gen}(1^n)$: $k \leftarrow \{0,1\}^n$
- $\text{Enc}(k, m)$: Choose $r \leftarrow \{0,1\}^n$, output $c = (r, F_k(r) \oplus m)$
- $\text{Dec}(k, c)$: Parse c as (r, c') , compute $m = F_k(r) \oplus c'$

The Attack:

- \mathcal{A} receives ciphertext $c = (r^*, F_k(r^*) \oplus m)$

Is PRF+OTP CCA Secure?

PRF+OTP Encryption

- $\text{Gen}(1^n)$: $k \leftarrow \{0,1\}^n$
- $\text{Enc}(k, m)$: Choose $r \leftarrow \{0,1\}^n$, output $c = (r, F_k(r) \oplus m)$
- $\text{Dec}(k, c)$: Parse c as (r, c') , compute $m = F_k(r) \oplus c'$

The Attack:

- \mathcal{A} receives ciphertext $c = (r^*, F_k(r^*) \oplus m)$
- \mathcal{A} constructs forged ciphertext $\bar{c} = (r^*, 0^n)$, and queries $\text{Dec}_k(\bar{c})$

Is PRF+OTP CCA Secure?

PRF+OTP Encryption

- $\text{Gen}(1^n)$: $k \leftarrow \{0,1\}^n$
- $\text{Enc}(k, m)$: Choose $r \leftarrow \{0,1\}^n$, output $c = (r, F_k(r) \oplus m)$
- $\text{Dec}(k, c)$: Parse c as (r, c') , compute $m = F_k(r) \oplus c'$

The Attack:

- \mathcal{A} receives ciphertext $c = (r^*, F_k(r^*) \oplus m)$
- \mathcal{A} constructs forged ciphertext $\bar{c} = (r^*, 0^n)$, and queries $\text{Dec}_k(\bar{c})$
- $\text{Dec}_k(\bar{c})$ returns $\bar{m} = F_k(r^*) \oplus 0^n = F_k(r^*)$

Is PRF+OTP CCA Secure?

PRF+OTP Encryption

- $\text{Gen}(1^n)$: $k \leftarrow \{0,1\}^n$
- $\text{Enc}(k, m)$: Choose $r \leftarrow \{0,1\}^n$, output $c = (r, F_k(r) \oplus m)$
- $\text{Dec}(k, c)$: Parse c as (r, c') , compute $m = F_k(r) \oplus c'$

The Attack:

- \mathcal{A} receives ciphertext $c = (r^*, F_k(r^*) \oplus m)$
- \mathcal{A} constructs forged ciphertext $\bar{c} = (r^*, 0^n)$, and queries $\text{Dec}_k(\bar{c})$
- $\text{Dec}_k(\bar{c})$ returns $\bar{m} = F_k(r^*) \oplus 0^n = F_k(r^*)$
- \mathcal{A} can now use $F_k(r^*)$ to decrypt c

Is PRF+OTP CCA Secure?

PRF+OTP Encryption

- $\text{Gen}(1^n)$: $k \leftarrow \{0,1\}^n$
- $\text{Enc}(k, m)$: Choose $r \leftarrow \{0,1\}^n$, output $c = (r, F_k(r) \oplus m)$
- $\text{Dec}(k, c)$: Parse c as (r, c') , compute $m = F_k(r) \oplus c'$

The Attack:

- \mathcal{A} receives ciphertext $c = (r^*, F_k(r^*) \oplus m)$
- \mathcal{A} constructs forged ciphertext $\bar{c} = (r^*, 0^n)$, and queries $\text{Dec}_k(\bar{c})$
- $\text{Dec}_k(\bar{c})$ returns $\bar{m} = F_k(r^*) \oplus 0^n = F_k(r^*)$
- \mathcal{A} can now use $F_k(r^*)$ to decrypt c

Takeaway

PRF+OTP is not CCA-Secure

Defining CCA-Secure Encryption

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

Defining CCA-Secure Encryption

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cca}}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$

Defining CCA-Secure Encryption

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cca}}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot), \text{Dec}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.

Defining CCA-Secure Encryption

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cca}}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot), \text{Dec}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}

Defining CCA-Secure Encryption

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cca}}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot), \text{Dec}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot), \text{Dec}_k(\cdot)}$ outputs a guess bit b' (\mathcal{A} may not query $\text{Dec}_k(c)$)

Defining CCA-Secure Encryption

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cca}}(n)$

- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot), \text{Dec}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot), \text{Dec}_k(\cdot)}$ outputs a guess bit b' (\mathcal{A} may not query $\text{Dec}_k(c)$)
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cca}}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

Defining CCA-Secure Encryption

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cca}}(n)$


- The challenger chooses $k \leftarrow \text{Gen}(1^n)$
- $\mathcal{A}^{\text{Enc}_k(\cdot), \text{Dec}_k(\cdot)}(1^n)$ outputs m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- $\mathcal{A}^{\text{Enc}_k(\cdot), \text{Dec}_k(\cdot)}$ outputs a guess bit b' (\mathcal{A} may not query $\text{Dec}_k(c)$)
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cca}}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

Definition: An encryption scheme $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space \mathcal{M} is CCA-secure if for all PPT \mathcal{A} it holds that


$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cca}}(n) = 1] \leq 1/2 + \text{negl}(n)$$

- 1 Lecture 8 Review
- 2 Chosen-ciphertext Attack (CCA) Security (Chapter 3.7)
- 3 Importance of CCA Security (Chapter 3.7)

Padding Oracle Attack on CBC Mode




Padding Oracle Attack on CBC Mode



- This assumes that $|m|$ is a multiple of block-length L .


Padding Oracle Attack on CBC Mode



- This assumes that $|m|$ is a multiple of block-length L .
- If it is not, standard approach is to pad m to a multiple of L
 - Need to be able to tell what is part of m and what is padding


Handwritten diagram illustrating padding:
A horizontal line is divided into segments. The first segment is labeled m_1 and the second is labeled m_2 . The third segment contains several zeros (0000) followed by a 1, representing padding.

Padding Oracle Attack on CBC Mode




- This assumes that $|m|$ is a multiple of block-length L .
- If it is not, standard approach is to pad m to a multiple of L
 - Need to be able to tell what is part of m and what is padding
 - Add 1 to L bytes to end of m to pad to next multiple of L .

Padding Oracle Attack on CBC Mode




- This assumes that $|m|$ is a multiple of block-length L .
- If it is not, standard approach is to pad m to a multiple of L
 - Need to be able to tell what is part of m and what is padding
 - Add 1 to L bytes to end of m to pad to next multiple of L .
 - To identify padding, pad value indicates number of Bytes of padding

Padding Oracle Attack on CBC Mode




- This assumes that $|m|$ is a multiple of block-length L .
- If it is not, standard approach is to pad m to a multiple of L
 - Need to be able to tell what is part of m and what is padding
 - Add 1 to L bytes to end of m to pad to next multiple of L .
 - To identify padding, pad value indicates number of Bytes of padding
 - Example: $m' = m || 0x2 || 0x2$ if need 2 Bytes of padding

Padding Oracle Attack on CBC Mode



- This assumes that $|m|$ is a multiple of block-length L .
- If it is not, standard approach is to pad m to a multiple of L
 - Need to be able to tell what is part of m and what is padding
 - Add 1 to L bytes to end of m to pad to next multiple of L .
 - To identify padding, pad value indicates number of Bytes of padding
 - Example: $m' = m || 0x2 || 0x2$ if need 2 Bytes of padding
- Decryption can then remove padding and return m
 - If padding incorrect, return “bad padding” error

Padding Oracle Attack on CBC Mode




- Consider encryption of a 2-block message m

Quiz


You will now develop an attack on this mode of operations.

Padding Oracle Attack on CBC Mode




- Consider encryption of a 2-block message m

Padding Oracle Attack on CBC Mode



- Consider encryption of a 2-block message m
- Note that $m_2 = F_k^{-1}(c_2) \oplus c_1$

Padding Oracle Attack on CBC Mode



- Consider encryption of a 2-block message m
- Note that $m_2 = F_k^{-1}(c_2) \oplus c_1$
 - If we change c_1 to $c'_1 = c_1 \oplus \delta$ without changing c_2 then, we change m_2 to $m'_2 = m_2 \oplus \delta$

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 1: Learn size of padding

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 1: Learn size of padding

- Change 1st Byte of c_1 (thus, also m_2) and see if error occurs
 - Error only occurs if $|pad| = L$

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 1: Learn size of padding

- Change 1st Byte of c_1 (thus, also m_2) and see if error occurs
 - Error only occurs if $|pad| = L$
- Change Bytes $2, \dots, L$ until first time we get error, this is first Byte of padding

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 2: Using knowledge of $b = |pad|$, decrypt m

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 2: Using knowledge of $b = |pad|$, decrypt m

- Change c_1 (and thus also m_2) by δ_i defined as

$$\delta_i = \underbrace{0x00 || \dots || 0x00 || 0x(i)}_{L-(b+1) \text{ Bytes}} || \underbrace{0x(b+1) || \dots || 0x(b+1)}_{b \text{ Bytes}} \oplus \underbrace{0x00 || \dots || 0x00 || 0x00}_{L-b \text{ Bytes}} || \underbrace{0xb || \dots || 0xb}_{b \text{ Bytes}}$$

Handwritten diagram illustrating the padding structure. It shows m' followed by four b 's. Brackets group the last three b 's. Arrows point from each b to a $b+1$ below it, indicating a carry or increment operation.

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 2: Using knowledge of $b = |pad|$, decrypt m

- Change c_1 (and thus also m_2) by δ_i defined as

$$\delta_i = \underbrace{0x00 || \dots || 0x00}_{L-(b+1) \text{ Bytes}} || 0x(i) || \underbrace{0x(b+1) || \dots || 0x(b+1)}_{b \text{ Bytes}} \oplus$$

$$\underbrace{0x00 || \dots || 0x00 || 0x00}_{L-b \text{ Bytes}} || \underbrace{0xb || \dots || 0xb}_{b \text{ Bytes}}$$

- $m_2 \oplus \delta_i = \underbrace{m_2^1 || \dots || m_2^{L-(b+1)}}_{L-(b+1) \text{ Bytes}} || (0x(i) \oplus m_2^{L-b}) || \underbrace{0x(b+1) || \dots}_{b \text{ Bytes}}$

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 2: Using knowledge of $b = |pad|$, decrypt m

- Change c_1 (and thus also m_2) by δ_i defined as

$$\delta_i = \underbrace{0x00 \parallel \dots \parallel 0x00}_{L-(b+1) \text{ Bytes}} \parallel 0x(i) \parallel \underbrace{0x(b+1) \parallel \dots \parallel 0x(b+1)}_{b \text{ Bytes}} \oplus \underbrace{0x00 \parallel \dots \parallel 0x00}_{L-b \text{ Bytes}} \parallel \underbrace{0xb \parallel \dots \parallel 0xb}_{b \text{ Bytes}}$$

- $m_2 \oplus \delta_i = \underbrace{m_2^1 \parallel \dots \parallel m_2^{L-(b+1)}}_{L-(b+1) \text{ Bytes}} \parallel (0x(i) \oplus m_2^{L-b}) \parallel \underbrace{0x(b+1) \parallel \dots}_{b \text{ Bytes}}$
- Will only decrypt correctly if $0xi \oplus m_2^{L-b} = 0x(b+1)$

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 2: Using knowledge of $b = |pad|$, decrypt m

- Change c_1 (and thus also m_2) by δ_i defined as

$$\delta_i = \underbrace{0x00 \parallel \dots \parallel 0x00}_{L-(b+1) \text{ Bytes}} \parallel 0x(i) \parallel \underbrace{0x(b+1) \parallel \dots \parallel 0x(b+1)}_{b \text{ Bytes}} \oplus \underbrace{0x00 \parallel \dots \parallel 0x00}_{L-b \text{ Bytes}} \parallel \underbrace{0xb \parallel \dots \parallel 0xb}_{b \text{ Bytes}}$$

- $m_2 \oplus \delta_i = \underbrace{m_2^1 \parallel \dots \parallel m_2^{L-(b+1)}}_{L-(b+1) \text{ Bytes}} \parallel (0x(i) \oplus m_2^{L-b}) \parallel \underbrace{0x(b+1) \parallel \dots}_{b \text{ Bytes}}$
- Will only decrypt correctly if $0xi \oplus m_2^{L-b} = 0x(b+1)$
 - Trying all 256 values for i , \mathcal{A} can learn m_2^{L-b} (a Byte of m)

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 2: Using knowledge of $b = |pad|$, decrypt m

- Change c_1 (and thus also m_2) by δ_i defined as

$$\delta_i = \underbrace{0x00 || \dots || 0x00}_{L-(b+1) \text{ Bytes}} || \underbrace{0x(i) || 0x(b+1) || \dots || 0x(b+1)}_{b \text{ Bytes}} \oplus \underbrace{0x00 || \dots || 0x00 || 0x00}_{L-b \text{ Bytes}} || \underbrace{0xb || \dots || 0xb}_{b \text{ Bytes}}$$

- $m_2 \oplus \delta_i = \underbrace{m_2^1 || \dots || m_2^{L-(b+1)}}_{L-(b+1) \text{ Bytes}} || (0x(i) \oplus m_2^{L-b}) || \underbrace{0x(b+1) || \dots}_{b \text{ Bytes}}$
- Will only decrypt correctly if $0xi \oplus m_2^{L-b} = 0x(b+1)$
 - Trying all 256 values for i , \mathcal{A} can learn m_2^{L-b} (a Byte of m)
- Repeat attack for all Bytes of m_2 by changing to appropriate padding

Padding Oracle Attack

Observation: We know that m_2 ends in $(0xb)$ repeated b times

Step 2: Using knowledge of $b = |pad|$, decrypt m

- Change c_1 (and thus also m_2) by δ_i defined as

$$\delta_i = \underbrace{0x00 \parallel \dots \parallel 0x00}_{L-(b+1) \text{ Bytes}} \parallel 0x(i) \parallel \underbrace{0x(b+1) \parallel \dots \parallel 0x(b+1)}_{b \text{ Bytes}} \oplus \underbrace{0x00 \parallel \dots \parallel 0x00}_{L-b \text{ Bytes}} \parallel \underbrace{0xb \parallel \dots \parallel 0xb}_{b \text{ Bytes}}$$

- $m_2 \oplus \delta_i = \underbrace{m_2^1 \parallel \dots \parallel m_2^{L-(b+1)}}_{L-(b+1) \text{ Bytes}} \parallel (0x(i) \oplus m_2^{L-b}) \parallel \underbrace{0x(b+1) \parallel \dots}_{b \text{ Bytes}}$
- Will only decrypt correctly if $0xi \oplus m_2^{L-b} = 0x(b+1)$
 - Trying all 256 values for i , \mathcal{A} can learn m_2^{L-b} (a Byte of m)
- Repeat attack for all Bytes of m_2 by changing to appropriate padding
- Can mount similar attack to decrypt m_1

Padding Oracle Attack

Attack outline:

- 1 Learn size of padding using decryption errors
- 2 Using knowledge of $|pad|$, decrypt m Byte-by-Byte

Padding Oracle Attack

Attack outline:

- 1 Learn size of padding using decryption errors
- 2 Using knowledge of $|pad|$, decrypt m Byte-by-Byte

Observations:

- Can view error as partial decryption
- Even very limited decryption oracle can lead to an attack

Padding Oracle Attack

Attack outline:

- 1 Learn size of padding using decryption errors
- 2 Using knowledge of $|pad|$, decrypt m Byte-by-Byte

Observations:

- Can view error as partial decryption
- Even very limited decryption oracle can lead to an attack

Warning

Be very careful with error messages in crypto constructions