

Cryptography

Lecture 3

Arkady Yerukhimovich

September 4, 2024

Announcements

- ① Homework will now be due on Fridays at 5pm
- ② Homework 1 is out now on Piazza
- ③ Office hours: Starting next week
 - Monday 2:15-3:15
 - Friday 2:30-3:30

- 1 Lecture 2 Review
- 2 One-Time Pad Encryption – Review
- 3 Limitations of Perfect Secrecy (Ch. 2.3)
- 4 Proof Techniques
- 5 Computationally-Secure Private-Key Encryption (Ch. 3.1, 3.2.1)

Lecture 2 Review

- Probability review
- Perfectly-secure private-key encryption
- One-time pad

- 1 Lecture 2 Review
- 2 One-Time Pad Encryption – Review
- 3 Limitations of Perfect Secrecy (Ch. 2.3)
- 4 Proof Techniques
- 5 Computationally-Secure Private-Key Encryption (Ch. 3.1, 3.2.1)

The One-Time Pad

One-Time Pad Encryption Scheme

- Let $\mathcal{M} = \mathcal{K} = \mathcal{C} = \{0, 1\}^\ell$
- Gen: $k \leftarrow \mathcal{K}$
- Enc: $c = k \oplus m$ (\oplus denotes bitwise exclusive-OR)
- Dec: $m = k \oplus c$

Correctness: For all $k \in \mathcal{K}$ and all $m \in \mathcal{M}$,

$$\text{Dec}_k(\text{Enc}_k(m)) =$$

The One-Time Pad

One-Time Pad Encryption Scheme

- Let $\mathcal{M} = \mathcal{K} = \mathcal{C} = \{0, 1\}^\ell$
- Gen: $k \leftarrow \mathcal{K}$
- Enc: $c = k \oplus m$ (\oplus denotes bitwise exclusive-OR)
- Dec: $m = k \oplus c$

Correctness: For all $k \in \mathcal{K}$ and all $m \in \mathcal{M}$,

$$\text{Dec}_k(\text{Enc}_k(m)) = k \oplus (k \oplus m) = (k \oplus k) \oplus m = 0^\ell \oplus m = m$$

Security: The OTP is perfectly secret

$$\Pr[M = m \mid C = c] = \Pr[M = m]$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c]$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

$$\begin{aligned}\Pr[C = c \mid M = m] &= \Pr[\text{Enc}_K(m) = c] = \Pr[m \oplus K = c] \\ &= \Pr[K = m \oplus c] = 2^{-\ell}\end{aligned}$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\cancel{2^{-\ell}} \Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\cancel{\Pr[C = c]} \cdot 2^{-\ell}}$$

$$\begin{aligned}\Pr[C = c \mid M = m] &= \Pr[\text{Enc}_K(m) = c] = \Pr[m \oplus K = c] \\ &= \Pr[K = m \oplus c] = 2^{-\ell}\end{aligned}$$

$$\begin{aligned}\Pr[C = c] &= \sum_{m' \in \mathcal{M}} \Pr[C = c \mid M = m'] \cdot \Pr[M = m'] \\ &= 2^{-\ell} \cdot \sum_{m' \in \mathcal{M}} \Pr[M = m'] = 2^{-\ell}\end{aligned}$$

Limitations of the One-Time Pad

The one-time pad has some critical limitations that make it not ideal for real-world use.

Limitations of the One-Time Pad

The one-time pad has some critical limitations that make it not ideal for real-world use.

- Can only use a key k to encrypt at most one message

$$c_1 = k \oplus m_1, \quad c_2 = k \oplus m_2$$

$$c_1 \oplus c_2 = m_1 \oplus m_2$$

Limitations of the One-Time Pad

The one-time pad has some critical limitations that make it not ideal for real-world use.

- Can only use a key k to encrypt at most one message
- Need the length of the key to be as long as the message (i.e., $|k| \geq |m|$)

Limitations of the One-Time Pad

The one-time pad has some critical limitations that make it not ideal for real-world use.

- Can only use a key k to encrypt at most one message
- Need the length of the key to be as long as the message (i.e., $|k| \geq |m|$)

Why?

Outline

- 1 Lecture 2 Review
- 2 One-Time Pad Encryption – Review
- 3 Limitations of Perfect Secrecy (Ch. 2.3)
- 4 Proof Techniques
- 5 Computationally-Secure Private-Key Encryption (Ch. 3.1, 3.2.1)

Limitations of Perfect Secrecy

Theorem: If $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ is a perfectly secret encryption scheme with message space \mathcal{M} , then $|\mathcal{K}| \geq |\mathcal{M}|$.

Limitations of Perfect Secrecy

Theorem: If $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ is a perfectly secret encryption scheme with message space \mathcal{M} , then $|\mathcal{K}| \geq |\mathcal{M}|$.

Proof: (by contradiction)

- Assume that Π is perfectly secure and that $|\mathcal{K}| < |\mathcal{M}|$.

Limitations of Perfect Secrecy

Theorem: If $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ is a perfectly secret encryption scheme with message space \mathcal{M} , then $|\mathcal{K}| \geq |\mathcal{M}|$.

Proof: (by contradiction)

- Assume that Π is perfectly secure and that $|\mathcal{K}| < |\mathcal{M}|$.
- Let M be chosen uniformly over \mathcal{M} and let $c \in \mathcal{C}$ be any ciphertext s.t. $\Pr[C = c] > 0$.

Limitations of Perfect Secrecy

Theorem: If $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ is a perfectly secret encryption scheme with message space \mathcal{M} , then $|\mathcal{K}| \geq |\mathcal{M}|$.

Proof: (by contradiction)

- Assume that Π is perfectly secure and that $|\mathcal{K}| < |\mathcal{M}|$.
- Let M be chosen uniformly over \mathcal{M} and let $c \in \mathcal{C}$ be any ciphertext s.t. $\Pr[C = c] > 0$.
- Define $\mathcal{M}(c) = \{m \mid m = \text{Dec}_k(c) \text{ for some } k \in \mathcal{K}\}$

Limitations of Perfect Secrecy

Theorem: If $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ is a perfectly secret encryption scheme with message space \mathcal{M} , then $|\mathcal{K}| \geq |\mathcal{M}|$.

Proof: (by contradiction)

- Assume that Π is perfectly secure and that $|\mathcal{K}| < |\mathcal{M}|$.
- Let M be chosen uniformly over \mathcal{M} and let $c \in \mathcal{C}$ be any ciphertext s.t. $\Pr[C = c] > 0$.
- Define $\mathcal{M}(c) = \{m \mid m = \text{Dec}_k(c) \text{ for some } k \in \mathcal{K}\}$
 - Observe that $|\mathcal{M}(c)| \leq |\mathcal{K}|$

Limitations of Perfect Secrecy

Theorem: If $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ is a perfectly secret encryption scheme with message space \mathcal{M} , then $|\mathcal{K}| \geq |\mathcal{M}|$.

Proof: (by contradiction)

- Assume that Π is perfectly secure and that $|\mathcal{K}| < |\mathcal{M}|$.
- Let M be chosen uniformly over \mathcal{M} and let $c \in \mathcal{C}$ be any ciphertext s.t. $\Pr[C = c] > 0$.
- Define $\mathcal{M}(c) = \{m \mid m = \text{Dec}_k(c) \text{ for some } k \in \mathcal{K}\}$
 - Observe that $|\mathcal{M}(c)| \leq |\mathcal{K}|$
- By assumption, $|\mathcal{K}| < |\mathcal{M}|$, so there exists $m' \in \mathcal{M}$ such that $m' \notin \mathcal{M}(c)$

Limitations of Perfect Secrecy

Theorem: If $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ is a perfectly secret encryption scheme with message space \mathcal{M} , then $|\mathcal{K}| \geq |\mathcal{M}|$.

Proof: (by contradiction)

- Assume that Π is perfectly secure and that $|\mathcal{K}| < |\mathcal{M}|$.
- Let M be chosen uniformly over \mathcal{M} and let $c \in \mathcal{C}$ be any ciphertext s.t. $\Pr[C = c] > 0$.
- Define $\mathcal{M}(c) = \{m \mid m = \text{Dec}_k(c) \text{ for some } k \in \mathcal{K}\}$
 - Observe that $|\mathcal{M}(c)| \leq |\mathcal{K}|$
- By assumption, $|\mathcal{K}| < |\mathcal{M}|$, so there exists $m' \in \mathcal{M}$ such that $m' \notin \mathcal{M}(c)$
- But, then $\Pr[M = m' \mid C = c] = 0 \neq \Pr[M = m']$ (i.e., Π is not perfectly secret), contradiction!

Limitations of Perfect Secrecy

Theorem: If $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ is a perfectly secret encryption scheme with message space \mathcal{M} , then $|\mathcal{K}| \geq |\mathcal{M}|$.

Proof: (by contradiction)

- Assume that Π is perfectly secure and that $|\mathcal{K}| < |\mathcal{M}|$.
- Let M be chosen uniformly over \mathcal{M} and let $c \in \mathcal{C}$ be any ciphertext s.t. $\Pr[C = c] > 0$.
- Define $\mathcal{M}(c) = \{m \mid m = \text{Dec}_k(c) \text{ for some } k \in \mathcal{K}\}$
 - Observe that $|\mathcal{M}(c)| \leq |\mathcal{K}|$
- By assumption, $|\mathcal{K}| < |\mathcal{M}|$, so there exists $m' \in \mathcal{M}$ such that $m' \notin \mathcal{M}(c)$
- But, then $\Pr[M = m' \mid C = c] = 0 \neq \Pr[M = m']$ (i.e., Π is not perfectly secret), contradiction!

Take Away

Perfectly secure encryption must have keys as long as the message.

- 1 Lecture 2 Review
- 2 One-Time Pad Encryption – Review
- 3 Limitations of Perfect Secrecy (Ch. 2.3)
- 4 Proof Techniques**
- 5 Computationally-Secure Private-Key Encryption (Ch. 3.1, 3.2.1)

Proof Techniques for this Class

We will use the following proof techniques in this class:

Proof Techniques for this Class

We will use the following proof techniques in this class:

- Direct Proof

Proof Techniques for this Class

We will use the following proof techniques in this class:

- Direct Proof
- Proof by Contradiction

Proof Techniques for this Class

We will use the following proof techniques in this class:

- Direct Proof
- Proof by Contradiction
- Proof by Reduction

Proof Techniques for this Class

We will use the following proof techniques in this class:

- Direct Proof
- Proof by Contradiction
- Proof by Reduction
- Proof by Induction

Exercise

Consider a OTP encryption:

- What happens if $k = 0^\ell$?

$$c = m \oplus 0^\ell = m$$

Exercise

Consider a OTP encryption:

- What happens if $k = 0^\ell$?
- Is this a problem?

Consider a OTP encryption:

- What happens if $k = 0^\ell$?
- Is this a problem?
- Suppose we modify Gen to never output $k = 0^\ell$, is this still perfectly secure?

Consider a OTP encryption:

- What happens if $k = 0^\ell$?
- Is this a problem?
- Suppose we modify Gen to never output $k = 0^\ell$, is this still perfectly secure?
- Why or why not?

Outline

- 1 Lecture 2 Review
- 2 One-Time Pad Encryption – Review
- 3 Limitations of Perfect Secrecy (Ch. 2.3)
- 4 Proof Techniques
- 5 Computationally-Secure Private-Key Encryption (Ch. 3.1, 3.2.1)

Asymptotics in Cryptography

- A function $f : \mathbb{Z}^+ \rightarrow \mathbb{Z}^+$ is *polynomial* if there exist $c \in \mathbb{Z}^+$ such that $f(n) < n^c$ for all n

Asymptotics in Cryptography

- A function $f : \mathbb{Z}^+ \rightarrow \mathbb{Z}^+$ is *polynomial* if there exist $c \in \mathbb{Z}^+$ such that $f(n) < n^c$ for all n
 - Interpretation: f grows no faster than a polynomial in n .

Asymptotics in Cryptography

- A function $f : \mathbb{Z}^+ \rightarrow \mathbb{Z}^+$ is *polynomial* if there exist $c \in \mathbb{Z}^+$ such that $f(n) < n^c$ for all n
 - Interpretation: f grows no faster than a polynomial in n .
 - Examples: $f(n) = n^2$, $f(n) = 100n^3 + n + 6$

Asymptotics in Cryptography

- A function $f : \mathbb{Z}^+ \rightarrow \mathbb{Z}^+$ is *polynomial* if there exist $c \in \mathbb{Z}^+$ such that $f(n) < n^c$ for all n
 - Interpretation: f grows no faster than a polynomial in n .
 - Examples: $f(n) = n^2$, $f(n) = 100n^3 + n + 6$
- A function $f : \mathbb{Z}^+ \rightarrow [0, 1]$ is *negligible* if for every polynomial p it holds that $f(n) < 1/p(n)$ for large enough n .

Asymptotics in Cryptography

- A function $f : \mathbb{Z}^+ \rightarrow \mathbb{Z}^+$ is *polynomial* if there exist $c \in \mathbb{Z}^+$ such that $f(n) < n^c$ for all n
 - Interpretation: f grows no faster than a polynomial in n .
 - Examples: $f(n) = n^2$, $f(n) = 100n^3 + n + 6$
- A function $f : \mathbb{Z}^+ \rightarrow [0, 1]$ is *negligible* if for every polynomial p it holds that $f(n) < 1/p(n)$ for large enough n .
 - Interpretation: f goes to 0 faster than any inverse polynomial in n

Asymptotics in Cryptography

- A function $f : \mathbb{Z}^+ \rightarrow \mathbb{Z}^+$ is *polynomial* if there exist $c \in \mathbb{Z}^+$ such that $f(n) < n^c$ for all n
 - Interpretation: f grows no faster than a polynomial in n .
 - Examples: $f(n) = n^2$, $f(n) = 100n^3 + n + 6$
- A function $f : \mathbb{Z}^+ \rightarrow [0, 1]$ is *negligible* if for every polynomial p it holds that $f(n) < 1/p(n)$ for large enough n .
 - Interpretation: f goes to 0 faster than any inverse polynomial in n
 - Examples: $f(n) = 2^{-n}$, $f(n) = 2^{-\log^2 n}$

$$\lim_{n \rightarrow \infty} \frac{n^2}{2^n} = 0 \qquad 2^{\log^2 n} = n^{\log n}$$

Asymptotics in Cryptography

- A function $f : \mathbb{Z}^+ \rightarrow \mathbb{Z}^+$ is *polynomial* if there exist $c \in \mathbb{Z}^+$ such that $f(n) < n^c$ for all n
 - Interpretation: f grows no faster than a polynomial in n .
 - Examples: $f(n) = n^2$, $f(n) = 100n^3 + n + 6$
- A function $f : \mathbb{Z}^+ \rightarrow [0, 1]$ is *negligible* if for every polynomial p it holds that $f(n) < 1/p(n)$ for large enough n .
 - Interpretation: f goes to 0 faster than any inverse polynomial in n
 - Examples: $f(n) = 2^{-n}$, $f(n) = 2^{-\log^2 n}$

Computational Security

A cryptographic scheme is *computationally secure* if any probabilistic polynomial time (PPT) adversary only breaks security with at most a *negligible probability*.

Necessity of Relaxations

Consider the case of private-key encryption with $|\mathcal{K}| < |\mathcal{M}|$:

Necessity of Relaxations

Consider the case of private-key encryption with $|\mathcal{K}| < |\mathcal{M}|$:

- Adversary Runtime:

Necessity of Relaxations

Consider the case of private-key encryption with $|\mathcal{K}| < |\mathcal{M}|$:

- Adversary Runtime:
Suppose \mathcal{A} can run in unbounded time.

Necessity of Relaxations

Consider the case of private-key encryption with $|\mathcal{K}| < |\mathcal{M}|$:

- Adversary Runtime:

Suppose \mathcal{A} can run in unbounded time. Given a ciphertext c , try to decrypt with all $k \in \mathcal{K}$, some m must be missing.

\mathcal{A} runs in time 2^k

Necessity of Relaxations

Consider the case of private-key encryption with $|\mathcal{K}| < |\mathcal{M}|$:

- Adversary Runtime:
Suppose \mathcal{A} can run in unbounded time. Given a ciphertext c , try to decrypt with all $k \in \mathcal{K}$, some m must be missing.
- Adversary Success Probability:
Consider an \mathcal{A} that learns pairs $(m_1, c_1), \dots, (m_\ell, c_\ell)$.

Necessity of Relaxations

Consider the case of private-key encryption with $|\mathcal{K}| < |\mathcal{M}|$:

- Adversary Runtime:

Suppose \mathcal{A} can run in unbounded time. Given a ciphertext c , try to decrypt with all $k \in \mathcal{K}$, some m must be missing.

- Adversary Success Probability:

Consider an \mathcal{A} that learns pairs $(m_1, c_1), \dots, (m_\ell, c_\ell)$. \mathcal{A} can just guess $k \leftarrow \mathcal{K}$ and check where $\text{Dec}_k(c_i) = m_i$ for all i (i.e., k is the correct key). \mathcal{A} can guess correct k with probability $1/|\mathcal{K}| > 0$.

Necessity of Relaxations

Consider the case of private-key encryption with $|\mathcal{K}| < |\mathcal{M}|$:

- Adversary Runtime:

Suppose \mathcal{A} can run in unbounded time. Given a ciphertext c , try to decrypt with all $k \in \mathcal{K}$, some m must be missing.

- Adversary Success Probability:

Consider an \mathcal{A} that learns pairs $(m_1, c_1), \dots, (m_\ell, c_\ell)$. \mathcal{A} can just guess $k \leftarrow \mathcal{K}$ and check where $\text{Dec}_k(c_i) = m_i$ for all i (i.e., k is the correct key). \mathcal{A} can guess correct k with probability $1/|\mathcal{K}| > 0$.

Computational Security

A cryptographic scheme is *computationally secure* if any *probabilistic polynomial time (PPT) adversary* only breaks security with at most a *negligible probability*.

Why This Choice of Relaxation?

Computational Security

A cryptographic scheme is *computationally secure* if any *probabilistic polynomial time (PPT) adversary* only breaks security with at most a *negligible probability*.

Why This Choice of Relaxation?

- Efficient = probabilistic polynomial time (PPT)
 - Standard from algorithms / complexity theory

Computational Security

A cryptographic scheme is *computationally secure* if any *probabilistic polynomial time (PPT) adversary* only breaks security with at most a *negligible probability*.

Why This Choice of Relaxation?

- Efficient = probabilistic polynomial time (PPT)
 - Standard from algorithms / complexity theory
- Convenient closure properties:

Computational Security

A cryptographic scheme is *computationally secure* if any *probabilistic polynomial time (PPT) adversary* only breaks security with at most a *negligible probability*.

Why This Choice of Relaxation?

- Efficient = probabilistic polynomial time (PPT)
 - Standard from algorithms / complexity theory
- Convenient closure properties:
 - $\text{poly}(n) \cdot \text{poly}(n) = \text{poly}(n)$
A PPT algorithm making calls to PPT subroutines is PPT

Computational Security

A cryptographic scheme is *computationally secure* if any *probabilistic polynomial time (PPT) adversary* only breaks security with at most a *negligible probability*.

Why This Choice of Relaxation?

- Efficient = probabilistic polynomial time (PPT)
 - Standard from algorithms / complexity theory
- Convenient closure properties:
 - $\text{poly}(n) \cdot \text{poly}(n) = \text{poly}(n)$
A PPT algorithm making calls to PPT subroutines is PPT
 - $\text{poly}(n) \cdot \text{negl}(n) = \text{negl}(n)$
Poly many calls to subroutines with negligible success probability, have negligible success probability

Computational Security

A cryptographic scheme is *computationally secure* if any *probabilistic polynomial time (PPT) adversary* only breaks security with at most a *negligible probability*.

Redefining Encryption Functionality

Private-key (symmetric-key) encryption scheme:

- Gen: Outputs randomly chosen key k
- $\text{Enc}(k, m) : c \leftarrow \text{Enc}_k(m)$
- $\text{Dec}(k, c) : m = \text{Dec}_k(c)$

Correctness

For all k output by Gen and all messages m , $\text{Dec}_k(\text{Enc}_k(m)) = m$

Redefining Encryption Functionality

Private-key (symmetric-key) encryption scheme:

- Gen, Enc, Dec run in polynomial time (in their input size)
- Gen: Outputs randomly chosen key k
- $\text{Enc}(k, m) : c \leftarrow \text{Enc}_k(m)$
- $\text{Dec}(k, c) : m = \text{Dec}_k(c)$

Correctness

For all k output by Gen and all messages m , $\text{Dec}_k(\text{Enc}_k(m)) = m$

Redefining Encryption Functionality

$|n| = \overbrace{11111111}^{n \text{ times}}$

Private-key (symmetric-key) encryption scheme:

- Gen, Enc, Dec run in polynomial time (in their input size)
- Gen: $k \leftarrow \text{Gen}(1^n)$ – n is called the *security parameter*
- $\text{Enc}(k, m) : c \leftarrow \text{Enc}_k(m)$
- $\text{Dec}(k, c) : m = \text{Dec}_k(c)$

Correctness

For all k output by Gen and all messages m , $\text{Dec}_k(\text{Enc}_k(m)) = m$

$$|1^n| = \log n$$

Redefining Encryption Functionality

Private-key (symmetric-key) encryption scheme:

- Gen, Enc, Dec run in polynomial time (in their input size)
- Gen: $k \leftarrow \text{Gen}(1^n)$ – n is called the *security parameter*
- $\text{Enc}(k, m) : c \leftarrow \text{Enc}_k(m)$ for $m \in \{0, 1\}^*$
- $\text{Dec}(k, c) : m = \text{Dec}_k(c)$

Correctness

For all k output by Gen and all messages m , $\text{Dec}_k(\text{Enc}_k(m)) = m$

Redefining Encryption Functionality

Private-key (symmetric-key) encryption scheme:

- Gen, Enc, Dec run in polynomial time (in their input size)
- Gen: $k \leftarrow \text{Gen}(1^n)$ – n is called the *security parameter*
- $\text{Enc}(k, m) : c \leftarrow \text{Enc}_k(m)$ for $m \in \{0, 1\}^*$
- $\text{Dec}(k, c) : m = \text{Dec}_k(c)$

Correctness

For all k output by Gen and all messages m , $\text{Dec}_k(\text{Enc}_k(m)) = m$

Redefining Encryption Functionality

Private-key (symmetric-key) encryption scheme:

- Gen, Enc, Dec run in polynomial time (in their input size)
- Gen: $k \leftarrow \text{Gen}(1^n)$ – n is called the *security parameter*
- $\text{Enc}(k, m) : c \leftarrow \text{Enc}_k(m)$ for $m \in \{0, 1\}^*$
- $\text{Dec}(k, c) : m = \text{Dec}_k(c)$

Correctness

For all n , for all k output by $\text{Gen}(1^n)$ and all messages $m \in \{0, 1\}^*$,
 $\text{Dec}_k(\text{Enc}_k(m)) = m$

Redefining Encryption Security

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}$

- \mathcal{A} outputs two messages $m_0, m_1 \in \mathcal{M}$
- The challenger chooses $k \leftarrow \text{Gen}$, $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- \mathcal{A} outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

Definition: An encryption scheme $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space \mathcal{M} is *perfectly indistinguishable* if for all \mathcal{A} it holds that

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1] = 1/2$$

Redefining Encryption Security

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n)$

- \mathcal{A} outputs two messages $m_0, m_1 \in \mathcal{M}$
- The challenger chooses $k \leftarrow \text{Gen}$, $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- \mathcal{A} outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

Definition: An encryption scheme $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space \mathcal{M} is *perfectly indistinguishable* if for all \mathcal{A} it holds that

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1] = 1/2$$

Redefining Encryption Security

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n)$$

- \mathcal{A} outputs two messages m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $k \leftarrow \text{Gen}$, $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- \mathcal{A} outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

Definition: An encryption scheme $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space \mathcal{M} is *perfectly indistinguishable* if for all \mathcal{A} it holds that

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1] = 1/2$$

Redefining Encryption Security

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n)$

- \mathcal{A} outputs two messages m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $k \leftarrow \text{Gen}(1^n)$, $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- \mathcal{A} outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

Definition: An encryption scheme $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space \mathcal{M} is *perfectly indistinguishable* if for all \mathcal{A} it holds that

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1] = 1/2$$

Redefining Encryption Security

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n)$

- \mathcal{A} outputs two messages m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $k \leftarrow \text{Gen}(1^n)$, $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A} .
- \mathcal{A} outputs a guess bit b' .
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

Definition: An encryption scheme $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space \mathcal{M} is *perfectly indistinguishable* if for all \mathcal{A} it holds that

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1] = 1/2$$

Redefining Encryption Security

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n)$

- \mathcal{A} outputs two messages m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $k \leftarrow \text{Gen}(1^n)$, $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- \mathcal{A} outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

Definition: An encryption scheme $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space \mathcal{M} is *perfectly indistinguishable* if for all \mathcal{A} it holds that

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1] = 1/2$$

Redefining Encryption Security

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary \mathcal{A} and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n)$

- \mathcal{A} outputs two messages m_0, m_1 such that $|m_0| = |m_1|$.
- The challenger chooses $k \leftarrow \text{Gen}(1^n)$, $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to \mathcal{A}
- \mathcal{A} outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1$ (i.e., \mathcal{A} wins) if $b' = b$.

Definition: An encryption scheme $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space \mathcal{M} has *indistinguishable encryptions in the presence of an eavesdropper* if for all PPT \mathcal{A} it holds that

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1] \leq 1/2 + \text{negl}(n)$$

How to Construct

- Recall that we encrypted by computing $\text{Enc}_k(m) = m \oplus k$
- But, if $|k| < |m|$, this is not secure

How to Construct

- Recall that we encrypted by computing $\text{Enc}_k(m) = m \oplus k$
- But, if $|k| < |m|$, this is not secure

Key Idea

What if we had a way to stretch key k into something longer that still looked random?