

Cryptography

Lecture 1

Arkady Yerukhimovich

August 24, 2026

Outline

- 1 Principles of Modern Cryptography (Ch. 1.1, 1.4)
- 2 Private-Key Encryption (Ch. 1.2)
- 3 Probability Review (Ch. A.3)
- 4 Perfectly-Secure Encryption (Ch. 2.1)
- 5 The One-Time Pad (Ch. 2.2)

A (Very) Brief History of Cryptography

- For 1000s of years, cryptography was “the art of writing or solving codes”
- Largely heuristic approaches to design codes, leading to a break-fix cycle
- Beginning in the 1970s, modern cryptography turned cryptography into a science, giving it a strong mathematical basis.



Principles of Modern Cryptography

- Formal definitions
- Precise assumptions
- Proofs of security

Kerckhoffs' Principle

“The cipher method must not be required to be secret, and it must be able to fall into the hands of the enemy without inconvenience.”

The Rule of Modern Crypto

No security by obscurity!

Outline

- 1 Principles of Modern Cryptography (Ch. 1.1, 1.4)
- 2 Private-Key Encryption (Ch. 1.2)**
- 3 Probability Review (Ch. A.3)
- 4 Perfectly-Secure Encryption (Ch. 2.1)
- 5 The One-Time Pad (Ch. 2.2)

Private-key encryption

Alice



Bob



Private-key encryption



Key k



Key k

Private-key encryption




Key k
Message m



Key k

Private-key encryption



Alice

Bob

c


Key k

Key k


Message m

Encrypt m : $c \leftarrow \text{Enc}_k(m)$

Private-key encryption



Private-key encryption



Security – Informal

Eve gets to observe c , but can not learn m

Defining Encryption Functionality

Private-key (symmetric-key) encryption scheme:

- Gen: Outputs randomly chosen key k
- $\text{Enc}(k, m) : c \leftarrow \text{Enc}_k(m)$
- $\text{Dec}(k, c) : m = \text{Dec}_k(c)$

Terminology

m - plaintext

c - ciphertext

Correctness

For all k output by Gen and all messages m , $\text{Dec}_k(\text{Enc}_k(m)) = m$

Defining Encryption Security

Security Guarantee

What is a successful attack?

Threat Model

What can the adversary do?

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k

Threat Model

What can the adversary do?

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k
- $\mathcal{A}$ learns the message m

Threat Model

What can the adversary do?

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k
- $\mathcal{A}$ learns the message m
- $\mathcal{A}$ learns any character of m

Threat Model

What can the adversary do?

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k
- $\mathcal{A}$ learns the message m
- $\mathcal{A}$ learns any character of m
- Semantic security:
Regardless of what $\mathcal{A}$ knows about m , she learns no new information

Threat Model

What can the adversary do?

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k
- $\mathcal{A}$ learns the message m
- $\mathcal{A}$ learns any character of m
- Semantic security:
Regardless of what $\mathcal{A}$ knows about m , she learns no new information

Threat Model

What can the adversary do?

- ciphertext-only

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k
- $\mathcal{A}$ learns the message m
- $\mathcal{A}$ learns any character of m
- Semantic security:
Regardless of what $\mathcal{A}$ knows about m , she learns no new information

Threat Model

What can the adversary do?

- ciphertext-only
- known-plaintext

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k
- $\mathcal{A}$ learns the message m
- $\mathcal{A}$ learns any character of m
- Semantic security:
Regardless of what $\mathcal{A}$ knows about m , she learns no new information

Threat Model

What can the adversary do?

- ciphertext-only
- known-plaintext
- chosen-plaintext

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k
- $\mathcal{A}$ learns the message m
- $\mathcal{A}$ learns any character of m
- Semantic security:
Regardless of what $\mathcal{A}$ knows about m , she learns no new information

Threat Model

What can the adversary do?

- ciphertext-only
- known-plaintext
- chosen-plaintext
- chosen-ciphertext

Time for a quiz and then a short break

Outline

- 1 Principles of Modern Cryptography (Ch. 1.1, 1.4)
- 2 Private-Key Encryption (Ch. 1.2)
- 3 Probability Review (Ch. A.3)**
- 4 Perfectly-Secure Encryption (Ch. 2.1)
- 5 The One-Time Pad (Ch. 2.2)

Definitions

Let E_1 and E_2 be events: (e.g., a coin toss comes up HEADS)

Definitions

Let E_1 and E_2 be events: (e.g., a coin toss comes up HEADS)

- $\overline{E}$, $\neg E$ is complement of E (i.e., not E)

$$\Pr[E] = 1 - \Pr[\overline{E}]$$

Definitions

Let E_1 and E_2 be events: (e.g., a coin toss comes up HEADS)

- $\overline{E}$, $\neg E$ is complement of E (i.e., not E)

$$\Pr[E] = 1 - \Pr[\overline{E}]$$

- $E_1 \wedge E_2$ is conjunction (AND) of two events (i.e., they both occur)

$$\Pr[E_1 \wedge E_2] \leq \Pr[E_1]$$

Definitions

Let E_1 and E_2 be events: (e.g., a coin toss comes up HEADS)

- $\overline{E}$, $\neg E$ is complement of E (i.e., not E)

$$\Pr[E] = 1 - \Pr[\overline{E}]$$

- $E_1 \wedge E_2$ is conjunction (AND) of two events (i.e., they both occur)

$$\Pr[E_1 \wedge E_2] \leq \Pr[E_1]$$

- $E_1 \vee E_2$ is disjunction (OR) of two events (i.e., at least one occurs)

$$\Pr[E_1 \vee E_2] \geq \Pr[E_1]$$

Definitions

Let E_1 and E_2 be events: (e.g., a coin toss comes up HEADS)

- $\bar{E}$, $\neg E$ is complement of E (i.e., not E)

$$\Pr[E] = 1 - \Pr[\bar{E}]$$

- $E_1 \wedge E_2$ is conjunction (AND) of two events (i.e., they both occur)

$$\Pr[E_1 \wedge E_2] \leq \Pr[E_1]$$

- $E_1 \vee E_2$ is disjunction (OR) of two events (i.e., at least one occurs)

$$\Pr[E_1 \vee E_2] \geq \Pr[E_1]$$

Definition

E_1 and E_2 are *independent* if $\Pr[E_1 \wedge E_2] = \Pr[E_1] \cdot \Pr[E_2]$

Bayes' Theorem

- Conditional Probability of E_1 given E_2 ($\Pr[E_2] > 0$):

$$\Pr[E_1 \mid E_2] = \frac{\Pr[E_1 \wedge E_2]}{\Pr[E_2]}$$

Bayes' Theorem

- Conditional Probability of E_1 given E_2 ($\Pr[E_2] > 0$):

$$\Pr[E_1 \mid E_2] = \frac{\Pr[E_1 \wedge E_2]}{\Pr[E_2]}$$

- Bayes' Theorem:

$$\text{If } \Pr[E_2] \neq 0, \text{ then } \Pr[E_1 \mid E_2] = \frac{\Pr[E_2 \mid E_1] \cdot \Pr[E_1]}{\Pr[E_2]}$$

Bayes' Theorem

- Conditional Probability of E_1 given E_2 ($\Pr[E_2] > 0$):

$$\Pr[E_1 | E_2] = \frac{\Pr[E_1 \wedge E_2]}{\Pr[E_2]}$$

- Bayes' Theorem:

$$\text{If } \Pr[E_2] \neq 0, \text{ then } \Pr[E_1 | E_2] = \frac{\Pr[E_2 | E_1] \cdot \Pr[E_1]}{\Pr[E_2]}$$

- Proof:

By definition of conditional probability,

$$\Pr[E_1 | E_2] \cdot \Pr[E_2] = \Pr[E_1 \wedge E_2] = \Pr[E_2 | E_1] \cdot \Pr[E_1].$$

$$\text{So, } \Pr[E_1 | E_2] = \frac{\Pr[E_2 | E_1] \cdot \Pr[E_1]}{\Pr[E_2]}$$

Law of Total Probability

- Law of Total Probability: If $E_1, E_2, \dots, E_n$ are a partition (non-overlapping) of all possibilities. Then, for any event A ,

$$\Pr[A] = \sum_{i=1}^n \Pr[A \wedge E_i] = \sum_{i=1}^n \Pr[A \mid E_i] \cdot \Pr[E_i]$$

- Proof Sketch:




Some Useful Definitions and Facts

- Law of Total Probability: If $E_1, E_2, \dots, E_n$ are a partition (non-overlapping) of all possibilities. Then, for any event A ,

$$\Pr[A] = \sum_{i=1}^n \Pr[A \wedge E_i] = \sum_{i=1}^n \Pr[A \mid E_i] \cdot \Pr[E_i]$$

- Proof Sketch:



Some Useful Definitions and Facts

- Union Bound:


$$\Pr[E_1 \vee E_2] \leq \Pr[E_1] + \Pr[E_2]$$

Some Useful Definitions and Facts

- Union Bound:

$$\Pr[E_1 \vee E_2] \leq \Pr[E_1] + \Pr[E_2]$$


- Proof Sketch:



Outline

- 1 Principles of Modern Cryptography (Ch. 1.1, 1.4)
- 2 Private-Key Encryption (Ch. 1.2)
- 3 Probability Review (Ch. A.3)
- 4 Perfectly-Secure Encryption (Ch. 2.1)**
- 5 The One-Time Pad (Ch. 2.2)

Private-key encryption



Security

Eve gets to observe c , but can not learn m

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k
- $\mathcal{A}$ learns the message m
- $\mathcal{A}$ learns any character of m
- Semantic security:
Regardless of what $\mathcal{A}$ knows about m , she learns no new information

Threat Model

What can an adversary do?

- ciphertext-only
- known-plaintext
- chosen-plaintext
- chosen-ciphertext

Defining Encryption Security

Security Guarantee

What is a successful attack?

- $\mathcal{A}$ learns the key k
- $\mathcal{A}$ learns the message m
- $\mathcal{A}$ learns any character of m
- Semantic security:
Regardless of what $\mathcal{A}$ knows about m , she learns no new information

Threat Model

What can an adversary do?

- ciphertext-only
- known-plaintext
- chosen-plaintext
- chosen-ciphertext

Formalizing the Definition

Probability Distributions:

- Let M be a random variable denoting value of the message
 - M ranges over plaintext space $\mathcal{M}$
 - Distribution of M reflects $\mathcal{A}$'s prior knowledge of message being sent (not all messages are equally likely)

Formalizing the Definition

Probability Distributions:

- Let M be a random variable denoting value of the message
 - M ranges over plaintext space $\mathcal{M}$
 - Distribution of M reflects $\mathcal{A}$'s prior knowledge of message being sent (not all messages are equally likely)
- Let K be a random variable denoting the key
 - K ranges over keyspace $\mathcal{K}$
 - Distribution of K is defined by Gen (independent of M)

Formalizing the Definition

Probability Distributions:

- Let M be a random variable denoting value of the message
 - M ranges over plaintext space $\mathcal{M}$
 - Distribution of M reflects $\mathcal{A}$'s prior knowledge of message being sent (not all messages are equally likely)
- Let K be a random variable denoting the key
 - K ranges over keyspace $\mathcal{K}$
 - Distribution of K is defined by Gen (independent of M)
- Let C be a random variable (ranging over ciphertext space $\mathcal{C}$) denoting the ciphertext. Its distribution is defined by the following experiment:
 - A key k is chosen using Gen
 - A message m is chosen according to distribution of M over $\mathcal{M}$
 - Compute $c \leftarrow \text{Enc}_k(m)$

Formalizing the Definition

Probability Distributions:

- Let M be a random variable denoting value of the message
 - M ranges over plaintext space $\mathcal{M}$
 - Distribution of M reflects $\mathcal{A}$'s prior knowledge of message being sent (not all messages are equally likely)
- Let K be a random variable denoting the key
 - K ranges over keyspace $\mathcal{K}$
 - Distribution of K is defined by Gen (independent of M)
- Let C be a random variable (ranging over ciphertext space $\mathcal{C}$) denoting the ciphertext. Its distribution is defined by the following experiment:
 - A key k is chosen using Gen
 - A message m is chosen according to distribution of M over $\mathcal{M}$
 - Compute $c \leftarrow \text{Enc}_k(m)$

Remember

$\mathcal{M}$ is a space, M is a random variable, m is a value taken on by M
We will often look at $\Pr[M = m]$

Formalizing the Definition

Informal Definition

$\mathcal{A}$ knows the distribution of M over $\mathcal{M}$. After seeing one ciphertext c , she should learn no additional info about m .

Formalizing the Definition

Informal Definition

$\mathcal{A}$ knows the distribution of M over $\mathcal{M}$. After seeing one ciphertext c , she should learn no additional info about m .

Encryption scheme $(\text{Gen}, \text{Enc}, \text{Dec})$ with message space $\mathcal{M}$ is *perfectly secret* if

Formalizing the Definition

Informal Definition

$\mathcal{A}$ knows the distribution of M over $\mathcal{M}$. After seeing one ciphertext c , she should learn no additional info about m .

Encryption scheme $(\text{Gen}, \text{Enc}, \text{Dec})$ with message space $\mathcal{M}$ is *perfectly secret* if

Def. 1 For all distributions over $\mathcal{M}$

Formalizing the Definition

Informal Definition

$\mathcal{A}$ knows the distribution of M over $\mathcal{M}$. After seeing one ciphertext c , she should learn no additional info about m .

Encryption scheme $(\text{Gen}, \text{Enc}, \text{Dec})$ with message space $\mathcal{M}$ is *perfectly secret* if

Def. 1 For all distributions over $\mathcal{M}$, for all $m \in \mathcal{M}$

Formalizing the Definition

Informal Definition

$\mathcal{A}$ knows the distribution of M over $\mathcal{M}$. After seeing one ciphertext c , she should learn no additional info about m .

Encryption scheme $(\text{Gen}, \text{Enc}, \text{Dec})$ with message space $\mathcal{M}$ is *perfectly secret* if

Def. 1 For all distributions over $\mathcal{M}$, for all $m \in \mathcal{M}$, for all $c \in \mathcal{C}$ with $\Pr[C = c] > 0$

Formalizing the Definition

Informal Definition

$\mathcal{A}$ knows the distribution of M over $\mathcal{M}$. After seeing one ciphertext c , she should learn no additional info about m .

Encryption scheme $(\text{Gen}, \text{Enc}, \text{Dec})$ with message space $\mathcal{M}$ is *perfectly secret* if

Def. 1 For all distributions over $\mathcal{M}$, for all $m \in \mathcal{M}$, for all $c \in \mathcal{C}$ with $\Pr[C = c] > 0$

$$\Pr[M = m \mid C = c] = \Pr[M = m]$$

Formalizing the Definition

Informal Definition

$\mathcal{A}$ knows the distribution of M over $\mathcal{M}$. After seeing one ciphertext c , she should learn no additional info about m .

Encryption scheme $(\text{Gen}, \text{Enc}, \text{Dec})$ with message space $\mathcal{M}$ is *perfectly secret* if

Def. 1 For all distributions over $\mathcal{M}$, for all $m \in \mathcal{M}$, for all $c \in \mathcal{C}$ with $\Pr[C = c] > 0$

$$\Pr[M = m \mid C = c] = \Pr[M = m]$$

Def. 2 For all pairs $m, m' \in \mathcal{M}$ s.t. $|m| = |m'|$, for all $c \in \mathcal{C}$

$$\Pr[\text{Enc}_K(m) = c] = \Pr[\text{Enc}_K(m') = c]$$

A Game-Based Definition

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary $\mathcal{A}$ and a challenger:

A Game-Based Definition

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary $\mathcal{A}$ and a challenger:

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}$

- $\mathcal{A}$ outputs two messages $m_0, m_1 \in \mathcal{M}$, s.t. $|m_0| = |m_1|$
- The challenger chooses $k \leftarrow \text{Gen}$, $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to $\mathcal{A}$
- $\mathcal{A}$ outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1$ (i.e., $\mathcal{A}$ wins) if $b' = b$.

A Game-Based Definition

Let $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ be an encryption scheme. Consider the following game between an adversary $\mathcal{A}$ and a challenger:


$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}$

- $\mathcal{A}$ outputs two messages $m_0, m_1 \in \mathcal{M}$, s.t. $|m_0| = |m_1|$
- The challenger chooses $k \leftarrow \text{Gen}$, $b \leftarrow \{0, 1\}$, computes $c \leftarrow \text{Enc}_k(m_b)$ and gives c to $\mathcal{A}$
- $\mathcal{A}$ outputs a guess bit b'
- We say that $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1$ (i.e., $\mathcal{A}$ wins) if $b' = b$.


Definition: An encryption scheme $\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space $\mathcal{M}$ is *perfectly indistinguishable* if for all $\mathcal{A}$ it holds that

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}} = 1] = 1/2$$


A Game-Based Definition




A Game-Based Definition




A Game-Based Definition



A Game-Based Definition



A Game-Based Definition



Winning Condition

$b' = b$ Perfect indistinguishability: $\Pr[b' = b] = \frac{1}{2}$

We have seen three equivalent definitions of perfect secrecy:

- Message distribution unchanged after observing the ciphertext
- Identical ciphertext distributions for any two equal-length messages
- No adversary distinguishes their encryptions better than random guessing

Important

All three definitions are equivalent, and we will use them interchangeably.

Outline

- 1 Principles of Modern Cryptography (Ch. 1.1, 1.4)
- 2 Private-Key Encryption (Ch. 1.2)
- 3 Probability Review (Ch. A.3)
- 4 Perfectly-Secure Encryption (Ch. 2.1)
- 5 The One-Time Pad (Ch. 2.2)**

Let's Recall Our Goal – Perfect Secrecy

Informal Security Goal

$\mathcal{A}$ knows the distribution of M over $\mathcal{M}$. After seeing one ciphertext c , she should learn no additional info about m .

Encryption scheme $(\text{Gen}, \text{Enc}, \text{Dec})$ with message space $\mathcal{M}$ is *perfectly secret* if

- For all distributions over $\mathcal{M}$, for all $m \in \mathcal{M}$, for all $c \in \mathcal{C}$ with $\Pr[C = c] > 0$

$$\Pr[M = m \mid C = c] = \Pr[M = m]$$

The One-Time Pad

XOR

x	y	$x \oplus y$
0	0	0
0	1	1
1	0	1
1	1	0

The One-Time Pad

XOR		
x	y	$x \oplus y$
0	0	0
0	1	1
1	0	1
1	1	0

One-Time Pad Encryption Scheme

- Let $\mathcal{M} = \mathcal{K} = \mathcal{C} = \{0, 1\}^\ell$

The One-Time Pad

XOR

x	y	$x \oplus y$
0	0	0
0	1	1
1	0	1
1	1	0

One-Time Pad Encryption Scheme

- Let $\mathcal{M} = \mathcal{K} = \mathcal{C} = \{0, 1\}^\ell$
- Gen: $k \leftarrow \mathcal{K}$

The One-Time Pad

XOR		
x	y	$x \oplus y$
0	0	0
0	1	1
1	0	1
1	1	0

One-Time Pad Encryption Scheme

- Let $\mathcal{M} = \mathcal{K} = \mathcal{C} = \{0, 1\}^\ell$
- Gen: $k \leftarrow \mathcal{K}$
- Enc: $c = k \oplus m$ ($\oplus$ denotes bitwise XOR)

The One-Time Pad

XOR		
x	y	$x \oplus y$
0	0	0
0	1	1
1	0	1
1	1	0

One-Time Pad Encryption Scheme

- Let $\mathcal{M} = \mathcal{K} = \mathcal{C} = \{0, 1\}^\ell$
- Gen: $k \leftarrow \mathcal{K}$
- Enc: $c = k \oplus m$ ($\oplus$ denotes bitwise XOR)
- Dec: $m = k \oplus c$

The One-Time Pad

XOR		
x	y	$x \oplus y$
0	0	0
0	1	1
1	0	1
1	1	0

One-Time Pad Encryption Scheme

- Let $\mathcal{M} = \mathcal{K} = \mathcal{C} = \{0, 1\}^\ell$
- Gen: $k \leftarrow \mathcal{K}$
- Enc: $c = k \oplus m$ ($\oplus$ denotes bitwise XOR)
- Dec: $m = k \oplus c$

Correctness: For all $k \in \mathcal{K}$ and all $m \in \mathcal{M}$,

$$\text{Dec}_k(\text{Enc}_k(m)) =$$

The One-Time Pad

XOR		
x	y	$x \oplus y$
0	0	0
0	1	1
1	0	1
1	1	0

One-Time Pad Encryption Scheme

- Let $\mathcal{M} = \mathcal{K} = \mathcal{C} = \{0, 1\}^\ell$
- Gen: $k \leftarrow \mathcal{K}$
- Enc: $c = k \oplus m$ ($\oplus$ denotes bitwise XOR)
- Dec: $m = k \oplus c$

Correctness: For all $k \in \mathcal{K}$ and all $m \in \mathcal{M}$,

$$\text{Dec}_k(\text{Enc}_k(m)) = k \oplus (k \oplus m) = (k \oplus k) \oplus m = 0^\ell \oplus m = m$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c]$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

$$\Pr[C = c \mid M = m]$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

$$\Pr[C = c \mid M = m] = \Pr[\text{Enc}_K(m) = c]$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

$$\Pr[C = c \mid M = m] = \Pr[\text{Enc}_K(m) = c] = \Pr[m \oplus K = c]$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

$$\begin{aligned}\Pr[C = c \mid M = m] &= \Pr[\text{Enc}_K(m) = c] = \Pr[m \oplus K = c] \\ &= \Pr[K = m \oplus c] = 2^{-\ell}\end{aligned}$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

$$\begin{aligned}\Pr[C = c \mid M = m] &= \Pr[\text{Enc}_K(m) = c] = \Pr[m \oplus K = c] \\ &= \Pr[K = m \oplus c] = 2^{-\ell}\end{aligned}$$

$$\Pr[C = c]$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

$$\begin{aligned}\Pr[C = c \mid M = m] &= \Pr[\text{Enc}_K(m) = c] = \Pr[m \oplus K = c] \\ &= \Pr[K = m \oplus c] = 2^{-\ell} \\ \Pr[C = c] &= \sum_{m' \in \mathcal{M}} \Pr[C = c \mid M = m'] \cdot \Pr[M = m']\end{aligned}$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

$$\begin{aligned}\Pr[C = c \mid M = m] &= \Pr[\text{Enc}_K(m) = c] = \Pr[m \oplus K = c] \\ &= \Pr[K = m \oplus c] = 2^{-\ell} \\ \Pr[C = c] &= \sum_{m' \in \mathcal{M}} \Pr[C = c \mid M = m'] \cdot \Pr[M = m'] \\ &= 2^{-\ell} \cdot \sum_{m' \in \mathcal{M}} \Pr[M = m'] =\end{aligned}$$

The One-Time Pad

One-Time Pad Encryption Scheme

Gen: $k \leftarrow \mathcal{K}$

Enc: $c = k \oplus m$

Theorem: The OTP is perfectly secret ($\Pr[M = m \mid C = c] = \Pr[M = m]$)

$$\Pr[M = m \mid C = c] = \frac{\Pr[C = c \mid M = m] \cdot \Pr[M = m]}{\Pr[C = c]}$$

$$= \frac{2^{-\ell} \cdot \Pr[M = m]}{2^{-\ell}} = \Pr[M = m]$$

$$\Pr[C = c \mid M = m] = \Pr[\text{Enc}_K(m) = c] = \Pr[m \oplus K = c]$$

$$= \Pr[K = m \oplus c] = 2^{-\ell}$$

$$\Pr[C = c] = \sum_{m' \in \mathcal{M}} \Pr[C = c \mid M = m'] \cdot \Pr[M = m']$$

$$= 2^{-\ell} \cdot \sum_{m' \in \mathcal{M}} \Pr[M = m'] = 2^{-\ell}$$

Limitations of the One-Time Pad

The one-time pad has some critical limitations that make it not ideal for real-world use.

- Can only use a key k to encrypt at most one message

Limitations of the One-Time Pad

The one-time pad has some critical limitations that make it not ideal for real-world use.

- Can only use a key k to encrypt at most one message
- Need the length of the key to be as long as the message (i.e., $|k| \geq |m|$)

Limitations of the One-Time Pad

The one-time pad has some critical limitations that make it not ideal for real-world use.

- Can only use a key k to encrypt at most one message
- Need the length of the key to be as long as the message (i.e., $|k| \geq |m|$)

Why?