


PANDA: Pose-Aware NPU Digital Audio Interface for Contactless Musical Performance



PANDA project icon.

Acronym expansion: Pose-Aware NPU Digital Audio Interface

Final Report

Authors: FILLME

Affiliation: FILLME

Date: 2026-05-27

Code availability: Not publicly released.

Abstract

This report presents **PANDA**, short for Pose-Aware NPU Digital Audio Interface, a real-time camera-based musical interface that converts hand and finger motions into playable drum and piano events. The system tracks hand landmarks from a USB camera, estimates downward fingertip velocity and finger-joint angular velocity, and triggers audio only when both motion cues indicate an intentional strike. Two musical modes are implemented on the same perception-and-strike-detection core: (1) a **drum pad mode**, where any fingertip may strike an on-screen rectangular pad, and (2) a **piano mode**, where notes are mapped to hand and finger identity. The final piano default layout maps the left hand from thumb to pinky as G4, F4, E4, D4, C4 and the right hand as C5, D5, E5, F5, G5. The implementation supports CPU MediaPipe, CPU TFLite baseline, hybrid CPU+NPU hand-landmark inference, and a low-latency NPU dual-halves mode. Evaluation utilities and unit tests validate strike detection, pad-zone parsing, piano-note mapping, ROI transforms, and benchmark helpers. Prototype measurements show that the low-latency NPU dual-halves backend can approach the 60 FPS frame budget, while the more accurate palm-detection pipeline is limited by CPU palm detection. The project demonstrates a practical path toward low-cost, contactless musical instruments on edge AI hardware, with clear remaining work in end-to-end audio-latency measurement, robust hit-accuracy evaluation, and user studies.

Keywords: PANDA, contactless musical interface, hand tracking, gesture recognition, air drums, virtual piano, edge AI, NPU, real-time interaction

1. Introduction

Musical performance interfaces traditionally rely on physical contact: a drumstick contacts a drumhead, or a finger depresses a piano key. Contact provides both tactile feedback and a clear sensing event. However, camera-based hand tracking makes it possible to build **contactless musical instruments** that require no specialized controller beyond a camera and display. Such systems are attractive for prototyping, education, accessibility, public installations, and embedded AI demonstrations.

The main challenge is that visually recognizing a musical strike is harder than recognizing a static hand pose. A simple fingertip-position trigger produces false positives when the whole hand moves, while a simple velocity trigger may fire during non-musical gestures. PANDA addresses this by combining two motion cues:

1. **Fingertip downward velocity**: the fingertip moves rapidly in the image direction associated with a striking motion.
2. **Finger-joint angular velocity**: the finger itself articulates, distinguishing a deliberate finger strike from arm-only translation.

This report summarizes the final implemented system, its two musical modes, generated visual assets, software architecture, testing strategy, and prototype performance measurements.

1.1 Contributions


The implemented project contributes:

- A real-time hand-landmark musical interface supporting both **drum pad** and **piano** modes.
- A common strike detector using fingertip velocity plus joint angular velocity.
- A pad-zone drum interface with configurable rectangular hit regions and visual flash feedback.
- A piano interface with a corrected default mapping: left thumb G4, left pinky C4, right hand C5–G5.
- A mirrored selfie-view display, enabled by default, so the performer's left/right hand motion matches the visible camera feed and on-screen targets.
- Generated interface diagrams for both modes.
- Report figures generated programmatically for system architecture, strike logic, and backend latency.
- A repeatable validation pipeline covering mapping, detector behavior, pad validation, ROI helpers, and benchmark helpers.

2. System Overview

Figure 1 summarizes the runtime pipeline. Frames are captured from a USB camera using an OpenCV-based capture layer [3], processed by one of several hand-tracking backends, converted into per-hand landmark coordinates, passed to the strike detector, mapped to either piano notes or drum pad sounds, and finally played through pre-rendered PCM audio buffers.

AI Air-Drum Pad Runtime Pipeline



The same vision and strike detector support both musical interfaces; only mapping changes.

Figure 1. Runtime pipeline diagram generated programmatically for this report.

The same vision pipeline and strike detector support both musical modes. The mapping layer changes according to mode:

- **Piano mode:** $\text{hand_id} \times \text{fingertip_id} \rightarrow \text{note name}$.
- **Drum mode:** fingertip position inside pad rectangle $\rightarrow$ drum sound.

2.1 Implemented Modes

Drum Pad Mode

Drum mode no longer uses a fixed per-finger drum mapping. Instead, it uses normalized on-screen rectangles. Any tracked fingertip can play a pad if the strike detector fires while the fingertip is inside that pad. The default layout has eight pads: kick, snare, hat, ride, tom_l, tom_m, crash, and clap.

Drum Pads — Default Layout

8 on-screen rectangles: move any fingertip into a pad and strike downward

```
$ python3 main.py --camera 0
```



Any tracked fingertip can hit any rectangle; drum mode is no longer a fixed per-finger map.

Figure 2. Default drum pad layout generated programmatically for this report.

A larger diagram lists all built-in drum sound keys available for custom pad layouts.

All Available Drum Sounds

16 built-in percussion samples usable as pad sound keys

```
$ python3 main.py --drum-pads pads.example.json --camera 0
```



Use these sound keys in pads.example.json or another --drum-pads layout.

Figure 3. Built-in drum sound-key catalog generated programmatically for this report.

Piano Mode

Piano mode maps fingers to notes. The final default layout is:

Hand	Thumb	Index	Middle	Ring	Pinky
Left / Hand 0	G4	F4	E4	D4	C4
Right / Hand 1	C5	D5	E5	F5	G5

This preserves the user's intended left-hand orientation: the **left thumb is G4** and the **left pinky is C4**, while the right hand remains ascending from C5 to G5.

Piano — Default C Major

10-slot piano: left thumb G4 → pinky C4, right hand C5–G5

```
$ python3 main.py --piano --camera 0
```




Figure 4. Default piano layout generated programmatically for this report.

A custom JSON piano layout example is also generated using the same default slot order.

Piano — Custom JSON Example

Fixed 10-note layout from instruments.piano.example.json

```
$ python3 main.py --piano --instruments instruments.piano.example.json --camera 0
```




Figure 5. Piano custom-layout example generated programmatically for this report.

2.2 Manual Screenshots Still Required

Some figures require live hardware capture rather than offline generation. They are left as FILLME placeholders:

[FILLME image placeholder: FILLME: final live full-screen drum mode with camera feed, pad overlay, sidebar, and strike list.]

[FILLME image placeholder: FILLME: final live full-screen piano mode with camera feed, finger trails, sidebar, and strike list.]

3. Background and Related Work

PANDA sits at the intersection of gesture-based musical interfaces, real-time hand tracking, and embedded edge AI. Prior gesture instruments often use depth cameras, wearable sensors, inertial measurement units, or vision-based pose estimation. Compared with wearable sensors, camera-only systems reduce setup cost and improve accessibility, but they must infer intent from noisy visual motion alone.

This project uses a hand-landmark approach similar to modern single-camera hand-pose systems such as MediaPipe Hands [1] and the MediaPipe Hand Landmarker task [2]: a palm or hand detector localizes the hand, a landmark network estimates keypoints, and application logic derives gestures from keypoint dynamics. The project also investigates CPU/NPU deployment trade-offs, because low-latency musical interaction requires both accurate perception and rapid audio response.

The implementation is intentionally modular: hand tracking can be swapped across backends, while strike detection and sound mapping remain independent of the model runtime.

4. Methods

4.1 Hand-Landmark Representation


Each detected hand is represented by 21 normalized landmarks. The application uses five fingertip indices:

Finger	Landmark index
Thumb	4
Index	8
Middle	12
Ring	16
Pinky	20

For each fingertip, a three-point chain is selected for angular motion. For example, the index finger uses MCP-PIP-TIP landmarks. The thumb uses a thumb-specific chain involving the IP joint.

4.2 Strike Detection

A strike is emitted only when two independent conditions hold at the same time. Figure 6 shows the decision logic.



A hit is emitted only when downward motion and finger articulation occur together, reducing false positives from arm-only motion.

Figure 6. Strike-decision logic diagram generated programmatically for this report.

Let (y_t) be the fingertip's normalized vertical image coordinate at time (t) . The downward fingertip velocity is approximated by

$$v_y = \frac{y_t - y_{t-1}}{t - t_{t-1}}.$$

Because image coordinates increase downward, positive (v_y) indicates downward motion. Let (θ_t) be the angle at the selected finger joint. Joint angular speed is approximated by

$$\omega = \left| \frac{\theta_t - \theta_{t-1}}{t - t_{t-1}} \right|.$$

A strike candidate satisfies

$$\lVert \mathbf{v}_y \rVert \geq \tau_v \quad \text{and} \quad \omega \geq \tau_\omega.$$

The detector then applies confidence filtering, minimum displacement filtering, and cooldown logic. The middle finger has a lower internal threshold scale because its visual angular change is often smaller than the other fingers in camera coordinates.

4.3 Drum Pad Mapping

Each drum pad is a normalized rectangle

$$\lVert (x_1, y_1, x_2, y_2), \quad 0 \leq x_1 < x_2 \leq 1, \quad 0 \leq y_1 < y_2 \leq 1. \rVert$$

If a fingertip strike occurs and the fingertip coordinate lies inside a pad, the detector returns that pad's sound key. Cooldown is tracked by pad label, allowing different pads to be played in rapid sequence.

Custom drum layouts are loaded from JSON:

```
{
  "pads": [
    {"label": "kick", "sound": "kick", "x1": 0.05, "y1": 0.35, "x2": 0.29, "y2": 0.59, "color": [80, 80, 180]}
  ]
}
```

4.4 Piano Mapping

Piano mapping uses a 10-slot tuple ordered as:

```
[Hand 0 thumb, index, middle, ring, pinky,
 Hand 1 thumb, index, middle, ring, pinky]
```

The final default tuple is:

```
("G4", "F4", "E4", "D4", "C4", "C5", "D5", "E5", "F5", "G5")
```

This mapping is implemented as the default runtime note configuration and is mirrored in the custom piano-layout configuration used to generate the example figure.

4.5 Audio Generation

The system pre-renders synthetic drum and piano sounds into `pygame.mixer.Sound` objects [4] to avoid synthesizing audio on every strike. Piano tones are approximately 0.5 seconds long. Short drum samples were lengthened so triggered sounds remain audible despite perception and output latency.

5. Implementation

5.1 Runtime Backends

The application supports four major backend configurations, including MediaPipe-based CPU inference [1], [2] and DEEPX .dxnn NPU execution through the DXNN toolchain [5].

Backend	Palm detection	Hand landmarks	Intended use
cpu	MediaPipe internal [1], [2]	MediaPipe internal [1], [2]	Simple CPU-only baseline
cpu-baseline	CPU TFLite	CPU TFLite	Comparable pipeline without NPU
npu-full	CPU TFLite	NPU .dxnn	Accurate palm pipeline with NPU hand inference

Backend	Palm detection	Hand landmarks	Intended use
npu	none / dual-halves approximation	NPU . dxnn	Fastest low-latency approximation

The NPU-full path is architecturally preferred for accurate hand localization, but CPU palm detection dominates latency. The dual-halves NPU mode is faster because it removes palm detection, but it is a geometric approximation and should be evaluated under the target camera setup.

5.2 User Interface

The runtime display contains the camera feed, hand/finger landmark trails, mode-specific overlays, and a sidebar. The camera feed is mirrored by default, producing a selfie-style interface in which moving a hand leftward in physical space also moves it leftward on the screen. This small interface detail is important for playability: without the mirror flip, the performer must mentally invert left/right motion while aiming at drum pads or piano cues. A `--no-mirror` option remains available for camera setups that already provide mirrored input.

In drum mode, rectangles are drawn directly on the mirrored camera feed and flash briefly when hit. In piano mode, the sidebar shows the hand-to-note mapping and recent note events.

The generated diagrams are used both as report figures and as sidebar assets, keeping the report and runtime UI consistent.

6. Experimental Methodology

6.1 Software Validation

The validation suite performs Python syntax checks, unit tests, and palm decode tests. Hardware-dependent benchmark smoke tests are separated from the default quality gate so that the report can distinguish portable software validation from board-specific performance evaluation.

6.2 Backend Latency Measurement

The backend evaluation was designed to separate three questions that are often conflated in a real-time vision instrument:

1. How fast is a simple CPU-only hand-tracking baseline?
2. How much of the latency comes from palm detection versus hand landmark inference?
3. Does the NPU accelerate the part of the pipeline that is actually deployed on the NPU, and what accuracy risks are introduced by faster approximations?

For that reason, four runtime configurations were evaluated rather than a single prototype.

Configuration	What it evaluates	Why this baseline is required
cpu / MediaPipe	End-to-end CPU reference using MediaPipe's built-in palm and hand stack	Establishes the simplest robust baseline and verifies that the musical logic works without model-conversion dependencies
cpu-baseline	Palm TFLite + hand landmark TFLite, both on CPU	Uses the same two-stage palm→ROI→hand structure as npu-full, so it isolates whether replacing only hand inference with NPU is beneficial
npu-full	Palm TFLite on CPU + hand landmark . dxnn on NPU	Tests the intended accurate hybrid edge-AI pipeline while preserving reliable float32 palm detection
npu dual-halves	No palm detector; screen split into two approximate hand regions; hand landmark . dxnn on NPU	Estimates the low-latency lower bound when palm detection is removed, useful for live demos but less robust to hand placement


The main evaluation metric in this report is **vision-loop latency**: time spent in camera-frame processing, palm/hand inference, ROI handling, and landmark production before the audio trigger logic. This is not a full acoustic end-to-end latency

measurement. The target interactive frame budget is 16.7 ms for 60 FPS, while the final acoustic measurement should separately report motion-to-sound latency.

The hardware/software environment for the recorded prototype measurements was:

Item	Value
Board	Orange Pi 5 Plus (RK3588, aarch64)
OS / Python	Linux, Python 3.10.12
DX-RT / dx_engine [5]	1.1.4
DX-COM [5]	v2.1.0-rc.4 on external compile server
Camera	USB camera, 640×480
Offline dataset	90 captured frames in dataset/frame_*.png

The palm detector was also tested as an NPU .dxnn candidate. Although the NPU palm model was fast at roughly 12 ms, INT8 quantization damaged the score head: ONNX-to-NPU score correlation was approximately -0.11, making real hand detection unreliable. Therefore, all accurate palm-based configurations use CPU TFLite palm detection, and palm detection remains the main latency bottleneck.



Four runtime configurations are compared to isolate palm detection, hand-landmark inference, and NPU dispatch effects; final audio latency still requires manual high-speed-camera capture.

Figure 7. Backend latency comparison generated programmatically for this report.

6.3 Required Manual Measurements

A complete academic evaluation still requires manual measurements of the physical interaction loop. The protocols are defined here so that the missing data can be inserted directly into this report rather than stored only in auxiliary notes.

- 1. End-to-end audio latency:** record the performer's hand and the speaker output simultaneously using a high-speed camera or synchronized audio/video setup. For each strike, identify the video frame where the downward hit begins and the first audio waveform onset at the speaker. Compute $\Delta t = t_{\text{audio}} - t_{\text{video}}$. Use at least 30 strikes per mode and report mean, standard deviation, and P95 latency.
- 2. Hit accuracy:** run guided trials in both drum and piano modes using the built-in visual/audio cue evaluator. The evaluator displays a predefined beat sequence, records detected strike events, matches events to scheduled cues, and exports `cues.csv`, `events.csv`, `matches.csv`, `summary.json`, `summary.md`, and an optional review video. A true positive is an intended strike detected within the allowed time window. A false negative is an intended strike with no valid

event. A false positive is an unintended or duplicate event outside the allowed window. Report TP, FP, FN, precision, recall, and qualitative failure cases.

3. **Per-run logging:** retain the internal build identifier, backend, camera resolution, model checksums, `vy_trigger`, `joint_dps`, `cooldown`, lighting conditions, and raw event log fields such as `t`, `frame_id`, `infer_ms`, `hand_id`, `finger_id`, `pad/note`, and `trigger`.

The following figures are still placeholders because they require live hardware capture.

[FILLME image placeholder: FILLME: high-speed-camera setup showing hand motion and speaker/audio waveform for E2E latency measurement.]

[FILLME image placeholder: FILLME: plot or table image from manual hit-accuracy experiment across piano and drum modes.]

7. Results

7.1 Functional Results

The implementation satisfies the main functional goals:

- Detects hand landmarks from live camera input.
- Detects intentional strikes using fingertip and joint dynamics.
- Plays piano notes from hand/finger identity.
- Plays drum sounds from on-screen rectangular pad hits.
- Supports custom piano-note JSON and drum-pad JSON layouts.
- Shows generated mapping diagrams in documentation and runtime sidebar.

7.2 Current Test Results

The latest validation run produced:

Test group	Result
Python syntax check	Passed
Unit tests	34/34 passed
Palm decode tests	15/15 passed
Dataset benchmark smoke	Skipped intentionally in the portable validation run

The unit tests cover default piano mapping, synthetic audio duration, pad-zone generation, pad JSON validation, instrument slot validation, strike detector thresholds, middle-finger sensitivity, cooldown behavior, ROI helpers, benchmark helper functions, dataset capture indexing, and the guided evaluation cue/matching/output helpers.

7.3 Backend Performance Summary

The table below reports the high-level latency comparison for the four evaluated runtime configurations. The `cpu` row is a practical reference path. The `cpu - base line` and `npu - full` rows form the controlled CPU-vs-NPU comparison because they share the same `palm→ROI→hand` pipeline and differ only in hand landmark inference. The `npu dual-halves` row is not an accuracy-equivalent baseline; it is a low-latency approximation that removes palm detection to estimate the best-case live-demo path.

Backend	Palm stage	Hand stage	Approx. total for 2 hands	Interpretation
cpu (MediaPipe)	~15 ms	~10 ms	~35 ms	Simple CPU-only functional baseline; no extra model files required
cpu-base-line (TFLite)	~95 ms	~5 ms	~105 ms	Same two-stage structure as npu-full; isolates the hand-landmark accelerator comparison
npu-full (TFLite + NPU)	~95 ms	~8 ms	~111 ms	Accurate hybrid path, but CPU palm detection dominates total time
npu dual-halves	0 ms	~8 ms × 2	~16 ms	Fastest path and close to 60 FPS budget, but it approximates hand location without palm detection

The result has two important implications. First, moving only the hand landmark model to NPU is insufficient when CPU palm detection still dominates the accurate pipeline. Second, the low-latency dual-halves path is valuable for demonstrations, but it should not be treated as accuracy-equivalent to the palm-based configurations because it assumes stable hand placement.

7.4 Offline Dataset Benchmark Summary

A 90-frame offline benchmark was run to compare the two structurally matched pipelines, `cpu-base-line` and `npu-full`, using the same captured input frames. This benchmark removes live camera variability and focuses on per-frame processing latency and landmark agreement.

Configuration	Mean latency	P95 latency	Component profile	Interpretation
cpu-base-line, palm every frame	84.40 ms	86.78 ms	palm 39.26 ms + hand 44.80 ms	CPU TFLite reference for the two-stage pipeline
npu-full, palm every frame	50.32 ms	54.52 ms	palm 40.93 ms + hand 9.13 ms	Same palm/ROI path, but hand inference is moved to NPU
npu-full, --palm-redetect-every 5 (20-frame smoke)	15.29 ms	50.96 ms	palm frames 3/20, tracking frames 17/20	Shows latency potential of palm skipping, but drift and hit accuracy must be verified
npu-full, --async-palm smoke	10–20 ms range	input-pacing dependent	tracking with asynchronous palm refresh	Experimental path; live stability still needs validation

The matched `cpu-base-line` vs. `npu-full` comparison shows that the NPU substantially reduces hand-landmark time in the TFLite-style pipeline (44.80 ms to 9.13 ms in the recorded 90-frame run). However, palm detection remains about 40 ms, so the accurate pipeline still exceeds the 60 FPS target unless palm frequency is reduced or palm detection is accelerated.

Landmark accuracy was estimated by comparing `npu-full` landmarks against the CPU-baseline reference in normalized image coordinates.

Hand	Matched frames	Mean error over 21 points	Mean fingertip error	Mean max error	Worst max error
Right	90	0.0270	0.0336	0.0532	0.1593
Left	83	0.0256	0.0353	0.0457	0.0734

An affine correction model was then fit to reduce systematic NPU landmark bias. On the same 90-frame training set, the corrected errors were:

Hand	Matched frames	Mean error over 21 points	Mean fingertip error	Mean max error	Worst max error
Right	90	0.0102	0.0112	0.0223	0.1701
Left	83	0.0092	0.0090	0.0193	0.0437

The correction reduces average and fingertip error on the training capture, but it should not be reported as a generalized accuracy improvement until it is evaluated on a separate hold-out capture with different lighting, hand size, hand pose, and camera distance.

8. Discussion

8.1 Why Two Motion Cues Matter

A virtual instrument should not trigger whenever a hand moves. The combined velocity-and-angle criterion improves musical intent detection because it requires the fingertip to move downward and the finger to articulate. This is especially important in piano mode, where individual finger identity matters, and in drum mode, where the same fingertip can cross pad boundaries during normal movement.

8.2 Drum Pad Mode vs. Per-Finger Drum Mapping

The project originally used per-finger drum mapping. The final drum interface uses rectangular pads instead, which is more intuitive because it resembles a physical drum pad controller. It also lets the performer use any finger for any drum sound. The trade-off is that pad layout now depends on camera framing and screen coordinates, so calibration and visual feedback become more important.

8.3 Piano Mapping Convention

The final piano mapping follows the user-specified convention: left-hand thumb is highest among left-hand notes (G4) and left-hand pinky is lowest (C4), while the right hand ascends from C5 to G5. This mapping matches common left-hand physical intuition when the left hand is viewed in a camera-facing diagram.

8.4 Edge AI Trade-Offs

The NPU accelerates hand landmark inference, but a full robust pipeline also needs palm detection. In the experiments reported above, the NPU palm candidate was fast but unusable because INT8 quantization damaged detection scores, leaving CPU TFLite palm detection in the accurate pipeline. Consequently, the most accurate NPU-full backend can be slower than expected because palm detection dominates. This suggests that future work should focus on either improving palm model quantization, replacing the detector, or reducing palm frequency while controlling drift.

9. Limitations

The current prototype has several limitations:

- **No complete final E2E audio-latency measurement** is included; a manual high-speed-camera or synchronized audio/video experiment is required.
- **No formal user study** has been conducted.
- **No final hit-accuracy table** is available for tempo-controlled trials.
- **Depth ambiguity** remains because the system uses a single RGB camera.
- **Lighting and background sensitivity** may affect landmark stability.
- **NPU-full accuracy and latency** remain limited by CPU palm detection.
- **Tactile feedback is absent**, so timing may feel different from physical instruments.

10. Future Work

Recommended next steps are:

1. Capture final live screenshots for the FILLME figures.
2. Measure E2E audio latency using a high-speed camera and synchronized audio waveform.
3. Run hit-accuracy trials for both modes at multiple tempos.
4. Add per-user calibration for pad positions, handedness, and strike thresholds.
5. Investigate palm detector alternatives suitable for NPU deployment.
6. Add optional MIDI output so the system can drive external instruments.
7. Run the guided visual/audio cue evaluator to collect final hit-accuracy results for both modes.
8. Conduct a small user study comparing playability of drum and piano modes.

11. Conclusion

PANDA demonstrates a complete camera-based musical interface that converts hand motion into playable drum and piano events. The final implementation includes a pad-based drum interface, a corrected piano note mapping, low-latency audio playback, generated documentation diagrams, and a repeatable validation suite. The project shows that edge AI hand tracking can support expressive contactless musical interaction, but also highlights the importance of robust strike detection, accurate hand localization, and careful latency measurement. With further evaluation and NPU optimization, the system can serve as a strong foundation for embedded AI musical interfaces and real-time gesture-control demonstrations.

Acknowledgments

FILLME: course, advisor, lab, hardware provider, or collaborator acknowledgments.

References

- [1] F. Zhang, V. Bazarevsky, A. Vakunov, A. Tkachenka, G. Sung, C.-L. Chang, and M. Grundmann, “MediaPipe Hands: On-device real-time hand tracking,” arXiv preprint arXiv:2006.10214, 2020. [Online]. Available: <https://arxiv.org/abs/2006.10214>. Accessed: May 27, 2026.
- [2] Google AI Edge, “Hand landmarks detection guide,” Google AI for Developers. [Online]. Available: https://ai.google.dev/edge/mediapipe/solutions/vision/hand_landmarker. Accessed: May 27, 2026.
- [3] OpenCV Team, “OpenCV modules,” OpenCV Documentation. [Online]. Available: <https://docs.opencv.org/4.x/>. Accessed: May 27, 2026.
- [4] pygame developers, “Pygame front page—pygame v2.6.0 documentation,” pygame. [Online]. Available: <https://www.pygame.org/docs/>. Accessed: May 27, 2026.
- [5] DEEPX, “Get Started,” DEEPX Developer. [Online]. Available: <https://developer.deepx.ai/article/get-started/>. Accessed: May 27, 2026.