CA HW5

b09902004 資工二 郭懷元

5.10

5.10.1

P1:

$$\text{clock rate} = \frac{1}{\text{cycle time}} = \frac{1}{0.66 \times 10^{-9}} \approx 1.52 \times 10^{9} = 1.52 \text{ GHz}$$

P2:

$$\text{clock rate} = \frac{1}{\text{cycle time}} = \frac{1}{0.90 \times 10^{-9}} \approx 1.11 \times 10^{9} = 1.11 \text{ GHz}$$

5.10.2

P1:

$$\begin{aligned}\text{AMAT} &= \text{hit time} + \text{miss rate} \times \text{miss penalty} \\ &= 0.66 + 0.08 \times 70 \text{ ns} \\ &= 6.26 \text{ ns} \\ &= \frac{6.26}{0.66} = 9.49 \text{ cycles}\end{aligned}$$

P2:

$$\begin{aligned}\text{AMAT} &= \text{hit time} + \text{miss rate} \times \text{miss penalty} \\ &= 0.90 + 0.06 \times 70 \text{ ns} \\ &= 5.10 \text{ ns} \\ &= \frac{5.10}{0.90} = 5.67 \text{ cycles}\end{aligned}$$

5.10.3

P1's CPI:

$$\begin{aligned}\text{CPI} &= \text{base CPI} + \text{data mem ins ratio} \times \text{AMAT} \\ &= 1.0 + 0.36 \times 9.49 = 4.42\end{aligned}$$

P2's CPI:

$$\begin{aligned}\text{CPI} &= \text{base CPI} + \text{data mem ins ratio} \times \text{AMAT} \\ &= 1.0 + 0.36 \times 5.67 = 3.04\end{aligned}$$

P1's latency:

$$\text{latency} = \text{cycle time} \times \text{CPI} = 0.66 \times 4.42 = 2.92 \text{ ns}$$

P2's latency:

$$\text{latency} = \text{cycle time} \times \text{CPI} = 0.90 \times 3.04 = 2.74 \text{ ns}$$

P2 is faster because it has lower latency.

5.10.4

AMAT without L2 cache: 9.49 cycles

AMAT with L2 cache:

$$\begin{aligned}\text{L2 global miss rate} &= \text{L1 miss rate} \times \text{L2 local miss rate} \\ &= 0.08 \times 0.95 \\ &= 0.076\end{aligned}$$

$$\begin{aligned}\text{AMAT} &= \text{L1 hit time} \\ &\quad + \text{L1 miss rate} \times \text{L2 hit time} \\ &\quad + \text{L2 global miss rate} \times \text{miss penalty} \\ &= 0.66 + 0.08 \times 5.62 + 0.076 \times 70 \text{ ns} \\ &= 6.43 \text{ ns} \\ &= \frac{6.43}{0.66} = 9.74 \text{ cycles}\end{aligned}$$

AMAT is worse with L2 cache.

5.10.5

$$\begin{aligned}\text{CPI} &= \text{base CPI} + \text{data mem ins ratio} \times \text{AMAT} \\ &= 1.0 + 0.36 \times 9.74 = 4.51\end{aligned}$$

5.10.6

Because base CPI and cycle time is the same, we can compare only AMAT.

Let the needed L2 miss rate be r.

$$\begin{aligned}(0.66 + 0.08 \times 5.62 + 0.08 \times r \times 70)\ \text{ns} &< 6.26\ \text{ns} \\ r &< \frac{6.26 - 0.66 - 0.08 \times 5.62}{0.08 \times 70} \\ r &< 0.92\end{aligned}$$

L2 miss rate needs to be less than 0.92.

5.10.7

P2's latency without L2 cache: 2.74 ns

Let the needed L2 miss rate be r, needed CPI be c.

$$\begin{aligned}0.66 \times c &< 2.74 \\ c &< 4.15\end{aligned}$$

$$\begin{aligned}c &= 1.0 + 0.36 \times \frac{0.66 + 0.08 \times 5.62 + 0.08 \times r \times 70}{0.66} \\ &= 1.0 + \frac{0.36}{0.66} \times (1.11 + 5.6r) \\ &< 4.15\end{aligned}$$

$$\begin{aligned}r &< \frac{(4.15 - 1.0) \times \frac{0.66}{0.36} - 1.11}{5.6} \\ r &< 0.83\end{aligned}$$

L2 miss rate needs to be less than 0.83.

5.16

5.16.1

1. Access `0x123d`
Tag	TLB	Page table	Physical Page Number	Page fault
`0x1`	Miss	Hit	In disk	True
Valid	Tag	Physical Page Number	Time Since Last Access
1	`0xb`	`12`	`5`
1	`0x7`	`4`	`2`
1	`0x3`	`6`	`4`
1	`0x1`	`13`	`1`
2. Access `0x08b3`
Tag	TLB	Page table	Physical Page Number	Page fault
`0x0`	Miss	Hit	`5`	False
Valid	Tag	Physical Page Number	Time Since Last Access
1	`0x0`	`5`	`1`
1	`0x7`	`4`	`3`
1	`0x3`	`6`	`5`
1	`0x1`	`13`	`2`
3. Access `0x365c`
Tag	TLB	Page table	Physical Page Number	Page fault
`0x3`	Hit	-	`6`	False

Valid	Tag	Physical Page Number	Time Since Last Access
1	`0x0`	`5`	`2`
1	`0x7`	`4`	`4`
1	`0x3`	`6`	`1`
1	`0x1`	`13`	`3`

4. Access `0x871b`

Tag	TLB	Page table	Physical Page Number	Page fault
`0x8`	Miss	Hit	In disk	True

Valid	Tag	Physical Page Number	Time Since Last Access
1	`0x0`	`5`	`3`
1	`0x8`	`14`	`1`
1	`0x3`	`6`	`2`
1	`0x1`	`13`	`4`

5. Access `0xbee6`

Tag	TLB	Page table	Physical Page Number	Page fault
`0xb`	Miss	Hit	`12`	False

Valid	Tag	Physical Page Number	Time Since Last Access
1	`0x0`	`5`	`4`
1	`0x8`	`14`	`2`
1	`0x3`	`6`	`3`
1	`0xb`	`12`	`1`

6. Access `0x3140`

Tag	TLB	Page table	Physical Page Number	Page fault
`0x3`	Hit	-	`6`	False

Valid	Tag	Physical Page Number	Time Since Last Access
1	`0x0`	`5`	`5`
1	`0x8`	`14`	`3`
1	`0x3`	`6`	`1`
1	`0xb`	`12`	`2`

7. Access `0xc049`

Tag	TLB	Page table	Physical Page Number	Page fault
`0xc`	Miss	Miss	In disk	True

Valid	Tag	Physical Page Number	Time Since Last Access
1	`0xc`	`15`	`1`
1	`0x8`	`14`	`4`
1	`0x3`	`6`	`2`
1	`0xb`	`12`	`3`

5.16.2