



Fundamentos do Processamento de Dados

Introdução a Programação com Python [26E1_2]

Formatting

Style: %

- %s string
- %d decimal integer
- %f decimal float
- %% literal %

```
print('%s' % 42)
print('%f' % 7.03)
print('%d' % 42)
print('%d%%' % 100)
```

```
42
7.030000
42
100%
```

```
cat = 'Chester'
weight = 28

print("Our cat %s weighs %s pounds" % (cat, weight))
print("Our cat %s weighs %s pounds" % (weight, cat))
```

```
Our cat Chester weighs 28 pounds
Our cat 28 weighs Chester pounds
```

```
value = 63.15983493

print('%f' % value)
print('%.5f' % value)
print('%.2f' % value)
```

```
63.159835
63.15983
63.16
```

Style: {} e format()



```
dir('str')
```

```
[ '__add__',  
  '__class__',  
  '__contains__',  
  '__delattr__',  
  '__dir__',  
  '__doc__',  
  '__eq__',  
  '__format__',  
  '__ge__',  
  '__getattr__',  
  '__getitem__',  
  '__getnewargs__',  
  '__getstate__',  
  '__gt__',  
  '__hash__',  
  '__init__',  
  '__init_subclass__',  
  '__iter__',  
  '__le__',  
  '__len__',  
  '__lt__',  
  '__mod__',  
  '__mul__',  
  '__ne__',  
  '__new__',  
  '__reduce__',  
  '__reduce_ex__',  
  '__repr__',  
  '__rmod__',  
  '__rmul__',  
  '__setattr__',  
  '__sizeof__',
```

```
thing = 'woodchuck'  
  
print('{}'.format(thing))
```

woodchuck

```
thing = 'woodchuck'  
place = 'lake'  
  
print('The {} is in the {}'.format(thing, place))
```

The woodchuck is in the lake.

```
print('The {1} is in the {0}'.format(place, thing))
```

The woodchuck is in the lake.

```
print('The {thing} is in the {place}'.format(thing='duck', place='bathtub'))
```

The duck is in the bathtub

```
print('The test with format string: {thing + place} '.format(thing='duck', place='bathtub'))
```

 Execution error
KeyError: 'thing + place'

Show error details

Style: f-strings

```
thing = 'wereduck'
place = 'werepond'

print(f'The {thing} is in the {place}')
```

The wereduck is in the werepond

```
print(f'The test with format string (concat): {thing + place}')
```

The test with format string (concat): wereduckwerepond

```
print(f'The {thing.capitalize()} is in the {place.rjust(20)}')
```

The Wereduck is in the werepond

Documentação oficial sobre strings: <https://docs.python.org/3/library/stdtypes.html#text-sequence-type-str>

INPUT

```
input()
```

'123'

```
name = input()
print(f'Hello World {name}, python is fatastic!')
```

Hello World Gesiel Lopes, python is fatastic!

```
name = input('Qual o seu nome: ')
print(f'Hello World {name}, python is fatastic!')
```

Hello World Gesiel Lopes, python is fatastic!

```
## conversao de G para F
# formula: (°F - 32) x 5/9 = °C

graus_f = input('Digite o valor em Graus Fahrenheit: ')
graus_c = (graus_f - 32) * 5/9
print(f'Graus Fahrenheit: {graus_f} em Graus Celsius: {graus_c}')
```

 Execution error
TypeError: unsupported operand type(s) for -: 'str' and 'int'

Show error details

```
graus_f = input('Digite o valor em Graus Fahrenheit: ')
graus_f = int(graus_f)
graus_c = (graus_f - 32) * 5/9
print(f'Graus Fahrenheit: {graus_f} em Graus Celsius: {graus_c}')
```

Graus Fahrenheit: 236 em Graus Celsius: 113.33333333333333

como considerar apenas três casa decimais no resultado da célula anterior?