

Viewing TTY Logs with Lighttpd

This section provides the steps to convert the ttylogs captured by the DShield sensor into an HTML formatted document that can be accessed from Kibana interface.

Enable tty logging in each DShield sensors:

```
guy@picollector: sudo vi /srv/cowrie/cowrie.cfg
```

Search for `ttylog = false` change to: `ttylog = true`

Default ttylog → `/srv/cowrie/var/lib/cowrie/tty`

```
$ sudo systemctl restart isc-agent
```

```
$ sudo /srv/dshield/status.sh
```

Install txt2html to convert the ttylogs to an html format to have to ability to access them from ELK

```
$ sudo apt-get install txt2html
```

Install lighttpd in the ELK server

```
$ sudo apt-get install lighttpd
```

```
$ sudo systemctl enable lighttpd
```

```
$ sudo systemctl start lighttpd
```

Log location: `/var/www/html`

```
$ ls -la /var/www/html
```

Confirm the webserver is accessible and running then move the default index out of the default directory

Using browser access: `http://elk`

```
$ sudo mv /var/www/html/index.lighttpd.html .
```

Configure TTYLog in Kibana

Management -> Kibana -> Data Views -> cowrie*

Edit TTYLog and change the IP 192.168.25.231 to your ELK server IP or Name

URL template

```
http://192.168.25.231/{{rawValue}}.html
```

In ELK server, create SSH Shared Keys and don't put a password:

```
$ ssh-keygen
```

Copy id_rsa.pub over to each sensor(s). Likely the easiest way to copy the public key over might be to scp from DShield sensor

```
$ scp guy@192.168.25.231:/home/guy/.ssh/id_rsa.pub .
```

```
$ cat id_rsa.pub >> .ssh/authorized_keys
```

```
$ rm id_rsa.pub
```

Test SSH between the ELK server to DShield sensor

```
$ ssh -l guy 192.168.25.165 -p 12222
```

Setup DShield Sensor for TTYLogs to HTML Format

There are 2 scripts provided for the sensor

- replayttylog.sh → Used when setting up TTYLogs parsing for the first time
- ttylog.sh → Runs on a hourly cronjob

If the sensor has been running for a while, un `replayttylog.sh` until it is completed. This could take a while depending on the number of logs is currently stored. The converted hashes will be stored in the home directory in `~/ttylog`.

```
$ mkdir scripts
```

```
$ cd scripts
```

```
$ curl https://raw.githubusercontent.com/bruneaug/DShield-SIEM/main/sensor_scripts/replayttylog.sh -o replayttylog.sh
```

```
$ curl https://raw.githubusercontent.com/bruneaug/DShield-SIEM/main/sensor_scripts/ttylog.sh -o ttylog.sh
```

```
$ chmod 755 *.sh
```

```
$ ~/scripts/replayttylog.sh
```

When the script finish to run, it is time to manually transfer the logs to the Elastic server.



