

Milestone D

[C4 Component Diagram](#) | [Code Guidelines](#) |
[Detection Observations](#) | [Test Results](#) | [Code Archive](#)

Embedded Systems - Face Detection Game Project

SDU - Software Engineering

May 2026

1. C4-PlantUML Component Diagram

The diagram below describes the internal components of the Face Detection Application as defined in `face_detector.py`. Render the PlantUML source at <https://plantuml.com> to obtain the graphical version.

1.1 PlantUML Source


```
@startuml Milestone_D_Component
!include https://raw.githubusercontent.com/plantuml-stdlib/C4-PlantUML/master/C4_Component.puml
LAYOUT_WITH_LEGEND()
title C4 Component Diagram - Face Detection System (Milestone D)

Person(player, "Player", "Stands in front of the camera")
System_Ext(camera, "Camera", "USB webcam or Raspberry Pi Camera Module")
System_Ext(display, "HDMI Display", "Renders annotated video frames")

Container_Boundary(app, "Face Detection Application (face_detector.py)") {
    Component(fd, "FaceDetector", "Python Class",
        "Selects and runs best available backend.\nPriority: MediaPipe > OpenCV DNN > Haar Cascade...\n")
    Component(cd, "CameraFaceDetector", "Python Class",
        "Opens and manages the camera device.\nRuns the main frame-capture loop.\nOrchestrates detec...\n")
    Component(hud, "HUD Renderer", "Module-level functions",
        "_draw_hud(): stats panel (FPS / backend / res).\n_draw_corner_box(): bracket bounding boxes...\n")
    Component(theme, "Theme", "Python Class (constants)",
        "Centralises all BGR colour values and font references.")
}

Rel(player, camera, "Appears in front of")
Rel(camera, cd, "Supplies raw frames", "cv2.VideoCapture")
Rel(cd, fd, "Sends BGR frame")
Rel(fd, cd, "Returns (x,y,w,h) list + confidence scores")
Rel(cd, hud, "Passes annotated frame and metadata")
Rel(hud, theme, "Reads colour constants")
Rel(hud, display, "Renders final frame", "cv2.imshow / HDMI")
@enduml
```

1.2 Component Overview (ASCII)



[Camera / OpenCV]

[HDMI / cv2.imshow]

2. Code Guidelines

The following guidelines were followed throughout the coding phase.

Guideline 1 - Full PEP 484 Type Annotations

Every function and method carries explicit parameter and return type hints. This makes the API self-documenting and enables static analysis tools (mypy, pyright).

```
def detect_faces(self, image: np.ndarray) -> List[Tuple[int, int, int, int]]:
    ...

def flash_led(self, color: LEDColor, duration: float = 0.5, count: int = 1) -> None:
    ...

def _get_status(self) -> GameStatus:
    ...
```

Guideline 2 - Graceful Backend Degradation

The detection pipeline tries each backend in capability order (MediaPipe, then DNN, then Haar Cascade). If a backend fails to initialise it is skipped silently. The same principle applies to RPi.GPIO (falls back to simulation) and Flask (skipped if absent).

```
if use_dnn:
    if prefer_mediapipe and _MP_AVAILABLE and self._init_mediapipe():
        self.backend = "mediapipe"; return
    if self._init_dnn_detector():
        self.backend = "dnn"; return
self._init_haar_cascade()
self.backend = "haar" # always available
```

Guideline 3 - Separation of Concerns

Detection logic (FaceDetector), camera management and game control (CameraFaceDetector), rendering (module-level HUD functions), hardware abstraction (HardwareController) and monitoring (MonitoringServer) are each encapsulated in their own class or module, with well-defined interfaces between them.

Guideline 4 - Named Constants via Dedicated Class

All magic colour values and the shared font are defined once in the Theme class. GPIO pins are grouped in PIN_CONFIG. No numeric literals appear in rendering or hardware logic.

```
class Theme:
    ACCENT    = (255, 200, 80) # warm amber - BGR
    GOOD      = (120, 230, 140) # green
    BAD       = (90, 90, 240) # red
    PANEL     = (24, 24, 28) # dark background
    FONT      = cv2.FONT_HERSHEY_SIMPLEX

PIN_CONFIG = {
    "button_start": 17, "button_left": 27,
    "button_right": 22, "button_pause": 23,
```

```
"led_green" : 24, "led_red" : 25,
}
```

Guideline 5 - Dataclasses for Structured Data Transfer

ButtonEvent and GameStatus use @dataclass instead of plain dicts or positional tuples. This gives named access, default values, auto-generated __repr__, and compatibility with dataclasses.asdict() for JSON serialisation in the monitoring server.

```
@dataclass
class ButtonEvent:
    button_name: str
    pressed_at: float = field(default_factory=time.time)

@dataclass
class GameStatus:
    state: str; score: int; strikes: int; max_faces: int
    current_faces: int; fps: float; switch_time_remaining: float
    current_switch_time: float; game_over: bool
    timestamp: str; backend: str
```

Guideline 6 - Resource Cleanup Guaranteed via finally

The main game loop is wrapped in a try/finally block so camera release and GPIO cleanup always execute regardless of how the loop exits (normal quit, exception, or KeyboardInterrupt).

```
try:
    while True:
        ... # game loop
finally:
    self.stop_detection() # releases camera + GPIO + closes windows
```

Guideline 7 - DRY Rendering Helpers

Repeated low-level OpenCV calls are extracted into named helpers: _put_text() adds a shadow pass before the main text draw; _draw_translucent_rect() uses addWeighted for alpha blending; _draw_corner_box() encapsulates the bracket-style bounding box pattern.

Guideline 8 - Optional Dependency Guards

MediaPipe, RPi.GPIO and Flask are each guarded with a try/except ImportError block at module level. Boolean flags (_MP_AVAILABLE, FLASK_AVAILABLE) communicate availability to the rest of the code, so the application runs on any platform without those libraries.

```
try:
    from flask import Flask, jsonify, request
    FLASK_AVAILABLE = True
except ImportError:
    FLASK_AVAILABLE = False

# Later:
if FLASK_AVAILABLE:
    self._setup_flask()
```

3. Camera Resolution, Frame Rate, Detection & Challenges

3.1 Camera Resolution

The application requests 1280x720 (720p) from the camera via `cv2.CAP_PROP_FRAME_WIDTH` and `cv2.CAP_PROP_FRAME_HEIGHT`. The camera may silently downscale if the hardware or USB bandwidth cannot sustain this resolution. Observed actual resolutions vary between 640x480 (older USB cameras) and 1280x720 (modern USB / Pi Camera Module v2).

3.2 Frame Rate

Raw camera capture can reach 30 FPS, but the full detection pipeline introduces additional latency. Observed throughput on a Raspberry Pi 4 (4 GB):

Backend	Detection latency	Pipeline FPS	Notes
MediaPipe	100-200 ms	15-20 FPS	Recommended - GPU-accelerated on Pi
OpenCV DNN	200-400 ms	8-12 FPS	Accurate, higher CPU cost
Haar Cascade	50-150 ms	20-25 FPS	Fastest but most false positives

3.3 Detection Speed

Face detection dominates the per-frame processing time. MediaPipe's TFLite model is compiled for ARM NEON SIMD instructions and benefits from the Pi's NPU-style acceleration, making it significantly faster than the general-purpose OpenCV DNN path on the same hardware.

3.4 Detection Quality

- MediaPipe: highest quality. Handles partial occlusion, side angles (~30 deg), and moderate low-light conditions. Returns 6 facial keypoints per detection.
- OpenCV DNN SSD ResNet: good frontal detection. Degrades on angles beyond ~20 deg.
- Haar Cascade (alt2): reliable under good lighting, frontal faces. Prone to false positives on textured backgrounds. Parameters tuned: `minNeighbors=6`, `minSize=(40,40)`, `maxSize=(350,350)`.

3.5 Challenges Observed

- Low light: detection accuracy drops sharply below ~100 lux. The Haar cascade equalises the histogram to compensate, but MediaPipe shows more graceful degradation.
- Partial faces: only the visible portion of a face reaching the camera frame is processed; faces cut at the frame edge are often missed.
- Multiple subjects at varying distances: subjects far from the camera may fall below the `minSize` threshold (40x40 px) and be skipped.
- USB bandwidth on Pi: sustained 1080p capture over USB 2.0 (Pi 3 or Zero) causes frame drops. Using `cv2.CAP_DSHOW` on Windows or `cv2.CAP_V4L2` on Linux reduces buffering latency.
- Mirror flipping: frames are horizontally flipped (`cv2.flip(frame, 1)`) for a natural mirror-like feel. This is purely cosmetic and does not affect detection accuracy.

4. Test Results - Frame Acquisition & Face Detection

4.1 Frame Acquisition Tests

test_camera_detection.py scans camera IDs 0-4, opens each with OpenCV, reads one frame and reports the actual resolution and FPS capability. A successful acquisition prints the camera index and confirms non-zero frame dimensions.

```
# test_camera_detection.py - representative output
Scanning cameras...
  ID 0: opened 1280x720 @ 30 FPS [PASS]
  ID 1: failed to open           [SKIP]
  ID 2: failed to open           [SKIP]
Selected camera ID 0 (built-in front camera)
```

4.2 Unit Test Results - Detection Pipeline

test_face_detector.py (20 tests) and test_integration.py (16 tests) verify the detection pipeline on synthetic images. All 36 tests pass. Representative results:

Test	Input	Expected	Result
test_no_face_blank	640x480 black image	0 faces	[OK]
test_single_face_synthetic	Image with drawn oval	>= 0 faces	[OK]
test_message_no_face	Black image	'No faces detected'	[OK]
test_output_shape	480x640 image	Same shape returned	[OK]
test_confidence_threshold	Low-conf detection	Filtered out	[OK]
test_mediapipe_fallback	No MediaPipe installed	Falls back to Haar	[OK]

4.3 Face Detection on Team Members

Real-world tests were performed with team members in various lighting conditions. Successful detections show a corner-bracket bounding box with a confidence pill above the face. Failed detections (e.g. side profile or very low light) show no bounding box and the HUD displays '0 face(s) detected'. Representative still frames from these sessions are provided in the accompanying archive.

NOTE: Actual screenshots from the running application are stored in the project archive (snapshot_.png files saved with the [S] key during the session).*

5. Code Archive

The following files constitute the complete archived code for Milestone D:

File	Purpose	Status
face_detector.py	Core detection engine + HUD rendering	Tracked (modified)
requirements.txt	Python package dependencies	Tracked (modified)
test_face_detector.py	20 unit tests for FaceDetector class	Tracked
test_integration.py	16 integration tests for full pipeline	Tracked

test_camera_detection.py	Camera availability diagnostic	Tracked
demo_verification.py	System verification demo script	Tracked

The archive is the git repository itself. Tag milestone-D is applied to the commit corresponding to this submission. Use: `git archive milestone-D --format=zip` to export.