EXPLORER

build.gradle

- OPEN EDITORS
- WDI
  - ▸ __tests__
  - ▾ android
    - ▸ .gradle
    - ▸ .settings
    - ▾ app
   - ▸ .settings
      - ▸ build
      - ▸ src
      - .classpath
      - .project
      - BUCK
      - build.gradle
      - proguard-rules.pro
    - ▸ build
    - ▸ gradle
    - ▸ keystores
    - .project
    - build.gradle
- DOCKER
- CODE OUTLINE
- MAVEN PROJECTS

```
130        // For each separate APK per architecture, set a unique version code a
131        // http://tools.android.com/tech-docs/new-build-system/user-guide/apk-s
132        def versionCodes = ["armeabi-v7a":1, "x86":2]
133        def abi = output.getFilter(OutputFile.ABI)
134        if (abi != null) {  // null for the universal-debug, universal-release
135            output.versionCodeOverride =
136                versionCodes.get(abi) * 1048576 + defaultConfig.versionCode
137        }
138      }
139    }
140  }

142  dependencies {
143      compile fileTree(dir: "libs", include: ["*.jar"])
144
145      implementation "org.jetbrains.kotlin:kotlin-stdlib-jre7:$kotlin_version"
146
147      compile "com.android.support:appcompat-v7:23.0.1"
148      compile "com.facebook.react:react-native:+"  // From node_modules
149  }
150
151  // Run this once to be able to run the application with BUCK
152  // puts all compile dependencies into folder libs for BUCK to use
153  task copyDownloadableDepsToLibs(type: Copy) {
154      from configurations.compile
155      into 'libs'
156  }
157
```

Native Modules 101